International
IOR Rectifier

REPETITIVE AVALANCHE AND dv/dt RATED
HEXFET® TRANSISTORS
THRU-HOLE (TO-204AA/AE)

IRF150
JANTX2N6764
JANTXV2N6764
[REF:MIL-PRF-19500/543]
100V, N-CHANNEL

Product Summary

Part Number	BVDSS	RDS(on)	ID
IRF150	100V	0.055Ω	38A

TO-3

The HEXFET® technology is the key to International Rectifier's advanced line of power MOSFET transistors. The efficient geometry and unique processing of this latest "State of the Art" design achieves: very low on-state resistance combined with high transconductance; superior reverse energy and diode recovery dv/dt capability.

The HEXFET transistors also feature all of the well established advantages of MOSFETs such as voltage control, very fast switching, ease of paralleling and temperature stability of the electrical parameters.

They are well suited for applications such as switching power supplies, motor controls, inverters, choppers, audio amplifiers and high energy pulse circuits.

Features:

- Repetitive Avalanche Ratings
- Dynamic dv/dt Rating
- Hermetically Sealed
- Simple Drive Requirements
- Ease of Paralleling

Absolute Maximum Ratings

	Parameter		Units
I_D @ V_{GS} = 10V, T_C = 25°C	Continuous Drain Current	38	A
I_D @ V_{GS} = 10V, T_C = 100°C	Continuous Drain Current	24	
I_{DM}	Pulsed Drain Current ①	152	
P_D @ T_C = 25°C	Max. Power Dissipation	150	W
	Linear Derating Factor	1.2	W/°C
V_{GS}	Gate-to-Source Voltage	±20	V
E_{AS}	Single Pulse Avalanche Energy ②	150	mJ
I_{AR}	Avalanche Current ①	38	A
E_{AR}	Repetitive Avalanche Energy ①	15	mJ
dv/dt	Peak Diode Recovery dv/dt ③	5.5	V/ns
T_J	Operating Junction	-55 to 150	°C
T_{STG}	Storage Temperature Range		
	Lead Temperature	300 (0.063 in. (1.6mm) from case for 10s)	
	Weight	11.5 (typical)	g

For footnotes refer to the last page

Electrical Characteristics @ Tj = 25°C (Unless Otherwise Specified)

	Parameter	Min	Typ	Max	Units	Test Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	100	—	—	V	V_{GS} = 0V, I_D = 1.0mA
$\Delta BV_{DSS}/\Delta T_J$	Temperature Coefficient of Breakdown Voltage	—	0.13	—	V/°C	Reference to 25°C, I_D = 1.0mA
$R_{DS(on)}$	Static Drain-to-Source On-State Resistance	—	—	0.055	Ω	V_{GS} = 10V, I_D =24A④
		—	—	0.065		V_{GS} =10V, I_D =38A ④
$V_{GS(th)}$	Gate Threshold Voltage	2.0	—	4.0	V	V_{DS} = V_{GS}, I_D =250µA
g_{fs}	Forward Transconductance	9.0	—	—	S (℧)	V_{DS} > 15V, I_{DS} =24A④
I_{DSS}	Zero Gate Voltage Drain Current	—	—	25	µA	V_{DS}=80V, V_{GS}=0V
		—	—	250		V_{DS} =80V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Leakage Forward	—	—	100	nA	V_{GS} =20V
I_{GSS}	Gate-to-Source Leakage Reverse	—	—	-100		V_{GS} =-20V
Q_g	Total Gate Charge	50	—	125	nC	V_{GS} =10V, I_D= 38A, V_{DS} =50V
Q_{gs}	Gate-to-Source Charge	8.0	—	22		
Q_{gd}	Gate-to-Drain ('Miller') Charge	25	—	65		
$t_{d(on)}$	Turn-On Delay Time	—	—	35	ns	V_{DD} =50V, I_D =38A, V_{GS} =10V, R_G =2.35Ω
t_r	Rise Time	—	—	190		
$t_{d(off)}$	Turn-Off Delay Time	—	—	170		
t_f	Fall Time	—	—	130		
$L_S + L_D$	Total Inductance	—	6.1	—	nH	Measured from the center of drain pad to center of source pad
C_{iss}	Input Capacitance	—	3700		pF	V_{GS} = 0V, V_{DS} =25V, f = 1.0MHz
C_{oss}	Output Capacitance	—	1100	—		
C_{rss}	Reverse Transfer Capacitance	—	200	—		

Source-Drain Diode Ratings and Characteristics

	Parameter	Min	Typ	Max	Units	Test Conditions
I_S	Continuous Source Current (Body Diode)	—	—	38	A	
I_{SM}	Pulse Source Current (Body Diode) ①	—	—	152		
V_{SD}	Diode Forward Voltage	—	—	1.9	V	T_j = 25°C, I_S =38A, V_{GS} = 0V ④
t_{rr}	Reverse Recovery Time	—	—	500	nS	T_j = 25°C, I_F = 38A, di/dt ≤100A/µs
Q_{RR}	Reverse Recovery Charge	—	—	2.9	µc	V_{DD} ≤ 30V ④
t_{on}	Forward Turn-On Time	Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by L_S + L_D.				

Thermal Resistance

	Parameter	Min	Typ	Max	Units	Test Conditions
R_{thJC}	Junction to Case	—	—	0.83	°C/W	
R_{thJA}	Junction to Ambient	—	—	30		Typical socket mount

For footnotes refer to the last page



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. Typical Transfer Characteristics



Fig 4. Normalized On-Resistance Vs. Temperature



Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage



Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage



Fig 7. Typical Source-Drain Diode Forward Voltage



Fig 8. Maximum Safe Operating Area



Fig 9. Maximum Drain Current Vs. Case Temperature



Fig 10a. Switching Time Test Circuit



Fig 10b. Switching Time Waveforms



Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case



Fig 12a. Unclamped Inductive Test Circuit



Fig 12b. Unclamped Inductive Waveforms



Fig 12c. Maximum Avalanche Energy Vs. Drain Current



Fig 13a. Basic Gate Charge Waveform



Fig 13b. Gate Charge Test Circuit

Foot Notes:

① Repetitive Rating; Pulse width limited by maximum junction temperature.
② V_{DD} =50V, starting T_J = 25°C, Peak I_L = 38A, V_{GS} =10V
③ I_{SD} ≤ 38A, di/dt ≤300A/µs, V_{DD}≤ 100V, T_J ≤ 150°C Suggested RG =2.35 Ω
④ Pulse width ≤ 300 µs; Duty Cycle ≤ 2%

Case Outline and Dimensions —TO-204AE (Modified TO-3)



PIN ASSIGNMENTS

1 – SOURCE
2 – GATE
3 – DRAIN (CASE)

NOTES:

1. DIMENSIONING & TOLERANCING PER ANSI Y14.5M–1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
4. OUTLINE CONFORMS TO JEDEC OUTLINE TO-204AE.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.