

THE LINUX



COMMANDS HANDBOOK

Table of Contents

[Preface](#)

[Introduction to Linux and shells](#)

[man](#)

[ls](#)

[cd](#)

[pwd](#)

[mkdir](#)

[rmdir](#)

[mv](#)

[cp](#)

[open](#)

[touch](#)

[find](#)

[ln](#)

[gzip](#)

[gunzip](#)

[tar](#)

[alias](#)

[cat](#)

[less](#)

[tail](#)

[wc](#)

[grep](#)

[sort](#)

cd

Once you have a folder, you can move into it using the

`cd` command. `cd` means **change directory**. You invoke it specifying a folder to move into. You can specify a folder name, or an entire path.

Example:

```
mkdir fruits
cd fruits
```

Now you are into the `fruits` folder.

You can use the `..` special path to indicate the parent folder:

```
cd .. #back to the home folder
```

The `#` character indicates the start of the comment, which lasts for the entire line after it's found.

You can use it to form a path:

```
mkdir
fruits
mkdir cars
cd fruits
cd ../cars
```

There is another special path indicator which is `.`, and indicates the **current** folder.

You can also use absolute paths, which start from the root folder `/`:

```
cd /etc
```

This command works on Linux, macOS, WSL, and anywhere you have a UNIX environment