

```

#include<stdio.h>
#include<stdlib.h>
struct node
{
    int st;
    struct node *link;
};

void findclosure(int,int);
void insert_trantbl(int ,char, int);
int findalpha(char);
void findfinalstate(void);
void unionclosure(int);
void print_e_closure(int);
static int
set[20],nostate,noalpha,s,notransition,nofinal,start,finalstate[20],c,r,buffer[20];
char alphabet[20];
static int e_closure[20][20]={0};
struct node * transition[20][20]={NULL};
void main()
{
    int i,j,k,m,t,n;

    struct node *temp;
    printf("enter the number of alphabets?\n");
    scanf("%d",&noalpha);
    getchar();
    printf("NOTE:- [ use letter e as epsilon]\n");

    printf("NOTE:- [e must be last character ,if it is present]\n");

    printf("\nEnter alphabets?\n");
    for(i=0;i<noalpha;i++)
    {
        alphabet[i]=getchar();
        getchar();
    }
    printf("Enter the number of states?\n");
    scanf("%d",&nostate);
    printf("Enter the start state?\n");
    scanf("%d",&start);
    printf("Enter the number of final states?\n");
    scanf("%d",&nofinal);
    printf("Enter the final states?\n");
    for(i=0;i<nofinal;i++)
        scanf("%d",&finalstate[i]);
    printf("Enter no of transition?\n");
    scanf("%d",&notransition);
    printf("NOTE:- [Transition is in the form--> qno  alphabet  qno]
\n",notransition);
    printf("NOTE:- [States number must be greater than zero]\n");
    printf("\nEnter transition?\n");
    for(i=0;i<notransition;i++)
    {
        scanf("%d %c%d",&r,&c,&s);
        insert_trantbl(r,c,s);
    }

    printf("\n");

    for(i=1;i<=nostate;i++)
    {

```

```

        c=0;
        for(j=0;j<20;j++)
        {
            buffer[j]=0;
            e_closure[i][j]=0;
        }
        findclosure(i,i);
    }
    printf("Equivalent NFA without epsilon\n");
    printf("-----\n");
    printf("start state:");
    print_e_closure(start);
    printf("\nAlphabets:");
    for(i=0;i<noalpha;i++)
        printf("%c ",alphabet[i]);
    printf("\nStates :");
    for(i=1;i<=nostate;i++)
        print_e_closure(i);

    printf("\nTransitions are...\n");

    for(i=1;i<=nostate;i++)
    {
        for(j=0;j<noalpha-1;j++)
        {
            for(m=1;m<=nostate;m++)
                set[m]=0;
            for(k=0;e_closure[i][k]!=0;k++)
            {
                t=e_closure[i][k];
                temp=transition[t][j];
                while(temp!=NULL)
                {
                    unionclosure(temp->st);
                    temp=temp->link;
                }
            }
            printf("\n");
            print_e_closure(i);
            printf("%c\t",alphabet[j]);
            printf("{");
            for(n=1;n<=nostate;n++)
            {
                if(set[n]!=0)
                    printf("q%d,",n);
            }
            printf("}");
        }
    }
    printf("\nFinal states:");
    findfinalstate();

}

void findclosure(int x,int sta)
{
    struct node *temp;
    int i;
    if(buffer[x])

```

```

        return;
        e_closure[sta][c++]=x;
        buffer[x]=1;
        if(alphabet[noalpha-1]=='e' && transition[x][noalpha-1]!=NULL)
        {
            temp=transition[x][noalpha-1];
            while(temp!=NULL)
            {
                findclosure(temp->st,sta);
                temp=temp->link;
            }
        }
    }
}

void insert_trantbl(int r,char c,int s)
{
    int j;
    struct node *temp;
    j=findalpha(c);
    if(j==999)
    {
        printf("error\n");
        exit(0);
    }
    temp=(struct node *) malloc(sizeof(struct node));
    temp->st=s;
    temp->link=transition[r][j];
    transition[r][j]=temp;
}

int findalpha(char c)
{
    int i;
    for(i=0;i<noalpha;i++)
        if(alphabet[i]==c)
            return i;

    return(999);
}

void unionclosure(int i)
{
    int j=0,k;
    while(e_closure[i][j]!=0)
    {
        k=e_closure[i][j];
        set[k]=1;
        j++;
    }
}

void findfinalstate()
{
    int i,j,k,t;
    for(i=0;i<nofinal;i++)
    {
        for(j=1;j<=nostate;j++)
        {
            for(k=0;e_closure[j][k]!=0;k++)
            {
                if(e_closure[j][k]==finalstate[i])
                {
                    print_e_closure(j);
                }
            }
        }
    }
}

```

```
        }
    }

}

void print_e_closure(int i)
{
    int j=0;
    printf("{");
    if(e_closure[i][j]!=0)
        printf("q%d,",e_closure[i][0]);
    printf("}\t");
}
```

```

^Z
[1]+  Stopped                  ./a.out
akhil@Ubuntu:~/Compiler-Lab/5)nfa with e to nfa without e$ ./a.out
enter the number of alphabets?
3
NOTE:- [ use letter e as epsilon]
NOTE:- [e must be last character ,if it is present]

Enter alphabets?
a
b
e
Enter the number of states?
5
Enter the start state?
1
Enter the number of final states?
1
Enter the final states?
3
Enter no of transition?
7
NOTE:- [Transition is in the form--> qno   alphabet   qno]
NOTE:- [States number must be greater than zero]

Enter transition?
1a2
1e3
2a1
3b4
4b3
3a5
5b3

Equivalent NFA without epsilon
-----
start state:{q1,}
Alphabets:a b e
States :{q1,}   {q2,}   {q3,}   {q4,}   {q5,}
Transitions are...:

{q1,}   a       {q2,q5,}
{q1,}   b       {q4,}
{q2,}   a       {q1,q3,}
{q2,}   b       {}
{q3,}   a       {q5,}
{q3,}   b       {q4,}
{q4,}   a       {}
{q4,}   b       {q3,}
{q5,}   a       {}
{q5,}   b       {q3,}
akhil@Ubuntu:~/Compiler-Lab/5)nfa with e to nfa without e$ █

```