```
[abhay@localhost Desktop]$ nano add.c
[abhay@localhost Desktop]$ nano header.h
[abhay@localhost Desktop]$ nano Makefile
[abhay@localhost Desktop]$ make
make: 'final' is up to date.
[abhay@localhost Desktop]$ nano Makefile
[abhay@localhost Desktop]$ ./final
Main.c
 Calling Hello function
 I am in hello

 Calling add function

 The sum is 8
 Back in main.c
[abhay@localhost Desktop]$ make final
make: 'final' is up to date.
[abhay@localhost Desktop]$ ./final
Main.c
 Calling Hello function
 I am in hello

 Calling add function

 The sum is 8
 Back in main.c
[abhay@localhost Desktop]$
```

```
 The sum is 8
 Back in main.c
[abhay@localhost Desktop]$ touch main.c
[abhay@localhost Desktop]$ ls
add.c  demo  final  header.h  hello.c  main.c  Makefile
[abhay@localhost Desktop]$ touch main.c
[abhay@localhost Desktop]$ nano main.c
[abhay@localhost Desktop]$ nano main.c
[abhay@localhost Desktop]$ nano hello.c
[abhay@localhost Desktop]$ nano add.c
[abhay@localhost Desktop]$ nano header.h
[abhay@localhost Desktop]$ nano Makefile
[abhay@localhost Desktop]$ make
make: 'final' is up to date.
[abhay@localhost Desktop]$ nano Makefile
[abhay@localhost Desktop]$ ./final
Main.c
 Calling Hello function
 I am in hello

 Calling add function

 The sum is 8
 Back in main.c
[abhay@localhost Desktop]$ make final
make: 'final' is up to date.
[abhay@localhost Desktop]$ ./final
Main.c
```

```
[abhay@localhost ~]$ ls
backup     demo.txt  Documents  Makefile  Pictures  Templates      Videos
backup.sh  Desktop   Downloads  Music     Public    timestamp.log
[abhay@localhost ~]$ cd Deskto[
bash: cd: Deskto[: No such file or directory
[abhay@localhost ~]$ cd Desktop
[abhay@localhost Desktop]$ ls
add.c  demo  final  header.h  hello.c  main.c  Makefile
[abhay@localhost Desktop]$ gcc main.c hello.c add.c -o final
[abhay@localhost Desktop]$ ./final
Main.c
 Calling Hello function
 I am in hello

 Calling add function

 The sum is 8
 Back in main.c
[abhay@localhost Desktop]$ touch main.c
[abhay@localhost Desktop]$ ls
add.c  demo  final  header.h  hello.c  main.c  Makefile
[abhay@localhost Desktop]$ touch main.c
[abhay@localhost Desktop]$ nano main.c
[abhay@localhost Desktop]$ nano main.c
[abhay@localhost Desktop]$ nano hello.c
[abhay@localhost Desktop]$ nano add.c
[abhay@localhost Desktop]$ nano header.h
[abhay@localhost Desktop]$ nano Makefile
```

```
  GNU nano 5.6.1                    add.c
#include<stdio.h>
#include"header.h"
void add (int a ,int b){
        int c;
        c=a+b;
        printf("\n The sum is %d",c);
}

                          [ Read 7 lines ]
^G Help      ^O Write Out  ^W Where Is   ^K Cut       ^T Execute   ^C Location
^X Exit      ^R Read File  ^\ Replace    ^U Paste     ^J Justify   ^_ Go To Line
```

```
  GNU nano 5.6.1                    hello.c
#include<stdio.h>
#include"header.h"
#include<unistd.h>
void hello(){
        printf("\n I am in hello\n");
}

                          [ Read 6 lines ]
^G Help      ^O Write Out   ^W Where Is    ^K Cut       ^T Execute   ^C Location
^X Exit      ^R Read File   ^\ Replace     ^U Paste     ^J Justify   ^_ Go To Line
```

```
  GNU nano 5.6.1                    main.c
#include<stdio.h>
#include"header.h"
void main(){
        printf("Main.c");
        printf("\n Calling Hello function");
        hello();
        printf("\n Calling add function\n");
        add(3,5);
        printf("\n Back in main.c\n");
}

                          [ Read 10 lines ]
^G Help      ^O Write Out  ^W Where Is   ^K Cut       ^T Execute    ^C Location
^X Exit      ^R Read File  ^\ Replace    ^U Paste     ^J Justify    ^_ Go To Line
```