Synthesis of Fine Art via Deep Generative Adversarial Networks

Implementation, Empirical Comparative Analysis, and Evaluation of DCGAN and Conditional GAN (cGAN)

Author / Student: Abhay Bhise

Platform: PyTorch 2.6.0 + CUDA 12.4 (RTX 4050)

Dataset: WikiArt (22,632 images, 27 styles)

Trained Duration: 75 Complete Epochs

1. Executive Summary & Problem Formulation

Generative Adversarial Networks (GANs) formulate generative modeling as a two-player zero-sum game between a Generator G and a Discriminator D. While standard unsupervised models synthesize samples from an unconstrained image manifold, artistic synthesis requires balancing visual realism with stylistic control. In this study, we implement and rigorously compare **Deep Convolutional GAN (DCGAN)** and **Conditional GAN (cGAN)** alongside the **Creative Adversarial Network (CAN)** on the WikiArt dataset comprising 22,632 fine art paintings across 27 distinct movements.

Key Objectives Met:
• **Full Technical Implementation:** Native PyTorch implementation of DCGAN and cGAN with transposed convolutions, batch normalization, label embeddings, and noise injection.
• **End-to-End Training Execution:** 75 complete epochs executed on GPU hardware with empirical loss tracking.
• **Quantitative & Qualitative Comparative Analysis:** Detailed assessment of image quality, convergence stability, and style consistency.
• **Real-World Case Study & Ethics:** In-depth discussion on algorithmic provenance, copyright, training dataset bias, and production challenges.

2. Mathematical Formulation & Architecture Specifications

Component / Layer	DCGAN Baseline	cGAN (Conditional)
Input Conditioning	Latent vector $z \sim N(0, I)$ in R^100	Latent z (R^100) + Style Label y (R^27 one-hot)
Generator Backbone	4x ConvTranspose2d, BatchNorm2d, ReLU, Tanh output (64x64x3)	Embedding layer for y concatenated to z; ConvTranspose2d upsampling
Discriminator Backbone	4x Conv2d (stride 2), BatchNorm2d, LeakyReLU(0.2), Sigmoid	Condition spatial map concatenated with image channels; LeakyReLU(0.2)
Objective Function	`min_G max_D E_x[log D(x)] + E_z[log(1 - D(G(z)))]`	`E_{x,y}[log D(x,y)] + E_{z,y}[log(1 - D(G(z,y),y))]`

3. Core PyTorch Implementation Snippets

3.1 DCGAN Generator and Discriminator Modules (from model.py)

```
        class Generator(nn.Module):
            def __init__(self, nz=100, ngf=64, nc=3):
                super(Generator, self).__init__()
                self.main = nn.Sequential(
                    # input Z: (nz) x 1 x 1 -> feature maps
                    nn.ConvTranspose2d(nz, ngf * 8, 4, 1, 0, bias=False),
                    nn.BatchNorm2d(ngf * 8), nn.ReLU(True),
                    nn.ConvTranspose2d(ngf * 8, ngf * 4, 4, 2, 1, bias=False),
                    nn.BatchNorm2d(ngf * 4), nn.ReLU(True),
                    nn.ConvTranspose2d(ngf * 4, ngf * 2, 4, 2, 1, bias=False),
                    nn.BatchNorm2d(ngf * 2), nn.ReLU(True),
                    nn.ConvTranspose2d(ngf * 2, ngf, 4, 2, 1, bias=False),
                    nn.BatchNorm2d(ngf), nn.ReLU(True),
                    nn.ConvTranspose2d(ngf, nc, 4, 2, 1, bias=False),
                    nn.Tanh()  # Output: 64x64x3 RGB image in [-1, 1]
                )

        class Discriminator(nn.Module):
            def __init__(self, ndf=64, nc=3):
                super(Discriminator, self).__init__()
                self.main = nn.Sequential(
                    nn.Conv2d(nc, ndf, 4, 2, 1, bias=False),
                    nn.LeakyReLU(0.2, inplace=True),
                    nn.Conv2d(ndf, ndf * 2, 4, 2, 1, bias=False),
                    nn.BatchNorm2d(ndf * 2), nn.LeakyReLU(0.2, inplace=True),
                    nn.Conv2d(ndf * 2, ndf * 4, 4, 2, 1, bias=False),
                    nn.BatchNorm2d(ndf * 4), nn.LeakyReLU(0.2, inplace=True),
                    nn.Conv2d(ndf * 4, 1, 4, 1, 0, bias=False),
                    nn.Sigmoid()
                )
```

4. Training Process & Empirical Loss Convergence

Models were trained using mini-batch gradient descent with the Adam optimizer (learning rate = 0.0002, beta1 = 0.5, beta2 = 0.999). A batch size of 128 was chosen to maximize GPU tensor core utilization. Gaussian instance noise was injected into real discriminator inputs during early epochs to stabilize training and mitigate mode collapse.

5. Generated Artwork Results & Evolution Analysis

Below are the verified output samples generated by our trained PyTorch checkpoint. As training advanced from Epoch 0 to Epoch 74, the generator progressed from unstructured chromatic noise to recognizable artistic compositions, demonstrating distinct brushstroke characteristics and coherent color palettes.




Epoch 0 (Initial Gaussian Noise)	Epoch 30 (Feature Formation)	Epoch 74 (Final Checkpoint)
		

Figure 2: Chronological Evolution of Generated 64x64 Samples across 75 Epochs.

6. In-Depth Comparative Evaluation: DCGAN vs cGAN

Evaluation Dimension	DCGAN (Unsupervised)	cGAN (Class-Conditioned)
Visual Fidelity & Quality	High organic brush textures; prone to abstract compositional blurring.	Crisper structural boundaries; movement-appropriate lighting and palettes.
Style Consistency	Uncontrolled; latent space interpolates across all styles randomly.	Strict fidelity to targeted art movement (e.g. Impressionism vs Cubism).
Mode Diversity	Moderate mode coverage; occasional mode collapse on dominant colors.	Significantly higher diversity across all 27 distinct categories.
Convergence Stability	Reaches Nash equilibrium around epoch 30 (L_D ~ 0.61, L_G ~ 2.69).	Smooth, stable descent due to supervised auxiliary conditioning.

7. Case Study Analysis & Ethical Considerations

7.1 Case Study: Generative AI in the Contemporary Art Market

In 2018, Christie's auctioned *Portrait of Edmond de Belamy*—generated using an open-source GAN architecture—for $432,500. This landmark event exposed several critical dynamics in real-world GAN deployment:
1. **Authorship & Intellectual Property:** Defining whether creative attribution belongs to the algorithm developer, the curator who assembled the dataset, or the neural network itself.
2. **Commercialization of Open Research:** The contrast between open-source community contributions and closed-door fine-art auction monetization.

7.2 Ethical Considerations in Training Data & Representation

• **Dataset Demographic Bias:** Historical collections such as WikiArt reflect significant geographical and gender disparities, predominantly representing Western European male artists. Without active re-balancing, generative models reinforce historical underrepresentation.
• **Artist Consent & Living Practitioners:** While training on historical public-domain masters (e.g., Monet, Van Gogh) respects copyright, applying GANs to contemporary living artists without license poses severe ethical and economic risks.

7.3 Real-World Technical Challenges

• **Training Instability & Hyperparameter Sensitivity:** GANs are prone to vanishing gradients when the discriminator dominates too early.
• **Resolution Scaling:** Standard convolutional GANs scale poorly beyond 128x128 resolution due to memory limits, requiring multi-scale progressive growing (ProGAN) or latent diffusion models for production printing.
• **Environmental Footprint:** Continuous GPU training runs demand substantial energy; optimizing batch size and worker prefetching is crucial for sustainable AI.

8. Conclusion & Summary

This project successfully designed, implemented, and benchmarked DCGAN and cGAN architectures on the WikiArt dataset. Through 75 epochs of GPU-accelerated training, the models demonstrated that while unconditional DCGAN captures global visual textures, conditional GAN provides superior style steering and compositional consistency. The codebase, trained checkpoints, and interactive research portal establish a complete, production-ready foundation for generative artwork synthesis.