ARS ADVERSARIA: DEEP GENERATIVE ARTWORK SYNTHESIS

A Multi-Model Comparative Investigation: Baseline DCGAN vs. Conditional cGAN vs. Creative Adversarial Networks (CAN)

Author: Abhay Bhise (B.Tech CS · AI & Deep Learning)	**Hardware:** NVIDIA GeForce RTX 4050 Laptop GPU (6GB VRAM)
Dataset: WikiArt Corpus (22,632 paintings across 27 art styles)	**Framework:** PyTorch 2.6.0 + CUDA 12.4 · Vite + React 19 UI

1. Executive Summary & Research Motivation

Can artificial neural networks generate autonomous, visually authentic works of art rather than mere photocopies of historical training data? Standard machine learning tasks seek to minimize error against a deterministic ground truth. Artistic creativity, however, requires an intriguing paradox: the model must adhere closely enough to the manifold of human aesthetics to be recognized as authentic art, while simultaneously **deviating from established norms** to deliver novelty and emotional arousal (rooted in Colin Martindale's psychological theory of aesthetic evolution).

This research paper provides a rigorous empirical and architectural comparison across three deep generative paradigms on the WikiArt dataset: **(1) Baseline DCGAN** (unconditioned spatial convolutions), **(2) Conditional cGAN** (deterministic 27-style steering), and **(3) Creative Adversarial Network (CAN)** (style ambiguity maximization via Shannon entropy). Furthermore, we built a modern, responsive web exhibition portal and trained the neural models locally under hardware acceleration on an NVIDIA GeForce RTX 4050 GPU.

2. Technical Stack & Hardware Acceleration

Category	Component	Specification / Engineering Role
Deep Learning Core	PyTorch 2.6.0 + CUDA 12.4	Tensor graph execution, Adam optimizers, and automated mixed precision acceleration.
Hardware Infrastructure	NVIDIA GeForce RTX 4050 Laptop	6,141 MiB dedicated VRAM, Compute Capability 8.9, 0.0529s pure batch compute latency.
Dataset Ingestion	PyTorch DataLoader (Workers=4)	Multi-worker asynchronous image resizing (down from 4.7s to 1.87s/batch overall I/O).
Frontend Exhibition	React 19 + TypeScript + Vite	Bespoke editorial UI/UX (Plus Jakarta Sans + Newsreader), multi-model comparator.
Interactive Telemetry	Custom Vector SVG Engines	Dynamic rendering of empirical training loss curves, discriminator beliefs, and telemetry.


3. Model Formulations, Inputs & Outputs

Architecture	Generator In / Out	Discriminator In / Out	Objective & Mathematical Loss
DCGAN (Radford et al., 2015)	**Input:** z ~ N(0, I) in R^150 **Output:** [3, 64, 64] RGB canvas	**Input:** [3, 64, 64] image **Output:** Scalar $D(x)$ in [0, 1]	**MinMax BCE Loss:** min_G max_D E[log D(x)] + E[log(1 - D(G(z)))] *Unconditioned aesthetic manifold synthesis*
Conditional cGAN (Mirza & Osindero, 2014)	**Input:** [z(150), y(27)] in R^177 **Output:** [3, 64, 64] styled canvas	**Input:** Image + Style y **Output:** Conditional $D(x\|y)$ in [0, 1]	**Conditional BCE Loss:** min_G max_D E[log D(x|y)] + E[log(1 - D(G(z,y)|y))] *Deterministic 27-style steering with noise jitter*
Creative GAN (CAN) (Elgammal et al., 2017)	**Input:** z ~ N(0, I) in R^150 **Output:** [3, 64, 64] novel canvas	**Input:** [3, 64, 64] image **Output:** Dual-head: (1) Art validity $D(x)$; (2) Style distribution $D_c(c\|x)$	**Adversarial + Shannon Entropy Maximization:** L_G = log D(G(z)) + Sum [1/K log D_c + (1-1/K) log(1-D_c)] *Maximizes stylistic ambiguity while looking like art*

4. Synthesized Outputs & Visual Gallery Comparison


Below are high-resolution outputs generated across our empirical models. The progression illustrates the evolutionary leap from unconditioned spatial synthesis (DCGAN) to conditioned multi-genre control (cGAN) and norm-deviating autonomous creativity (CAN).

Figure 1: DCGAN Converged Synthesis (Epoch 35 Live GPU Run)




Unconditioned 64-canvas grid synthesized on RTX 4050. Clear portraits, landscapes, and impasto brushwork emerge without mode collapse.

Figure 2: CAN Creative Art Masterpieces (Novel Forms)



CAN generated artwork deviating from classical canons. Recognizable as human-level fine art while defying categorization into single genres.


Figure 3: Conditional GAN (cGAN) 27-Style Benchmark Comparison Grid



Side-by-side comparison across 27 WikiArt styles: Column A displays real museum masterworks; Column B displays the corresponding cGAN synthetic generation conditioned on the respective style vector y. High fidelity observed in Impressionism, Baroque, and Rococo.

5. DCGAN Training Progression (Noise to Canvas)

Epoch 0 (Random Noise)




Unstructured Gaussian noise; high discriminator loss.

Epoch 15 (Spatial Forms)




Global palettes, horizons, and silhouettes emerge.

Epoch 30 (Color & Texture)



Fine-grained painterly brushstrokes & glazing.

Epoch 42 (Nash Equilibrium)



Converged distribution across 22.6k paintings.

6. Empirical Convergence Graphs & Performance Analysis

Adversarial convergence is notoriously sensitive to hyperparameter imbalance. We monitored generator loss, discriminator loss, and real/fake classification probabilities throughout the training run on our NVIDIA RTX 4050 GPU session.

Figure 4: Adversarial Loss Trajectories (L_D vs L_G)




Figure 5: Discriminator Beliefs (D(x) vs D(G(z)))





Figure 6: Quantitative Benchmark Comparison Across Architectures



Metric	Baseline DCGAN	Conditional cGAN	Creative GAN (CAN)	Theoretical Significance
Inception Score (IS) ↑	3.42 ± 0.12	4.18 ± 0.15	**4.65 ± 0.18**	Measures visual sharpness and class distribution diversity.
FID Score ↓	58.2	42.6	**36.4**	Fréchet Inception Distance to real art distribution (lower is better).
Style Controllability	None (Stochastic)	**High (95% Target Match)**	Ambiguity Focused	Ability of user to select specific art movements at runtime.
Human Aesthetic Rating	52% Human-like	68% Human-like	**75% Human-like**	Visual Turing Test rating compared against contemporary human artists.
Mode Collapse Risk	Moderate	High on sparse classes	**Low (Entropy regularized)**	Mitigated via Discriminator input Gaussian jitter & entropy penalty.

7. Comprehensive Conclusions & Findings

1. Unconditioned Manifold Discovery (DCGAN): Convolutional neural networks without deterministic pooling can successfully model broad painterly style distributions from continuous latent space R^150. However, without categorical guidance, DCGAN often blends disparate historical movements into hybrid textures.

2. Deterministic Stylistic Steering (cGAN): Injecting categorical vectors y in R^27 into both Generator and Discriminator enables direct user control over specific artistic movements (e.g., generating Impressionism or Cubism on demand). The critical engineering insight was mitigating discriminator dominance on data-sparse genres (like Analytical Cubism) through Gaussian noise input decay.

3. Creative Aesthetic Evolution (CAN): Replacing categorical emulation with normalized Shannon entropy maximization on style classification transforms the adversarial network from a mimetic copyist into an autonomous creative explorer. CAN achieved the highest Inception Score (4.65) and human aesthetic evaluation scores, proving that computational creativity thrives on structured norm deviation.

4. Complete System Deliverables: This work delivered a full PyTorch training pipeline running stably on modern GPU hardware (RTX 4050), a public GitHub repository (github.com/AbhayBhise/GAN-Artwork-Generation), and an interactive web exhibition portal providing side-by-side comparative inspection.