

DUL-99 — Sylhet Lost Circulation Historical Knowledge Pack

Synthetic historical offset-well record for RAG, similarity matching, and hazard explanation

WELL & EVENT SUMMARY

Field Metric	Value	Field Metric	Value
Well Name:	Duliajan-99 (DUL-99)	Field / Basin:	Duliajan Field, Upper Assam Shelf
Event Depth:	3,180 – 3,210 m MD	Formation Target:	Sylhet Karst Limestone
Primary Hazard:	Severe Mud Loss / Fractured Vugs	Rig Assigned:	OIL Rig 14 (2000 HP)
Doc Type:	REPORT 1: QUICK SPOT KNOWLEDGE PACK	Packet Depth:	3,550 m (MD)

INCIDENT NARRATIVE

Bit penetrated a natural vuggy fracture network in Sylhet Limestone at 3,210m. Returns dropped to zero (100% total mud loss). Annular fluid level dropped by 120m rapidly threatening hydrostatic head loss.

MITIGATION & RECOVERY EXECUTED

- Step 1: Annular top-up with fresh water to maintain hydrostatic column.
- Step 2: Pumped 60 bbl Coarse LCM pill (Nut Plug, Mica, Calcium Carbonate 25 lb/bbl).
- Step 3: Placed 35 bbl Class-G thixotropic cement plug across 3,200m–3,210m interval.
- Step 4: Drilled out cement plug after 12-hour set time with full returns restored at 1.22 g/cc mud weight.

TOTAL NPT ELAPSED: 44.0 Hours | LCM & CEMENT MATERIAL COST: ■18.5 Lakhs