

DUL-88 — Kopili Gas Kick Historical Knowledge Pack

Synthetic historical offset-well record for RAG, similarity matching, and hazard explanation

WELL & EVENT SUMMARY

Field Metric	Value	Field Metric	Value
Well Name:	Duliajan-88 (DUL-88)	Field / Basin:	Duliajan Field, Upper Assam Shelf
Event Depth:	2,842.00 m MD	Formation Target:	Kopili Overpressured Formation
Primary Hazard:	High Pressure Gas Influx / Kick	Rig Assigned:	OIL Rig 14 (2000 HP)
Spud Date:	15-Aug-2022	Target Depth:	3,400 m (MD)
Doc Type:	REPORT 1: QUICK SPOT KNOWLEDGE BASE	Status:	Controlled & Stabilized

INCIDENT NARRATIVE

While drilling 8.5-inch section at depth 2,842m in overpressured Kopili shale, active mud pit gain of 15.2 barrels was observed and total gas units spiked to 2,450 units. Driller shut in well on Annular BOP. SIDPP reached 240 psi and SICP reached 350 psi.

RECORDED PARAMETERS AT INCIDENT TIME

Pressure Metric	Value Recorded	Operational Context
Shut-In Casing Pressure (SICP)	350 psi	1.34 g/cc EMW gas accumulation
Shut-In Drill Pipe Pressure (SIDPP)	240 psi	1.32 g/cc EMW pore pressure measure
Original Mud Weight	1.24 g/cc	Underbalanced by 0.08 g/cc
Kill Mud Weight Required	1.36 g/cc	Includes 0.04 g/cc safety margin
Mud Pit Gain	15.2 bbl	Gas influx volume into wellbore
Peak Connection Gas	2,450 Units	Methane 82%, Ethane 11%, Propane 7%

MITIGATION & KILL PROCEDURE

- Step 1: Added API Barite to active tanks to raise mud weight to 1.36 g/cc.
- Step 2: Executed Wait & Weight method down drill string while maintaining constant drill pipe pressure.
- Step 3: Flared 45,000 cu ft gas safely at degasser outlet.
- Step 4: Zero SIDPP/SICP achieved after 1.5 circulation bottoms-up.

TOTAL NPT ELAPSED: 22.0 Hours | ZERO CASUALTIES / ZERO ENVIRONMENTAL RELEASE