

DUL-88 — Kopili Gas Kick Historical Knowledge Pack

Synthetic historical offset-well record for overpressure/influx retrieval and response context

IMPORTANT: This document is synthetic demonstration data prepared for the NWIS/SIH prototype. It must not be represented as an authentic confidential OIL record, real incident report, or verified SPE publication.

Well & Event Summary

Field	Value
Well	Duliajan-88 (DUL-88)
Field	Duliajan Field, Upper Assam Shelf
Coordinates	26.841°N, 95.324°E
Kick depth	2842 m
Formation	Kopili Shale/Sand Transition
Reservoir	Kopili Sandstone Gas Zone
Hole size	8.5 inch
BOP	10,000 psi

Incident Detection

While drilling at 2842 m in an overpressured Kopili interval, a synthetic mud-logging stream showed a pit gain and a sharp increase in gas units. The driller shut in using the annular preventer. This document is intended to teach the prototype how a gas-influx historical case can be retrieved.

Recorded Kick Indicators

Parameter	Value
Pit gain	15.2 bbl
Gas units	45 → >2200
Peak connection gas	2450 units
SICP	350 psi
SIDPP	240 psi
Original mud weight	1.24 g/cc
Kill mud weight	1.36 g/cc

Mitigation Sequence

Step	Action
1	Shut in well using annular preventer
2	Increase mud density using barite to 1.36 g/cc
3	Apply wait-and-weight style circulation
4	Circulate kill mud
5	Manage gas through controlled surface handling
6	Verify stabilization before resuming normal operations

NWIS Retrieval Metadata

Search terms: DUL-88, Kopili, gas kick, influx, pit gain, gas units, SICP, SIDPP, 1.36 g/cc. The AI should use this report as historical evidence and should not automatically prescribe a field action without engineering validation and operating procedures.

Synthetic Sensor Feature Example

timestamp	depth_m	pit_gain_bbl	gas_units	spp_psi	mud_weight_gcc	formation
14:00	2838	0.2	55	2900	1.24	Kopili
14:05	2839	0.8	110	2910	1.24	Kopili
14:10	2840	3.5	480	2920	1.24	Kopili
14:15	2841	8.0	1200	2940	1.24	Kopili
14:20	2842	15.2	2200	2960	1.24	Kopili