

WELL SUMMARY & OPERATIONAL SCOPE

Well Name:	Duliajan-88 (DUL-88)	Field / Basin:	Duliajan Field (Upper Assam Shelf)
Coordinates:	26.841° N, 95.324° E	Kick Depth:	2,842 m (MD)
Formation:	Kopili Shale / Sand Transition	Mud Type:	Polymer Water-Based Mud
Reservoir:	Kopili Sandstone Gas Zone	BOP Rating:	10,000 psi Annular & Ram

INCIDENT DESCRIPTION: HIGH PRESSURE GAS INFLUX

While drilling 8.5-inch section at depth 2,842m in the overpressured Kopili formation, the rig mud logger detected a sudden active pit gain of 15 barrels and total gas units spiked from 45 units to over 2,200 units (C1 to C4 hydrocarbons). Driller immediately shut in the well using the Annular Preventer as per OIL Standard Operating Procedure (SOP).

■ **HAZARD CLASSIFICATION:** High-Pressure Gas Influx / Kick in Overpressured Kopili Shale-Sand Interface.

WELL CONTROL & PRESSURE PARAMETERS RECORDED

Pressure Metric	Value Recorded	EMW Equivalent	Operational Context
Shut-In Casing Pressure (SICP)	350 psi	1.34 g/cc EMW	Annular gas column accumulation
Shut-In Drill Pipe Pressure (SIDPP)	240 psi	1.32 g/cc EMW	Formation pore pressure measure
Original Mud Weight	1.24 g/cc	1.24 g/cc	Underbalanced by 0.08 g/cc
Kill Mud Weight Required	1.36 g/cc	1.36 g/cc	Includes 0.04 g/cc safety margin
Mud Pit Gain	15.2 bbl	-	Gas influx volume into wellbore
Peak Connection Gas	2,450 Units	-	Methane 82%, Ethane 11%, Propane 7%

WELL CONTROL & KILL MITIGATION PROCEDURE

- Weighting Up Mud System:** Added API Barite to active tanks, raising mud weight from 1.24 g/cc to 1.36 g/cc kill mud.
- Engineer's Method (Wait & Weight):** Circulated kill mud down drill string while maintaining constant drill pipe pressure, venting gas influx safely through choke manifold and gas degasser.
- Gas Flare Igniter:** Flared off 45,000 cu ft of gas at poor-boy degasser outlet safely.
- Complete Well Stabilization:** Observed zero SIDPP/SICP after 1.5 circulation bottoms-up. Resumed normal drilling operations.

TOTAL NPT ELAPSED: 22.0 Hours | **ZERO CASUALTIES / ZERO ENVIRONMENTAL RELEASE**