

Assignment: 03 :- CURSOR

- 1] write a cursor to display empno, empname, salary, job and deptno of all the employees using % rowtype.

→

Set Serveroutput on

Declare

cursor E is select * from emp;

rec_emp emp%rowtype;

Begin

open emp E;

fetch E into rec_emp;

while E%found

Loop

fetch E into rec_emp;

Dbms_output.put_line(rec_emp.empno || ' ' ||

rec_emp.empname || ' ' || rec_emp.sal || ' ' ||

rec_emp.job || ' ' || rec_emp.deptno);

END Loop;

close E;

END;

/

2] write a cursor to input job from the user and display information for the inputted job.

Employee Information

Job : CLERK

Employee Number	Employee Name	Salary	Commission	Hiredate	Department Number
xx	xxxxx	xx	x	xx-xx-xx	xx
:	:	:	:	:	:

Total Salary : xxxx



set serveroutput on format wrapped
declare

vjob emp.job%type := '&vjob';

cursor E is select * from emp where job = vjob;
totalamt number;

begin

dbms_output.put_line('-----');

dbms_output.put_line('Employee Information');

dbms_output.put_line('-----');

dbms_output.put_line('Job : ' || vjob);

dbms_output.put_line(rpad('-', 71, '- '));

dbms_output.put_line(rpad('employee', 10) || rpad('employee', 10)
|| rpad('salary', 10) || rpad('commission', 5) ||
rpad('Hiredate', 15) || rpad('department', 10));

```
Dbms_output.put_line (rpad ('Number', 10) || rpad ('Name', 10) ||  
rpad ('', 40) || rpad ('Number', 10));
```

```
Dbms_output.put_line (rpad ('-', 71, '-'));
```

```
for rec_emp in E  
Loop
```

```
Dbms_output.put_line (rpad (rec_emp.empno, 10) ||  
rpad (rec_emp.ename, 10) || rpad (rec_emp.sal, 10)  
|| rpad (nvl (rec_emp.comm, 0), 15) ||  
rpad (rec_emp.hiredate, 15) || rpad (rec_emp.deptno, 10));
```

```
END Loop;
```

```
Dbms_output.put_line (rpad ('-', 71, '-'));
```

```
select sum(sal) into Tot_amt from Emp where  
Job = vjob;
```

```
Dbms_output.put_line (rpad ('Total Salary :', 24) ||  
Tot_amt);
```

```
END;
```

```
/
```


- 3] Write a cursor to display electricity bill report in the following format:

----- Electricity Bill Report -----

Customer Number	Customer Name	Previous Reading	Current Reading	Consumption	Unit Price	Total Bill
xx	xxxx	xx	xx	xx	xx	xxx
:	:	:	:	:	:	:

Set serveroutput on format wrapped

Declare

cursor EB is select cust-name, m.cust-no, prev-read,
curr-read, unit-price from customer_dtl d, customer_mst
m where d.cust-no = m.cust-no;

Consumption number;

Tot-bill Number;

Begin

Dbms_output.put_line('-----');

Dbms_output.put_line('Electricity Bill');

Dbms_output.put_line('-----');

Dbms_output.put_line(rpad('-', 93, '-'));

Dbms_output.put_line(rpad('cust-no', 10) || rpad('cust-name', 15)

|| rpad('prev-read', 15) || rpad('curr-read', 15)

|| rpad('consumption', 15) || rpad('unit-price', 15)

|| rpad('tot-bill', 10));

```
Dbms_output.put_line (rpad ('-', 93, '-'));
```

```
for xcust in REB
```

```
Loop
```

```
consumption := xcust.curr_read - xcust.prev_read;
```

```
Tot_bill := consumption * xcust.unit_price;
```

```
Dbms_output.put_line (rpad (xcust.cust_no, 10) ||
```

```
  rpad (xcust.cust_name, 15) || rpad (xcust.prevcurrread, 15)
```

```
  || rpad (xcust.curr_read, 15) || rpad (consumptioncurr_read, 15)
```

```
  || rpad (xcust.unit_price, 15) || rpad (Tot_bill, 10));
```

```
END Loop;
```

```
Dbms_output.put_line (rpad ('-', 93, '-'));
```

```
END;
```

```
/
```

4) write a cursor to display Department wise Employee Information in following format.

Department wise Employee Information

Department No: xx Department Name: xxxx

Employee Employee Job Salary Commission Hiredate
Number Name

xx xxxxx xx xx xx xx-xx-xx
: : : : : :



set serveroutput on format wrapped

Declare

cursor E is select * from emp;

cursor D is select * from dept;

Begin

Dbms_output.put_line('-----');

Dbms_output.put_line(' Department wise Employee information');

Dbms_output.put_line('-----');

for rec_d in D

Loop

Dbms_output.put_line(' Department no : ' || rec_d.deptno ||
' Department name: ' || rec_d.dname);

Dbms_output.put_line('-----');


```
Dbms_output.put_line (rpad ('Employee', 15) ||  
                        rpad ('Employee', 15) ||  
                        rpad ('Job', 15) ||  
                        rpad ('Salary', 15) ||  
                        rpad ('Commission', 15) ||  
                        rpad ('Hire date', 15));
```

```
Dbms_output.put_line (rpad ('Number', 15) ||  
                        rpad ('name', 15));
```

```
Dbms_output.put_line (rpad ('-', 85, '-'));
```

```
for rec_e in E  
loop
```

```
if rec_d.deptno = rec_e.deptno then  
    Dbms_output.put_line (rpad (rec_e.empno, 15)  
                          || rpad (rec_e.ename, 15)  
                          || rpad (rec_e.job, 15)  
                          || rpad (rec_e.sal, 15)  
                          || rpad (nvl (rec_e.comm, 0), 15)  
                          || rpad (rec_e.hiredate, 15));
```

```
end if;
```

```
end loop;
```

```
Dbms-output.put_line (rpad ('=' , 85, '='));
```

```
End Loop;
```

```
END;
```

```
/
```


5. write a cursor to display doctor wise patient report in following format.

DOCTORWISE PATIENT REPORT

Doctor ID: DO1 Doctors: vijay patel Case fee : 300
 patient ID patientname consulting fee medicine cost ^{Test} fee Total Amount

 1 purnav 200 300 0 400
 : : : : :

* Total Amount = consulting fee + medicine fee + Test fee



Set serveroutput on format wrapped

Declare

cursor doc is select * from doctor-master;

cursor pat is select * from patient-detail;

Totalamt number;

Begin

dbms_output.put_line(' ----- ');

dbms_output.put_line(' DOCTORWISE PATIENT REPORT ');

dbms_output.put_line(' ----- ');

for doca in doc

Loop

dbms_output.put_line(' doctor ID : ' || doca.docid ||

' Doctor : ' || doca.dnm || ' case fee : ' || doca.case-fee);

```
Dbms_output.put_line (rpad ('patient ID ', 15)
    || rpad ('patient name', 15) || rpad ('consulting fee', 20)
    || rpad ('medicine', 15) || rpad ('Test fee', 10)
    || rpad ('Total Amount', 15));
```

```
Dbms_output.put_line (rpad ('-', 90, '-'));
```

```
for patx in pat
```

```
Loop
```

```
Tot_amt:=patx.cons_fee + patx.medi_amt + patx.test_fee;
```

```
Dbms_output.put_line (rpad (patx.pid, 15) || rpad (patx.
    pnm, 15) || rpad (patx.cons_fee, 20) ||
    rpad (patx.medi_amt, 15) || rpad (patx.test_fee, 10)
    || rpad (tot_amt, 15));
```

```
END LOOP;
```

```
Dbms_output.put_line (rpad ('=', 90, '='));
```

```
END LOOP;
```

```
END;
```

```
/
```