

▼ Necessary Imports

```
import nltk, re, pprint, string
from nltk import word_tokenize, sent_tokenize
string.punctuation = string.punctuation + "'"+'''+'-'+'''+'+'+'-'
string.punctuation = string.punctuation.replace('.', '')
file = open('./dataset.txt', encoding = 'utf8').read()
```

▼ Preprocess of the Data

```
file_nl_removed = ""
for line in file:
    line_nl_removed = line.replace("\n", " ")
    file_nl_removed += line_nl_removed
file_p = "".join([char for char in file_nl_removed if char not in string.punctuation])
```

▼ Statistics of the Data

```
nltk.download('punkt')
sents = nltk.sent_tokenize(file_p)
print("The number of sentences is", len(sents))

words = nltk.word_tokenize(file_p)
print("The number of tokens is", len(words))

average_tokens = round(len(words)/len(sents))
print("The average number of tokens per sentence is",
average_tokens)

unique_tokens = set(words)
print("The number of unique tokens are", len(unique_tokens))

[nltk_data] Downloading package punkt to /root/nltk_data...
[nltk_data]   Unzipping tokenizers/punkt.zip.
The number of sentences is 981
The number of tokens is 27361
The average number of tokens per sentence is 28
The number of unique tokens are 3039
```

▼ Building the N-Gram Model

```
from nltk.util import ngrams
from nltk.corpus import stopwords
nltk.download('stopwords')
stop_words = set(stopwords.words('english'))

[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data]   Unzipping corpora/stopwords.zip.

unigram=[]
bigram=[]
trigram=[]
fourgram=[]
tokenized_text = []

for sentence in sents:
    sentence = sentence.lower()
    sequence = word_tokenize(sentence)
    for word in sequence:
        if (word == '.'):
            sequence.remove(word)
        else:
            unigram.append(word)
    tokenized_text.append(sequence)
    bigram.extend(list(ngrams(sequence, 2)))
    trigram.extend(list(ngrams(sequence, 3)))
    fourgram.extend(list(ngrams(sequence, 4)))
```

```
#removes ngrams containing only stopwords
def removal(x):
    y = []
    for pair in x:
        count = 0
        for word in pair:
            if word in stop_words:
                count = count or 0
            else:
                count = count or 1
        if (count==1):
            y.append(pair)
    return(y)
```

```
bigram = removal(bigram)
trigram = removal(trigram)
fourgram = removal(fourgram)
freq_bi = nltk.FreqDist(bigram)
freq_tri = nltk.FreqDist(trigram)
freq_four = nltk.FreqDist(fourgram)
print("Most common n-grams without stopword removal and without add-1 smoothing: \n")
print("Most common bigrams: ", freq_bi.most_common(5))
print("\nMost common trigrams: ", freq_tri.most_common(5))
print("\nMost common fourgrams: ", freq_four.most_common(5))
```

Most common n-grams without stopword removal and without add-1 smoothing:

Most common bigrams: [(['said', 'the'], 209), (['said', 'alice'], 115), (['the', 'queen'], 65), (['the', 'king'], 60), (['a', 'little'

Most common trigrams: [(['the', 'mock', 'turtle'], 51), (['the', 'march', 'hare'], 30), (['said', 'the', 'king'], 29), (['the', 'white'

Most common fourgrams: [(['said', 'the', 'mock', 'turtle'], 19), (['she', 'said', 'to', 'herself'], 16), (['a', 'minute', 'or', 'two']

▼ Script for downloading the stopwords using NLTK

```
from nltk.corpus import stopwords
stop_words = set(stopwords.words('english'))
```

▼ Print 10 Unigrams and Bigrams after removing stopwords

```
print("Most common n-grams with stopword removal and without add-1 smoothing: \n")
unigram_sw_removed = [p for p in unigram if p not in stop_words]
fdist = nltk.FreqDist(unigram_sw_removed)
print("Most common unigrams: ", fdist.most_common(10))
bigram_sw_removed = []
bigram_sw_removed.extend(list(ngrams(unigram_sw_removed, 2)))
fdist = nltk.FreqDist(bigram_sw_removed)
print("\nMost common bigrams: ", fdist.most_common(10))
```

Most common n-grams with stopword removal and without add-1 smoothing:

Most common unigrams: [(['said', 462), (['alice', 385), (['little', 128), (['one', 101), (['like', 85), (['know', 85), (['would', 83), (['went'

Most common bigrams: [(['said', 'alice'], 122), (['mock', 'turtle'], 54), (['march', 'hare'], 31), (['said', 'king'], 29), (['thought'

▼ Add-1 smoothing

```
ngrams_all = {1:[], 2:[], 3:[], 4:[]}
for i in range(4):
    for each in tokenized_text:
        for j in ngrams(each, i+1):
            ngrams_all[i+1].append(j)
ngrams_voc = {1:set([]), 2:set([]), 3:set([]), 4:set([])}
for i in range(4):
    for gram in ngrams_all[i+1]:
        if gram not in ngrams_voc[i+1]:
            ngrams_voc[i+1].add(gram)
```

```

total_ngrams = {1:-1, 2:-1, 3:-1, 4:-1}
total_voc = {1:-1, 2:-1, 3:-1, 4:-1}
for i in range(4):
    total_ngrams[i+1] = len(ngrams_all[i+1])
    total_voc[i+1] = len(ngrams_voc[i+1])

ngrams_prob = {1:[], 2:[], 3:[], 4:[]}
for i in range(4):
    for ngram in ngrams_voc[i+1]:
        tlist = [ngram]
        tlist.append(ngrams_all[i+1].count(ngram))
        ngrams_prob[i+1].append(tlist)

for i in range(4):
    for ngram in ngrams_prob[i+1]:
        ngram[-1] = (ngram[-1]+1)/(total_ngrams[i+1]+total_voc[i+1])

```

▼ Prints top 10 unigram, bigram, trigram, fourgram after smoothing

```

print("Most common n-grams without stopword removal and with add-1 smoothing: \n")
for i in range(4):
    ngrams_prob[i+1] = sorted(ngrams_prob[i+1], key = lambda x:x[1], reverse = True)

print ("Most common unigrams: ", str(ngrams_prob[1][:10]))
print ("\nMost common bigrams: ", str(ngrams_prob[2][:10]))
print ("\nMost common trigrams: ", str(ngrams_prob[3][:10]))
print ("\nMost common fourgrams: ", str(ngrams_prob[4][:10]))

```

Most common n-grams without stopword removal and with add-1 smoothing:

Most common unigrams: [[('the',), 0.05598462224968249], [('and',), 0.02900490852298081], [('to',), 0.02478289225277177], [('a',), 0.02

Most common bigrams: [[('said', 'the'), 0.0053395713087035016], [('of', 'the'), 0.0033308754354293268], [('said', 'alice'), 0.00294947

Most common trigrams: [[('the', 'mock', 'turtle'), 0.001143837575064341], [('the', 'march', 'hare'), 0.0006819031697498955], [('said',

Most common fourgrams: [[('said', 'the', 'mock', 'turtle'), 0.00043521782652217433], [('she', 'said', 'to', 'herself'), 0.000369935152

▼ Next word Prediction

```

str1 = 'after that alice said the'
str2 = 'alice felt so desperate that she was'

token_1 = word_tokenize(str1)
token_2 = word_tokenize(str2)
ngram_1 = {1:[], 2:[], 3:[]} #to store the n-grams formed
ngram_2 = {1:[], 2:[], 3:[]}
for i in range(3):
    ngram_1[i+1] = list(ngrams(token_1, i+1))[-1]
    ngram_2[i+1] = list(ngrams(token_2, i+1))[-1]
print("String 1: ", ngram_1, "\nString 2: ", ngram_2)

String 1:  {1: ('the',), 2: ('said', 'the'), 3: ('alice', 'said', 'the')}
String 2:  {1: ('was',), 2: ('she', 'was'), 3: ('that', 'she', 'was')}

for i in range(4):
    ngrams_prob[i+1] = sorted(ngrams_prob[i+1], key = lambda x:x[1], reverse = True)

pred_1 = {1:[], 2:[], 3:[]}
for i in range(3):
    count = 0
    for each in ngrams_prob[i+2]:
        if each[0][-1] == ngram_1[i+1]:
            count +=1
            pred_1[i+1].append(each[0][-1])
            if count ==5:
                break
    if count<5:
        while(count!=5):

```

```

        pred_1[i+1].append("NOT FOUND")
#if no word prediction is found, replace with NOT FOUND
        count +=1
for i in range(4):
    ngrams_prob[i+1] = sorted(ngrams_prob[i+1], key = lambda x:x[1], reverse = True)

pred_2 = {1:[], 2:[], 3:[]}
for i in range(3):
    count = 0
    for each in ngrams_prob[i+2]:
        if each[0][-1] == ngram_2[i+1]:
            count +=1
            pred_2[i+1].append(each[0][-1])
            if count ==5:
                break
    if count<5:
        while(count!=5):
            pred_2[i+1].append("\0")
            count +=1

print("Next word predictions for the strings using the probability models of bigrams, trigrams, and fourgrams\n")
print("String 1 - after that alice said the-\n")
print("Bigram model predictions: {} \nTrigram model predictions: {} \nFourgram model predictions: {} \n" .format(pred_1[1], pred_1[2], pred_1[3])
print("String 2 - alice felt so desperate that she was-\n")
print("Bigram model predictions: {} \nTrigram model predictions: {} \nFourgram model predictions: {}" .format(pred_2[1], pred_2[2], pred_2[3]))

Next word predictions for the strings using the probability models of bigrams, trigrams, and fourgrams

String 1 - after that alice said the-

Bigram model predictions: ['queen', 'king', 'mock', 'gryphon', 'hatter']
Trigram model predictions: ['king', 'hatter', 'mock', 'caterpillar', 'gryphon']
Fourgram model predictions: ['NOT FOUND', 'NOT FOUND', 'NOT FOUND', 'NOT FOUND', 'NOT FOUND']

String 2 - alice felt so desperate that she was-

Bigram model predictions: ['a', 'the', 'not', 'going', 'that']
Trigram model predictions: ['now', 'quite', 'a', 'beginning', 'walking']
Fourgram model predictions: ['now', 'dozing', 'ready', 'losing', 'walking']

```