

Solution COND Operator

- 1) Use the COND operator instead of IF
- 2) Delete the temporary variable l_ord_description

```
DATA: l_tab_doctyp      TYPE RANGE OF esart.

l_tab_doctyp = VALUE #( ( sign = 'I' option = 'EQ' low = 'NB' )
                        ( sign = 'I' option = 'EQ' low = 'ZNB' ) ).

SELECT *                "* means get all fields
  UP TO 10 ROWS         "only retrieves 10 rows
  FROM ekko
  INTO TABLE @DATA(lt_ekko)
  WHERE bsart IN @l_tab_doctyp.

LOOP AT lt_ekko ASSIGNING FIELD-
SYMBOL(<f_ekko>).      "loops around the data in table it_ekko

  WRITE: / |PO number: | && <f_ekko>-ebeln.

  WRITE: | { <f_ekko>-pincr ALPHA = OUT } |.

  WRITE: COND #( WHEN <f_ekko>-bsart = 'NB' AND <f_ekko>-waers = 'USD'
                  THEN 'Standard Order in United States'
                  WHEN <f_ekko>-bsart = 'NB' AND <f_ekko>-
waers = 'EUR'
                  THEN 'Standard Order in Europe'
                  WHEN <f_ekko>-bsart = 'NB'
                  THEN 'Standard Order - Others'
                ).

ENDLOOP.
```