

Working with table environments in texor

by Abhishek Ulayil

Abstract This is a small sample article to demonstrate usage of **texor** to convert table environments.

1 Introduction

Tables are commonly used in RJ articles to display data in a tabular format. However, there are differences in the way tables are handled by LaTeX and HTML. LaTeX tables have more customization and are usually optimized for printing, whereas the web articles need tables optimized for varying sizes of media. Pandoc converts most of the tables somewhat easily, but is unable to do well with table customization packages and complex tables. Some pandoc extensions are used in order to tackle them, they are : `simple_tables`, `pipe_tables`

2 Generic tables

Normal LaTeX tables will be converted just fine, even if they include a bit of math and other elements. However do note that the conversion will be done to traditional or pandoc style markdown instead of Rmarkdown specific using `knitr::kable(...)` function. Also any custom LaTeX commands or specific font characters would not be supported.

| Graphics Format | LaTeX | Markdown | Rmarkdown | HTML |
|-----------------|-------|----------|-----------|------|
| PNG | Yes | Yes | Yes | Yes |
| JPG | Yes | Yes | Yes | Yes |
| PDF | Yes | No | No | No |
| SVG | No | Yes | Yes | Yes |
| Tikz | Yes | No | Yes | No |
| Algorithm | Yes | No | No | No |

Table 1: Image Format support in various Markup/Typesetting Languages

3 Multicolumn tables

| EXAMPLE | X | | Y | |
|---------|-----|-----|-----|-----|
| | 1 | 2 | 1 | 2 |
| EX1 | X11 | X12 | Y11 | Y12 |
| EX2 | X21 | X22 | Y21 | Y22 |
| EX3 | X31 | X32 | Y31 | Y32 |
| EX4 | X41 | X42 | Y41 | Y42 |
| EX5 | X51 | X52 | Y51 | Y52 |

Table 2: An Example Table with Multicolumn

The above example illustrates a multicolumn table 2, which the **texor** package can handle through subroutines and pre-processing step to transform the LaTeX code.

- The Stream Editor modifies the `\multicolumn{...}` to `\multicolumnx{...}`
- Then a LaTeX macro redefines the `\multicolumnx{...}` to `\multicolumn{---}`, which is accepted by pandoc.
- Finally pandoc reads the table and transforms it to markdown.

Also note that the stream editor is used to rename `table*` environment to `table` environment because the markdown/HTML will not support the specific changes `table*` environment will bring.

4 Complex tables

A complex table with various other elements like figures, math , code and so on, are also supported by [texor](#).


| Inline Format | LaTeX Support | Web Support | Rendering |
|---------------|---------------|-------------|--|
| Text | Yes | Yes | Hello |
| Image | Yes | Yes |  |
| CodeBlock | Yes | Yes | <pre>x <- 1:100 y <- dbinom(x,100,prob = 0.5) plot(x,y)</pre> |
| Math | Yes | Yes | $e = mc^2$ |
| Link | Yes | Yes | Google |
| Nested Table | Yes | No | NaN |

Table 3: Image Format support in various Markup/Typesetting Languages

5 Wide tables

Widetable environments also gets some perks when converted by [texor](#) package. They get their own block and separate numbering (although references are shared by figures).

Here is a reference to the [table 4](#) and [table 5](#).

6 Summary

In summary the [texor](#) package supports:

- some common table environments.
- wide tables.
- some multicolumn tables.
- inclusion of different environments like figure/code in tables.

Bibliography

A. Krewinkel and A. Lucero pandoc 3.0 Release notes *pandoc* 2023 URL <https://pandoc.org/releases.html> [p]

Abhishek Ulayil
Student, Institute of Actuaries of India
Mumbai, India
 ORCID: 0009-0000-6935-8690

| index | A | B | C | D | E | F | G | H |
|-------|--------|--------|---------|------|-------|------|------|------|
| 1 | 359.00 | NaN | 5796.00 | 0.00 | 16.14 | 1.00 | NaN | 0.00 |
| 2 | 25.73 | 0.00 | 1029.20 | NaN | 40.00 | 0.68 | 0.00 | 0.00 |
| 2.1 | 26.26 | 0.00 | 13.40 | 0.00 | 2.14 | 0.68 | 0.00 | NaN |
| 2.2 | 32.06 | 20.06 | 47.64 | 0.04 | 1.80 | 0.68 | 0.01 | NaN |
| 2.3 | 51.94 | 420.27 | 21.17 | 0.20 | 1.77 | 0.74 | 0.05 | NaN |
| 2.4 | 40.62 | 30.44 | 0.90 | 0.57 | 1.44 | 1.31 | 0.24 | NaN |
| ... | ... | ... | ... | ... | ... | ... | ... | ... |

| index | I | J | K | L | M | N | O |
|-------|------|--------|------|------|------|------|---------|
| 1 | 0.00 | −1.73 | 0.00 | 0.00 | 0.00 | 0.00 | NaN |
| 2 | 0.21 | −33.41 | 0.00 | 0.11 | 0.00 | NaN | −197.85 |
| 2.1 | 0.24 | −24.00 | 0.00 | 0.15 | NaN | 0.06 | −70.46 |
| 2.2 | 0.6 | −19.42 | 0.00 | 0.15 | 0.00 | 0.11 | −16.48 |
| 2.3 | 0.75 | −31.77 | 0.00 | 0.18 | 0.01 | 0.37 | −0.82 |
| 2.4 | 0.26 | −1.89 | 0.1 | 0.55 | 0.70 | 0.22 | −6.55 |
| ... | ... | ... | ... | ... | ... | ... | ... |

Table 4: A dummy research data

| Package | Commits | Version | Last Updated |
|---------------------------|---------|---------|--------------|
| texor | 260 | 1.1.0 | 28-Jul-2023 |
| rebib | 76 | 0.2.4 | 29-Jul-2023 |
| rjtools | 314 | 1.0.11 | 30-Jul-2023 |
| rmarkdown | 3189 | 2.23 | 31-Jul-2023 |

Table 5: A dummy summary of a few CRAN packages