Today's Content

1. Infix to Postfix
2. Evaluate Postfix

Expression Evaluation:

We write expression in infix:

infix: operator between operands

Issue is system cannot evaluate infix, so it converts infix → postfix & evaluate postfix expression.

postfix: operator after operands.

Q: Given Infix Expression

1. Convert to postfix
2. Evaluate postfix.

Infix Expression	Postfix Expression		
a + b	ab +		
a - b	ab -		
a / b	ab /		
a * b	ab *		
a + b*c	a + bc*	a bc* +	
4 + 3*3 - 2	4 + 33* - 2	4 33* + 2 -	
6 + 3 * (3+2) - 5	6 + 3 * 32+ - 5	6 + 3 32+ * - 5	6 3 32+ * + 5 -

#obs: In postfix no ()

Given an Infin, convert to Postfin Expression.

#Note: Infin expression is vector of strings, where each string can be operand/operator/bracket.

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Infin:	A	+	B	*	C	-	D	*	(	F	+	G	*	K	)
Postfin:	A	B	C	*	+	D	F	G	K	*	+	*	-		

#Idea: Infin → Postfin TC: O(N) SC: O(N)



```
Iterate in Infin:
    if Infin[i] is operand: Postfin.push_back(Infin[i])
    if Infin[i] is open bracket: st.push(Infin[i])
    if Infin[i] is closing bracket:
        while(st.top() != open bracket){
            Postfin.push_back(st.top());
            st.pop();
        }
        st.pop();
    if Infin[i] is operator,
        while(st.size()>0 && st.top() != open bracket &&
                                pred(st.top()) >= pred(Infin[i])){
            Postfin.push_back(st.top());
            st.pop();
        }
    st.push(Infin[i])

while(st.size()>0){
    Postfin.push_back(st.top());
    st.pop();
}
```

Evaluate Post Expressin:

#Note: Post expressim is vector of strings, where each string can be operand/operatr/bracket.

```
          0  1  2  3  4  5  6  7  8  9  10
Infin :   16 + 3  *  (  30 + 20 ) - 15;

          0  1  2  3  4  5  6  7  8
postfin:  16 3  30 20 +  *  +  15 -
```



	A	operatr	B	
#Note:	2nd pop()	T	1st pop()	
operatr :	30	+	20	= 50 push st
operatr :	3	*	50	= 150 push st
operatr :	16	+	150	= 166 push st
operatr :	166	-	15	= 151 push st

Retrn top of stack = 151.

#Idea: Evaluate Postfin Expressim. TC: O(N) SC: O(N)

```
stack<int> st;
Iterate m Postfin:
    if Postfin[i] is operand : st.push( stoi( postfin[i] ));
    if Postfin[i] is operatr:
        int B = st.top(); st.pop();
        int A = st.top(); st.pop();
        st.push(A operatr B)
}

return st.top();
```