



Web Programming

Javascript

Module 2

Agenda

1

JavaScript Regular Expressions

Objectives

At the end of this module you will be able to:

- Understand the use of regular expressions
- Validate user inputs using regular expressions

JavaScript Regular Expressions



Regular Expression in Javascript

- The most difficult part of creating user interface for a web application is user validation
- Developing user interfaces that will be accessed by different browsers is much more painful, due to lack of useful validation functions in Javascript
- Luckily, Javascript (version 1.2 and above) has incorporated regular expressions, using which we can perform validations easily
- Regular expression are tools for performing pattern matching
- We can perform complex task that requires lengthy procedures with just few lines using regular expressions

Use of Patterns

- Regular expressions are implemented in Javascript in the following way:
- `var regexp = /pattern/`
- To use regular expressions to validate a String you need to define a pattern String that defines the search criteria
- Use a relevant String method to denote actions like search or test
- Patterns are defined using String literal characters or meta characters

Metacharacters

- Metacharacters are characters with special meaning

| Metacharacter | What it means |
|---------------|--|
| \d | Find a digit |
| \D | Find a non-digit character |
| \w | Find a word character |
| \W | Find a non-word character |
| \s | Find a whitespace character |
| \S | Find a non-whitespace character |
| \b | Find a match at the beginning or end of a word |
| \B | Find a match not at the beginning or end of a word |

Example 1

- The following example demonstrates how to use patterns that will check whether the key pressed is a digit or not:

```
<html>
<body>
<script language="javascript">
function onlyNumbers(e) {
    var keynum
    var keychar
    var numcheck
    if(window.event) {
        keynum = e.keyCode
    }
```

Contd..

Example 1 (Contd.).

```
    keychar = String.fromCharCode(keynum)
    numcheck = /\d/
    return numcheck.test(keychar)
}
</script>
```

```
<form>
<input type="text" onkeypress="return onlyNumbers(event)" />
</form>
</body>
</html>
```

Example 1 (Contd.).

- When the user presses any key, an event is generated. The key on which the event is generated, is stored in the variable `keynum` by capturing the `keyCode`.
- The javascript String method *`fromCharCode()`* is used to convert the unicode value to character and it is stored in the variable `keychar`.
- The variable *`numcheck`* defines a pattern for searching. Here `\d` is the metacharacter, which is used to find a digit.
- The String method *`test()`* is used to match the pattern(here it is trying to match the character obtained from the keypress with `\d`, i.e a digit).
- Thus, the function *`onlyNumbers()`* will return the value of the keypress only if it is a digit(0 – 9). It will not return any other character.

Brackets

- Brackets are used to find a range of characters

| Expression | What it means |
|--------------------------|--|
| [xyz] | Find any character between the brackets |
| [^xyz] | Find any character not between the brackets |
| [A-Z] | Find any character from uppercase A to uppercase Z |
| [a-z] | Find any character from lowercase a to lowercase z |
| [A-z] | Find any character from uppercase A to lowercase z |
| [0-9] | Find any digit from 0 to 9 |
| [Bandra Andheri Borivli] | Find any of the alternatives specified |

Example 2

- The following example demonstrates how to use patterns that will check whether the key pressed is an alphabet(Lower case or upper case):

```
<html>
<body>
<script language="javascript">
function onlyCharacters(e) {
    var keynum
    var keychar
    var charcheck
    if(window.event) {
        keynum = e.keyCode
    }
```

Example 2 (Contd.).

```
    keychar = String.fromCharCode(keynum)
    charcheck = /[A-Za-z]/
    return charcheck.test(keychar)
}
</script>
```

```
<form>
<input type="text" onkeypress="return onlyCharacters(event)" />
</form>
</body>
</html>
```

Quiz

What happens when you move the mouse pointer on the image displayed?

```
<html>
  <body bgcolor="pink">
    
    <script>
      function vh() {
        document.ash.src="ash3.bmp";
      }
      function hv() {
        document.ash.src="ash2.bmp";
      }
    </script>
  </body></html>
```

Quiz (Contd.).

What happens when you move the mouse pointer on the image displayed? What happens when you move the mouse pointer out of the image?

```
<html>

<script>
function vh(){
    document.ash.height=document.ash.height+1;
    document.ash.width=document.ash.width+1;
}
function hv(){
    document.ash.height=document.ash.height-100;
    document.ash.width=document.ash.width-100;
}
</script></body></html>
```

Summary

In this module, you were able to:

- Understand the use of regular expressions
- Validate user inputs using regular expressions



Thank You