

③

```

Q2. #include <stdio.h>
    #include <string.h>
    struct wordRev {
        char word[100];
    };

Q2. #include <stdio.h>
    #include <string.h>

    int main() {
        char arr[50];
        int count = 0;

        printf("Enter string:");
        gets(arr);

        printf("Before sorting: %s", arr);

        int length = strlen(arr);
        int j = length/2;
        int k = length-1;
        for (int i = 0; i < j; i++) {
            char temp;

```

④

```

        temp = arr[i];
        arr[i] = arr[k];
        arr[k] = temp;
        k--;
    }
    printf("After reverse string is %s\n", arr);
    return 0;
}

```

①

```

Q1. class subarray {
    int arr;
    int sum;
    void subarray(int arr, int sum) {
        this.arr = arr;
        this.sum = sum;
    }
    void findSubarray() {
        for (int i = 0; i < arr.length; i++) {
            int s = 0; // current sum
            for (int j = i; j < arr.length; j++) {
                if (s == sum) {
                    System.out.println("sum found "
                        + i + " and " + j);
                    System.out.println("sum of elements
                        between indices " + i);

```

②

```

        for (int k = i; k <= j; k++) {
            System.out.println(arr[k]);
            if (k < j) {
                System.out.println(" + ");
            }
            System.out.println(" " + sum);
        }
    }
    public class findSubarrayApp {
        public static void main (String x[]) {
            subarray sub = new subarray();
            int arr = { 1, 4, 20, 3, 10, 5 };
            int sum = 33;
            sub.subarray(arr, sum);
            sub.findSubarray();
        }
    }
}

```

93

```

class printPrime {
    public int checkPrime (int n)
    {
        if (n <= 1)
        {
            return 0;
        }
        for (int i = 2; i <= n/2; i++)
        {
            if (n % i == 0)
            {
                return 0;
            }
        }
        return 1;
    }
}

public class printPrimeApp {
    public static void main (String
    x[])
    {
        printPrime pm = new printPrime ();
    }
}

```

int count = 0;

```

for (int i = 200; i >= 1; i--)
{
    if (printPrime.check
    if (pm.checkPrime(i) == 1)
    {
        System.out.println(i);
        count++;
    }
    if (count == 5)
    {
        break;
    }
}
}
}

```

Sal.

① Company table

```

create table Company (
    cid int(5) primary key
    auto-increment,
    name varchar(100) not null
);

```

② Employee table

```

create table Employee (
    eid int(5) primary key
    auto-increment,
    name varchar(100) not null,
    email varchar(100) not null unique,
    contact varchar(100) not null
    unique,
    salary int(5) check (salary > 500)
);

```

③ CSJOSH

```

create table csjosh (
    eid int(5)
    eid int(5)
    Foreign key (cid) References Company
    (cid),
    Foreign key (eid) References Employee
    (eid);

```


9

~~Insert~~ insert Record in company

- ① - insert into company ~~values~~ (name)
values ("TCS");
- insert into company ~~values~~ (name)
values ("Infosys");
- insert into company (name)
values ("Cognizant");

② Insert Record in Employee

- insert into Employee (name, email,
contact, salary, des)
values ("abc", "abc@gmail.com", 12345,
10000, "Dev");
- insert into Employee (name, email,
contact, salary, des)
values ("mno", "mno@gmail.com",
54554, 10000, "Tester");

10

③ insert into cjoin

- ① insert into cjoin ~~(1,1)~~ values
(1,1);
- ② insert into cjoin values (1,2);
- ③ insert into cjoin values (2,1);