```
Last login: Mon Oct 14 16:24:52 on ttys000
(base) abhiramabhi@macbookpro ~ % ls
Applications                      PycharmProjects
Autodesk                          Untitled.ipynb
Desktop                           aa.c
Documents                         abollam1@charlotte.edu - Google Drive
Downloads                         abollam2@gitam.in - Google Drive
GameMakerProjects                 basic
IdeaProjects                      calc.py
Library                           fastapi-tutorial
Movies                            gamemakerstudio2
Music                             github_practice
Pictures                          scikit_learn_data
Public                            untitled folder
(base) abhiramabhi@macbookpro ~ % cd Documents
(base) abhiramabhi@macbookpro Documents % ls
Adobe                   file.pdf
GitHub                  part1.drawio
Honor code AB.pdf       part1.drawio.pdf
Part1.png               part3.png
ScrollingShooter_801381722   passport.pdf
Tab.png                 visa.pdf
compant-query.sql
(base) abhiramabhi@macbookpro Documents % cd GitHub
(base) abhiramabhi@macbookpro GitHub % ls
FastAPI          Sand                main.py
HorribleCodeActivity    Sand2
ITSC3155-Students       banking-2
(base) abhiramabhi@macbookpro GitHub % ls
FastAPI          Sand                main.py
HorribleCodeActivity    Sand2
ITSC3155-Students       banking-2
(base) abhiramabhi@macbookpro GitHub % cd FastAPI
(base) abhiramabhi@macbookpro FastAPI % ls
README.md       main1.py
(base) abhiramabhi@macbookpro FastAPI % git add
Nothing specified, nothing added.
hint: Maybe you wanted to say 'git add .'?
hint: Disable this message with "git config advice.addEmptyPathspec false"
(base) abhiramabhi@macbookpro FastAPI % git add .
(base) abhiramabhi@macbookpro FastAPI % git commit -m "Final"
[main 171e2a4] Final
 1 file changed, 25 insertions(+)
 create mode 100644 main.py
(base) abhiramabhi@macbookpro FastAPI % git push
fatal: No configured push destination.
Either specify the URL from the command-line or configure a remote repository using

    git remote add <name> <url>

and then push using the remote name

    git push <name>

(base) abhiramabhi@macbookpro FastAPI % git remote add FastAPI https://github.com/Abhi3003-18/FastAPI
(base) abhiramabhi@macbookpro FastAPI % git push FastAPI
Everything up-to-date
(base) abhiramabhi@macbookpro FastAPI % █
```

Responses

Curl

```
curl -X 'GET' \
  'http://127.0.0.1:8000/items/20' \
  -H 'accept: application/json'
```

Request URL

```
http://127.0.0.1:8000/items/20
```

Server response

Code	Details
200	Response body

```
{
  "item_id": 20,
  "q": null
}
```

Response headers

```
content-length: 23
content-type: application/json
date: Mon,21 Oct 2024 03:56:25 GMT
server: uvicorn
```

Responses

Code	Description	Links
200	Successful Response	No links

Media type

application/json

Controls Accept header.

Example Value | Schema

```
"string"
```

Execute	Clear

Responses

Curl

```
curl -X 'PUT' \
  'http://127.0.0.1:8000/items/20' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
  "name": "string",
  "price": 0,
  "is_offer": true
}'
```

Request URL

```
http://127.0.0.1:8000/items/20
```

Server response

Code	Details
200	**Response body**

```
{
  "item_name": "string",
  "item_id": 20
}
```

Response headers

```
content-length: 35
content-type: application/json
date: Mon,21 Oct 2024 03:55:30 GMT
server: uvicorn
```

Responses

Code	Description	Links
200	Successful Response	No links

GET / Read Root ^

Parameters Cancel

No parameters

Servers

These operation-level options override the global server options.

/ ▾

| Execute | Clear |

Responses

Curl

```
curl -X 'GET' \
  'http://127.0.0.1:8000/' \
  -H 'accept: application/json'
```

Request URL

```
http://127.0.0.1:8000/
```

Server response

Code	Details
200	**Response body**
	``` { "Hello": "World" ```