

# GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Sunday, 12 January 2025, 10:57 PM
Completed	Sunday, 12 January 2025, 11:05 PM
Duration	8 mins 1 sec

Question 1

Correct

Flag question

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

arr=[1,2,3,4,6]

- the sum of the first three elements, 1+2+3=6. The value of the last element is 6.
- Using zero based indexing, arr[3]=4 is the pivot between the two subarrays.
- The index of the pivot is 3.

Function Description

Complete the function balancedSum in the editor below.

Returns:

int: an integer representing the index of the pivot

Constraints

- $3 \leq n \leq 10^5$
- $1 \leq arr[i] \leq 2 \times 10^4$ , where  $0 \leq i < n$
- It is guaranteed that a solution always exists.

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer  $n$ , the size of the array  $arr$ .

Each of the next  $n$  lines contains an integer,  $arr[i]$ , where  $0 \leq i < n$ .

Sample Case 0

Sample Input 0

STDIN    Function Parameters

-----

4    →  $arr[]$  size  $n = 4$

1    →  $arr = [1, 2, 3, 3]$

3

Sample Output 0

2

Explanation 0

- The sum of the first two elements,  $1+2=3$ . The value of the last element is 3.
- Using zero based indexing,  $arr[2]=3$  is the pivot between the two subarrays.
- The index of the pivot is 2.

Sample Case 1

Sample Input 1

STDIN    Function Parameters

-----

3    → arr[] size n = 3

1    → arr = [1, 2, 1]

2

1

Sample Output 1

## Explanation 1

- The first and last elements are equal to 1.
- Using zero based indexing, arr[1]=2 is the pivot between the two subarrays.
- The index of the pivot is 1.

**Answer:** (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'balancedSum' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER_ARRAY arr as parameter.
6  */
7
8  int balancedSum(int arrcount, int* arr)
9  {
10     int tsum = 0, lsum = 0;
11     for (int i=0; i<arrcount;i++){
12         tsum+=arr[i];
13     }
14     for (int i=0;i<arrcount;i++){
15         tsum-=arr[i];
16         if (lsum == tsum){
17             return i;
18         }
19         lsum+=arr[i];
20     }
21     return 1;
22 }
23
```

✓	<pre>int arr[] = {1,2,3,3}; printf("%d", balancedSum(4, arr))</pre>	2	2	✓
---	---	---	---	---

Passed all tests! ✓

Question **2**

Correct

🚩 [Flag question](#)

Calculate the sum of an array of integers.

Example

numbers = [3, 13, 4, 11, 9]

The sum is  $3 + 13 + 4 + 11 + 9 = 40$ .

Function Description

Complete the function arraySum in the editor below.

arraySum has the following parameter(s):

int numbers[n]: an array of integers

Returns

int: integer sum of the numbers array

Constraints

$1 \leq \text{numbers}[i] \leq 10^4$

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n, the size of the array numbers.  
Each of the next n lines contains an integer numbers[i] where  $0 \leq i < n$ .

Sample Case 0  
Sample Input 0

STDIN	Function
-----	-----
5	→ numbers[] size n = 5
1	→ numbers = [1, 2, 3, 4, 5]
2	
3	
4	
5	

Sample Output 0

15

$1 + 2 + 3 + 4 + 5 = 15.$

Sample Case 1

Sample Input 1

STDIN      Function

-----

2      →    numbers[] size n = 2

12     →    numbers = [12, 12]

12

Sample Output 1

24

Explanation 1

$12 + 12 = 24.$

**Answer:** (penalty regime: 0 %)

Reset answer

```
1 1 /*
2 2 * Complete the 'arraySum' function below.
3 3 *
4 4 * The function is expected to return an INTEGER.
5 5 * The function accepts INTEGER ARRAY numbers as parameter.
```

```
8 int arraySum(int ncount, int n[])
9 {
10     int sum=0;
11     for (int i=0; i<ncount;i++){
12         sum+=n[i];
13     }
14     return sum;
15 }
16
```

	Test	Expected	Got	
✓	int arr[] = {1,2,3,4,5}; printf("%d", arraySum(5, arr))	15	15	✓

Passed all tests! ✓

Question **3**

Correct

🚩 [Flag question](#)

Given an array of n integers, rearrange them so that the sum of the absolute differences of all adjacent elements is minimized. Then, compute the sum of those absolute differences. Example n = 5 arr = [1, 3, 3, 2, 4] If the list is rearranged as arr' = [1, 2, 3, 3, 4], the absolute differences are |1 - 2| = 1, |2 - 3| = 1, |3 - 3| = 0, |3 - 4| = 1. The sum of those differences is 1 + 1 + 0 + 1 = 3. Function Description Complete the function minDiff in the editor below. minDiff has the following parameter: arr: an integer array Returns: int: the sum of the absolute differences of adjacent elements Constraints 2 ≤ n ≤ 105 0 ≤ arr[i] ≤ 109, where 0 ≤ i < n Input Format For Custom Testing The first line of input contains an integer, n, the size of arr. Each of the



5 5 → arr[] = [5, 1, 3, 7, 3] 1 3 7 3 Sample Output 6 Explanation n = 5 arr = [5, 1, 3, 7, 3]  
 If arr is rearranged as arr' = [1, 3, 3, 5, 7], the differences are minimized. The final  
 answer is  $|1 - 3| + |3 - 3| + |3 - 5| + |5 - 7| = 6$ . Sample Case 1 Sample Input For Custom  
 Testing STDIN Function ----- 2 → arr[] size n = 2 3 → arr[] = [3, 2] 2 Sample  
 Output 1 Explanation n = 2 arr = [3, 2] There is no need to rearrange because there are  
 only two elements. The final answer is  $|3 - 2| = 1$ .

**Answer:** (penalty regime: 0 %)

Reset answer

```

1  /*
2   * Complete the 'minDiff' function below.
3   *
4   * The function is expected to return an INTEGER.
5   * The function accepts INTEGER_ARRAY arr as parameter.
6   */
7  int compare(const void* a, const void*b){
8      return (*(int*)a - *(int*)b);
9  }
10 int minDiff(int arr_count, int* arr)
11 {
12     qsort(arr, arr_count, sizeof(int), compare);
13     int min_sum = 0;
14     for (int i=1; i<arr_count; i++){
15         min_sum += abs(arr[i] - arr[i-1]);
16     }
17     return min_sum;
18 }
19

```

Test

Expected

Got

Passed all tests! ✓

Finish review