

Sheth L.U.J. College of Arts And Sir M.V. College of Science and Commerce

Data Analysis with SAS / SPSS / R

PRACTICAL NO 2 MODULE 2

AIM: Generating frequency tables using table() or count()

OUTPUT:

```
DATA SET - RStudio
File Edit Code View Plots Session Build Debug Profile Tools Help
Go to file/function Addins

Source
Console Terminal Background Jobs
R 4.5.2 - C:/Users/as993/DATA SET/

> # Practical 2: Generating Frequency Tables
> # Dataset: before_after_marketing_campaign.csv
> #
> # Install & load required package
> if(!require(dplyr)) install.packages("dplyr")
> library(dplyr)
> #
> # 1. Load Dataset
> #
> df <- read.csv("before_after_marketing_campaign.csv",
+               stringsAsFactors = FALSE)
> #
> print("--- Dataset Loaded ---")
[1] "--- Dataset Loaded ---"
> print(colnames(df)) # Ye check karein taaki columns dikh jayein
[1] "customer_id" "region" "marketing_channel" "campaign_type"
[5] "before_campaign_sales" "after_campaign_sales" "before_campaign_visits" "after_campaign_visits"
[9] "conversion_rate_before" "conversion_rate_after" "campaign_cost_usd" "customer_retained"
> #
> # 2. Frequency Tables
> #
> print("--- 2. Frequency Tables (Campaign Type Distribution) ---")
[1] "--- 2. Frequency Tables (Campaign Type Distribution) ---"
> # A. Using Base R table()
> # Good for: Simple counts
> # Correction: 'campaign_phase' -> 'campaign_type'
> campaign_counts <- table(df$campaign_type)
> print(campaign_counts)

Brand Awareness 3979 Discount New Product Launch 3945
> # B. Using dplyr::count()
> # Good For: Dataframe output
```

```
DATA SET - RStudio
File Edit Code View Plots Session Build Debug Profile Tools Help
Go to file/function Addins

Source
Console Terminal Background Jobs
R 4.5.2 - C:/Users/as993/DATA SET/

> # 1. Load Dataset
> #
> df <- read.csv("before_after_marketing_campaign.csv",
+               stringsAsFactors = FALSE)
> #
> print("--- Dataset Loaded ---")
[1] "--- Dataset Loaded ---"
> print(colnames(df)) # Ye check karein taaki columns dikh jayein
[1] "customer_id" "region" "marketing_channel" "campaign_type"
[5] "before_campaign_sales" "after_campaign_sales" "before_campaign_visits" "after_campaign_visits"
[9] "conversion_rate_before" "conversion_rate_after" "campaign_cost_usd" "customer_retained"
> #
> # 2. Frequency Tables
> #
> print("--- 2. Frequency Tables (Campaign Type Distribution) ---")
[1] "--- 2. Frequency Tables (Campaign Type Distribution) ---"
> # A. Using Base R table()
> # Good for: Simple counts
> # Correction: 'campaign_phase' -> 'campaign_type'
> campaign_counts <- table(df$campaign_type)
> print(campaign_counts)

Brand Awareness 3979 Discount New Product Launch 3945
> # B. Using dplyr::count()
> # Good For: Dataframe output
> # Correction: 'campaign_phase' -> 'campaign_type'
> campaign_df <- df %>% count(campaign_type)
> print(campaign_df)
  campaign_type n
1 Brand Awareness 3979
2 Discount 4076
3 New Product Launch 3945
> |
```

NAME : ABHISHEK DINESH SINGH
ROLL NO: S116