

Git Helper

for Azure DevOps

User Guide

Connect · Clone · Change · Commit · Push · Pull Request

Git Helper — User Guide

Git Helper is a friendly Git client for **Azure DevOps**. It explains your repo's state in plain language, shows the next safe step, and covers the whole loop: **connect** → **clone** → **change** → **commit** → **push** → **pull request** — without the Git CLI.

Get the app: download the installer for Windows or macOS from the [latest release](#), or run it from source (`npm run dev` → <http://localhost:5173>). First launch on Windows: **More info** → **Run anyway**; on macOS: **right-click** → **Open**.

Contents

1. [Connect to Azure DevOps](#)
 2. [Clone a repository](#)
 3. [Your repositories](#)
 4. [Status](#) — your home screen
 5. [Changes](#) — review what you did
 6. [Commit](#) — save your work
 7. [Branches](#)
 8. [Compare & merge](#)
 9. [History](#)
 10. [Resolve merge conflicts](#)
 11. [Stash](#) — park work for later
 12. [Push, Pull, Fetch](#)
 13. [Azure DevOps cloud features](#)
 14. [Appearance: dark mode & colors](#)
 15. [Troubleshooting](#)
-

1. Connect to Azure DevOps

When the app opens without a connection you land on the **Connect** screen.

Fill in three things:

Field	What to enter
Organization	The name after <code>dev.azure.com/</code> in your browser — e.g. for <code>dev.azure.com/fabrikam</code> enter <code>fabrikam</code>
Project	The project name exactly as it appears in Azure DevOps
Personal access token	A PAT — see below

Creating a PAT (one time): in Azure DevOps click your avatar (top right) → **User settings** → **Personal access tokens** → **New Token**. Give it a name, pick your organization, and under **Scopes** choose **Code** → **Read & write** (read-only is enough for browsing, but cloning private repos, pushing, and completing pull requests need write). Copy the token and paste it into the app.

Your token is kept in an **encrypted session cookie on your machine** — it is never stored in the browser or sent anywhere except Azure DevOps.

Press **Connect**. The sidebar now shows the **Azure DevOps** section (Dashboard, Repositories, Branches, Compare branches, Pull requests).

Prefer to work without Azure? Use **Work with a local repository** below the form — pick any Git folder on your machine and skip to [Status](#).

Connecting later, and disconnecting

You don't have to connect right away — the two modes are independent:

- **+ Connect Azure DevOps** (bottom of the sidebar) — if you started with a local repository only, click this any time to open the Connect screen and add the Azure side. Both sections then live together in the sidebar, and cloning from [Repositories](#) becomes available.
- **Disconnect Azure** (bottom of the sidebar) — signs you out and forgets the token for this session. Your local repositories are untouched.
- **Close local repo** — deselects the current local repository (it stays in [Your repositories](#) for one-click reopening).

The connection lasts for your session (about 8 hours) — after that, just connect again with the same PAT until the token itself expires.


2. Clone a repository

1. In the sidebar under **Azure DevOps**, open **Repositories**.
2. Every repo in your project is listed. Click **Clone to local** on the one you want.
3. A dialog asks **where** to put it — click **Choose...** to browse your disk (you can jump between drives, go **Up**, or **Home**), then **Clone here**.
4. A **progress bar appears at the top** of the app while Git downloads (`Receiving objects...` 45%).
5. When it finishes, the repo **opens automatically** in the local workspace — you land on [Status](#), already wired to Azure as its `origin` .

You only ever clone a repo **once** — after that it stays in [Your repositories](#).

3. Your repositories


Everything you've cloned or opened is remembered. Switch repos any time with the **Current repository** dropdown at the top of the sidebar, or manage the full list via **+ Open another folder...**



- **Open** — makes it the current repo.
 - **VS Code** — opens that repo's folder in Visual Studio Code.
 - **X** — removes it from the list (the files on disk are *not* deleted).
 - **Open a folder** — add any existing Git repo from your machine using the built-in folder browser.
-

4. Status — your home screen

Whenever you open a repo you land here. It answers: *where am I, what's the state, and what should I do next?*



Top to bottom:

- **On branch** — shows the current branch. The dropdown **switches branches** right here (remote branches are listed too — picking one checks it out locally).
- **The 1-2-3 strip** — your workflow at a glance: **Change** → **Commit** → **Push**, with live counts. The highlighted step is your next move; completed steps show ✓. Each step is clickable.
- **The banner** — plain-language summary (green = safe, amber = needs attention, red = blocked).
- **Fetch / Pull / Push** — talk to Azure DevOps. The counter shows how many commits you're ahead ↑ / behind ↓.
- **Stash** — park uncommitted work safely ([details](#)).
- **Where's the issue?** — cards that point you at whatever needs doing, with a button straight to the fix.

Top-right: **Open in VS Code** and **Refresh**. The navbar also shows the current repo/branch and the [appearance controls](#).


5. Changes — review what you did

Sidebar → **Changes** (the badge shows how many files changed).

- Every changed file is listed with **green +added / red –removed** counts and a label (modified / new / deleted / renamed).
- **Click a file** to expand its diff — green lines were added, red removed.
- **Discard** throws away that file's changes (it asks first — this cannot be undone).
- Conflicted files show a link straight to the [conflict resolver](#).
- **Stage & commit** → takes you to the Commit screen.

6. Commit — save your work

Sidebar → **Commit**.



1. **Stage** the files that belong together (per file, or **Stage all**). Staged files are what the commit will contain; click any file to double-check its diff. **Unstage** moves it back.
2. Write a message. Keep the first line a short summary (the counter warns past 72 characters) — e.g. *"Add order receipts to payment service"*.
3. Press **Commit**.


Two safety nets for the last commit (only while it hasn't been pushed):

- **Undo last commit** — takes the commit apart but **keeps all its changes staged**, so nothing is lost. Great for "oops, wrong files".
- **Amend the last commit instead** (checkbox) — replaces the last commit with the current staged files + message. Great for "forgot one file" or a typo in the message.

After committing, the strip moves to **Push** — [share it](#).

7. Branches


Sidebar → **Branches**.



- **Create a branch** — type a name (e.g. `feature/my-change`) and press **Create**; you're switched onto it immediately.
- Each branch row shows its last commit, and ahead ↑ / behind ↓ its upstream.
- **Switch** — check out that branch. Branches marked **remote** exist on Azure but not on your machine yet — **Check out** creates your local copy.
- **Merge into current** — merges that branch into the one you're on. If the same lines changed on both sides you're taken to the [conflict resolver](#).
- **Delete** — removes a local branch (Git refuses if it has unmerged work).
- Expand a row (▸) to see the commits that branch adds over the main branch.

8. Compare & merge

Sidebar → **Compare & merge**. See exactly what one branch would bring into another **before** merging — the best way to avoid surprise conflicts.




1. Pick a **Base** (merge *into*) and a **Compare** (merge *from*) — ⇌ **Swap** flips them.
2. You get: how many commits ahead/behind, the common ancestor, the exact **commit list**, and every **file changed** with expandable diffs.
3. One click merges: **Merge compare into base** (the app switches to the base branch for you if needed). Conflicts route into the resolver.

If the compare branch has *nothing new* and is just behind, the app says so in plain words and offers ⇌ **Flip it** — setting up the catch-up merge that branch actually needs.

9. History


Sidebar → **History**.



- **Graph | List** — the graph draws real branch/merge lanes; List is a clean linear feed.
- **Show** — the current branch (default), any specific branch, or **All branches**.
- **Simplify merges** — hides merged-in side branches and tells the branch's own story (great for busy shared branches).
- **Click any commit** → a details panel slides in from the right: full message, author, branch tags, and **every file it changed** — click a file for its diff. Click other commits to flip through them; **Esc** closes.

10. Resolve merge conflicts

When a merge/pull/stash hits a conflict, **Resolve conflicts** appears in the sidebar with a red count, and everything routes you here.



For each conflicted file you see three panes:

- **Ours** — how it looks on *your* branch.
- **Theirs** — the incoming change.
- **Result** — an editor holding what will be saved.

Pick a starting point (**Take "ours"**, **Take "theirs"**, or edit by hand to combine both), make the Result read correctly, and remove every <<<<<< / ===== / >>>>>> marker (the counter tracks them). Press **Mark resolved**, repeat for each file, then finish with a normal [commit](#).

11. Stash — park work for later

On [Status](#), when you have uncommitted changes:

- **Stash N changes** — sets *everything* aside (new files included) and leaves a clean tree. Perfect when you must switch branches mid-work.
 - Each stash is listed with **Restore** (bring it back — conflicts route to the resolver) and **Delete**.
-

12. Push, Pull, Fetch

The toolbar on [Status](#):

Button	What it does
Fetch	Checks Azure for news (updates the ↑↓ counters; changes nothing locally)
Pull	Brings the upstream's commits into your branch (a conflict opens the resolver)
Push	Sends your commits to Azure. A brand-new branch is published automatically (sets its upstream)

Amber "behind" states are safe — pull first, then push.

13. Azure DevOps cloud features

These live in the sidebar's **Azure DevOps** section (after [connecting](#)) and work in the hosted web app too.

Dashboard

Pick a repo in the sidebar dropdown; the dashboard shows each branch's plain-language status vs the default branch — a divergence diagram and recent commits, with a traffic-light verdict.

Repositories

Every repo in the project, with default branch and links — plus **Clone to local** ([see cloning](#)).

Branches (cloud)

All branches on the server with ahead/behind counts and a verdict. **New PR** starts a pull request from any branch.

Compare branches (cloud)

Same idea as local [Compare & merge](#) but computed by Azure: pick base and target, see ahead/behind, common ancestor, and changed files. If the target is behind, the app warns you *before* you open a PR — that's where conflicts come from. **Open pull request** → carries your selection into the PR form.

Pull requests

Filter by **All / Created by me / Assigned to me** and by state. Open a PR to see its description, reviewers and their votes, and comment threads. On an active PR, **Complete this pull request** merges it on Azure: choose the strategy (merge / squash / rebase / semi-linear), optionally **delete the source branch**, and confirm. Policy blocks and conflicts are explained in plain language.


Merging branches *in the cloud* always goes through a pull request — that's the Azure DevOps way. For instant local merges use [Compare & merge](#).

14. Appearance: dark mode & colors

In the top navbar (desktop) or the menu drawer (mobile):

- 🌙 / 🌞 **toggle** — light or dark mode (follows your system setting by default).
- **Five color dots** — pick the app's accent color: Indigo, Violet, Teal, Rose, or Orange.

Both choices are remembered.



The ☐ **button** at the far left of the navbar collapses the sidebar to a slim icon rail — hover an icon for its name; click ☐ again to expand.

15. Troubleshooting

Problem	Fix
"Azure DevOps returned a sign-in page..." when connecting	Check the organization spelling, that the PAT hasn't expired and was created for <i>this</i> organization, and that no company policy (IP restrictions / Conditional Access) blocks the network you're on.
Clone/push fails with authentication error	Your PAT needs Code → Read & write scope. Create a new token and reconnect.
"Open in VS Code" does nothing	Install the <code>code</code> command: VS Code → <code>Ctrl/Cmd+Shift+P</code> → "Shell Command: Install 'code' command in PATH".
Commit fails asking who you are	Set your Git identity once: <code>git config --global user.name "Your Name"</code> and <code>git config --global user.email you@company.com</code> .
Windows: "Windows protected your PC"	Click More info → Run anyway (the installer isn't code-signed).
macOS: "cannot verify the developer"	Right-click the app → Open → Open (one time).
Undo/Amend button is disabled	The last commit is already pushed — rewriting shared history is blocked on purpose. Make a new commit instead.
A branch I see on Azure isn't in my local list	It appears under Branches marked remote — click Check out . If it's brand new, press Fetch first.