



Model Development Phase Template

Date	7 July 2024
Team ID	739894
Project Title	Predicting the Compressive Strength of Concrete
Maximum Marks	5 Marks

Feature Selection Report Template

In the forthcoming update, each feature will be accompanied by a brief description. Users will indicate whether it's selected or not, providing reasoning for their decision. This process will streamline decision-making and enhance transparency in feature selection.

Feature	Description	Selected (Yes/No)	Reasoning
Cement (kg/m³)	Amount of cement in the mix	Yes	Major contributor to the compressive strength.
Water Content	Amount of water in the mix (kg/m^3)	Yes	Influences the hydration process and strength.
Coarse Aggregate	Amount of coarse aggregate (kg/m^3)	Yes	Provides bulk and affects the concrete's strength. Provides bulk and structural integrity to the mix
Age	Age of concrete in days	Yes	Compressive strength increases over time. Strength increases with age;





		typically measured at 7, 28, and 90 days.
Amount of fine aggregate (kg/m^3)	Yes	Affects the workability and strength of concrete. Impacts workability and the overall mix composition.
Amount of superplasticizer in the mix (kg/m^3)	Yes	Improves workability and can enhance strength.
Amount of fly ash in the mix (kg/m^3)	Yes	Used as a supplementary cementitious material.
Amount of blast furnace slag (kg/m^3)	Yes	Improves durability and strength
Ratio of water to cement content	Yes	Crucial for determining workability and strength.
Temperature during curing (°C)	Yes	Affects the rate of strength gain.
Duration of mixing process (minutes)	Yes	Proper mixing ensures homogeneity.
Method used for curing (e.g., water curing)	Yes	Impacts the strength development.
	aggregate (kg/m^3) Amount of superplasticizer in the mix (kg/m^3) Amount of fly ash in the mix (kg/m^3) Amount of blast furnace slag (kg/m^3) Ratio of water to cement content Temperature during curing (°C) Duration of mixing process (minutes) Method used for curing (e.g.,	aggregate (kg/m^3) Amount of superplasticizer in the mix (kg/m^3) Amount of fly ash in the mix (kg/m^3) Amount of blast furnace slag (kg/m^3) Ratio of water to cement content Temperature during curing (°C) Duration of mixing process (minutes) Method used for curing (e.g., Yes





Chemical Admixture	Type and amount of chemical	Yes	Can significantly alter the properties of
S	admixtures used		concrete.