

## TABLE OF CONTENTS

| CONTENT                                         | Page No |
|-------------------------------------------------|---------|
| TABLE OF CONTENTS                               | 1-2     |
| ABSTRACT                                        | 3       |
|                                                 |         |
| CONTENT                                         | Page No |
| CHAPTER 1 - INTRODUCTION                        | 4       |
| 1.1 Overview                                    | 5       |
| 1.2 Project Objective & Scope                   | 6-7     |
| CHAPTER 2 -BACKGROUND AND LITERATURE SURVEY     | 8       |
| 2.1 Literature Survey                           | 8       |
| 2.2 Requirement Specification                   |         |
| 2.3 Feasibility Report                          |         |
| 2.4 Innovativeness and Usefulness               | 9       |
| 2.5 Market Potential and Competitive advantages |         |
| CHAPTER 3 - PROCESS MODEL                       | 10      |
| 3.1 Proposed Methodology                        |         |
| 3.2 Software Process Model                      |         |
| 3.3 Project Plan                                |         |
| 3.4 Project Estimation and Scheduling           |         |
| CHAPTER 4 - DESIGN                              | 18      |
| 4.1 Use case diagram                            |         |
| 4.2 Sequence Diagram                            |         |
| 4.3 Activity Diagram                            |         |
| 4.4 Class Diagram                               |         |
| 4.5 E-R Diagram                                 |         |
| 4.6 Data Flow Diagram                           |         |
| 4.7 Flow Chart                                  |         |
| 4.8 Algorithm                                   |         |
| CHAPTER 5 - TECHNICAL DETAILS                   | 28      |
| 5.1 Software Specification and details          |         |
| 5.2 Hardware requirements                       |         |
| CHAPTER 6 - IMPLEMENTATION                      | 32      |

|                                                       |           |
|-------------------------------------------------------|-----------|
| <b>CHAPTER 7 - TESTING &amp; RESULTS</b>              | <b>37</b> |
| <b>7.1 Testing Methods Used</b>                       |           |
| <b>7.2 Test Cases &amp; Results</b>                   |           |
| <b>CHAPTER 8 - SCREEN LAYOUTS</b>                     | <b>40</b> |
| <b>CHAPTER 9 - CONCLUSION AND FUTURE ENHANCEMENTS</b> | <b>46</b> |
| <b>CHAPTER 10 - REFERENCES</b>                        | <b>49</b> |
| <b>CHAPTER 11 - PUBLISHED PAPER WITH CERTIFICATE</b>  | <b>51</b> |

## **Abstract**

Label Blend is an AI-assisted synthetic dataset generation system designed to automate image annotation and dataset preparation for computer vision applications. The project

integrates Blender 3D, Python scripting, and YOLO segmentation techniques to generate realistic synthetic images along with automatic polygon annotations.

The system creates realistic virtual environments in Blender and produces labeled datasets without requiring extensive manual annotation. By using compositor-generated masks and automated polygon extraction, the project significantly reduces dataset preparation time and improves annotation consistency. The generated datasets can be directly used for training deep learning models such as YOLOv8 segmentation models.

The project is especially useful in agricultural AI applications like weed detection, object segmentation, and computer vision research where collecting and labeling real-world data is expensive and time-consuming. Label Blend provides a scalable, cost-effective, and innovative solution for generating large AI-ready datasets.

## **CHAPTER 1 – INTRODUCTION**

### **1.1 Overview**

Artificial Intelligence and Computer Vision systems require large amounts of annotated data for training machine learning models. Manual image annotation is one of the most time-consuming and expensive tasks in AI development. Label Blend is developed to automate this process using synthetic data generation techniques.

The project uses Blender 3D to create realistic environments and generate images automatically. Using Blender's compositor and Python scripts, segmentation masks are generated and converted into polygon annotations compatible with YOLO segmentation models.

This approach helps developers generate large datasets quickly while maintaining annotation accuracy and consistency. The project mainly focuses on reducing manual labor in dataset creation.

## Custom Description of Project with Aim

The proposed project “*Label-Blend Studio*” supports the broader sustainability initiative “*Innovating for Sustainability: Driving Smart Resource Conservation Practices in Domestic Appliances.*” The project aims to enable intelligent AI model development by generating reliable synthetic datasets that can be used to train computer vision systems for detecting inefficiencies, faults, or hazardous usage patterns in domestic appliances.

Using synthetic image generation, annotation automation, and segmentation techniques, the tool allows researchers and developers to train AI models without requiring large-scale real-world data collection. This reduces the dependency on electricity, processing power, time, and human effort typically involved in extensive manual dataset creation. By accelerating AI development cycles, the project indirectly contributes to **energy-efficient, safer, and smarter domestic technologies**.

The system can be integrated to train AI models for use cases such as identifying water or energy wastage points, detecting appliance overheating, monitoring improper usage, and optimizing smart automation workflows for home devices. It supports the design and deployment of eco-friendly technologies by allowing rapid AI prototyping using synthetic data.

## 1.2 Project Objective & Scope

### Objective

- To automate image annotation using synthetic data generation.
- To generate segmentation datasets for YOLO models.
- To reduce manual labeling effort and annotation cost.
- To improve dataset scalability for AI applications.
- To create realistic environments using Blender.

### Scope

- AI dataset generation
- Object segmentation
- Agricultural weed detection datasets
- Computer vision research

- Autonomous annotation systems
- Synthetic image generation for deep learning

## Problem Statement

Object detection and segmentation models such as YOLO, SSD, and Mask R-CNN rely heavily on accurately labeled datasets. In industries such as **autonomous vehicles, robotics, and precision agriculture**, capturing diverse training data in varied environments is extremely challenging. Lack of labeled images with real-world variations like lighting, rotation, scale, and background causes **low model performance and unreliable predictions**. Therefore, there is a critical need for a **system that generates synthetic, augmented images with accurate bounding box or segmentation labels**.

## Objectives of the Project

1. To develop a desktop-based application that automatically generates synthetic images using transparent cutout objects merged with randomized background environments.
2. To automate the process of bounding box and segmentation labeling in standard YOLO format to minimize human effort and time.
3. To implement data augmentation techniques such as random rotation, scaling, positioning, and lighting adjustments for improving dataset diversity.
4. To enable multi-class dataset creation for various AI/ML use cases such as object detection, instance segmentation, robotics, autonomous systems, and agricultural automation.
5. To reduce dataset generation time from hours/days to minutes using multiprocessing and parallel data processing techniques.
6. To provide a user-friendly interface allowing effortless loading of cutouts, setting parameters, managing workspaces, and exporting structured datasets.

7. To support scalability for academic research and industrial AI applications by enabling the generation of high-quality labeled datasets for supervised learning.
8. To improve AI model performance and reduce underfitting by overcoming data scarcity through synthetic dataset generation.
9. To integrate a Photoshop-like cutout creation module for improved usability and dataset customization.
10. To enhance the effectiveness of AI training workflows by delivering export-ready datasets compatible with leading deep learning frameworks such as YOLOv5, YOLOv8, SSD, and Mask R-CNN.

### **Objectives (continued)**

1. Develop an automated synthetic image generation and labeling application.
2. Implement augmentation and segmentation techniques to enhance dataset diversity.
3. Minimize manual work and dataset creation time using multiprocessing.
4. Support multi-class supervised learning dataset generation for AI models.
5. Improve AI model training accuracy by solving labeled data scarcity.

## **Vision**

To develop an automated synthetic image segmentation and labeling suite that assists in building AI models focused on enhancing sustainability, safety, and smart resource conservation in domestic appliances by overcoming data scarcity issues through efficient synthetic data generation

## **CHAPTER 2 - BACKGROUND AND LITERATURE SURVEY**

### **2.1 Literature Survey**

Many machine learning projects depend on manually annotated datasets. Existing annotation tools such as Labeling and CVAT require significant human effort. Recent advancements in synthetic data generation have shown that virtual environments can be used to generate training datasets automatically.

Research in Blender-based synthetic dataset generation demonstrates that synthetic images can improve model training efficiency while reducing annotation cost. YOLO segmentation models have also gained popularity for real-time object detection and segmentation tasks.

Label Blend combines synthetic image generation with automatic polygon annotation to create a fully automated dataset pipeline.

### **2.2 Requirement Specification**

#### **Functional Requirements**

- Generate realistic synthetic images
- Produce segmentation masks
- Convert masks into polygon annotations
- Export YOLO-compatible labels
- Support automated dataset generation

#### **Non-Functional Requirements**

- High processing efficiency
- Scalable dataset generation
- User-friendly workflow

- Reliable annotation accuracy

## **2.3 Feasibility Report**

### **Technical Feasibility**

The project is technically feasible using Blender, Python, OpenCV, and YOLO frameworks.

### **Economic Feasibility**

The project uses open-source tools, reducing development costs significantly.

### **Operational Feasibility**

The system can be easily integrated into AI dataset pipelines.

## **2.4 Innovativeness and Usefulness**

- Automatic polygon annotation generation
- Blender-based realistic synthetic datasets
- Reduced manual labeling effort
- Faster AI dataset preparation
- Useful for computer vision and agricultural AI systems

## **2.5 Market Potential and Competitive Advantages**

The demand for AI datasets is increasing rapidly in industries such as agriculture, robotics, autonomous systems, and surveillance. Label Blend offers advantages such as:

- Lower annotation cost
- Faster dataset generation
- Custom environment creation
- Improved scalability



## **CHAPTER 3- PROCESS MODEL**

### **3.1 Proposed Methodology**

- Create a realistic 3D environment in Blender.
- Generate synthetic images.
- Produce black and white segmentation masks.
- Extract polygons using Python and OpenCV.
- Convert annotations into YOLO segmentation format.
- Train YOLO models using generated datasets.

### **3.2 Software Process Model**

The project follows the Incremental Development Model:

- Requirement Analysis
- Design
- Development
- Testing
- Deployment

### **3.3 Project Plan**


- Research and analysis
- Blender environment setup
- Python automation development
- Annotation pipeline implementation
- YOLO integration
- Testing and validation

### **3.4 Project Estimation and Scheduling**

|          |        |
|----------|--------|
| Research | 1 Week |
|----------|--------|

|               |        |
|---------------|--------|
|               |        |
| Design        | 1 Week |
| Development   | 4 Week |
| Testing       | 1 Week |
| Documentation | 2 Week |

## Implementation Roadmap



## Users of the System

*Label-Blend Studio* is designed to serve a broad spectrum of users in the AI and computer vision domain, ranging from beginners to advanced researchers. The primary user categories include:

1. **AI/ML Engineers and Data Scientists**  
Professionals working on developing machine learning models for object detection, segmentation, and automation using tools like YOLO, SSD, or Mask R-CNN.
2. **Computer Vision Developers**  
Developer require labeled image datasets to train AI systems for robotics, automation, defect detection, and smart monitoring.
3. **Researchers & Academicians**  
Students and researchers working on AI/ML projects, sustainable innovation, and simulation-based machine learning requiring synthetic datasets.
4. **Industrial Automation Experts**  
Professionals building AI solutions for monitoring energy efficiency, appliance optimization, safety alerts, and smart home automation.
5. **Agricultural and Environmental Technology Developers**  
Developer require domain-specific datasets, such as weed detection, crop monitoring, or anomaly tracking, where real-world data is scarce.
6. **Prototype Developers and Innovators**  
AI tool creators and startups focused on rapid prototyping and testing in the absence of large real-world datasets.

## Functional Requirements

### User Interface & Workspace

- Provide an intuitive GUI using tabs and workspace management.
- Allow users to work on multiple projects simultaneously.
- Support loading cutout images and background images effortlessly.

## **Synthetic Dataset Generation**

- Automatically merge cutouts over randomized backgrounds.
- Apply augmentation such as rotation, scaling, position shifting, and lighting variations.
- Support both single-object and multi-object scenes.

## **Automatic Label Generation**

- Generate annotations in YOLO format (.txt files).
- Provide support for bounding box and polygon segmentation formats.

## **Cutout Creation**

- Include an integrated utility similar to Photoshop for cutout creation.
- Allow manual or automatic background removal.

## **Parameter Configuration**

- Allow users to define number of images, resolution, image ID start number, and augmentation settings.

## Performance Optimization

- Utilize multiprocessing and threading for high-speed dataset generation.
- Enable parallel processing for large batch image synthesis.

## Export System

- Store output in a structured folder format (**images/** and **labels/**).
- Allow dataset export in formats compatible with YOLO v5/v8, SSD, and RCNN framework

## Non-Functional Requirements

### 1. Performance Requirements

- a. The system should be capable of generating at least *100+ synthetic annotated images per minute* depending on system hardware.
- b. Multiprocessing and threading should be utilized to minimize latency and ensure faster dataset generation.
- c. The application must handle high-resolution images (e.g., 1080p or 4K) efficiently without significant lag.

### 2. Usability Requirements

- a. The interface must be intuitive and easy to navigate by users with basic computer knowledge.
- b. Clear buttons, tooltips, and labeling should simplify workflow management.
- c. Minimal number of steps (ideally < 5 clicks) should be required to complete dataset generation.

### 3. Reliability and Stability

- a. The system should consistently generate correct annotations without accuracy loss.

- b. If any process fails, the system should display an appropriate error message without crashing.
- c. The software must handle 1000+ synthetic images generation per session without performance breakdown.

#### **4. Scalability**

- a. The tool should support the extension of features (e.g., new annotation formats, augmentation methods).
- b. It should allow integration with external AI tools and dataset pipelines.
- c. Capable of handling multiple open workspaces simultaneously without significant CPU stress.

#### **5. Maintainability**

- a. The application should be developed using modular and object-oriented programming principles.
- b. Codebase must be well documented to enable future enhancements.
- c. Configuration files (e.g., class labels, template settings) should be editable without code modifications.

#### **6. Compatibility**

- a. The system must be compatible with Windows 10/11 and should work on Python 3.10+.
- b. The exported dataset should be directly usable in frameworks like YOLO, TensorFlow, PyTorch, and OpenCV-based systems.
- c. Compatible with multiple image formats such as PNG, JPG, and JPEG.

#### **7. Security**

- a. The system should not allow unauthorized modification of internal code or dataset structures.

- b. Personal or proprietary images processed by users must not be uploaded externally, ensuring *local data privacy*.
- c. File paths and outputs should be secured from accidental overwrite.

## 8. Resource Optimization

- a. The software should consume minimal RAM and CPU when idle.
- b. Background processes should automatically close after task completion.
- c. Efficient memory handling must be ensured to prevent system freeze or crash during large-scale generation.

### User Interface Priorities (Front end and Back end technologies)

The system must prioritize a **highly responsive, visually intuitive interface** that allows users to easily load cutouts, backgrounds, configure parameters, and monitor synthetic image generation in real time. The UI should deliver **clear feedback, progress tracking, and seamless workspace navigation**.

On the back end, the system must ensure **efficient image processing, high-speed augmentation, multiprocessing support, accurate annotation generation, and stable project handling**. It should maintain reliability even under large batch operations.

### Front End Technologies

- PySide6 (Qt for Python) – Core GUI framework for building the Responsive tool.
- Qt Design Studio– Visual UI layout tool for designing windows, buttons, forms, and layout elements.
- QLabel / QGraphicsView – Used to display images, previews, and real-time visualization of synthetic data generation.
- OpenCV UI Integration – Enables interactive visualization of augmentation (rotation, scaling, lighting changes).
- Threading via QThread – Prevents UI freeze during heavy image processing tasks.
- Custom Icons and Stylesheets (Qt Styles) – Enhances user experience through professional UI design.

- Modal Dialogs & Progress Bars – Confirm actions, show generation progress, and improve usability.

## Back End Technologies

- Python 3.10+ – Core programming language.
- OpenCV (cv2) – Image manipulation, transformations, augmentation, and merging operations.
- Pillow (PIL) – PNG cutout management and transparency handling.
- NumPy – Array calculations, transformation matrices, and random vector generation.
- Multiprocessing & Threading Libraries ([multiprocessing](#), [threading](#)) – Accelerate bulk dataset generation.
- OS and File Handling Modules – Manage folder structure ([images/](#), [labels/](#)).
- OOP Design Paradigm – Supports multiple dataset workspaces and modular workflow.
- JSON / YAML Support – Save user configurations, class mappings, and workspace settings.



## CHAPTER 4 - DESIGN


### 4.1 Use Case Diagram

. Actors:

- User
- Blender Engine
- Annotation System
- YOLO Training Module

Use Cases:

- Generate Images
- Create Masks
- Extract Polygons
- Export Dataset
- Train Model



## 4.2 Sequence Diagram

User → Blender → Mask Generator → Python Annotation Module → YOLO Dataset Export

[illegible]

```

Starting training for 50 epochs...
Epoch GPU_mem box_loss cls_loss off_loss Instances Size
1/50 86 1.8661 3.75 2.386 31 1280x1805 47.67 [14:45:00-00, 18:45:00-00]
Class Images Instances ResP F H
mAP50 mAP50-95 0.5 1.73 [00:20:00-00, 00:20:00-00]
CLAS Images Instances ResP F H
mAP50 mAP50-95 0.5 1.73 [00:20:00-00, 00:20:00-00]
CLAS Images Instances ResP F H
mAP50 mAP50-95 1.0005 3.75 [00:20:00-00, 00:20:00-00]
CLAS Images Instances ResP F H
mAP50 mAP50-95 1.0005 3.75 [00:20:00-00, 00:20:00-00]
all 40 49 0.00551 0.429 0.111 0.0143
Epoch GPU_mem box_loss cls_loss off_loss Instances Size
2/50 86 1.735 3.375 2.338 32 1280x1805 47.67 [15:03:00-00, 18:45:00-00]
Class Images Instances ResP F H
mAP50 mAP50-95 0.5 1.73 [00:20:00-00, 00:20:00-00]
CLAS Images Instances ResP F H
mAP50 mAP50-95 0.5 1.73 [00:20:00-00, 00:20:00-00]
CLAS Images Instances ResP F H
mAP50 mAP50-95 0.75 3.75 [00:20:00-00, 00:20:00-00]
CLAS Images Instances ResP F H
mAP50 mAP50-95 1.0005 3.75 [00:20:00-00, 00:20:00-00]
all 40 49 0.00551 0.429 0.111 0.0143

```

The *Label-Blend Studio* generates various reports throughout the dataset creation process to help users analyze performance, validate annotation quality, export usage summaries, and support academic or industrial documentation. These reports enable better dataset monitoring, troubleshooting, and AI training evaluation.

- Number of synthetic images generated
- Number of labels created (per class)
- Total time taken for dataset creation
- Resolution and augmentation details
- File path of exported dataset

“500 synthetic images and 500 YOLO annotations successfully generated in 52 seconds.”

## **2. Class Distribution Report**

- List of object classes used
- Number of images each class appears in
- Balancing insights (helps prevent class imbalance)

## **3. Augmentation Summary Report**

- Types of augmentations applied (scaling, rotation, lighting, placement)
- Transformation ranges used
- Percentage of images augmented per technique

## **4. Performance Report**

- Time taken per batch or per image generation
- CPU utilization insights
- Multiprocessing/threading performance efficiency
- System requirements recommendation

## **6. Export Compatibility Report**

- Names of supported AI model frameworks
- Annotation format used (YOLO v5/v8, segmentation format)
- File structure validation (images/ and labels/ folders)

## **7. Project Summary Report**

- Dataset version and workspace name
- Total objects placed
- Auto-generated metadata for documentation and research use
- Can be attached in thesis/PPT or uploaded during AI model training

### **4.3 Activity Diagram**

Activities include:

- Environment creation
- Rendering
- Mask generation
- Polygon extraction
- Dataset export

### **4.4 Class Diagram**

Classes:

- Blender Renderer
- Mask Processor
- Polygon Extractor
- Dataset Exporter
- YOLO Trainer

### **4.5 E-R Diagram**

Entities:

- Image
- Annotation
- Polygon
- Dataset

Relationships:

- Image contains Annotation

- Annotation contains Polygon

## 4.6 Data Flow Diagram

Input → Blender Scene → Render Engine → Mask Generator → Annotation Processor → Dataset Output

## 4.7 Flow Chart

Start → Create Scene → Render Image → Generate Mask → Extract Polygon → Save YOLO Labels → End

LabelBlend is developed as an automated synthetic dataset generation and annotation system for Artificial Intelligence and Computer Vision applications. The system is useful in multiple domains where large annotated datasets are required for training deep learning models.

The major applications of LabelBlend are as follows:

- Training object detection and segmentation models such as YOLOv5, YOLOv8, SSD, Faster R-CNN, and Mask R-CNN.
- Generating synthetic datasets for deep learning and computer vision research.
- Reducing manual annotation effort in AI dataset preparation.
- Creating datasets for agricultural AI applications such as weed detection and crop monitoring.
- Supporting autonomous systems and robotics applications.
- Assisting in academic and industrial AI/ML research projects.
- Generating customized datasets for industrial automation systems.
- Creating training datasets for object detection, instance segmentation, and image recognition tasks.

The system provides a scalable and cost-effective solution for generating high-quality annotated datasets with minimal human intervention.

## Working Procedure of the System

The LabelBlend system follows an automated workflow for synthetic image generation and annotation.

## **Step 1: Loading Object Images**

The user first loads transparent object cutout images along with their corresponding class labels. These cutout images represent target objects that need to be placed in synthetic scenes.

## **Step 2: Adding Background Images**

Background images are added to simulate realistic environments. These backgrounds help improve the diversity and realism of the generated dataset.

## **Step 3: Parameter Configuration**

The user configures different generation parameters such as:

### **a) Number of Images to Generate**

Defines the total number of synthetic images to be created.

### **b) Minimum and Maximum Object Size**

Controls the scaling range of objects placed in generated images.

### **c) Starting Image Number**

Specifies the starting index for image naming and dataset organization.

## **Step 4: Dataset Generation**

After configuring parameters, the system automatically:

- Places objects randomly
- Applies scaling and rotation
- Generates synthetic images
- Creates annotations
- Saves output files

## **Step 5: Output Generation**

The generated dataset is stored in separate directories:

- output/images/ → Contains generated images
- output/labels/ → Contains YOLO annotation files

The output dataset can be directly used for AI model training.

## **Dataset Generation Features**

The LabelBlend system includes several advanced features to improve dataset quality and realism.

### **Random Object Transformation**

Objects are automatically:

- Resized
- Rotated
- Positioned randomly

This increases dataset diversity and improves model generalization.

### **Automatic Annotation Generation**

The system automatically generates YOLO-compatible annotations without requiring manual labeling.

The generated annotations contain:

- Object class ID
- Bounding box coordinates
- Normalized coordinate values

### **YOLO-Compatible Output**

The generated datasets are fully compatible with:

- YOLOv5
- YOLOv8
- YOLO segmentation models
- Other object detection frameworks

This allows direct integration into deep learning training pipelines.



## Installation and Setup

### System Requirements

The following software requirements are necessary for running the LabelBlend system:

| Component            | Requirement           |
|----------------------|-----------------------|
| Programming Language | Python 3.10 or higher |
| Environment Manager  | pipenv                |
| Operating System     | Windows/Linux         |
| Additional Libraries | OpenCV, NumPy, Pillow |

### Setup Procedure

#### Step 1: Clone the Repository

Download the project repository to the local system.

```
git clone https://github.com/yourusername/LabelBlend.git
```

#### Step 2: Open Project Directory

```
cd LabelBlend
```

#### Step 3: Install pipenv

Install the Python virtual environment manager.

```
pip install pipenv
```

#### Step 4: Install Project Dependencies

```
pipenv install
```

#### Step 5: Activate Virtual Environment

```
pipenv shell
```

## **Step 6: Run the Application**

```
python main.py
```

After execution, the graphical interface of LabelBlend starts successfully.

## **Advantages of LabelBlend**

The major advantages of the proposed system are:

- Reduces manual annotation cost
- Faster dataset generation
- High scalability
- Improved annotation consistency
- Supports AI and deep learning workflows
- Easy integration with YOLO frameworks
- Generates customized synthetic datasets
- Useful for research and industrial applications

## **Future Scope**

The future scope of LabelBlend includes:

- Real-time synthetic data generation
- AI-assisted scene generation
- Multi-class segmentation support
- Cloud-based dataset generation
- Integration with advanced AI frameworks
- Real-time robotics applications
- Automatic environment randomization

## **Contribution and Development**

The project can be further improved through:

- Feature enhancements
- Optimization techniques
- Advanced rendering support
- Better annotation algorithms
- Community contributions and testing

Feedback and suggestions can help improve system performance and usability.

## **License**

This project is developed for educational and research purposes. The software architecture and implementation can be extended for commercial and industrial AI applications.

## **4.8 Algorithm**

### **Polygon Extraction Algorithm**

1. Load segmentation mask image.
2. Convert image to binary format.
3. Detect contours using OpenCV.
4. Extract polygon coordinates.
5. Normalize coordinates.
6. Save in YOLO segmentation format.

## **CHAPTER 5- TECHNICAL DETAILS**

| Software              | Purpose                    |
|-----------------------|----------------------------|
| Python                | Automation scripting       |
| Open CV               | Polygon extraction         |
| Yolo V8 and SAM Model | Model training             |
| NumPy                 | Numerical processing       |
| Vs code               | Development environment    |
| Blender 3D            | Synthetic image generation |

## 5.2 Hardware Requirements

| Component | Specification          |
|-----------|------------------------|
| Processor | Intel i5 or higher     |
| RAM       | 8GB minimum            |
| GPU       | NVIDIA GPU recommended |
| Storage   | 10 GB free space       |

### Proposed System

The proposed system, **Label-Blend Studio**, is a desktop-based synthetic image generation and labeling suite designed to overcome the limitations of manual dataset collection and annotation in computer vision projects. Traditional dataset preparation involves capturing

real-world images and manually annotating each instance, which is highly time-consuming, labor-intensive, and prone to inconsistency. The proposed system automates this process by generating synthetic images using pre-segmented cutout objects intelligently placed into randomized background environments.

It enables users to automatically apply augmentation techniques such as **rotation, scaling, lighting variation, and object repositioning** to create highly diverse datasets suitable for supervised learning. The system incorporates **automatic label generation in YOLO bounding-box and polygon-based segmentation formats**, eliminating the need for manual annotation. The dataset produced is ready to be used for training AI models like **YOLOv5, YOLOv8, SSD, Faster R-CNN, and segmentation networks such as Mask R-CNN**.

### System Architecture / Working Model Description

The working model of *Label-Blend Studio* is based on a modular, object-oriented architecture, divided into four major components: Input Module, Augmentation Engine, Annotation Generator, and Export System.

First, users load cutout images (with class labels) and background images through the GUI interface, which is built using PySide6. The input manager validates formats and initializes workspace parameters such as number of images, size range, and augmentation settings.

The Augmentation Engine performs automated synthetic image generation using OpenCV, Pillow, and NumPy, applying randomized rotation, scaling, transformation vectors, lighting effects, and placement positioning. Multiprocessing ensures high-speed parallel generation.

The Annotation Generator computes bounding box and segmentation coordinates and exports corresponding **.txt** files in YOLO-compatible format, maintaining synchronization with generated images.

Finally, the Export System structures the output into folders (**images/**, **labels/**) and generates a dataset summary report. Multiple workspaces allow users to generate different datasets simultaneously.

The architecture ensures real-time progress monitoring, error handling, efficient processing, and scalability for future integration of advanced AI-based annotation methods. The tool operates offline, preserving data privacy and supporting sustainable development through reduced resource usage.

### Future Scope

In future versions, *Label-Blend Studio* can integrate advanced Generative AI models such as GANs for automated object and environment creation, reducing dependency on pre-made cutouts. Cloud based deployment may enable collaborative dataset generation and integration with ML Ops pipelines. The tool can be extended to support multiple

annotation formats like COCO and Pascal VOC, alongside real-time AI model training and accuracy evaluation. It may also incorporate adaptive augmentation based on model feedback. Additionally, the system can be used in smart appliance monitoring and sustainability-driven applications, enabling predictive maintenance and energy-efficient AI solutions.

Use-Case Example- The project can be used by a developer that is facing the data scarcity problem for his ai model that is used to detect farming related objects like, weed, grass-type, or animal breed detections etc.

| Challenges                                                                                                                     | Solutions                                                                                                                                                     |
|--------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Data Diversity &amp; Quality Issues</b> – Breed images vary in <b>lighting, pose, environment</b> → impacts model accuracy. | Deploy <b>Label Blend Studio</b> for <b>synthetic dataset generation, data augmentation, and auto-labeling</b> to ensure high-quality, diverse training data. |
| <b>Adoption Barriers for Field Workers (FLWs)</b> – Limited <b>technical literacy &amp; low connectivity</b> in rural areas.   | Build <b>offline-first mobile app</b> with <b>intuitive UI/UX, guided image capture, and automated feedback</b> for easy adoption                             |
| <b>Model Accuracy at Scale</b> – Risk of <b>misclassification</b> in <b>crossbred variations</b> .                             | Implement <b>continuous model retraining</b> with <b>real + synthetic datasets, active learning pipelines, and computer vision model optimization</b>         |

## Conclusion

The proposed system *Label-Blend Studio* successfully addresses the major challenge of data scarcity and manual annotation in computer vision by providing an automated synthetic image generation and labeling solution. It enables AI practitioners, researchers, and developers to rapidly generate high-quality, multi-class training datasets using augmentation and segmentation techniques, significantly reducing time, cost, and manual effort. With its user-friendly interface, multiprocessing support, and export-ready annotation formats, the tool accelerates AI model development and enhances prediction accuracy. Aligned with sustainability objectives, it promotes efficient resource

utilization, making it a valuable innovation for both academic research and industrial AI application

The implementation phase of Label Blend focused on developing a complete automated pipeline for synthetic dataset generation, segmentation mask creation, polygon extraction, and YOLO-compatible annotation export. The implementation integrates Blender 3D, Python automation, OpenCV image processing, and YOLOv8 segmentation training.

The system architecture was divided into multiple interconnected modules to maintain modularity, scalability, and efficient processing.

## CHAPTER 6 - IMPLEMENTATION

### 6.1 Blender Environment Development

The first stage of implementation involved creating realistic 3D environments in Blender. Objects such as weeds, plants, ground surfaces, stones, and environmental assets were placed in virtual scenes to simulate real-world agricultural conditions.

Different lighting conditions, camera angles, and object placements were used to increase dataset diversity. Randomization techniques were applied to:

- Object rotation
- Object scaling
- Camera position
- Light intensity
- Background textures

This helped generate robust datasets capable of improving model generalization.

The Blender Python API (bpy) was used extensively to automate scene generation and rendering.

#### Example Tasks Automated in Blender

- Automatic object spawning
- Scene randomization
- Camera movement
- Batch rendering
- Mask generation
- Output management

## 6.2 Automatic Image Rendering

The rendering module was developed using Blender's scripting interface. Python scripts controlled the rendering process and generated thousands of synthetic images automatically.

The rendering pipeline performed:

1. Scene setup
2. Camera positioning
3. Object placement
4. Lighting adjustments
5. Image rendering
6. File export

Images were exported in PNG format to preserve quality and transparency information.

### Rendering Workflow

- Blender scene loads
- Objects randomized
- Camera parameters updated
- Image rendered
- Image stored in dataset directory

## 6.3 Segmentation Mask Generation

To create segmentation datasets, black-and-white masks were generated using Blender's compositor system.

Each target object was assigned a unique material or object index. During rendering:

- Target objects appeared in white color
- Background appeared in black color

These masks acted as segmentation references for polygon extraction.

### Advantages of Using Masks

- Precise object boundaries
- Noise-free annotations
- Faster dataset preparation
- Consistent labeling

The masks were saved automatically alongside rendered images.



## 6.4 Python-Based Polygon Extraction

After mask generation, Python scripts using OpenCV were developed to extract object contours and convert them into polygon coordinates.

The processing pipeline included:

1. Loading mask image
2. Converting image to grayscale
3. Thresholding binary regions
4. Detecting contours
5. Extracting polygon points
6. Normalizing coordinates
7. Exporting YOLO segmentation labels

### OpenCV Functions Used

- `cv2.imread()`
- `cv2.threshold()`
- `cv2.findContours()`
- `cv2.approxPolyDP()`

The contour detection algorithm identified object boundaries accurately and converted them into polygonal representations.

## 6.5 YOLO Segmentation Label Generation

The extracted polygon coordinates were converted into YOLOv8 segmentation format.

### YOLO Segmentation Format

Each annotation file contains:

- Class ID
- Normalized polygon coordinates

### Example Format

0 0.45 0.32 0.48 0.35 0.52 0.40 ...

Where:

- 0 represents class ID
- Remaining values represent normalized polygon points

The generated labels were saved as .txt files corresponding to each image.

## 6.6 Dataset Organization

The dataset was organized into:

- Training images
- Validation images
- Segmentation labels

### Dataset Structure

```
dataset/
├── images/
│   ├── train/
│   └── val/
└── labels/
    ├── train/
    └── val/
```

This structure ensured direct compatibility with YOLOv8 training pipelines.

## 6.7 YOLOv8 Model Training

The generated dataset was used to train YOLOv8 segmentation models.

### Training Process

1. Dataset configuration setup
2. Model initialization
3. Training execution
4. Validation
5. Performance evaluation

## Training Parameters

- Epochs: 100
- Batch Size: 8
- Image Size: 640×640
- Optimizer: SGD/Adam

The trained model successfully detected and segmented objects from test images.

| Technology | Purpose                        |
|------------|--------------------------------|
| Blender 3D | Synthetic environment creation |
| Python     | Automation and scripting       |
| OpenCV     | Image processing               |
| YOLOv8     | Segmentation training          |
| NumPy      | Numerical operations           |
| VS Code    | Development environment        |

## CHAPTER 7 - TESTING & RESULTS

Testing was performed to verify the correctness, efficiency, and reliability of each module in the system.

## **7.1 Testing Methods Used**

### **Functional Testing**

Functional testing verified whether all modules performed according to system requirements.

#### **Tested Functionalities**

- Automatic rendering
- Mask generation
- Polygon extraction
- YOLO annotation export
- Dataset organization

Each module was tested independently before integration.

### **Performance Testing**

Performance testing evaluated:

- Rendering speed
- Annotation generation speed
- Processing efficiency
- Memory utilization

The system successfully processed large datasets without major performance issues.

### **Dataset Validation**

Generated annotations were manually verified to ensure:

- Correct object boundaries
- Accurate polygon generation
- Proper class labeling

Validation confirmed high annotation consistency.

### **Annotation Accuracy Testing**

Polygon outputs were compared with segmentation masks to measure annotation precision.

Metrics evaluated:

- Boundary accuracy
- Coordinate consistency
- Polygon completeness

## 7.2 Test Cases & Results

| Test Case            | Objective                    | Expected Result                      | Actual Result                   | Status |
|----------------------|------------------------------|--------------------------------------|---------------------------------|--------|
| Image Rendering      | Verify rendering process     | Synthetic images generated correctly | Images generated successfully   | Passed |
| Scene Randomization  | Verify object variation      | Different scene outputs              | Randomized scenes produced      | Passed |
| Mask Generation      | Verify segmentation masks    | Accurate black-white masks           | Correct masks generated         | Passed |
| Contour Detection    | Detect object boundaries     | Correct contour extraction           | Accurate contours detected      | Passed |
| Polygon Conversion   | Convert contours to polygons | Valid polygon coordinates            | Coordinates generated correctly | Passed |
| YOLO Label Export    | Verify annotation format     | YOLO-compatible labels               | Proper labels exported          | Passed |
| Dataset Organization | Verify folder structure      | Correct train/validation folders     | Structure maintained            | Passed |
| YOLO Training        | Verify model compatibility   | Successful model training            | Training completed successfully | Passed |

## 7.3 Results Obtained

The project successfully generated:

- Synthetic datasets
- Segmentation masks
- Polygon annotations
- YOLO-compatible labels

The trained YOLOv8 model demonstrated accurate segmentation performance on generated datasets.

## **Key Achievements**


- Reduced manual annotation effort
- Improved dataset scalability
- Faster dataset generation
- Accurate polygon extraction
- Successful AI model training

## **CHAPTER 8 - SCREEN LAYOUTS**

This chapter contains screenshots demonstrating different stages of the system workflow.

### **Project Images**


Main Window



By label blend now we can create multi-class dataset with bounding box or segmentation annotation for AI/ML pipelines in minutes or even seconds

Inbuilt Image Editor

Main Window



Bounding Box

Segmentation






Image Selector



Generated Labelled Dataset






## 8.1 Blender Environment

Include screenshots showing:


- 3D scene setup
- Object placement
- Camera configuration
- Lighting setup



## 8.2 Generated Synthetic Images

Include:


- Rendered dataset images
- Different camera angles
- Randomized environments



### 8.3 Segmentation Masks

Include:

- Black-and-white masks
- Object-highlighted outputs
- Multiple segmentation examples



## 8.4 Polygon Annotation Output

Include:

- Contour visualization
- Polygon coordinate outputs
- Overlay annotations



## 8.5 YOLO Training Results

Include:

- Training graphs
- Accuracy metrics
- Loss curves
- Validation outputs


```
starting training for 50 epochs...
Epoch  GPU_mem  box_loss  cls_loss  dfl_loss  Instances  Size
1/50    0G        1.863    3.75     2.386     31         1280: 100%|██████████| 47/47 [14:43<00:00, 18.
WARNING NMS time limit 1.300s exceeded
Class   Images Instances  Box(P)  R    mAP50  mAP50-95): 0%|██████████| 0/3 [00:00<?W
WARNING NMS time limit 1.300s exceeded
Class   Images Instances  Box(P)  R    mAP50  mAP50-95): 33%|██████████| 1/3 [00:20<0W
WARNING NMS time limit 1.300s exceeded
Class   Images Instances  Box(P)  R    mAP50  mAP50-95): 67%|██████████| 2/3 [00:37<0W
WARNING NMS time limit 0.900s exceeded
Class   Images Instances  Box(P)  R    mAP50  mAP50-95): 100%|██████████| 3/3 [00:45<0
all      40         49     0.00351 0.429 0.111  0.0343

Epoch  GPU_mem  box_loss  cls_loss  dfl_loss  Instances  Size
2/50    0G        1.735    3.175    2.238     32         1280: 100%|██████████| 47/47 [15:03<00:00, 19.
WARNING NMS time limit 1.300s exceeded
Class   Images Instances  Box(P)  R    mAP50  mAP50-95): 0%|██████████| 0/3 [00:00<?W
WARNING NMS time limit 1.300s exceeded
Class   Images Instances  Box(P)  R    mAP50  mAP50-95): 33%|██████████| 1/3 [00:15<0W
WARNING NMS time limit 1.300s exceeded
Class   Images Instances  Box(P)  R    mAP50  mAP50-95): 67%|██████████| 2/3 [00:31<0W
WARNING NMS time limit 0.900s exceeded
Class   Images Instances  Box(P)  R    mAP50  mAP50-95): 100%|██████████| 3/3 [00:39<0
```



## 8.6 Detection Output

Include:



- Segmentation prediction images
- Bounding polygons
- Real-time detection results

## **CHAPTER 9 - CONCLUSION AND FUTURE ENHANCEMENTS**

### **9.1 Conclusion**

LabelBlend successfully demonstrates an automated approach for synthetic dataset generation and segmentation annotation using Blender and Artificial Intelligence techniques.

The project effectively reduces the dependency on manual annotation by automatically generating segmentation masks and converting them into YOLO-compatible polygon labels. The integration of Blender, Python, OpenCV, and YOLOv8 created a scalable and efficient AI dataset generation pipeline.

The generated synthetic datasets proved suitable for training deep learning segmentation models and can significantly reduce time, labor, and cost involved in computer vision dataset preparation.

The project also demonstrates the practical application of synthetic data generation in agriculture, AI research, robotics, and autonomous systems.

### **9.2 Future Enhancements**

The project can be enhanced further in multiple directions to improve scalability, realism, and automation.

#### **Real-Time Synthetic Dataset Generation**

Future systems can generate datasets dynamically during model training.

#### **Multi-Object Annotation Support**

Support for multiple object classes and simultaneous annotations can be added.

#### **AI-Assisted Scene Randomization**

Artificial Intelligence can automatically create optimized scenes for better model training diversity.

## Cloud-Based Dataset Pipeline

Cloud integration can allow distributed rendering and annotation generation.

## Integration with Additional AI Frameworks

Future versions may support:

- TensorFlow
- Detectron2
- MM Detection
- SAM (Segment Anything Model)

## Physics-Based Environment Simulation

Realistic weather, lighting, and environmental effects can improve dataset realism.

## Real-Time Detection Integration

The trained model can be integrated into:

- Agricultural robots
- Smart drones
- Autonomous systems



## CHAPTER 10 - REFERENCES


1. Blender Foundation. *Blender Official Documentation*.  
Available: <https://docs.blender.org/>
2. Ultralytics. *YOLOv8 Documentation*.  
Available: <https://docs.ultralytics.com/>
3. OpenCV Team. *OpenCV Documentation*.  
Available: <https://docs.opencv.org/>
4. Python Software Foundation. *Python Documentation*.  
Available: <https://docs.python.org/>
5. Goodfellow, Ian, et al. *Deep Learning*. MIT Press.
6. Research papers on:
  - a. Synthetic dataset generation
  - b. Computer vision
  - c. Object segmentation
  - d. AI-based annotation systems
7. Journals:
  - a. IEEE Transactions on Pattern Analysis
  - b. International Journal of Computer Vision
  - c. Machine Learning Research Journals

## Additional References

1. **Natyashastra – Hand Gestures and Expressions**  
Bharata Muni. *Natyashastra English Translation*.  
Available at: <https://archive.org/details/NatyaShastraEnglishTranslation>
2. **IEEE Xplore – Vision-Based Hand Gesture Recognition**  
IEEE Research Publications on Gesture Recognition and Computer Vision.  
Available at: <https://ieeexplore.ieee.org/>
3. **Mudra Library – Open Source Mudra Dataset**  
Kaggle Dataset Repository for Hand Gesture and Mudra Datasets.  
  
Available at: <https://www.kaggle.com/datasets>
4. **Springer – Human Action and Gesture Recognition using Deep Learning**  
Springer Journal on Artificial Intelligence and Gesture Recognition Research.  
  
Available at: <https://link.springer.com/journal/42979>
5. **IGNCA – Digital Repository of Mudras**  
Indira Gandhi National Centre for the Arts (IGNCA).  
Digital archive of Indian classical mudras and cultural hand gestures.  
  
Available at: <http://ignca.gov.in/>
6. **ResearchGate – Deep Learning for Gesture and Pose Recognition**  
  
Research papers and publications related to gesture recognition and pose estimation.  
Available at: <https://www.researchgate.net/>
7. OpenCV Team.  
*OpenCV Documentation*.  
Available at: <https://docs.opencv.org/>
8. Ultralytics.  
*YOLOv8 Documentation*.  
Available at: <https://docs.ultralytics.com/>
9. Python Software Foundation.  
*Python Official Documentation*.  
Available at: <https://docs.python.org/>
10. Blender Foundation.  
*Blender Official Documentation*.  
Available at: <https://docs.blender.org/>




## CHAPTER 11:- PUBLISHED PAPER WITH CERTIFICATE



### Project Demo Link:

<https://youtu.be/Pplf59qdIj4>



**Project Inference link:**  
**<https://youtu.be/TtHNoEp-X44>**