Detection of Alphanumeric Handwritten Values using Fuzzy Logic

INT3141 – Soft Computing Techniques | Project Submission (Intermediate)

Manipal University Jaipur, Department of Information Technology, B.Tech IT, V Sem, 2026-27

Team members: <Name 1 (Reg. No.)>, <Name 2 (Reg. No.)>, <Name 3 (Reg. No.)>

Course coordinator: Dr. Sulabh Bansal

Code repository: <GitHub link>

1. Introduction

Handwritten character recognition is one of the application areas named in the course hand-out. Handwriting is imprecise: the same letter written twice never looks identical, and different letters (O/0, S/5, I/1) can look alike. Such imprecision cannot be handled well by crisp yes/no rules, which is exactly the situation fuzzy logic was designed for (CO2). In this project we build a system that watches a live camera feed (laptop or USB camera), finds handwritten characters, and recognises each of them with a fuzzy rule base. For every character the system also reports how reliable the reading is, computed by a second small fuzzy controller.

Course outcomes addressed: INT3141.2 (apply fuzzy logic and reasoning) and INT3141.5 (develop and test a soft computing technique on a real-life problem).

2. Formal Problem Description

2.1 Input

A video frame is a function $I : \{0,\ldots,H-1\} \times \{0,\ldots,W-1\} \rightarrow \{0,\ldots,255\}^3$ (colour image, H×W pixels; 480×640 for the laptop camera). The frame contains $n \geq 0$ handwritten characters written in dark ink on a light background. Training data: a labelled set $D = \{(g_i, y_i)\}$, where $g_i \in$ [0,1]^{28×28} is a grey-scale character image and $y_i \in A$ is its label.

Alphabet: A is the set of 47 EMNIST-balanced classes – the digits 0–9, the upper-case letters A–Z (some letters that look the same in both cases, e.g. C/c, O/o, S/s, are one class) and the lower-case letters a, b, d, e, f, g, h, n, q, r, t.

2.2 Output

An ordered sequence of n pairs $((c_1, \rho_1), \ldots, (c_n, \rho_n))$ where $c_k \in A$ is the recognised character at position k (reading order: left to right, top to bottom) and $\rho_k \in [0,100]$ is its fuzzy reliability in percent. The text output is the string $s = c_1c_2\ldots c_n$ with a space inserted where the horizontal gap between two characters is more than 1.2 × the median character width.

2.3 Mathematical formulation

Step 1 – Segmentation. The frame is converted to grey, blurred, and thresholded with a local (adaptive) threshold, giving a binary ink mask M(x,y) ∈ {0,1}. Each 8-connected component of M whose area and height are within limits is a character candidate with bounding box b_k. Each candidate is resized to fit a 20×20 box (aspect ratio kept) and centred in a 28×28 image g_k – the same format as the training data.

Step 2 – Feature vector. A feature map φ : [0,1]^{28×28} → [0,1]^{177} gives x = φ(g). The first 49 numbers are the average ink in each 4×4 block (ink-density zones); the other 128 are stroke-direction values: the image is cut into 4×4 cells and in each cell the gradient strength is added up in 8 orientation bins (0°–180°), then the whole vector is scaled to unit length.

Step 3 – Fuzzy rule base. For every class k there are m = 4 fuzzy rules R_{k,r} (188 rules in total):

$$R_{k,r}:\ \text{IF } x_1 \text{ is } \sim c_1 \text{ AND } x_2 \text{ is } \sim c_2 \text{ AND } \ldots \text{ AND } x_{177} \text{ is } \sim c_{177} \ \text{ THEN class} = k$$

Each antecedent "x_j is ~c_j" is a Gaussian membership function μ_j(x_j) = exp(−(x_j − c_j)² / (2σ_j²)). The centres c and widths σ of the rules come from fuzzy c-means clustering (Section 3.2). AND is implemented as the geometric mean of the memberships, so the firing strength of a rule is

$$f_{k,r}(x) = \left(\Pi_j \, \mu_j(x_j) \right)^{1/177} = \exp\left(-\frac{1}{177} \Sigma_j \, (x_j - c_j)^2 / (2\sigma_j^2) \right)$$

Rules of the same class are combined with OR = max, and the class membership is μ_k(x) = max_r f_{k,r}(x). Defuzzification (maximum-membership): ĉ = argmax_k μ_k(x). Strength s = μ_ĉ(x); gap γ = μ_ĉ(x) − (second largest μ_k(x)).

Step 4 – Reliability controller (Mamdani). Inputs s ∈ [0,1] and γ ∈ [0,1] are fuzzified with triangular sets (Figure 3), nine IF-THEN rules (e.g. IF strength is HIGH AND gap is LARGE THEN reliability is HIGH) are evaluated with AND = min, clipped outputs are joined with max, and the centroid of the result gives ρ ∈ [0,100].

2.4 Objective and performance measures

Find the rule parameters that maximise top-1 accuracy Acc = (1/N) Σ [ĉ(x_i) = y_i] on a held-out test set, and make ρ meaningful: samples with higher ρ should be recognised correctly more often. Secondary measure: top-3 accuracy (true class among the three largest μ_k).

2.5 Assumptions and scope

- Dark ink on light paper, one or more lines of separate (non-cursive) characters, reasonably large and well lit.
- Only the 47 classes above; no punctuation. Touching characters are not split.
- Recognition is character-by-character; there is no dictionary or language model.

3. Methodology




Figure 1: System block diagram

3.1 Dataset

EMNIST-balanced (Cohen et al., 2017): 112,800 training and 18,800 test images, 28×28, 47 classes with equal numbers of samples. It is derived from NIST handwriting and is the letters-and-digits extension of MNIST.

3.2 Learning the fuzzy rules with fuzzy c-means

For each class, its training feature vectors are clustered by fuzzy c-means (FCM, fuzzifier 2, 4 clusters). Unlike k-means, every sample belongs to every cluster with a degree $u_{ik} \in [0,1]$, $\Sigma_k u_{ik} = 1$. FCM repeats two steps: (a) $c_k = \Sigma u_{ik}^2 x_i / \Sigma u_{ik}^2$; (b) $u_{ik} = 1 / \Sigma_l (d_{ik}/d_{il})^2$. Each cluster becomes one rule: its centre gives c_j and the membership-weighted standard deviation gives σ_j. A floor of 0.3 × the overall standard deviation of feature j is applied, so a rule is never unrealistically narrow. The reason for several rules per class is that one letter has several writing styles (e.g. 4 vs. open-top 4, 7 with or without a bar).

3.3 Reliability fuzzy controller

Strength \ Gap	**SMALL**	**MEDIUM**	**LARGE**
LOW	LOW	LOW	MEDIUM
MEDIUM	LOW	MEDIUM	HIGH
HIGH	MEDIUM	HIGH	HIGH




Figure 2/3: membership functions of the reliability controller and the distribution of ρ on the test set

3.4 Camera application

A Tkinter desktop application reads frames with OpenCV, runs the pipeline of Figure 1 about 6 times per second, and draws a box around each character, coloured green/amber/red by reliability level (≥65 / 35–65 / <35 %). The side panel shows the detected text, the average reliability bar,

and for each character the three best classes with their membership values. Buttons: Freeze/Resume, Save snapshot, Open image…, Switch camera.




Figure 4: pipeline on a sample image (characters taken from the EMNIST test set and placed on a paper-like background)

4. Results (progress till date)

Measure	Value
Top-1 accuracy (18,800 test images, 47 classes)	66.3%
Top-3 accuracy	86.8%
Number of fuzzy rules	188
Random-guess baseline	2.1 %

Does the reliability value mean anything? Test samples grouped by the reliability the controller assigned:

Reliability group	Samples	Accuracy in group
LOW (<35)	1096	28.6%
MEDIUM (35-65)	9661	51.5%
HIGH (>=65)	8043	89.2%

Accuracy rises from the LOW to the HIGH group, so ρ is a useful warning: when the fuzzy controller says HIGH the reading is right about nine times out of ten.




Figure 5: confusion matrix




Figure 6: accuracy per class

Observations. Most errors are between look-alike shapes: 9/q/g, F/f, 1/I/L, O/0, e/a and 3/B (the most frequent confusions in our test run). This is the inherent imprecision that motivated the fuzzy approach; the top-3 accuracy shows that the correct character is almost always among the top candidates.

5. Limitations and future work

- Accuracy (about 66 %) is lower than a trained neural network would reach (CO3). The fuzzy rules are deliberately simple and explainable: every decision can be traced back to rules and membership values.
- Future: tune the rule widths and number of rules per class with a genetic algorithm (CO4); add a perceptron / neural network and compare; use context (dictionary) to resolve O/0 and I/1; split touching characters.
- Camera robustness: strong shadows, thin pen strokes and tilted paper reduce quality.

6. Tools and how to run

Python 3, NumPy (fuzzy c-means and fuzzy rules written from scratch), OpenCV (image processing), Tkinter + Pillow (GUI), Matplotlib (figures). Commands: python src/train.py | python src/evaluate.py | python src/app.py [camera index or image file]

7. References

- L. A. Zadeh, “Fuzzy sets”, Information and Control, 8(3), 1965.
- J. C. Bezdek, Pattern Recognition with Fuzzy Objective Function Algorithms, Plenum, 1981 (fuzzy c-means).
- E. H. Mamdani and S. Assilian, “An experiment in linguistic synthesis with a fuzzy logic controller”, 1975.
- G. Cohen, S. Afshar, J. Tapson, A. van Schaik, “EMNIST: an extension of MNIST to handwritten letters”, 2017.
- S. Rajasekaran and G. A. Vijayalakshmi Pai, Neural Networks, Fuzzy Logic and Genetic Algorithms, PHI.
- N. Dalal and B. Triggs, “Histograms of oriented gradients for human detection”, CVPR 2005 (idea behind direction features).