

Liar's domination in unit disk graphs[☆]Ramesh K. Jallu^{a,*,1}, Sangram K. Jena^b, Gautam K. Das^b^a The Czech Academy of Sciences, Institute of Computer Science, Czech Republic^b Department of Mathematics, Indian Institute of Technology Guwahati, India

ARTICLE INFO

Article history:

Received 25 March 2020

Received in revised form 5 August 2020

Accepted 28 August 2020

Available online 2 September 2020

Communicated by T. Calamoneri

Keywords:

Dominating set

Liar's dominating set

Unit disk graph

Approximation scheme

ABSTRACT

In this article, we study a variant of the minimum dominating set problem known as the minimum liar's dominating set (MLDS) problem. We prove that the MLDS problem is NP-hard in unit disk graphs. We point out that the approximation guarantee of $\frac{1}{2}$ for the approximation algorithm for unit disk graphs proposed by Banerjee and Bhore (2019) [11] is not correct and we propose a simple $O(n + m)$ time 7.31-factor approximation algorithm, where n and m are the number of vertices and edges, respectively, in the given unit disk graph. Finally, we prove that the MLDS problem admits a polynomial-time approximation scheme.

© 2020 Elsevier B.V. All rights reserved.

1. Introduction

Given a simple undirected graph $G = (V, E)$, the open and closed neighborhoods of a vertex $v_i \in V$ are defined by $N_G(v_i) = \{v_j \in V \mid (v_i, v_j) \in E\}$ and $N_G[v_i] = N_G(v_i) \cup \{v_i\}$, respectively. A *dominating set* D of G is a subset of V such that every vertex in $V \setminus D$ is adjacent to at least one vertex in D . We say that a vertex v_i is dominated by v_j in G , if $v_j \in D$ and $(v_i, v_j) \in E$. The dominating set problem asks to find a dominating set of minimum size in a given graph. A *minimum k -dominating set* D of G is a minimum dominating set of G with the property that every vertex in $V \setminus D$ is dominated by at least k vertices in D . A set $D \subseteq V$ is a *k -tuple dominating set* in G , if each vertex $v_i \in V$ is dominated by at least k vertices in D . In the other words, $|N_G[v_i] \cap D| \geq k$ for each $v_i \in V$. The minimum cardinality of a k -tuple dominating set of a graph G is called the *k -tuple domination number* of G .

A *liar's dominating set* (LDS) in a simple undirected graph $G = (V, E)$, is a dominating set D having the following two properties: (i) for every $v_i \in V$, $|N_G[v_i] \cap D| \geq 2$, and (ii) for every pair of distinct vertices v_i and v_j in V , $|(N_G[v_i] \cup N_G[v_j]) \cap D| \geq 3$. In a given graph G , the problem of finding an LDS of minimum cardinality in G is known as the *minimum liar's dominating set* (MLDS) problem, and the cardinality of an MLDS is known as the liar's domination number of G . Every 3-tuple dominating set is a liar's dominating set as it satisfies both the conditions of a liar's dominating set, and hence, the liar's domination number lies between 2-tuple and 3-tuple domination numbers.

Our interest in the LDS problem arises from the following scenario. Consider a graph in which each node is a possible location for an intruder such as a thief, or a saboteur. We would like to detect and report the intruder's location in the graph. A protection device such as a camera or a sensor placed at a node can not only detect (and report) the intruder's

[☆] Preliminary version of this paper appeared in COCOON, 2018.

* Corresponding author.

E-mail addresses: jallu@cs.cas.cz (R.K. Jallu), sangram@iitg.ac.in (S.K. Jena), gkd@iitg.ac.in (G.K. Das).

¹ Ramesh K. Jallu was supported by the Czech Science Foundation, grant number GJ19-06792Y, and by institutional support RVO:67985807.

presence at it, but also at its neighbors. Our objective is to place a minimum number of protection devices such that the intrusion of the intruder at any vertex is detected and reported. In this situation, one must place the devices at the vertices of a minimum dominating set of the graph to achieve the goal. The protection devices are prone to failure and hence certain degree of redundancy is needed in the solution. Also, sometimes the devices may misreport the intruder's location deliberately or due to transmission error. Assume that at most one protection device in the closed neighborhood of the intruder can lie (misreport). In this context, one must place the protection devices at the vertices of an MLDS of the graph to achieve the objective. The first property in the definition of LDS deals with single device fault-tolerance, while the second property deals with the case in which two distinct locations about the intruder are reported.

2. Related work

The MLDS problem is introduced by Slater [1]. He showed that the problem is NP-hard for general graphs, and gave a lower bound on the liar's domination number in case of trees by proving that the size of any liar's dominating set of a tree of order n is between $\frac{3}{4}(n+1)$ and n . Later, Roden and Slater [2] characterized tree classes with liar's domination number equal to $\frac{3}{4}(n+1)$. In the same paper, they also showed that the MLDS problem is NP-hard even for bipartite graphs. Panda and Paul [3] proved that the problem is NP-hard for split graphs and chordal graphs. The hardness of the problem is also studied for bounded degree graphs, doubly chordal graphs, and p -claw free graphs [4]. Sterling [5] considered the problem on two-dimensional grid graphs and presented bounds on the liar's domination number.

Alimadadi et al. [6] provided the characterization of graphs and trees for which the liar's domination number is $|V|$ and $|V| - 1$, respectively. Panda and Paul [7,8] studied variants of liar's domination, namely, connected liar's domination and total liar's domination. A *connected liar's dominating set* (CLDS) is an LDS whose induced subgraph is connected. A *total liar's dominating set* (TLDS) is a dominating set D with the following two properties: (i) for every $v \in V$, $|N_G(v) \cap D| \geq 2$, and (ii) for every distinct pair of vertices u and v , $|(N_G(u) \cup N_G(v)) \cap D| \geq 3$, where $N_G(\cdot)$ is the open neighborhood of a vertex. The objective of both problems is to find CLDS and TLDS of minimum size, respectively. The authors showed that both the problems are NP-hard.

An LDS of minimum cardinality can be computed in linear time for trees [3], interval graphs [9], and block graphs [4]. On the other hand, like the minimum dominating set problem, no polynomial-time algorithm can achieve sublogarithmic approximation factor for the MLDS, CLDS, TLDS problems in general graphs, unless $P = NP$, and one can only hope for $O(\log \Delta)$ -factor approximation algorithms, where Δ is the degree of the graph [7,8,4]. The MLDS problem is shown to be APX-complete for p -claw free graphs for $p \geq 5$ and even for graphs with maximum degree 4 [4]. Jallu and Das [10] first studied the geometric version of the MLDS problem, and presented constant factor approximation algorithms with high running time. Recently, Banerjee and Bhore [11] proposed a $\frac{11}{2}$ -factor approximation algorithm in sub-quadratic time. However, unfortunately, their approximation analysis is erroneous and the approximation factor is at least 11 (refer Section 4).

2.1. Our contribution

We study the MLDS problem on a geometric intersection graph model, particularly in UDGs. A *unit disk graph* (UDG) is an intersection graph of equal radii disks in the plane. Given a set $\{d_1, d_2, \dots, d_n\}$ of n circular disks in the plane, each having radius 1, the corresponding UDG $G = (V, E)$ is defined as follows: each vertex $v_i \in V$ corresponds to a disk d_i , and there is an edge between two vertices v_i and v_j if and only if the Euclidean distance between the corresponding disk centers d_i and d_j is at most 1.

We show that the decision version of the MLDS problem is NP-complete in UDGs (refer to Section 3). We propose a simple linear time 7.31-factor approximation algorithm and a PTAS in Section 4 and Section 5, respectively. Finally, we conclude the paper in Section 6.

3. Hardness of the MLDS problem in UDGs

In this section, we show that the MLDS problem in UDGs is NP-complete by reducing the *vertex cover* problem defined in planar graphs to it, which is known to be NP-complete [12]. The decision versions of both the problems are formally defined below.

The MLDS problem in UDGs (LDS-UDG)

Instance: A unit disk graph $G = (V, E)$ and a positive integer k .

Question: Does there exist a liar's dominating set D in G such that $|D| \leq k$?

The vertex cover problem in planar graphs (VC-PLA)

Instance: A simple planar graph G with maximum degree 3 and a positive integer k .

Question: Does there exist a vertex cover C of G such that $|C| \leq k$?

Lemma 3.1 ([13]). *A planar graph $G = (V, E)$ with maximum degree 4 can be embedded in the plane using $O(|V|^2)$ area in such a way that its vertices are at integer coordinates and its edges are drawn so that they are made up of line segments of the form $x = i$ or $y = j$, for integers i and j .*




Fig. 1. (a) A planar graph G with maximum degree 3, (b) its embedding on a grid, and (c) construction of a UDG from the embedding.

This kind of embedding is known as *orthogonal drawing* of a graph. Biedl and Kant [14] gave a linear time algorithm that produces an orthogonal drawing of a given graph with the property that the number of bends along each edge is at most 2 (see Fig. 1).

Corollary 3.2. A planar graph $G = (V, E)$ with maximum degree 3 and $|E| \geq 2$ can be embedded in the plane such that its vertices are at $(4i, 4j)$ and its edges are drawn as a sequence of consecutive line segments on the lines $x = 4i$ or $y = 4j$, for integers i and j .

Lemma 3.3. Let $G = (V, E)$ be an instance of VC-PLA with $|E| \geq 2$. An instance $G' = (V', E')$ of LDS-UDG can be constructed from G in polynomial-time.

Proof. We construct G' in four phases.

Phase 1: Embedding of G into a grid of size 4×4

Embed the instance G in the plane as discussed previously using one of the algorithms in [15,16]. An edge in the embedding is a sequence of connected line segment(s) of length four units each. If the total number of line segments used in the embedding is ℓ , then the sum of the lengths of the line segments is 4ℓ as each line segment has length 4 units. We name the points in the embedding correspond to the vertices of G by *node points* (see Fig. 1(b)).

Phase 2: Adding extra points to the embedding

Divide the set of line segments in the embedding into two categories, namely, proper and improper. We call a line segment *proper* if none of its end points correspond to a vertex in G . A line segment is *improper* if it is not a proper segment. For each edge (p_i, p_j) of length 4 units we add two points at distances 1 and 1.5 units of p_i and p_j , respectively (thus adding four points in total, see the edge (p_4, p_6) in Fig. 1(c)). For each edge of length greater than 4 units, we also add points as follows: for each improper line segment we add four points at distances 1, 1.5, 2.5, and 3.5 units from the endpoint corresponding to a vertex in G , and for each proper line segment we add four points at distances 0.5 and 1.5 units from its endpoints (see Fig. 1(c)). We name the points added in this phase *joint points*.

Phase 3: Adding extra line segments and points

Add a line segment of length 1.4 units (on the lines $x = 4i$ or $y = 4j$ for some integers i or j) for every point p_i , which corresponds to a vertex v_i in G , without coinciding with the line segments that had already been drawn. Observe that adding this line segment on the lines $x = 4i$ or $y = 4j$ is possible without losing the planarity as the maximum degree of G is 3. Now, add three points (say x_i , y_i , and z_i) on these line segments at distances 0.2, 1.2, and 1.4 units, respectively, from p_i . We name the points added in this phase *support points*.




Fig. 2. (a) A vertex cover $\{v_2, v_3, v_4\}$ in G , and (b) the construction of J' in G' (the tie between v_2 and v_3 , and v_3 and v_4 is broken by choosing v_3).

Phase 4: Construction of UDG

For convenience, let us denote the set of node points, joint points, and support points by N , J , and S , respectively. Let $N = \{p_i \mid v_i \in V\}$, $J = \{q_1, q_2, \dots, q_{4\ell}\}$, and $S = \{x_i, y_i, z_i \mid v_i \in V\}$. We construct a UDG $G' = (V', E')$, where $V' = N \cup J \cup S$ and there is an edge between two points in V' if and only if the Euclidean distance between the points is at most 1 (see Fig. 1(c)). Observe that, $|N| = |V| (= n)$, $|J| = 4\ell$, where ℓ is the total number of line segments in the embedding, and $|S| = 3|V| (= 3n)$. Hence, $|V'| = 4(n + \ell)$ and ℓ is bounded by a polynomial of n . Therefore, G' can be constructed in polynomial-time. $\square$

Theorem 3.4. *Lds-UDG is NP-complete.*

Proof. $\text{Lds-UDG} \in \text{NP}$, since for any given set $D \subseteq V$ and a positive integer k , we can verify whether D is a liar's dominating set of size at most k or not in polynomial-time.

We prove the hardness of Lds-UDG by reducing Vc-PLA to it. Let $G = (V, E)$ be an instance of Vc-PLA . Construct an instance $G' = (V', E')$ of Lds-UDG as discussed in Lemma 3.3. We now prove the following claim: *G has a vertex cover of size at most k if and only if G' has a liar's dominating set of size at most $k + 3\ell + 3n$.*

Necessity: Let $C \subseteq V$ be a vertex cover of G such that $|C| \leq k$. Let $N' = \{p_i \in N \mid v_i \in C\}$, i.e., N' is the set of vertices (or node points) in G' that correspond to the vertices in C . From each segment in the embedding we choose 3 vertices (joint points). The set of chosen vertices, say $J' \subseteq J$, together with N' and S will form an LDS of desired cardinality in G' . We now discuss the process of obtaining the set J' . Initially $J' = \emptyset$. As C is a vertex cover, every edge in G has at least one of its end vertices in C . Let (v_i, v_j) be an edge in G and $v_i \in C$ (the tie can be broken arbitrarily if both v_i and v_j are in C). Note that the edge (v_i, v_j) is represented as a sequence of line segments in the embedding. Start traversing the segments (of (v_i, v_j)) from p_i , where p_i corresponds to v_i , and add all the vertices to J' except the first one from each segment encountered in the traversal (see (p_2, p_5) in Fig. 2 (b)). The bold vertices are part of J' while traversing from p_2 .

Apply the above process to each edge in G . Observe that the cardinality of J' is 3ℓ as we have chosen 3 vertices from each segment in the embedding. Let $D = N' \cup J' \cup S$. Now, we argue that D is a liar's dominating set in G' .

1. Each $p_i \in N$ is dominated by x_i in S . If $p_i \in N'$ (i.e., the corresponding vertex $v_i \in C$ in G), then $|N_{G'}[p_i] \cap D| \geq |\{p_i, x_i\}| = 2$. If $p_i \notin N'$, then there must exist at least one vertex q_j in J' dominating p_i . The existence of q_j is guaranteed by the way we constructed J' . Hence, $|N_{G'}[p_i] \cap D| \geq |\{q_j, x_i\}| = 2$. In either case every vertex in N is dominated by at least two vertices in D . It is needless to say that vertex in J is dominated by at least two vertices in $N' \cup J'$. Similarly, every vertex in S is dominated by itself, by its neighbor(s) in S , and perhaps by one vertex in N' . Therefore, every vertex in V' is double dominated by vertices in D .

2. Consider a pair of distinct vertices in V' . Of course, every pair of distinct vertices in S satisfy the liar's second condition. We prove that remaining pairs of distinct vertices also do satisfy the liar's second condition by considering all possible cases.

Case a. $p_i, p_j \in N$: If at least one of p_i, p_j belongs to N' (without loss of generality say $p_i \in N'$), then $|N_{G'}[p_i] \cup N_{G'}[p_j] \cap D| \geq |\{x_i, x_j, p_i\}| = 3$. If none of p_i, p_j belongs to N' , then there must exist some $q_i, q_j \in J'$ such that q_i, q_j dominate p_i, p_j , respectively. Hence, $|N_{G'}[p_i] \cup N_{G'}[p_j] \cap D| \geq |\{x_i, x_j, q_i, q_j\}| = 4$.

Case b. $q_i, q_j \in J$: If both $q_i, q_j \in J'$, then it is trivial that $|N_{G'}[q_i] \cup N_{G'}[q_j] \cap D| \geq 3$. Suppose one of q_i, q_j belongs to J' (without loss of generality let us assume $q_i \in J'$). As every vertex in G' is double dominated, q_j must be dominated by two vertices in J' or by either some q_k in J' and some p_l in N' . In either case we get $|N_{G'}[q_i] \cup N_{G'}[q_j] \cap D| \geq 3$. A similar argument works even if none of q_i, q_j belong to J' .

Case c. $p_i \in N$ and $q_j \in J$: If none of p_i and q_j belong to D , then the argument is trivial as each one is dominated by at least two vertices in D . If both belong to D , then $|N_{G'}[p_i] \cup N_{G'}[q_j] \cap D| \geq |\{p_i, x_i, q_j\}| = 3$. If $p_i \in D$ and $q_j \notin D$ (the other case is similar), then $|N_{G'}[p_i] \cup N_{G'}[q_j] \cap D| \geq 3$ holds as q_j is double dominated.

Likewise, we can argue for other pair combinations too. Therefore, every pair of distinct vertices in V' is dominated by at least 3 vertices in D .




Fig. 3. Illustration of Claim (iii). The vertices marked red must be in D . (For interpretation of the colors in the figure(s), the reader is referred to the web version of this article.)

Therefore, D is an LDS in G' and $|D| = |N'| + |J'| + |S| \leq k + 3\ell + 3n$.

Sufficiency: Let $D \subseteq V'$ be an LDS of size at most $k + 3\ell + 3n$. We prove that G has a vertex cover of size at most k with the aid of the following claims.

- (i) $S \subset D$.
- (ii) Every segment in the embedding must contribute at least 3 vertices to D and hence $|J \cap D| \geq 3\ell$, where ℓ is the total number of segments in the embedding.
- (iii) If p_i and p_j correspond to end vertices of an edge (v_i, v_j) in G , and if both p_i, p_j are not in D , then there must be at least $3\ell' + 1$ vertices in D form the segment(s) representing the edge (v_i, v_j) , where ℓ' is the number of segments representing the edge (v_i, v_j) in the embedding.

Claim (i) directly follows from the definition of liar's dominating set. Observe that we added points x_i, y_i, z_i such that p_i is adjacent to x_i , x_i is adjacent to y_i , and y_i is adjacent to z_i in G' , i.e., $\{(p_i, x_i), (x_i, y_i), (y_i, z_i)\} \subset E'$, for each i . Hence, z_i and y_i must be in D due to the first condition of the liar's domination. Also, every connected component of D in G must contain at least three vertices due to the second condition of liar's domination. Hence, $x_i \in D$. Therefore, any liar's dominating set of G' must contain $\{x_i, y_i, z_i\}$, $1 \leq i \leq n$, i.e., $S \subset D$.

Claim (ii) follows from the fact that only consecutive points are adjacent (in G') on any segment in the embedding. Let η be a segment in the embedding having vertices q_i, q_{i+1}, q_{i+2} , and q_{i+3} . On contrary, assume that η has only two of its vertices in D . Note that both q_{i+1} and q_{i+2} can not be in D simultaneously. If both are present in D , then they do not satisfy the second condition as q_i and q_{i+3} are not in D , i.e., $|(N_{G'}[q_{i+1}] \cup N_{G'}[q_{i+2}]) \cap D| = |\{q_{i+1}, q_{i+2}\}| = 2$; contradiction to D is an LDS. Without loss of generality we assume that $q_{i+2} \notin D$ (the similar argument works even if $q_{i+1} \notin D$). If q_i and q_{i+1} are in D , then $|(N_{G'}[q_{i+1}] \cup N_{G'}[q_{i+2}]) \cap D| = |\{q_i, q_{i+1}\}| = 2$. If q_i and q_{i+3} are in D , then $|(N_{G'}[q_{i+1}] \cup N_{G'}[q_{i+2}]) \cap D| = |\{q_i, q_{i+3}\}| = 2$. If q_{i+1} and q_{i+3} are in D , then $|(N_{G'}[q_{i+1}] \cup N_{G'}[q_{i+2}]) \cap D| = |\{q_{i+1}, q_{i+3}\}| = 2$. In either case we arrived at a contradiction.

Claim (iii) follows from Claim (ii). Let (v_i, v_j) be an edge in G such that p_i and p_j are not in D . By Claim (ii) every segment must contribute at least three vertices to D . Hence, the number of vertices in D from the segments representing the edge (v_i, v_j) is at least $3\ell'$. We argue that if both p_i and p_j are not in D , then the number of vertices in D from the segments representing the edge (v_i, v_j) is at least $3\ell' + 1$. Suppose that there are exactly $3\ell'$ vertices in D from the segments. That is, no segment representing the edge (v_i, v_j) contains more than three vertices in D . Let $p_i, q_1, q_2, \dots, q_{4\ell'}, p_j$ be the vertices encountered while traversing the segments from p_i . If $\ell' = 1$, the argument can be proven as in the proof of Claim (ii). Assume $\ell' > 1$.

Case a. ℓ' is even: Since p_i and p_j are not in D and due to the second condition of the liar's domination, the vertices q_1, q_2, q_3 from the first segment and $q_{4\ell'-2}, q_{4\ell'-1}, q_{4\ell'}$ from the last segment must be in D . The vertices q_4 and $q_{4\ell'-3}$ can not be in D as we assumed that each segment contains exactly three vertices in D . If we continue in the same manner for the rest of the segments from both sides, we end up in not choosing the vertices $q_{2\ell'}$ and $q_{2\ell'+1}$ from the $\frac{\ell'}{2}$ -th and $(\frac{\ell'}{2} + 1)$ -th segments, respectively. Note that $q_{2\ell'}$ is the last vertex on $\frac{\ell'}{2}$ -th segment and $q_{2\ell'+1}$ is the first vertex on $(\frac{\ell'}{2} + 1)$ -th segment and $(q_{2\ell'}, q_{2\ell'+1})$ is an edge in G' (see Fig. 3(a)). Also, note that $|(N_{G'}[q_{2\ell'}] \cup N_{G'}[q_{2\ell'+1}]) \cap D| = |\{q_{2\ell'-1}, q_{2\ell'+2}\}| = 2$. Implies, the vertices $q_{2\ell'}$ and $q_{2\ell'+1}$ are not satisfying the second condition, which is a contradiction to our assumption that D is an LDS of G' .

Case b. ℓ' is odd: If we proceed as in Case a, we can observe that D must contain *all* the four vertices on $(\frac{\ell'}{2} + 1)$ -th segment, i.e., the middle segment, (see Fig. 3(b)). Which is a contradiction to our assumption that no segment, representing the edge (v_i, v_j) , contains more than three vertices in D .

We now show that, by removing and/or replacing some vertices in D , a set of k vertices from N can be chosen such that the corresponding vertices in G is a vertex cover. The vertices in S account for $3n$ vertices in D (due to Claim (i)). Let $D = D \setminus S$ and $C = \{v_i \in V \mid p_i \in D \cap N\}$. If any edge (v_i, v_j) in G has none of its end vertices in C , then we do the following: consider the sequence of segments representing the edge (v_i, v_j) in the embedding. Since, both p_i and p_j are not in D , there must exist a segment having all its vertices in D (due to Claim (iii)). Consider the segment having its four vertices in D . Delete any one of the vertices on the segment and introduce p_i (or p_j). Update C and repeat the process till every edge has at least one of its end vertices in C . Due to Claim (ii), C is a vertex cover in G with $|C| \leq k$. Therefore, LDS-UDG is NP-complete. $\square$

4. Approximation algorithm

Banerjee and Bhore [11] in their recent paper proposed an approximation algorithm and claim that their algorithm achieves a 5.5-factor approximation ratio for the MLDS problem in UDGs. However, their approximation analysis is erroneous. We first provide a counterexample defying their claim and then propose a simple 7.31-factor approximation algorithm for the said problem.

For completeness here we give the idea of the algorithm proposed in [11] briefly. As a first step, the point set P (i.e., the set of disk centers) is sorted according to their x -coordinates. Now consider the leftmost point, say p_i , and consider p_i in the solution. Next, compute the set of points of P that are inside the circle centered at p_i and of radius $\frac{1}{2}$, 1, and $\frac{3}{2}$. Let these sets be $Cov_{\frac{1}{2}}(C(p_i))$, $Cov_1(C(p_i))$, and $Cov_{\frac{3}{2}}(C(p_i))$, respectively. The points which lie outside the set $Cov_{\frac{3}{2}}(C(p_i))$, their corresponding disks of radius 1 do not contain any point from $Cov_{\frac{1}{2}}(C(p_i))$. So, it suffices to consider the points inside $Cov_{\frac{3}{2}}(C(p_i))$ to ensure liar's domination for $Cov_{\frac{1}{2}}(C(p_i))$. Since p_i is the leftmost point in P , the set $Q = Cov_{\frac{3}{2}}(C(p_i)) \setminus Cov_1(C(p_i))$ can contain at most five mutually independent points (i.e., the mutual distance between those five points is greater than one. In the other words, the unit radius disks centered at those points do not contain the centers of other disks). In the next step (call it Case 1), for each point $q_i \in Q$, the algorithm chooses at most two points from the set $S(q_i) = Cov_{\frac{1}{2}}(C(p_i)) \cap Cov_1(C(q_i))$ in the solution, if available, where $Cov_1(C(q_i))$ is the set of points lying in the unit disk centered at q_i . After selection of these points, Q is updated to $Q \setminus Cov_1(C(q_i))$ and proceed to next point in Q . Thus, the algorithm picks at most $5 \times 2 + 1 = 11$ points in this iteration. Let $S = \bigcup_{q_i \in Q} S(q_i)$. However, S could be an empty set due to either $Q = \emptyset$ or $S(q_i) = \emptyset$ for each $q_i \in Q$ (call it Case 2). If $S = \emptyset$ or $|S| < 2$, then the algorithm chooses at most 4 points (including p_i) from $Cov_1(C(p_i))$ depending on the cardinality of $Cov_{\frac{1}{2}}(C(p_i))$. Thus, in this case the algorithm picks fewer than 11 points from $Cov_1(C(p_i))$. The points chosen so far ensures the liar's domination for the points in $Cov_{\frac{1}{2}}(C(p_i))$. Now, P is updated to $P \setminus Cov_{\frac{1}{2}}(C(p_i))$, and the process is repeated (with the next leftmost point, say p_j) until P is empty.

For each point $p_i \in P$, any optimal solution should contain at least two points from $Cov_1(C(p_i))$ due to the first condition of liar's domination, and the algorithm chooses at most 11 points. Thus, the authors claim that the proposed algorithm is a $\frac{11}{2}$ -factor approximation by the charging argument 11 points in the solution returned by algorithm can be charged to two points in the optimal solution. But, the same two points in the optimal solution could be charged multiple times.

Suppose p_i and p_j are the leftmost points considered in two successive iterations, respectively. There may be a case that the algorithm could end up by choosing a set of 11 points in the solution to dominate $Cov_{\frac{1}{2}}(C(p_j))$ for which the same optimal solution for $Cov_{\frac{1}{2}}(C(p_i))$ is enough to ensure liar's domination for $Cov_{\frac{1}{2}}(C(p_j))$. We elaborate our claim in detail with an example.

Consider the set of points in Fig. 4(a) as an instance to the algorithm. The points are sorted according to their x -coordinates. Let the leftmost point be p_i (see Fig. 4(b)). The points $\{q_1, q_2, q_3, q_4, q_5\} \in Q$ are five mutually independent points chosen by the algorithm such that $Cov_{\frac{1}{2}}(C(p_i)) \cap Cov_1(C(q_j)) = 2$, for $j = 1, 2, \dots, 5$. Along with p_i , the total number of points chosen in this iteration is 11. Update $P = P \setminus Cov_{\frac{1}{2}}(C(p_i))$. In the next iteration, p_j is the leftmost point (see Fig. 4(c)) and $\{q_6, q_7, q_8, q_9, q_{10}\} \in Q$ are five mutually independent points chosen by the algorithm so that $Cov_{\frac{1}{2}}(C(p_j)) \cap Cov_1(C(q_i)) = 2$, for $i = 6, 7, \dots, 10$. The algorithm chooses 11 points (including p_j) in the solution. Observe that in both the iterations the algorithm doesn't enter Case 2 and, hence, chooses 22 points. In fact, any two (resp. three) red points (see Fig. 4(c)) are sufficient to ensure the liar's domination first (resp. second) condition for the point sets $Cov_{\frac{1}{2}}(C(p_i))$ and $Cov_{\frac{1}{2}}(C(p_j))$. After a few iterations p_k will be chosen as the next leftmost point and the algorithm chooses 11 points (by Case 1) in the solution (see Fig. 4(d)). However, the same three red points ensure liar's domination for $Cov_{\frac{1}{2}}(C(p_i))$, $Cov_{\frac{1}{2}}(C(p_j))$, and $Cov_{\frac{1}{2}}(C(p_k))$. So, the approximation factor of the algorithm proposed in [11] is at least 11.




Fig. 4. (a) A point set: an instance, (b) 11 points chosen from $\text{Cov}_{\frac{1}{2}}(C(p_i))$ out of which 3 red points are in optimal solution, (c) and (d) the selected red points for $\text{Cov}_{\frac{1}{2}}(C(p_i))$ will ensure liar's domination for $\text{Cov}_{\frac{1}{2}}(C(p_j))$ and $\text{Cov}_{\frac{1}{2}}(C(p_k))$. (For interpretation of the colors in the figure(s), the reader is referred to the web version of this article.)

4.1. A 7.31-factor approximation algorithm

In this Subsection, we propose a 7.31-factor approximation algorithm (see Algorithm 1) for minimum liar's dominating set (MLDS) problem in UDGs. The basic idea of the algorithm is: sequentially compute three maximal independent sets in the given UDG and add extra vertices, if necessary, to ensure liar's domination. In [17] Shang et al. established a relation between maximal independent set and minimum k -dominating set in UDGs. By using their result, we can have a 10-factor approximation algorithm for liar's dominating set in UDGs. In the following lemma, the proof idea is similar to [17], we establish a relation between the cardinalities of maximal independent set and minimum liar's dominating set to obtain a 7.31-factor approximation algorithm for the MLDS problem in UDGs.

Lemma 4.1. Let $G = (V, E)$ be a UDG. If I and D_{opt} denote a maximal independent set and an MLDS of G , respectively, then $|I| \leq \sqrt{\frac{10}{3}} |D_{opt}|$.

Proof. Let $I' = I \cap D_{opt}$, $X = I \setminus I'$, $Y = D_{opt} \setminus I'$. For $u, v \in X$, let $c_{u,v}$ denote the number of vertices in Y which lie in the closed neighborhoods of u and v in G , i.e., $c_{u,v} = |(N[u] \cup N[v]) \cap Y|$. As D_{opt} is a liar's dominating set of G , $c_{u,v} \geq 3$ for each $u, v \in X$, and we get $\sum_{u,v \in X} c_{u,v} \geq 3 \cdot \frac{|X|(|X|-1)}{2}$. For $u', v' \in Y$, analogues to $c_{u,v}$, let $d_{u',v'} = |(N[u'] \cup N[v']) \cap X|$. As G is a UDG, for each vertex in Y there can be at most 5 independent vertices in its neighborhood, and thus $d_{u',v'} \leq 10$ for each u' and v' in Y . Hence, we get $10 \cdot \frac{|Y|(|Y|-1)}{2} \geq \sum_{u',v' \in Y} d_{u',v'}$. Note that the number of edges in E induced between X and Y is $\sum_{u,v \in X} c_{u,v} (= \sum_{u',v' \in Y} d_{u',v'})$. Thus, we have $3 \cdot \frac{|X|(|X|-1)}{2} \leq 10 \cdot \frac{|Y|(|Y|-1)}{2}$, which implies $|X| \leq \sqrt{\frac{10}{3}} |Y|$. Therefore, $|I| = |X| + |I'| \leq \sqrt{\frac{10}{3}} |Y| + |I'| \leq \sqrt{\frac{10}{3}} |D_{opt}|$. $\square$

Algorithm 1 Liar's dominating set in UDG.

Require: A UDG $G = (V, E)$

Ensure: A liar's dominating set D of $G = (V, E)$

```

1:  $i \leftarrow 0$ ,  $I_i \leftarrow \emptyset$ , and  $D \leftarrow \emptyset$ 
2: for ( $i = 1$  to 3) do
3:   if ( $V \neq \emptyset$ ) then
4:      $I_i \leftarrow MIS(V)$ 
5:      $D \leftarrow D \cup I_i$ ;  $V \leftarrow V \setminus I_i$ 
6:   end if
7: end for
8: for every  $u \in I_1$  do
9:   if  $N_G(u) \cap (I_2 \cup I_3) = \emptyset$  then
10:    let  $v \in N_G(u)$ 
11:     $D = D \cup \{v\}$ 
12:   else if  $|N_G(u) \cap (I_2 \cup I_3)| = 1$  then
13:    let  $w$  be a neighbor of  $v \in N_G(u) \cap (I_2 \cup I_3)$  such that  $w \neq u$ 
14:     $D = D \cup \{w\}$ 
15:   end if
16: end for
17: return  $D$ 

```

$\triangleright MIS(\cdot)$ returns a maximal independent set

Lemma 4.2. The set D returned by Algorithm 1 is an LDS of G .

Proof. Algorithm 1 sub-sequentially computes three maximal independent sets I_1 , I_2 , and I_3 in G (see line numbers 2–7). Let $I = I_1 \cup I_2 \cup I_3$. Note that any vertex not in I has a neighbor (dominator) in each I_1 , I_2 , and I_3 . Thus, each vertex (resp. every pair of distinct vertices) not in $I_1 \cup I_2 \cup I_3$ satisfies the first (resp. second) condition of liar's domination. Also, every vertex in I_3 is adjacent to a vertex in I_1 and I_2 . Thus, the vertices in I_3 satisfy both the conditions of the liar's domination. Similarly, every vertex in I_2 is adjacent to a vertex in I_1 (otherwise, I_1 cannot be a maximal independent set) and, hence, the vertices in I_2 satisfy both the conditions of the liar's domination. For any vertex $u \in I_1$, if $N_G(u) \cap (I_2 \cup I_3) = \emptyset$, then the algorithm adds an arbitrary neighbor v of u to D (see line number 11). If $N_G(u) \cap (I_2 \cup I_3) \neq \emptyset$, then u has neighbor in $I_2 \cup I_3$. In either case the vertices in I_1 satisfy the two conditions of the liar's domination.

For any pair of distinct vertices $u \in I$ and $v \in V \setminus I$, the second condition is already satisfied as v has a neighbor in each I_1 , I_2 , and I_3 . Similarly, for any pair of distinct vertices $u \in I_1$ and $v \in I_2$, if v has multiple neighbors in I_1 or u has multiple neighbors in I_2 , then the second condition is satisfied. If u is the only neighbor of v in I_1 and vice versa, then the algorithm adds an arbitrary neighbor w of v to D , see line number 14, and thus the second condition is ensured for u and v . If $v \in I_3$, the second condition is trivially holds as v has a neighbor in each I_1 and I_2 . A similar argument works for the case $u \in I_2$ and $v \in I_3$. Therefore, D is an LDS in G . $\square$

Theorem 4.3. For a given UDG $G = (V, E)$, Algorithm 1 achieves approximation ratio 7.31 for the MLDS problem in $O(|V| + |E|)$ time.

Proof. Let D^* be an MLDS of G . Algorithm 1 sequentially computes three maximal independent sets I_1 , I_2 , and I_3 in G and $I = I_1 \cup I_2 \cup I_3$ is not necessarily be an LDS of G as there might be some vertices with one of the following cases: (i) a vertex $u \in I_1$ not satisfying the first condition, or (ii) a pair of distinct vertices $u \in I_1$ and $v \in I_2$ not satisfying the second condition of the liar's domination. In the former case, we add an arbitrary neighbor of u , and in the latter case we add an neighbor w of v . Note that in either case such a neighbor is guaranteed to exist in G , and $|D| \leq |I| + |I_1|$. Without loss of generality we can assume that $|I_3| \leq |I_2| \leq |I_1|$. Therefore, $|D| \leq 4|I_1| \leq 4 \cdot \sqrt{\frac{10}{3}} |D^*| \leq 7.31 |D^*|$ (by Lemma 4.1). The running time follows as Algorithm 1 uses the subroutine $MIS(\cdot)$ (in line number 4) to compute a maximal independent set. $\square$




Fig. 5. A 4-separated collection $S = \{S_1, S_2, S_3, S_4\}$.

5. Approximation scheme

In this section, we propose a PTAS for the MLDS problem in UDGs, i.e., for a given UDG $G = (V, E)$ and a parameter $\varepsilon > 0$, we propose an algorithm which produces a liar's dominating set of size no more than $(1 + \varepsilon)$ times the size of a minimum liar's dominating set in G . We use $\delta_G(u, v)$ to denote the number of edges on a shortest path between u and v in G . For $A, B \subseteq V$, $\delta_G(A, B)$ denotes the distance between A and B and is defined as $\delta_G(A, B) = \min_{u \in A, v \in B} \{\delta_G(u, v)\}$. For $A \subseteq V$, $D(A)$ and $D_{opt}(A)$ denote an LDS and an optimal (minimum size) LDS of A in G , respectively. We define the closed neighborhood of a set $A \subseteq V$ as $N_G[A] = \bigcup_{v \in A} N_G[v]$.

The proposed PTAS is based on the concept of m -separated collection of subsets of V ($m \geq 4$). Let $G = (V, E)$ be a UDG. A collection $S = \{S_1, S_2, \dots, S_k\}$ such that $S_i \subseteq V$ for $i = 1, 2, \dots, k$, is said to be an m -separated collection, if $\delta_G(S_i, S_j) > m$, for $1 \leq i \leq k$ and $1 \leq j \leq k$ (see Fig. 5 for a 4-separated collection). Nieberg and Hurink [18] introduced 2-separated collection to propose a PTAS for the minimum dominating set problem in UDGs and our PTAS follows from it. However, the algorithm in [18] cannot be directly applied as in intermediate steps of the algorithm we need to add extra nodes (see line numbers 12–21 in Algorithm 2) to ensure the liar's domination. We argue that the extra nodes added (to ensure a feasibility solution) are small enough and do not affect the approximation factor.

Lemma 5.1. Let $S = \{S_1, S_2, \dots, S_k\}$ be an m -separated collection. If $|S_i| \geq 3$ for $1 \leq i \leq k$, then $\sum_{i=1}^k |D_{opt}(S_i)| \leq |D_{opt}(V)|$.

Proof. Observe that $N_G[S_i] \cap N_G[S_j] = \emptyset$ for $i \neq j$ and $1 \leq i, j \leq k$. Also, $D_{opt}(S_i) \cap D_{opt}(S_j) = \emptyset$ as S_i and S_j are m -separated. Let $S'_i = \{u \in V \mid v \in S_i \text{ and } \delta_G(u, v) \leq 2\}$ for $i = 1, 2, \dots, k$. Observe that $S_i \subseteq S'_i$ and $S'_i \cap D_{opt}(V)$ is a liar's dominating set of S_i for $i = 1, 2, \dots, k$. Since, $\delta_G(S_i, S_j) > m (\geq 4)$ for $i \neq j$, implies $S'_i \cap S'_j = \emptyset$. Therefore, $(S'_i \cap D_{opt}(V)) \cap (S'_j \cap D_{opt}(V)) = \emptyset$ and $\bigcup_{i=1}^k (S'_i \cap D_{opt}(V)) \subseteq D_{opt}(V)$. Also, $|D_{opt}(S_i)| \leq |S'_i \cap D_{opt}(V)|$ for $i = 1, 2, \dots, k$ as $S'_i \cap D_{opt}(V)$ is a liar's dominating set of S_i , and $D_{opt}(S_i)$ is a minimum size liar's dominating set. Thus, $\sum_{i=1}^k |D_{opt}(S_i)| \leq \sum_{i=1}^k |S'_i \cap D_{opt}(V)| \leq |D_{opt}(V)|$. $\square$

Lemma 5.2. Let $S = \{S_1, S_2, \dots, S_k\}$ be an m -separated collection, and $N_1, N_2, \dots, N_k$ be subsets of V with $S_i \subseteq N_i$ for all $i = 1, 2, \dots, k$. If there exists $\rho \geq 1$ such that $|D_{opt}(N_i)| \leq \rho |D_{opt}(S_i)|$ holds for all $i = 1, 2, \dots, k$, and if $\bigcup_{i=1}^k D_{opt}(N_i)$ is a liar's dominating set in G , then the value of $\sum_{i=1}^k |D_{opt}(N_i)|$ is at most ρ times the size of a minimum liar's dominating set in G .

Proof. $\sum_{i=1}^k |D_{opt}(N_i)| \leq \rho \sum_{i=1}^k |D_{opt}(S_i)| \leq \rho |D_{opt}(V)|$. The latter inequality follows from Lemma 5.1. $\square$

5.1. Algorithm

In this section, we discuss the construction of a 4-separated collection $S = \{S_1, S_2, \dots, S_k\}$ and subsets $N_1, N_2, \dots, N_k$ of V such that $S_i \subseteq N_i$ for all $i = 1, 2, \dots, k$. The algorithm proceeds in an iterative manner. Initially $V_1 = V$. In the i -th iteration the algorithm computes S_i and N_i . For a given $\varepsilon > 0$, the i -th iteration of the algorithm starts with an arbitrary vertex $v \in V_i$ and increases the value of $r (= 2, 3, \dots)$ as long as $|D(N_G^{r+4}[v])| > \rho |D(N_G^r[v])|$ holds. Here, $D(N_G^{r+4}[v])$ and $D(N_G^r[v])$ are liar's dominating sets of $N_G^{r+4}[v]$ and $N_G^r[v]$, respectively, and $\rho = 1 + \varepsilon$. The smallest r violating the above condition, say $\hat{r}$, is obtained. Set $S_i = N_G^{\hat{r}}[v]$ and $U_i = N_G^{\hat{r}+4}[v]$. Now, the removal of U_i from V_i may lead to some isolated (i) vertex $u \in V_i$, and/or (ii) connected component with two vertices $u, w \in V_i$. In case (i), for each such vertex u find $x, y \in U_i$ such that $\{u, x, y\}$ forms a connected component and update U_i as follows: $U_i = U_i \setminus \{x, y\}$. In case (ii), for each such pair of vertices u, w find $x \in U_i$ such that $\{u, w, x\}$ forms a connected component and update U_i as follows: $U_i = U_i \setminus \{x\}$. Set

Algorithm 2 Liar's dominating set.**Require:** A unit disk graph $G = (V, E)$ with $|V| \geq 3$ and an arbitrary small $\varepsilon > 0$ **Ensure:** A liar's dominating set $\mathcal{D}$ of V

```

1:  $i \leftarrow 0$  and  $V_{i+1} \leftarrow V$ 
2:  $\mathcal{D} \leftarrow \emptyset$  and  $\rho \leftarrow 1 + \varepsilon$ 
3: while ( $V_{i+1} \neq \emptyset$ ) do
4:   pick an arbitrary  $v \in V_{i+1}$ 
5:    $N_G^0[v] \leftarrow v$  and  $r \leftarrow 2$ 
6:   while  $|D(N_G^{r+4}[v])| > \rho |D(N_G^r[v])|$  do ▷ call Algorithm 1
7:      $r \leftarrow r + 1$ 
8:   end while
9:    $\hat{r} \leftarrow r$  ▷ the smallest  $r$  violating while condition in step 6
10:   $i \leftarrow i + 1$  ▷ the index  $i$  keeps track of the number of iterations
11:   $S_i \leftarrow N_G^{\hat{r}}[v]$  and  $U_i \leftarrow N_G^{\hat{r}+4}[v]$ 
12:  if ( $V_{i+1} \setminus N_G^{\hat{r}+4}[v]$  contains isolated components of size 1 and/or 2) then
13:    for (each component,  $\{u\}$ , of size 1) do
14:      find  $x, y \in U_i$  such that  $\{u, x, y\}$  is a connected component
15:       $U_i \leftarrow U_i \setminus \{x, y\}$ 
16:    end for
17:    for (each component,  $\{u, w\}$ , of size 2) do
18:      find  $x \in U_i$  such that  $\{u, w, x\}$  is a connected component
19:       $U_i \leftarrow U_i \setminus \{x\}$ 
20:    end for
21:  end if
22:   $N_i \leftarrow U_i$ 
23:   $\mathcal{D} \leftarrow \mathcal{D} \cup D(N_i)$  ▷ call Algorithm 1
24:   $V_{i+1} \leftarrow V_i \setminus N_i$ 
25: end while
26: return  $\mathcal{D}$ 

```

$N_i = U_i$ and $V_{i+1} = V_i \setminus N_i$. The process stops if $V_{i+1} = \emptyset$ and returns the sets S_i s and N_i s. The collection of the sets S_i s is a 4-separated collection. The pseudo code is given in Algorithm 2.

The liar's dominating set of a r -th neighborhood of a vertex v , $D(N_G^r[v])$, can be computed with respect to G as described in Algorithm 1. Algorithm 1 successively finds maximal independent sets I_1, I_2 , and I_3 . Now, $I_1 \cup I_2 \cup I_3$ is a liar's dominating set for $N_G^r[v] \setminus I_1$ as every vertex not in I_1 either belongs to $I_2 \cup I_3$ or is adjacent to at least one vertex in each I_1, I_2 , and I_3 . To ensure the liar's domination for the vertices in I_1 , for each vertex u in I_1 we add at most a vertex (see line numbers 8–16 in Algorithm 1). In summary, Algorithm 2 deals with obtaining an m -separated collection $S = \{S_1, S_2, \dots, S_k\}$ and collection $N = \{N_1, N_2, \dots, N_k\}$ such that $S_i \subseteq N_i \subseteq V$ and using Algorithm 1 (that deals with obtaining a liar's dominating set of the r -th neighborhood of a vertex) as a sub-routine, Algorithm 2 computes a liar's dominating set for G .

Lemma 5.3. $D(N_G^r[v])$ is an LDS of $N_G^r[v]$ in G and $|D(N_G^r[v])| \leq O(r^2)$.

Proof. Algorithm 1 computes $D(N_G^r[v])$ by first computing maximal independent sets I_1, I_2 , and I_3 subsequently and then it adds at most one vertex for each vertex in I_1 to ensure that $D(N_G^r[v])$ is a feasible solution. We can show $D(N_G^r[v])$ is an LDS of $N_G^r[v]$ in G as in the proof of Lemma 4.2. Hence, $|D(N_G^r[v])| \leq 4 \cdot |I_1| \leq 4 \cdot \frac{\pi(r+1)^2}{\pi(1)^2} = O(r^2)$. The latter inequality follows from the standard area argument, the number of non-intersecting unit disks can be packed in a larger disk of radius $r + 1$ centered at v . $\square$

Lemma 5.4. In each iteration of Algorithm 2, there exists an r violating the condition $|D(N_G^{r+4}[v])| > \rho |D(N_G^r[v])|$, where $\rho = 1 + \varepsilon$.

Proof. We prove the lemma by contradiction. Suppose there exists $v \in V$ such that $|D(N_G^{r+4}[v])| > \rho |D(N_G^r[v])|$ for $r = 2, 3, \dots$. Observe that $|D(N_G^2[v])| \geq 3$ as there exists at least three vertices in G .

If $r = 4k$, $4(r+1)^2 \geq |D(N_G^{r+4}[v])| > \rho |D(N_G^{r-4}[v])| > \dots > \rho^{\frac{r}{4}} |D(N_G^2[v])| \geq 3\rho^{\frac{r}{4}}$, and

if $r = 4k + s$ for $1 \leq s \leq 3$,

$4(r+1)^2 \geq |D(N_G^{r+4}[v])| > \rho |D(N_G^{r-4}[v])| > \dots > \rho^{\frac{r-1}{4}} |D(N_G^3[v])| \geq 3\rho^{\frac{r-1}{4}}$.

In both the cases the first inequality follows from Lemma 5.3. Hence,

$$4(r+1)^8 > \begin{cases} \rho^r, & \text{if } r \text{ is } 4k \\ \rho^{r-1}, & \text{if } r \text{ is } 4k + s \end{cases} \quad (1)$$

The right hand part in inequality (1) is an exponential function in r and the left hand part is a polynomial in r , for arbitrarily large r none of the inequalities can be true. Hence, we arrived at contradiction. Thus there exists an r violating the condition. $\square$

The following lemma suggests that the smallest r violating inequality (1) is bounded by a constant that depends only on ε .

Lemma 5.5. *The smallest r violating the inequality (1) is bounded by $O(\frac{1}{\varepsilon} \log \frac{1}{\varepsilon})$.*

Proof. Let $\hat{r}$ be the smallest r violating the inequalities in (1). Using the inequalities (i) $\log(1 + \varepsilon) > \frac{\varepsilon}{2}$ for $0 < \varepsilon < 1$, (ii) $\log x < x$ for $x > 1$, and (iii) $\log \frac{1}{\varepsilon} \geq 1$ for $\varepsilon \leq \frac{1}{10}$, we show $\hat{r} \leq O(\frac{1}{\varepsilon} \log \frac{1}{\varepsilon})$. Let $x = \frac{c}{\varepsilon} \log \frac{1}{\varepsilon}$. Consider the inequality $4(x + 1)^8 \leq 4(2x)^8 \leq (1 + \varepsilon)^x$. The former inequality trivially holds for the choice of x and for any $\varepsilon > 0$, and taking the logarithm on both sides of the latter inequality, we get $\frac{\log 4 + 8 \log 2x}{x} \leq \log(1 + \varepsilon)$. By inequality (i), now, it suffices to show that $\frac{\log 4 + 8 \log 2x}{x} \leq \frac{\varepsilon}{2}$. Using the inequalities (ii) and (iii), the choice of x satisfies the inequality for any constant c satisfying $\log 2c + 2 < \frac{c}{16}$. $\square$

Lemma 5.6. *For a given $v \in V$, liar's dominating set $D_{opt}(N_i)$ of N_i can be computed in polynomial time.*

Proof. Note that $N_i \subseteq N_G^{r+4}[v]$. The size of a liar's dominating set $D(N_i)$ of N_i is bounded by $O(r^2)$ (by Lemma 5.3). Again, $r = O(\frac{1}{\varepsilon} \log \frac{1}{\varepsilon})$ by Lemma 5.5. Therefore, the size of the minimum size liar's dominating set $D_{opt}(N_i)$ of N_i is bounded by a constant. The process of checking whether a given set is a liar's dominating set or not can be done in polynomial-time. Therefore, we can consider every subset of N_i as a possible liar's dominating set and check whether it is a liar's dominating set or not in polynomial-time. Finally, the minimum size liar's dominating set is reported. $\square$

Lemma 5.7. *For the collection of neighborhoods $\{N_1, N_2, \dots, N_k\}$ created by Algorithm 2, the union $\mathcal{D} = \bigcup_{i=1}^k D(N_i)$ is a liar's dominating set in G .*

Proof. We first prove that for every $v \in V$, $|N_G[v] \cap \mathcal{D}| \geq 2$. Observe that $\bigcup_{i=1}^k N_i = V$ as $V_{i+1} = V_i \setminus N_i$ and $N_i \subseteq V_i$. Thus, every vertex $v \in N_i$ for some $1 \leq i \leq k$. By Lemma 5.3, $|N_G[v] \cap \mathcal{D}| \geq 2$ is satisfied.

Now we prove the second condition. Let $u, v \in V$ be any two arbitrary vertices. The following cases may arise.

Case 1. $u, v \in N_i$ for some $1 \leq i \leq k$

Since $D(N_i)$ is the liar's dominating set of N_i in G , we have, $|(N_G[u] \cup N_G[v]) \cap D(N_i)| \geq 3$ for every $u, v \in N_i$. Hence, $|(N_G[u] \cup N_G[v]) \cap \mathcal{D}| \geq 3$ for every $u, v \in V$.

Case 2. $u \in N_i$ and $v \in N_j$ for some $i \neq j$ and $1 \leq i, j \leq k$

If u and v are not adjacent in G , the proof is trivial. Hence, we assume that $(u, v) \in E$ i.e., u and v are adjacent in G . Now the following sub-cases may arise.

(a) $u \in D(N_i)$ and $v \in D(N_j)$

Observe that $|N_G[u] \cap D(N_i)| \geq 2$ and $|N_G[v] \cap D(N_j)| \geq 2$ as $D(N_i)$ and $D(N_j)$ are liar's dominating sets of N_i and N_j , respectively. Hence, u has a neighbor, say w , in $D(N_i)$, similarly v has also a neighbor, say x , in $D(N_j)$. However, maybe $w = x$ or maybe not. In either case $|(N_G[u] \cup N_G[v]) \cap \mathcal{D}| \geq 3$ holds.

(b) $u \notin D(N_i)$ and $v \in D(N_j)$ (the other case proof is similar)

Since $D(N_i)$ is a liar's dominating set of N_i , we have $|N_G[u] \cap D(N_i)| \geq 2$. Hence, $|(N_G[u] \cup N_G[v]) \cap \mathcal{D}| \geq 3$ is true as v is part of the solution.

(c) $u \notin D(N_i)$ and $v \notin D(N_j)$ (the proof is similar to the previous cases). $\square$

Corollary 5.8. *For the collection $N = \{N_1, N_2, \dots, N_k\}$ created by Algorithm 2, the union $\mathcal{D}^* = \bigcup_{i=1}^k D_{opt}(N_i)$ is a liar's dominating set.*

Theorem 5.9. *For a given UDG, $G = (V, E)$, and an $\varepsilon > 0$, we can design a $(1 + \varepsilon)$ -factor approximation algorithm to find an LDS in G with running time $n^{O(c^2)}$, where $c = O(\frac{1}{\varepsilon} \log \frac{1}{\varepsilon})$.*

Proof. Note that Algorithm 2 generates the collection of sets $S = \{S_1, S_2, \dots, S_k\}$ and $N = \{N_1, N_2, \dots, N_k\}$ such that S is a 4-separated collection of V with $S_i \subseteq N_i$ for each $i \in \{1, 2, \dots, k\}$ and $\bigcup_{i=1}^k N_i = V$ with $N_i \cap N_j = \emptyset$ for $i \neq j$. Corollary 5.8 suggests that $\mathcal{D}^* = \bigcup_{i=1}^k D_{opt}(N_i)$ is a liar's dominating set of G . The approximation bound follows from Lemma 5.1, and Lemma 5.2. Let $|N_i| = n_i$ for $1 \leq i \leq k$. By Lemma 5.6, an optimal liar's dominating set $D_{opt}(N_i)$ of N_i can be computed in $n_i^{O(\frac{1}{\varepsilon^2} \log \frac{1}{\varepsilon})}$ time. Therefore, the total running time to compute $\mathcal{D}^*$ is $\sum_{i=1}^k n_i^{O(\frac{1}{\varepsilon^2} \log \frac{1}{\varepsilon})} \leq n^{O(\frac{1}{\varepsilon^2} \log \frac{1}{\varepsilon})}$. $\square$

6. Conclusion

In this article, we studied the minimum liar's dominating set problem (MLDS) in UDGs. We proved that the decision version of the MLDS problem is NP-complete. We proposed a simple 7.31-factor approximation algorithm and a PTAS for the

problem. The proposed PTAS leads to a better approximation algorithm compared to the proposed 7.31-factor approximation algorithm, however at the cost of higher time complexity. We believe that it is possible to get much better approximation ratios with lower time complexity by exploring inherent geometric properties of UDGs. As a future direction, we work on it and hope to design such algorithms for the MLDS problem.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

References

- [1] P.J. Slater, Liar's domination, *Networks* 54 (2) (2009) 70–74.
- [2] M.L. Roden, P.J. Slater, Liar's domination in graphs, *Discrete Math.* 309 (19) (2009) 5884–5890.
- [3] B.S. Panda, S. Paul, Liar's domination in graphs: complexity and algorithm, *Discrete Appl. Math.* 161 (7) (2013) 1085–1092.
- [4] B.S. Panda, S. Paul, D. Pradhan, Hardness results, approximation and exact algorithms for liar's domination problem in graphs, *Theor. Comput. Sci.* 573 (2015) 26–42.
- [5] C. Sterling, Liar's domination in grid graphs, Ph.D. thesis, East Tennessee State University, 2012.
- [6] A. Alimadadi, M. Chellali, D.A. Mojdeh, Liar's dominating sets in graphs, *Discrete Appl. Math.* 211 (2016) 204–210.
- [7] B.S. Panda, S. Paul, Connected liar's domination in graphs: complexity and algorithms, *Discrete Math. Algorithms Appl.* 5 (04) (2013) 1350024.
- [8] B.S. Panda, S. Paul, Hardness results and approximation algorithm for total liar's domination in graphs, *J. Comb. Optim.* 27 (4) (2014) 643–662.
- [9] B.S. Panda, S. Paul, A linear time algorithm for liar's domination problem in proper interval graphs, *Inf. Process. Lett.* 113 (19) (2013) 815–822.
- [10] R.K. Jallu, G.K. Das, Liar's dominating set problem on unit disk graphs, *Discrete Appl. Math.* (2020), <https://doi.org/10.1016/j.dam.2020.01.017>, in press.
- [11] S. Banerjee, S. Bhore, Algorithm and hardness results on liar's dominating set and k -tuple dominating set, in: *International Workshop on Combinatorial Algorithms*, Springer, 2019, pp. 48–60.
- [12] M.R. Garey, D.S. Johnson, *Computers and Intractability: a Guide to the Theory of NP-Completeness*, Freeman, 1979.
- [13] L.G. Valiant, Universality considerations in VLSI circuits, *IEEE Trans. Comput.* 100 (2) (1981) 135–140.
- [14] T. Biedl, G. Kant, A better heuristic for orthogonal graph drawings, *Comput. Geom.* 9 (3) (1998) 159–180.
- [15] J. Hopcroft, R. Tarjan, Efficient planarity testing, *J. ACM* 21 (4) (1974) 549–568.
- [16] A. Itai, C.H. Papadimitriou, J.L. Szwarcfiter, Hamilton paths in grid graphs, *SIAM J. Comput.* 11 (4) (1982) 676–686.
- [17] W. Shang, F. Yao, P. Wan, X. Hu, On minimum m -connected k -dominating set problem in unit disc graphs, *J. Comb. Optim.* 16 (2) (2008) 99–106.
- [18] T. Nieberg, J. Hurink, A PTAS for the minimum dominating set problem in unit disk graphs, in: *International Workshop on Approximation and Online Algorithms*, Springer, 2005, pp. 296–306.