

Domination in Unit Disk Graphs

Nieberg and Hurink [?] proposed a polynomial-time approximation scheme (PTAS) for the Minimum Dominating Set problem in Unit Disk Graphs (UDGs) that does not rely on the geometric representation of the graph, achieving a $(1 + \varepsilon)$ -approximation in time $n^{O(1/\varepsilon \log(1/\varepsilon))}$, and also providing a robustness feature by either returning a valid solution or a certificate that the input is not a UDG.

Semi-total Domination in Unit Disk Graphs

Authors: Sasmita Rout, Gautam Kumar Das

Published in: CALDAM 2024 (LNCS 14508)

DOI: 10.1007/978-3-031-52213-0_9

1. Problem Studied

- The paper studies the **Semi-total Dominating Set (STDS)** problem in Unit Disk Graphs (UDGs).
- A set $D_{t2} \subseteq V$ is a STDS if:
 1. D_{t2} is a dominating set.
 2. For every $u \in D_{t2}$, there exists $v \in D_{t2}$ such that $\text{dist}(u, v) \leq 2$.

2. Motivation and Applications

- STDS is a natural variant lying between classical dominating sets and total dominating sets.
- Relevant in wireless networks and sensor placements where both coverage and minimal connectivity are required.

3. Main Contributions

- Proved that the STDS problem is **NP-complete** in UDGs via a reduction from Vertex Cover on planar graphs.
- Proposed a **6-factor approximation algorithm** for STDS in UDGs.
- Introduced a **$2 + \ln(D+1)$** approximation for general graphs, improving over the previous bound of **$2 + 3\ln(D+1)$** .
- Showed that a PTAS for STDS in UDGs exists with an approximation factor of $2 + \varepsilon$.

4. Techniques Used

- **NP-Completeness:** Used grid embedding and geometric gadget constructions to simulate vertex cover behavior.
- **Approximation Algorithm:**
 1. Compute a maximal independent set D .

2. For each vertex in D lacking a neighbor within distance 2 in D , add a neighbor from $N(u)$ to set T .
3. Return $D \cup T$ as the semi-total dominating set.

5. Results Summary

Graph Type	Approach	Approx. Factor	Time Complexity
UDG	Greedy + Local Fix	6	$O(nk)$
UDG (PTAS)	Local Search + Packing	$2 + \varepsilon$	$n^{O(1/\varepsilon \log \varepsilon)}$
General Graph	Set Cover-Based	$2 + \ln(D + 1)$	—

6. Comparison with Prior Work

- Improves over the $2 + 3 \ln(D + 1)$ result from Henning and Pandey (2019).
- The first work to give a dedicated algorithm and complexity result for STDS in UDGs.
- Relates to: $\gamma(G) \leq \gamma_{t2}(G) \leq \gamma_t(G)$.

7. Limitations / Assumptions

- Assumes no isolated vertices.
- Requires geometric embedding (disk centers must be known).
- Maximal independent set construction may not be efficient for very large or distributed settings.