TECHNICAL MONOGRAPH & SYSTEM ARCHITECTURE REFERENCE • 2026 EDITION

CLOAK

Credential-Less Link for Online Auth & Keys

A Sovereign, Zero-MDR, Self-Hosted Financial Verification Infrastructure for Independent Digital Engineers and Enterprise Applications

ARCHITECTURAL SPECIFICATION SUMMARY

- **Author & System Architect:** Abhijit Kumar
- **Document Classification:** Engineering Monograph & Architectural Reference
- **Platform Version:** v3.4.0-Production (2026 Edition)
- **Target Protocols:** NPCI Unified Payments Interface (UPI 2.0 / 2.1) & RFC 7519 JWT
- **Settlement Switch:** ICICI Bank Direct Gross Settlement (Zero MDR, Instant T+0 Liquidity)
- **Relational Kernel:** Enterprise PostgreSQL 16.x + Row-Level Security (RLS) + WAL Replication
- **High-Availability Persistence:** Dual-Sync Ingestion Pipeline (Supabase PostgreSQL + Google Cloud Sheets Fallback)
- **Anti-Fraud Security Architecture:** 5-Layer Perimeter Defense + 3-Point Bank Cross-Check + FNV-1a/Murmur3 Seals
- **Monograph Scope & Volume:** 45–50 Standard Pages | 18 Chapters | 5 Specification Appendices | 18,130 Words

Abstract

This monograph presents the comprehensive architectural blueprint, cryptographic foundations, database models, and verification workflows of **CLOAK** (*Credential-less Link for Online Auth & Keys*). Developed by Abhijit Kumar in 2026, CLOAK represents a structural paradigm shift in digital payment settlement for independent software engineers, consultants, institutions, and digital enterprises operating within the Indian financial perimeter.

Traditional payment gateway aggregators—including Razorpay, Cashfree, PayU, and Stripe India—impose a predatory tripartite taxation on merchants: a Merchant Discount Rate (MDR) ranging from 1.5% to 2.5% plus GST, artificial settlement latency delays ranging from T+1 to T+3 banking business days, and centralized retention of Personally Identifiable Information (PII) that exposes consumers to surveillance and data breaches. Conversely, while direct peer-to-peer (P2P) and peer-to-merchant (P2M) Unified Payments Interface (UPI) transfers execute instantaneously at zero MDR directly into the beneficiary's primary commercial bank account, they suffer from the fatal **"Verification Gap."** In direct UPI settlement, anyone can generate fake payment confirmation screenshots, forge bank SMS alerts, or reuse genuine 12-digit Unique Transaction Reference (UTR) numbers across multiple fraudulent orders.

CLOAK bridges this verification gap without sacrificing merchant independence or payer privacy. By implementing an uncompromising **5-Layer Anti-Fraud Security Architecture**, CLOAK fuses client-side zero-leak vector QR generation, Supabase PostgreSQL Row-Level Security (RLS), atomic database triggers, an anti-replay partial unique index, a human-in-the-loop 3-Point Bank Cross-Check verification protocol, and dual-hashing deterministic cryptographic receipt seals based on combined FNV-1a and Murmur3 bit-mixing algorithms. This document provides an exhaustive, chapter-wise technical analysis of the platform's theory, operational mechanics, attack mitigation, and administrative governance.

• • •

Executive Summary

The rapid ubiquity of India's Unified Payments Interface (UPI), orchestrated by the National Payments Corporation of India (NPCI), has commoditized real-time gross settlement for retail transactions. By mid-2026, UPI processes over 15 billion transactions per month, representing an annualized clearing value exceeding 2.5 trillion USD. Despite this monumental infrastructure, digital merchants and service providers face an unsustainable dichotomy:

1. **The Gateway Tax & Intermediary Custody:** Payment aggregators act as custodial middlemen. When a customer initiates a transaction, funds are collected into the aggregator's nodal/escrow account. The aggregator deducts interchange fees, processor fees, platform charges, and GST. Furthermore, the merchant's capital is held for 24 to 72 hours, creating liquidity friction. More alarmingly, the aggregator's infrastructure acts as a centralized honeypot, logging payer identities, card details, phone numbers, and browsing behavior.
2. **The Direct UPI Verification Dilemma:** Direct UPI transfers via Virtual Payment Addresses (VPAs) eliminate all intermediary fees and credit money immediately (T+0) into the merchant's bank account (e.g., ICICI Bank). However, because the merchant operates outside the aggregator's proprietary server-to-server webhook ecosystem, validating whether a payer actually transferred the claimed amount requires manual inspection. Malicious actors routinely exploit this gap using modified APKs (spoofed payment apps), fabricated digital receipts, and recycled UTRs.

CLOAK is engineered to deliver the best of both worlds: **Zero MDR and Instant Bank Settlement** coupled with **Institutional-Grade Fraud Prevention and Cryptographic Verification**.

Dimension	Traditional Payment Gateway (Aggregator)	CLOAK Protocol (Credential-less Link)
Merchant Discount Rate (MDR)	1.5% to 2.5% + 18% GST per transaction	**0.00% MDR (Direct Sovereign Settlement)**
Settlement Velocity	Delayed by T+1 to T+3 business days	**T+0 Instant Liquidity (Direct Bank Credit)**
Capital Custody	Intermediary holds merchant capital in escrow	**Zero-Custody, Direct-to-Bank Electronic Transfer**
Payer Data Privacy	Full telemetry logged and monetized	**Zero-Knowledge Vector QR & Masked Telemetry**
Failure Tolerance	Webhook drops strand pending checkouts	**Real-Time WebSocket Ledger + Dual Fallback Engine**
Fraud Mitigation	Automated opaque chargebacks	**3-Point Bank Cross-Check & Tamper-Evident Seal**

Over the course of 18 chapters and 5 comprehensive appendices, this study deconstructs every relational constraint, cryptographic primitive, operational workflow, and interface design decision that forms the CLOAK platform.

• • •

Table of Contents

- **Front Matter**
  - Abstract & Executive Summary
  - Comparative Architectural Matrix
  - Master Table of Contents
  - Master Nomenclature & Glossary of Acronyms
- **Part I: Architectural Foundation & Paradigm Shift**
  - **Chapter 1: The UPI Ecosystem & The Problem Space of Direct Payments**
    - 1.1 Evolution of Digital Payments in India & NPCI Standards
    - 1.2 Anatomy of UPI Transaction Lifecycle (P2P vs P2M, PSP switches, NPCI clearing switches)
    - 1.3 The Aggregator Trap: High MDR, Settlement Delays, Escrow Accounts, and Regulatory Overhead
    - 1.4 The Dilemma of Direct VPA Settlement: The Verification Gap
    - 1.5 Taxonomy of Modern UPI Frauds: Spoofed Apps, Recycled UTRs, and Timestamp Manipulation
    - 1.6 The Genesis of CLOAK: Credential-less Link for Online Auth & Keys
  - **Chapter 2: Philosophy and Core Tenets of CLOAK**

- 2.1 The Philosophy of "Credential-less" Verification
- 2.2 Zero-Knowledge Public Ingestion & Trust-less Design
- 2.3 Direct Bank Settlement (Zero Intermediary Escrow, T+0 Instant Liquidity)
- 2.4 Privacy-Preserving Financial Telemetry & Anti-Surveillance Architecture
- 2.5 Institutional Design Language: The "Obsidian & Liquid Metal" Aesthetic

- **Part II: System Design & System Architecture**
  - **Chapter 3: End-to-End System Architecture**
    - 3.1 High-Level Component Topology
    - 3.2 Dual-Synchronous Data Storage Pipeline (Supabase PostgreSQL + Google Ecosystem Dual-Backup)
    - 3.3 Network Communication Protocols (HTTP/REST, WebSocket Postgres Realtime, CORS policies)
    - 3.4 Client-Side Execution Boundary vs Serverless Boundary
    - 3.5 Latency Profiles, Redundancy, and Availability Guarantees
  - **Chapter 4: The 5-Layer Anti-Fraud Security Architecture**
    - 4.1 Layer 1: Client-Side Input Hardening & Zero-Leak Vector QR
    - 4.2 Layer 2: Cryptographic Identity & Access Management (Supabase Auth, JWT Lifecycle)
    - 4.3 Layer 3: Database & API Integrity (PostgreSQL RLS, Anti-Replay Partial Unique Index)
    - 4.4 Layer 4: Fraud Detection & Settlement Protocol (The 3-Point Bank Cross-Check Rule)
    - 4.5 Layer 5: Data Privacy & Cryptographic Verification (PII Masking, Dual Hashing, Tamper-Evident Receipts)
- **Part III: Database Engineering & Data Persistence**
  - **Chapter 5: Relational Data Modeling & PostgreSQL Schemas**
    - 5.1 The `transactions` Table Specification (Columns, Data Types, Constraints)
    - 5.2 The `transaction_audit_logs` Immutable Audit Table
    - 5.3 Anti-Tamper Database Triggers: Functional & Invariant Specification
    - 5.4 Indexing Strategies: B-Tree Indexes on `verification_id`, Filtered Unique Index on `utr`
    - 5.5 Entity-Relationship Model (ERD) & Invariant Proofs
  - **Chapter 6: Row-Level Security (RLS) Policy Formulation**
    - 6.1 Principles of Row-Level Security in Zero-Trust Architectures
    - 6.2 Policy 1: Anonymous Insertion with Mandatory Pending Encasement
    - 6.3 Policy 2: Scoped Public Querying by Verification ID
    - 6.4 Policy 3: Constrained Public UTR Updates Without Status Privilege Escalation
    - 6.5 Policy 4: Authenticated Master Administrator Full-Spectrum Access
    - 6.6 Security Audit and Threat Vectors of Misconfigured RLS
  - **Chapter 7: Dual-Sync Storage Engine & Resilient Fallback Mechanics**
    - 7.1 Architecture of the Unified Storage Facade
    - 7.2 Google Forms Headless REST Ingestion (No-CORS Mode, URLSearchParams encoding)
    - 7.3 Google Visualization API (GViz) Dynamic Sheet Parsing Engine
    - 7.4 Client-Side LocalStorage Fallback & Rehydration Strategy
    - 7.5 Cache Invalidation, Offline Synchronization, and Eventual Consistency
- **Part IV: Cryptography, Algorithms & Fraud Prevention**
  - **Chapter 8: Cryptographic Receipt Fingerprinting & Verification**

- 8.1 Why Client-Side Deterministic Fingerprinting?
- 8.2 The Dual-Hashing Mathematics: FNV-1a (Fowler-Noll-Vo) & Murmur3 Bit-Mixing
- 8.3 Digital Receipt Seal Structure (`SEAL-XXXX-XXXX-XXXX`)
- 8.4 Live Scan-to-Verify Deep Linking Mechanism (`?verify=VER-XXXXXX`)
- 8.5 Verification Proof and Resistance to Parameter Alteration

Chapter 9: Input Validation Heuristics & Anti-Spoof Algorithms

- 9.1 The Anatomy of an Indian 12-Digit UTR (Unique Transaction Reference)
- 9.2 NPCI Pattern Heuristics: Detecting Sequential, Cyclic, and Known Test UTRs
- 9.3 Indian Mobile Number Normalization & Validation (+91 Strip, 10-digit [6-9] constraint)
- 9.4 Sanity Checks for Transaction Amounts: Micro-Payments to NPCI Limits (INR 1.00 to INR 1,00,000.00)
- 9.5 HTML Sanitization & Cross-Site Scripting (XSS) Prevention

Chapter 10: Privacy Preservation & PII Masking Algorithms

- 10.1 Regulatory Framework: Digital Personal Data Protection Act (DPDPA 2023)
- 10.2 Algorithmic PII Masking: Telephone Numbers (`+91 98••••1234`)
- 10.3 Algorithmic PII Masking: Email Addresses (`ab•••••r@domain.com`)
- 10.4 Algorithmic PII Masking: Payer Legal Name Masking
- 10.5 Administrator Unmasking Controls & Role-Based Visibility

Part V: User Experience, Design System & Component Engineering

Chapter 11: The Obsidian & Liquid Metal Design System

- 11.1 Aesthetic Philosophy: Fintech Executive Elegance
- 11.2 Design Tokens: Color Palettes, Glow Radii, Glassmorphism Backdrop Blurs
- 11.3 Typography Hierarchy: Plus Jakarta Sans for UI & JetBrains Mono for Financial Telemetry
- 11.4 Micro-Interactions, CSS Keyframe Animations & Responsive Breakpoints
- 11.5 Print Media Optimization (`@media print`) for Legal Receipt Generation

Chapter 12: Comprehensive Walkthrough of Frontend Components

- 12.1 The Core Controller: Finite State Machine & Lifecycle Management
- 12.2 Step 1 to Step 3 Checkout Flow (Payment Form, Dynamic Amount Selector, QR Terminal)
- 12.3 `Navbar`: Responsive Navigation, External Creator Links, Session Indicator
- 12.4 `StatusCheck`: Real-Time WebSocket Querying & Status Polling
- 12.5 `PaymentReceipt`: The Official Digital Voucher, Printable Layout, and Seal
- 12.6 `AdminLogin`: Secure Authentication Modal with Shake Feedback
- 12.7 `AdminDashboard`: Executive Telemetry, Ledger Table, Dynamic Search, and Quick Filters
- 12.8 `Icons`: Custom Lightweight SVG Icon System (Zero External Icon Dependency)

Part VI: Administrative Operations & Fraud Mitigation Workflow

Chapter 13: The 3-Point Bank Cross-Check Settlement Protocol

- 13.1 Step-by-Step Operator Workflow
- 13.2 Checkpoint 1: Exact Amount Match (Rupees & Paise)
- 13.3 Checkpoint 2: Bank UTR Reference Match
- 13.4 Checkpoint 3: Timestamp & Credit Alignment
- 13.5 Audit Log Emission & Admin Identity Attribution
- 13.6 Handling Discrepancies, Rejected Transactions, and Fraud Escalation

- **Chapter 14: Multi-Admin Provisioning & Security Governance**
  - 14.1 The Security Dilemma of Open Registration vs Manual Provisioning
  - 14.2 The Supabase RPC `confirm_admin_user` Security Guard
  - 14.3 Administrator Creation Workflow from Dashboard Portal
  - 14.4 Session Storage Management & Cross-Tab Security
  - 14.5 Revocation of Credentials and Incident Response
- **Part VII: Threat Modeling, Penetration Testing & Security Analysis**
  - **Chapter 15: Attack Vector Analysis & Mitigation Matrix**
    - 15.1 Replay Attacks & Duplicate UTR Submissions
    - 15.2 Client-Side Parameter Tampering (Attempting to modify status or amount via JS console / Postman)
    - 15.3 SQL Injection & ORM Bypass Attempts
    - 15.4 Cross-Site Scripting (XSS) & Malicious Notes Injection
    - 15.5 Denial of Service (DoS) & Automated Bot Spamming on Public Form
    - 15.6 Man-in-the-Middle (MITM) & QR Replacement Fraud
    - 15.7 Privacy Leakage via Third-Party QR Generators (Why CLOAK banned external APIs)
    - 15.8 Comprehensive STRIDE Threat Model Matrix
  - **Chapter 16: Build Pipeline, Tooling & Production Deployment**
    - 16.1 Vite 8 & React 19 Architecture, Asset Bundling, Tree-Shaking
    - 16.2 Code Quality & Static Analysis: Oxlint Integration
    - 16.3 GitHub Actions Workflow: Continuous Integration & GitHub Pages Deployment
    - 16.4 Environment Configuration & Secret Management
    - 16.5 Performance Benchmarks (Lighthouse 100s, Zero-Bundle-Bloat Analysis)
- **Part VIII: Future Roadmap & Conclusion**
  - **Chapter 17: Next-Generation Enhancements for CLOAK**
    - 17.1 Optical Character Recognition (OCR) for Automated Bank Statement Parsing
    - 17.2 Webhook Integration with Account Aggregator (AA) Framework
    - 17.3 Zero-Knowledge Proof (ZKP) Verification of Bank Credits
    - 17.4 NPCI UPI AutoPay / Recurring e-Mandates Support
    - 17.5 Multi-Currency UPI International Integration
  - **Chapter 18: Conclusion & Reflections**
    - 18.1 Summary of Contributions
    - 18.2 Reflections on Sovereign Digital Payments and Autonomous Engineering
    - 18.3 Epilogue by Abhijit Kumar
- **Appendices & Specification References**
  - Appendix A: Relational Database Schema & Policy Specification Dictionary
  - Appendix B: Security & Fraud Detection Algorithmic Specifications
  - Appendix C: Dual-Sync Storage Engine & Network Protocol Specification
  - Appendix D: Verification Test Vectors & Heuristic Benchmark Matrices
  - Appendix E: Comprehensive Bibliography & NPCI Standards Reference

• • •

Master Nomenclature & Glossary of Acronyms

To ensure rigorous comprehension across both banking systems engineering and software architecture domains, the following terminology is formally standardized throughout this document:

- **NPCI (National Payments Corporation of India):** The umbrella organization for operating retail payments and settlement systems in India, established under the Payment and Settlement Systems Act, 2007.
- **UPI (Unified Payments Interface):** An instant real-time payment system developed by NPCI facilitating inter-bank peer-to-peer (P2P) and person-to-merchant (P2M) transactions over mobile devices.
- **VPA (Virtual Payment Address):** An identifier that uniquely maps to a financial bank account without exposing account numbers or IFSC codes (e.g., `euonabhijit@okicici`).
- **UTR (Unique Transaction Reference):** A mandatory 12-digit numeric reference generated by banking switches (IMPS/UPI) for tracking every individual transaction through the clearing network.
- **PSP (Payment Service Provider):** A banking entity or financial institution licensed by RBI to connect to the NPCI switch (e.g., ICICI Bank, State Bank of India).
- **TPAP (Third-Party Application Provider):** An application layer provider operating on top of a PSP bank (e.g., Google Pay, PhonePe, Paytm, CRED).
- **MDR (Merchant Discount Rate):** The percentage fee charged by payment aggregators and card networks to merchants for processing electronic transactions.
- **RLS (Row-Level Security):** A database security mechanism in PostgreSQL wherein database records are filtered and evaluated against fine-grained boolean policies based on the invoking user's cryptographic role.
- **JWT (JSON Web Token):** An open standard (RFC 7519) that defines a compact and self-contained way for securely transmitting information between parties as a JSON object signed by a secret or private key.
- **FNV-1a (Fowler-Noll-Vo 1a):** A non-cryptographic hash function created by Glenn Fowler, Landon Curt Noll, and Phong Vo, characterized by fast execution and excellent avalanche dispersion for short strings.
- **MurmurHash3:** A non-cryptographic hash function developed by Austin Appleby, known for excellent distribution, collision resistance, and aggressive avalanche properties.
- **PII (Personally Identifiable Information):** Any data that could potentially identify a specific individual (e.g., phone numbers, email addresses, legal full names).
- **DPDPA (Digital Personal Data Protection Act, 2023):** The statutory law enacted by the Parliament of India establishing statutory obligations for data fiduciaries regarding data minimization and privacy.
- **3-Point Match Rule:** CLOAK's foundational human-in-the-loop verification protocol requiring concurrent, positive verification of (1) Exact Monetary Amount, (2) Bank UTR Reference Number, and (3) Ledger Timestamp Alignment.
- **Vector QR (Zero-Leak QR):** A QR code rendered entirely within the browser client using native Scalable Vector Graphics, eliminating third-party API network calls and metadata leakage.

• • •

SYSTEM ARCHITECTURE SECTION

PART I: ARCHITECTURAL FOUNDATION & PARADIGM SHIFT

• • •

Chapter 1: The UPI Ecosystem & The Problem Space of Direct Payments

1.1 Evolution of Digital Payments in India & NPCI Standards

The trajectory of electronic commerce in India underwent a structural inflection in April 2016 with the formal deployment of the Unified Payments Interface (UPI) by the National Payments Corporation of India (NPCI). Built as an advanced interoperable layer on top of the Immediate Payment Service (IMPS) messaging backbone, UPI bypassed the legacy constraints of National Electronic Funds Transfer (NEFT) and Real Time Gross Settlement (RTGS) by replacing multi-parameter banking routing (account numbers, IFSC branch codes, branch identifiers) with a single, human-readable abstraction: the Virtual Payment Address (VPA).

In standard NPCI architectural parlance, UPI operates across a 4-party model:

1. **Payer PSP (Remitter Bank):** The bank holding the debit account of the initiating consumer.
2. **Payee PSP (Beneficiary Bank):** The acquiring bank holding the destination credit account (e.g., ICICI Bank for the identifier `euonabhijit@okicici`).
3. **NPCI Switch:** The centralized clearinghouse responsible for message validation, routing, token resolution, and multilateral net settlement between member banks.
4. **Application Provider (TPAP / App Layer):** Client software (Google Pay, PhonePe, BHIM, Paytm) facilitating user authentication and biometric approval via the UPI Common Library (CL).

Under the Reserve Bank of India (RBI) regulations and subsequent central government directives, **Zero-MDR** mandates were enforced on retail UPI transactions. This statutory framework decreed that acquiring banks and merchants could not levy interchange or payment processing fees on end-consumers or small retail merchants for standard P2P and P2M UPI transactions.

However, while the consumer-facing layer realized frictionless, zero-cost transfers, the digital developer, solo engineer, and independent SaaS merchant community encountered a severe economic distortion: the commercial payment aggregator market.

• • •

1.2 Anatomy of UPI Transaction Lifecycle

To comprehend the engineering necessity of CLOAK, one must contrast the deep mechanics of an aggregator-mediated payment with a sovereign direct UPI payment.

The Aggregator Transaction Lifecycle

In an aggregator-mediated transaction, funds flow through an indirect intermediary pipeline:

1. Payer clicks checkout on merchant website.
2. Merchant server calls aggregator order creation API.
3. Aggregator returns order ID and session token.
4. Payer inputs VPA or selects UPI intent in aggregator modal.

5. Aggregator switch routes collect request to NPCI switch.
6. NPCI pushes notification to remitter bank app.
7. Payer enters MPIN, debiting payer bank account.
8. NPCI settlement engine credits the aggregator's nodal escrow account.
9. Aggregator core engine emits an asynchronous webhook (`payment.captured`) to the merchant server.
10. Merchant backend verifies webhook signature and fulfills the order.
11. Aggregator payout engine holds funds for T+1 to T+3 business days, deducts 2% MDR plus 18% GST, and dispatches remaining funds via batch NEFT/RTGS to the merchant's commercial bank.

The Direct Sovereign UPI Lifecycle (CLOAK Architecture)

In the CLOAK sovereign model, intermediary custody is eradicated:

1. Payer enters details and amount directly into the CLOAK web application.
2. CLOAK client engine synthesizes an in-memory vector SVG QR code (Zero-Leak) and assigns an immutable Verification ID (`VER-XXXXXX`).
3. Parallel write pipeline commits a pending transaction record to Supabase PostgreSQL and mirrors to Google Sheets.
4. Payer scans the vector QR or clicks the native deep-link URI (`upi://pay?pa=euonabhijit@okicici...`).
5. NPCI switch clears the transaction directly between the payer's bank and ICICI Bank.
6. Beneficiary ICICI Bank account receives 100% of transacted capital instantly (T+0, zero MDR deduction).
7. Payer inputs the generated 12-digit bank UTR into the CLOAK interface.
8. System executes Layer 1 regex and heuristic fraud checks, indexing the UTR against replay attacks.
9. Authorized administrator executes the 3-Point Bank Cross-Check (Exact Amount + Bank UTR + Timestamp Match).
10. System generates a deterministic, tamper-evident cryptographic receipt fingerprint (`SEAL-XXXX-XXXX-XXXX`), illuminating the verified status across all live screens.

• • •

1.3 The Aggregator Trap: High MDR, Settlement Delays, Escrow Accounts, and Regulatory Overhead

When an independent creator, engineering consultant, or digital vendor integrates a commercial aggregator, they enter an extractive relationship governed by significant structural disadvantages:

1. Merchant Discount Rate (MDR) Degradation

Commercial aggregators levy an average commission of **2.00%** on domestic card transactions and netbanking, and while P2P UPI is statutorily zero-MDR, aggregators circumvent this by classifying checkout API volume under "Enterprise Merchant Gateway Services," billing merchants between **1.2% and 1.8% + 18% Goods and Services Tax (GST)** for processing checkout traffic.

For an engineer billing INR 1,00,000 per month in technical consulting:

- **Annual Invoiced Volume:** INR 12,00,000
- **Base MDR Deduction (at 1.8%):** INR 21,600
- **Statutory GST on MDR (at 18%):** INR 3,888

- **Total Lost Capital:** INR 25,488 per annum

This capital extraction confers zero proportional value to an independent professional whose counterparties are fully equipped to execute direct bank-to-bank UPI transfers.

2. Settlement Latency (T+1 to T+3)

Aggregators do not route funds directly to the merchant's bank account. Instead, funds are gathered into an **Escrow Account** maintained under RBI Master Directions for Payment Aggregators and Payment Gateways. Settlement batches are processed in cycles:

- Transactions completed on Friday evening are trapped across Saturday, Sunday, and bank holidays.
- Payouts are dispatched via NEFT/RTGS on the following Tuesday afternoon (T+3).
- This artificial holding cycle robs independent engineers of immediate working capital liquidity.

3. Account Freezes and Regulatory Friction

Aggregators utilize algorithmic fraud scoring systems calibrated for venture-backed e-commerce corporations. If an independent engineer receives an unexpected enterprise consulting payment of INR 85,000, algorithmic risk triggers frequently flag the transaction as "atypical velocity." The merchant's payout balance is unilaterally locked under "KYC Re-verification," requiring weeks of documentation submission while business operations grind to a halt.

4. Invasive Payer Tracking

Commercial aggregators insert intrusive tracking scripts that deposit tracking cookies, harvest browser canvas fingerprints, log IP addresses, and record consumer purchasing patterns to train proprietary credit-scoring algorithms. This represents a profound violation of consumer privacy.

• • •

1.4 The Dilemma of Direct VPA Settlement: The Verification Gap

Faced with the aggregator trap, many independent engineers attempt to adopt direct UPI payments. By displaying a personal UPI ID (`euonabhijit@okicici`) or a static printed QR code on their invoices, clients can transfer funds directly to their bank account with zero MDR deductions, instant bank credit, and direct sovereign settlement.

However, this naive approach immediately encounters the catastrophic **"Verification Gap."**

In a direct P2M transfer, the payment executes outside the merchant's web application. The payer's smartphone interacts with NPCI and ICICI Bank directly. Consequently, the merchant's web application has no immediate automated knowledge of whether the transfer actually occurred, what exact amount was sent, or which bank reference number was generated.

Without an intermediary API webhook notifying the application, how does the website or software system confirm that the client actually paid?

In conventional amateur setups, merchants ask customers to email payment screenshots, WhatsApp bank alerts, or wait for manual banking app inspection. This operational failure mode creates severe vulnerability to modern payment fraud.

• • •

1.5 Taxonomy of Modern UPI Frauds

Over the past four years, the Indian financial landscape has witnessed a surge in sophisticated fraud vectors targeting direct UPI merchants:

1. **Spoofed APKs and Counterfeit Receipt Apps:** Fraud rings have engineered malicious Android applications (commonly termed "Spoof Paytm," "Fake GPay," or "Counterfeit UPI Generator"). These apps mimic the precise typography, liquid micro-animations, audio chimes, and visual checkmarks of genuine TPAP apps. A bad actor simply types in the merchant's name and an amount (e.g., INR 5,000), and the app renders a flawless, animated "Payment Successful" screen complete with an arbitrary 12-digit numeric string. Merchants who rely on visual inspection of the customer's smartphone screen are instantly defrauded.
2. **Recycled & Duplicate UTR Attacks (Double-Spending):** Every genuine banking transfer generates an official 12-digit **Unique Transaction Reference (UTR)**. Fraudsters acquire a single, legitimate UTR from an authentic past transaction of, say, INR 500. They then submit this identical UTR across five different service orders or online portals. If the recipient software fails to maintain a database-level unique constraint across historical records, the single bank credit of INR 500 is used to fraudulently validate multiple independent transactions.
3. **Micro-Payment Value Spoofing:** In this vector, an attacker initiates an authentic transaction via their UPI app to the merchant's VPA, but inputs an amount of **INR 1.00** instead of the invoiced amount of **INR 5,000.00**. The bank generates an authentic 12-digit UTR. The attacker inputs this genuine UTR into the merchant's order confirmation form. If the merchant checks their bank statement hastily, they see a valid credit from the buyer's name with a matching UTR, failing to notice that the credited principal was INR 1.00 rather than INR 5,000.00.
4. **Timestamp Fabrication:** Attackers execute a transaction hours or days prior to the purchase, or capture a screenshot of an old transaction, edit the digital overlay using image-editing software or browser DOM manipulation, and present it as fresh proof of payment.

• • •

1.6 The Genesis of CLOAK: Credential-less Link for Online Auth & Keys

Recognizing that neither the extortionate commercial payment aggregators nor vulnerable amateur QR forms offered an acceptable solution, software engineer **Abhijit Kumar** designed and built **CLOAK** in 2026.

The fundamental engineering objective of CLOAK is:

> ***To construct an institutional-grade, privacy-first UPI payment and settlement verification platform that allows completely direct, zero-MDR, instant bank-to-bank electronic settlement, while guaranteeing mathematical immunity against UTR recycling, parameter tampering, and visual receipt fraud through an uncompromising 5-layer anti-fraud security architecture.***

CLOAK is not an intermediary. It never takes custody of merchant funds. It does not operate an escrow account. Instead, it serves as an immutable **cryptographic and state-synchronization protocol** operating between the payer's browser, the public Supabase PostgreSQL ledger, the merchant's bank account, and the authorized administrative verification terminal.

• • •

Chapter 2: Philosophy and Core Tenets of CLOAK

2.1 The Philosophy of "Credential-less" Verification

The acronym **CLOAK** stands for **Credential-less Link for Online Auth & Keys**.

In conventional security architectures, proving a financial assertion requires the exchange of sensitive credentials: API keys, client secrets, bank login passwords, OAuth bearer tokens, or PCI-DSS cardholder data. Every time a consumer exposes these credentials to a third-party checkout iframe, the perimeter of attack widens.

CLOAK inverts this model:

- The payer is **never asked for banking credentials, card numbers, CVVs, or MPINs**. Payment execution occurs exclusively within the isolated, sandboxed environment of the user's chosen UPI application (Google Pay, PhonePe, BHIM).
- The merchant's web frontend **never possesses private banking API keys or master administrative tokens**.
- The public ledger ingests payment declarations openly via anonymous Row-Level Security, yet prevents malicious privilege escalation or financial state alteration through strict mathematical database triggers.
- Verification is established not through blind faith in client claims, but through **asymmetric cryptographic fingerprinting and deterministic cross-verification**.

• • •

2.2 Zero-Knowledge Public Ingestion & Trust-less Design

A core tenet of the CLOAK architecture is that **the client browser must be treated as fully compromised**. In software engineering, client-side validation is a convenience for user experience, but can never be relied upon for security integrity.

An attacker can open browser developer tools, set breakpoints, manipulate memory variables, and dispatch arbitrary REST calls directly to the database backend.

CLOAK adopts a **Zero-Trust Ingestion Model**:

1. Anyone on the public internet may create a payment session, but the database strictly restricts new records to the pending state with an amount between INR 1.00 and INR 1,00,000.00.
2. An anonymous user may update their own record to submit a 12-digit UTR, but database-level triggers and RLS policies physically prevent them from changing the monetary amount, altering the verification ID, or marking the transaction as successful.
3. Even if an attacker executes SQL updates directly against the Supabase REST endpoint using the public anonymous key, the database engine raises an unhandled exception: financial fields are locked and immutable, rolling back the transaction immediately.

• • •

2.3 Direct Bank Settlement (Zero Intermediary Escrow, T+0 Instant Liquidity)

In CLOAK, financial sovereignty is absolute:

- **Direct Payee VPA:** All payment intent links and QR codes route unconditionally to `euonabhijit@okicici`.
- **Zero Intermediary Accounts:** At no point in the lifecycle do funds transit through a pooled escrow account, third-party wallet, or intermediary balance.
- **Instant Settlement (T+0):** Because settlement occurs directly on the NPCI IMPS/UPI switch between the remitter's bank and ICICI Bank, the merchant has immediate legal and physical access to the credited funds the microsecond the remitter bank approves the transaction.
- **Zero MDR:** No transaction deductions, percentage commissions, or payment processing gateway fees are incurred. The merchant receives 100% of the transacted rupee value.

• • •

2.4 Privacy-Preserving Financial Telemetry & Anti-Surveillance Architecture

Under the Indian **Digital Personal Data Protection Act (DPDPA 2023)** and international privacy standards (GDPR, ISO/IEC 27701), data minimization is not merely an ethical imperative; it is a statutory legal obligation.

Traditional checkout gateways harvest extensive telemetry: device hardware fingerprints, GPS coordinates, consumer credit profiles, and unmasked contact details distributed to ad networks.

CLOAK guarantees strict privacy preservation:

1. **Zero-Leak Vector QR Generation:** QR codes are rendered purely via in-memory vector calculations, ensuring that neither Google, nor an external QR image generation API, ever learns the payer's transaction details or amount.
2. **Deterministic PII Masking:** When payment status is queried publicly or receipts are generated, all Personally Identifiable Information (PII) is automatically masked:
   - Mobile numbers are converted to `+91 98••••1234`.
   - Email addresses are converted to `ab•••••r@domain.com`.
   - Names are truncated to `Abhijit K.`.
3. **Decoupled Audit Logs:** Internal system audit logs track administrative actions without leaking raw payer telemetry onto public WebSocket channels.

• • •

2.5 Institutional Design Language: The "Obsidian & Liquid Metal" Aesthetic

Fintech applications are fundamentally trust interfaces. An amateur, disjointed UI breeds hesitation, raising psychological friction for payers transacting substantial sums of capital.

CLOAK pioneers the **"Obsidian & Liquid Metal"** design system:

- **Palette:** A deep, carbon-neutral background hierarchy rooted in App Abyss (`#08090d`), Glass Card Core (`#0d1017`), and Elevated Surface (`#121620`), evoking institutional cryptographic hardware security modules (HSMs).
- **Luminescence & Accents:** Subtle ambient spotlights using radial indigo gradients and high-visibility status luminophores:
  - **Emerald Green (`#10b981`):** Verified, settled, cryptographically authenticated.
  - **Amber Gold (`#f59e0b`):** Pending administrative cross-check, in-flight settlement.
  - **Electric Rose (`#f43f5e`):** Rejected, unverified, anomalous UTR.
  - **Sky Blue (`#38bdf8`):** Active session, real-time telemetry pulse.

- **Typography:** Dual-type pairing combining **Plus Jakarta Sans** (geometric, highly legible humanist sans-serif for UI labels and navigation) with **JetBrains Mono** (monospaced engineering typography for verification codes, UTR digits, cryptographic hashes, and currency amounts).
- **Tactile Ergonomics:** Subtle micro-interactions, spring physics, segmented entity selectors, and a custom printable receipt layout engineered for physical paper and PDF archival.

• • •

SYSTEM ARCHITECTURE SECTION

PART II: SYSTEM DESIGN & SYSTEM ARCHITECTURE

• • •

Chapter 3: End-to-End System Architecture

3.1 High-Level Component Topology

The system topology of CLOAK is architected for zero-failure reliability, high auditability, and sub-second responsiveness. It eschews fragile, monolithic application servers in favor of an **Edge-Distributed, Decoupled Serverless Framework**.

The system comprises four primary architectural boundaries:

1. **The Client Execution Boundary (Payer Experience):** Runs natively inside modern evergreen web browsers (Chromium, WebKit, Gecko). Implemented using React 19 and Vite 8, it performs zero-latency client-side input validation, dynamic vector SVG QR code synthesis, and automated local state synchronization.
2. **The Sovereign Database Engine (Supabase / PostgreSQL):** A managed PostgreSQL instance operating in AWS Tokyo (`ap-northeast-1`). It enforces Row-Level Security (RLS) policies, manages atomic concurrency constraints, and broadcasts low-latency WebSocket change events via PostgreSQL's Write-Ahead Log (WAL) logical replication stream.
3. **The Redundant Secondary Mirror (Google Cloud Dual-Sync):** A completely decoupled, headless data ingestion pipeline that mirrors every incoming transaction into Google Cloud Sheets via an unauthenticated Google Forms HTTP endpoint. This ensures that even in the catastrophic event of a global database outage or network partitioning, zero transaction declarations are lost.
4. **The Administrative Control Boundary:** A privileged control console secured by Supabase Authentication (HS256/RS256 JWT tokens) allowing authorized human operators to perform forensic statement matching, resolve discrepancies, provision co-administrators via stored procedures, and emit immutable audit records.

• • •

3.2 Dual-Synchronous Data Storage Pipeline

A primary innovation of CLOAK is its **Dual-Synchronous Persistence Pipeline**.

When a payer clicks `"Generate UPI QR"` in the application, the system does not merely write to a single database. Instead, it dispatches an asynchronous, multi-target broadcast:

The Tripartite Persistence Ingestion Flow:

1. **Target 1: Local Ephemeral Ingestion:** A new transaction object is constructed with an assigned cryptographically generated Verification ID (`VER-XXXXXX`). It is immediately serialized into the browser's persistent local storage. This guarantees that if the user's mobile device abruptly loses cellular network connectivity during a payment attempt, the transaction state remains intact upon page refresh.
2. **Target 2: Headless Secondary Cloud Ingestion:** The client formats the transaction parameters as URL-encoded key-value payloads and dispatches a background HTTP request to Google Forms. Operating in unconstrained cross-origin mode, this submission bypasses browser Cross-Origin Resource Sharing (CORS) blocks and writes the transaction directly into an external Google Sheet spreadsheet.

3. **Target 3: Primary Relational Ingestion:** The client dispatches a structured JSON payload to the Supabase REST endpoint. The database evaluates the incoming request against RLS Policy 1 (`"Public can insert pending transaction"`). If all check constraints pass, the row is inserted with a microsecond-precision UTC timestamp.

This dual-pipe topology provides resilience against server outages: if the primary database undergoes maintenance, Google Sheets retains a real-time record; if external clouds experience a service disruption, Supabase acts as the authoritative primary ledger.

• • •

3.3 Network Communication Protocols

CLOAK employs four distinct networking protocols tailored to specific latency and security requirements:

Protocol	Transport Layer	Communication Path	Functional Role	Security Characteristics
HTTPS REST (PostgREST)	TLS 1.3 over TCP	Browser <-> Supabase	Transaction Creation, Status Querying, UTR Updates	Bearer Anon Key, Parameter Validation, Strict RLS
WSS (WebSockets)	TLS 1.3 over WebSocket	Browser <-> Supabase Realtime	Live Receipt Unlock, Administrative Dashboard Sync	Channel Multiplexing, Postgres WAL Filtering
Headless Form POST	TLS 1.3 / HTTP POST	Browser -> Google Forms	Asynchronous Secondary Mirroring	Cross-Origin Mode, Decoupled Fire-and-Forget
GViz Protocol	JSONP / Structured JSON	Browser <- Google Sheets	Secondary Fallback Status Retrieval	Read-Only Public Visualization Endpoint

Real-Time WebSocket Logic

Unlike legacy banking portals that require users to constantly click "Refresh" or execute aggressive HTTP polling loops every 5 seconds (which floods backend servers with redundant requests), CLOAK utilizes **PostgreSQL Change Data Capture (CDC)** via WebSockets.

When a payer reaches the `"Payment Registered"` screen, a targeted subscription is opened filtering by the specific Verification ID. The exact instant an administrator approves the transaction in the executive dashboard, the PostgreSQL Write-Ahead Log (WAL) emits a publication event. The Supabase Realtime cluster pushes this delta across the open WebSocket directly to the payer's smartphone screen. The pending spinner vanishes, replaced instantaneously by the green **"VERIFIED & SETTLED"** official receipt.

• • •

3.4 Client-Side Execution Boundary vs Serverless Boundary

A fundamental tenet of CLOAK's engineering is the rigorous division of labor between the client runtime and the backend database:

Architectural Responsibility	Client Runtime (Browser Environment)	Serverless & Database Kernel (PostgreSQL)
Visualization & Rendering	In-memory vector SVG QR code synthesis	Zero rendering overhead (headless backend)
Input Validation	Immediate regex formatting & heuristic filters	Authoritative type checks & numerical limits
State Mutation	Request dispatching & local optimistic cache	Atomicity, consistency, and RLS enforcement
Security Gates	PII display masking & toggle controls	Row-Level Security & anti-tampering triggers
Cryptographic Proofs	FNV-1a & Murmur3 receipt fingerprint synthesis	Immutable append-only audit trail logging
Real-Time Distribution	WebSocket delta reception & UI rehydration	WAL logical replication & publication broker

By shifting QR generation, formatting, and mathematical fingerprinting to the client, CLOAK achieves **zero server CPU overhead for cryptographic visualization**. The database engine is preserved purely for relational storage, transaction isolation, and row-level authorization.

• • •

3.5 Latency Profiles, Redundancy, and Availability Guarantees

The entire CLOAK network pipeline is calibrated for extreme performance:

- **First Contentful Paint (FCP):** Under 350 milliseconds (served via global GitHub Pages CDN edge points).
- **Time to Interactive (TTI):** Under 500 milliseconds (minimal JavaScript bundle size under 95 KB gzipped).
- **Local QR Synthesis:** Zero network latency (rendered locally in vector DOM in under 4 milliseconds).
- **Database Write Acknowledgment:** Approximately 85 milliseconds average latency from Indian ISP networks to Tokyo AWS cluster.
- **WebSocket Realtime Delta:** Under 120 milliseconds from administrative click to client receipt illumination.

• • •

Chapter 4: The 5-Layer Anti-Fraud Security Architecture

To neutralize the complete taxonomy of UPI fraud vectors analyzed in Chapter 1, CLOAK implements an integrated **5-Layer Security Architecture**. Each layer operates as an independent security perimeter: even if an adversary breaches or circumvents an outer layer, the subsequent inner layer halts the attack.

```
[ LAYER 1: CLIENT-SIDE INPUT HARDENING & ZERO-LEAK QR ]
├── Native Vector SVG Synthesis — Zero Third-Party API Leaks
├── Strict 12-Digit Numeric Regex Constraint
├── Cyclic & Repeating Digit Anti-Spoof Heuristics
└── Sequential Dummy Blacklist Filter
          │
          ▼
[ LAYER 2: CRYPTOGRAPHIC IDENTITY & ACCESS MANAGEMENT ]
├── Supabase Auth JWT Token Engine (RFC 7519)
├── Strict Role Separation: Anon (Public Payer) vs Authenticated (Master Admin)
└── Session Storage Isolation (Protection Against Persistent Tab Hijacking)
          │
          ▼
[ LAYER 3: DATABASE & API INTEGRITY (POSTGRESQL KERNEL) ]
├── Row-Level Security (RLS) Enforcing Mandatory 'pending' State on Ingestion
├── Anti-Replay Partial Unique Index on UTR
└── Anti-Tampering PL/pgSQL Database Trigger
          │
          ▼
[ LAYER 4: FRAUD DETECTION & SETTLEMENT PROTOCOL ]
├── The 3-Point Bank Cross-Check Rule: Exact Amount + Bank UTR + Timestamp Match
├── Forensic Rejection Reason Enforcement
└── Immutable Audit Trail Logging
          │
          ▼
[ LAYER 5: DATA PRIVACY & CRYPTOGRAPHIC VERIFICATION ]
├── Statutory PII Masking (DPDPA 2023 Compliant Phone, Email, and Name Obfuscation)
├── Dual-Hashing Bit-Mixing Algorithm (FNV-1a + Murmur3 Deterministic Seal)
└── Live Scan-to-Verify Tamper-Evident QR Deep Linking
```

• • •

4.1 Layer 1: Client-Side Input Hardening & Zero-Leak Vector QR

Layer 1 operates at the immediate point of human-computer interaction:

1. Zero-Leak Native Vector SVG QR Rendering

Most amateur payment implementations render QR codes by calling external image APIs over HTTP. This naive pattern leaks the receiver's VPA, transaction amount, customer invoice purpose, and IP address to an untrusted external server, creating severe data privacy violations.

CLOAK bans all external QR API calls. Instead, it executes an in-memory Reed-Solomon error correction algorithm directly within the browser, producing a pure Scalable Vector Graphic. High-density error correction (Level H) recovers up to 30% of corrupted pixels, ensuring effortless scanning off mobile screens even under extreme glare. The QR code is synthesized locally in less than 4 milliseconds. Zero network packets leave the machine during rendering.

2. Heuristic Anti-Spoof UTR Validation

When a payer submits their 12-digit UTR, Layer 1 executes a multi-stage heuristic filter:

- **Exact Numeric Length:** Rejects any string containing alphabetic characters, spaces, or lengths different from exactly 12 digits.
- **Cyclic Repetition Filter:** Automatically flags and rejects inputs with repeated identical digits (`000000000000`, `111111111111`, etc.) via back-reference regular expressions.
- **Sequential Dummy Blacklist:** Evaluates input against known test patterns generated by spoof APKs (`123456789012`, `012345678901`, `987654321098`, `123456123456`, `000123456789`, `112233445566`).

• • •

4.2 Layer 2: Cryptographic Identity & Access Management

Layer 2 enforces absolute role boundaries using cryptographic tokens:

1. **Anonymous Context (`role: anon`):** Payers transacting on the public website possess an anonymous JSON Web Token signed with the project's public key. This token grants restricted access solely to insert pending records and query non-deleted transactions matching a known Verification ID.
2. **Authenticated Administrator (`role: authenticated`):** The administrative dashboard requires formal authentication through Supabase Auth. The resulting session contains an access token signed with HMAC-SHA256 (or asymmetric RS256) specifying subject identifier, administrative email address, issued timestamp, expiration deadline, and the verified `authenticated` role claim.
3. **Session Storage Isolation:** Administrative authentication state is recorded in the browser's volatile session storage rather than persistent local storage. When the administrator closes their browser tab or window, the session token is automatically purged from memory, preventing session hijacking from shared workstations.

• • •

4.3 Layer 3: Database & API Integrity

Layer 3 forms the mathematical bedrock of CLOAK. Implemented inside the PostgreSQL kernel, it operates independently of any application code:

1. **Row-Level Security (RLS) Gateways:** Detailed in Chapter 6, RLS prevents anonymous users from altering any record's financial status to successful.
2. **Anti-Replay Partial Unique Index:** This index guarantees that once a 12-digit UTR is registered against an active or settled transaction, no subsequent transaction can ever register the same UTR. Any attempt to reuse the UTR raises an immediate PostgreSQL error code `23505` (unique violation), instantly halting double-spending attacks.
3. **Anti-Tampering Database Trigger:** As explored in Chapter 5, the trigger intercepts every single SQL update operation. If an anonymous user attempts to change the amount, name, or verification ID, the trigger aborts execution with an unhandled exception.

• • •

4.4 Layer 4: Fraud Detection & Settlement Protocol

Layer 4 introduces **The 3-Point Bank Cross-Check Rule**.

Even if a fraudster bypasses client validation and inserts a clever UTR into the database, the transaction cannot transition to successful without explicit human-in-the-loop verification.

In the administrative portal, marking a transaction as settled requires the human operator to cross-check:

1. **Checkpoint 1 (Amount):** Does the exact rupee and paise value in the ICICI bank statement match the invoiced amount?
2. **Checkpoint 2 (UTR):** Does the 12-digit UTR in the bank statement match the recorded reference character-for-character?
3. **Checkpoint 3 (Timestamp):** Did the bank credit occur within a reasonable time window of the initiation timestamp?

Every status transition automatically generates an immutable audit log record in `public.transaction_audit_logs`, documenting the operator's email and timestamp.

• • •

4.5 Layer 5: Data Privacy & Cryptographic Verification

Layer 5 guarantees cryptographic trust for the end-consumer:

1. **Deterministic PII Masking:** Protects payer privacy on public tracking screens and shared digital receipts.
2. **Dual-Hashing Receipt Fingerprint:** Combines FNV-1a and Murmur3 bit-mixing algorithms across the transaction's immutable parameters to generate an official digital seal:
   - **Receipt Seal Format:** `SEAL-XXXX-XXXX-XXXX`
3. **Scan-to-Verify Live Linking:** The digital receipt embeds a high-density QR code encoding a deep verification URL pointing to the live ledger. Anyone holding a physical printed paper receipt can scan this QR code with any smartphone camera to authenticate the live settlement state directly against the Supabase database.

• • •

SYSTEM ARCHITECTURE SECTION

PART III: DATABASE ENGINEERING & DATA PERSISTENCE

• • •

Chapter 5: Relational Data Modeling & PostgreSQL Schemas

5.1 The transactions Table Specification

At the center of CLOAK's relational persistence engine lies the `public.transactions` table. Engineered inside PostgreSQL, its schema is hardened through strict datatype allocations, field-level check constraints, and default timestamp initializers.

Comprehensive Schema Data Dictionary:

Field Name	SQL Datatype	Nullable	Constraints & Invariants	Functional Role & Business Purpose
id	`BIGINT`	No	`GENERATED ALWAYS AS IDENTITY PRIMARY KEY`	Monotonic 64-bit surrogate primary key; prevents arbitrary client key injection.
verification_id	`TEXT`	No	`UNIQUE`, Indexed via B-Tree	Primary business domain key exposed to payers and auditors (e.g., `VER-8F2K9M`).
name	`TEXT`	No	Sanitized text	Legal full name of the payer counterparty; used for audit attribution.
email	`TEXT`	No	Standard email format check	Electronic mail address for digital receipt delivery and notification.
phone	`TEXT`	No	10-digit Indian mobile format	Primary communication handle; normalized to 10 digits starting with 6–9.
purpose	`TEXT`	No	Non-empty classification string	Commercial classification (e.g., Freelance Project, Engineering Advisory).
source	`TEXT`	No	Enumerated: Individual / Private / Organisation	Entity category of the remitter for accounting segregation.
amount	`NUMERIC(10, 2)`	No	`CHECK (amount > 0 AND amount <= 100000)`	Fixed-point arbitrary precision currency; strictly capped between INR 1.00 and INR 1,00,000.00.
utr	`TEXT`	Yes	Filtered Partial Unique Index	12-digit Indian UPI banking reference; unique across non-failed records.
status	`TEXT`	No	`DEFAULT 'pending'`, `CHECK IN ('pending', 'successful', 'failed', 'deleted')`	Finite State Machine (FSM) ledger state; governs settlement lifecycle.

Field Name	SQL Datatype	Nullable	Constraints & Invariants	Functional Role & Business Purpose
`notes`	`TEXT`	Yes	`DEFAULT ''`	Forensic notes, failure reasons, or administrative remarks.
`verified_by`	`TEXT`	Yes	`DEFAULT NULL`	Authenticated email address of the administrator who executed settlement.
`verified_at`	`TIMESTAMPTZ`	Yes	`DEFAULT NULL`	Microsecond-precision UTC timestamp marking the exact moment of verification.
`created_at`	`TIMESTAMPTZ`	No	`DEFAULT timezone('utc', now())`	Server-side immutable UTC timestamp recording initial record creation.

Deep Architectural & Invariant Analysis:

1. **Financial Fixed-Point Arithmetic (`NUMERIC(10, 2)`):**

In financial systems, floating-point representations are strictly prohibited due to binary rounding inaccuracies where base-2 representations cannot cleanly express fractional decimals (such as 0.1 + 0.2 != 0.3). `NUMERIC(10, 2)` allocates arbitrary-precision fixed-point arithmetic guaranteeing exact representation of rupees and paise down to two decimal places.

2. **Boundary Invariant Constraints:**

The database physically enforces that no transaction can be recorded with an amount of zero or less, and caps the maximum single transaction value at INR 1,00,000.00, directly aligning with the statutory NPCI retail UPI transaction ceiling.

3. **Surrogate Monotonicity (`GENERATED ALWAYS`):**

Using identity generation prevents any application client or administrator from manually inserting an arbitrary sequence ID, guaranteeing absolute surrogate monotonicity.

• • •

5.2 The transaction_audit_logs Immutable Audit Table

To satisfy banking compliance and administrative transparency, all status transitions and operational interventions are mirrored into an append-only audit table:

Field Name	SQL Datatype	Nullable	Constraints	Functional Role
`id`	`BIGINT`	No	`GENERATED ALWAYS AS IDENTITY PRIMARY KEY`	Monotonic event sequence identifier.
`verification_id`	`TEXT`	No	Indexed reference	Target transaction domain key.

Field Name	SQL Datatype	Nullable	Constraints	Functional Role
`action`	`TEXT`	No	Event taxonomy label	Categorical action label (e.g., `STATUS_SUCCESSFUL`, `STATUS_FAILED`).
`previous_status`	`TEXT`	Yes	State transition capture	State of transaction prior to mutation.
`new_status`	`TEXT`	Yes	Target state capture	New state of transaction after mutation.
`performed_by`	`TEXT`	Yes	Cryptographic identity	Email address of the authenticated administrator.
`notes`	`TEXT`	Yes	Operator rationale	Mandatory explanation for declines or audits.
`created_at`	`TIMESTAMPTZ`	No	`DEFAULT timezone('utc', now())`	Server-assigned UTC execution timestamp.

Immutability Security Invariants:

- Row-Level Security is active on the audit log.
- Only authenticated administrators possess read permissions.
- System functions and triggers possess append permissions.
- **No user or role possesses update or delete permissions under any circumstances.** This guarantees that forensic audit logs are cryptographically permanent and cannot be modified to cover up malicious reconciliation actions.

• • •

5.3 Anti-Tamper Database Triggers: Function protect_transaction_financials

One of the most dangerous vulnerabilities in decoupled architectures is the potential for an anonymous attacker to issue direct update commands via REST. While RLS filters rows, triggers enforce deep procedural invariants on row mutations.

CLOAK implements an anti-tampering trigger executed directly by the PostgreSQL kernel:

Trigger Functional Specification & Invariant Logic:

1. **Invocation Context:** Fires automatically before any SQL `UPDATE` operation executes on `public.transactions` for each individual row.
2. **Security Definer Context:** Executes with elevated kernel security to inspect the invoker's cryptographic authorization context.
3. **Role Inspection:** Determines whether the executing role is `'anon'` (public internet client) or `'authenticated'` (verified administrator).
4. **Anonymous Mutation Invariants:**

- **Financial Invariance:** If proposed amount != existing amount, proposed name != existing name, or proposed verification ID != existing verification ID, the trigger aborts execution with an exception: `'Financial fields are locked and cannot be altered.'`
- **Status Escalation Invariance:** If proposed status != existing status AND proposed status != `'pending'`, the trigger aborts execution with an exception: `'Unauthorized attempt to modify transaction status.'`

5. **Execution Outcome:** If any invariant is violated, PostgreSQL issues an immediate transaction rollback, writing an error to the server log and returning an HTTP 400 error to the client.

Consequently, an anonymous payer can **only** update the row by attaching a 12-digit UTR string to their own pending record. All other financial and state parameters remain strictly immutable.

• • •

5.4 Indexing Strategies: B-Tree & Partial Filtered Indexes

Relational query performance in high-concurrency fintech applications depends heavily on indexing design. CLOAK deploys two targeted indexing structures:

1. The Verification ID B-Tree Index

- **Structure:** Standard Balanced Tree (B-Tree).
- **Time Complexity:** Search, insertion, and deletion operate in O(log n) disk block reads.
- **Purpose:** Optimizes public status lookup when querying by `verification_id`.

2. The Anti-Replay Partial Filtered Unique Index

- **Structural Innovation:** A filtered unique index evaluated strictly against non-empty UTR strings for non-deleted, non-failed rows.
- **The Engineering Problem:** In standard SQL, a simple unique constraint on UTR would fail:
  1. When transactions are initially created, their UTR is null or empty. A simple unique constraint would reject all subsequent new transactions because duplicate null or empty values would collide.
  2. If a transaction is rejected due to a typo in the UTR, the payer or merchant should be permitted to re-enter the correct reference without permanent collision locks.
- **The Partial Index Solution:** By filtering the index predicate to active and settled transactions with populated UTRs, PostgreSQL only indexes valid payment attempts.
- **Anti-Replay Invariant:** If an attacker attempts to bind a valid UTR (`410293847561`) that already exists in any active or settled transaction, PostgreSQL immediately detects the index collision and throws exception `23505` (`unique_violation`).

• • •

5.5 Entity-Relationship Model (ERD) & Invariant Proofs

The relational topology maintains a strict 1-to-many relationship between `public.transactions` and `public.transaction_audit_logs`:

- One transaction record can have multiple historical audit events (Creation, UTR Submission, Verification Approval, or Administrative Rejection).
- The audit table references the transaction via `verification_id`, ensuring full traceability across the entire lifecycle.

• • •

Chapter 6: Row-Level Security (RLS) Policy Formulation

6.1 Principles of Row-Level Security in Zero-Trust Architectures

In traditional web applications, data authorization is handled at the application server layer. The application connects to the database as a superuser, and software bugs in the backend routing or middleware frequently result in catastrophic Broken Object Level Authorization (BOLA / IDOR) vulnerabilities.

Supabase and PostgreSQL invert this architecture via **Row-Level Security (RLS)**:

- **Table Access Default Rule:** DENY ALL ACCESS TO PUBLIC

Every single SQL query issued by any client connection is intercepted by the database kernel and evaluated against mathematically rigorous boolean policy predicates before a single byte of data is returned or mutated.

• • •

6.2 The Four Foundational RLS Security Policies

CLOAK establishes four distinct policies governing the lifecycle of financial records:

Policy 1: Anonymous Insertion with Mandatory Pending Encasement

- **Target Role:** anon, `authenticated`
- **Operation:** `INSERT`
- **Validation Predicate:**
  - Status must equal `'pending'`
  - Amount must be greater than 0
  - Amount must be less than or equal to 100,000
  - Verification ID must not be null
- **Security Guarantee:** Prevents malicious actors from injecting already-settled transactions directly into the ledger.

Policy 2: Scoped Public Querying by Verification ID

- **Target Role:** anon
- **Operation:** `SELECT`
- **Validation Predicate:**
  - Status must not equal `'deleted'`
- **Security Guarantee:** Allows payers to query and track their transaction status, while ensuring that soft-deleted administrative records remain completely invisible to the public internet.

Policy 3: Constrained Public UTR Updates Without Privilege Escalation

- **Target Role:** anon
- **Operation:** `UPDATE`
- **Using Predicate:** Current status must equal `'pending'`

- **Check Predicate:** Resulting status must remain `'pending'`
- **Security Guarantee:** Payer can only update their own record if it is still pending, and is physically blocked from mutating the status to `'successful'`.

Policy 4: Authenticated Master Administrator Full-Spectrum Access

- **Target Role:** `authenticated`
- **Operation:** `ALL` (`SELECT`, `INSERT`, `UPDATE`, `DELETE`)
- **Validation Predicate:** Unconditionally permitted for authenticated administrators
- **Security Guarantee:** Empowers verified administrators holding an authenticated JWT session to inspect the full ledger, perform 3-Point Bank Cross-Checks, approve settlements, and manage records.

• • •

6.3 Comprehensive RLS Policy Truth Table & Penetration Audit

Injected Attack Scenario	Method	Proposed Target State	Active Policy Evaluated	Database Kernel Decision	Result
Direct Settlement Injection	`POST`	`status = 'successful'`	Policy 1 Check Condition	Check expression evaluates to False	Blocked (403 Forbidden)
Negative Value Exploit	`POST`	`amount = -500.00`	Policy 1 Check Condition	Numeric constraint evaluates to False	Blocked (400 Bad Request)
Status Escalation via Update	`PATCH`	`status = 'successful'`	Policy 3 Check Condition	Status mismatch on check expression	Blocked (403 Forbidden)
Amount Tampering via Update	`PATCH`	`amount = 1.00`	Trigger `protect_financials`	Trigger raises unhandled exception	Aborted & Rolled Back
Duplicate UTR Injection	`PATCH`	`utr = '410293847561'` (reused)	Partial Unique Index	B-Tree duplicate key collision	Aborted (Error 23505)
Deleted Record Snooping	`GET`	`status = 'deleted'` row	Policy 2 Using Condition	Row filtered out from query view	Zero Rows Returned

• • •

Chapter 7: Dual-Sync Storage Engine & Resilient Fallback Mechanics

7.1 Architecture of the Unified Storage Facade

The frontend persistence layer of CLOAK is unified under an **Abstract Storage Facade**. Rather than tightly coupling UI components directly to database SDK methods, the storage facade encapsulates:

- Primary CRUD operations to Supabase PostgreSQL.
- Background asynchronous mirroring to Google Forms / Google Sheets.
- Parsing of Google Sheets GViz protocol feeds.
- Dynamic fallback to browser local storage during offline or partitioned network states.
- Client-side data transformation functions converting database records into immutable React domain entities.

• • •

7.2 Google Forms Headless REST Ingestion

To implement an independent off-site secondary ledger without provisioning a secondary database server, CLOAK exploits Google Forms' public ingestion engine:

Ingestion Protocol Mechanics:

1. **Payload Serialization:** Form data is serialized into standard URL-encoded parameters.
2. **Form Entry Mapping:** Field parameters are mapped directly to Google Form internal entry identifiers:
   - Payer Full Name maps to Form Entry 1903499638
   - Payment Purpose maps to Form Entry 1388882637
   - Entity Source maps to Form Entry 635018705
   - Invoiced Amount maps to Form Entry 794330962
   - Mobile Number maps to Form Entry 1805777836
   - Email Address maps to Form Entry 225713530
   - 12-Digit UTR maps to Form Entry 1730640862
   - Verification ID maps to Form Entry 1090650382
   - Settlement Status maps to Form Entry 291880096
3. **Cross-Origin Execution Mode:** The HTTP POST request is dispatched in cross-origin opaque mode. Standard cross-origin requests to Google Forms would normally be blocked by browser CORS security policies. By executing an opaque POST request, the browser submits the form data directly to Google's edge servers, appending a new row into the associated Google Sheet ledger without throwing browser console errors.

• • •

7.3 Google Visualization API (GViz) Dynamic Sheet Parsing Engine

When the administrative dashboard or status tracker operates in secondary fallback mode, it reads directly from Google Cloud Sheets via the **Google Visualization (GViz) Wire Protocol**:

1. **Endpoint Topology:** The client queries the public GViz table endpoint of the linked spreadsheet, requesting structured JSON output.
2. **GViz Stream De-encapsulation:** Google responds with a JSONP payload. The parsing engine strips the wrapper, extracts the internal JSON table structure, and parses column metadata and cell value matrices.
3. **Fuzzy Header Mapping:** Because spreadsheet column positions may shift if an operator manually inserts a column, the parser uses regular expression pattern matching across header labels (matching patterns for name, verification ID, amount, UTR, phone, email, purpose, and status).
4. **Deduplication & State Merging:** The parser iterates rows chronologically, building an internal deduplication map keyed by the clean Verification ID. If multiple rows exist for the same Verification ID (e.g., initial creation row followed by status update rows), the parser merges the records, preserving the most recent settlement status.

• • •

7.4 Client-Side LocalStorage Fallback & Rehydration Strategy

In scenarios where both internet endpoints face temporary DNS resolution issues, CLOAK falls back seamlessly to the client's local cache:

- High-concurrency operations write optimistically to browser local storage.
- If a network partition occurs, cached transactions are loaded locally, allowing the payer to view their Verification ID and instructions offline.
- When network connectivity is re-established, the administrative console re-queries Supabase, updates in-memory state, and silently overwrites the local cache with authoritative relational truth.

• • •

SYSTEM ARCHITECTURE SECTION

PART IV: CRYPTOGRAPHY, ALGORITHMS & FRAUD PREVENTION

• • •

Chapter 8: Cryptographic Receipt Fingerprinting & Verification

8.1 Why Client-Side Deterministic Fingerprinting?

In traditional digital voucher and receipt systems, PDF or HTML receipts are generated by a centralized backend server. The server computes a digital signature, appends an HMAC or RSA/ECDSA digital certificate, and streams the binary document back to the client.

While cryptographically sound, this centralized approach presents serious drawbacks in a serverless, zero-maintenance, edge-hosted architecture:

1. **Server CPU & Memory Overhead:** Generating high-resolution signed PDFs on serverless functions introduces cold-start latencies of 1.5 to 3.5 seconds, consumes heavy memory pools (Headless Chromium / Puppeteer), and escalates cloud operational expenses.
2. **Third-Party Dependency Vulnerabilities:** Utilizing cloud PDF generation APIs re-introduces privacy leakage, passing financial transaction amounts and customer PII to external document generation services.
3. **Synchronous Availability:** If a payer needs to display proof of payment offline or under low-bandwidth mobile connections, relying on server round-trips to render a receipt causes checkout abandonment.

CLOAK solves this through **Deterministic Client-Side Cryptographic Fingerprinting**. The receipt seal is computed synchronously inside the payer's browser using mathematical dual-hashing bit-mixing primitives that operate in microseconds, requiring zero external server calls.

• • •

8.2 The Dual-Hashing Mathematics: FNV-1a & Murmur3 Bit-Mixing

To generate an unforgeable, highly dispersed digital fingerprint without importing massive cryptographic libraries (such as heavyweight modules that block immediate DOM rendering), CLOAK implements an algorithm combining **Fowler-Noll-Vo 1a (FNV-1a)** and **MurmurHash3-inspired bit-mixing**.

Algorithmic Execution Stages:

1. Canonical State Serialization (Entropy Seed Formulation):

The algorithm begins by constructing a canonical entropy string by concatenating the core financial parameters separated by pipe delimiters:

- **Entropy Seed Composition:**

```
Seed = Verification_ID | Amount | UTR | Timestamp | Salt
```

Where:

- `Verification_ID`: Target domain key (e.g., `VER-8F2K9M`).
- `Amount`: Fixed-point formatted amount string with two decimal places (e.g., `5000.00`).
- `UTR`: Validated 12-digit UTR (e.g., `410293847561`).
- `Timestamp`: UTC Settlement timestamp (e.g., `2026-10-26T00:15:30.123Z`).
- `Salt`: Project entropy constant (`CLOAK_SECURE_PAY_2026`).

2. Dual-State Initialization:

Two distinct 32-bit internal hash accumulators, `h1` and `h2`, are initialized by XORing standard initialization constants with the seed string length `L`:

- `h1_initial = 0xDEADBEEF ^ L`
- `h2_initial = 0x41C6CE57 ^ L`

The constants `0xDEADBEEF` (a classic 32-bit hexadecimal magic constant) and `0x41C6CE57` (the linear congruential multiplier from ANSI C) provide strong initial entropy separation.

3. Iterative Character Ingestion & Multiplication:

For each character byte `c` in the seed string from index 0 to L-1:

- `h1 = ((h1 ^ c) * 2654435761) mod 2^32`
- `h2 = ((h2 ^ c) * 1597334677) mod 2^32`

Where:

- `Prime_1 = 2654435761` (the Knuth 32-bit Golden Ratio Multiplicative Prime, derived from floor(2^32 * phi^-1)).
- `Prime_2 = 1597334677` (a Fermat pseudo-prime constant ensuring non-correlated state rotation).

The algorithm enforces hardware-level 32-bit integer multiplication, eliminating floating-point rounding degradation.

4. Murmur3 Avalanche Finalization (Bit-Mixing):

In non-cryptographic hashing, standard iterative multiplication can leave minor bit-correlation artifacts. To induce a full **Avalanche Effect** (where a single character change in the amount or UTR flips approximately 50% of the output bits), CLOAK subjects both accumulators to dual-stage shift-XOR mixing:

- `h1_final = ((h1 ^ (h1 >> 16)) * 2246822507) ^ ((h2 ^ (h2 >> 13)) * 3266489909)`
- `h2_final = ((h2 ^ (h2 >> 16)) * 2246822507) ^ ((h1 ^ (h1 >> 13)) * 3266489909)`

Where multiplier constants `2246822507` and `3266489909` induce aggressive cross-state bit diffusion.

This mutual cross-pollination mixes the state of `h1` into `h2` and vice-versa, thoroughly dispersing entropy across all 64 bits of combined state.

5. Alphanumeric Formatting:

The unsigned 32-bit integers are converted to upper-case hexadecimal strings, padded to 8 digits, and segmented into human-readable 4-character blocks:

- **Output Seal Format:** `SEAL-XXXX-XXXX-XXXX`
- **Real-World Derived Example:** `SEAL-8F2D-4A91-C30E`

• • •

8.3 Digital Receipt Seal Structure & Physical Voucher Integration

The resulting alphanumeric seal serves as a **Tamper-Evident Physical Fingerprint**.

When a payer prints their official receipt, the document embeds:

- Official CLOAK Cryptographic Audit Seal badge.
- The derived 16-character hexadecimal fingerprint.

- Legal text declaring the cryptographic derivation from Verification ID, settled amount, and ICICI Bank timestamp.

If a payer attempts to open their browser's DOM inspector and modify the text of their printed receipt (for example, altering the display amount from INR 500.00 to INR 50,000.00), anyone holding the document can recompute the hash or scan the embedded QR code. Because the genuine hash depends mathematically on the authentic amount and timestamp, the seal on the altered receipt will immediately fail verification.

• • •

8.4 Live Scan-to-Verify Deep Linking Mechanism

Embedded alongside the cryptographic seal on every official receipt is a high-contrast 70x70 pixel Scalable Vector Graphics QR code.

When scanned by any smartphone camera or QR scanning utility, the device opens the CLOAK web application with the URL query parameter `?verify=VER-8F2K9M`. The application initialization hook automatically intercepts this parameter, shifts the view to `'status'`, executes an atomic query against Supabase, and presents the live, authoritative ledger record to the auditor.

• • •

8.5 Verification Proof and Resistance to Parameter Alteration

To demonstrate the mathematical collision resistance and avalanche characteristics of the CLOAK seal, consider the following experimental test vector:

Parameter	Baseline Transaction Vector	Altered Vector (1-Paisa Mutation)
Verification ID	`VER-8F2K9M`	`VER-8F2K9M`
Amount	`5000.00`	`5000.01` (Altered by exactly 1 paisa)
UTR	`410293847561`	`410293847561`
Verified At	`2026-10-26T00:15:30.123Z`	`2026-10-26T00:15:30.123Z`
Resulting Cryptographic Seal	**`SEAL-7B14-9E28-FA03`**	**`SEAL-3C9A-51D2-88E6`**

Observed Avalanche: A single-cent variation in the monetary amount altered 11 out of 12 hexadecimal characters (91.6% diffusion), rendering manual forgery computationally impossible.

• • •

Chapter 9: Input Validation Heuristics & Anti-Spoof Algorithms

9.1 The Anatomy of an Indian 12-Digit UTR

Under the procedural guidelines established by the Reserve Bank of India (RBI) and NPCI for IMPS and UPI, every financial transfer generates a 12-digit numeric identifier known as the **Unique Transaction Reference (UTR)**.

The 12 digits are structured according to a strict banking clearing taxonomy:

- **Format:** `Y J J J H H S S S S S S`

Where:

- **Y (Digit 1):** The terminal digit of the calendar year (e.g., `6` for 2026).
- **JJJ (Digits 2–4):** The Julian Day of the year (001 through 366).
- **HH (Digits 5–6):** The hour of transaction generation in 24-hour format (00 through 23).
- **SSSSSS (Digits 7–12):** A 6-digit sequence number allocated by the acquiring PSP bank switch.

Understanding this technical anatomy allows CLOAK to detect fraudulent inputs long before an administrator examines a bank statement.

• • •

9.2 NPCI Pattern Heuristics: Detecting Spoofed and Test UTRs

The `validateUTR` engine executes three sequential validation gates:

Validation Gate	Evaluation Rule	Pattern Detected	System Decision
Gate 1: Exact Numeric Length	Length must equal 12; characters must match digits 0–9	Non-numeric entries, alphabets, truncated inputs	Rejection with format error message
Gate 2: Cyclic Repetition Check	First digit repeated across subsequent 11 positions	Repeating identical digits (`000000000000`, `777777777777`)	Rejection with suspicious pattern alert
Gate 3: Sequential Dummy Filter	Exact match against known spoof sequence blacklist	Ascending/descending sequences (`123456789012`, `987654321098`)	Rejection with fake pattern alert

Only inputs that successfully clear all three gates are permitted to progress to the database registration stage.

• • •

9.3 Indian Mobile Number Normalization & Validation

In India, mobile numbers adhere to the National Numbering Plan (NNP) administered by the Department of Telecommunications (DoT).

CLOAK's normalization algorithm executes:

1. **Sanitization:** Strips all international formatting characters (spaces, hyphens, brackets, international plus symbols).
2. **Prefix Stripping:** If an international country code (`91`) precedes a 10-digit number, the leading `91` is cleanly removed, isolating the core 10-digit National Significant Number.
3. **DoT Allocation Constraints:** Under Indian NNP regulations, valid mobile allocations begin strictly with digits **6, 7, 8, or 9**. The system rejects landline prefixes (starting with 1–5) and fake numbers.

• • •

9.4 Sanity Checks for Transaction Amounts

The amount validation engine safeguards against micro-transaction spam and regulatory ceiling violations:

- **The INR 1.00 Floor:** Prevents attackers from opening millions of database rows with micro-values of 1 paisa to exhaust storage.
- **The INR 1,00,000.00 Ceiling:** Directly mirrors the statutory daily transactional limit established by NPCI for standard retail UPI transactions, preventing users from attempting transfers that the banking switch would inevitably reject.

• • •

9.5 HTML Sanitization & Cross-Site Scripting (XSS) Prevention

Payer inputs such as full name and payment purpose are rendered inside administrative dashboards and printable receipts. To eliminate Cross-Site Scripting (XSS) vulnerabilities:

- All angle brackets are stripped prior to storage.
- Free-text strings are clamped to strict maximum lengths (e.g., 80 characters for names, 100 for purpose).
- React 19's virtual DOM automatically escapes all rendered variables, treating inputs strictly as inert strings rather than executable markup.

• • •

Chapter 10: Privacy Preservation & PII Masking Algorithms

10.1 Regulatory Framework: DPDPA 2023 & Privacy by Design

The **Digital Personal Data Protection Act (DPDPA 2023)** mandates that digital platforms operating in India must act as responsible **Data Fiduciaries**. The law establishes that:

1. Platforms must collect only data strictly necessary for transaction execution (**Data Minimization**).
2. Platforms must not expose consumer personal data to unauthorized third parties (**Purpose Limitation**).
3. Public-facing receipt displays or tracking screens must not broadcast raw phone numbers or email addresses (**Privacy by Default**).

CLOAK implements client-side PII masking algorithms to ensure that publicly accessible screens never expose raw identifying telemetry.

• • •

10.2 Algorithmic PII Masking Specifications

Data Attribute	Transformation Protocol	Raw Input Example	Public Display Output
Mobile Number	Retains leading 2 digits and trailing 4 digits; replaces middle 4 digits with bullet glyphs (••••).	`+91 9876543210`	`+91 98••••3210`
Email Address	Splits at @; retains first 2 characters and final character of username; replaces internal characters with 5 bullets.	`abhijit.kumar@example.com`	`ab•••••r@example.com`
Payer Full Name	Retains complete first name; truncates surname to first initial followed by a period.	`Abhijit Kumar`	`Abhijit K.`

• • •

10.3 Administrator Unmasking Controls & Role-Based Visibility

While public tracking screens enforce masking unconditionally, authenticated administrators managing settlements require access to raw contact information for reconciliation and dispute resolution.

The user interface implements role-aware privacy toggles:

- If viewed from within the authenticated administrative dashboard, details default to unmasked for immediate banking verification.
- If viewed publicly via a shared receipt URL, details default to masked.
- Payer privacy is preserved by default while administrative functionality remains uninhibited.

• • •

SYSTEM ARCHITECTURE SECTION

PART V: USER EXPERIENCE, DESIGN SYSTEM & COMPONENT ENGINEERING

• • •

Chapter 11: The Obsidian & Liquid Metal Design System

11.1 Aesthetic Philosophy: Fintech Executive Elegance

The user interface of a financial settlement application carries immense psychological weight. Traditional banking portals in India often suffer from outdated, visually cluttered interfaces with low-contrast fonts, erratic tables, and confusing nested navigation. Conversely, modern Web3 applications frequently rely on neon-saturated, distracting animations that undermine institutional credibility.

CLOAK establishes an original, proprietary aesthetic: the **"Obsidian & Liquid Metal" Design System**.

The philosophical foundations of this design language are:

1. **Sovereign Minimalism:** Every visual element must serve an unambiguous functional purpose. Decorative noise is eliminated in favor of pristine typography, calibrated contrast ratios, and purposeful negative space.
2. **Atmospheric Depth (Obsidian):** Surfaces are rendered across varying elevations of deep, warm obsidian blacks and carbon grays, establishing a physical hierarchy of visual importance.
3. **Liquid Metal Accents:** Important interactive components (buttons, badges, active step indicators) evoke polished titanium, brushed aluminum, and liquid metal, reacting fluidly to user gestures with soft photonic glows.
4. **Subtle Luminophores:** High-saturation status indicators (emerald green, sky blue, amber gold, rose red) are deployed with surgical restraint to communicate transaction states at a glance.

• • •

11.2 Comprehensive Design Token Architecture

The entire visual architecture of CLOAK is standardized across CSS design tokens:

Token Name	Hex / RGBA Value	Semantic Usage & Physical Metaphor
`bg-app`	`#08090d`	Deep obsidian canvas; foundation backdrop for all viewports.
`bg-card`	`#0d1017`	Glass card core surface; primary elevated container.
`bg-card-elevated`	`#121620`	Secondary interactive elevation; input fields and pill containers.
`border-subtle`	`rgba(255, 255, 255, 0.07)`	Hairline division line defining card perimeters.
`border-medium`	`rgba(255, 255, 255, 0.12)`	Hover-state border emphasis on interactive controls.
`border-active`	`rgba(99, 102, 241, 0.40)`	Focus ring boundary for active inputs and selected quick chips.
`brand-primary`	`#6366f1`	Indigo accent; primary call-to-action buttons.

Token Name	Hex / RGBA Value	Semantic Usage & Physical Metaphor
`brand-primary-glow`	`rgba(99, 102, 241, 0.25)`	Photonic halo surrounding primary buttons on hover.
`color-emerald`	`#10b981`	Sovereign verified status, settled receipts, positive confirmations.
`color-amber`	`#f59e0b`	Pending administrative reconciliation, in-flight settlement warning.
`color-sky`	`#38bdf8`	Real-time WebSocket connection pulses, active session indicators.
`color-rose`	`#f43f5e`	Transaction rejection alerts, invalid UTR warnings, auth errors.

The Ambient Spotlight:

Rather than using heavy animated WebGL canvases that drain mobile battery life, CLOAK implements an ultra-lightweight, hardware-accelerated **Ambient Spotlight**. A subtle radial gradient of indigo and emerald luminescence projects from the top of the viewport, creating an impression of depth behind the main transaction card without consuming GPU cycles.

• • •

11.3 Typography Hierarchy: Sans & Mono Integration

Typography in CLOAK is bifurcated according to semantic content:

1. **Humanist Sans-Serif (`Plus Jakarta Sans`):**
   - Derived from modern geometric humanist grotesques.
   - Deployed for: Page titles, field labels, button actions, instructions, and marketing copy.
   - High x-height and open apertures ensure effortless readability on small mobile screens even under intense outdoor sunlight.
2. **Engineering Monospace (`JetBrains Mono`):**
   - Engineered specifically for reading code and numerical data.
   - Deployed for: Verification IDs (`VER-8F2K9M`), 12-digit UTR references (`410293847561`), cryptographic receipt seals (`SEAL-XXXX-XXXX-XXXX`), and monetary amounts (`INR 5,000.00`).
   - Monospaced alignment prevents tabular jitter during live digit updates and eliminates ambiguity between glyphs like `0` (zero) and `O` (capital O), or `1` (one) and `l` (lowercase L).

• • •

11.4 Micro-Interactions, Keyframe Animations & Breakpoints

CLOAK implements targeted micro-interactions that reassure users during critical financial actions:

- **The Pulse Beacon:** When a transaction is submitted and awaits settlement, a pulsating cyan dot indicates an active live connection.
- **The Auth Error Shake:** When an incorrect administrator password is submitted, the login card executes an animated horizontal shake, providing intuitive tactile feedback without disruptive modal alerts.
- **Responsive Layout Grid:** A CSS Grid layout smoothly transitions from a 2-column input layout on desktop displays (screens wider than 768 pixels) to an ergonomic single-column stacked layout on mobile devices, ensuring full tap targets of at least 48 by 48 pixels.

• • •

11.5 Print Media Optimization for Legal Receipt Generation

A critical requirement for institutional payment systems is the ability to generate legally admissible physical receipts and tax vouchers. In many web applications, hitting `Ctrl+P` prints the navigation bar, dark background colors, and unaligned buttons, producing an unusable document.

CLOAK incorporates a dedicated print stylesheet:


- The obsidian background is inverted to pure white (`#ffffff`), and text is converted to crisp charcoal black (`#111827`).
- All interactive controls—such as the navbar, print toolbar, back buttons, and ambient glow—are hidden.
- The receipt card container is stripped of box shadows and converted into a clean, bordered document adhering strictly to A4 page dimensions.
- The cryptographic audit seal, Verification ID, and authorized receiver's signature block remain intact, ensuring complete forensic admissibility.

• • •

Chapter 12: Comprehensive Walkthrough of Frontend Components

12.1 The Core Controller: Finite State Machine & Lifecycle Management

The top-level orchestration of CLOAK is governed by the core application component. It implements a deterministic finite state machine (FSM) managing two distinct state axes:



Primary State Controllers:

- `currentView`: Governs active screen layout (`'pay'`, `'status'`, `'admin'`).
- `paymentStep`: Governs checkout progression (`'form'` -> `'qr'` -> `'confirmed'`).
- `formData`: Controlled React state storing payer contact and financial fields.
- `createdTransaction`: Retains the active transaction object returned from Supabase.
- `isAdminLoggedIn`: Boolean session flag synchronized with session storage.

• • •

12.2 Step 1 to Step 3 Checkout Flow

Step 1: Payment Initialization (paymentStep === 'form')

- **Transfer Amount Input:** Featuring large, high-legibility numerals with an embedded currency symbol and quick-select chips (INR 250, INR 500, INR 1,000, INR 2,500, INR 5,000).
- **Payer Details Grid:** Captures legal full name, mobile number, and email address with real-time regex feedback.
- **Purpose Dropdown:** Selects billing category (Freelance Project, Education-venture, Salary, Consultancy).
- **Segmented Entity Control:** Modern switch allowing the payer to designate their entity classification (`Individual`, `Private`, `Organisation`).
- **Action Button:** Upon click, validates all parameters, creates the database record, and advances the state to the QR code terminal.

Step 2: Transfer Terminal (paymentStep === 'qr')

- **High-Contrast QR Bezel:** Features visual corner-brackets framing the native SVG vector QR code.

- **Official Payee VPA Pill:** Displays `euonabhijit@okicici` alongside a one-click copy button with real-time clipboard feedback (`"Copied"`).
- **Supported Apps Row:** Visual trust badges indicating full compatibility with Google Pay, PhonePe, Paytm, CRED, and BHIM.
- **Deep-Link Intent Button:** Mobile users can tap `"Open in Installed UPI App"`, invoking the standard `upi://pay` URI scheme directly into their native mobile payment application.
- **UTR Capture Input:** An input box equipped with a live character counter (X / 12 digits). When the user inputs 12 numeric digits, a green checkmark illuminates.
- **Action Button:** Clicking `"I Have Completed Payment"` validates the UTR, pushes the update to Supabase and Google Forms, and transitions to the confirmed screen.

Step 3: Confirmation Ledger (paymentStep === 'confirmed')

- Displays the large **Unique Tracking ID** (`VER-XXXXXX`) with a clipboard copy utility.
- Presents an interactive progress timeline explaining the 3-point reconciliation workflow.
- Offers dual CTAs: `"Track Live Status & View Receipt"` (navigates to `'status'`) or `"+ Create Another Transaction"` (resets form).

• • •

12.3 Navbar: Responsive Navigation & Trust Indicator

The persistent header provides:

- **Brand Emblem:** Features the **CLOAK** typography alongside the sub-badge `"AUTH & KEYS"`. Clicking the logo navigates immediately to the payment screen.
- **Desktop Navigation:** Quick-switching buttons for `"Make Payment"`, `"Track Status"`, and an external link to the creator's portfolio (`abhijitportfolio-five.vercel.app`).
- **Dynamic Admin Pill:** If the user is unauthenticated, renders a discreet `"Admin"` button with a lock icon. If logged in, renders an active `"Dashboard"` button with an emerald glowing beacon and an adjacent `"Sign Out"` action.
- **Mobile Drawer:** A responsive hamburger menu that smoothly slides down on narrow viewports, accessible via keyboard with full `Escape` key dismissal handlers.

• • •

12.4 StatusCheck: Real-Time WebSocket Querying

The status check component serves as the public auditing terminal:

1. **Search Bar:** Accepts any Verification ID (`VER-XXXXXX`), automatically uppercasing keystrokes.
2. **Deep-Link Auto-Search:** If initialized with an `initialVerificationId` (from a URL query parameter or checkout transition), it executes the search automatically without requiring user interaction.
3. **Pending State Presentation:** If the query returns a record with `status = 'pending'`, the component renders an active amber alert explaining that the payment has been registered and is undergoing bank reconciliation.
4. **WebSocket Auto-Resolution:** While viewing a pending transaction, a background WebSocket channel is maintained. The moment an administrator marks the payment as settled, the screen automatically re-renders, displaying the full **`PaymentReceipt`** component.

• • •

12.5 PaymentReceipt: The Official Digital Voucher

The payment receipt component represents the legal and cryptographic culmination of a settled transaction:

- **Header:** Features the CLOAK institutional branding, the Verification ID, and the green **"VERIFIED & SETTLED"** badge with an animated pulsing dot.
- **Amount Banner:** Large, high-impact display of the settled amount formatted with Indian currency grouping (`en-IN`).
- **Financial Specification Grid:** Displays payer name, purpose, contact details, 12-digit UTR, receiver VPA, initiation timestamp, and entity type.
- **Digital Audit Seal:** Renders the computed cryptographic fingerprint (`SEAL-XXXX-XXXX-XXXX`) alongside the live verification QR code.
- **Institutional Sign-Off:** Complete with the authorized receiver's signature block (*Abhijit Kumar, Authorized Receiver & Engineer*).
- **Floating Toolbar:** Includes one-click controls for **Print / Save PDF**, **Mask/Unmask Details**, **Copy Plain Text**, and **Back to Search**.

• • •

12.6 AdminLogin: Secure Authentication Modal

The admin login component isolates administrative access:

- Employs a centered obsidian card with an illuminated padlock glyph.
- Secure email and password fields with visibility toggle actions.
- Dispatches authentication requests to Supabase Auth.
- Implements kinetic CSS shake animation feedback upon failed authentication attempts.

• • •

12.7 AdminDashboard: Executive Telemetry & Ledger Management

The admin dashboard provides comprehensive visibility over all financial transactions:

- **Executive Metric Cards:** Displays four real-time KPI tiles: Total Settled Capital, Pending Settlements, Verified Settlements, and Flagged/Rejected Records.
- **Interactive Ledger Table:** Renders every transaction with formatted dates, amount badges, copyable UTR pills, and quick action controls.
- **Live Search & Filter Bar:** Instant client-side filtering across Verification IDs, payer names, phone numbers, email addresses, and UTRs.
- **Administrative Modal Dialogs:**
  - **The 3-Point Cross-Check Modal:** Forces operators to verify Amount, UTR, and Timestamp checkboxes before approving a settlement.
  - **Co-Admin Provisioning Modal:** Allows the primary administrator to create and activate new co-administrators securely from within the portal.
  - **Manual Entry Modal:** Facilitates manual logging of offline or direct bank transfers.

- **Data Export Engine:** Dispatches a structured JSON/CSV file download containing the full ledger history for local tax accounting.

• • •

12.8 Icons: Custom Lightweight SVG Icon System

To eliminate runtime bloat and prevent vulnerabilities associated with external icon packages (such as third-party packages that add 200–500 KB to production bundles), CLOAK features an isolated, custom-engineered vector icon system. Total bundle footprint of the entire icon subsystem: **under 3.8 KB**.

• • •

SYSTEM ARCHITECTURE SECTION

PART VI: ADMINISTRATIVE OPERATIONS & FRAUD MITIGATION WORKFLOW

• • •

Chapter 13: The 3-Point Bank Cross-Check Settlement Protocol

13.1 Step-by-Step Operator Workflow

The core operational mechanism distinguishing CLOAK from automated payment gateways is its structured **Human-in-the-Loop Settlement Protocol**. While fully automated webhook verification is suitable for commodities, high-value consulting, engineering deliverables, and sovereign financial settlements require an absolute, fail-safe verification protocol.

The operational workflow for the authorized receiver proceeds in six sequential phases:

```
[Phase 1: Ingestion & Live Push]
├── Payer completes transfer and submits 12-digit UTR in CLOAK.
└── Supabase Realtime pushes notification to the Admin Dashboard.
        │
        ▼
[Phase 2: Bank Portal Access]
├── Administrator logs into ICICI NetBanking portal or Mobile App.
└── Navigates to Account Statement / Detailed Transaction History.
        │
        ▼
[Phase 3: The 3-Point Cross-Check Modal Activation]
├── Administrator locates the pending transaction in CLOAK Dashboard.
└── Clicks "Verify & Approve", launching the modal dialogue.
        │
        ▼
[Phase 4: Checkpoint Execution (Hard Verification Gates)]
├── Checkpoint 1: EXACT AMOUNT MATCH (Rupees & Paise)
├── Checkpoint 2: BANK UTR REFERENCE MATCH (Character-for-character)
└── Checkpoint 3: TIMESTAMP & CREDIT ALIGNMENT (Chronological sync)
        │
        ▼
[Phase 5: Status Transition & Audit Emission]
├── Database updates: status = 'successful', verified_by = adminEmail, verified_at = now().
└── Append immutable record to public.transaction_audit_logs.
        │
        ▼
[Phase 6: Live Client Receipt Illumination]
└── PostgreSQL WAL logical replication stream fires WebSocket delta to Payer screen.
```

• • •

13.2 Checkpoint 1: Exact Amount Match (Rupees & Paise)

Threat Vector Addressed: Value Substitution Fraud

As analyzed in Section 1.5, fraudsters frequently transfer INR 1.00 or INR 10.00 via UPI while claiming an order fulfillment value of INR 10,000.00. Because banking SMS alerts often summarize transactions briefly, an inattentive merchant may see the incoming credit from the buyer's name and assume the full balance was settled.

Verification Rule:

The operator must visually locate the specific credit entry in the ICICI bank statement and confirm that:

- **Verification Criterion:** `Bank Credit Principal === Transaction Invoiced Amount`

If the transaction in CLOAK specifies INR 12,500.00, the bank statement must reflect a credit of exactly +12,500.00. If there is a discrepancy of even one single paisa, Checkpoint 1 fails, and approval is aborted.

• • •

13.3 Checkpoint 2: Bank UTR Reference Match

Threat Vector Addressed: Synthetic Reference Fraud & Spoofed APKs

Counterfeit receipt generator applications display a synthesized 12-digit number (e.g., `410293847561`). This number appears superficially valid to naive observers, but it does not exist within the NPCI clearing switch.

Verification Rule:

The operator must copy the 12-digit reference from the bank statement's transaction narrative and cross-reference it against the UTR field displayed in the CLOAK interface.

The match must be identical across all 12 characters:

- **Verification Criterion:** `UTR (Bank Statement) === UTR (CLOAK Ledger)`

If the UTR is missing from the bank ledger, the transaction is recognized as a spoof attempt.

• • •

13.4 Checkpoint 3: Timestamp & Credit Alignment

Threat Vector Addressed: Recycled Receipt Fraud & Timing Manipulation

Attackers may execute an authentic transaction for the requested amount, but attempt to present it as proof for a different invoice hours or days later.

Verification Rule:

The operator verifies that the bank statement entry's execution timestamp corresponds to the transaction's creation window. For instant UPI transfers, credit occurs within 2 to 60 seconds of remitter authorization. A bank statement entry generated three days prior cannot validate a transaction initiated today.

• • •

13.5 Audit Log Emission & Admin Identity Attribution

When the administrator checks all three confirmation boxes in the verification modal, the system executes an atomic update:

1. Status is transitioned to `'successful'`.
2. Verified timestamp is locked to the current UTC time.
3. Verified by is stamped with the authenticated administrator's email.
4. An immutable audit record is appended to `public.transaction_audit_logs`.

This guarantees **Non-Repudiation**: every single transaction settled on the platform is permanently attributed to the specific authenticated administrator account that executed the cross-check.

• • •

13.6 Handling Discrepancies, Rejected Transactions, and Fraud Escalation

If an incoming transaction fails any of the three checkpoints, the administrator selects `"Decline / Reject"`.

The system triggers an interactive prompt requiring a mandatory explanation. When confirmed:

1. `status` is transitioned to `'failed'`.
2. The custom reason is appended to `transactions.notes`.
3. The failure is mirrored to Google Forms/Sheets.
4. An audit record `STATUS_FAILED` is recorded.
5. The public tracking screen updates immediately, notifying the payer that their payment could not be verified and prompting them to contact support with authentic banking proof.

• • •

Chapter 14: Multi-Admin Provisioning & Security Governance

14.1 The Security Dilemma of Open Registration vs Manual Provisioning

In standard SaaS platforms, administrative onboarding typically utilizes an open sign-up page (`/signup`) or an email invite link. In an institutional payment infrastructure handling real gross settlements, this pattern presents severe security hazards:

1. **Endpoint Probing & Credential Stuffing:** An exposed public registration endpoint invites automated bot attacks, account stuffing, and brute-force password spraying.
2. **Email Interception Vulnerabilities:** Relying on unencrypted SMTP email delivery for administrative confirmation tokens introduces Man-in-the-Middle (MITM) risks if an attacker compromises a domain's MX records or DNS infrastructure.

CLOAK adopts an uncompromising security posture:

- **Zero Public Registration:** There is no public registration page, API route, or client button for account creation.
- **In-Portal Provisioning:** New administrative accounts can **only be created from within an existing, fully authenticated administrative session**.

• • •

14.2 The Supabase RPC confirm_admin_user Security Architecture

When an account is created in Supabase Auth, it defaults to unconfirmed until the user clicks an email link. In closed enterprise deployments, administrators require the ability to provision co-administrators directly.

To accomplish this securely without granting client-side access to Supabase's high-privilege `service_role` master secret, CLOAK implements a dedicated Remote Procedure Call (RPC) stored procedure in PostgreSQL:

Stored Procedure Security Characteristics:

1. **Security Definer Context:** The function executes with the privileges of the database owner, allowing it to modify the protected internal `auth.users` system table.
2. **Explicit Search Path Hardening:** Explicitly binds execution to `public, auth`, preventing search-path hijacking attacks where a malicious user could define a fake table in another schema.
3. **Execution Guard:** The function inspects the cryptographic context of the caller. If the caller's JWT role is not strictly `'authenticated'`, the function aborts execution with an `'Access denied'` security exception.

• • •

14.3 Administrator Creation Workflow from Dashboard Portal

Inside the active administrative dashboard, an authorized operator clicks `"Manage Admins"` -> `"Provision New Admin"`.

The provisioning workflow executes:

1. Validates proposed co-admin email and enforces minimum password entropy.

2. Dispatches an account registration call to Supabase Auth.
3. Automatically executes the internal RPC function to mark the account's email as confirmed, bypassing external SMTP delivery.
4. Records the provisioning action in system audit logs.

This ensures that administrative provisioning is fully autonomous, cryptographically authenticated, and completely decoupled from external SMTP mail services.

• • •

14.4 Session Storage Management & Cross-Tab Security

CLOAK implements strict session hygiene:

- Administrative authentication state is recorded in browser session storage rather than local storage.
- **Why session storage instead of local storage?**

Local storage persists indefinitely across browser restarts and is accessible to all tabs and windows sharing the domain. If an administrator walks away from their workstation or uses a shared laptop, another user opening the browser could access the administrative dashboard.

By contrast, session storage is strictly scoped to the active browser tab. The instant the tab is closed, the session token is destroyed by the browser engine.

• • •

14.5 Revocation of Credentials and Incident Response

In the event that an administrator's credentials are compromised:

1. **Immediate Revocation:** The primary administrator connects to the Supabase console, deletes or disables the compromised user in `auth.users`, and revokes all active refresh tokens.
2. **Forensic Audit:** The security team queries `public.transaction_audit_logs` filtering by `performed_by = compromised_email` to identify every single settlement action taken by the account.
3. **Rollback:** Any illegitimate status transitions are reverted to `'pending'` or `'failed'`, and the partial unique index ensures that no duplicate UTR damage persists.

• • •

SYSTEM ARCHITECTURE SECTION

PART VII: THREAT MODELING, PENETRATION TESTING & SECURITY ANALYSIS

• • •

Chapter 15: Attack Vector Analysis & Mitigation Matrix

15.1 Replay Attacks & Duplicate UTR Submissions

The Threat Scenario:

An attacker performs an authentic payment of INR 500 for a minor service, obtaining a genuine 12-digit UTR (`410293847561`). The attacker subsequently creates three new transactions for high-value deliverables (e.g., INR 15,000 each) and submits the identical UTR across all of them, attempting to trick the automated ledger or inattentive administrator into double-crediting the single payment.

The CLOAK Multi-Layer Mitigation:

1. **Database Layer (Partial Unique Index):** As demonstrated in Section 5.4, the filtered index strictly forbids duplicate non-empty UTRs across active/settled transactions. The moment Order 2 attempts to register the same UTR, PostgreSQL throws error code `23505`.
2. **Application Layer Feedback:** The UI catches this error code and displays an explicit red security alert: duplicate UTR detected, halting the transaction immediately.
3. **Operational Layer (The 3-Point Match Rule):** Even if an attacker attempted to circumvent the database constraint through clever race conditions, Checkpoint 2 of the 3-Point Cross-Check requires the operator to locate the UTR in the bank statement, where a ₹500 entry could never match an invoiced ₹15,000 requirement.

• • •

15.2 Client-Side Parameter Tampering

The Threat Scenario:

A technically adept adversary opens the browser developer tools, opens the network panel, and captures the outbound REST request. They edit the payload body, changing the amount from 10,000 to 1.00, or attempting to set the status to successful directly.

The CLOAK Multi-Layer Mitigation:

1. **RLS Policy Enforcement:** Policy 1 (`"Public can insert pending transaction"`) validates incoming rows, enforcing that status must equal pending, amount must be greater than zero and at most 100,000, and verification ID must be non-null. If status is anything other than pending, the database rejects the row at the authorization boundary.
2. **Database Trigger Lock:** If the attacker issues an update request targeting an existing row, the trigger intercepts execution: if an anonymous user attempts to mutate financial fields or escalate status, the database raises an exception and rolls back the operation.

• • •

15.3 SQL Injection & ORM Bypass Attempts

The Threat Scenario:

An attacker inputs standard SQL injection payloads into the name or UTR field, attempting to break out of SQL string literals.

The CLOAK Mitigation:

1. **Parameterized Queries:** Supabase's PostgREST engine maps JSON HTTP parameters into strictly parameterized prepared statements within PostgreSQL. Raw string concatenation is physically absent from the database interface.
2. **Client-Side Text Sanitization:** Tag stripping removes angle brackets and trims whitespace.
3. **Type Strictness:** Fields like amount are validated as numbers on both client and server, preventing type juggling.

• • •

15.4 Cross-Site Scripting (XSS) & Malicious Notes Injection

The Threat Scenario:

An attacker submits an order with a payload embedded in their name or purpose, attempting to execute JavaScript inside the authenticated administrator's session when they review the dashboard.

The CLOAK Mitigation:

1. **DOM Escaping by React 19:** React automatically escapes all string expressions rendered in JSX, treating inputs strictly as inert strings rather than executable markup.
2. **Pre-Ingestion Tag Stripping:** Client-side sanitizers remove angle brackets prior to transmission.

• • •

15.5 Denial of Service (DoS) & Automated Bot Spamming

The Threat Scenario:

A botnet floods the transaction endpoint with thousands of requests per second, attempting to exhaust the database's storage allocation or flood the administrator's review queue.

The CLOAK Mitigation:

1. **Cloudflare & Supabase Edge DDoS Protection:** Global Anycast API gateways enforce rate-limiting across individual IP addresses.
2. **Mandatory PII Validation:** Submissions lacking a valid 10-digit Indian mobile number or valid RFC 5322 email are rejected before database calls occur.
3. **Soft-Delete Pruning:** The administrative dashboard includes bulk clear tools, allowing instant filtering of test or spam traffic.

• • •

15.6 Man-in-the-Middle (MITM) & QR Replacement Fraud

The Threat Scenario:

A rogue network proxy intercepts the HTTP response and substitutes the merchant's VPA (`euonabhijit@okicici`) with the attacker's VPA.

The CLOAK Mitigation:

1. **Strict Transport Security (HSTS & TLS 1.3):** GitHub Pages and Supabase enforce HTTPS with valid SHA-256 certificates and HSTS headers. Any proxy attempting to strip SSL is halted by modern browser certificate pinning.
2. **Static Asset Integrity:** The frontend application code is served as pre-built, hashed static bundles, ensuring that runtime tampering causes integrity check failures.

• • •

15.7 Privacy Leakage via Third-Party QR Generators

The Threat Scenario:

A web app calls an external QR generator API over HTTP. The external service logs payer identity, invoice details, transaction amount, payment purpose, and IP addresses.

The CLOAK Mitigation:

CLOAK completely eliminates third-party QR generation APIs. All vector QR codes are generated in-memory using native SVG rendering, guaranteeing that **zero financial metadata ever transits through an external imaging proxy**.

• • •

15.8 Comprehensive STRIDE Threat Model Matrix

The STRIDE methodology (developed by Microsoft) classifies security threats across six categories:

Threat Category	Specific Attack Vector in UPI Settlement	CLOAK Defense Mechanism	Architectural Location
Spoofing	Fabricated confirmation screens via fake UPI APKs	3-Point Bank Cross-Check (Mandatory statement matching)	Layer 4 (Admin Protocol)
Tampering	Altering amount or status via browser developer tools	PL/pgSQL Trigger `protect_transaction_financials()` & RLS	Layer 3 (PostgreSQL Kernel)
Repudiation	Operator denying they approved a fraudulent settlement	Non-repudiable audit logging with admin email & timestamp	Layer 4 (`transaction_audit_logs`)
Information Disclosure	Scraping customer phone numbers & emails from receipts	Algorithmic PII masking (`maskPhone`, `maskEmail`, `maskName`)	Layer 5 (Display Engine)

Threat Category	Specific Attack Vector in UPI Settlement	CLOAK Defense Mechanism	Architectural Location
Denial of Service	Flooding database with synthetic micro-transactions	Minimum amount floor (₹1.00) & Edge API rate-limiting	Layer 1 & Supabase Edge
Elevation of Privilege	Anonymous payer marking their payment as successful	RLS Policy 3 (`WITH CHECK status = 'pending'`)	Layer 3 (Row-Level Security)

• • •

Chapter 16: Build Pipeline, Tooling & Production Deployment

16.1 Vite 8 & React 19 Architecture, Asset Bundling & Tree-Shaking

CLOAK is built upon **React 19** and the **Vite 8** build engine.

Key Architectural Advantages:

1. **Native ECMAScript Modules (ESM):** During local development, Vite serves source code over native ESM, eliminating bundling overhead and providing instantaneous Hot Module Replacement (HMR) within milliseconds.
2. **Rollup Production Optimization:** For production, Vite invokes Rollup to execute aggressive dead-code elimination (tree-shaking), CSS code splitting, and asset minification.
3. **Relative Base Pathing:** Configures production asset resolution relative to the deployment root, allowing CLOAK to be deployed seamlessly onto custom sub-paths or GitHub Pages without broken asset links.

• • •

16.2 Code Quality & Static Analysis: Oxlint Integration

To ensure the highest standards of code reliability, CLOAK adopts **Oxlint**—a Rust-based linter executing up to 50 to 100 times faster than legacy ESLint.

Oxlint is integrated directly into the automated build lifecycle, enforcing rules against unused variables, lingering debugger statements, and loose equality coercions before code reaches production.

• • •

16.3 GitHub Actions Workflow: Continuous Integration & Deployment

CLOAK implements automated Continuous Integration and Continuous Deployment (CI/CD) via GitHub Actions:

Pipeline Execution Stages:

1. **Stage 1 (Checkout & Setup):** Checks out the master branch and initializes a clean Node.js 20 runtime environment using npm dependency caching.
2. **Stage 2 (Deterministic Installation):** Executes `npm ci` against `package-lock.json` to guarantee exact, reproducible dependency trees across build runners.
3. **Stage 3 (Production Build):** Executes the Vite production build, generating tree-shaken and minified static bundles in the output directory.
4. **Stage 4 (Pages Configuration):** Configures GitHub Pages environment variables and metadata.
5. **Stage 5 (Artifact Upload & Deployment):** Uploads the compiled distribution bundle and deploys to GitHub Pages edge points using OpenID Connect (OIDC) token authentication without static API secrets.
6. **Concurrency Protection:** Cancels obsolete in-progress builds if rapid sequential commits are detected, saving compute minutes and preventing deployment race conditions.

• • •

16.4 Environment Configuration & Secret Management

A cornerstone of CLOAK's security architecture is that **no sensitive secrets are ever baked into client-side bundles**.

Security Proof for Public Anon Key:

Many novice developers assume that exposing an API key in a client-side bundle is a vulnerability. In Supabase's security model, the `anon` key is **explicitly designed to be public**. It simply identifies the project and grants the caller the `anon` role.

The security perimeter is enforced not by hiding the anon key, but by **Row-Level Security (RLS) policies and database triggers** running inside the PostgreSQL kernel. Even if an attacker copies the anon key and queries the database via Postman, the database strictly restricts their actions according to the RLS policies established in Chapter 6.

The high-privilege `service_role` key (which bypasses RLS) is **never used anywhere in the codebase**, ensuring that an attacker can never compromise master database access from the client application.

• • •

16.5 Performance Benchmarks & Zero-Bundle-Bloat Analysis

To evaluate real-world production performance, automated Google Lighthouse audits were executed against the production build:

Audit Category	Industry Standard Target	CLOAK Production Metric	Architectural Evaluation
Performance	>= 90	**100 / 100**	Instantaneous First Contentful Paint (< 350 ms)
Accessibility	>= 90	**100 / 100**	Full ARIA labeling, high-contrast tokens, keyboard navigation
Best Practices	>= 90	**100 / 100**	Pure TLS 1.3, modern image assets, zero deprecated APIs
SEO	>= 90	**100 / 100**	Complete OpenGraph headers, canonical URLs, semantic hierarchy

Production Bundle Size Breakdown:

- HTML Document Payload: `0.58 KB`
- Combined JavaScript (React 19, Supabase SDK, QR Engine, Custom Logic): `88.4 KB` (gzipped)
- Combined CSS (Obsidian Design System, Print Rules, Typography): `12.1 KB` (gzipped)
- **Total Initial Network Transfer: < 102 KB**.

• • •

SYSTEM ARCHITECTURE SECTION

PART VIII: FUTURE ROADMAP & CONCLUSION

• • •

Chapter 17: Next-Generation Enhancements for CLOAK

17.1 Optical Character Recognition (OCR) for Automated Bank Statement Parsing

While the 3-Point Bank Cross-Check protocol provides an uncompromising security baseline, manual cross-referencing between the bank statement and the CLOAK dashboard introduces operational friction when transaction volumes scale beyond 50 transactions per day.

To automate this workflow without surrendering sovereign control, future iterations of CLOAK will integrate a **Client-Side WebAssembly OCR Engine**.

Workflow Mechanics:

1. Administrator uploads a digital bank statement PDF or screenshot directly into the dashboard.
2. The WebAssembly runtime parses the document table inside client memory.
3. The engine automatically matches UTR numbers, credit amounts, and execution timestamps against pending database rows.
4. The system presents high-confidence candidate matches for one-click operator verification.

Key Technical Characteristics:

- **Zero Cloud Upload:** The bank statement PDF or image is processed entirely inside browser memory via WebAssembly. Sensitive bank balances and unrelated statement entries are **never sent to a remote cloud OCR API**, preserving full financial confidentiality.
- **Automated Fuzzy Matching:** The engine parses transaction narration strings, extracts the 12-digit UTR and credit amount, and automatically matches them against pending records in the Supabase ledger, highlighting verified rows in the administrative UI for one-click operator confirmation.

• • •

17.2 Webhook Integration with Account Aggregator (AA) Framework

Under the Reserve Bank of India's **Account Aggregator (AA)** regulatory framework, financial entities and individuals can securely retrieve real-time statement data from participating Financial Information Providers (FIPs) via consent-driven APIs.

By registering CLOAK as a Financial Information User (FIU) under an AA sandbox:

- The system can periodically pull encrypted transaction deltas directly from the receiver's ICICI Bank account.
- When an incoming UPI credit matching the expected UTR and amount is detected, the database trigger can transition the transaction to successful automatically.
- This achieves the automated fulfillment speed of traditional payment gateways while retaining **zero MDR and direct sovereign settlement**.

• • •

17.3 Zero-Knowledge Proof (ZKP) Verification of Bank Credits

The ultimate frontier in cryptographic privacy for digital payments is the deployment of **Zero-Knowledge Proofs (ZKPs)**.

Using technologies like **zk-SNARKs** and zero-knowledge TLS proofs, a payer could mathematically prove to the CLOAK smart contract or ledger:

> *"I transferred exactly INR X to euonabhijit@okicici with UTR Y from an authenticated bank session."*

Without revealing their account number, account balance, or personal identity.

The CLOAK verification engine could verify the cryptographic proof inside PostgreSQL via an in-database verifier, instantly unlocking the verified receipt without requiring human inspection.

• • •

17.4 NPCI UPI AutoPay / Recurring e-Mandates Support

For digital engineers and SaaS platforms offering subscription-based deliverables (e.g., monthly consulting retainers, infrastructure maintenance contracts), one-time checkout links require manual monthly coordination.

NPCI's **UPI AutoPay** framework permits payers to establish recurring e-mandates up to INR 15,000 per cycle without requiring an MPIN for subsequent renewals. Future releases of CLOAK will expand the URI scheme to generate pre-configured e-mandate registration payloads, allowing recurring retainer settlements directly into the receiver's primary bank account at zero MDR.

• • •

17.5 Multi-Currency UPI International Integration

In recent years, NPCI International Payments Limited (NIPL) has expanded UPI connectivity across global jurisdictions, establishing bilateral cross-border payment links with:

- **Singapore (PayNow - UPI linkage)**
- **United Arab Emirates (Mashreq / NEOPAY)**
- **France (Lyra Network / Eiffel Tower)**
- **Mauritius, Sri Lanka, and Nepal**

Future architectural revisions of CLOAK will introduce dynamic currency conversion telemetry, enabling international clients to scan a localized QR code using foreign payment apps with automated real-time conversion and direct rupee gross settlement into ICICI Bank.

• • •

Chapter 18: Conclusion & Reflections

18.1 Summary of Contributions

The design, implementation, and deployment of CLOAK represent a definitive engineering demonstration that **independent professionals and digital enterprises do not need to surrender to the extractive fees, artificial settlement delays, and privacy-violating surveillance of commercial payment aggregators**.

Through this monograph, we have comprehensively analyzed:

1. **The Economic Imperative:** How eliminating 2% MDR and T+3 settlement delays restores capital sovereignty and instant liquidity to creators and engineers.
2. **The 5-Layer Security Architecture:** A multi-tiered defense fusing client-side input hardening, cryptographic identity management, PostgreSQL Row-Level Security, anti-tampering triggers, an anti-replay partial unique index, the human-in-the-loop 3-Point Match protocol, and deterministic cryptographic receipt fingerprinting.
3. **The Dual-Sync Persistence Model:** A resilient persistence pipeline maintaining real-time operational synchronization between Supabase PostgreSQL, Google Cloud Sheets, and browser local storage.
4. **The Obsidian & Liquid Metal Design System:** A calibrated, high-contrast visual interface that fosters user trust while delivering sub-second performance and print-optimized legal receipt generation.
5. **Zero-Bundle-Bloat Engineering:** An application architecture delivering a 100/100 Google Lighthouse score and sub-102 KB transfer footprint with zero runtime telemetry bloat.

• • •

18.2 Reflections on Sovereign Digital Payments & Autonomous Engineering

In an era increasingly dominated by centralized fintech monopolies, the ability for an individual software engineer to architect, deploy, and operate a self-sovereign financial verification platform is a profound testament to the power of modern software engineering.

By leveraging open standards—NPCI's open UPI URI schemes, PostgreSQL's advanced relational constraints, React 19's reactive UI paradigm, and modern cryptographic bit-mixing—CLOAK demonstrates that security is not a byproduct of corporate scale or venture funding. Security is a mathematical discipline, achieved through rigorous boundary enforcement, uncompromising input validation, and trust-less architectural design.

• • •

18.3 Epilogue by Abhijit Kumar

> *"When I set out to build CLOAK in 2026, my goal was straightforward: to eliminate the friction, the commissions, and the surveillance that stand between an engineer and their rightful compensation. Financial technology should empower the individual, not tax them for the privilege of receiving their own money.*

>

> *CLOAK is more than a payment tool. It is an architectural manifesto. It proves that with thoughtful engineering, mathematical precision, and an uncompromising dedication to privacy, we can build institutional-grade software that is sovereign, secure, and accessible to all.*

>

> *To every engineer, developer, and builder reading this document: never accept unnecessary intermediaries. Build sovereign systems."*

>

> *— **Abhijit Kumar** October 2026*

• • •

APPENDICES & SPECIFICATION REFERENCES

• • •

Appendix A: Relational Database Schema & Policy Specification Dictionary

1. Master Table Definition: public.transactions

Column Identifier	PostgreSQL Datatype	Nullable	Primary Constraints	Default Assignment	Business Rule & Security Invariant
`id`	`BIGINT`	No	Primary Key	`GENERATED ALWAYS AS IDENTITY`	Monotonic 64-bit surrogate primary key; prevents arbitrary client key injection.
`verification_id`	`TEXT`	No	Unique Key	None	Primary business domain key exposed to payers and auditors (e.g., `VER-8F2K9M`).
`name`	`TEXT`	No	Sanitized text	None	Legal full name of the payer counterparty; used for audit attribution.
`email`	`TEXT`	No	RFC 5322 check	None	Electronic mail address for digital receipt delivery and notification.
`phone`	`TEXT`	No	10-digit check	None	Primary communication handle; normalized to 10 digits starting with 6–9.
`purpose`	`TEXT`	No	Non-empty text	None	Commercial classification (e.g., Freelance Project, Engineering Advisory).
`source`	`TEXT`	No	Enumerated set	None	Entity category: Individual, Private, or Organisation.
`amount`	`NUMERIC(10, 2)`	No	Value boundary	None	Fixed-point currency; strictly constrained: 0 < amount <= 100,000.
`utr`	`TEXT`	Yes	Partial Unique	None	12-digit Indian UPI banking reference; unique across non-failed records.
`status`	`TEXT`	No	State set check	`'pending'`	Finite State Machine (FSM) ledger state: pending, successful, failed, deleted.

Column Identifier	PostgreSQL Datatype	Nullable	Primary Constraints	Default Assignment	Business Rule & Security Invariant
`notes`	`TEXT`	Yes	Free text	`''`	Forensic notes, failure reasons, or administrative remarks.
`verified_by`	`TEXT`	Yes	Email check	`NULL`	Authenticated email address of the administrator who executed settlement.
`verified_at`	`TIMESTAMPTZ`	Yes	Timestamp check	`NULL`	Microsecond-precision UTC timestamp marking the exact moment of verification.
`created_at`	`TIMESTAMPTZ`	No	Timestamp check	`timezone('utc', now())`	Server-side immutable UTC timestamp recording initial record creation.

• • •

2. Forensic Audit Log Table: public.transaction_audit_logs

Column Identifier	PostgreSQL Datatype	Nullable	Primary Constraints	Default Assignment	Functional Role
`id`	`BIGINT`	No	Primary Key	`GENERATED ALWAYS AS IDENTITY`	Monotonic event sequence identifier.
`verification_id`	`TEXT`	No	Domain reference	None	Target transaction domain key.
`action`	`TEXT`	No	Non-empty label	None	Categorical action label (e.g., `STATUS_SUCCESSFUL`, `STATUS_FAILED`).
`previous_status`	`TEXT`	Yes	State capture	None	State of transaction prior to mutation.
`new_status`	`TEXT`	Yes	State capture	None	New state of transaction after mutation.
`performed_by`	`TEXT`	Yes	Cryptographic ID	None	Email address of the authenticated administrator.
`notes`	`TEXT`	Yes	Operator note	None	Mandatory explanation for declines or audits.

Column Identifier	PostgreSQL Datatype	Nullable	Primary Constraints	Default Assignment	Functional Role
`created_at`	`TIMESTAMPTZ`	No	Timestamp check	`timezone('utc', now())`	Server-assigned UTC execution timestamp.

• • •

3. Row-Level Security (RLS) Policy Specification Truth Matrix

Policy Identifier	Target Operations	Permitted Roles	Evaluation Clause (Using)	Validation Gate (With Check)	Enforced Invariant
Policy 1: Ingestion	`INSERT`	`anon, authenticated`	N/A	`status = 'pending' AND amount > 0 AND amount <= 100000 AND verification_id IS NOT NULL`	Unauthenticated public clients can only initialize pending records within valid numerical thresholds.
Policy 2: Querying	`SELECT`	`anon`	`status != 'deleted'`	N/A	Payers can look up active and settled records; soft-deleted records are completely hidden.
Policy 3: Reference	`UPDATE`	`anon`	`status = 'pending'`	`status = 'pending'`	Anonymous clients can attach a UTR to pending rows, but cannot alter status to successful.
Policy 4: Admin	`ALL`	`authenticated`	`TRUE`	`TRUE`	Authenticated administrators holding valid JWT credentials possess full administrative ledger access.

• • •

4. Database Trigger Execution & Anti-Tamper Specification

- **Trigger Name:** `trg_protect_transaction_financials`
- **Execution Event:** Before any SQL `UPDATE` operation executes on `public.transactions` (Row-Level).
- **Execution Mode:** Security Definer with explicit search path binding (`public, auth`).
- **Rule 1 (Financial Lock):** If the calling role is anonymous and any of `amount`, `name`, or `verification_id` differ between the existing tuple and the proposed tuple, raise an unhandled exception: *Financial fields are locked and cannot be altered.*
- **Rule 2 (Status Lock):** If the calling role is anonymous and the proposed `status` differs from the existing `status` and does not equal `'pending'`, raise an unhandled exception: *Unauthorized attempt to modify transaction status.*
- **Outcome:** The transaction is rolled back by the database engine, preserving ledger integrity.

• • •

Appendix B: Security & Fraud Detection Algorithmic Specifications

1. Indian UPI 12-Digit UTR Heuristic Detection Algorithm

The reference validation engine processes user inputs across four sequential analytical stages:

1. **Stage 1 (Type & Length Sanitization):** Verifies that the input is a valid non-empty string. Strips surrounding whitespace. Evaluates against a 12-digit numeric regular expression requiring exactly twelve numeric digits (0 through 9).
2. **Stage 2 (Cyclic & Repeating Repetition):** Applies a back-reference regular expression capturing the leading digit and evaluating whether the following eleven characters are identical. Rejects sequences such as `000000000000` or `111111111111`.
3. **Stage 3 (Sequential Dummy Pattern Blacklist):** Compares the normalized string against known dummy sequences generated by mock payment applications:
   - Linear ascending sequences: `012345678901`, `123456789012`
   - Linear descending sequences: `987654321098`
   - Repetitive 6-digit blocks: `123456123456`
   - Leading-zero sequences: `000123456789`
   - Paired sequences: `112233445566`
4. **Stage 4 (Acceptance & Sanitized Return):** If all gates pass, the reference is marked as heuristically valid and passed to the ledger registration pipeline.

• • •

2. Indian Mobile Number Normalization Algorithm

1. **Stage 1 (Character Filtering):** Strips all international formatting glyphs, including whitespace, hyphens, brackets, and leading addition signs.
2. **Stage 2 (Prefix Normalization):** Inspects whether the sanitized string has a length of 12 and begins with the national country code `91`. If present, cleanly strips the leading `91`, isolating the 10-digit National Significant Number.
3. **Stage 3 (Regulatory Allocation Check):** Evaluates the 10-digit string against Department of Telecommunications (DoT) National Numbering Plan rules, verifying that the leading digit is strictly within the set {6, 7, 8, 9} and is followed by exactly nine numeric digits.

• • •

3. Dual-Hashing Receipt Seal Mathematical Model

The cryptographic seal generation operates across five formal deterministic transformations:

1. **Seed Construction:**

```
Seed = v || "|" || a || "|" || u || "|" || t || "|" || K_salt
```

(where v = Verification ID, a = Amount, u = UTR, t = Verified Timestamp, K_salt = Static System Pepper, and || denotes string concatenation)

2. **Accumulator Initialization:**

```
h1_0 = 0xDEADBEEF XOR L
h2_0 = 0x41C6CE57 XOR L
```

(where L = byte length of Seed)

3. **Character Byte Iteration (for each character byte c_i):**

```
h1_(i+1) = ((h1_i XOR c_i) * 2654435761) mod 2^32
h2_(i+1) = ((h2_i XOR c_i) * 1597334677) mod 2^32
```

4. **Final Avalanche Bit-Mixing:**

```
h1_prime = ((h1 XOR (h1 >> 16)) * 2246822507) XOR ((h2 XOR (h2 >> 13)) * 3266489909)
h2_prime = ((h2 XOR (h2 >> 16)) * 2246822507) XOR ((h1 XOR (h1 >> 13)) * 3266489909)
```

5. **Deterministic Hexadecimal Seal Emission:**

```
SEAL-[h1_prime[0..3]]-[h1_prime[4..7]]-[h2_prime[0..3]]
```

(producing a 16-character hyphenated uppercase hexadecimal string, e.g., SEAL-A7F2-9C4B-E180)

• • •

Appendix C: Dual-Sync Storage Engine & Network Protocol Specification

1. Dual-Write Asynchronous Ingestion Topology

When a transaction is created, the client execution engine dispatches concurrent persistence commands:

- **Stream 1 (Local Ephemeral):** Synchronously writes the full transaction entity to browser storage under the key `upi_payment_transactions`.
- **Stream 2 (Secondary Cloud Mirror):** Encodes fields into form entry identifiers and dispatches a background POST request to Google Forms in unconstrained cross-origin mode.
- **Stream 3 (Primary Relational):** Dispatches a structured JSON payload over TLS 1.3 to the Supabase REST endpoint.

• • •

2. Google Visualization (GViz) Dynamic Sheet Parsing Protocol

When operating in fallback status mode, the engine reads directly from Google Cloud Sheets:

1. Dispatches an HTTP GET request to the Google Visualization API endpoint: `https://docs.google.com/spreadsheets/d/[SHEET_ID]/gviz/tq?tqx=out:json`
2. Strips the JSONP encapsulation wrapper.
3. Applies regular expression pattern matching to identify table column headers regardless of physical column order:
    - Full Name matches regular expression: `full\s*name` or exact word `name`
    - Verification ID matches regular expression: `payment\s*id|verification\s*id`
    - UTR Reference matches regular expression: `upi\s*ref|utr|reference`
    - Monetary Amount matches regular expression: `amount`
    - Payment Status matches regular expression: `payment\s*status` or exact word `status`
4. Iterates rows in chronological order, deduplicating records by Verification ID and preserving the most recent settlement status.

• • •

Appendix D: Verification Test Vectors & Heuristic Benchmark Matrices

1. UTR Heuristic Benchmark Test Suite

Test Identifier	Input Vector	Expected Classification	Rationale & Gate Evaluated
UTR-TEST-01	`""` (Empty string)	Rejected	Fails Gate 1: Required string input.
UTR-TEST-02	`"12345"`	Rejected	Fails Gate 1: Truncated character length (< 12).
UTR-TEST-03	`"4102938475612"`	Rejected	Fails Gate 1: Excessive character length (> 12).
UTR-TEST-04	`"41029384ABCD"`	Rejected	Fails Gate 1: Contains non-numeric characters.
UTR-TEST-05	`"000000000000"`	Rejected	Fails Gate 2: Cyclic repetition of identical zero glyphs.
UTR-TEST-06	`"777777777777"`	Rejected	Fails Gate 2: Cyclic repetition of identical seven glyphs.
UTR-TEST-07	`"123456789012"`	Rejected	Fails Gate 3: Matches known ascending dummy sequence.
UTR-TEST-08	`"987654321098"`	Rejected	Fails Gate 3: Matches known descending dummy sequence.
UTR-TEST-09	`"410293847561"`	**Accepted**	Passes all gates: Authentic 12-digit Indian banking format.
UTR-TEST-10	`"629104857201"`	**Accepted**	Passes all gates: Authentic 12-digit Indian banking format.

• • •

2. Amount Boundary Test Suite

Test Identifier	Input Amount	Expected Result	Enforcement Boundary
AMT-TEST-01	`₹0.00`	Rejected	Enforces strictly positive balance rule (> 0).
AMT-TEST-02	`-₹500.00`	Rejected	Rejects negative numerical input.

Test Identifier	Input Amount	Expected Result	Enforcement Boundary
AMT-TEST-03	`₹0.50`	Rejected	Enforces sub-rupee micro-transaction floor (>= INR 1.00).
AMT-TEST-04	`₹1,00,001.00`	Rejected	Enforces NPCI statutory ceiling (<= INR 1,00,000.00).
AMT-TEST-05	`₹5,000.00`	**Accepted**	Valid standard integer consulting payment.
AMT-TEST-06	`₹250.75`	**Accepted**	Valid fixed-point decimal payment with paise precision.

• • •

Appendix E: Comprehensive Bibliography & NPCI Standards Reference

1. **National Payments Corporation of India (NPCI).** (2016–2026). *Unified Payments Interface (UPI) System Specifications and API Architecture (v2.0 & v2.1)*. Mumbai, India.
2. **Reserve Bank of India (RBI).** (2020). *Guidelines on Regulation of Payment Aggregators and Payment Gateways (DPSS.CO.PD.No.1810/02.14.008/2019-20)*. Central Office, Mumbai.
3. **Ministry of Electronics and Information Technology (MeitY).** (2023). *The Digital Personal Data Protection Act, 2023 (Act No. 22 of 2023)*. The Gazette of India, New Delhi.
4. **Fowler, G., Noll, L. C., & Vo, P.** (1991). *The FNV Non-Cryptographic Hash Algorithm*. IETF Internet-Draft.
5. **Appleby, A.** (2011). *MurmurHash3 Algorithms and Bit-Mixing Verification*. SMHasher Project Repository.
6. **PostgreSQL Global Development Group.** (2026). *PostgreSQL 16.x Documentation: Chapter 41 (Row-Level Security) and Chapter 43 (Triggers)*.
7. **Internet Engineering Task Force (IETF).** (2015). *RFC 7519: JSON Web Token (JWT)*. Authored by M. Jones, J. Bradley, N. Sakimura.
8. **World Wide Web Consortium (W3C).** (2018). *Web Content Accessibility Guidelines (WCAG) 2.1*. W3C Recommendation.