

Select the flow below and import it to your NodeRED flow editor, using the Import from Clipboard menu item.

```
1 [{"id":"ed9566e2.126a98","type":"template","z":"943925bf.6bc6d8","name":"format
html page","field":"payload","fieldType":"msg","format":"handlebars","syntax"
:"mustache","template":"<h1>Drinks available on : {{payload.day}}</h1>\n\n<ul
>\n{{#payload.drinks}}\n<li>{{drink}}</li> \n{{/payload.drinks}}\n</ul>\n\n
<h3>Specials:</h3> \n<hr>\n<ul>\n{{^payload.specials}}\nNone today, sorry
\n{{/payload.specials}}\n\n{{#payload.specials}}\n<li>{{drink}}</li>\n{{
/payload.specials}}\n</ul>","x":450,"y":900,"wires":[["15b02a6f.ea4fd6"]]}
,{ "id":"b3694c9e.4c96b","type":"function","z":"943925bf.6bc6d8","name"
:"Drinks","func":"msg.payload = \n          {'day':'Monday',\n
'drinks':[{ 'drink': 'coffee'}, \n          {'drink': 'tea'}, \n
          {'drink': 'orange juice'}]}\n          ;\nreturn msg;","outputs"
:1,"noerr":0,"x":270,"y":880,"wires":[["ed9566e2.126a98"]]}, {"id":"4c8e5f10
.b371a","type":"function","z":"943925bf.6bc6d8","name":"Specials","func":"msg
.payload = \n          {'day':'Monday',\n          'drinks':[{ 'drink':
'coffee'}, \n          {'drink': 'tea'}, \n
          {'drink': 'orange juice'}],\n          'specials':[{ 'drink': 'hot chocolate'},
\n          {'drink': 'espresso'}]}\n          ;\nreturn msg;","
"outputs":1,"noerr":0,"x":260,"y":920,"wires":[["ed9566e2.126a98"]]}, {"id"
:"8e28ca8e.71d738","type":"http in","z":"943925bf.6bc6d8","name":"/menu","url"
:"/menu","method":"get","swaggerDoc":"","x":90,"y":880,"wires":[["b3694c9e
.4c96b"]]}, {"id":"74bef85d.8b4108","type":"http response","z":"943925bf
.6bc6d8","name":"","x":790,"y":900,"wires":[]}, {"id":"174cd750.e8b329","type"
:"http in","z":"943925bf.6bc6d8","name":"/specials","url":"/specials","method"
:"get","swaggerDoc":"","x":100,"y":920,"wires":[["4c8e5f10.b371a"]]}, {"id"
:"15b02a6f.ea4fd6","type":"function","z":"943925bf.6bc6d8","name"
:"setHTTPHeader","func":"// If sending JSON data the content type is:\n//msg
.headers={\"Content-Type\":\"application/json\"}\n\n// For HTML use the
content type line below:\nmsg.headers={\"Content-Type\":\"text/html\"}\n\nreturn
msg;","outputs":1,"noerr":0,"x":640,"y":900,"wires":[["74bef85d.8b4108"]]}]
```

Examine the template and ensure you understand how the various template features works. Feel free to modify the template and the function nodes to explore the features of the template node.