

FLOOR TOP HARDENER



Bag size	25KG
Coverage	Light to Moderate Duty :2.5 - 3.5 kg/m² Moderate to Heavy Duty :3.5 - 5 kg/m² Super Heavy Duty :5 - 7.5 kg/m²
Application Ratio	• Scattering to be done in 2 stages • Scatter 60% of FTH over concrete, Let it sink • After 30 - 45 min scatter 40% of FTH
Areas of Application	Loading and unloading bays, Floors in Airport and Customshangars. Floors in Industrial environments, Warehouse, Factories, Public areas, carparking, Museums, Garages, Service Stations and outdoor Surface of all kinds.
Pot life	1-hour
Abrasion Resistance(MM)	Low Duty :0.20 Medium Duty : .13, Heavy Duty :.09
Color	Grey
Shelf life	12 months from the date of Manufacturing



TILE GROUT

Pack size	1 kg packs and 10 kg carton
Coverage	Depends on the tile size, Joint width and depth up to 3mm
Mixing Ratio	4L to 4.5 L Portable water would be added for a 25 kg bag
Areas of Application	For Interior and Exterior Tile Joints Can be used for a variety of tiles and stones Suitable for all types of ceramic tiles, variety of stones, glass mosaics, vitrified tiles, etc. Recommended for domestic and commercial applications
Pot life	1 hour
Conformity standards	Confirms to ANSI A118.6, EN 13888-3:2009 and ISO 13007-3: 2010 with Class “CG1” Characteristics
Colors	Available in 15 colors
Shelf life	6 months from the date of Manufacturing

Renafix

GP GROUT

Free Flow • Non Shrink



GP-GROUT

Pack size	25KG
Application Depth	10-100MM
Mixing Ratio	4 to 4.5 L Portable water would be added for a 25 kg bag
Areas of Application	Prefabricated Concrete Panels and Beams Stanchion base Plates, Equipment base plates and Columns, Bridge Bearings, Precast wall Panels, beams and columns, Anchoring dowels, Bolts and other fittings Underpinning and Void filling
Pot life	15 to 20 Min
Conformity standards	Confirms to ASTM C109, ASTM C348, ASTM 469 -02 and ASTM C1107:2011 Standard Specification for Packaged Dry, Hydraulic-Cement Grout (Nonshrink)
Compressive Strength in Days	1 - 24 N/mm ² , 3 - 45.2 N/mm ² , 7 - 56.0 N/mm ² 28 - 67.7 N/mm ²
Color	Grey
Shelf life	6 Months from the date of Manufacturing

Renabond

AAC JOINT MORTAR

Quick work • Self Curing



BLOCK JOINT ADHESIVE

Pack size	40KG
Coverage	1 40kg bag Covers 1 m3 of AAC Blocks (4"-75 blocks -100 sqft), (6" - 65 blocks -85 sqft) (8"-55 blocks - 70 sqft), (9" - 45 blocks - 60 sqft)
Mixing Ratio	10 L of Portable water for 40 kg of Powder
Areas of Application	(AAC Blocks) or Aerated Lightweight Concrete blocks (ALC Blocks), Fly ash bricks, and cellular concrete blocks
Pot life	40 min
Conformity standards	IS 2250 and ASTM C1660-09
Color	Grey
Shelf life	12 months from the date of Manufacturing

Renaplast

READY MIX PLASTER

Long Lasting • Superior Finish



READY MIX PLASTER

Pack size	50KG
Coverage	22-25 sqft
Mixing Ratio	9 to 11 Ltr of Portable water for 50 kg of Powder
Areas of Application	For Interior and Exterior Bricks Hollow Bricks, AAC Blocks, Walls Ideal for Patching, Repairing cracks, dents and Smoothing uneven plasterwork
Pot life	45 min
Conformity standards	IS 1661
Color	Grey
Shelf life	3 Months from the date of Manufacturing

Renacon

WALL PUTTY

Super Smooth Finish



FINE WALL PUTTY

Pack size	20KG
Coverage	16 to 20sqft
Mixing Ratio	16 to 20 Ltr of Portable water for 40 kg of Powder
Areas of Application	Interior and Exterior Applications. to Make uneven surfaces even and smooth
Pot life	45 min
Conformity standards	EN 1015-12:2000
Color	White
Shelf life	9 Months from the date of Manufacturing

Renacon

WALL PUTTY

Super Smooth Finish



COARSE WALL PUTTY

Pack size	40 & 20KG
Coverage	4 to 10 sqft per kg
Mixing Ratio	12 to 13 L of Portable water for 40 kg of Powder and 7 to 8 L for 20 kg of powder
Areas of Application	Interior and Exterior Applications.to Make uneven surfaces even and smooth
Pot life	45 min
Conformity standards	EN 1015-12:2000
Color	White
Shelf life	9 Months from the date of Manufacturing

Renafix

TILE ADHESIVE

Perfect FIX for a superior floor



TILE ADHESIVE-201

Pack size	20KG
Coverage	Approx 55-60 sft per 20kg bag with 1/4" x 1/4" (6mm x 6mm) square notched trowel for average bed thickness of 3mm.
Mixing Ratio	4 to 5 L of Portable water for 20 kg of Adhesive
Areas of Application	Internal cement floor for Ceramic Tiles
Pot life	2 to 3 hours
Applicable Standards	ANSI A118.1-1999; EN 12004 & ISO 13007; IS15477
Color	White
Size of the tile/ Stone	Small format tiles (300mm x 300mm) & below
Shelf life	12 months from the date of Manufacturing

Renafix

TILE ADHESIVE

Perfect FIX for a superior floor



TILE ADHESIVE-211

Pack size	20KG
Coverage	Approx 55-60 sft per 20kg bag with 1/4" x 1/4" (6mm x 6mm) square notched trowel for average bed Thickness of 3mm.
Mixing Ratio	4 to 5 L of Portable water for 20 kg of Adhesive
Areas of Application	• Internal cement floor for (Ceramic tiles) • Internal - concrete / plaster wall (Ceramic tiles)
Pot life	3 to 4 hours
Applicable Standards	ANSI A118.1-1999; EN 12004 & ISO 13007;IS15477:2019
Colors	Grey / White
Size of the tile/ Stone	Small format tiles (300mm x 300mm) & below
Shelf life	12 months from the date of Manufacturing

Renafix

TILE ADHESIVE

Perfect FIX for a superior floor



TILE ADHESIVE-222

Pack size	20KG
Coverage	Approx 55-60 sft per 20kg bag with 1/4" x 1/4" (6mm x 6mm) square notched trowel for average bed Thickness of 3mm.
Mixing Ratio	4 to 5 L of Portable water for 20 kg of Adhesive
Areas of Application	• Internal cement floor - ceramic & vitrified tiles • Internal - concrete / plaster wall - ceramic & vitrified tiles
Pot life	3 to 4 hours
Applicable Standards	ANSI A118.4; EN 12004 & ISO 13007; IS15477:2019
Colors	Grey / White
Size of the tile/ Stone	• Vitrified tiles (300mm x 300mm) & below • Ceramic tiles (up to 600mm x 600mm)
Shelf life	12 Months from the date of Manufacturing

Renafix

TILE ADHESIVE

Perfect FIX for a superior floor



TILE ADHESIVE-333

Pack size	20KG
Coverage	55 Sft per 20 kg pack using 1/4 x 1/4 (6mm x 6mm) square notched trowel for a bed thickness of 3mm.
Mixing Ratio	4 to 5 L of Portable water for 20 kg of Adhesive
Areas of Application	• Internal cement floor -ceramic & vitrified tiles, Glass Mosaic Tiles - Paper Faced • Internal - concrete / plaster wall - Ceramic / Vitrified Tiles / Glass Mosaic Tiles - Paper Faced/Small Format Natural Stone • Internal Shear wall - Ceramic / Vitrified Tiles /Small Format Natural Stone • External - concrete/ plaster wall - Ceramic / Vitrified tiles / Glass Mosaic Tiles - Paper Faced/Medium Format Stones
Pot life	4 hours
Applicable Standards	ANSI A118.4; EN 12004 & ISO 13007; IS15477:2019
Color	Grey
Size of the tile/ Stone	Ceramic tiles & vitrified tiles(up to 600mm x 600mm)
Shelf life	18 months from the date of Manufacturing

Renafix

TILE ADHESIVE

Perfect FIX for a superior floor



TILE ADHESIVE-444

Pack size	20KG
Coverage	Approx 55-60 sft per 20kg bag with 1/4" x 1/4" (6mm x6mm) square notched trowel for average bed Thickness of 3mm.
Mixing Ratio	6 to 6.5 L of Portable water for 20 kg of Adhesive
Areas of Application	• Internal cement floor -ceramic & vitrified tiles, Glass Mosaic Tiles- Paper Faced • Internal - concrete /plaster wall -Ceramic / Vitrified Tiles /Glass Mosaic Tiles - Paper Faced/ Small Format Natural Stone/Large Format Stones • Internal Shear wall -Ceramic / Vitrified Tiles /Small Format Natural Stone • Internal - gypsum board wall /calcium silicate board wall - Ceramic / Vitrified Tiles / Glass Mosaic Tiles - Paper Faced • External - concrete/ plaster wall - Ceramic / Vitrified tiles / Glass Mosaic Tiles - Paper Faced/Medium Format Stones
Pot life	4 hours
Applicable Standards	ANSI A118.4; EN 12004 & ISO 13007; IS15477
Color	Grey
Size of the tile/ Stone	For Larger Tiles (600mm x 600mm & above) • kindly consult our technical team before application
Shelf life	12 months from the date of Manufacturing