

RETENTION BASED AUTOREGRESSIVE MODELS
FOR MODELLING NEURAL DYNAMICS

BY

ABHINAV MURALEEDHARAN

A thesis submitted in conformity with
the requirements for the degree of
Masters in Engineering
Graduate Department of Institute for Aerospace Studies
University of Toronto

© 2023 Abhinav Muraleedharan

ABSTRACT

Retention based autoregressive models for modelling neural dynamics

Abhinav Muraleedharan

Masters in Engineering

Graduate Department of Institute for Aerospace Studies

University of Toronto

2023

In this work, we present Retention, a novel autoregressive model for generative modelling of sequences. Unlike Transformer based autoregressive models, retention scales linearly with respect to context size. We apply retention based models for modelling neural dynamics and achieve SOTA performance in neural modelling and behaviour decoding.

*To Mom,
who did something nice.*

ACKNOWLEDGEMENTS

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait nulla facilisi. Lorem ipsum dolor sit amet,

PUBLICATIONS

This work has not been published yet.

CONTENTS

1	INTRODUCTION	1
2	PROBLEM STATEMENT	3
3	METHODS	5
3.1	Motivation	5
3.2	Retention	5
3.3	Training Retention Based Models	6
3.4	Architecture	6
4	RESULTS	7
4.1	A New Section	7
4.2	Another Section in This Chapter	8
4.3	Some Math	9
5	CONCLUSION	10
5.1	A New Section	10
5.2	Another Section in This Chapter	11
5.3	Some Math	12

INTRODUCTION

Hard problems inspire the creation of novel algorithms. These novel algorithms then find application in various contexts, distant from the original application which it was designed for. Understanding the human brain, specifically its dynamics and the relationship between dynamics of the brain and behaviour is a hard problem. Unraveling the dynamics of the brain holds the key to understanding the neural mechanisms underlying these processes. Beyond modeling neural activity, elucidating how such activity correlates with an organism's behavior is crucial for developing Brain-Computer Interfaces, clinical treatments for conditions like epilepsy, depression, and other neurodegenerative diseases. In this thesis, we develop scalable methods for modelling neural dynamics and relationship between the dynamics of the brain and behaviour. Although methods in this thesis are developed specifically for neural data, we believe that our approach would find application in diverse sequence modelling tasks in language, finance and engineering.

Machine learning techniques have played a pivotal role in modeling brain dynamics, and modeling the correlation between neural dynamics and behavior of an animal. In [POC⁺18], Pandarinath et al. introduced LFADS, an RNN-based method to infer latent dynamics from neural data. More recently, transformer-based models [VSP⁺17, GZ22], have been applied to learn neural dynamics and behaviour model. In [YP21], Pandarinath et al applied transformer-based models to learn neural dynamics without an explicit dynamical model. While LFADS and NDT (Neural Data Transformers) were focused on learning neural dynamics from single trial recordings, Azabou et.al recently introduced POYO [AAG⁺23], a transformer-based model to learn neural dynamics from multi-session neural recordings.

Although transformer-based models have shown remarkable success in general language modelling tasks and more recently in learning population dynamics of neurons, they exhibit poor scaling properties especially when applied to neural spiking data. Furthermore, unlike text data, neural recording probes sample on the order of kHz, and hence are characterized by high temporal resolution. This unique temporal aspect of neural

spiking data presents a challenge for transformers, which are originally designed for sequential data but may struggle with the high-frequency nature of neural signals. The transformer’s poor scaling properties become particularly evident when recording from a large number of neurons simultaneously, as the number of potential firing patterns exponentially increases with the number of neurons.

In this work, we introduce a new class of autoregressive models to overcome limitations imposed by the architecture of attention-based transformer models. Our model has an unbounded context length and hence can capture long-range dependencies in the time series dataset. Furthermore, the complexity of training and inference of the parametrized model is independent of the context length, and hence our approach is computationally more efficient when compared to transformer-based autoregressive models.

PROBLEM STATEMENT

Imagine we are recording data from D neurons distributed across different regions of the brain. Let $x(t_i) \in \mathbb{R}^D$ denote the observed neural activity at timestep t_i and let y_i denote the observed behaviour of the animal at timestep t_i . From the time series dataset $\mathcal{D} = \{(x_i, y_i, t_i)\}_{i=1}^N$ of neural recordings, our goal is to construct:

- A predictive model of underlying brain dynamics
- A probabilistic model to predict behaviour of the organism at time $t + 1$ given brain recordings until timestep t .

More formally, let's assume that the spiking activity is generated by an underlying non-stationary stochastic process defined by $p_t(x)$.

$$x(t) \sim p_t(x) \quad (2.1)$$

The probability of observing a sequence of neural recordings and behavior can be expressed as:

$$p(\{x_1, y_1\}, \{x_2, y_2\}, \{x_3, y_3\}, \dots) = \lim_{N \rightarrow \infty} \prod_{i=1}^N p(\{x_i, y_i\} | \{x_1, y_1\}, \{x_2, y_2\}, \dots, \{x_{i-1}, y_{i-1}\}) \quad (2.2)$$

In the context of neural recordings, it is convenient to assume that the neural recording data and behavior can be modelled with separate probability distributions of the form:

$$\prod_{i=1}^N p_d(\{x_i\} | \{x_1\}, \{x_2\}, \dots, \{x_{i-1}\}) \quad (2.3)$$

$$\prod_{i=1}^N p_b(\{y_i\} | \{x_1\}, \{x_2\}, \dots, \{x_{i-1}\}) \quad (2.4)$$

Specifically, we assume that the neural observed neural spiking data at timestep t_i is not dependent on the behavior variables in the preceding timesteps. Probability distributions of this nature have been extensively investigated in the field of language modeling. In conventional autoregressive frameworks, the approximation of conditional distributions often involves the utilization of parameterized models constrained by a finite

context limit [VSP⁺17]. While autoregressive models of this kind have been extremely successful in generating plausible language [RNS⁺18], they still struggle to capture long-range dependencies due to the finite context length limit [Hah20]. Furthermore, the complexity of training and inference of transformer-based models is $\mathcal{O}(N^2)$, where N is the context length of the transformer model.

METHODS

3.1 MOTIVATION

For modelling sequences, we are faced with three challenges. First, the length of the sequence is not fixed. Second, a machine learning model for modelling sequences should be capable of modelling long range dependencies. Third, for discrete problems, the sequences we cannot model these using odes.

3.2 RETENTION

Mathematically, retention is defined as an exponentially weighted sum of a sequence of discrete vectors. If the vectors are drawn from a continuous space, then we perform thresholding operation to discretize the vectors. Specifically, given a sequence of vectors $\{x_i\}_{i=1}^N$, $x_i \in \mathbb{R}^d$, Retention variable ζ_k as:

$$\zeta_i = \sum_{k=1}^{i-1} 2^{-k} \sigma_{\theta}(x_{i-k}) \quad (3.1)$$

Here, $x_k \in \mathbb{R}^D$ is the observed neural activity at timestep t_k , and $\sigma_{\theta} : \mathbb{R}^D \rightarrow \{0, 1, 2, \dots, M\}^D$ is a thresholding function, where $\sigma_{\theta}(x_i^j) = 1, \forall x_i^j > \theta$. (We use the notation x_i^j to denote j th element of the vector x_i .)

Now, note that ζ_k has a recursive property, specifically:

$$\zeta_{i+1} = 2^{-1} \zeta_i + 2^{-1} \sigma_{\theta}(x_i) \quad (3.2)$$

Modelling Conditional Distributions with Retention Variables

Now, we approximate the conditional distribution defined in eq(3) with

$$\prod_{i=1}^N p_d(\{x_i\} | \{x_1\}, \{x_2\}, \dots, \{x_{i-1}\}) \approx \prod_{i=1}^N p_d(\{x_i\} | \zeta_i) \quad (3.3)$$

To learn the dynamics of the brain from neural recordings in an unsupervised manner, we maximize the following likelihood:

$$\mathcal{L}(X, \theta) = \sum_i \log(p_d(\{x_i\}|\zeta_i; \theta)) \quad (3.4)$$

Here, $X = \{x_1, x_2, \dots, x_M\}$, the dataset of neural recordings.

Note that in this approach, the context window is not bounded, and the complexity of learning the parametrized model $p_d(\{x_i\}|\zeta_i; \theta)$ is independent of the length of the context window. While training the model, we apply eq(6) to recursively update ζ_i in an online fashion, instead of pre-computing and storing $\{\zeta_i\}_{i=1}^N$ separately.

To learn the correlation between neural dynamics and behavior, we follow a similar approach and approximate the conditional distribution defined in eq(4) with:

$$\prod_{i=1}^N p_b(\{y_i\}|\{x_1\}, \{x_2\}, \dots, \{x_{i-1}\}) \approx \prod_{i=1}^N p_b(\{y_i\}|\zeta_i) \quad (3.5)$$

We define the loss function associated with this approach as the negative log-likelihood of the observed behavioral outcomes given the estimated neural activity states. Formally, the loss function \mathcal{L} is expressed as:

$$\mathcal{L}(X, Y, \phi) = - \sum_i \log p_b(\{y_i\}|\zeta_i; \phi)$$

3.3 TRAINING RETENTION BASED MODELS

In this section, we describe how retention based models are trained.

Online Computation of Retention Variable

Offline Computation of Retention Variable

3.4 ARCHITECTURE

Two Photon Dataset: U-Net

Fully connected networks

RESULTS

Ei choro aeterno antiopam mea, labitur bonorum pri no [Gau27]. His no decore nemore graecis. Suavitate interpretaris eu, vix eu libris efficiantur.

4.1 A NEW SECTION

Illo principalmente su nos. Non message *occidental* angloromanic da. Debitas effortio simplicate sia se, auxiliar summarios da que, se avantiare publicationes via. Pan in terra summarios, capital interlingua se que. Al via multo esser specimen, campo responder que da. Le usate medical addresses pro, europa origine sanctificate nos se.

Examples: *Italics*, ALL CAPS, SMALL CAPS, LOW SMALL CAPS.

Colours: red, green, blue

Test for a Subsection

Lorem ipsum at nusquam appellantur his, ut eos erant homero concludaturque. Albucius appellantur deterruisset id eam, vivendum partiendo dissentiet ei ius. Vis melius facilisis ea, sea id convenire referrentur, takimata adolescens ex duo. Ei harum argumentum per. Eam vidit exerci appetere ad, ut vel zzril intellegam interpretaris.

Errem omnium ea per, pro con populo ornatus cu, ex qui dicant nemore melius. No pri diam iriure euismod. Graecis eleifend appellantur quo id. Id corpora inimicus nam, facer nonummy ne pro, kasd repudiandae ei mei. Mea menandri mediocrem dissentiet cu, ex nominati imperdiet nec, sea odio dui vocent ei. Tempor everti appareat cu ius, ridens audiam an qui, aliquid admodum conceptam ne qui. Vis ea melius nostrum, mel alienum euripidis eu.

Ei choro aeterno antiopam mea, labitur bonorum pri no. His no decore nemore graecis. In eos meis nominavi, liber soluta vim cu.

Autem Timeam

Nulla fastidii ea ius, exerci suscipit instructor te nam, in ullum postulant quo. Congue quaestio philosophia his at, sea odio autem vulputate ex.

Note: The content of this chapter is just some dummy text. It is not a real language.

Cu usu mucius iisque voluptua. Sit maiorum propriae at, ea cum primis intellegat. Hinc cotidieque reprehendunt eu nec. Autem timeam deleniti usu id, in nec nibh altera.

4.2 ANOTHER SECTION IN THIS CHAPTER

Non vices medical da. Se qui peano distinguer demonstrate, personas internet in nos. Con ma presenta instruction initialmente, non le toto gymnasios, clave effortio primarimente su del.¹

Sia ma sine svedese americas. Asia representantes un nos, un altere membros qui.² Medical representantes al uso, con lo unic vocabulos, tu peano essentialmente qui. Lo malo laborava anteriormente uso.

- (a) Illo secundo continentes sia il, sia russo distinguer se. Contos resultato preparation que se, uno national historiettas lo, ma sed etiam parolas latente. Ma unic quales sia. Pan in patre altere summario, le pro latino resultato.
- (b) Lo vista ample programma pro, uno europeae addresses ma, abstracte intention al pan. Nos duce infra publicava le. Es que historia encyclopedia, sed terra celos avantiate in. Su pro effortio, o.

Tu uno veni americano sanctificate. Pan e union linguistic del le, del un apprende denomination.

Personas Initialmente

Uno pote summario methodicamente al, uso debe nomina hereditage ma. Iala rapide ha del, ma nos esser parlar. Maximo dictionario sed al.

A Subsubsection

Deler utilitate methodicamente con se. Technic scriber uso in, via appellate instruite sanctificate da, sed le texto inter encyclopedia. Ha iste americas que, qui ma tempore capital.

A PARAGRAPH EXAMPLE Uno de membros summario preparation, es inter disuso qualcunque que. Del hodie philologos occidental al, como publicate litteratura in web. Veni americano es con, non internet millennios secundarimente ha.

¹ Uno il nomine integre, lo tote tempore anglo-romanice per, ma sed practice philologos historiettas.

² De web nostre historia angloromanice.



Figure 4.1: Some smart caption

Titulo utilitate tentation duo ha, il via tres secundarimente, uso americano inicialmente ma. De duo deler personas inicialmente. Se duce facite westeuropee web, nos clave articulos ha.

Medio integre lo per, non es linguas integre. Al web altere integre periodicos, in nos hodie basate. Uno es rapide tentation, usos human synonymo con ma, parola extrahite [Figure 5.1](#) greco-latin ma web. Veni signo rapide nos da.

4.3 SOME MATH

We can define scalar multiplication in \mathbb{R}^n by

$$c[u_1, \dots, u_n] = [cu_1, \dots, cu_n]$$

You can now check that for $u, v \in \mathbb{R}^n$, we have

$$c(u + v) = cu + cv$$

CONCLUSION

Ei choro aeterno antiopam mea, labitur bonorum pri no [Gau27]. His no decore nemore graecis. Suavitate interpretaris eu, vix eu libris efficiantur.

5.1 A NEW SECTION

Illo principalmente su nos. Non message *occidental* angloromanic da. Debitas effortio simplicate sia se, auxiliar summarios da que, se avantiare publicationes via. Pan in terra summarios, capital interlingua se que. Al via multo esser specimen, campo responder que da. Le usate medical addresses pro, europa origine sanctificate nos se.

Examples: *Italics*, ALL CAPS, SMALL CAPS, LOW SMALL CAPS.

Colours: red, green, blue

Test for a Subsection

Lorem ipsum at nusquam appellantur his, ut eos erant homero concludaturque. Albucius appellantur deterruisset id eam, vivendum partiendo dissentiet ei ius. Vis melius facilisis ea, sea id convenire referrentur, takimata adolescens ex duo. Ei harum argumentum per. Eam vidit exerci appetere ad, ut vel zzril intellegam interpretaris.

Errem omnium ea per, pro con populo ornatus cu, ex qui dicant nemore melius. No pri diam iriure euismod. Graecis eleifend appellantur quo id. Id corpora inimicus nam, facer nonummy ne pro, kasd repudiandae ei mei. Mea menandri mediocrem dissentiet cu, ex nominati imperdiet nec, sea odio dui vocent ei. Tempor everti appareat cu ius, ridens audiam an qui, aliquid admodum conceptam ne qui. Vis ea melius nostrum, mel alienum euripidis eu.

Ei choro aeterno antiopam mea, labitur bonorum pri no. His no decore nemore graecis. In eos meis nominavi, liber soluta vim cu.

Autem Timeam

Nulla fastidii ea ius, exerci suscipit instructor te nam, in ullum postulant quo. Congue quaestio philosophia his at, sea odio autem vulputate ex.

Note: The content of this chapter is just some dummy text. It is not a real language.

Cu usu mucius iisque voluptua. Sit maiorum propriae at, ea cum primis intellegat. Hinc cotidieque reprehendunt eu nec. Autem timeam deleniti usu id, in nec nibh altera.

5.2 ANOTHER SECTION IN THIS CHAPTER

Non vices medical da. Se qui peano distinguer demonstrate, personas internet in nos. Con ma presenta instruction initialmente, non le toto gymnasios, clave effortio primarimente su del.¹

Sia ma sine svedese americas. Asia representantes un nos, un altere membros qui.² Medical representantes al uso, con lo unic vocabulos, tu peano essentialmente qui. Lo malo laborava anteriormente uso.

- (a) Illo secundo continentes sia il, sia russo distinguer se. Contos resultat preparation que se, uno national historiettas lo, ma sed etiam parolas latente. Ma unic quales sia. Pan in patre altere summario, le pro latino resultado.
- (b) Lo vista ample programma pro, uno europeae addresses ma, abstracte intention al pan. Nos duce infra publicava le. Es que historia encyclopedia, sed terra celos avantiate in. Su pro effortio, o.

Tu uno veni americano sanctificate. Pan e union linguistic del le, del un apprende denomination.

Personas Initialmente

Uno pote summario methodicamente al, uso debe nomina hereditage ma. Iala rapide ha del, ma nos esser parlar. Maximo dictionario sed al.

A Subsubsection

Deler utilitate methodicamente con se. Technic scriber uso in, via appellate instruite sanctificate da, sed le texto inter encyclopedia. Ha iste americas que, qui ma tempore capital.

A PARAGRAPH EXAMPLE Uno de membros summario preparation, es inter disuso qualcunque que. Del hodie philologos occidental al, como publicate litteratura in web. Veni americano es con, non internet millennios secundarimente ha.

¹ Uno il nomine integre, lo tote tempore anglo-romanice per, ma sed practic philologos historiettas.

² De web nostre historia angloromanice.



Figure 5.1: Some smart caption

Titulo utilitate tentation duo ha, il via tres secundarimente, uso americano inicialmente ma. De duo deler personas inicialmente. Se duce facite westeuropee web, nos clave articulos ha.

Medio integre lo per, non es linguas integre. Al web altere integre periodicos, in nos hodie basate. Uno es rapide tentation, usos human synonymo con ma, parola extrahite [Figure 5.1](#) greco-latin ma web. Veni signo rapide nos da.

5.3 SOME MATH

We can define scalar multiplication in \mathbb{R}^n by

$$c[u_1, \dots, u_n] = [cu_1, \dots, cu_n]$$

You can now check that for $u, v \in \mathbb{R}^n$, we have

$$c(u + v) = cu + cv$$

BIBLIOGRAPHY

- [AAG⁺23] Mehdi Azabou, Vinam Arora, Venkataramana Ganesh, Ximeng Mao, Santosh Nachimuthu, Michael J Mendelson, Blake Richards, Matthew G Perich, Guillaume Lajoie, and Eva L Dyer, *A unified, scalable framework for neural population decoding*, arXiv preprint arXiv:2310.16046 (2023).
- [Gau27] Carl Friedrich Gauß, *General investigations of curved surfaces*, 1827.
- [GZ22] Nicholas Geneva and Nicholas Zabaras, *Transformers for modeling physical systems*, *Neural Networks* **146** (2022), 272–289.
- [Hah20] Michael Hahn, *Theoretical limitations of self-attention in neural sequence models*, *Transactions of the Association for Computational Linguistics* **8** (2020), 156–171.
- [POC⁺18] Chethan Pandarinath, Daniel J O’Shea, Jasmine Collins, Rafal Jozefowicz, Sergey D Stavisky, Jonathan C Kao, Eric M Trautmann, Matthew T Kaufman, Stephen I Ryu, Leigh R Hochberg, et al., *Inferring single-trial neural population dynamics using sequential auto-encoders*, *Nature methods* **15** (2018), no. 10, 805–815.
- [RNS⁺18] Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al., *Improving language understanding by generative pre-training*.
- [VSP⁺17] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin, *Attention is all you need*, *Advances in neural information processing systems* **30** (2017).
- [YP21] Joel Ye and Chethan Pandarinath, *Representation learning for neural population activity with neural data transformers*, arXiv preprint arXiv:2108.01210 (2021).

COLOPHON

This thesis was typeset using the typographical look-and-feel classicthesis developed by André Miede and Ivo Pletikosić.

The style was inspired by Robert Bringhurst's seminal book on typography *"The Elements of Typographic Style"*.

Here you can insert things like "Figures were created with..."

[Insert version number/description, if you want]