# Invite System

Exact API fields, screens, navigation, authentication handoff, and online-game transition.

## Overview

The invite system is a link-based online game flow. The creator creates an invite and receives an invite code, game ID, and shareable link. The other player opens the link, previews the invitation, logs in if required, joins the invite, and then both clients connect to the same online game through WebSocket.

## End-to-end flow

```
Player A -> POST /api/invite Server -> invite_code + game_id + link Player A -> opens online_game/{gameId} Player B -> https://caisaara.duckdns.org/play/{code} App -> GET /api/invite/{code} Player B -> POST /api/invite/{code}/join Both -> WebSocket /ws/{gameId}?token={accessToken}
```

## Create invite request

Source: data/remote/dto/CreateInviteRequest.kt and data/remote/InviteService.kt

| Field | Type | JSON name | Meaning |
|---|---|---|---|
| timeControlMinutes | Int | time_control_minutes | Initial minutes per player. |
| incrementSeconds | Int | increment_seconds | Increment added after a move. |
| color | String | color | Creator preference: white, black, or random. |
| rated | Boolean | rated | Whether the server should treat the match as rated. |

```
POST /api/invite Body: { time_control_minutes, increment_seconds, color, rated }
```

## Create invite response

Source: data/remote/dto/CreateInviteResponse.kt

| Field | Type | JSON name | Meaning |
|---|---|---|---|
| inviteCode | String | invite_code | Code embedded in the invite URL. |
| gameId | String | game_id | Online game identity used after joining. |
| link | String | link | Shareable URL returned by the server. |
| timeControlMinutes | Int | time_control_minutes | Server-confirmed time control. |
| incrementSeconds | Int | increment_seconds | Server-confirmed increment. |
| color | String | color | Server-confirmed creator color. |
| rated | Boolean | rated | Server-confirmed rated status. |
| status | String | status | Invite/game status. |

## Creator screens and classes

| Layer | File | Responsibility |
|---|---|---|
| UI | presentation/invite/PlayWithFriendScreen.kt | Entry screen; currently presents Create Match Link. |
| UI | presentation/invite/CreateInviteScreen.kt | Color, takeback, link display, copy, share, and waiting-board actions. |
| State | presentation/invite/CreateInviteViewModel.kt | Validates fields and calls repository. |
| Data | data/repository/InviteRepository.kt | Wraps invite API calls in Result. |
| API | data/remote/InviteService.kt | Retrofit endpoints. |
| Navigation | presentation/navigation/AppNavigation.kt | Routes to creation and online game. |

## Join flow

```
1. Android deep link matches https://caisaara.duckdns.org/play/{code}. 2. JoinInviteViewModel.load() calls GET /api/invite/{code}. 3. The preview displays inviter, time control, increment, and your color. 4. If there is no token, PendingInviteStore saves the code and navigation goes to login. 5. After login, goHomeThenPendingInvite() consumes the code and reopens the invite. 6. JOIN GAME calls POST /api/invite/{code}/join. 7. The returned game_id navigates to online_game/{gameId}.
```

## Join response fields

Source: data/remote/dto/InvitePreviewResponse.kt and JoinGameResponse.kt.

| Object | Fields used by app |
|---|---|
| InvitePreviewResponse | inviter.id, inviter.username, timeControlMinutes, incrementSeconds, color, gameId |
| JoinGameResponse | gameId |

## Important current behavior

Friend search is visual only and disabled. Invite creation defaults to 10 minutes and zero increment because CreateInviteScreen does not currently expose the ViewModel time-control setters. Public Spectators is displayed but is not included in CreateInviteRequest. Allow Takebacks maps to rated = false.