

Introduction to Software Systems (CS6.201)

Summer 2021, IIIT Hyderabad

03 June, Thursday (Lecture 4)

Taught by Sai Anirudh Karri

Arrays

Arrays can be declared by listing out the elements, separated by spaces and enclosed in parentheses; for example ("cse" "csd" "ece" "ecd" "cld" "cnd" "chd").

If the array is accessed using \$, only the first (index 0) entry is printed. In order to print all entries, use the syntax `${list[*]}`. One can index into lists using the syntax `${list[indx]}`. Individual elements in the list can also be altered by using `list[indx]` as an lvalue. Lists have no boundaries; any index can be used.

Search-and-replace can be run on the contents of an array; for example `${list[*]/find/replace}` will return the edited array. It will *not* edit the original array; `${list[*]}` is unchanged.

Loops

for loops follow the syntax

```
for var in list
do
    code
done
```

In case of a variable range, one can use the syntax `{1..n}`. If one does not want to use consecutive numbers, the `$(seq b step until)` syntax runs the loop with values `b`, `b+step`, and so on till `until`.

while loops are similar:

```
while cond
do
    code
done
```

Just like in if statements, the condition needs to have the `test` command or be enclosed in square brackets.

Switch case

Switch case statements have the following syntax:

```
case <expr> in
  case_1 ) code1 ;;
  case_2 ) code2 ;;
  ...
  *) default ;;
esac
```