

# Introduction to Software Systems (CS6.201)

Summer 2021, IIIT Hyderabad

03 June, Thursday (Lecture 4)

Taught by Sai Anirudh Karri

## Arrays

Arrays can be declared by listing out the elements, separated by spaces and enclosed in parentheses; for example ("cse" "csd" "ece" "ecd" "cld" "cnd" "chd").

If the array is accessed using \$, only the first (index 0) entry is printed. In order to print all entries, use the syntax \${list[\*]}. One can index into lists using the syntax \${list[indx]}. Individual elements in the list can also be altered by using list[indx] as an lvalue. Lists have no boundaries; any index can be used.

Search-and-replace can be run on the contents of an array; for example \${list[\*]/find/replace} will return the edited array. It will *not* edit the original array; \${list[\*]} is unchanged.

## Loops

for loops follow the syntax

```
for var in list
do
    code
done
```

In case of a variable range, one can use the syntax {1..5}. If one does not want to use consecutive numbers, the \$(seq 1 4 20) (for instance) syntax runs the loop with values 1, 5, 11, and so on.

while loops are similar:

```
while cond
do
    code
done
```

Just like in if statements, the condition needs to have the **test** command or be enclosed in square brackets.

## Switch case

Switch case statements have the following syntax:

```
case <expr> in
  case_1 ) code1 ;;
  case_2 ) code2 ;;
  ...
  *) default ;;
esac
```