Does Timing Matter? Temporal Signals and Time-Robustness in AI Detection of Mental-Health Risk from Reddit Posts

Group 2, COMP 8790 Topics in Applied AI

Phase I report (draft)

Abstract

Saeed and Ahmed (2025) report that adding posting-time features to a BiLSTM text classifier improves six-way classification of mental-health subreddits (weighted F1 0.7376 versus 0.7222). We test that claim against a strong text-only baseline (TF-IDF with logistic regression) and a fine-tuned MentalRoBERTa, using five replicates, paired bootstrap intervals, and a time-shift split that avoids a data-collection artefact we found in the shared dataset. For TF-IDF and the BiLSTM we find no reliable gain from time features on the paper's own random split, a gain of at most 0.006 macro F1 for the weaker BiLSTM on two splits, and a small loss for TF-IDF under time shift. Training on earlier posts and testing on later ones costs no measurable accuracy over Nov 2021 to Nov 2022. [**Method B results to be added.**]

1 Introduction

Reddit communities are used to study mental-health language at scale, and detection models could support triage tools. A recent paper claims that when a post was written (hour, weekday, month) carries useful signal. If true it is cheap to add, if false it may be a shortcut that breaks when data drift. We ask whether the claim holds against a strong text baseline and how each method behaves when trained on earlier posts and tested on later ones. Posts are labelled by subreddit, not by clinical diagnosis, so this is a study of community language and not of diagnosis.

2 Problem Definition

Given a post x with text and a timestamp, predict one of six classes (depression, anxiety, bipolar, BPD, schizophrenia, mentalillness). **RQ1:** do posting-time features significantly improve macro F1 over a strong text-only model, and how much does each method lose when trained on earlier posts and tested on later ones? Our main metric is macro F1, because it weights small classes equally. We also report weighted F1 to compare with the paper, whose recall equals its accuracy, which is what weighted averaging gives.

3 Related Work

Saeed and Ahmed (2025) combine a BiLSTM text branch with an LSTM over time features through cross-modal attention, and report the gain above on 2021 to 2022 Reddit data; they release no code. Ji et al. (2022) pretrain MentalBERT and MentalRoBERTa on mental-health Reddit text and show gains on detection tasks, which is why we use MentalRoBERTa as our strong model. Low et al. (2020) study how language in mental-health subreddits changed during COVID-19 and release a dataset with author identifiers, which we use as a second check. [**Team members to add their reviewed papers.**]

4 Methodology

Data. The Kaggle "Mental Disorders Identification (Reddit)" file (701,787 posts, 2010 to 2022, timestamps with hour, no author column) is the anchor paper's data. After the same filters (2021 and 2022 only, no NSFW, no empty or very short posts) and our leakage control, 483,715 posts remain. Leakage control removes subreddit mentions ("r/depression", "this sub"), texts that appear under more than one label, and duplicates. Condition names stay in the text, which makes the task easier than real detection and is a limitation. Each replicate draws a stratified 60k sample by label and month.

Splits. `random` (80/20 stratified, as in the paper), `random_matched` (same test, training reduced to the size of the time split), `temporal_late` (train Nov 2021 to Jun 2022, test Aug to Nov 2022), and `temporal_2021_22` (train 2021, test 2022). The last is confounded: in this file depression, bipolar and schizophrenia posts essentially start in Nov 2021 (Fig. 3), so it tests a collection change and not language drift. We therefore use `temporal_late` as the valid shift test. Comparing it with `random_matched` separates the effect of time from the effect of less training data.

Methods. **A:** TF-IDF (1 to 2 grams, 50k features) with class-weighted logistic regression, C tuned on a validation set. **B:** MentalRoBERTa fine-tuned with the

[CLS] vector, 128 tokens, 2 epochs, 20k training subsample. **C:** the anchor paper's BiLSTM with an LSTM time branch and shared attention, rebuilt from its equations (embedding 128, BiLSTM 64, dropout 0.6, RMSprop). Each method is run with text only and with text plus time features (month, day, weekday, weekend, hour, working hour); C also has a concatenation variant. A design check shows the BiLSTM can memorise 300 posts.

Statistics. A replicate is a fresh sample, split and model initialisation (five replicates). Differences use a paired bootstrap of test posts (1000 resamples); models are compared with McNemar's test.

5 Reproduction of the Anchor Paper

Table 1 compares weighted F1 on the random split. Our BiLSTM matches the paper's text-only level but not its gain from time. Possible causes of the gap, all choices we had to make because no code was released: no stopword removal or lemmatisation, learned embeddings instead of Word2Vec, time features fed as a length-6 sequence, early stopping on a separate validation set (the paper selects on the reported set), and a different sample. All are logged in `logs/decision_log.md`.

	Paper	Ours (C)
text only	0.7222	0.7302
text + time	0.7376	0.7296

Table 1: Weighted F1, random split. Ours is the mean of five replicates.

6 Comparative Experiments

Model	Features	random	matched	late
A	text	.642	.636	.636
A	text+time	.643	.633	.620
C	text	.630	.609	.608
C	text+time	.630	.614	.614
B	text		**[to add]**	
B	text+time		**[to add]**	

Table 2: Macro F1, mean of five replicates (B: three).

McNemar's test favours A over C on `random_matched` and `temporal_late` ($p < 0.001$) and C over A on `random` by a small margin ($p = 0.002$).

7 Research Question: Does Timing Help?




Figure 1: Change in macro F1 from adding time features, 95% bootstrap interval.

On the random split every interval includes zero. For A the change is −0.003 on `random_matched` and −0.016 on `temporal_late`, so time hurts under shift. For C with attention the change is +0.005 and +0.006 (intervals exclude zero but are about half a point), and concatenation gives no gain. Time alone scores 0.15, the uniform random-guess level (0.145). Posting-time features therefore do not add reliable signal over text.

8 Extension Experiment: Time Robustness

Macro F1 on `temporal_late` minus `random_matched`, text only, is −0.001 [−0.008, +0.005] for C and −0.001 [−0.007, +0.006] for A, so training on earlier posts costs nothing measurable over these months. The confounded 2021 to 2022 split looks much worse: A with time features falls to 0.248, and to 0.543 when month and day are removed, because month features learn the class mix of 2021 (Fig. 2).

9 Results and Analysis

The strongest text-only model is the simplest, and time features add nothing for it. The BiLSTM's small gain may come from time acting as a weak regulariser for a weaker text encoder, which we have not tested. Errors




Figure 2: Same-period versus later-period macro F1.




Figure 3: Class share by month: three classes only exist from Nov 2021.

concentrate in the small and noisy classes, mainly mentalillness (Fig. 4).

10 Limitations

Labels are subreddits and not diagnoses. Condition names remain in the text. The Kaggle file has no author column, so same-user leakage cannot be checked there (it is checked on the Zenodo data). Method C is our rebuild. Method B uses a 20k subsample and three replicates because of free GPU limits, so cross-method gaps partly reflect training size. The valid shift window is short (about nine months).

11 Research Findings

(1) The anchor paper's timing gain is not reproduced against a strong text baseline. (2) Time features can hurt under time shift. (3) No measurable loss from training on earlier posts within Nov 2021 to Nov 2022. (4) The 2021 to 2022 split used by the paper is confounded by a collection change. **[Update with Method B.]**




Figure 4: Method A, text only, `temporal_late`.

12 Conclusion

Timing does not reliably matter for classifying these subreddits once a strong text model is used, and claims of timing gains should be checked on splits that avoid collection artefacts.

References

[1] Saeed and Ahmed. Temporal features for mental-health classification on Reddit. arXiv:2503.07653, 2025.

[2] Ji et al. MentalBERT: Publicly available pretrained language models for mental healthcare. LREC, 2022.

[3] Low et al. Natural language processing reveals vulnerable mental health support groups and heightened health anxiety on Reddit during COVID-19. J. Med. Internet Res., 2020.