

1. When does Exceptions in Java arises in code sequence?

- ☒ a) Run Time
- b) Compilation Time
- c) Can Occur Any Time
- d) None of the mentioned

2. Which of these keywords is not a part of exception handling?

- a) try
- b) finally
- ☒ c) thrown
- d) catch

3. Which of these keywords must be used to monitor for exceptions?

- ☒ a) try
- b) finally
- c) throw
- d) catch

4. Which of these keywords must be used to handle the exception thrown by try block in some rational manner?

- a) try
- b) finally
- c) throw
- ☒ d) catch

5. Which of these keywords is used to manually throw an exception?

- a) try
- b) finally
- ☒ c) throw

6. What will be the output of the following Java program?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            System.out.print("Hello" + " " + 1 / 0);
        }
        catch(ArithmeticException e)
        {
            System.out.print("World");
        }
    }
}
```

- a) Hello
- ☒ b) World
- c) HelloWorld
- d) Hello World

7. What will be the output of the following Java program?

```

class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a, b;
            b = 0;
            a = 5 / b;
            System.out.print("A");
        }
        catch(ArithmeticException e)
        {
            System.out.print("B");
        }
    }
}

```

- a) A
- ✓ b) B
- c) Compilation Error
- d) Runtime Error

8. What will be the output of the following Java program?

```

class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a, b;
            b = 0;
            a = 5 / b;
            System.out.print("A");
        }
        catch(ArithmeticException e)
        {
            System.out.print("B");
        }
        finally
        {
            System.out.print("C");
        }
    }
}

```

- a) A
- b) B
- c) AC

☒ BC

9. What will be the output of the following Java program?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int i, sum;
            sum = 10;
            for (i = -1; i < 3 ;++i)
                sum = (sum / i);
        }
        catch(ArithmeticException e)
        {
            System.out.print("0");
        }
        System.out.print(sum);
    }
}
```

a) 0

b) 05

☒ Compilation Error

d) Runtime Error

Exceptional handling:

10. Which of the following keywords is used for throwing exception manually?

a) finally

b) try

☒ throw

d) catch

11. Which of the following classes can catch all exceptions which cannot be caught?

a) RuntimeException

☒ Error

c) Exception

d) ParentException

12. Which of the following is a super class of all exception type classes?

a) Catchable

b) RuntimeExceptions

c) String

☒ Throwable

13. Which of the following operators is used to generate instance of an exception which can be thrown using throw?

a) thrown

b) alloc

c) malloc

☒ d) new

14. Which of the following keyword is used by calling function to handle exception thrown by called function?

☒ a) throws

b) throw

c) try

d) catch

15. Which of the following handles the exception when a catch is not used?

a) finally

b) throw handler

☒ c) default handler

d) java run time system

16. Which part of code gets executed whether exception is caught or not?

☒ a) finally

b) try

c) catch

d) throw

17. Which of the following should be true of the object thrown by a thrown statement?

a) Should be assignable to String type

b) Should be assignable to Exception type

☒ c) Should be assignable to Throwable type

d) Should be assignable to Error type

18. At runtime, error is recoverable.

a) True

☒ b) False

19. Which of these is a super class of all exceptional type classes?

a) String

b) RuntimeExceptions

☒ c) Throwable

d) Cacheable

20. Which of these class is related to all the exceptions that can be caught by using catch?

a) Error

☒ b) Exception

c) RuntimeException

d) All of the mentioned

21. Which of these class is related to all the exceptions that cannot be caught?

☒ a) Error

b) Exception

c) RuntimeException

d) All of the mentioned

22. Which of these handles the exception when no catch is used?

- ☒ a) Default handler
- b) finally
- c) throw handler
- d) Java run time system

23. What exception thrown by parseInt() method?

- a) ArithmeticException
- b) ClassNotFoundException
- c) NullPointerException
- ☒ d) NumberFormatException

24. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            System.out.print("Hello" + " " + 1 / 0);
        }
        finally
        {
            System.out.print("World");
        }
    }
}
```

- a) Hello
- b) World
- c) Compilation Error
- ☒ d) First Exception then World

25. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int i, sum;
            sum = 10;
            for (i = -1; i < 3 ;++i)
            {
                sum = (sum / i);
                System.out.print(i);
            }
        }
        catch(ArithmeticException e)
        {
            System.out.print("0");
        }
    }
}
```

```
    }  
  }  
a) -1  
b) 0  
c) -10  
d) -101
```

26. Which of these keywords is used to generate an exception explicitly?

- a) try
- b) finally
- c) throw
- d) catch

27. Which of these class is related to all the exceptions that are explicitly thrown?

- a) Error
- b) Exception
- c) Throwable
- d) Throw

28. Which of these operator is used to generate an instance of an exception than can be thrown by using throw?

- a) new
- b) malloc
- c) alloc
- d) thrown

29. Which of these keywords is used to by the calling function to guard against the exception that is thrown by called function?

- a) try
- b) throw
- c) throws
- d) catch

30. What will be the output of the following Java code?

```
class exception_handling  
{  
    public static void main(String args[])  
    {  
        try  
        {  
            int a = args.length;  
            int b = 10 / a;  
            System.out.print(a);  
            try  
            {  
                if (a == 1)  
                    a = a / a - a;  
                if (a == 2)  
                {  
                    int []c = {1};  
                    c[8] = 9;  
                }  
            }  
        }  
    }  
}
```

```

    }
    catch (ArrayIndexOutOfBoundsException e)
    {
        System.out.println("TypeA");
    }
    catch (ArithmeticException e)
    {
        System.out.println("TypeB");
    }
}
}
}

```

- a) TypeA
- b) TypeB
- ☒ c) Compile Time Error
- d) 0TypeB

31. What will be the output of the following Java code?

```

class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            System.out.print("A");
            throw new NullPointerException ("Hello");
        }
        catch(ArithmeticException e)
        {
            System.out.print("B");
        }
    }
}

```

- a) A
- b) B
- c) Hello
- ☒ d) Runtime Exception

32. What will be the output of the following Java code?

```

public class San
{
    public static void main(String[] args)
    {
        try
        {
            return;
        }
        finally
        {
            System.out.println( "Finally" );
        }
    }
}

```

```
}  
}
```

- ☒ a) Finally
- b) Compilation fails
- c) The code runs with no output
- d) An exception is thrown at runtime

33. What will be the output of the following Java code?

```
public class San  
{  
    public static void main(String args[])  
    {  
        try  
        {  
            System.out.print("Hello world ");  
        }  
        finally  
        {  
            System.out.println("Finally executing ");  
        }  
    }  
}
```

- a) The program will not compile because no exceptions are specified
- b) The program will not compile because no catch clauses are specified
- c) Hello world
- ☒ d) Hello world Finally executing

34. Which of these clause will be executed even if no exceptions are found?

- a) throws
- ☒ b) finally
- c) throw
- d) catch

35. A single try block must be followed by which of these?

- a) finally
- b) catch
- c) finally & catch
- ☒ d) none of the mentioned

36. Which of these exceptions handles the divide by zero error?

- ☒ a) ArithmeticException
- b) MathException
- c) IllegalAccessException
- d) IllegarException

37. Which of these exceptions will occur if we try to access the index of an array beyond its length?

- a) ArithmeticException
- b) ArrayException

- c) ArrayIndexException
- ☒ d) ArrayIndexOutOfBoundsException

38. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a = args.length;
            int b = 10 / a;
            System.out.print(a);
        }
        catch (ArithmeticException e)
        {
            System.out.println("1");
        }
    }
}
```

Note : Execution command line : \$ java exception_handling

- a) 0
- ☒ b) 1
- c) Compilation Error
- d) Runtime Error

39. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            throw new NullPointerException ("Hello");
        }
        catch(ArithmeticException e)
        {
            System.out.print("B");
        }
    }
}
```

- a) A
- b) B
- c) Compilation Error
- ☒ d) Runtime Error

40. What will be the output of the following Java code?

```

class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a = 1;
            int b = 10 / a;
            try
            {
                if (a == 1)
                    a = a / a - a;
                if (a == 2)
                {
                    int c[] = {1};
                    c[8] = 9;
                }
            }
            finally
            {
                System.out.print("A");
            }
        }
        catch (Exception e)
        {
            System.out.println("B");
        }
    }
}

```

- ☒ a) A
- ☐ b) B
- ☐ c) AB
- ☐ d) BA

41. What will be the output of the following Java code?

```

class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a = args.length;
            int b = 10 / a;
            System.out.print(a);
            try
            {
                if (a == 1)
                    a = a / a - a;
                if (a == 2)

```

```

        {
            int []c = {1};
            c[8] = 9;
        }
    }
    catch (ArrayIndexOutOfBoundsException e)
    {
        System.out.println("TypeA");
    }
    catch (ArithmeticException e)
    {
        System.out.println("TypeB");
    }
}
}

```

Note: Execution command line: \$ java exception_handling one two

- a) TypeA
- b) TypeB
- ☒ c) Compilation Error
- d) Runtime Error

42. What is the use of try & catch?

- a) It allows us to manually handle the exception
- b) It allows to fix errors
- ☒ c) It prevents automatic terminating of the program in cases when an exception occurs
- d) All of the mentioned

43. Which of these keywords are used for the block to be examined for exceptions?

- ☒ a) try
- b) catch
- c) throw
- d) check

44. Which of these keywords are used for the block to handle the exceptions generated by try block?

- a) try
- ☒ b) catch
- c) throw
- d) check

45. Which of these keywords are used for generating an exception manually?

- a) try
- b) catch
- ☒ c) throw
- d) check

46. Which of these statements is incorrect?

- a) try block need not to be followed by catch block
- b) try block can be followed by finally block instead of catch block
- c) try can be followed by both catch and finally block

☒ try need not to be followed by anything

47. What will be the output of the following Java code?

```
class Output
{
    public static void main(String args[])
    {
        try
        {
            int a = 0;
            int b = 5;
            int c = b / a;
            System.out.print("Hello");
        }
        catch(Exception e)
        {
            System.out.print("World");
        }
    }
}
```

- a) Hello
- ☒ b) World
- c) HelloWorld
- d) Compilation Error

48. What will be the output of the following Java code?

```
class Output
{
    public static void main(String args[])
    {
        try
        {
            int a = 0;
            int b = 5;
            int c = a / b;
            System.out.print("Hello");
        }
        catch(Exception e)
        {
            System.out.print("World");
        }
    }
}
```

- ☒ a) Hello
- ☒ b) World
- c) HelloWorld
- d) Compilation Error

49. What will be the output of the following Java code?

```

class Output
{
    public static void main(String args[])
    {
        try
        {
            int a = 0;
            int b = 5;
            int c = b / a;
            System.out.print("Hello");
        }
    }
}

```

- a) Hello
- b) World
- c) HelloWOrld
- ✓ d) Compilation Error

50. What will be the output of the following Java code?

```

class Output
{
    public static void main(String args[])
    {
        try
        {
            int a = 0;
            int b = 5;
            int c = a / b;
            System.out.print("Hello");
        }
        finally
        {
            System.out.print("World");
        }
    }
}

```

- a) Hello
- b) World
- ✓ c) HelloWOrld
- d) Compilation Error

51. What will be the output of the following Java code?

```

class Output
{
    public static void main(String args[])
    {
        try

```

```
{
    int a = 0;
    int b = 5;
    int c = b / a;
    System.out.print("Hello");
}
catch(Exception e)
{
    System.out.print("World");
}
finally
{
    System.out.print("World");
}
}
```

- a) Hello
- b) World
- c) HelloWorld
- ☒ d) WorldWorld

52. Which of these classes is used to define exceptions?

- ☒ a) Exception
- ☒ b) Throwable
- c) Abstract
- d) System

53. Which of these methods return description of an exception?

- a) ☒ getException()
- ☒ b) getMessage()
- c) obtainDescription()
- d) obtainException()

54. Which of these methods is used to print stack trace?

- a) ☒ obtainStackTrace()
- ☒ b) printStackTrace()
- c) getStackTrace()
- d) displayStackTrace()

55. Which of these methods return localized description of an exception?

- ☒ a) getLocalizedMessage()
- ☒ b) getMessage()
- c) obtainLocalizedMessage()
- d) printLocalizedMessage()

56. Which of these classes is super class of Exception class?

- ☒ a) Throwable
- b) System
- c) RunTime
- d) Class

57. What will be the output of the following Java code?

```
class Myexception extends Exception
{
    int detail;
    Myexception(int a)
    {
        detail = a;
    }
    public String toString()
    {
        return "detail";
    }
}
class Output
{
    static void compute (int a) throws Myexception
    {
        throw new Myexception(a);
    }
    public static void main(String args[])
    {
        try
        {
            compute(3);
        }
        catch(Myexception e)
        {
            System.out.print("Exception");
        }
    }
}
```

- a) 3
- ☒ b) Exception
- c) Runtime Error
- d) Compilation Error

58. What will be the output of the following Java code?

```
class Myexception extends Exception
{
    int detail;
    Myexception(int a)
    {
        detail = a;
    }
    public String toString()
    {
        return "detail";
    }
}
class Output
{
    static void compute (int a) throws Myexception
    {
        throw new Myexception(a);
    }
    public static void main(String args[])
    {
        try
        {
            compute(3);
        }
        catch(DevideByZeroException e)
        {
            System.out.print("Exception");
        }
    }
}
```

- a) 3
- b) Exception
- c) Runtime Error
- ✓ d) Compilation Error

59. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            throw new NullPointerException ("Hello");
            System.out.print("A");
        }
        catch(ArithmeticException e)
        {

```



```

        System.out.print("B");
    }
}

```

- a) A
- b) B
- ☒ c) Compilation Error
- d) Runtime Error

60. What will be the output of the following Java code?

```

class Myexception extends Exception
{
    int detail;
    Myexception(int a)
    {
        detail = a;
    }
    public String toString()
    {
        return "detail";
    }
}
class Output
{
    static void compute (int a) throws Myexception
    {
        throw new Myexception(a);
    }
    public static void main(String args[])
    {
        try
        {
            compute(3);
        }
        catch(Exception e)
        {
            System.out.print("Exception");
        }
    }
}

```

- a) 3
- ☒ b) Exception
- c) Runtime Error
- d) Compilation Error

61. What will be the output of the following Java code?

```

class exception_handling

```

```

{
    public static void main(String args[])
    {
        try
        {
            int a = args.length;
            int b = 10 / a;
            System.out.print(a);
            try
            {
                if (a == 1)
                    a = a / a - a;
                if (a == 2)
                {
                    int c = {1};
                    c[8] = 9;
                }
            }
        }
        catch (ArrayIndexOutOfBoundsException e)
        {
            System.out.println("TypeA");
        }
        catch (ArithmeticException e)
        {
            System.out.println("TypeB");
        }
    }
}

```

Note : Execution command line : \$ java exception_handling one

a) TypeA

b) TypeB

✓ c) Compilation Error

d) Runtime Error