

# CD lab 5

name: Abhinav Singh Bhagtana  
reg no: 230905225  
roll no: A-029

Q1.Count the number of vowels and consonants in the given input.

```
%{  
#include <stdio.h>  
int vowels = 0;  
int consonants = 0;  
%}  
  
%%  
  
[aeiouAEIOU]      { vowels++; }  
[a-zA-Z]          { consonants++; }  
.  
{ }  
  
%%  
  
int main() {  
    printf("Enter a string: \n");  
    yylex();  
    printf("\n--- Results ---\n");  
    printf("Vowels: %d\n", vowels);  
    printf("Consonants: %d\n", consonants);  
    return 0;  
}  
  
int yywrap() {  
    return 1;  
}
```

## output:

Enter a string:  
hi hello my name

--- Results ---  
Vowels: 5  
Consonants: 8

Q2.Count the number of words, characters, blanks and lines in a given text.

```
%{  
#include <stdio.h>  
int words = 0;  
int chars = 0;  
int blanks = 0;
```

```

int lines = 0;
%}

%%
[a-zA-Z_][a-zA-Z0-9_]* { words++; chars += yyleng; }
[ ]+          { blanks += yyleng; }
\n           { lines++; }
.            { chars++; }
%%

int main() {
    printf("Enter string (Ctrl+D to finish):\n");
    yylex();
    printf("\n--- Results ---\n");
    printf("Words: %d\nChars: %d\nBlanks: %d\nLines: %d\n", words, chars, blanks, lines);
    return 0;
}

```

```

int yywrap() { return 1; }

```

**output:**

```

Enter string (Ctrl+D to finish):
hi hello
my name

```

```

--- Results ---
Words: 4
Chars: 13
Blanks: 2
Lines: 2

```

Q3.Find the number of positive integer, negative integer, positive floating positive number and negative floating point number

```

%{
#include <stdio.h>
int posint = 0;
int negint = 0;
int floatpos = 0;
int floatneg = 0;
%}

%%

-[0-9]+\.[0-9]+ { floatneg++; }

\+?[0-9]+\.[0-9]+ { floatpos++; }

```

```
-[0-9]+      { negint++; }
```

```
\+?[0-9]+    { posint++; }
```

```
[ \t\n]      { }
```

```
.            { }
```

```
%%
```

```
int main() {  
    printf("Enter numbers (Ctrl+D to finish):\n");  
    yylex();  
    printf("\n--- Summary ---\n");  
    printf("Positive integers: %d\n", posint);  
    printf("Negative integers: %d\n", negint);  
    printf("Positive floating point: %d\n", floatpos);  
    printf("Negative floating point: %d\n", floatneg);  
    return 0;  
}
```

```
int yywrap() { return 1; }
```

**output:**

Enter numbers (Ctrl+D to finish):

54

34

24.4

-23

-2333

-0.09

--- Summary ---

Positive integers: 2

Negative integers: 2

Positive floating point: 1

Negative floating point: 1

Q4. Given a input C file, replace all scanf with READ and printf with WRITE statements also find the number of scanf and printf in the file.

```
%{
```

```
#include <stdio.h>
```

```
int s_count = 0;
```

```
int p_count = 0;
```

```
%}
```

```
%%
```

```
"scanf"    { s_count++; fprintf(yyout, "READ"); }
```

```

"printf" { p_count++; fprintf(yyout, "WRITE"); }

%%

int main(int argc, char **argv) {
    if (argc < 3) {
        printf("Usage: %s <input_file> <output_file>\n", argv[0]);
        return 1;
    }

    yyin = fopen(argv[1], "r");
    if (!yyin) {
        perror("Error opening input file");
        return 1;
    }

    yyout = fopen(argv[2], "w");
    if (!yyout) {
        perror("Error creating output file");
        return 1;
    }

    yylex();

    fprintf(yyout, "\n\n/* --- Statistics --- */\n");
    fprintf(yyout, "/* Total scanf replaced: %d */\n", s_count);
    fprintf(yyout, "/* Total printf replaced: %d */\n", p_count);

    fclose(yyin);
    fclose(yyout);

    printf("Processing complete. Check %s for results.\n", argv[2]);
    return 0;
}

int yywrap() {
    return 1;
}

input:
#include <stdio.h>
int main()
{
    int n;
    printf("hello world");
    scanf("%d",&n);
}

```

```

        printf("taken input");
        printf("output %d",n);
        return 0;
}
output:
#include <stdio.h>
int main()
{
    int n;
    WRITE("hello world");
    READ("%d",&n);
    WRITE("taken input");
    WRITE("output %d",n);
    return 0;
}

```

```

/* --- Statistics --- */
/* Total scanf replaced: 1 */
/* Total printf replaced: 3 */

```

Q5.That changes a number from decimal to hexadecimal notation.

```

%{
#include <stdio.h>
#include <stdlib.h>

int num[100];
int i = 0;
%}

%%
[0-9]+ {

    num[i++] = atoi(yytext);
}
[ \t\n] { }
. { }
%%

void printHex(int n) {
    if (n == 0) {
        printf("0");
        return;
    }

    char hex[50];
    int j = 0;

```

```

while (n > 0) {
    int temp = n % 16;
    if (temp < 10)
        hex[j++] = temp + 48; // '0'-'9'
    else
        hex[j++] = temp + 55; // 'A'-'F'
    n = n / 16;
}

for (int k = j - 1; k >= 0; k--) {
    printf("%c", hex[k]);
}

int main() {
    printf("Enter numbers (Ctrl+D to finish):\n");
    yylex();

    printf("\n--- Hexadecimal Results ---\n");
    for(int k = 0; k < i; k++) {
        printf("Decimal %d to Hex: ", num[k]);
        printHex(num[k]);
        printf("\n");
    }
    return 0;
}

int yywrap() { return 1; }

```

**output:**

Enter numbers (Ctrl+D to finish):

234

234

233

33

2

--- Hexadecimal Results ---

Decimal 234 to Hex: EA

Decimal 234 to Hex: EA

Decimal 233 to Hex: E9

Decimal 33 to Hex: 21

Decimal 2 to Hex: 2

Q6.Convert uppercase characters to lowercase characters of C file excluding the characters present in the comment.

```
%{
#include <stdio.h>
#include <ctype.h>
int count = 0;
%}
```

```
%x COMMENT
```

```
%%
```

```
"/".* { fprintf(yyout, "%s", yytext); }
```

```
"/*"      { fprintf(yyout, "%s", yytext); BEGIN(COMMENT); }
<COMMENT>"*/"  { fprintf(yyout, "%s", yytext); BEGIN(INITIAL); }
<COMMENT>.      { fputc(yytext[0], yyout); }
<COMMENT>\n     { fputc('\n', yyout); }
```

```
[A-Z]      {
              count++;
              fputc(tolower(yytext[0]), yyout);
            }
```

```
.          { fputc(yytext[0], yyout); }
\n         { fputc('\n', yyout); }
```

```
%%
```

```
int main(int argc, char **argv) {
    if (argc < 3) {
        printf("Usage: %s <input_file> <output_file>\n", argv[0]);
        return 1;
    }
}
```

```
yyin = fopen(argv[1], "r");
yyout = fopen(argv[2], "w");
```

```
if (!yyin || !yyout) {
    perror("File error");
    return 1;
}
```

```
yylex();
```

```
fprintf(yyout, "\n\n/* --- Statistics --- */\n");
fprintf(yyout, "/* Total uppercase characters replaced: %d */\n", count);

fclose(yyin);
fclose(yyout);
return 0;
}
```

```
int yywrap() { return 1; }
```

**input:**

```
#INCLUDE <stdio.h>
//INCLUDED STDIO
int MAIN(){
    RETURN 1;
}
```

**output:**

```
#include <stdio.h>
//INCLUDED STDIO
int main(){
    return 1;
}
```

```
/* --- Statistics --- */
```

```
/* Total uppercase characters replaced: 17 */
```