

(Ethics: Any behavior on any homework or exam that could be considered copying or cheating will result in an immediate zero on the assignment for all parties involved and will be reported to academichonesty@iit.edu. See the IIT Code of Academic Honesty, <https://web.iit.edu/student-affairs/handbook/fine-print/code-academic-honesty>)

1. Calculate denotational semantics for the following nondeterministic programs.
 - a. Let $S \equiv \text{if } x > y \rightarrow x := x - 1 \ \square \ x > y \rightarrow y := y + 1 \ \square \ x + y = 4 \rightarrow x := y/x \ \square \ x + y = 4 \rightarrow x := x/y \text{ fi}$, and let $\sigma = \{x = 3, y = 1\}$. Calculate $M(S, \sigma)$ and show your work.
 - b. Let $W \equiv \text{do } x > y \rightarrow x := x - 1 \ \square \ x > y \rightarrow y := y + 1 \ \square \ x + y = 4 \rightarrow x := y/x \ \square \ x + y = 4 \rightarrow x := x/y \text{ od}$, and let $\sigma = \{x = 3, y = 1\}$. Calculate $M(W, \sigma)$ and show your work.
2. Let b be an array of size $n \geq 1$, and $\forall 0 \leq i < n. b[i] = 0 \vee b[i] = 1$. Decide which number (0 or 1) is the majority in b without counting their quantities.

Write a program named **MAJORITY** in our language that can solve the above problem and bind the majority among 0 and 1 to variable *major*. You can assume that b is written in the memory state; and to simplify the question, we artificially define $b[n] = 100$, so you don't need to worry about a possible runtime error when the array index reaches n . Your program doesn't have to be deterministic. Be careful of the grammar in our programming language.

Here are some hints:

- 1) We can use the following linear-search-like algorithm: scan the array b to pair up each 0 with a 1. Once we have some 1's left over, then 1 is the majority; once we have some 0's left over, then 0 is the majority; if we can pair up all numbers, then either of them can be the majority.

- 2) A student Jason wrote a partial solution that can be useful to solve the above problem:

$J \equiv \text{do } b[k_0] = 1 \rightarrow k_0 := k_0 + 1 \ \square \ b[k_1] = 0 \rightarrow k_1 := k_1 + 1 \text{ od}$

Consider k_0 and k_1 as pointers for number 0 and 1 respectively. What program J does is to find the next k_0 and k_1 such that $b[k_0] = 0$ and $b[k_1] = 1$. You can use J inside of your program.

3. True or false. Justify your answer briefly.
 - a. If $M(S, \sigma)$ contains exactly one state, then S must be a deterministic statement.
 - b. If $\sigma \models \{p\} S \{q\}$, then $\sigma \models p$.
 - c. If $\sigma \not\models_{tot} \{p\} S \{q\}$, then $\sigma \not\models p$.
 - d. If $\sigma \models \{p\} S \{q\}$, then $M(S, \sigma) \models q$.
 - e. If $\sigma \not\models \{p\} S \{q\}$, then $\sigma \not\models_{tot} \{p\} S \{q\}$.
4. Let predicate function $P(k, s) \equiv s^2 \leq k \leq (s + 1)^2$. For each of the following triples, decide whether it is valid under total correctness, justify your answer briefly.
 - a. $\{P(k, s + 1)\} s := s + 1 \{P(k, s)\}$
 - b. $\{P(k, s)\} s := s + 1 \{P(k, s + 1)\}$
 - c. $\{P(k, s) \wedge s < 0\} s := s + 1; k := k + 1 \{P(k, s)\}$
 - d. $\{P(k, s) \wedge s = s_0\} s := s + 1 \{P(k, s_0)\}$
 - e. $\{P(k + 1, s + 1)\} s := s + 1; k := k + 1 \{P(k, s)\}$
5. Answer the following questions and justify your answer briefly.
 - a. Let $\sigma \models \{x \neq 0\} \text{ while } x \neq 0 \text{ do } x := x - 2 \text{ od } \{x < 0\}$, what are the possible values of $\sigma(x)$?
 - b. Let $\sigma \models_{tot} \{x \neq 0\} \text{ while } x \neq 0 \text{ do } x := x - 2 \text{ od } \{x < 0\}$, what are the possible values of $\sigma(x)$?

6. Let $\sigma \models_{tot} \{p_1\} S \{q_1\}$ and $\sigma \models_{tot} \{p_2\} S \{q_2\}$. Decide whether σ necessarily satisfies the following triples under total correctness, justify your answer briefly.
 - a. $\{p_1 \wedge p_2\} S \{q_1 \vee q_2\}$
 - b. $\{p_1 \vee p_2\} S \{q_1 \wedge q_2\}$
 - c. $\{p_1 \vee p_2\} S \{q_1 \vee q_2\}$
7. Let $\models \{p_1\} S \{q_1\}$ and $\models \{p_2\} S \{q_2\}$. Decide whether the following triples are valid under partial correctness, justify your answer briefly.
 - a. $\{p_1 \wedge p_2\} S \{q_1 \wedge q_2\}$
 - b. $\{p_2\} S \{q_1 \rightarrow q_2\}$
 - c. $\{\neg p_1 \rightarrow p_2\} S \{\neg q_1 \rightarrow q_2\}$
8. Let $w \Leftrightarrow wp(S, q)$, and let S be a deterministic program. Decide whether each of the following statements is true or false, justify your answer briefly. We assume $\tau(q) \neq \perp$ for any well-formed state τ .
 - a. $\models_{tot} \{w\} S \{q\}$
 - b. $\models \{w \wedge q\} S \{q\}$
 - c. There exists some state σ such that $\sigma \not\models w$ but $M(S, \sigma) \models q$.
 - d. If $\sigma \models w$, then $M(S, \sigma) \neq \{\perp\}$.
 - e. If $\sigma \not\models w$, then $\sigma \models \{\neg w\} S \{\neg q\}$.

You don't have to logically simplify your answers to questions 9 and 10.

9. Let $S \equiv y := y \% x$ and $q \equiv \text{sqrt}(y) > x$.
 - a. Calculate $wlp(S, q)$.
 - b. Calculate $wp(S, q)$.
10. Let $S \equiv \mathbf{if} \ y \geq 0 \rightarrow x := y/x \ \square \ x \geq 0 \rightarrow x := x/y \ \mathbf{fi}$ and $q \equiv x < y < z$.
 - a. Calculate $wlp(S, q)$.
 - b. Calculate $wp(S, q)$.