

(Ethics: Any behavior on any homework or exam that could be considered copying or cheating will result in an immediate zero on the assignment for all parties involved and will be reported to academichonesty@iit.edu. See the IIT Code of Academic Honesty, <https://web.iit.edu/student-affairs/handbook/fine-print/code-academic-honesty>)

In questions 1 and 2, we will create a program that calculates the factorial of natural number n and stores the result as $x = fac(n)$. Here, function $fac(n)$ is the function that gives the factorial of n :

$$fac(n) = \begin{cases} 1, & \text{if } n = 0 \\ n * fac(n - 1), & \text{if } n > 0 \end{cases}$$

1. Answer the following questions.
 - a. What are the pre- and post- conditions needed for this program?
 - b. Create a loop invariant p by replacing the named constant n by a variable y in the postcondition (what can be the range of variable y ?) and create the corresponding loop condition B .
 - c. Find a bound expression t for this program. Show your work.
2. Create a full proof outline under the total correctness for this program. Don't forget to initialize variables x and y before the loop starts, find reasonable values for them. Justify each logical implications used in the proof outline.
3. Find an optimized precondition p which contains no conditional expressions and create a full proof outline for the following minimal proof outline. You may assume that $0 \leq i < size(b)$, $0 \leq j < size(b)$, $0 \leq k < size(b)$ so you don't need to worry about the array-index-out-of-bounds error.

$$\{p\} b[i] := b[j]; b[j] := b[k] \{b[i] > b[k]\}$$

4. Create a full proof outline for the following minimal proof outline. You may assume that $0 \leq j < size(b)$, $0 \leq k < size(b)$, so you don't need to worry about the array-index-out-of-bounds error.

$$\{k < b[k] < b[j]\} b[b[k]] := b[j] \{b[k] \neq b[j]\}$$

5. Draw an evaluation graph for the configuration $\langle S, \sigma \rangle$ where $S \equiv [x := 1 \parallel x := -1]; y := y + x$.
6. Draw an evaluation graph for the configuration $\langle W, \{x = 0, y = 1, n = 2\} \rangle$ where $W \equiv \mathbf{while} \ x < n \ \mathbf{do} \ [x := x + 1 \parallel y := y * 2] \ \mathbf{od}$.
7. Given the following two threads written in provable triples. Answer the following questions and justify your answers.

$$\begin{aligned} S_1 &\equiv \{x = 0\} y := x + 2 \{y = 2\} \\ S_2 &\equiv \{x < 0\} z := 0 \{z > x\} \end{aligned}$$

- a. Are these two threads disjoint?
 - b. Do they have disjoint conditions?
8. Answer the following questions about the two following threads written in proof outlines. Here, T_1, T_2 and T_3 are statements. Remember, we only need to check if atomic statements cause interference.

$$S_1^* \equiv \{p_1\} \text{ if } B_1 \text{ then } \{p_2\} < T_1 > \text{ else } \{p_3\} \text{ skip fi } \{p_4\}$$

$$S_2^* \equiv \{q_1\} < T_2 >; \{\text{inv } q_2\} \text{ while } B_2 \text{ do } \{q_3\} < T_3 > \text{ od } \{q_4\}$$

- a. List the interference freedom checks to decide whether S_1^* interferes with S_2^* .
- b. List the interference freedom checks to decide whether S_2^* interferes with S_1^* .