INDIAN INSTITUTE OF ENGINEERING SCIENCE AND TECHNOLOGY, SHIBPUR
Howrah, West Bengal, India – 711103

DEPARTMENT OF COMPUTER SCIENCE AND TECHNOLOGY



A PROJECT REPORT SUBMITTED IN PARTIAL FULFILLMENT OF THE REQUIREMENTS

ON

"DETECTION OF CIPHER TYPES USING ARTIFICIAL NEURAL NETWORKS"

SUBMITTED BY

Rajdeep Ghosh (510519002)
Swarnali Mondal (510510103)
Krishnendu Bera (510519004)
Arnab Sen (510519006)
Sanjana Chakravarty (510519038)
Abhiroop Mukherjee (510519109)

UNDER THE GUIDANCE OF

DR. MALAY KULE

(Academic Year: 2022–2023)

INDIAN INSTITUTE OF ENGINEERING SCIENCE AND TECHNOLOGY, SHIBPUR
Howrah, West Bengal, India – 711103

DEPARTMENT OF COMPUTER SCIENCE AND TECHNOLOGY



Certificate

It is certified hereby that this report, titled "Detection of Cipher Types using Artificial Neural Networks", and all the attached documents herewith are authentic records of Rajdeep Ghosh (510519002), Swarnali Mondal (510510103), Krishnendu Bera (510519004), Arnab Sen (510519006), Sanjana Chakravarty (510519038), and Abhiroop Mukherjee (510519109) from the Prestigious Department of Computer Science And Technology of the Distinguished and Respected IIEST Shibpur under my guidance.

The works of these students are satisfies all the requirements for which it is submitted. To the extent of my knowledge, it has not been submitted to any different institutions for the awards of degree.

Dr. Malay Kule
Asst. Professor

Dr. Asit Kumar Das
Head Of Department

ACKNOWLEDGEMENT

We, as the students of IIEST, consider ourselves honoured to be working with Dr. Malay Kule and Mr. Subinoy Sikdar. The success of this project would not have been possible without his useful insights, appropriate guidance and necessary criticism.

We would pass our token of token of gratitude to the Department of Computer Science And Technoogy as well for providing us with the opportunity to be able to tackle real world problems while improving our problem solving ability and thinking capacity by organising this project. We all have learnt quite a handful of new skills and are eager to use them henceforth as well.

Rajdeep Ghosh (510519002)
Swarnali Mondal (510510103)
Krishnendu Bera (510519004)
Arnab Sen (510519006)
Sanjana Chakravarty (510519038)
Abhiroop Mukherjee (510519109)

Contents

1 INTRODUCTION **1**

2 PRELIMINARIES **1**

3 LITERATURE SURVEY **1**

4 PROPOSED WORK **2**
4.1 Dataset Generation 2
4.2 Model using CNN 2
4.3 Model using Transformer 3

5 EXPERIMENTAL RESULTS **4**
5.1 Model using CNN 4
5.2 Model using Transformer 5

6 FUTURE **7**

7 CONCLUSION **7**

1 INTRODUCTION

Information is the power in the present day. Information and data should be protected from unauthorized access, distortion, or any unauthorized activity.

Cryptography is the study of secret writing. Information is no longer hidden due to the existence of network adversaries. Our communication channel is completely unstable; a third party might covertly eavesdrop and obtain information from the network or from the channel. Here, cryptography is crucial in preventing unauthorized access to our data. Using key(s), cryptography converts plaintext messages into unreadable ciphertext and vice versa. Encryption is the process of employing a key(s) to transform the original message into an unintelligible format, while decryption is the act of using a key(s) to convert the cipher text back to plaintext. The messages can only be encrypted or decrypted by the authorized user.

The project's objective is to examine encrypted text files to find and categorize their cipher types using artificial neural networks. The cipher algorithm classification model is based on the steps:

1. Creation of a collection of cipher texts with various ' cipher texts.
2. Building a Deep Neural Network (DNN) and training it with a variety of cipher texts and training parameters to enable accurate learning and cipher text classification.
3. Determine the cipher text's kind.

First, the Caesar, Affine, Vigenère, Substitution, and Rail Fence ciphers were used to encrypt English texts. Following the submission of the encrypted files to the CNN and Transformer models, predictions are created, and accuracy is assessed.

2 PRELIMINARIES

To ramp up for this project, we needed a basic knowledge of neural networks and deep learning and an overview of the encryption algorithms that we would be targeting in this project.

Having some knowledge of encryption algorithms might be useful for feature extraction.

The ML topics that were covered in this project are:

- Perceptron
- Artificial Neural Network (ANN)
- Recurrent Neural Network (RNN)
- Convolutional Neural Network (CNN)
- Transformers
- Attention Mechanism in Deep Learning

3 LITERATURE SURVEY

4 PROPOSED WORK

4.1 Dataset Generation

The dataset has been generated for five types of ciphers:

- Caesar
- Affine
- Vigenère
- Substitution
- Rail Fence

The plaintext used for encryption was text from Shakespeare's Hamlet and Macbeth.

For Data Preporcessing, we converted text to lowercase and removed all whitespaces and punctuation.

Each of the classes has 6815 data points, resulting in a total of 34075 data points and each data point consists of the ciphertext (input) and the encryption algorithm (output).

We wrote a Python script for each of the ciphers to encrypt the data into a Pandas DataFrame. The combined DataFrame is exported as a CSV file for the resulting dataset.

4.2 Model using CNN

The main intuition behind this method is that CNN uses its kernel as a "local receptive field", which means that a CNN kernel (small in size as we are dealing with stream cipher and not block cipher) can look its nearby characters and will find some pattern in the ciphertext

So, we first converted a every ciphertexts into their respective list of tokens using a TextVectorizer, then we converted that list into an image as follows:

$$\begin{bmatrix} a & b & c & d \end{bmatrix} \longrightarrow \begin{bmatrix} a & b & c & d \\ a & b & c & d \\ a & b & c & d \\ a & b & c & d \end{bmatrix}$$

Figure 1: Converting text to "image"

Note that this conversion depends on the length of string used, i.e. for a string for length n, we will generate a $n \times n$ "image". After we generate all variable sized images, we resize them to 60×60 using Bilinear Interpolation.

Now we can see that a kernel (say 3×3 with stride one) can observe its previous as well as its next character and can use that information to find pattern in the ciphertext.

We use a CNN to extract features from the "image" then we feed those features to a Dense Network to classify between the ciphertext types.

4.3 Model using Transformer

The main intuition behind this method is to compute the relative importance of a ciphertext character with respect to the other ciphertext characters. A transformer model works on the encoder decoder architecture converting ciphertext characters to tokens and then computing the relative importance of a token to other tokens.




Figure 2: Transformer architecture

A transformer is an advanced sequence to sequence model that is used to predict the next token depending upon all the previous tokens. From our dataset containing encrypted text and the algorithm used for encryption, we create a text prompt from each row for example:

Cipher text: ymccaygimgamkyyiycuycqocyeagmigkycmyyoyy
Algorithm: affine

The model learns the relative importance of each token and uses it to predict the next. For example, if the model is trained with the above prompt and then we supply the following prompt:

Cipher text: ymccaygimgamkyyiycuycqocyeagmigkycmyyoyy
Algorithm:

The model shall generate the output as “affine” which it learnt from training.

In our use case, we have used the GPT-Neo (Generative Pre-Trained) model with 125 million parameters to achieve our objective. It consists of stacks of encoders and decoders put one after the other, of which has been pre-trained on Wikipedia Corpus as well as Common Crawl (This has over 12 Petabytes of data which is 12 years of data uploaded on the internet) datasets for performing extremely well on language-based use cases. Generative, as the word suggests, is for making our code generate text. The architecture is similar to GPT2 except that GPT Neo uses local attention in every other layer with a window size of 256 tokens. All these models are available for free in huggingface transformers library that can be used for a variety of NLP tasks.

Following steps were taken for this model:

1. Each data of the dataset is converted into text prompts that is passed through a tokenizer that creates embeddings for each token in our input string.
2. The input dataset has been split into the ratio 80:10:10 for training, testing and validating purposes.
3. The training and validation set has been used to fine-tune the model's hyperparameters specific to our use-case i.e. detecting the algorithm used in the ciphertext generation.
4. We used the fine-tuned model on our test dataset to check the accuracy of our model.

For our testing purpose, we used various decoding strategies to find the one which gives the best result. Out of the strategies: Greedy Search, Beam Search and Sampling with set temperature, we found sampling to give the most accurate results of all three. It is a method that is in between the greedy and sampling approach.

The greedy method selects the next token that has the highest probability as the output while sampling selects one of the possible next tokens randomly. When we set a temperature, the randomness is lowered such that the likelihood of high probability words are increased and that of the low probability are decreased. We found that a **temperature set to 0.7** gave the optimum accuracy on our test data.

5 EXPERIMENTAL RESULTS

5.1 Model using CNN

Our dataset consisted of 34075 rows that were split for training, testing, and validating in the ratio 80:10:10. The following are the sizes for each split:

- Train dataset: 27260 rows
- Validation dataset: 3408 rows
- Test dataset: 3407 rows

We also added an EarlyStopping Callback of patience 10 which automatically stopped training if we do not see any validation accuracy improvement after 10 epochs.

```
Epoch 1/10000
852/852 [==============================] - 11s 10ms/step - loss: 1.1977 - accuracy: 0.4627 - val_loss: 1.0805 - val_accuracy: 0.5161
Epoch 2/10000
852/852 [==============================] - 9s 10ms/step - loss: 1.0930 - accuracy: 0.5132 - val_loss: 1.0625 - val_accuracy: 0.5174
Epoch 3/10000
852/852 [==============================] - 9s 10ms/step - loss: 1.0494 - accuracy: 0.5465 - val_loss: 0.9777 - val_accuracy: 0.5789
Epoch 4/10000
852/852 [==============================] - 9s 10ms/step - loss: 1.0158 - accuracy: 0.5716 - val_loss: 0.9707 - val_accuracy: 0.5864
Epoch 5/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.9896 - accuracy: 0.5856 - val_loss: 1.0243 - val_accuracy: 0.5668
Epoch 6/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.9701 - accuracy: 0.5977 - val_loss: 0.9334 - val_accuracy: 0.6190
Epoch 7/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.9557 - accuracy: 0.6036 - val_loss: 1.0162 - val_accuracy: 0.5668
Epoch 8/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.9384 - accuracy: 0.6118 - val_loss: 0.9276 - val_accuracy: 0.6102
Epoch 9/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.9172 - accuracy: 0.6206 - val_loss: 1.1872 - val_accuracy: 0.5215
Epoch 10/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.9054 - accuracy: 0.6286 - val_loss: 0.9491 - val_accuracy: 0.6086
Epoch 11/10000
852/852 [==============================] - 9s 10ms/step - loss: 0.8890 - accuracy: 0.6372 - val_loss: 0.9704 - val_accuracy: 0.5879
Epoch 12/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.8593 - accuracy: 0.6549 - val_loss: 1.0264 - val_accuracy: 0.5836
Epoch 13/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.8401 - accuracy: 0.6607 - val_loss: 0.9895 - val_accuracy: 0.5970
Epoch 14/10000
852/852 [==============================] - 9s 10ms/step - loss: 0.8155 - accuracy: 0.6744 - val_loss: 0.9790 - val_accuracy: 0.6005
Epoch 15/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.7853 - accuracy: 0.6884 - val_loss: 1.0477 - val_accuracy: 0.5800
Epoch 16/10000
852/852 [==============================] - 8s 10ms/step - loss: 0.7653 - accuracy: 0.6952 - val_loss: 1.0013 - val_accuracy: 0.5967

```

Figure 3: Training Log for the 5-class Classification Model

Here we can see that as Training Stopped at epoch 16, our best model was in epoch 6 which had validation accuracy of 61.90%

After some trial and errors, we found that for the best model we could make by altering the network size, had 2.7 million parameters for the five-class classification and 20.4 million parameters for the four-class model




Figure 4: Model Diagram for 4 Class Classifier




Figure 5: Model Diagram for 5 Class Classifier

We were getting the test accuracy **60.71% for four class classifier and 60.24% for the five-class classifier**

5.2 Model using Transformer

Here we used GPT-neo with 125 million parameters and fine-tuned it with our generated dataset.

Our dataset consisted of 34075 rows that were split for training, testing, and validating in the ratio 80:10:10. The following are the sizes for each split:

- Train dataset: 27260 rows
- Validation dataset: 3408 rows
- Test dataset: 3407 rows

At the beginning, each of our input prompts are converted into tokens using GPT2 tokenizer.

```
print((final_test_dataset[5]))
print(test_dataset[5])
```

```
Cyphertext: ymccaygimgamkyyiycuycqocyeagmigkycmyyoyy
Algorithm: affine

(tensor([   34,  4464,   372,  5239,    25,   331,    76,   535,   323,    70,
         9600,   321,  2584,    88,  7745,    66,  4669,    66,    80,   420,
         5948,   363,    76,   328,  2584,    66,  1820,    88,   726,    88,
          198,  2348, 42289,    25,  1527,   500,   198, 50256, 50256, 50256,
        50256, 50256, 50256, 50256, 50256, 50256, 50256, 50256, 50256, 50256,
        50256, 50256, 50256, 50256, 50256]), tensor([1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,
        1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
        0, 0, 0, 0, 0, 0, 0]))
```

Figure 6: GPT2 Tokenizer in action

Here we see that the input prompt containing ciphertext and result has their corresponding tokens. Since we have used a tokenizer of fixed size, the unused indexes have higher integer values and have been masked by an attention mask containing 0 at that index.

The training and validation data was fit into the model each having a batch size of 32 and was run for 5 epochs.

```
Num examples = 27260
Num Epochs = 5
Instantaneous batch size per device = 32
Total train batch size (w. parallel, distributed & accumulation) = 32
Gradient Accumulation steps = 1
Total optimization steps = 4260
Number of trainable parameters = 125198592
```

Figure 7: Training Parameters for the GPT2 Fine Tuning

[4260/4260 37:12, Epoch 5/5]

Step	Training Loss	Validation Loss
500	1.920900	1.839412
1000	1.826400	1.815576
1500	1.794200	1.798747
2000	1.760900	1.792532
2500	1.746500	1.784798
3000	1.721100	1.785910
3500	1.708000	1.788620
4000	1.688200	1.787953

Figure 8: Training and Validation Loss obtained every 500 steps

After fine-tuning, we tested the model on our test dataset containing 3407 rows. The model has shown an **overall accuracy of 85.236%**.

```
print(f"Correct: {correct}, Total: {total}")
print(f"Accuracy: {correct/total}")
```

```
Total test dataset size = 3407

Accuracy 0.8324038743762842

Completed 100.0%

Computed 3407 results
Correct: 2836, Total: 3407
Accuracy: 0.8324038743762842
```

Figure 9: Testing Accuracy for the Fine-Tuned GPT2 Model

6 FUTURE

We would also like to alter the test to "image" conversion for the dataset to make CNN model perform better as it is not performing up to the standards that we want.

We would like to finetune our models to see if we can increase the accuracy. We are also curious to see if we can use an RNN instead of transformers and record the difference in accuracy of the two.

A similar analysis can be performed on other models such as:

- OPT
- BERT
- GPTJ
- Bloom

Apart from this, we would like to explore feature detection to create a model and compare this approach with the transformer-based model.

Once we are satisfied with the model accuracy on 5 classes of ciphers, we would like to extend the model to detect more classes such as AES, DES, RSA, etc.

7 CONCLUSION