EE 720: Introduction to Number Theory and Cryptography (Spring 2018)

Instructor: Saravanan Vijayakumaran Indian Institute of Technology Bombay

Date: January 23, 2018

Assignment 2: 10 points

Find the pdf file corresponding to your roll number in the directory https://www.ee.iitb.ac.in/~sarva/courses/EE720/2018/assignments/assignment2/. Upload the answers as a pdf file in Moodle. Use the tex file provided in the directory to fill in your answers. The upload deadline will be 11:00pm IST on Wednesday, January 31, 2018.

1. [5 points] State whether the following encryption scheme is perfectly secret or not. Justify your answer either with a proof or a counterexample.

The message space is $\mathcal{M} = \{m \in \{0,1\}^l \mid \text{the last bit of } m \text{ is } 0\}$. Algorith Gen chooses a uniform key from the keyspace $\{0,1\}^{l-1}$. $\operatorname{Enc}_k(m) = m \oplus (k\|0)$ and $\operatorname{Dec}_k(c) = c \oplus (k\|0)$.

Solution: Write your answer here

2. [5 points] When the one-time pad is used with the all-zeros key, i.e. $k = 0^l$, we have $\operatorname{Enc}_k(m) = m \oplus k = m$. This means that the plaintext will be sent as it is. To prevent this, suppose we modify the one-time pad to use only non-zero keys, $k \neq 0^l$. The key generation algorithm Gen picks key k uniformly from the set $\{0,1\}^l \setminus \{0^l\}$ which has cardinality $2^l - 1$. Is this modified scheme still perfectly secret? Justify your answer either with a proof or a counterexample.

Solution: Write your answer here