EE 720: Introduction to Number Theory and Cryptography (Spring 2018)
Instructor: Saravanan Vijayakumaran
Indian Institute of Technology Bombay

Assignment 2: 10 points Date: January 23, 2018

Find the pdf file corresponding to your roll number in the directory `https://www.ee.iitb.ac.in/~sarva/courses/EE720/2018/assignments/assignment2/`. Upload the answers as a **pdf** file in Moodle. Use the tex file provided in the directory to fill in your answers. The **upload deadline** will be 11:00pm IST on Wednesday, January 31, 2018.

1. [5 points] Let $\texttt{negl}_1$ be a negligible function. Prove that for any positive polynomial p, the function $\texttt{negl}_2$ defined by $\texttt{negl}_2(n) = p(n) \cdot \texttt{negl}_1(n)$ is negligible.

   Solution: Write your answer here

2. [5 points] When the one-time pad is used with the all-zeros key, i.e. $k = 0^l$, we have $\texttt{Enc}_k(m) = m \oplus k = m$. This means that the plaintext will be sent as it is. To prevent this, suppose we modify the one-time pad to use only non-zero keys, $k \neq 0^l$. The key generation algorithm `Gen` picks key k uniformly from the set $\{0,1\}^l \setminus \{0^l\}$ which has cardinality $2^l - 1$. Is this modified scheme still perfectly secret? Justify your answer either with a proof or a counterexample.

   Solution: Write your answer here