

## MACHINE LEARNING

In Q1 to Q7, only one option is correct, Choose the correct option:

1. The value of correlation coefficient will always be:
- A) between 0 and 1
  - B) greater than -1
  - C) between -1 and 1
  - D) between 0 and -1

**Answer – C) between -1 and 1**

2. Which of the following cannot be used for dimensionality reduction?
- A) Lasso Regularisation
  - B) PCA
  - C) Recursive feature elimination
  - D) Ridge Regularisation

**Answer – C) Recursive feature elimination**

3. Which of the following is not a kernel in Support Vector Machines?
- A) linear
  - B) Radial Basis Function
  - C) hyperplane
  - D) polynomial

**Answer – C) hyperplane**

4. Amongst the following, which one is least suitable for a dataset having non-linear decision boundaries?
- A) Logistic Regression
  - B) Naïve Bayes Classifier
  - C) Decision Tree Classifier
  - D) Support Vector Classifier

**Answer – A) Logistic Regression**

5. In a Linear Regression problem, 'X' is independent variable and 'Y' is dependent variable, where 'X' represents weight in pounds. If you convert the unit of 'X' to kilograms, then new coefficient of 'X' will be?
- (1 kilogram = 2.205 pounds)
- A)  $2.205 \times$  old coefficient of 'X'
  - B) same as old coefficient of 'X'
  - C) old coefficient of 'X'  $\div 2.205$
  - D) Cannot be determined

**Answer – A) 2.205 x old coefficient of 'X'**

6. As we increase the number of estimators in ADABOOST Classifier, what happens to the accuracy of the model?
- A) remains same
  - B) increases
  - C) decreases
  - D) none of the above

**Answer – B) increases**

---

## MACHINE LEARNING

7. Which of the following is not an advantage of using random forest instead of decision trees?
- A) Random Forests reduce overfitting
  - B) Random Forests explains more variance in data then decision trees
  - C) Random Forests are easy to interpret
  - D) Random Forests provide a reliable feature importance estimate

**Answer – C) Random Forests are easy to interpret**

**In Q8 to Q10, more than one options are correct, Choose all the correct options:**

8. Which of the following are correct about Principal Components?
- A) Principal Components are calculated using supervised learning techniques
  - B) Principal Components are calculated using unsupervised learning techniques
  - C) Principal Components are linear combinations of Linear Variables.
  - D) All of the above

**Answer – B) & C)**

9. Which of the following are applications of clustering?
- A) Identifying developed, developing and under-developed countries on the basis of factors like GDP, poverty index, employment rate, population and living index
  - B) Identifying loan defaulters in a bank on the basis of previous years' data of loan accounts.
  - C) Identifying spam or ham emails
  - D) Identifying different segments of disease based on BMI, blood pressure, cholesterol, blood sugar levels.

**Answer – B) & C)**

10. Which of the following is(are) hyper parameters of a decision tree?
- A) max\_depth
  - B) max\_features
  - C) n\_estimators
  - D) min\_samples\_leaf

**Answer – B) & D)**

**Q11 to Q15 are subjective answer type questions, Answer them briefly.**

11. What are outliers? Explain the Inter Quartile Range (IQR) method for outlier detection.

**Answer – Outlier** is an observation that lies an abnormal distance from other values in a random sample from a population. In other words, they are the unusual values in a dataset.

**Inter Quartile Range (IQR)** has the formula

$$IQR=Q3-Q1,$$

---

## MACHINE LEARNING

Where IQR is the range between first and third quartile range. The datapoints which falls below  $Q1 - 1.5$  and above  $Q3 + 1.5$  are outliers.

IQR is used to measure variability by dividing a data set into quartiles. The data is sorted in ascending order and split into 4 equal parts.  $Q1$ ,  $Q2$ ,  $Q3$  called first, second and third quartiles are the values which separate the 4 equal parts.

- $Q1$  represents the 25th percentile of the data.
- $Q2$  represents the 50th percentile of the data.
- $Q3$  represents the 75th percentile of the data.

If a dataset has  $2n / 2n+1$  data points, then

$Q1$  = median of the dataset &

$Q2$  = median of  $n$  smallest data points.

$Q3$  = median of  $n$  highest data points.

IQR is the range between the first and the third quartiles namely  $Q1$  and  $Q3$ :  $IQR = Q3 - Q1$ . The data points which fall below  $Q1 - 1.5 IQR$  or above  $Q3 + 1.5 IQR$  are outliers.

---

12. What is the primary difference between bagging and boosting algorithms?

**Answer** – Difference between **Bagging** and **Boosting** algorithms are:

- a. Bagging is a way to decrease the variance in the prediction by generating additional data for training from dataset using combinations with repetitions to produce multi-sets of the original data. Boosting is an iterative technique which adjusts the weight of an observation based on the last classification.
  - b. Bagging is the method of merging same type of predictions and Boosting is a method of merging different types of predictions.
  - c. In Bagging the result is obtained by averaging the responses of the  $N$  learners. Boosting assigns a second set of weights, this time for the  $N$  classifiers in order to take a weighted average of their estimates.
- 

13. What is adjusted  $R^2$  in linear regression. How is it calculated?

**Answer** - Adjusted  $R^2$  is a modified version of  $R^2$  that has been adjusted for the number of predictors in the model. Its value can be calculated based on value of  $R^2$ .

Every time you add an independent variable to a model,  $R$  squared increases, even if the independent variable is insignificant. Its value can be calculated based on value of  $r$ -squared, number of independent variables (predictors), total sample size.

---

## MACHINE LEARNING

It is calculated as:

$$\text{Adjusted } R^2 = 1 - [(1-R^2) * (n-1) / (n-k-1)]$$

Where, ***n*** is the number of points in data sample, and ***k*** is the number of independent regressors, i.e. the number of variables in model, excluding the constant.

---

14. What is the difference between standardization and normalization?

**Answer – Normalization** is a scaling technique in which values are shifted and rescaled so that they end up ranging between 0 and 1. It is also known as **Min-Max scaling**.

It rescales the values into a range of [0,1]. This might be useful in some cases where all parameters need to have the same positive scale. However, the outliers from the data set are lost.

$$\begin{aligned} X_{\text{changed}} &= \frac{X - X_{\min}}{X_{\max} - X_{\min}} \\ &= \frac{X - X_{\min}}{X_{\max} - X_{\min}} \end{aligned}$$

**Standardization** is another scaling technique where the values are centred around the mean with a unit standard deviation. It means that the mean of the attribute becomes zero and the resultant distribution has a unit standard deviation.

It rescales data to have a mean ( $\mu$ ) of 0 and standard deviation ( $\sigma$ ) of 1 (unit variance).

$$X_{\text{changed}} = \frac{X - \mu}{\sigma}$$


---

15. What is cross-validation? Describe one advantage and one disadvantage of using cross-validation.

**Answer – Cross-Validation** is a statistical method of evaluating and comparing learning algorithms by dividing data into two segments: one used to learn or train a model and the other used to validate the model. It is a technique for assessing how statistical analysis generalizes to an independent dataset. It is a technique for evaluating machine learning models by training several models on subsets of the available input data and evaluating them on complementary subset of data.

**Advantage:**

**Reduces Overfitting:** In Cross Validation, we split the dataset into multiple folds and train the algorithm on different folds. This prevents our model from overfitting the training dataset. So, in this way, the model attains the generalization capabilities which is a good sign of a robust algorithm

**Disadvantage:**

**Increases Training Time:** Cross Validation drastically increases the training time. Earlier you had to train your model only on one training set, but with Cross Validation you have to train your model on multiple training sets.

---