CODEALPHA ROBOTICS & AUTOMATION INTERNSHIP

Task 4: IoT in Robotics and Automation

IoT-Enabled Robotic Pick-and-Place Automation System

Student: Er. Abhishek Kumar Gupta

College: Lakshmi Narain College of Technology, Bhopal, Madhya Pradesh

Branch: Electronics and Communication Engineering (ECE), 5th Semester

Internship: CodeAlpha – Robotics & Automation Internship

Internship Dates: 01/10/2026 – 31/10/2026

Abstract

IoT connects sensors, robots, controllers, machines and software so that operational data can be collected, communicated and analyzed. This report presents a conceptual IoT-enabled robotic pick-and-place system and explains its architecture, operation, applications, benefits, challenges, cybersecurity and future scope.

1. Introduction

Traditional robotic systems can perform repetitive operations accurately, but IoT adds connectivity and data visibility. Sensors can report object detection, machine condition, production status and alarms to a local monitoring system or dashboard. This supports remote supervision, maintenance planning and process improvement.

2. What is IoT?

The Internet of Things is a network of physical devices equipped with sensing, processing and communication capabilities. In industrial environments, IoT connects field devices with controllers, gateways, databases, dashboards and analytics applications.

3. IoT, Robotics and Automation

Robotics provides programmable physical movement, automation provides controlled execution of processes, and IoT provides connectivity and data exchange. Together they form a connected automation system. For example, a robotic arm can pick an object while sensors verify its presence and an IoT gateway transmits status and cycle information.

4. Proposed IoT-Based Robotic Pick-and-Place System

A conceptual robotic work cell is proposed in which a 3-DOF robotic arm performs a pick-and-place sequence. Sensors detect the workpiece and monitor selected machine conditions. A microcontroller or PLC performs local control, while an IoT gateway sends selected data to a monitoring dashboard.

5. System Architecture

The architecture can be divided into five layers: (1) physical layer—robot, gripper, work area and safety devices; (2) sensing and actuation layer—object, position, temperature/current sensors and actuators; (3) control layer—microcontroller or PLC; (4) connectivity layer—network and IoT gateway; and (5) application layer—dashboard, storage, alarms and analytics.

6. Working Procedure

The system initializes and checks its conditions. A sensor detects an object. The controller commands the robotic arm to the pick position, activates the gripper and verifies the pick condition. The arm moves to the destination and releases the object. Cycle data and selected sensor/status values are transmitted through the IoT gateway and displayed on a dashboard. Abnormal conditions can generate alarms and cause the local controller to enter a safe state according to the system's safety design.

7. Sensors and Data

Possible data points include object presence, joint position, motor temperature, motor current, operating state, cycle count, cycle time, fault codes, emergency-stop status and energy-related measurements. The actual sensors depend on the hardware used.

8. Communication Technologies

An IoT automation system may use MQTT for lightweight publish/subscribe messaging or OPC UA for structured industrial interoperability. Ethernet or wireless networking may be selected according to the environment. Selection should consider reliability, latency, interoperability and security.

9. Applications

IoT-connected robotics can be applied to manufacturing, assembly, material handling, warehouse automation, inspection, packaging, predictive maintenance, remote equipment monitoring and smart production lines.

10. Benefits

Major benefits include real-time monitoring, remote visibility, maintenance planning, easier fault analysis, production and cycle-time tracking, machine integration and data-driven process improvement.

11. Challenges and Limitations

Challenges include cybersecurity risks, communication failures, network latency, sensor errors, incompatible devices, data-storage requirements and integration cost. Cloud connectivity should not replace local real-time control or safety functions.

12. Cybersecurity and Safety

Security measures should include authentication, access control, secure communication, software maintenance, network segmentation where appropriate, logging and controlled remote access. Emergency stopping and protective interlocks should remain part of the properly designed machine-safety system.

13. Future Scope

Future developments may include predictive maintenance using machine learning, digital twins, energy monitoring, anomaly detection, edge computing, automatic production reports and integration with manufacturing execution systems.

14. Conclusion

IoT extends robotics and automation by adding connectivity, monitoring, data collection and analytics. The proposed pick-and-place system demonstrates how a robotic cell can become a connected automation system. A practical implementation would require appropriate hardware, networking, cybersecurity controls, safety engineering and software integration.

15. References

1. NIST SP 800-82, Guide to Operational Technology (OT) Security. 2. OPC Foundation, OPC Unified Architecture (OPC UA) resources. 3. OASIS, MQTT Version 5.0 specification. 4. International Federation

of Robotics (IFR), robotics and automation resources. 5. CodeAlpha Robotics & Automation Internship – Task 4.