

## **TECHNICAL SPECIFICATIONS**

## Concrete Tiles - HORIZON 8 ® (Without Rainbars)

Last Updated on 2020.05.21

No.	Image	Last Updated on 2020.05.21  Details				
1		Weight	Length (L) : 420 mm Horizontal Width (W) : 330 mm (300 + 30mm) Weight : 4.50 kg/pcs (approximation			
		Minimum Pitch	: 15 - 17.4 °	17.5 - 19.9 °	20 - 24.9 °	≥ 25 °
		Batten Spacing	: 295 mm	295 - 310 mm	295 - 320mm	295 - 345mm
		Minimum Headlap Coverage (based on	: 125 mm	110 - 125 mm	100 - 125 mm	75 - 125 mm
	† Patter Considerate la	minimum Headlap) Laying Pattern	: 11.3 pcs/m2	10.8 pcs/m2 Bond (Lay with	10.4 pcs/m2	9.7 pcs/m2
	* Batten Spacing has to be determined based on actual rafter length.	Fixing Method		ews 70mm / Tile		u / Sealed)
2		Name : Angular Ridge Tile Length (L) : 385 mm (355 + 30mm) Horizontal Width (W) : 240 mm Height (H) : 140 mm Internal Angle : 110° Weight : 4.90 kg/pcs (approximately)  Coverage : 2.90 pcs/m				
3		Name Length (L) Horizontal Width (W) Height (H) Internal Angle Weight	: Angular Ridge End : 270 mm : 240 mm : 140 mm : 110° : 4.20 kg/pcs (approximately)			
4		Name Length (L) Horizontal Width (W) Height (H) Internal Angle Weight Coverage	: Angular Hip Tile : 385 mm (355 + 30mm) : 240 mm : 102 mm : 124° : 4.10 kg/pcs (approximately) : 2.90 pcs/m			
5		Name Length (L) Horizontal Width (W) Height (H) Weight	: Angular Hip End : 268 mm : 243 mm : 102 mm : 2.90 kg/pcs (approximately)			
6		Name Horizontal Width (W) Spread Angle (θ) Weight	: 3 Way Apex : 223 mm : 135° from main ridge line to hip line : 90° between hip lines : 4.60 kg/pcs (approximately)			



## **TECHNICAL SPECIFICATIONS**

## Concrete Tiles - HORIZON 8 ® (Without Rainbars)

Last Updated on 2020.05.21

No.	Image	Details		
7		Name Length (L) Width (W) Internal Angle Weight Coverage	: Universal Angular Verge Tile : 420mm : 155 ~ 175mm : 95° : 4.00 kg/pcs (approximately) : 2.90 - 3.40 pcs/m	
8		Name Length (L) Horizontal Width (W) Internal Angle Weight Coverage Batten Spacing	: Monoridge Tile : 300 mm : 330 mm (300 + 30 mm) : 75° : 4.60 kg/pcs (approximately) : 3.30 pcs/m : 190 - 200mm (Outter side of fascia board to batten)	
9		Name Length (L) Horizontal Width (W) Internal Angle (θ) Weight		
10		Name Length (L) Horizontal Width (W) Headlap Batten Spacing Weight Securing Method	: MONIER Top Light (Horizon 8) (For roof pitch ≥15°) : 420 mm : 330 mm (300 + 30mm) : 75 mm - 125 mm : 295 - 345 mm : 0.80 kg/pcs (approximately) : U-Clip & Tile Clip	
11		Name Length x Width Opening Dimension uPVC Pipe Diameter Pitch (θ) Elastomer Material Weight	: V-Pipe Tile (For roof pitch ≥15°) : 420 (L) mm x 330 (W) mm : 180 (L) mm x 120 (W) mm : 110mm Max. (Outer Diamter) : 15° - 45° : Ethylene Propylene Diene Monomer (EDPM) : 6.00 kg/pcs (approximately)	