

Web Development Full Notes

*From HTML, CSS & JavaScript to
Frontend, Backend, APIs, Databases,
Security & Deployment*



HTML, CSS
& JavaScript



Frontend
Development



Backend
Development



APIs &
Web Services



Databases



Security &
Deployment

DataXOdyssey

Web Development Fundamentals

What is Web Development?

- Web development is the process of building websites and web applications that run on the internet.
- It involves designing, developing and maintaining both the **front end** (what you see) and **back end** (what happens behind the scenes).

Key Components

Frontend (Client-side)

- HTML
- CSS
- JavaScript

What you see and interact with in the browser.

Backend (Server-side)

- Server
- Application logic
- Database
- APIs

Processes requests, handles logic and manages data.

Database

- Stores data
- SQL / NoSQL

Used to store, retrieve and manage data.

Frontend vs Backend

Frontend Development

- Focuses on user interface and user experience
- Built using HTML, CSS, JavaScript
- Frameworks: React, Vue, Angular, etc.

Backend Development

- Focuses on server, database and application logic
- Languages: Node.js, Python, Java, PHP, etc.
- Frameworks: Express, Django, Spring, etc.

Common Technologies

Frontend

- HTML
- CSS
- JavaScript
- React / Angular / Vue


Backend

- Node.js
- Express
- Python (Django)
- Java (Spring)
- PHP (Laravel)

Database

- MySQL
- PostgreSQL
- MongoDB
- SQLite
- Firebase

How the Web Works?



1. You type a URL in your browser.
2. The browser sends a request to the server.
3. The server processes the request and fetches the data (e.g. HTML, images, etc.).
4. The server sends a response back to the browser.
5. The browser renders the website for you.

Client vs Server

Client (Browser)

- Runs on your device
- Sends requests to server
- Renders the response (HTML, CSS, JavaScript)
- 4 Examples: Chrome, Firefox, Edge, Safari

Server

- Runs on a remote machine
- Processes client requests
- Executes application logic
- Interacts with database
- Sends response back to the client
- Examples: Apache, Nginx, Node.js, Express, etc.

Static vs Dynamic Websites


Static Website

- Same content for all users
- Built using HTML, CSS (and sometimes JS)
- No server-side processing (or minimal)
- Examples: Portfolios, Brochure sites

Dynamic Website

- Content can change based on user or data
- Uses backend and database
- Supports user interaction (login, forms, etc.)
- Examples: E-commerce sites, Social media, Web apps

Web Development Workflow



HTML Fundamentals

1. What is HTML?

- HTML (HyperText Markup Language) is the standard language used to create web pages.
- It defines the structure and content of a webpage.
- HTML uses tags to tell the browser what each piece of content is (e.g. heading, paragraph, image, etc.).

2. HTML Document Structure

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8">
    <meta name="viewport"
      content="width=device-width,
      initial-scale=1.0">
    <title>My Website</title>
  </head>
  <body>
    <h1>Hello World!</h1>
  </body>
</html>
```

3. HTML Elements & Tags

- HTML elements are defined using tags.
- Most elements have an opening tag and a closing tag.
- Some elements are self-closing (e.g. `<br>`, `<img>`).

Examples:

`<h1>Heading</h1>` → Element
`<p>Paragraph</p>` → Element
`` → Self-closing
`<br />` → Self-closing

4. Headings, Paragraphs & Text

`<h1>`This is a Heading 1`</h1>`
`<h2>`This is a Heading 2`</h2>`
`<h3>`This is a Heading 3`</h3>`

`<p>`This is a paragraph of text.
It can span multiple lines.`</p>`

`<strong>`Bold text`</strong>`
`<em>`Italic text`</em>`
`<mark>`Highlighted text`</mark>`
`<small>`Smaller text`</small>`

Output:

This is a Heading 1
This is a Heading 2
This is a Heading 3

This is a paragraph of text.
It can span multiple lines.

Bold text
Italic text
Highlighted text
Smaller text

5. Links

- Links are used to navigate to other pages, websites or sections within a page.

`<a href="https://www.google.com">`
Visit Google`</a>`
`<a href="about.html">`About Us`</a>`
`<a href="#section1">`Go to Section`</a>`

Output:

[Visit Google](https://www.google.com)
[About Us](about.html)
[Go to Section](#section1)

6. Images

- Images are added using the `<img>` tag.

``

Attributes:

- src : path to the image file
- alt : alternative text
- width / height : image size

7. Lists

Unordered List (bullets)

`<ul>`
`<li>`Item 1`</li>`
`<li>`Item 2`</li>`
`<li>`Item 3`</li>`
`</ul>`

Output:

- Item 1
- Item 2
- Item 3

Ordered List (numbers)

`<ol>`
`<li>`First`</li>`
`<li>`Second`</li>`
`<li>`Third`</li>`
`</ol>`

Output:

- First
- Second
- Third

8. Tables

```
<table>
  <tr>
    <th>Name</th>
    <th>Age</th>
  </tr>
  <tr>
    <td>Alice</td>
    <td>25</td>
  </tr>
  <tr>
    <td>Bob</td>
    <td>30</td>
  </tr>
</table>
```

Output:

Name	Age
Alice	25
Bob	30

9. Multimedia

Video

`<video width="320" controls>`
`<source src="video.mp4"`
`type="video/mp4">`
Your browser does not
support the video tag.
`</video>`

Audio

`<audio controls>`
`<source src="audio.mp3"`
`type="audio/mpeg">`
Your browser does not
support the audio tag.
`</audio>`

10. HTML5 Semantic Elements

- Semantic elements clearly describe their meaning to both the browser and developers.
- They improve accessibility and SEO.

`<header>` - Top section (logo, navigation)
`<nav>` - Navigation links
`<main>` - Main content
`<section>` - A section of content
`<article>` - Independent content (e.g. blog post)
`<aside>` - Sidebar content
`<footer>` - Bottom section (copyright, links)

HTML Forms & Semantic HTML

1. HTML Forms – Overview

- Forms are used to collect user input and send it to a server.
- Created using the `<form>` element.
- Contain input fields, labels and other form controls.
- Commonly used for login, registration, search, feedback, etc.

Basic Syntax:

```
<form action="/submit" method="post">
  <!-- form elements -->
</form>
```

2. Common Form Elements

Element	Purpose
<code><input></code>	Creates input fields
<code><label></code>	Defines a label for an input
<code><textarea></code>	Multi-line text input
<code><select></code>	Dropdown list
<code><option></code>	Options in a dropdown
<code><button></code>	Clickable button
<code><fieldset></code>	Groups related fields
<code><legend></code>	Title for a fieldset
<code><datalist></code>	Predefined options
<code><output></code>	Displays result of a calculation

3. Input Types

Type	Example / Use
text	Single line text
password	Masked input
email	Email address
number	Numeric input
date	Date picker
radio	Single choice
checkbox	Multiple choice
file	File upload
range	Slider control
color	Color picker
tel	Phone number
url	Website URL
search	Search input

4. Form Example

HTML Code:

```
<form action="/submit" method="post">
  <label for="name">Name:</label>
  <input type="text" id="name"
    name="name" required>

  <label for="email">Email:</label>
  <input type="email" id="email"
    name="email" required>

  <label for="message">Message:</label>
  <textarea id="message" name="message"
    rows="4" required></textarea>

  <button type="submit">Submit</button>
</form>
```

Rendered Output:

Name:

Email:

Message:

5. Radio Buttons & Checkboxes

Radio Buttons (Single Choice)

```
<p>Gender:</p>
<input type="radio" id="male"
  name="gender" value="Male">
<label for="male">Male</label>
<input type="radio" id="female"
  name="gender" value="Female">
<label for="female">Female</label>
```

Output:

Gender:

☒ Male
☐ Female

Checkboxes (Multiple Choice)

```
<p>Hobbies:</p>
<input type="checkbox" id="reading"
  name="hobby" value="Reading">
<label for="reading">Reading</label>
<input type="checkbox" id="traveling"
  name="hobby" value="Traveling">
<label for="traveling">Traveling</label>
```

Output:

Hobbies:

☒ Reading
☐ Traveling
☐ Music

6. Dropdown, File Upload & Other Inputs

Dropdown (Select)

```
<label for="country">Country:</label>
<select id="country" name="country">
  <option value="f">--Select--</option>
  <option value="IN">India</option>
  <option value="US">USA</option>
  <option value="UK">UK</option>
</select>
```

Output:

Country:

File Upload

```
<label for="file">Upload File:</label>
<input type="file" id="file" name="file">
```

Output:

Upload File:

No file chosen

Other Useful Inputs

```
<input type="range" min="0" max="100">
<input type="color">
<input type="search" placeholder="Search...">
```

Output:

9. HTML5 Semantic Elements

- Semantic elements clearly describe the meaning of the content.
- They make HTML more readable, improve accessibility and help with SEO.
- accessibility and help with SEO.
- They do not change how the page looks, but give structure and meaning.

7. Fieldset & Legend

```
<fieldset>
  <legend>Personal Details</legend>
  <label>Name:</label>
  <input type="text" name="name">
  <br><br>
  <label>Email:</label>
  <input type="email" name="email">
</fieldset>
```

Output:

Personal Details

Name:

Email:

10. Common Semantic Elements

Element	Purpose
<code><header></code>	Top section (logo, navigation)
<code><nav></code>	Navigation links
<code><main></code>	Main content
<code><section></code>	A section of content
<code><article></code>	Independent content (e.g. blog post)
<code><aside></code>	Sidebar content
<code><footer></code>	Bottom section (copyright, links)

8. Form Validation

- Use `required` attribute for mandatory fields.
- Use input types like email, number, date for built-in validation.
- Use `pattern` attribute for custom validation.
- Show helpful error messages.

Example:

```
<input type="email" required
  placeholder="Enter a valid email">
```

11. Semantic Layout Example

```
<header>
  <h1>My Website</h1>
</header>
<nav>Navigation Links</nav>
<main>
  <section>Main Content</section>
  <aside>Sidebar</aside>
</main>
<footer>© 2026 My Website</footer>
```

CSS Fundamentals

1. What is CSS?

- CSS (Cascading Style Sheets) is used to style and layout web pages.
- It controls the look and feel of HTML elements.
- You can change colors, fonts, sizes, spacing, and positioning using CSS.
- CSS can be written in three ways: Inline, Internal and External.

2. Ways to Add CSS

Inline CSS (inside element)

```
<p style="color: blue; font-size: 16px;">Hello</p>
```


Internal CSS (inside <head>)

```
<head>
  <style>
    p { color: blue; }
  </style>
</head>
```

External CSS (separate file)

```
<head>
  <link rel="stylesheet" href="styles.css">
</head>
```

3. CSS Syntax



- **Selector:** selects the HTML element.
- **Property:** the style you want to change.
- **Value:** the value to assign to the property.
- Each rule ends with a semicolon (;).

4. Selectors

Selectors are used to target HTML elements.

Selector	Example
Element	p { ... }
ID	#header { ... }
Class	.container { ... }
Multiple	h1, p { ... }
Descendant	div p { ... }
Child	div > p { ... }
Attribute	input[type="text"] { ... }
Pseudo-class	a:hover { ... }

5. Colors

- CSS supports different ways to set colors.

```
p { color: red; } /* name */
p { color: #ff0000; } /* hex */
p { color: rgb(255, 0, 0); }
p { color: rgba(255, 0, 0, 0.5); }
p { color: hsl(0, 100%, 50%); }
```

Background Color

```
div { background-color: #f0f0f0; }
```

6. Fonts & Text

```
p {
  font-family: Arial, sans-serif;
  font-size: 16px;
  font-weight: bold;
  font-style: italic;
  text-align: center;
  text-decoration: underline;
  text-transform: uppercase;
  line-height: 1.5;
  letter-spacing: 1px;
}
```


7. Units

CSS supports different units for size and spacing.

Unit	Example
px	font-size: 16px;
%	width: 50%;
em	font-size: 2em;
rem	font-size: 1.5rem;
vh	height: 100vh;
vw	width: 50vw;
auto	width: auto;

8. Box Model

Every element is a box with content, padding, border and margin.




```
div {
  width: 300px;
  padding: 20px;
  border: 2px solid #333;
  margin: 10px;
}
```

9. Margin vs Padding

Margin


(space outside the element)



```
div { margin: 20px; }
```

Padding

(space inside the element)



```
div { padding: 20px; }
```

10. Borders

Used to set a border around an element.

```
div {
  border: 2px solid #333;
  border-radius: 8px;
  border-style: dashed;
}
```

11. Display Property

Controls how an element is displayed.

Value	Description
block	Takes full width
inline	Takes only needed width
inline-block	Inline element with block features
none	Hides the element
flex	Flexible box layout
grid	Grid layout

12. Common CSS Properties

Category	Properties
Text	color, font-size, font-family, text-align
Background	background-color, background-image
Spacing	margin, padding
Borders	border, border-radius
Size	width, height, max-width, min-height
Layout	display, position, float, clear
Other	opacity, visibility, cursor, overflow

CSS Layout & Responsive Design

1. CSS Layout Overview

- CSS provides different layout methods to position and arrange elements on a web page.
- Common techniques: Block, Inline, Flexbox, Grid, Positioning and Responsive design.
- Layout helps create clean, structured and user-friendly web pages.

2. Display Property

Controls how an element behaves in the layout.

Value	Description
block	Takes full width, starts on new line
inline	Takes only required width
inline-block	Like inline but allows width and height
none	Hides the element
flex	Flexible box layout
grid	Grid layout

```
.box {  
  display: block;  
}
```

3. Flexbox Layout

- Flexbox is used for one-dimensional layouts (row or column).
- Best for aligning and distributing space between items.

Flex Container

```
.container {  
  display: flex;  
  justify-content: space-between;  
  align-items: center;  
  gap: 10px;  
}
```

Output:

Item 1 Item 2 Item 3

4. Flex Properties

Property	Purpose
flex-direction	Direction of items (row or column)
justify-content	Horizontal alignment
align-items	Vertical alignment
gap	Space between items
flex-wrap	Wrap items to next line
flex	Controls item size

```
.container {  
  display: flex;  
  flex-direction: row;  
  justify-content: center;  
  align-items: center;  
  gap: 10px;  
}
```

5. Flex Direction

Row (default)

Item 1 Item 2 Item 3

```
flex-direction: row;
```

Column

Item 1
Item 2
Item 3

```
flex-direction: column;
```

6. CSS Grid Layout

- Grid is used for two-dimensional layouts (rows and columns).
- Best for complex layouts.

Grid Container

```
.grid-container {  
  display: grid;  
  grid-template-columns: repeat(3, 1fr);  
  gap: 10px;  
}
```

Output:

Item 1 Item 2 Item 3
Item 4 Item 5 Item 6

7. Grid Properties

Property	Purpose
grid-template-columns	Defines columns
grid-template-rows	Defines rows
gap	Space between items
justify-items	Horizontal alignment
align-items	Vertical alignment
grid-column	Item spans columns
grid-row	Item spans rows

```
.grid-container {  
  display: grid;  
  grid-template-columns: 1fr 2fr;  
  gap: 10px;  
}
```

8. Positioning

Value	Description
static	Default position
relative	Positioned relative to normal position
absolute	Positioned relative to nearest positioned parent
fixed	Fixed position on screen
sticky	Sticks when scrolling

```
.box {  
  position: absolute;  
  top: 10px;  
  right: 10px;  
}
```

9. Media Queries

- Media queries make your website responsive across different screen sizes.
- Common breakpoints: mobile, tablet, desktop.

```
/* Mobile (default) */  
.container { font-size: 14px; }  
  
/* Tablet */  
@media (min-width: 768px) {  
  .container { font-size: 16px; }  
}  
  
/* Desktop */  
@media (min-width: 1024px) {  
  .container { font-size: 18px; }  
}
```

10. Responsive Design Example

Mobile (< 768px)

Header
Content
Sidebar
Footer

Tablet (768px - 1024px)

Header
Content Sidebar
Footer

Desktop (> 1024px)

Header
Sidebar Content Sidebar
Footer

11. Important Tips

- Use Flexbox for simple one-dimensional layouts.
- Use Grid for complex two-dimensional layouts.
- Use media queries to make your website responsive.
- Use relative units (% , rem , em) instead of fixed pixels for better responsiveness.
- Keep a mobile-first approach.
- Test your layout on different screen sizes.

Modern CSS

1. What is Modern CSS?

- Modern CSS includes new features and techniques that make styling easier, more powerful and responsive.
- Helps create attractive, interactive and modern web designs without using JavaScript.
- Common features: Transitions, Animations, Variables, Pseudo-classes/elements, Advanced selectors, etc.

2. CSS Variables (Custom Properties)

- Variables store values like colors, fonts, sizes, etc., and can be reused.
- They make your CSS easier to maintain.

```
:root {
  --primary-color: #3498db;
  --text-color: #333;
  --font-size: 16px;
}

.button {
  background-color: var(--primary-color);
  color: var(--text-color);
  font-size: var(--font-size);
}
```

3. Transitions

- Transitions create smooth changes between CSS property values.

```
.btn {
  background-color: #3498db;
  transition: background-color 0.3s ease, transform 0.3s ease;
}

.btn:hover {
  background-color: #2980b9;
  transform: scale(1.05);
}
```



4. Animations

- Animations let you create complex animations with keyframes.


```
@keyframes slideIn {
  from {
    opacity: 0;
    transform: translateX(-50px);
  }
  to {
    opacity: 1;
    transform: translateX(0);
  }
}

.box {
  animation: slideIn 1s ease-in-out;
}
```

5. Transform & Scale

- Used to move, rotate, scale or skew elements.

```
.card {
  transform: translateY(10px) rotate(2deg) scale(1.05);
}
```



6. Filters

- Filters are used to add visual effects to elements like images.

```
.image {
  filter: grayscale(50%) brightness(0.8) contrast(1.2);
}
```



7. Pseudo-classes

- Used to style elements based on their state.

```
a:hover {
  color: #e74c3c;
}

input:focus {
  border: 2px solid #3498db;
  outline: none;
}

li:nth-child(odd) {
  background-color: #f8f8f8;
}
```

Common Pseudo-classes

:hover (mouse over)
:focus (input focus)
:active (when clicked)
:first-child
:last-child
:nth-child(n)
:nth-of-type(n)
:checked (checkbox/radio)
:disabled (disabled input)

8. Pseudo-elements

- Used to style a specific part of an element.

```
.text::first-letter {
  font-size: 2em;
  color: #3498db;
}

.text::first-line {
  font-weight: bold;
}

.button::after {
  content: " → ";
  margin-left: 8px;
}
```

9. Advanced Selectors

- Help target elements more precisely.

Selector	Example
Attribute selector	input[type="text"]
Multiple classes	.card.primary
Descendant selector	.container p
Child selector	ul > li
Adjacent sibling	h1 + p
General sibling	h1 ~ p
Not selector	:not(.active)
Combine selectors	div.card > h2.title

10. CSS Functions

- Useful built-in functions to create flexible and modern designs.

```
.box {
  width: calc(100% - 20px); /* calculation */
  background: linear-gradient(45deg, #3498db, #9b59b6);
  border-radius: 10px;
  box-shadow: 0 4px 8px rgba(0,0,0,0.2);
}
```

11. Responsive Images & Media

- Make images responsive using max-width.

```
img {
  max-width: 100%;
  height: auto;
}
```

- Use object-fit to control how images fill a container.

```
.image {
  width: 300px; height: 200px;
  object-fit: cover;
}
```

12. Useful Tips

- Use CSS variables for consistent design.
- Use Flexbox or Grid for layout.
- Combine transitions and transforms for smooth effects.
- Use media queries for responsiveness.
- Use modern units like rem, em, vw, vh.
- Keep your CSS organized and reusable.
- Use browser DevTools to test and debug.
- Prefer CSS over JavaScript for visual effects whenever possible.

JavaScript Fundamentals

1. What is JavaScript?

- JavaScript is a high-level, interpreted programming language used to make web pages interactive.
- It runs in the browser and can also be used on the server (e.g. Node.js).
- It can manipulate the HTML and CSS, handle user events, make API calls and more.

2. How to Add JavaScript?

Inline JavaScript (inside element)

```
<button onclick="alert('Hello!')">
  Click Me
</button>
```

Internal JavaScript (inside <script> tag)

```
<script>
  console.log("Hello JavaScript!");
</script>
```

External JavaScript (separate file)

```
<script src="script.js"></script>
```

3. Variables

- Variables are used to store data in memory.
- Use **let** (can change), **const** (cannot change) or **var** (old way).

Keyword	Scope	Can be Reassigned?
var	Function scope	Yes
let	Block scope	Yes
const	Block scope	No

Examples:

```
let name = "John"; // string
let age = 25;      // number
const pi = 3.14;   // constant value
```

4. Data Types

- JavaScript has different data types to store different kinds of values.

Type	Example	Description
String	"Hello"	Text data
Number	25	Numeric values
Boolean	true / false	True or false
Undefined	let x;	Variable declared but no value
Null	null	Intentional empty value
Object	{ name: "John" }	Collection of key-value pairs
Array	[1, 2, 3]	Ordered list of values

5. Operators

- Operators are used to perform operations on values and variables.

Type	Examples	Description
Arithmetic	+ - * / %	Math operations
Assignment	= += -=	Assign values
Comparison	== === != > <	Compare values
Logical	&& !	Logical operations
Increment/Decrement	++ --	Increase or decrease by 1
Ternary	condition ? value1 : value2	Short if-else

Example:

```
let a = 10;
let b = 5;
console.log(a + b); // 15
console.log(a > b); // true
```

6. Type Conversion

- JavaScript can automatically or manually convert between types.

Implicit Conversion (automatic)

```
console.log("5" + 2); // "52"
console.log("5" - 2); // 3
```

Explicit Conversion (manual)

```
let num = Number("10"); // 10
let str = String(10);   // "10"
let bool = Boolean(1);  // true
```

7. Conditions (If-Else)

- Used to execute different code based on a condition.

```
let age = 18;
if (age >= 18) {
  console.log("Adult");
} else {
  console.log("Minor");
}
```

8. Loops

- Used to repeat a block of code multiple times.

For Loop

```
for (let i = 0; i < 5; i++) {
  console.log(i);
}
```

While Loop

```
let i = 0;
while (i < 5) {
  console.log(i);
  i++;
}
```

9. Functions

- Functions are reusable blocks of code.
- They help to keep code organized and modular.

Function Declaration

```
function greet(name) {
  return "Hello " + name + "!";
}
console.log(greet("John"));
```

Function Expression

```
const add = function(a, b) {
  return a + b;
};
console.log(add(5, 3)); // 8
```

10. Arrays

- Arrays are used to store multiple values in a single variable.

```
let numbers = [1, 2, 3, 4];
console.log(numbers[0]); // 1
numbers.push(5); // [1,2,3,4,5]
```

Common Methods:

push()	- add to end
pop()	- remove from end
shift()	- remove from start
unshift()	- add to start
indexOf()	- find position
includes()	- check if value exists
length	- number of elements

11. Objects

- Objects store data in key-value pairs.

```
let person = {
  name: "John",
  age: 30,
  city: "London"
};
console.log(person.name); // John
console.log(person["age"]); // 30
```

12. Comments

- Used to add notes in the code to make it more readable.

Single-line comment

```
// This is a single-line comment
```

Multi-line comment

```
/* This is a multi-line comment
   that spans multiple lines.
*/
```

13. JavaScript in Browser (Console)

- Open browser developer tools (F12) and go to the Console tab to run and test JavaScript code.
- Useful for debugging and learning.

Examples to try in console:

```
console.log("Hello World!");
2 + 3;
let x = 10;
x * 2;
```

JavaScript Advanced Concepts

1. Arrays (Advanced)

- Arrays store multiple values.
- Use built-in methods for common operations.
- Array methods make code shorter and more readable.

```
const numbers = [1, 2, 3, 4, 5];
// add element
numbers.push(6); // [1,2,3,4,5,6]
// remove element
numbers.pop(); // [1,2,3,4,5]
// transform
const squares = numbers.map(n => n * n);
// filter
const even = numbers.filter(n => n % 2 === 0);
// sum
const sum = numbers.reduce((a, b) => a + b, 0);
```

4. Spread & Rest Operators

- Spread (...) expands values.
- Rest (...) collects multiple values into an array.

Spread Operator

```
const arr1 = [1, 2];
const arr2 = [3, 4];
const combined = [...arr1, ...arr2];
// [1,2,3,4]

const user1 = { name: "John" };
const user2 = { age: 30 };
const merged = { ...user1, ...user2 };
// { name: "John", age: 30 }
```

Rest Operator (in functions)

```
function sum(...numbers) {
  return numbers.reduce((a, b) => a + b, 0);
}
sum(1, 2, 3, 4); // 10
```

7. this Keyword

- **this** refers to the object that is executing the function.
- Its value depends on how the function is called.

```
const user = {
  name: "John",
  greet: function() {
    console.log("Hello " + this.name);
  }
};
user.greet(); // Hello John
```

10. Error Handling

- Use **try...catch** to handle errors.
- Use **finally** for cleanup code.

```
try {
  let result = riskyFunction();
  console.log(result);
} catch (error) {
  console.log("Error:", error.message);
} finally {
  console.log("Done");
}
```

2. Objects (Advanced)

- Objects store data in key-value pairs.
- Use modern features like destructuring, spread operator and shorthand notation.

```
const person = {
  name: "John",
  age: 30,
  city: "London"
};
```

Destructuring

```
const { name, age } = person;
```

Spread Operator (merge objects)

```
const address = { city: "London" };
const details = { ...person, ...address };
```

Shorthand Property

```
const name = "Alice";
const user = { name }; // { name: "Alice" }
```

5. Scope & Closures

- Scope determines where variables can be accessed.
- Closures let a function remember variables from its outer scope.

Scope Example

```
let globalVar = "Global";
{
  let blockVar = "Block";
  console.log(blockVar); // Block
}
// console.log(blockVar); // Error
```

Closure Example

```
function outer() {
  let count = 0;
  return function inner() {
    count++;
    return count;
  };
}
const counter = outer();
console.log(counter()); // 1
console.log(counter()); // 2
```

8. Arrow Functions

- A shorter syntax for writing functions.
- Does not have its own **this** (inherits from outer scope).

Regular Function

```
const add = function(a, b) {
  return a + b;
};
```

Arrow Function

```
const add = (a, b) => a + b;
const square = n => n * n;
```

3. Destructuring

- Extract values from arrays or objects into variables.
- Makes code cleaner and shorter.

Array Destructuring

```
const fruits = ["Apple", "Banana", "Mango"];
const [first, second] = fruits;
// first = "Apple"
// second = "Banana"
```

Object Destructuring

```
const user = { name: "John", age: 25 };
const { name, age } = user;
// name = "John"
// age = 25
```

Default Values

```
const { country = "UK" } = user;
// country = "UK" (if not present)
```

6. Higher-Order Functions

- Functions that take other functions as arguments or return a function.
- Common examples: **map**, **filter**, **reduce**, **forEach**, **sort**.

Method	Purpose	Example
map()	Transforms each item	[1,2].map(n => n*2)
filter()	Returns items that match condition	[1,2,3].filter(n => n > 1)
reduce()	Reduces to a single value	[1,2,3].reduce((a,b) => a + b, 0)
forEach()	Runs a function for each item	[1,2].forEach(n => console.log(n))
sort()	Sorts items	[3,1,2].sort()

9. Modules

- Split code into multiple files.
- Use **export** to share and **import** to reuse.
- Helps keep code organized.

math.js (export)

```
export const add = (a, b) => a + b;
export const PI = 3.14;
```

app.js (import)

```
import { add, PI } from "./math.js";
console.log(add(2, 3)); // 5
console.log(PI); // 3.14
```

11. Async Code (Callbacks, Promises, async/await)

- Used to handle operations that take time (e.g. API calls).

Callbacks

```
setTimeout(() => {
  console.log("Done");
}, 1000);
```

Promises

```
new Promise((resolve) => {
  setTimeout(() => {
    resolve("Done");
  }, 1000);
}).then(result => {
  console.log(result);
});
```

async/await

```
async function fetchData() {
  const result = await
    new Promise(res => {
      setTimeout(() => {
        res("Done", 1000);
      });
    });
  console.log(result);
}
fetchData();
```

12. Useful ES6+ Features

- **let** and **const**
- **Arrow functions**
- **Template literals** ('Hello \${name}')
- **Default parameters**
- **Destructuring**
- **Spread & rest operators**
- **Classes**
- **Modules (import/export)**
- **Promises and async/await**

Asynchronous JavaScript

1. What is Asynchronous JavaScript?

- JavaScript is single-threaded, so it can do one thing at a time.
- Asynchronous JavaScript allows non-blocking operations like API calls, timers or reading files without stopping the rest of the code.
- It helps keep web pages fast and responsive.



2. Callbacks

- A callback is a function passed into another function to be executed later.
- It was commonly used for asynchronous operations.

```
function fetchData(callback) {
  setTimeout(() => {
    console.log("Data fetched");
    callback();
  }, 2000);
}

function processData() {
  console.log("Processing data...");
}

fetchData(processData);
```

3. Promises

- A Promise represents the eventual completion (or failure) of an asynchronous operation.
- It makes the code cleaner and easier to manage than callbacks.

```
const fetchData = new Promise(
  (resolve, reject) => {
    setTimeout(() => {
      const success = true;
      if (success) {
        resolve("Data fetched");
      } else {
        reject("Error fetching data");
      }
    }, 2000);
  }
);

fetchData
  .then(data => console.log(data))
  .catch(error => console.log(error));
```

4. Promise States

- A Promise can be in one of three states: Pending, Fulfilled or Rejected.

State	Description
Pending	Initial state, neither fulfilled nor rejected.
Fulfilled	Operation completed successfully.
Rejected	Operation failed.

Example:

```
const p = new Promise((resolve, reject) => {
  resolve("Success"); // fulfilled
  // reject("Error"); // rejected
});
```

5. Chaining Promises

- You can chain multiple `.then()` methods to handle a sequence of asynchronous operations.

```
fetchData()
  .then(data => {
    console.log("Step 1:", data);
    return "Next Step";
  })
  .then(result => {
    console.log("Step 2:", result);
  })
  .catch(error => {
    console.log("Error:", error);
  });
```

6. async / await

- `async/await` is a modern way to handle Promises.
- It makes asynchronous code look and behave more like synchronous code.

```
function fetchData() {
  return new Promise(resolve => {
    setTimeout(() => resolve("Data fetched"), 2000);
  });
}

async function getData() {
  try {
    const data = await fetchData();
    console.log(data);
  } catch (error) {
    console.log("Error:", error);
  }
}

getData();
```

7. Promise.all()

- Runs multiple Promises in parallel.
- Waits for all to resolve, or fails if any reject.

```
const p1 = Promise.resolve("Result 1");
const p2 = new Promise(resolve => {
  setTimeout(() => resolve("Result 2"), 1000);
});
const p3 = Promise.resolve("Result 3");

Promise.all([p1, p2, p3])
  .then(results => console.log(results))
  .catch(error => console.log(error));
// ["Result 1", "Result 2", "Result 3"]
```

8. Promise.race()

- Returns the result of the first Promise that settles (resolve or reject).

```
const p1 = new Promise(resolve => {
  setTimeout(() => resolve("First"), 1000);
});
const p2 = new Promise(resolve => {
  setTimeout(() => resolve("Second"), 2000);
});

Promise.race([p1, p2])
  .then(result => console.log(result));
// "First"
```

9. Fetch API Example

- The Fetch API returns a Promise.
- Used to make HTTP requests.

```
async function getUsers() {
  try {
    const response = await fetch(
      "https://jsonplaceholder.typicode.com/users"
    );
    const data = await response.json();
    console.log(data);
  } catch (error) {
    console.log("Error fetching users:", error);
  }
}

getUsers();
```

10. Error Handling

- Use `.catch()` with Promises.
- Use `try...catch` with `async/await`.

With Promises

```
fetchData()
  .then(data => console.log(data))
  .catch(error => console.log(
    "Error:", error
  ));
```

With async/await

```
async function getData() {
  try {
    const data = await fetchData();
  } catch (error) {
    console.log("Error:", error);
  }
}
```

11. Useful Methods

Method	Purpose
<code>Promise.all()</code>	Runs multiple promises in parallel.
<code>Promise.race()</code>	Returns the first settled promise.
<code>Promise.allSettled()</code>	Waits for all promises to settle (success or failure).
<code>Promise.any()</code>	Returns the first fulfilled promise.
<code>Promise.resolve()</code>	Creates a resolved promise.
<code>Promise.reject()</code>	Creates a rejected promise.


12. Key Takeaways

- Use Promises or `async/await` instead of callbacks.
- `async/await` makes code easier to read and maintain.
- Use `Promise.all()` for parallel requests.
- Use `try...catch` for error handling.
- Fetch API is Promise-based and widely used for HTTP requests.
- Asynchronous JavaScript helps create fast, responsive and non-blocking applications.

DOM & Browser APIs

1. What is the DOM?

- The DOM (Document Object Model) represents the HTML document as a tree of objects.
- JavaScript can access and manipulate the DOM to change the content, structure and style of a web page.
- When the browser loads an HTML file, it creates a DOM tree.



2. Selecting Elements

Method	Description
getElementById()	Selects element by ID
getElementsByClassName()	Selects elements by class (HTMLCollection)
getElementsByTagName()	Selects elements by tag (HTMLCollection)
querySelector()	Selects first element using CSS selector
querySelectorAll()	Selects all elements using CSS selector (NodeList)

Examples


```
document.getElementById("title");
document.getElementsByClassName("item");
document.getElementsByTagName("p");
document.querySelector(".container");
document.querySelectorAll(".item");
```

3. Changing Content

- You can change the text, HTML or attributes of an element.

```
const title = document.getElementById("title");
title.textContent = "Hello World!";
title.innerHTML = "<span>Hello</span>";
title.setAttribute("class", "highlight");
title.style.color = "blue";
```

Output:



4. Creating & Removing Elements

- You can create new elements, add them to the DOM and also remove elements.

```
// Create a new element
const newDiv = document.createElement("div");
newDiv.textContent = "New Element";
newDiv.className = "box";
```

```
// Add to DOM
document.body.appendChild(newDiv);
```

```
// Remove an element
const removeBtn = document.getElementById("btn");
removeBtn.remove();
```

5. Traversing the DOM

- You can navigate between parent, child and sibling elements.

Property	Description
parentElement	Returns the parent element
children	Returns child elements
firstElementChild	First child element
lastElementChild	Last child element
nextElementSibling	Next sibling element
previousElementSibling	Previous sibling element

Example:

```
const parent = document.getElementById("parent");
console.log(parent.children);
console.log(parent.firstElementChild);
console.log(parent.nextElementSibling);
```

6. Handling Events

- Events let you respond to user actions like clicks, input, form submission, etc.

```
const btn = document.getElementById("btn");
btn.addEventListener("click", function() {
    alert("Button clicked!");
});
```

Common Events

Event	Triggered When
click	Element is clicked
dblclick	Element is double-clicked
mouseover	Mouse pointer is over element
mouseout	Mouse pointer leaves element
input	User types in an input field
change	Value is changed
submit	Form is submitted
keydown	A key is pressed

7. Working with Forms

- You can access form elements, get their values and handle form submission.

```
const form = document.getElementById("myForm");
form.addEventListener("submit", function(e) {
    e.preventDefault(); // prevent page reload
    const name = document.getElementById("name").value;
    const email = document.getElementById("email").value;
    console.log("Name:", name);
    console.log("Email:", email);
});
```

8. LocalStorage & SessionStorage

- Store data in the browser.
- localStorage keeps data even after the browser is closed.
- sessionStorage clears data when the tab is closed.

```
// localStorage
localStorage.setItem("name", "John");
localStorage.getItem("name"); // "John"
localStorage.removeItem("name");
localStorage.clear();

// sessionStorage
sessionStorage.setItem("token", "abc123");
sessionStorage.getItem("token");
```

9. Fetch API (API Calls)

- The Fetch API is used to make HTTP requests to get or send data (JSON).
- It returns a Promise.

```
// GET request
fetch("https://jsonplaceholder.typicode.com/posts")
    .then(response => response.json())
    .then(data => console.log(data))
    .catch(error => console.error(error));

// POST request
fetch("https://jsonplaceholder.typicode.com/posts", {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({ title: "Hello", body: "World" })
})
    .then(response => response.json())
    .then(data => console.log(data));
```

10. Other Useful Browser APIs

API	Use Case
setTimeout()	Run code after a delay
setInterval()	Run code repeatedly
navigator	Get browser and device info
location	Work with current URL
history	Navigate browser history
screen	Get screen size info
geolocation	Get user's location
matchMedia()	Check media query conditions

11. Example: Mini To-Do List

```
const input = document.getElementById("taskInput");
const list = document.getElementById("taskList");
document.getElementById("addBtn").addEventListener("click", function() {
    const li = document.createElement("li");
    li.textContent = input.value;
    list.appendChild(li);
    input.value = "";
});
```

12. Tips

- Use querySelector/querySelectorAll for more flexible selection.
- Use textContent to add text (safer than innerHTML).
- Use addEventListener instead of inline events.
- Use modern APIs like Fetch and localStorage.
- Keep your code modular and clean.
- Always handle errors (try...catch or .catch()).
- Check browser compatibility for advanced APIs.

Frontend Development

1. What is Frontend Development?

- Frontend development is about building the user interface (UI) that users see and interact with in a web browser.
- It combines HTML, CSS and JavaScript to create responsive, interactive and visually appealing web applications.
- Frontend developers focus on user experience (UX), performance and accessibility.

2. Core Technologies

Technology	Purpose
HTML	Defines the structure and content of web pages.
CSS	Styles the content and controls layout and design.
JavaScript	Adds interactivity and dynamic behavior.

Together:

HTML + CSS + JavaScript = Complete Frontend Development

3. How It Works?

- Browser requests a web page (URL).
- HTML is loaded and parsed to create the page structure (DOM).
- CSS is applied to style the elements (visual presentation).
- JavaScript is executed to add interactivity and dynamic behavior.
- The final result is rendered on the browser for the user.

4. Frontend Development Workflow

- Plan**
Understand requirements and design UI.
- Build**
Write HTML, CSS and JavaScript code.
- Test**
Check functionality, responsiveness and browser compatibility.
- Optimize**
Improve performance and accessibility.
- Deploy**
Publish the website to a server or hosting platform.

5. Frontend Developer Skills

Skill	Description
HTML	Semantic structure of web pages.
CSS	Layout, design, animations, responsive UI.
JavaScript	Interactivity, DOM manipulation, asynchronous code.
Responsive Design	Works on different devices and screen sizes.
Browser DevTools	Debugging and performance analysis.
Version Control	Use Git and GitHub.
Basic Design Skills	Understand UI/UX principles.

6. Project Structure

Typical Folder Structure

```
my-website/  
├── index.html → Main HTML file  
├── styles/  
│   └── style.css → CSS files  
├── scripts/  
│   └── main.js → JavaScript files  
├── images/ → Image assets  
└── other pages like about.html, contact.html, etc.
```

7. Example: Simple Web Page

HTML (index.html)

```
<!DOCTYPE html>  
<html>  
  <head>  
    <title>My Website</title>  
    <link rel="stylesheet" href="style.css">  
  </head>  
  <body>  
    <h1>Welcome to Frontend!</h1>  
    <button id="btn">Click Me</button>  
    <script src="main.js"></script>  
  </body>  
</html>
```

CSS (style.css)

```
body {  
  font-family: Arial;  
  text-align: center;  
  margin-top: 50px;  
}  
h1 {  
  color: #3498db;  
}
```

JavaScript (main.js)

```
document.getElementById("btn").  
  .addEventListener("click",  
    () => {  
      alert("Hello Frontend!");  
    });
```

8. Responsive Design

- Make websites work well on different devices (desktop, tablet, mobile).
- Use CSS media queries to apply different styles based on screen size.

Example:

```
@media (max-width: 768px) {  
  body {  
    font-size: 14px;  
  }  
  .container {  
    flex-direction: column;  
  }  
}
```

9. Best Practices

- Use semantic HTML.
- Keep HTML, CSS and JavaScript files organized.
- Write clean and readable code.
- Make your website responsive.
- Optimize images and assets.
- Use browser DevTools for debugging.
- Follow accessibility guidelines (e.g. alt text, proper contrast).
- Use version control (Git/GitHub).
- Test on multiple browsers and devices.

10. Popular Tools & Frameworks

Tool / Framework	Purpose
VS Code	Code editor for development.
Chrome DevTools	Debugging and performance analysis.
Git & GitHub	Version control and collaboration.
Bootstrap	CSS framework for faster UI design.
Tailwind CSS	Utility-first CSS framework.
React	JavaScript library for building UIs.
Vue.js	Progressive JavaScript framework.
Angular	Full-fledged JavaScript framework (by Google).

11. Career Opportunities

- Frontend Developer
- UI/UX Developer
- Web Developer (Full Stack)
- JavaScript Developer
- React / Angular / Vue Developer
- Freelancing & Remote Work
- Opportunities in product companies, agencies and startups

12. Key Takeaways


- Frontend development combines HTML, CSS and JavaScript.
- It focuses on building user-friendly, responsive and interactive web pages.
- Learn core concepts first, then explore modern frameworks.
- Focus on good design, performance and accessibility.
- Practice by building real projects to strengthen your skills.

Backend Development

1. What is Backend Development?

- Backend development is about building the server-side logic, databases and APIs that power web applications.
- It handles business logic, data processing, security and integration with other services.
- The backend works behind the scenes and communicates with the frontend.

2. How It Works?



3. HTTP Methods

Method	Purpose	Example
GET	Retrieve data	GET /users
POST	Create new data	POST /users
PUT	Update entire data	PUT /users/1
PATCH	Update partial data	PATCH /users/1
DELETE	Delete data	DELETE /users/1

Example (Express.js):

```
app.get("/users", (req, res) => {
  res.json({ message: "Get all users" });
});
app.post("/users", (req, res) => {
  res.json({ message: "Create user" });
});
```

4. Server with Node.js (Express)

- Node.js allows you to run JavaScript on the server.
- Express.js is a popular framework to build web servers and APIs.

Example: Simple Server

```
const express = require("express");
const app = express();
app.use(express.json()); // parse JSON
app.get("/", (req, res) => {
  res.send("Backend Server is Running!");
});
app.listen(3000, () => {
  console.log("Server running on port 3000");
});
```

5. Working with a Database

- Backends store and retrieve data from databases.
- Common databases: MySQL, PostgreSQL, MongoDB.

Example: MongoDB with Mongoose

```
const mongoose = require("mongoose");
mongoose.connect("mongodb://localhost:27017/myDB")
  .then(() => console.log("Connected to DB"))
  .catch(err => console.log(err));
const userSchema = new mongoose.Schema({
  name: String,
  email: String,
  age: Number
});
const User = mongoose.model("User", userSchema);
```

6. REST API Example

- A REST API exposes endpoints to perform CRUD operations on resources.
- It usually returns data in JSON format.

```
// Get all users
app.get("/users", async (req, res) => {
  const users = await User.find();
  res.json(users);
});
// Get user by ID
app.get("/users/:id", async (req, res) => {
  const user = await User.findById(req.params.id);
  res.json(user);
});
// Create a new user
app.post("/users", async (req, res) => {
  const user = new User(req.body);
  await user.save();
  res.json({ message: "User created", user });
});
```

7. Authentication & Authorization

- Authentication verifies who the user is.
- Authorization controls what the user can access.

Example: JWT Authentication

```
const jwt = require("jsonwebtoken");
const secretKey = "mySecretKey";
// Generate token
const token = jwt.sign({ id: user._id }, secretKey, { expiresIn: "1h" });
// Verify token (middleware)
function authenticate(req, res, next) {
  const token = req.headers.authorization;
  if (!token) return res.status(401).send("No token");
  try {
    const decoded = jwt.verify(token, secretKey);
    req.user = decoded;
    next();
  } catch (err) {
    res.status(401).send("Invalid token");
  }
}
```

8. Error Handling

- Use try...catch for async code.
- Send meaningful error messages.

```
app.get("/users/:id", async (req, res) => {
  try {
    const user = await User.findById(req.params.id);
    if (!user) return res.status(404).send("User not found");
    res.json(user);
  } catch (err) {
    console.error(err);
    res.status(500).send("Server error");
  }
});
```

9. Environment Variables

- Store sensitive information like database URL, API keys, secret keys in a .env file.
- Use the dotenv package to load them.

.env file

```
PORT=3000
MONGO_URI=mongodb://localhost:27017/myDB
JWT_SECRET=mySecretKey
```

Using in code

```
require("dotenv").config();
const port = process.env.PORT;
const mongoUri = process.env.MONGO_URI;
```

10. Common Backend Tools

Tool	Purpose
Node.js	Run JavaScript on server
Express.js	Web framework for building APIs
MongoDB / MySQL / PostgreSQL	Databases
Mongoose / Sequelize	Database ORM/ODM
Postman	Test APIs
Nodemon	Auto-restart server during development
dotenv	Manage environment variables
JWT	Authentication
Docker	Containerize applications

11. Project Structure

```
my-backend/
├── node_modules/
├── src/
│   ├── controllers/
│   ├── models/
│   ├── routes/
│   ├── middleware/
│   ├── config/
│   └── app.js
├── .env
├── package.json
└── README.md
```

12. Key Takeaways

- Backend development handles business logic, data and security.
- Use Node.js + Express to build REST APIs.
- Store and manage data in databases (MongoDB, MySQL, PostgreSQL).
- Implement authentication and authorization.
- Use environment variables for sensitive data.
- Follow good project structure and error handling.
- Practice by building real projects like user management system, todo app, or note-taking app.

REST APIs & Web Services

1. What are APIs?

- API (Application Programming Interface) allows different software systems to communicate with each other.
- A REST API is a type of web service that follows REST architectural principles.
- It uses standard HTTP methods and usually works with JSON data.

2. REST Principles

- Client-Server architecture
- Stateless (each request is independent)
- Uses standard HTTP methods
- Resources are identified by URLs
- Usually deals with JSON data
- Can be cached
- Simple and lightweight

3. HTTP Methods

Method	Purpose	Example
GET	Retrieve data	GET /users
POST	Create new data	POST /users
PUT	Update entire data	PUT /users/1
PATCH	Update partial data	PATCH /users/1
DELETE	Delete data	DELETE /users/1

4. API Request & Response

Request (GET)

```
GET /users/1 HTTP/1.1
Host: api.example.com
Accept: application/json
```

Response

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "id": 1,
  "name": "John",
  "email": "john@example.com"
}
```

5. API Endpoints Example

<https://api.example.com/users>

Endpoint	Description
GET /users	Get all users
GET /users/1	Get user by ID
POST /users	Create a new user
PUT /users/1	Update entire user
PATCH /users/1	Update part of a user
DELETE /users/1	Delete a user

6. Working with APIs (JavaScript)

GET Request (using fetch)

```
fetch("https://api.example.com/users")
  .then(response => response.json())
  .then(data => console.log(data))
  .catch(error => console.log(error));
```

POST Request (using fetch)

```
fetch("https://api.example.com/users") {
  method: "POST",
  headers: { "Content-Type": "application/json" },
  body: JSON.stringify({
    name: "John",
    email: "john@example.com"
  })
}
  .then(res => res.json())
  .then(data => console.log(data));
```

7. Status Codes

Code	Meaning
200	OK (Success)
201	Created (Resource created)
400	Bad Request (Invalid input)
401	Unauthorized (Authentication required)
403	Forbidden (No permission)
404	Not Found (Resource not found)
500	Internal Server Error (Server issue)

8. Authentication

- APIs are often protected and require authentication.
- Common methods:
 - API Key
 - Bearer Token (JWT)
 - OAuth

Example: Bearer Token

```
fetch("https://api.example.com/users", {
  headers: {
    "Authorization": "Bearer your_token",
    "Content-Type": "application/json"
  }
});
```

9. Error Handling

- Always handle errors when making API calls.
- Check response status and catch exceptions.

```
fetch("https://api.example.com/users")
  .then(response => {
    if (!response.ok) {
      throw new Error("API Error: " + response.status);
    }
    return response.json();
  })
  .then(data => console.log(data))
  .catch(error => console.log("Error:", error));
```

10. Common API Formats

- JSON (most common)
- XML (older systems)
- Sometimes CSV or plain text

JSON Example

```
{
  "id": 1,
  "name": "John",
  "age": 30,
  "isActive": true
}
```

XML Example

```
<user>
  <id>1</id>
  <name>John</name>
  <age>30</age>
  <isActive>true</isActive>
</user>
```

11. Web Services

- Web services are systems that enable communication over the web.
- Two main types:
 - REST (modern, lightweight, uses JSON)
 - SOAP (older, uses XML and follows strict standards)

12. Key Takeaways

- REST APIs use standard HTTP methods and are stateless.
- They usually exchange data in JSON format.
- Understand endpoints, request/response structure and status codes.
- Use authentication when required.
- Always handle errors in API calls.
- REST APIs are widely used in web and mobile applications.

Databases

1. What is a Database?

- A database is an organized collection of data that can be stored, managed and easily retrieved.
- It helps in efficiently handling large amounts of data.
- Databases are used by applications like websites, mobile apps and business systems.

2. Types of Databases

Type	Description
Relational (SQL)	Structured data in tables (e.g. MySQL, PostgreSQL, SQL Server, Oracle)
NoSQL	Flexible, non-tabular data (e.g. MongoDB, Cassandra, Redis)
In-Memory	Data stored in memory (e.g. Redis)
Cloud Databases	Managed database services (e.g. Amazon RDS, Azure SQL, Google Cloud SQL)

3. Relational Database Concepts

Table: Customers

customer_id	name	city
1	John	Delhi
2	Priya	Mumbai
3	Alex	Bangalore

Table: Orders

order_id	customer_id	amount
101	1	2500
102	2	1200
103	1	3400

- Data is stored in tables (rows and columns).
- Tables can be related using keys.
- Common keys: Primary Key (unique), Foreign Key (links tables).
- Relationships: One-to-One, One-to-Many, Many-to-Many.

4. SQL Basics

Common SQL Commands

Command	Purpose
SELECT	Retrieve data
INSERT	Add new data
UPDATE	Modify existing data
DELETE	Remove data
CREATE	Create table or database
ALTER	Modify table structure
DROP	Delete table or database

5. SQL Query Examples

Create Table

```
CREATE TABLE employees (  
  id INT PRIMARY KEY,  
  name VARCHAR(100),  
  department VARCHAR(50),  
  salary DECIMAL(10,2)  
);
```

Select Data

```
SELECT id, name, department  
FROM employees  
WHERE salary > 40000;
```

Delete Data

```
DELETE FROM employees  
WHERE id = 1;
```

Insert Data

```
INSERT INTO employees  
(id, name, department, salary)  
VALUES  
(1, 'John', 'HR', 50000);
```

Update Data

```
UPDATE employees  
SET salary = 55000  
WHERE id = 1;
```

Alter Table

```
ALTER TABLE employees  
ADD email VARCHAR(100);
```

6. Joins

Join Type	Description
INNER JOIN	Returns matching rows from both tables
LEFT JOIN	All rows from left table and matching from right
RIGHT JOIN	All rows from right table and matching from left
FULL JOIN	All rows from both tables
CROSS JOIN	Cartesian product (all combinations)

Example: INNER JOIN

```
SELECT c.name, o.order_id, o.amount  
FROM customers c  
INNER JOIN orders o  
ON c.customer_id = o.customer_id;
```

7. Constraints

Constraint	Purpose
PRIMARY KEY	Uniquely identifies each record
FOREIGN KEY	Links to primary key in another table
UNIQUE	Ensures all values are unique
NOT NULL	Prevents NULL values
CHECK	Ensures values meet a condition
DEFAULT	Sets a default value

Example:

```
CREATE TABLE products (  
  id INT PRIMARY KEY,  
  name VARCHAR(100) NOT NULL,  
  price DECIMAL(10,2) CHECK (price > 0)  
);
```

8. Indexes

- Indexes improve the speed of data retrieval.
- They create a sorted structure for a column (like a book index).
- Too many indexes can slow down write operations (INSERT/UPDATE).

Example:

```
CREATE INDEX idx_department  
ON employees(department);
```

9. Normalization

- Normalization organizes data to reduce redundancy and improve integrity.
- It involves dividing data into multiple tables and defining relationships.

Normal Form	Description
1NF	Remove duplicate data, ensure atomic values
2NF	1NF + remove partial dependency
3NF	2NF + remove transitive dependency
BCNF	Stronger version of 3NF

10. Transactions

- A transaction is a sequence of operations that are executed as a single unit.
- It follows ACID properties:

Property	Meaning
Atomicity	All or nothing
Consistency	Data remains valid
Isolation	Transactions are independent
Durability	Changes are permanent

Example:

```
BEGIN;  
UPDATE accounts  
SET balance = balance - 500  
WHERE id = 1;  
  
UPDATE accounts  
SET balance = balance + 500  
WHERE id = 2;  
  
COMMIT;
```

11. ACID vs BASE

ACID (Relational Databases)

- Atomicity
- Consistency
- Isolation
- Durability
- Used in traditional SQL databases (e.g. MySQL, PostgreSQL, Oracle)

BASE (NoSQL Databases)

- Basically Available
- Soft state
- Eventually consistent
- Used in distributed NoSQL systems (e.g. MongoDB, Cassandra)

12. Key Takeaways

- Databases store and manage data efficiently.
- Relational databases use tables and SQL.
- NoSQL databases provide flexible data models.
- Use appropriate data types and constraints.
- Indexes improve performance.
- Normalization reduces redundancy.
- Transactions ensure data consistency.
- Choose the right database based on business needs.

Authentication & Web Security

1. Why Authentication & Security?

- Authentication verifies who the user is.
- Authorization controls what the user can access.
- Web security protects your application and user data from attacks.
- It is essential to build secure, reliable and trusted web applications.

4. How Authentication Works?

- 1 User Login**
User enters credentials (e.g. username and password).
- 2 Validation**
Server verifies the credentials.
- 3 Create Session / Token**
If valid, server creates a session or returns a token (e.g. JWT).
- 4 Send to Client**
Session ID (cookie) or token (JWT) is sent to the client.
- 5 Access Protected Resources**
Client includes the session ID or token in subsequent requests.

2. Authentication Methods

Method	Description
Username & Password	Basic method using credentials.
Session-based	Stores user session on server.
Token-based (JWT)	Uses tokens for stateless authentication.
OAuth 2.0	Used for third-party login (e.g. Google, GitHub).
Multi-Factor Authentication (MFA)	Adds an extra layer (e.g. OTP, authenticator app).

3. Authorization Models

Model	Description
RBAC (Role-Based)	Access based on user roles (e.g. admin, user, editor).
ABAC (Attribute-Based)	Access based on user attributes (e.g. department, location).
ACL (Access Control List)	Defines permissions for specific resources.
OAuth 2.0 Scopes	Limits access to specific resources using scopes.
Least Privilege	Give only the minimum permissions required.

5. JSON Web Token (JWT)

- JWT is a self-contained token used for authentication.
- It has three parts: Header, Payload and Signature.
- It is stateless and widely used in APIs.

Example JWT

```
eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.  
eyJ1c2Vybm9iOiJxNjMiLCJyb2ZzIjoiaWRTaW4ifQ.  
Sf1KxwRJSMeKKF2QT4fwpMeJf36POk6yJV_adQssw5c
```

Header	Payload	Signature
{ "alg": "HS256", "typ": "JWT" }	{ "userId": 123, "role": "admin" }	Created using header, payload and a secret key.

6. JWT in Practice (Node.js)

```
// Generate a token  
const jwt = require("jsonwebtoken");  
const payload = { userId: 123, role: "admin" };  
const token = jwt.sign(payload, "mySecretKey", {  
  expiresIn: "1h"  
});  
console.log("Token:", token);
```

```
// Verify a token  
try {  
  const decoded = jwt.verify(token, "mySecretKey");  
  console.log("Valid token:", decoded);  
} catch (err) {  
  console.log("Invalid token");  
}
```

7. Common Security Threats

Threat	Description
SQL Injection	Malicious SQL queries to access or modify data.
Cross-Site Scripting (XSS)	Injecting malicious scripts into web pages.
Cross-Site Request Forgery (CSRF)	Tricking users into performing unintended actions.
Man-in-the-Middle (MITM)	Intercepting data between client and server.
Brute Force Attack	Trying many passwords to gain access.
Session Hijacking	Stealing a valid session to impersonate a user.

8. Security Best Practices

- Use HTTPS to encrypt data in transit.
- Store passwords using hashing (e.g. bcrypt) with salt.
- Use JWT with short expiration time.
- Implement rate limiting to prevent brute force attacks.
- Validate and sanitize user inputs.
- Use secure cookies (HttpOnly, Secure).
- Implement CSRF protection.
- Follow the principle of least privilege.
- Keep dependencies and libraries updated.

9. Secure Password Storage

- Never store plain text passwords.
- Use hashing algorithms like bcrypt.
- Add a salt to make passwords stronger.

Example (Node.js with bcrypt)

```
const bcrypt = require("bcrypt");  
const saltRounds = 10;  
  
// Hash password  
const hashedPassword = await bcrypt.hash(  
  "myPassword123",  
  saltRounds  
);  
  
// Verify password  
const isMatch = await bcrypt.compare(  
  "myPassword123",  
  hashedPassword  
);  
console.log(isMatch); // true or false
```

10. HTTPS and SSL/TLS

- HTTPS encrypts data between client and server using SSL/TLS.
- It prevents eavesdropping and tampering.
- Always use HTTPS, especially for login and sensitive data.
- Obtain SSL/TLS certificates from trusted providers (e.g. Let's Encrypt).

11. OAuth 2.0 (Third-Party Login)

- OAuth 2.0 allows users to login using third-party services (e.g. Google, GitHub).
- Your application gets an access token to access user information (with consent).
- Common flow: Authorization Code Flow.

Use Cases

- Login with Google / GitHub
- Access user profile information
- Integrate with external APIs

12. Key Takeaways

- Authentication verifies identity.
- Authorization controls access.
- Use secure methods like JWT, OAuth 2.0.
- Follow best practices for password storage, HTTPS, input validation and CSRF protection.
- Be aware of common threats like SQL injection, XSS and CSRF.
- Security is an ongoing process — keep learning and updating your knowledge.

Git, GitHub & Development Tools

1. What are Git and GitHub?

- Git is a distributed version control system to track changes in your code.
- GitHub is a cloud platform to host Git repositories, collaborate with others and manage code.
- They help developers work on projects, keep version history and collaborate efficiently.

2. Key Git Concepts

Concept	Description
Repository (repo)	A project folder tracked by Git.
Commit	A snapshot of changes.
Branch	A separate line of development.
Merge	Combines changes from branches.
Remote	A copy of the repository on GitHub or another server.
Clone	Creates a local copy of a remote repository.
Pull	Fetches and merges changes from remote.
Push	Uploads local changes to remote.

3. Common Git Commands

Command	Purpose
git init	Initialize a new repository
git clone <url>	Clone a remote repository
git status	Check the status of changes
git add <file>	Stage changes
git commit -m "msg"	Save changes with a message
git push	Upload changes to remote
git pull	Fetch and merge changes
git branch	List, create or delete branches
git checkout <branch>	Switch to a branch
git merge <branch>	Merge a branch into current
git log	View commit history

4. Git Workflow

- 1 Create / Clone Repository**
Start a new repo or clone an existing one.
- 2 Make Changes**
Edit, add or delete files.
- 3 Stage Changes**
Use `git add` to stage files.
- 4 Commit Changes**
Save changes with a meaningful message.
- 5 Push to Remote**
Upload changes to GitHub.
- 6 Collaborate**
Pull latest changes and merge with team members.

5. Branching and Merging

- Branches allow you to work on new features without affecting the main code.
- After development, you merge the branch into the main branch.

Example:

```
# Create a new branch
git branch feature-login
# Switch to the branch
git checkout feature-login
# Make changes and commit
git add .
git commit -m "Add login feature"
# Switch to main branch
git checkout main
# Merge the branch
git merge feature-login
```

6. Working with GitHub

- Create a repository to store your code in the cloud.
- Push your local code to GitHub.
- Use Pull Requests (PR) to suggest and review changes.
- Collaborate with others, track issues and manage projects.

Example: Push a local repo to GitHub

```
# Link local repo to GitHub
git remote add origin https://github.com/username/repo.git
# Push code to main branch
git push -u origin main
```

7. Pull Requests (PR)

- A Pull Request is a way to propose changes to a repository.
- Team members can review, discuss and approve changes.
- Helps maintain code quality and collaboration.

Steps:

- 1** Push your changes to a branch.
- 2** Open a Pull Request on GitHub.
- 3** Add a description of changes.
- 4** Get review and approval.
- 5** Merge the Pull Request.

8. Useful .gitignore

- The .gitignore file tells Git which files and folders to ignore.
- Typically used to ignore temporary files, dependencies and sensitive data.

Example .gitignore for a Node.js project

```
# Dependencies
node_modules/
# Environment variables
.env
# Logs
logs/
*.log
# OS files
.DS_Store
# Build files
dist/
build/
```

9. Other Development Tools

Tool	Purpose
VS Code	Popular code editor with useful extensions.
Terminal / CLI	Command line interface to run commands.
Node.js & npm	Run JavaScript and manage packages.
Postman	Test and develop APIs.
Docker	Containerize applications.
GitHub Desktop	GUI for Git and GitHub.
ESLint	Linting tool to maintain code quality.
Prettier	Code formatter for consistent styling.
Jupyter Notebook	Useful for data and AI development.

10. Git vs GitHub

Git	GitHub
Version control system	Cloud platform for Git repositories
Runs locally on your machine	Hosts code in the cloud
Tracks changes in code	Provides collaboration features
Works offline	Requires internet connection
Commands (git init, commit)	Features like Pull Requests, Issues
Can be used without GitHub	Built on top of Git

11. Best Practices

- Write clear and meaningful commit messages.
- Use branches for new features or bug fixes.
- Keep your repositories organized.
- Use .gitignore to avoid committing unnecessary files.
- Regularly pull changes from remote.
- Review code using Pull Requests.
- Follow consistent code formatting and linting.

12. Key Takeaways

- Git helps you track changes and manage versions of your code.
- GitHub enables collaboration and repository hosting.
- Branches and Pull Requests make team development easier.
- Use .gitignore to keep your repo clean.
- Combine Git with other tools like VS Code, Docker and Postman for a better development experience.
- Follow best practices to maintain clean, collaborative and high-quality code.

Deployment & Web Performance

1. What is Deployment?

- Deployment is the process of making your web application available to users on the internet.
- It involves building, hosting and managing your application on servers or cloud platforms.
- A deployed application can be accessed from anywhere using a domain or URL.

2. Deployment Workflow



3. Common Deployment Options

Platform	Best For	Key Features
Vercel	Frontend (React, Next.js)	Easy deploy, CI/CD, global CDN
Netlify	Static sites, Frontend	Simple setup, form handling, CDN
Render	Full-stack apps	Free tier, backend support
Railway	Full-stack apps	Simple deploy, database support
AWS	Production apps	Scalable, high availability
DigitalOcean	Production apps	VPS, simple and cost-effective

4. Deploying a Frontend (React)

Build the project

```
# Install dependencies
npm install
# Create production build
npm run build
```

Deploy on Vercel (CLI)

```
npm i -g vercel
vercel
# Follow the prompts
```

Or deploy via GitHub

- 1 Push code to GitHub repository
- 2 Connect repo to Vercel/Netlify
- 3 Select framework and deploy

5. Deploying a Backend (Node.js)

Example: Deploy on Render

- 1 Push your code to GitHub
- 2 Create a new Web Service on Render
- 3 Connect your repository
- 4 Set build command: `npm install`
- 5 Set start command: `npm start`
- 6 Add environment variables
- 7 Deploy and get your live URL

Example: app.js

```
const express = require("express");
const app = express();

app.get('/', (req, res) => {
  res.send("Backend is running!");
});

const PORT = process.env.PORT || 3000;
app.listen(PORT, () => {
  console.log(`Server running on port ${PORT}`);
});
```

6. Environment Variables

- Environment variables store sensitive information like API keys, database URLs and secrets.
- They keep your code secure and different for development, staging and production.

Example: .env file

```
PORT=3000
MONGO_URI=mongodb://localhost:27017/mydb
JWT_SECRET=mySecretKey
API_KEY=your_api_key
```

Access in Node.js

```
require("dotenv").config();
const port = process.env.PORT;
const mongoUri = process.env.MONGO_URI;
const apiKey = process.env.API_KEY;
```

7. Using a Custom Domain & SSL

- A custom domain makes your app accessible via a professional URL (e.g. `www.example.com`).
- SSL (HTTPS) encrypts data between the user and your server.
- Most platforms (Vercel, Netlify, Render) provide free SSL certificates.

Steps

- 1 Buy a domain (e.g. from GoDaddy, Namecheap)
- 2 Add domain in your hosting platform
- 3 Update DNS settings
- 4 Enable SSL (usually automatic)
- 5 Wait for propagation (may take a few hours)

8. Monitoring & Logging

- Monitoring helps you track your application's health and performance.
- Logging helps in debugging issues and understanding user behaviour.

Tool	Purpose
Vercel Analytics	Performance & user insights
Render Logs	View application logs
LogRocket	Track user sessions and errors
Sentry	Error tracking and monitoring
Google Analytics	User behaviour and traffic

10. Performance Metrics

Metric	Description
LCP (Largest Contentful Paint)	Time to load main content
FID (First Input Delay)	Time to respond to user interaction
CLS (Cumulative Layout Shift)	Visual stability of the page
TTFB (Time to First Byte)	Time to receive first byte from server
FCP (First Contentful Paint)	Time to display first content

11. Tools to Measure Performance

Tool	Purpose
Google Lighthouse	Analyze performance, SEO, accessibility
PageSpeed Insights	Get performance score and suggestions
Web Vitals	Track real user performance metrics
GTmetrix	Detailed performance report
Chrome DevTools	Inspect and analyze performance in browser

DataXOdyssey

9. Web Performance Optimization

- Faster websites provide a better user experience and improve SEO.
- Optimization helps reduce load time and server costs.

Key Techniques

- 1 Enable caching (browser & CDN)
- 2 Optimize and compress images
- 3 Use a CDN (e.g. Vercel, Cloudflare)
- 4 Minify CSS and JavaScript
- 5 Use lazy loading for images and components
- 6 Implement code splitting (e.g. `React.lazy`)
- 7 Reduce third-party scripts
- 8 Monitor performance (e.g. Lighthouse)

12. Key Takeaways

- Deployment makes your application accessible to real users.
- Use platforms like Vercel, Netlify or Render for easy deployment.
- Keep sensitive data in environment variables.
- Use a custom domain and SSL for a professional and secure setup.
- Monitor logs and performance regularly.
- Optimize your application to improve speed and user experience.

Full-Stack Roadmap + Cheat Sheet

1. What is Full-Stack Development?

- Full-stack development involves building both the frontend (client-side) and backend (server-side) of a web application.
- You work with databases, APIs, user interfaces, deployment and more.
- A full-stack developer can build, test and deploy a complete web application end to end.

2. Full-Stack Roadmap

- Learn the basics (HTML, CSS, JavaScript)
- Build frontend (React or similar)
- Learn backend (Node.js / Python / Java)
- Work with databases (SQL / NoSQL)
- Understand APIs (REST APIs)
- Implement authentication & security
- Use Git, GitHub and development tools
- Deploy your application
- Learn web performance & best practices
- Build real projects and improve

3. Frontend Cheat Sheet

Concept	Key Points
HTML	Structure of web pages
CSS	Styling and layout (Flexbox, Grid)
JavaScript	Interactivity and logic
React	Components, state, props, hooks
Routing	React Router for navigation
State Management	Context API / Redux
Build Tools	Vite / Webpack
HTTP Requests	fetch() or Axios
UI Libraries	Tailwind CSS / Bootstrap
Form Handling	Controlled components, validation

4. Backend Cheat Sheet

Concept	Key Points
Runtime	Node.js (JavaScript)
Framework	Express.js
Routing	Define API endpoints (GET, POST...)
Middleware	Handle requests and errors
Authentication	JWT, Sessions, OAuth
Validation	Validate request data
Error Handling	Try-catch, custom error middleware
Environment Vars	Use .env for sensitive data
Logging	Console / Winston / Morgan
Testing	Postman, Jest, Supertest

5. Database Cheat Sheet

Type	Examples	Key Usage
Relational (SQL)	MySQL PostgreSQL SQLite	Structured data, relationships, complex queries
NoSQL	MongoDB Cassandra Redis	Flexible schema, scalable, high performance
In-Memory	Redis	Caching, fast access
Cloud Databases	AWS RDS Azure SQL MongoDB Atlas	Managed database services
ORM / ODM	Sequelize Prisma (SQL) Mongoose (MongoDB)	Simplify database operations

6. API Cheat Sheet

Method	Purpose	Example
GET	Retrieve data	GET /users
POST	Create new data	POST /users
PUT	Update entire data	PUT /users/1
PATCH	Update partial data	PATCH /users/1
DELETE	Delete data	DELETE /users/1

API Response Format (JSON)

```
{  "success": true,  "data": {    "id": 1,    "name": "John",    "email": "john@example.com"  }}
```

7. Authentication Cheat Sheet

Method	Description
Username & Password	Basic authentication using credentials
Session-based	Store session on server
JWT (Token-based)	Stateless authentication using tokens
OAuth 2.0	Third-party login (Google, GitHub)
MFA	Add an extra layer of security (OTP, authenticator app)

8. Deployment Cheat Sheet

Platform	Best For	Key Features
Vercel	Frontend (React, Next.js)	Easy deploy, CI/CD, global CDN
Netlify	Static sites, Frontend	Simple setup, form handling, CDN
Render	Full-stack apps	Free tier, backend support
Railway	Full-stack apps	Simple deploy, database support
AWS	Production apps	Scalable, high availability
DigitalOcean	Production apps	VPS, simple and cost-effective

9. Useful Dev Tools

Tool	Purpose
VS Code	Code editor with extensions
Git & GitHub	Version control and collaboration
Node.js & npm	Run JavaScript and manage packages
Postman	Test and develop APIs
Docker	Containerize applications
ESLint	Linting tool for code quality
Prettier	Code formatter
Browser DevTools	Debug and inspect frontend code
GitHub Actions	CI/CD automation
Jupyter Notebook	Useful for testing and prototyping

10. Project Ideas

- Personal Portfolio Website
- Blog Platform (Full-stack)
- E-commerce Website
- Task Management App (To-Do)
- Expense Tracker
- Real-time Chat Application
- Movie/Book Recommendation App
- Job Board / Resume Portal
- URL Shortener
- Weather Dashboard (with external API)

11. Best Practices

- Write clean, modular and maintainable code.
- Follow consistent folder structure.
- Use environment variables for sensitive data.
- Validate user inputs and handle errors.
- Implement authentication and authorization.
- Use HTTPS and secure cookies.
- Optimize database queries and use indexes.
- Follow responsive design for better UI/UX.
- Use CI/CD for automated deployment.
- Monitor performance and logs.

12. Key Takeaways

- Full-stack development combines frontend, backend, database, APIs and deployment.
- Start with the fundamentals and build projects.
- Use the right tools and frameworks for your stack.
- Follow best practices for security, performance and maintainability.
- Deploy your applications to make them accessible worldwide.
- Keep learning, build real projects and improve your skills continuously.