\mathcal{PSOPT} Optimal Control Solver User Manual

Release 4.0.0 build 2019.02.24

Victor M. Becerra Email: v.m.becerra@ieee.org http://www.psopt.org

Copyright © 2019 Victor M. Becerra

Disclaimer

This software is provided "as is" and is distributed free of charge. It comes with no warrantees of any kind. See the license terms for more details. The author does hope, however, that users will find this software useful for research and other purposes.

Licensing Agreement

The software package \mathcal{PSOPT} is distributed under the GNU Lesser General Public License version 2.1. Users of the software must abide by the terms of the license.

GNU LESSER GENERAL PUBLIC LICENSE Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc. 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave

you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

O. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and

distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of

the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)
- b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.
- c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

- 7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:
 - a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
 - b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

- 8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.
- 9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.
- 10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
- 11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add

an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

- 15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.
- 16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Contents

1	Intr	oducti	ion to PSOPT	14
	1.1	What	is \mathcal{PSOPT}	14
		1.1.1	Why use \mathcal{PSOPT} and what alternatives exist	15
	1.2	PSOF	${\mathcal{PT}}$ user's group	17
		1.2.1	About the author	17
		1.2.2	Contacting the author	17
		1.2.3	How you can help	17
	1.3	What	is new in Release 4	18
	1.4	Gener	al problem formulation	19
			iew of the Legendre and Chebyshev pseudospectral meth-	
				20
		1.5.1	Introduction to pseudospectral optimal control	20
	1.6	Pseud	ospectral approximations	22
		1.6.1	Interpolation and the Lagrange polynomial	22
		1.6.2	Polynomial expansions	22
		1.6.3	Legendre polynomials and numerical quadrature	23
		1.6.4	Interpolation and Legendre polynomials	25
		1.6.5	Approximate differentiation	26
		1.6.6	Approximating a continuous function using Cheby-	
			shev polynomials	28
		1.6.7	Differentiation with Chebyshev polynomials	31
		1.6.8	Numerical quadrature with the Chebyshev-Gauss-Lobate	to
			method	31
		1.6.9	Differentiation with reduced round-off errors	32
	1.7	The pa	seudospectral discretizations used in \mathcal{PSOPT}	32
		1.7.1	Costate estimates	37
		1.7.2	Discretizing a multiphase problem	37
	1.8	Param	neter estimation problems	38
		1.8.1	Single phase case	39
		1.8.2	Multi-phase case	40
		1.8.3	Statistical measures on parameter estimates	41
		1.8.4	Remarks on parameter estimation	41
	1.9	Altern	native local discretizations	42

		1.9.1	Trapezoidal method	43
		1.9.2	Hermite-Simpson method	44
		1.9.3	Central difference method	45
		1.9.4	Costate estimates with local discretizations	45
	1.10	Extern	al software libraries used by \mathcal{PSOPT}	45
			BLAS and CLAPACK (or LAPACK)	45
			DMatrix library	46
			SuiteSparse	46
			LUSOL	46
		1.10.5	IPOPT	46
			ADOL-C	46
			GNUplot (optional)	47
	1.11		rted platform	47
			tory and home page	47
			e numbering	47
			ing and compiling \mathcal{PSOPT}	48
			Ubuntu Linux 18.4	48
	1.15		tions and known issues	48
2	Defi	ning o	ptimal control and estimation problems for \mathcal{PSOP}	51
	2.1	Interfa	ce data structures	51
	2.2	Requir	red functions	51
		2.2.1	<pre>endpoint_cost function</pre>	52
		2.2.2	<pre>integrand_cost function</pre>	53
		2.2.3	dae function	54
		2.2.4	events function	55
		2.2.5	linkages function	56
		2.2.6	Main function	57
	2.3	Specify	ying a parameter estimation problem	71
	2.4	Autom	natic scaling	72
	2.5	Differe	ntiation	73
	2.6	Genera	ation of initial guesses	73
	2.7	Evalua	ting the discretization error	74
	2.8	Mesh r	refinement	75
		2.8.1	Manual mesh refinement	75
		2.8.2	Automatic mesh refinement with pseudospectral grids	75
		2.8.3	Automatic mesh refinement with local collocation	77
		2.8.4	LATEX code generation	79
	2.9	Implen	nenting multi-segment problems	80
	2.10	Other	auxiliary functions available to the user	82
		2.10.1	cross function	82
		2.10.2	dot function	82
		2.10.3	<pre>get_delayed_state function</pre>	82
		2 10 4	get delayed control function	83

		2.10.5 get_interpolated_state function 84
		2.10.6 get_interpolated_control function 84
		2.10.7 get_control_derivative function
		2.10.8 get_state_derivative function 85
		2.10.9 get_initial_states function 86
		2.10.10 get_final_states function
		2.10.11 get_initial_controls function
		2.10.12 get_final_controls function
		2.10.13 get_initial_time function
		2.10.14 get_final_time function
		2.10.15 auto_link function
		2.10.16 auto_link_2 function
		2.10.17 auto_phase_guess function 89
		2.10.18 linear_interpolation function 89
		2.10.19 smoothed_linear_interpolation function 90
		2.10.20 spline_interpolation function 90
		2.10.21 bilinear_interpolation function 91
		2.10.22 smooth_bilinear_interpolation function 92
		2.10.23 spline_2d_interpolation function 92
		$2.10.24$ smooth_heaviside function 93
		2.10.25 smooth_sign function
		2.10.26 smooth_fabs function
		2.10.27 integrate function
		2.10.28 product_ad functions
		2.10.29 sum_ad function
		2.10.30 subtract_ad function
		2.10.31 inverse_ad function
		2.10.32 rk4_propagate function
		2.10.33 rkf_propagate function
		2.10.34 resample_trajectory function 99
	2.11	Pre-defined constants
	2.12	Standard output
		Implementing your own problem
		2.13.1 Building the user code from Linux 100
3	Exa	mples of using $PSOPT$ 101
	3.1	Alp rider problem
	3.2	Brachistochrone problem
	3.3	Breakwell problem
	3.4	Bryson-Denham problem
	3.5	Bryson's maximum range problem
	3.6	Catalytic cracking of gas oil
	3.7	Catalyst mixing problem
	3.8	Coulomb friction

3.9	DAE index 3 parameter estimation problem 149
3.10	Delayed states problem 1
3.11	Dynamic MPEC problem
3.12	Geodesic problem
3.13	Goddard rocket maximum ascent problem 175
3.14	Hang glider
3.15	Hanging chain problem
3.16	Heat diffusion problem
3.17	Hypersensitive problem
3.18	Interior point constraint problem
3.19	Isoperimetric constraint problem
3.20	Lambert's problem
3.21	Lee-Ramirez bioreactor
3.22	Li's parameter estimation problem
3.23	Linear tangent steering problem
3.24	Low thrust orbit transfer
3.25	Manutec R3 robot
3.26	Minimum swing control for a container crane 271
3.27	Minimum time to climb for a supersonic aircraft 276
3.28	Missile terminal burn maneouvre
3.29	Moon lander problem
3.30	Multi-segment problem
3.31	Notorious parameter estimation problem
3.32	Predator-prey parameter estimation problem
3.33	Rayleigh problem with mixed state-control path constraints . 316
3.34	Obstacle avoidance problem
3.35	Reorientation of an asymmetric rigid body
3.36	Shuttle re-entry problem
3.37	Singular control problem
3.38	Time varying state constraint problem
3.39	Two burn orbit transfer
3.41	Two-phase path tracking robot
3.42	Two-phase Schwartz problem
3.43	Vehicle launch problem
	Zero propellant maneouvre of the International Space Station 409

Chapter 1

Introduction to PSOPT

1.1 What is PSOPT

 \mathcal{PSOPT} is an open source optimal control package written in C++ that uses direct collocation methods. These methods solve optimal control problems by approximating the time-dependent variables using global or local polynomials. This allows to discretize the differential equations and continuous constraints over a grid of nodes, and to compute any integrals associated with the problem using well known quadrature formulas. Nonlinear programming then is used to find local optimal solutions. \mathcal{PSOPT} is able to deal with problems with the following characteristics:

- Single or multiphase problems
- Continuous time nonlinear dynamics
- General endpoint constraints
- Nonlinear path constraints (equalities or inequalities) on states and/or control variables
- Integral constraints
- Interior point constraints
- Bounds on controls and state variables
- General cost function with Lagrange and Mayer terms.
- Free or fixed initial and final conditions
- Linear or nonlinear linkages between phases
- Fixed or free initial time
- Fixed or free final time

- Optimisation of static parameters
- Parameter estimation problems with sampled measurements
- Differential equations with delayed variables.

The implementation has the following features:

- Automatic scaling
- Automatic first and second derivatives using the ADOL-C library
- Numerical differentiation by using sparse finite differences
- Automatic mesh refinement
- Automatic identification of the Jacobian and Hessian sparsity.
- DAE formulation, so that differential and algebraic constraints can be implemented in the same C++ function.

 \mathcal{PSOPT} has interfaces to the following NLP solver:

• IPOPT: an open source C++ implementation of an interior point method for large scale problems. See https://projects.coin-or.org/Ipopt for further details.

1.1.1 Why use PSOPT and what alternatives exist

These are some reasons why users may wish to use \mathcal{PSOPT} :

- Users who for any reason do not have access to commercial optimal control solvers and wish to employ a free open source package for optimal control which does not need a proprietary software environment to run.
- Users who need to link an optimal control solver from stand alone applications written in C++ or other programming languages.
- Users who want to do research with the software, for instance by implementing their own problems, or by customising the code.

PSOPT does not require a commercial software environment to run on, or to be compiled. PSOPT is fully compatible with the gcc compiler, and has been developed under Linux, a free operating system. Note also that the default NLP solver (IPOPT) requires a sparse linear solver from a range of options, some of which are available at no cost. The author has personally used free linear solver MUMPS.

There are commercial tools for solving large scale optimal control problems. Some modern commercial tools include: SOCS developed by J.T. Betts from Boeing, which is a well known tool that is able to solve very large optimal control problems and uses a direct transcription method. See:

http://www.boeing.com/phantom/socs/

• GESOP developed by Astos Solutions GmbH, Germany, which uses various methods for solving complex optimal control problems and includes a graphical user interface. See:

http://www.astos.de/products/gesop

 PROPT, developed by P. E. Rutquist and M. M. Edvall from Tomlab Optimization, which runs under MATLAB and uses pseudospectral methods. See:

http://www.tomdyn.com

• DIDO, developed by I.M. Ross from the Postgraduate Naval School in Monterey, California, is a package that runs under MATLAB and uses pseudospectral methods. See:

http://www.elissar.biz/DIDO.html

• GPOPS-II [33], which has been developed by Anil Rao (University of Florida) and co-workers. GPOPS-II uses pseudospectral methods and requires MATLAB. GPOPS-II. See:

http://www.gpops2.com/

Other software tools implementing direct transcription methods for optimal control include:

• DIRCOL, authored by O. von Stryk, which is a Fortran 77 based tool that uses a direct collocation method. See:

http://www.sim.informatik.tu-darmstadt.de/sw/dircol/dircol.html

• DYNOPT, authored by M. Fikar and M. Cizniar, which is a MATLAB based tool that uses orthogonal collocation on finite elements. See:

http://www.kirp.chtf.stuba.sk/fikar/research/dynopt/dynopt.htm

1.2 PSOPT user's group

A user's group has been created with the purpose of enabling users to share their experiences with using \mathcal{PSOPT} , and to keep a public record of exchanges with the author. It is also a way of being informed about the latest developments with \mathcal{PSOPT} and to ask for help. Membership is free and open. The \mathcal{PSOPT} user's group is located at:

http://groups.google.com/group/psopt-users-group

1.2.1 About the author

Victor M. Becerra obtained his first degree in Electrical Engineering in 1990 from Simon Bolivar University, Caracas Venezuela. Between 1989 and 1991 he worked in power systems analysis and control in CVG Edelca, Caracas. He obtained his PhD for his work on the development of nonlinear optimal control methods from City University, London, in 1994. Between 1994 and 1999 he was a Research Fellow at the Control Engineering Research Centre at City University, London. Between 2000 and 2015 he was an academic at the School of Systems Engineering, University of Reading, UK, where he became a Professor of Automatic Control in 2012. Between 2011 and 2012, he was seconded at the Ford Motor Company in Dunton, Essex, with funding by the Royal Academy of Engineering, where he developed methods for the calibration of gasoline engine oil temperature dynamic models. In 2015, he took the position of Professor of Power Systems Engineering at the University of Portsmouth, UK. He is a Senior Member of the IEEE, a Senior Member of the AIAA, and a Fellow of the Institute of Engineering and Technology. During his career, he has received research funding from the EPSRC, the Royal Academy of Engineering, the European Union, the Knowledge Transfer Partnership programme, Innovate UK and UK industry. He has published over 140 research papers and two books. His web site is: https://sites.google.com/a/port.ac.uk/victor-becerra/home.

1.2.2 Contacting the author

The author is open to discussing with users potential research collaboration leading to publications, academic exchanges, or joint projects. He can be contacted directly for help on the installation and use of the software. His email address is: v.m.becerra@ieee.org.

1.2.3 How you can help

You may help improve \mathcal{PSOPT} in a number of ways.

- Sending bug reports.
- Sending corrections to the documentation.

- Discussing with the author ways to improve the computational aspects or capabilities of the software.
- Sending to the author proposed modifications to the source code, for consideration to be included in a future release of \mathcal{PSOPT} .
- Sending source code with new examples which may be included (with due acknowledgement) in future releases of \mathcal{PSOPT} .
- Porting the software to new architectures.
- If you have had a good experience with \mathcal{PSOPT} , tell your students or colleagues about it.
- Quoting the use of \mathcal{PSOPT} in your scientific publications. This document may be referenced as follows:
 - Becerra, V.M. (2010). "Solving complex optimal control problems at no cost with PSOPT". Proc. IEEE Multi-conference on Systems and Control, Yokohama, Japan, September 7-10, 2010, pp. 1391-1396
 - Becerra, V.M. (2010). PSOPT Optimal Control Solver User Manual. Release 3. Available: http://code.google.com/p/psopt/ downloads/list
- Developing interfaces to other NLP solvers.

1.3 What is new in Release 4

- 1. PSOPT now builds on the latest long term Ubuntu release, which is Ubuntu 18.04.
- 2. Support of newer versions of IPOPT and ADOL-C.
- 3. Fixing of various memory leaks (with thanks to Flavio Santes)
- 4. Improvements and corrections to local mesh refinement procedure (with thanks to Emmanuel Schneider)
- 5. General improvements to the code.
- 6. Fixing of various bugs (with thanks to Flavio Santes and Emmanuel Schneider)
- 7. Support for a newer version of GNUPLOT.
- 8. Additional examples

- 9. Removed official support for SNOPT solver (this can be reinstated by users, if desired. The source code for the old interface is still there but it does not work at present)
- 10. Removed support for Microsoft Windows (this can be reinstated by users if desired. The old Makefiles are still part of the distribution, but they have not been updated)

1.4 General problem formulation

 \mathcal{PSOPT} solves the following general optimal control problem with N_p phases:

Problem \mathcal{P}_1

Find the control trajectories, $u^{(i)}(t), t \in [t_0^{(i)}, t_f^{(i)}]$, state trajectories $x^{(i)}(t), t \in [t_0^{(i)}, t_f^{(i)}]$, static parameters $p^{(i)}$, and times $t_0^{(i)}, t_f^{(i)}, i = 1, \dots, N_p$, to minimise the following performance index:

$$J = \sum_{i=1}^{N_p} \left[\varphi^{(i)}[x^{(i)}(t_f^{(i)}), p^{(i)}, t_f^{(i)}] + \int_{t_0^{(i)}}^{t_f^{(i)}} L^{(i)}[x^{(i)}(t), u^{(i)}(t), p^{(i)}, t] dt \right]$$

subject to the differential constraints:

$$\dot{x}^{(i)}(t) = f^{(i)}[x^{(i)}(t), u^{(i)}(t), p^{(i)}, t], \ t \in [t_0^{(i)}, t_f^{(i)}],$$

the path constraints

$$h_L^{(i)} \le h^{(i)}[x^{(i)}(t), u^{(i)}(t), p^{(i)}, t] \le h_U^{(i)}, t \in [t_0^{(i)}, t_f^{(i)}],$$

the event constraints:

$$e_L^{(i)} \leq e^{(i)}[x^{(i)}(t_0^{(i)}), u^{(i)}(t_0^{(i)}), x^{(i)}(t_f^{(i)}), u^{(i)}(t_f^{(i)}), p^{(i)}, t_0^{(i)}, t_f^{(i)}] \leq e_U^{(i)},$$

the phase linkage constraints:

$$\begin{split} \Psi_{l} &\leq \Psi[x^{(1)}(t_{0}^{(1)}), u^{(1)}(t_{0}^{(1)}), \\ & x^{(1)}(t_{f}^{(1)}), u^{(1)}(t_{f}^{(1)}), p^{(1)}, t_{0}^{(1)}, t_{f}^{(1)}, \\ & x^{(2)}(t_{0}^{(2)}), u^{(2)}(t_{0}^{(2)}) \\ & , x^{(2)}(t_{f}^{(2)}), u^{(2)}(t_{f}^{(2)}), p^{(2)}, t_{0}^{(2)}, t_{f}^{(2)}, \\ & \vdots \\ & x^{(N_{p})}(t_{0}^{(N_{p})}), u^{(N_{p})}(t_{0}^{(N_{p})}), \\ & x^{(N_{p})}(t_{f}^{(N_{p})}), u^{(N_{p})}(t_{f}^{(N_{p})})), p^{(N_{p})}, t_{0}^{(N_{p})}, t_{f}^{(N_{p})}] \leq \Psi_{u} \end{split}$$

the bound constraints:

$$\begin{split} u_L^{(i)} &\leq u^i(t) \leq u_U^{(i)}, \, t \in [t_0^{(i)}, t_f^{(i)}], \\ x_L^{(i)} &\leq x^i(t) \leq x_U^{(i)}, \, t \in [t_0^{(i)}, t_f^{(i)}], \\ p_L^{(i)} &\leq p^{(i)} \leq p_U^{(i)}, \\ \underline{t}_0^{(i)} &\leq t_0^{(i)} \leq \overline{t}_0^{(i)}, \\ \underline{t}_f^{(i)} &\leq t_f^{(i)} \leq \overline{t}_f^{(i)}, \end{split}$$

and the following constraints:

$$t_f^{(i)} - t_0^{(i)} \ge 0,$$

where $i = 1, \ldots, N_p$, and

$$u^{(i)}: [t_0^{(i)}, t_f^{(i)}] \to \mathcal{R}^{n_u^{(i)}}$$

$$x^{(i)}: [t_0^{(i)}, t_f^{(i)}] \to \mathcal{R}^{n_x^{(i)}}$$

$$p^{(i)} \in \mathcal{R}^{n_p^{(i)}}$$

$$\varphi^{(i)}: \mathcal{R}^{n_x^{(i)}} \times \mathcal{R}^{n_x^{(i)}} \times \mathcal{R}^{n_p^{(i)}} \times \mathcal{R} \times \mathcal{R} \to \mathcal{R}$$

$$L^{(i)}: \mathcal{R}^{n_x^{(i)}} \times \mathcal{R}^{n_u^{(i)}} \times \mathcal{R}^{n_p^{(i)}} \times [t_0^{(i)}, t_f^{(i)}] \to \mathcal{R}$$

$$f^{(i)}: \mathcal{R}^{n_x^{(i)}} \times \mathcal{R}^{n_u^{(i)}} \times \mathcal{R}^{n_p^{(i)}} \times [t_0^{(i)}, t_f^{(i)}] \to \mathcal{R}^{n_x^{(i)}}$$

$$h^{(i)}: \mathcal{R}^{n_x^{(i)}} \times \mathcal{R}^{n_u^{(i)}} \times \mathcal{R}^{n_p^{(i)}} \times [t_0^{(i)}, t_f^{(i)}] \to \mathcal{R}^{n_h^{(i)}}$$

$$e^{(i)}: \mathcal{R}^{n_x^{(i)}} \times \mathcal{R}^{n_u^{(i)}} \times \mathcal{R}^{n_u^{(i)}} \times \mathcal{R}^{n_u^{(i)}} \times \mathcal{R}^{n_p^{(i)}} \times \mathcal{R}^{n_p^{(i)}} \times \mathcal{R}^{n_p^{(i)}} \times \mathcal{R}^{n_p^{(i)}}$$

$$\Psi: U_{\Psi} \to \mathcal{R}^{n_{\psi}}$$

where U_{ψ} is the domain of function Ψ .

A multiphase problem like \mathcal{P}_1 is defined and discussed in the book by Betts [3].

1.5 Overview of the Legendre and Chebyshev pseudospectral methods

1.5.1 Introduction to pseudospectral optimal control

Pseudospectral methods were originally developed for the solution of partial differential equations and have become a widely applied computational tool in fluid dynamics [12, 11]. Moreover, over the last 15 years or so, pseudospectral techniques have emerged as important computational methods for solving optimal control problems [16, 17, 19, 35, 25]. While finite

difference methods approximate the derivatives of a function using local information, pseudospectral methods are, in contrast, global in the sense that they use information over samples of the whole domain of the function to approximate its derivatives at selected points. Using these methods, the state and control functions are approximated as a weighted sum of smooth basis functions, which are often chosen to be Legendre or Chebyshev polynomials in the interval [-1,1], and collocation of the differential-algebraic equations is performed at orthogonal collocation points, which are selected to yield interpolation of high accuracy. One of the main appeals of pseudospectral methods is their exponential (or spectral) rate of convergence, which is faster than any polynomial rate. Another advantage is that with relatively coarse grids it is possible to achieve good accuracy [41]. In cases where global collocation is unsuitable (for example, when the solution exhibits discontinuities), multi-domain pseudospectral techniques have been proposed, where the problem is divided into a number of subintervals and global collocation is performed along each subinterval [11].

Pseudospectral methods directly discretize the original optimal control problem to formulate a nonlinear programming problem, which is then solved numerically using a sparse nonlinear programming solver to find approximate local optimal solutions. Approximation theory and practice shows that pseudospectral methods are well suited for approximating smooth functions, integrations, and differentiations [10, 41], all of which are relevant to optimal control problems. For differentiation, the derivatives of the state functions at the discretization nodes are easily computed by multiplying a constant differentiation matrix by a matrix with the state values at the nodes. Thus, the differential equations of the optimal control problem are approximated by a set of algebraic equations. The integration in the cost functional of an optimal control problem is approximated by well known Gauss quadrature rules, consisting of a weighted sum of the function values at the discretization nodes. Moreover, as is the case with other direct methods for optimal control, it is easy to represent state and control dependent constraints.

The Legendre pseudospectral method for optimal control problems was originally proposed by Elnagar and co-workers in 1995 [16]. Since then, authors such as Ross, Fahroo and co-workers have analysed, extended and applied the method. For instance, convergence analysis is presented in [26], while an extension of the method to multi-phase problems is given in [35]. An application that has received publicity is the use of the Legendre pseudospectral method for generating real time trajectories for a NASA spacecraft maneouvre [25]. The Chebyshev pseudospectral method for optimal control problems was originally proposed in 1988 [43]. Fahroo and Ross proposed an alternative method for trajectory optimisation using Chebyshev polynomials [19].

Some details on approximating continuous functions using Legendre and

Chebyshev polynomials are given below. Interested readers are referred to [10] for further details.

1.6 Pseudospectral approximations

1.6.1 Interpolation and the Lagrange polynomial

It is a well known fact in numerical analysis [9] that if $\tau_0, \tau_1, \ldots, \tau_N$ are N+1 distinct numbers and f is a function whose values are given at those numbers, then a unique polynomial $P(\tau)$ of degree at most N exists with

$$f(\tau_k) = P(\tau_k), \text{ for } k = 0, 1, \dots, N$$

This polynomial is given by:

$$P(\tau) = \sum_{k=0}^{N} f(\tau_k) \mathcal{L}_k(\tau)$$

where

$$\mathcal{L}_k(\tau) = \prod_{i=0, i \neq k}^{N} \frac{\tau - \tau_i}{\tau_k - \tau_i}$$
(1.2)

 $P(\tau)$ is known as the Lagrange interpolating polynomial and $\mathcal{L}_k(\tau)$ are known as Lagrange basis polynomials.

1.6.2 Polynomial expansions

Assume that $\{p_k\}_{k=0,1,...}$ is a system of algebraic polynomials, with degree of $p_k = k$, that are mutually orthogonal over the interval [-1,1] with respect to a weight function w:

$$\int_{-1}^{1} p_k(\tau) p_m(\tau) w(\tau) d\tau = 0, \text{ for } m \neq k$$

Define $L_w^2[-1,1]$ as the space of functions where the norm:

$$||v||_w = \left(\int_{-1}^1 |v(\tau)|^2 w(\tau) d\tau\right)^{1/2}$$

is finite. A function $f \in L^2_w[-1,1]$ in terms of the system $\{p_k\}$ can be represented as a series expansion:

$$f(\tau) = \sum_{k=0}^{\infty} \hat{f}_k p_k(\tau)$$

where the coefficients of the expansion are given by:

$$\hat{f}_k = \frac{1}{\|p_k\|^2} \int_{-1}^1 f(\tau) p_k(\tau) w(\tau) d\tau$$
 (1.3)

The truncated expansion of f for a given N is:

$$\mathcal{P}_N f(\tau) = \sum_{k=0}^{N} \hat{f}_k p_k(\tau)$$

This type of expansion is at the heart of spectral and pseudospectral methods.

1.6.3 Legendre polynomials and numerical quadrature

A particular class of orthogonal polynomials are the Legendre polynomials, which are the eigenfunctions of a singular Sturm-Liouville problem [10]. Let $L_N(\tau)$ denote the Legendre polynomial of order N, which may be generated from:

$$L_N(\tau) = \frac{1}{2^N N!} \frac{d^N}{d\tau^N} (\tau^2 - 1)^N$$

Legendre polynomials are orthogonal over [-1,1] with the weight function w=1. Examples of Legendre polynomials are:

$$L_0(\tau) = 1$$

$$L_1(\tau) = \tau$$

$$L_2(\tau) = \frac{1}{2}(3\tau^2 - 1)$$

$$L_3(\tau) = \frac{1}{2}(5\tau^3 - 3\tau)$$

Figure 1.1 illustrates the Legendre polynomials $L_N(\tau)$ for N=0,1,2,4,5,10. Let $\tau_k, k=0,\ldots,N$ be the Lagrange-Gauss-Lobatto (LGL) nodes, which are defined as $\tau_0=-1, \ \tau_N=1, \ \text{and} \ \tau_k$, being the roots of $\dot{L}_N(\tau)$ in the interval [-1,1] for $k=1,2,\ldots,N-1$. There are no explicit formulas to compute the roots of $\dot{L}_N(\tau)$, but they can be computed using known numerical algorithms. For example, for N=20, the LGL nodes $\tau_k, k=0,\ldots,20$ are shown in Figure 1.2.

Note that if $h(\tau)$ is a polynomial of degree $\leq 2N-1$, its integral over $\tau \in [-1,1]$ can be exactly computed as follows:

$$\int_{-1}^{1} h(\tau)d\tau = \sum_{k=0}^{N} h(\tau_k)w_k \tag{1.4}$$

where τ_k , k = 0, ..., N are the LGL nodes and the weights w_k are given by:

$$w_k = \frac{2}{N(N+1)} \frac{1}{[L_N(\tau_k)]^2}, \ k = 0, \dots, N.$$
 (1.5)




Figure 1.1: Illustration of the Legendre polynomials $L_N(\tau)$ for N=0,1,2,4,5,10.




Figure 1.2: Illustration of the Legendre Gauss Lobatto (LGL) nodes for ${\cal N}=20.$

If $L(\tau)$ is a general smooth function, then for a suitable N, its integral over $\tau \in [-1, 1]$ can be approximated as follows:

$$\int_{-1}^{1} L(\tau)d\tau \approx \sum_{k=0}^{N} L(\tau_k)w_k \tag{1.6}$$

The LGL nodes are selected to yield highly accurate numerical integrals. For example, consider the definite integral

$$\int_{-1}^{1} e^{t} \cos(t) dt$$

The exact value of this integral to 7 decimal places is 1.9334214. For N=3 we have $\tau=[-1,-0.4472,0.4472,1],~w=[0.1667,0.8333,0.8333,0.1667],$ hence

$$\int_{-1}^{1} e^t \cos(t) dt \approx w^T h(\tau) = 1.9335$$

so that the error is $\mathcal{O}(10^{-5})$. On the other hand, if N=5, then the approximate value is 1.9334215, so that the error is $\mathcal{O}(10^{-7})$.

1.6.4 Interpolation and Legendre polynomials

The Legendre-Gauss-Lobatto quadrature motivates the following expression to approximate the weights of the expansion (1.3):

$$\hat{f}_k \approx \tilde{f}_k = \frac{1}{\gamma_k} \sum_{j=0}^N f(\tau_j) L_k(\tau_j) w_j$$

where

$$\gamma_k = \sum_{j=0}^{N} L_k^2(\tau_j) w_j$$

It is simple to prove (see [23]) that with these weights, function $f: [-1,1] \to \Re$ can be interpolated over the LGL nodes as a discrete expansion using Legendre polynomials:

$$I_N f(\tau) = \sum_{k=0}^{N} \tilde{f}_k L_k(\tau)$$
(1.7)

such that

$$I_N f(\tau_i) = f(\tau_i) \tag{1.8}$$

Because $I_N f(\tau)$ is an interpolant of $f(\tau)$ at the LGL nodes, and since the interpolating polynomial is unique, we may express $I_N f(\tau)$ as a Lagrange interpolating polynomial:

$$I_N f(\tau) = \sum_{k=0}^{N} f(\tau_k) \mathcal{L}_k(\tau)$$
(1.9)

so that the expressions (1.7) and (1.9) are mathematically equivalent. Expression (1.9) is computationally advantageous since, as discussed below, it allows to express the approximate values of the derivatives of the function f at the nodes as a matrix multiplication. It is possible to write the Lagrange basis polynomials $\mathcal{L}_k(\tau)$ as follows [23]:

$$\mathcal{L}_k(\tau) = \frac{1}{N(N+1)L_N(\tau_k)} \frac{(\tau^2 - 1)\dot{L}_N(\tau)}{\tau - \tau_k}$$

The use of polynomial interpolation to approximate a function using the LGL points is known in the literature as the *Legendre pseudospectral* approximation method. Denote $f^N(\tau) = I_N f(\tau)$. Then, we have:

$$f(\tau) \approx f^{N}(\tau) = \sum_{k=0}^{N} f(\tau_{k}) \mathcal{L}_{k}(\tau)$$
 (1.10)

It should be noted that $\mathcal{L}_k(\tau_j) = 1$ if k = j and $\mathcal{L}_k(\tau_j) = 0$, if $k \neq j$, so that:

$$f^{N}(\tau_k) = f(\tau_k) \tag{1.11}$$

Regarding the accuracy and error estimates of the Legendre pseudospectral approximation, it is well known that for smooth functions $f(\tau)$, the rate of convergence of $f^N(\tau)$ to $f(\tau)$ at the collocation points is faster than any power of 1/N. The convergence of the pseudospectral approximations used by \mathcal{PSOPT} has been analysed by Canuto et al [10].

Figure 1.3 shows the degree N interpolation of the function $f(\tau) = 1/(1+\tau+15\tau^2)$ in (N+1) equispaced and LGL points for N=20. With increasing N, the errors increase exponentially in the equispaced case (this is known as the Runge phenomenon) whereas in the LGL case they decrease exponentially.

1.6.5 Approximate differentiation

The derivatives of $f^N(\tau)$ in terms of $f(\tau)$ at the LGL points τ_k can be obtained by differentiating Eqn. (1.10). The result can be expressed as a matrix multiplication, such that:

$$\dot{f}(\tau_k) \approx \dot{f}^N(\tau_k) = \sum_{i=0}^N D_{ki} f(\tau_i)$$




Figure 1.3: Illustration of polynomial interpolation over equispaced and LGL nodes $\,$

.

where

$$D_{ki} = \begin{cases} -\frac{L_N(\tau_k)}{L_N(\tau_i)} \frac{1}{\tau_k - \tau_i} & \text{if } k \neq i \\ N(N+1)/4 & \text{if } k = i = 0 \\ -N(N+1)/4 & \text{if } k = i = N \\ 0 & \text{otherwise} \end{cases}$$
(1.12)

which is known as the differentiation matrix.

For example, this is the Legendre differentiation matrix for N=5.

$$D = \begin{bmatrix} 7.5000 & -10.1414 & 4.0362 & -2.2447 & 1.3499 & -0.5000 \\ 1.7864 & 0 & -2.5234 & 1.1528 & -0.6535 & 0.2378 \\ -0.4850 & 1.7213 & 0 & -1.7530 & 0.7864 & -0.2697 \\ 0.2697 & -0.7864 & 1.7530 & 0 & -1.7213 & 0.4850 \\ -0.2378 & 0.6535 & -1.1528 & 2.5234 & 0 & -1.7864 \\ 0.5000 & -1.3499 & 2.2447 & -4.0362 & 10.1414 & -7.5000 \end{bmatrix}$$

Figure 1.4 shows the Legendre differentiation of $f(t) = \sin(5t^2)$ for N = 20 and N = 30. Note the vertical scales in the error curves. Figure 1.5 shows the maximum error in the Legendre differentiation of $f(t) = \sin(5t^2)$ as a function of N. Notice that the error initially decreases very rapidly until such high precision is achieved (accuracy in the order of 10^{-12}) that round off errors due to the finite precision of the computer prevent any further reductions. This phenomenon is known as spectral accuracy.

1.6.6 Approximating a continuous function using Chebyshev polynomials

 \mathcal{PSOPT} also has facilities for pseudospectral function approximation using Chebyshev polynomials. Let $T_N(\tau)$ denote the Chebyshev polynomial of order N, which may be generated from:

$$T_N(\tau) = \cos(N\cos^{-1}(\tau)) \tag{1.13}$$

Let τ_k , k = 0, ..., N be the Chebyshev-Gauss-Lobatto (CGL) nodes in the interval [-1, 1], which are defined as $\tau_k = -\cos(\pi k/N)$ for k = 0, 1, ..., N.

Given any real-valued function $f(\tau): [-1,1] \to \Re$, it can be approximated by the Chebyshev pseudospectral method:

$$f(\tau) \approx f^{N}(\tau) = \sum_{k=0}^{N} f(\tau_{k}) \varphi_{k}(\tau)$$
 (1.14)

where the Lagrange interpolating polynomial $\varphi_k(\tau)$ is defined by:

$$\varphi_k(\tau) = \frac{(-1)^{k+1}}{N^2 \bar{c}_k} \frac{(1-\tau^2)\dot{T}_N(\tau)}{\tau - \tau_k}$$
(1.15)




Figure 1.4: Legendre differentiation of $f(t)=\sin(5t^2)$ for N=20 and N=30.




Figure 1.5: Maximum error in the Legendre differentiation of $f(t) = \sin(5t^2)$ as a function of N.

where

$$\bar{c}_k = \begin{cases} 2 & k = 0, N \\ 1 & 1 \le k \le N - 1 \end{cases}$$
 (1.16)

It should be noted that $\varphi_k(\tau_j) = 1$ if k = j and $\varphi_k(\tau_j) = 0$, if $k \neq j$, so that:

$$f^{N}(\tau_{k}) = f(\tau_{k}) \tag{1.17}$$

1.6.7 Differentiation with Chebyshev polynomials

The derivatives of $f^N(\tau)$ in terms of $f(\tau)$ at the CGL points τ_k can be obtained by differentiating (1.14). The result can be expressed as a matrix multiplication, such that:

$$\dot{f}(\tau_k) \approx \dot{F}^N(\tau_k) = \sum_{i=0}^N D_{ki} f(\tau_i)$$
(1.18)

where

$$D_{ki} = \begin{cases} \frac{\bar{c}_k}{2\bar{c}_i} \frac{(-1)^{k+i}}{\sin[(k+i)\pi/2N]\sin[(k-i)\pi/2N]} & \text{if } k \neq i \\ \frac{\tau_k}{2\sin^2[k\pi/N]} & \text{if } i \leq k = i \leq N-1 \\ -\frac{2N^2+1}{6} & \text{if } k = i = 0 \\ \frac{2N^2+1}{6} & \text{if } k = i = N \end{cases}$$
 (1.19)

which is known as the differentiation matrix.

1.6.8 Numerical quadrature with the Chebyshev-Gauss-Lobatto method

Note that if $h(\tau)$ is a polynomial of degree $\leq 2N-1$, its weighted integral over $\tau \in [-1,1]$ can be exactly computed as follows:

$$\int_{-1}^{1} g(\tau)h(\tau)d\tau = \sum_{k=0}^{N} h(\tau_k)w_k$$
 (1.20)

where τ_k , k = 0, ..., N are the CGL nodes, d the weights w_k are given by:

$$w_k = \begin{cases} \frac{\pi}{2N}, & k = 0, \dots, N. \\ \frac{\pi}{N}, & k = 1, \dots, N - 1 \end{cases}$$
 (1.21)

and $g(\tau)$ is a weighting function given by:

$$g(\tau) = \frac{1}{\sqrt{1 - \tau^2}} \tag{1.22}$$

If $L(\tau)$ is a general smooth function, then for a suitable N, its weighted integral over $\tau \in [-1, 1]$ can be approximated as follows:

$$\int_{-1}^{1} g(\tau)L(\tau)d\tau \approx \sum_{k=0}^{N} L(\tau_k)w_k \tag{1.23}$$

1.6.9 Differentiation with reduced round-off errors

The following differentiation matrix, which offers reduced round-off errors [10], is employed optionally by \mathcal{PSOPT} . It can be used both with Legrendre and Chebyshed points.

$$D_{jl} = \begin{cases} -\frac{\delta_l}{\delta_j} \frac{(-1)^{j+l}}{\tau_j - \tau_l} & j \neq l \\ \sum_{i=0, i \neq j}^{N} \frac{\delta_i}{\delta_j} \frac{(-1)^{i+j}}{\tau_j - \tau_i} & j = l \end{cases}$$
 (1.24)

1.7 The pseudospectral discretizations used in PSOPT

To illustrate the pseudospectral discretizations employed in \mathcal{PSOPT} , consider the following single phase continuous optimal control problem:

Problem \mathcal{P}_2

Find the control trajectories, $u(t), t \in [t_0, t_f]$, state trajectories $x(t), t \in [t_0, t_f]$, static parameters p, and times t_0, t_f , to minimise the following performance index:

$$J = \varphi[x(t_0), x(t_f), p, t_0, t_f] + \int_{t_0}^{t_f} L[x(t), u(t), p, t] dt$$

subject to the differential constraints:

$$\dot{x}(t) = f[x(t), u(t), p, t], t \in [t_0, t_f],$$

the path constraints

$$h_L \leq h[x(t), u(t), p, t] \leq h_U, t \in [t_0, t_f]$$

the event constraints:

$$e_L \le e[x(t_0), u(t_0), x(t_f), u(t_f), p, t_0, t_f] \le e_U,$$

the bound constraints on states and controls:

$$u_L \le u(t) \le u_U, t \in [t_0, t_f],$$

$$x_L < x(t) < x_U, t \in [t_0, t_f],$$

and the constraints:

$$\underline{t}_0 \le t_0 \le \overline{t}_0,$$

$$\underline{t}_f \le t_f \le \overline{t}_f$$
,

$$t_f - t_0 \ge 0,$$

where

$$u: [t_{0}, t_{f}] \to \mathcal{R}^{n_{u}}$$

$$x: [t_{0}, t_{f}] \to \mathcal{R}^{n_{x}}$$

$$p \in \mathcal{R}^{n_{p}}$$

$$\varphi: \mathcal{R}^{n_{x}} \times \mathcal{R}^{n_{x}} \times \mathcal{R}^{n_{p}} \times \mathcal{R} \times \mathcal{R} \to \mathcal{R}$$

$$L: \mathcal{R}^{n_{x}} \times \mathcal{R}^{n_{u}} \times \mathcal{R}^{n_{p}} \times [t_{0}, t_{f}] \to \mathcal{R}$$

$$f: \mathcal{R}^{n_{x}} \times \mathcal{R}^{n_{u}} \times \mathcal{R}^{n_{p}} \times [t_{0}, t_{f}] \to \mathcal{R}^{n_{x}}$$

$$h: \mathcal{R}^{n_{x}} \times \mathcal{R}^{n_{u}} \times \mathcal{R}^{n_{p}} \times [t_{0}, t_{f}] \to \mathcal{R}^{n_{h}}$$

$$e: \mathcal{R}^{n_{x}} \times \mathcal{R}^{n_{u}} \times \mathcal{R}^{n_{x}} \times \mathcal{R}^{n_{u}} \times \mathcal{R}^{n_{x}} \times \mathcal{R}^{n_{x}} \times \mathcal{R}^{n_{p}} \times \mathcal{R} \times \mathcal{R} \to \mathcal{R}^{n_{e}}$$

$$(1.25)$$

By introducing the transformation:

$$\tau \leftarrow \frac{2}{t_f - t_0} t - \frac{t_f + t_0}{t_f - t_0},$$

it is possible to write problem \mathcal{P}_3 using a new independent variable τ in the interval [-1,1], as follows:

Problem \mathcal{P}_3

Find the control trajectories, $u(\tau), \tau \in [-1, 1]$, state trajectories $x(\tau), \tau \in [-1, 1]$, and times t_0, t_f , to minimise the following performance index:

$$J = \varphi[x(-1), x(1), p, t_0, t_f] + \frac{t_f - t_0}{2} \int_{-1}^{1} L[x(t), u(t), p, t] d\tau$$

subject to the differential constraints:

$$\dot{x}(\tau) = \frac{t_f - t_0}{2} f[x(\tau), u(\tau), p, \tau], \ \tau \in [-1, 1],$$

the path constraints

$$h_L \le h[x(\tau), u(\tau), p, \tau] \le h_U, \tau \in [-1, 1]$$

the event constraints:

$$e_L \le e[x(-1), u(-1), x(1), u(1), p, t_0, t_f] \le e_U,$$

the bound constraints on controls and states:

$$u_L \le u(\tau) \le u_U, \, \tau \in [-1, 1],$$

$$x_L \le x(\tau) \le x_U, \ \tau \in [-1, 1],$$

and the constraints:

$$\underline{t}_0 \le t_0 \le \overline{t}_0$$
,

$$\underline{t}_f \le t_f \le \bar{t}_f,$$

$$t_f - t_0 \ge 0,$$

The description below refers to the Legendre pseudospectral approximation method. The procedure employed with the Chebyshev approximation method is very similar. In the Legendre pseudospectral approximation of problem \mathcal{P}_3 , the state $x(\tau)$, $\tau \in [-1,1]$ is approximated by the N-order Lagrange polynomial $x^N(\tau)$ based on interpolation at the Legendre-Gauss-Lobatto (LGL) quadrature nodes, so that:

$$x(\tau) \approx x^{N}(\tau) = \sum_{k=0}^{N} x(\tau_k)\phi_k(\tau)$$
 (1.26)

Moreover, the control $u(\tau)$, $\tau \in [-1,1]$ is similarly approximated using an interpolating polynomial:

$$u(\tau) \approx u^{N}(\tau) = \sum_{k=0}^{N} u(\tau_k)\phi_k(\tau)$$
 (1.27)

Note that, from (1.11), $x^N(\tau_k) = x(\tau_k)$ and $u^N(\tau_k) = u(\tau_k)$. The derivative of the state vector is approximated as follows:

$$\dot{x}(\tau_k) \approx \dot{x}^N(\tau_k) = \sum_{i=0}^N D_{ki} x^N(\tau_i), \ i = 0, \dots N$$
 (1.28)

where D is the $(N+1) \times (N+1)$ the differentiation matrix given by $(\ref{eq:condition})$. Define the following $n_u \times (N+1)$ matrix to store the trajectories of the

Define the following $n_u \times (N+1)$ matrix to store the trajectories of the controls at the LGL nodes:

$$U^{N} = \begin{bmatrix} u_{1}(\tau_{0}) & u_{1}(\tau_{1}) & \dots & u_{1}(\tau_{N}) \\ u_{2}(\tau_{0}) & u_{2}(\tau_{1}) & \dots & u_{2}(\tau_{N}) \\ \vdots & \vdots & \ddots & \vdots \\ u_{n_{u}}(\tau_{0}) & u_{n_{u}}(\tau_{1}) & \dots & u_{n_{u}}(\tau_{N}) \end{bmatrix}$$
(1.29)

Define the following $n_x \times (N+1)$ matrices to store, respectively, the trajectories of the states and their derivatives at the LGL nodes:

$$X^{N} = \begin{bmatrix} x_{1}(\tau_{0}) & x_{1}(\tau_{1}) & \dots & x_{1}(\tau_{N}) \\ x_{2}(\tau_{0}) & x_{2}(\tau_{1}) & \dots & x_{2}(\tau_{N}) \\ \vdots & \vdots & \ddots & \vdots \\ x_{n_{x}}(\tau_{0}) & x_{n_{x}}(\tau_{1}) & \dots & x_{n_{x}}(\tau_{N}) \end{bmatrix}$$
(1.30)

and

$$\dot{X}^{N} = \begin{bmatrix}
\dot{x}_{1}(\tau_{0}) & \dot{x}_{1}(\tau_{1}) & \dots & \dot{x}_{1}(\tau_{N}) \\
\dot{x}_{2}(\tau_{0}) & \dot{x}_{2}(\tau_{1}) & \dots & \dot{x}_{2}(\tau_{N}) \\
\vdots & \vdots & \ddots & \vdots \\
\dot{x}_{n_{x}}(\tau_{0}) & \dot{x}_{n_{x}}(\tau_{1}) & \dots & \dot{x}_{n_{x}}(\tau_{N})
\end{bmatrix}$$
(1.31)

From (1.28), X^N and \dot{X}_N are related as follows:

$$\dot{X}^N = X^N D^T \tag{1.32}$$

Now, form the following $n_x \times (N+1)$ matrix with the right hand side of the differential constraints evaluated at the LGL nodes:

$$F^{N} = \frac{t_{0} - t_{f}}{2} \begin{bmatrix} f_{1}(x^{N}(\tau_{0}), u^{N}(\tau_{0}), p, \tau_{0}) & \dots & f_{1}(x^{N}(\tau_{N}), u^{N}(\tau_{N}), p, \tau_{N}) \\ f_{2}(x^{N}(\tau_{0}), u^{N}(\tau_{0}), p, \tau_{0}) & \dots & f_{2}(x^{N}(\tau_{N}), u^{N}(\tau_{N}), p, \tau_{N}) \\ \vdots & \ddots & \vdots \\ f_{n_{x}}(x^{N}(\tau_{0}), u^{N}(\tau_{0}), p, \tau_{0}) & \dots & f_{n_{x}}(x^{N}(\tau_{N}), u^{N}(\tau_{N}), p, \tau_{N}) \end{bmatrix}$$

$$(1.33)$$

Now, define the differential defects at the collocation points as the $n_x \times (N+1)$ matrix:

$$\zeta^{N} = \dot{X}^{N} - F^{N} = X^{N} D^{T} - F^{N} \tag{1.34}$$

Define the matrix of path constraint function values evaluated at the LGL nodes:

$$H^{N} = \begin{bmatrix} h_{1}(x^{N}(\tau_{0}), u^{N}(\tau_{0}), p, \tau_{0}) & \dots & h_{1}(x^{N}(\tau_{N}), p, u^{N}(\tau_{N}), \tau_{N}) \\ h_{2}(x^{N}(\tau_{0}), u^{N}(\tau_{0}), p, \tau_{0}) & \dots & h_{2}(x^{N}(\tau_{N}), u^{N}(\tau_{N}), p, \tau_{N}) \\ \vdots & & \ddots & \vdots \\ h_{n_{h}}(x^{N}(\tau_{0}), u^{N}(\tau_{0}), p, \tau_{0}) & \dots & h_{n_{h}}(x^{N}(\tau_{N}), u^{N}(\tau_{N}), p, \tau_{N}) \end{bmatrix}$$

$$(1.35)$$

The objective function of \mathcal{P}_3 is approximated as follows:

$$J = \varphi[x(-1), x(1), p, t_0, t_f] + \frac{t_f - t_0}{2} \int_{-1}^{1} L[x(\tau), u(\tau), p, \tau] d\tau$$

$$\approx \varphi[x^N(-1), x^N(1), p, t_0, t_f] + \frac{t_f - t_0}{2} \sum_{k=0}^{N} L[x^N(\tau_k), u^N(\tau_k), p, \tau_k] w_k$$
(1.36)

where the weights w_k are defined in (1.5).

We are now ready to express problem \mathcal{P}_3 as a nonlinear programming problem, as follows.

Problem \mathcal{P}_4

$$\min_{y} F(y) \tag{1.37}$$

subject to:

$$G_l \le G(y) \le G_u$$

$$y_l \le y \le y_u \tag{1.38}$$

The decision vector y, which has dimension $n_y = (n_u(N+1) + n_x(N+1) + n_p + 2)$, is constructed as follows:

$$y = \begin{bmatrix} \operatorname{vec}(U^N) \\ \operatorname{vec}(X^N) \\ p \\ t_0 \\ t_f \end{bmatrix}$$
 (1.39)

The objective function is:

$$F(y) = \varphi[x^{N}(-1), x^{N}(1), p, t_{0}, t_{f}] + \frac{t_{f} - t_{0}}{2} \sum_{k=0}^{N} L[x^{N}(\tau_{k}), u^{N}(\tau_{k}), p, \tau_{k}] w_{k}$$
(1.40)

while the constraint function G(y), which is of dimension $n_g = n_x(N+1) + n_h(N+1) + n_e + 1$, is given by:

$$G(y) = \begin{bmatrix} \operatorname{vec}(\zeta^{N}) \\ \operatorname{vec}(H^{N}) \\ e[x^{N}(-1), u^{N}(-1), x^{N}(1), u^{N}(1), p, t_{0}, t_{f}] \\ t_{f} - t_{0} \end{bmatrix},$$
(1.41)

The constraint bounds are given by:

$$G_{l} = \begin{bmatrix} \mathbf{0}_{n_{x}(N+1)} \\ \operatorname{stack}(h_{L}, N+1) \\ e_{L} \\ (\underline{t}_{0} - \overline{t}_{f}) \end{bmatrix}, G_{u} \begin{bmatrix} \mathbf{0}_{n_{x}(N+1)} \\ \operatorname{stack}(h_{U}, N+1) \\ e_{U} \\ 0 \end{bmatrix}, \qquad (1.42)$$

and the bounds on the decision vector are given by:

$$y_{l} = \begin{bmatrix} \operatorname{stack}(u_{l}, N+1) \\ \operatorname{stack}(x_{L}, N+1) \\ p_{L} \\ \underline{t}_{0} \\ \underline{t}_{f} \end{bmatrix}, y_{u} \begin{bmatrix} \operatorname{stack}(u_{U}, N+1) \\ \operatorname{stack}(x_{U}, N+1) \\ p_{U} \\ \overline{t}_{0} \\ \overline{t}_{f} \end{bmatrix}, \qquad (1.43)$$

where vec(A) forms a nm-column vector by vertically stacking the columns of the $n \times m$ matrix A, and stack(x, n) creates a mn-column vector by stacking n copies of column m-vector x.

1.7.1 Costate estimates

Legendre approximation method

 \mathcal{PSOPT} implements the following approximation for the costates $\lambda(\tau) \in \Re^{n_x}, \tau \in [-1, 1]$ associated with \mathcal{P}_3 [18]:

$$\lambda(\tau) \approx \lambda^{N}(\tau) = \sum_{k=0}^{N} \lambda(\tau_{k})\phi_{k}(\tau), \tau \in [-1, 1]$$
 (1.44)

The costate values at the LGL nodes are given by:

$$\lambda(\tau_k) = \frac{\tilde{\lambda}_k}{w_k}, \ k = 0, \dots N$$
 (1.45)

where w_k are the weights given by (1.5), and $\tilde{\lambda}_k \in \Re^{n_x}$, k = 0, ..., N are the KKTs multiplier associated with the collocation constraints $\text{vec}(\zeta^N) = 0$. The KKT multipliers can normally be obtained from the NLP solver, which allows \mathcal{PSOPT} to return estimates of the costate trajectories at the LGL nodes.

It is known from the literature [18] that the costate estimates in the Legendre discretization method sometimes oscillate around the true values. To mitigate this, the estimates are smoothed by taking a weighted average for the estimates at k using the costate estimates at k-1, k and k+1 obtained from (1.44).

Chebyshev approximation method

 \mathcal{PSOPT} implements the following approximation for the costates $\lambda(\tau) \in \Re^{n_x}, \tau \in (-1,1)$ associated with \mathcal{P}_3 at the CGL nodes [32]:

$$\lambda(\tau_k) = \frac{\tilde{\lambda}_k}{\sqrt{1 - \tau_k^2 w_k}}, \ k = 0, \dots N - 1$$
 (1.46)

where w_k are the weights given by (1.21), and $\tilde{\lambda}_k \in \Re^{n_x}$, k = 0, ..., N are the KKTs multiplier associated with the collocation constraints $\text{vec}(\zeta^N) = 0$. Since (1.46) is singular for $\tau_0 = -1$ and $\tau_N = 1$, the estimates of the costates at $\tau = \pm 1$ are found using linear extrapolation. The costate estimates are also smoothed as described in 1.7.1

1.7.2 Discretizing a multiphase problem

It now becomes straightforward to describe the discretization used by \mathcal{PSOPT} in the case of \mathcal{P}_1 , a problem with multiple phases, to form a nonlinear program-

ming problem like \mathcal{P}_4 . The decision variables of the NLP associated with \mathcal{P}_1 are given by:

$$y = \begin{bmatrix} \operatorname{vec}(U^{N,(1)}) \\ \operatorname{vec}(X^{N,(1)}) \\ p^{(1)} \\ t_0^{(1)} \\ t_0^{(1)} \\ t_f^{(1)} \\ \vdots \\ \operatorname{vec}(U^{N,(N_p)}) \\ \operatorname{vec}(X^{N,(N_p)}) \\ \operatorname{vec}(X^{N,(N_p)}) \\ p^{(N_p)} \\ t_0^{(N_p)} \\ t_f^{(N_p)} \\ t_f^{(N_p)} \end{bmatrix}$$

$$(1.47)$$

where N_p is the number of phases in the problem, and the superindex in parenthesis indicates the phase to which the variables belong. The constraint function G(y) is given by:

$$G(y) = \begin{bmatrix} vec(\zeta^{N,(1)}) & vec(H^{N,(1)}) \\ e[x^{N,(1)}(-1), u^{N,(1)}(-1), x^{N,(1)}(1), u^{N,(1)}(1), p^{(1)}, t_0^{(1)}, t_f^{(1)}] \\ t_f^{(1)} - t_0^{(1)} & \vdots \\ vec(\zeta^{N,(N_p)}) & vec(H^{N,(N_p)}) \\ e[x^{N,(N_p)}(-1), u^{N,(N_p)}(-1), x^{N,(N_p)}(1), u^{N,(N_p)}(1), p^{(N_p)}, t_0^{(N_p)}, t_f^{(N_p)}] \\ t_f^{(N_p)} - t_0^{(N_p)} & \Psi \end{bmatrix},$$

$$(1.48)$$

where Ψ corresponds to the linkage constraints associated with the problem, evaluated at y.

Based on the problem information, it is straightforward (but not shown here) to form the bounds on the decision variables y_l , y_u and the bounds on the constraints function G_l , G_u to complete the definition of the NLP problem associated with \mathcal{P}_1 .

1.8 Parameter estimation problems

A parameter estimation problem arises when it is required to find values for parameters associated with a model of a system based on observations from the actual system. These are also called *inverse problems*. The approach used in the \mathcal{PSOPT} implementation uses the same techniques used for solving optimal control problems, with a special objective function used to measure the accuracy of the model for given parameter values.

1.8.1 Single phase case

For the sake of simplicity consider first a single phase problem defined over $t_0 \le t \le t_f$ with the dynamics given by a set of ODEs:

$$\dot{x} = f[x(t), u(t), p, t]$$

the path constraints

$$h_L \le h[x(t), u(t), p, t] \le h_U$$

the event constraints

$$e_L \le e[x(t_0), u(t_0), x(t_f), u(t_f), p, t_0, t_f] \le e_U$$

Consider the following model of the observations (or measurements) taken from the system:

$$y(\theta) = g[x(\theta), u(\theta), p, \theta]$$

where $g: \mathcal{R}^{n_x} \times \mathcal{R}^{n_u} \times \mathcal{R}^{n_p} \times \mathcal{R} \to \mathcal{R}^{n_o}$ is the observations function, and $y(\theta) \in \mathcal{R}^{n_o}$ is the estimated observation at sampling instant θ . Assume that $\{\tilde{y}\}_{k=1}^{n_s}$ is a sequence of n_s observations corresponding to the sampling instants $\{\theta_k\}_{k=1}^{n_s}$.

The objective is to choose the parameter vector $p \in \mathcal{R}^{n_p}$ to minimise the cost function:

$$J = \frac{1}{2} \sum_{k=1}^{n_s} \sum_{j=1}^{n_o} r_{j,k}^2$$

where the residual $r_{j,k} \in \mathcal{R}$ is given by:

$$r_{i,k} = w_{i,k}[g_i[x(\theta_k), u(\theta_k), p, \theta_k] - \tilde{y}_{i,k}]$$

where $w_{j,k} \in \mathcal{R}, j = 1, \dots, n_o, k = 1, \dots, n_s$ is a positive residual weight, g_j is the j-th element of the vector observations function g, and $\tilde{y}_{j,k}$ is the j-th element of the actual observation vector at time instant θ_k .

Note that in the parameter estimation case the times t_0 and t_f are assumed to be fixed. The sampling instants need not coincide with the collocation points, but they must obey the relationship:

$$t_0 \le \theta_k \le t_f, \ k = 1, \dots, n_s$$

1.8.2 Multi-phase case

In the case of a problem with N_p phases, let $t_0^{(i)} \leq t \leq t_f^{(i)}$ be the intervals for each phase, with the dynamics given by a set of ODEs:

$$\dot{x}^{(i)} = f^{(i)}[x(t)^{(i)}, u^{(i)}(t), p^{(i)}, t]$$

the path constraints

$$h_L^{(i)} \le h^{(i)}[x^{(i)}(t), u^{(i)}(t), p^{(i)}, t] \le h_U^{(i)}$$

the event constraints

$$e_L^{(i)} \le e^{(i)}[x^{(i)}(t_0), u^{(i)}(t_0), x^{(i)}(t_f), u^{(i)}(t_f), p^{(i)}, t_0^{(i)}, t_f^{(i)}] \le e_U^{(i)}$$

Consider the following model of the observations (or measurements) taken from the system for each phase:

$$y^{(i)}(\theta_k^{(i)}) = g^{(i)}[x^{(i)}(\theta_k^{(i)}), u^{(i)}(\theta_k^{(i)}), p^{(i)}, \theta_k^{(i)}]$$

where $g^{(i)}: \mathcal{R}^{n_x^{(i)}} \times \mathcal{R}^{n_u^{(i)}} \times \mathcal{R}^{n_p^{(i)}} \times \mathcal{R} \to \mathcal{R}^{n_o^{(i)}}$ is the observations function for each phase, and $y^{(i)}(\theta_k^{(i)}) \in \mathcal{R}^{n_o^{(i)}}$ is the estimated observation at sampling instant $\theta_k^{(i)}$. Assume that $\left\{\tilde{y}^{(i)}\right\}_{k=1}^{n_s^{(i)}}$ is a sequence of $n_s^{(i)}$ observations corresponding to the sampling instants $\left\{\theta_k^{(i)}\right\}_{k=1}^{n_s^{(i)}}$.

The objective is to choose the set of parameter vectors $p^{(i)} \in \mathcal{R}^{n_p^{(i)}}, i \in [1, N_p]$ to minimise the cost function:

$$J = \frac{1}{2} \sum_{i=1}^{N_p} \sum_{k=1}^{n_s^{(i)}} \sum_{j=1}^{n_o^{(i)}} \left[r_{j,k}^{(i)} \right]^2$$

where the residual $r_{j,k}^{(i)} \in \mathcal{R}$ is given by:

$$r_{i,k}^{(i)} = w_{i,k}^{(i)}[g_i^{(i)}[x(\theta_k^{(i)}), u^{(i)}(\theta_k^{(i)}), p^{(i)}, \theta_k^{(i)}] - \tilde{y}_i^{(i)}]$$

where $w_{j,k}^{(i)} \in \mathcal{R}$ is a positive residual weight, $g_j^{(i)}$ is the j-th element of the vector observations function $g^{(i)}$, and $\tilde{y}_j^{(i)}$ is the j-th element of the actual observation vector at time instant $\theta_k^{(i)}$

Note that in the parameter estimation case the times $t_0^{(i)}$ and $t_f^{(i)}$ are assumed to be fixed. The sampling instants need not coincide with the collocation points, but they must obey the relationship:

$$t_0^{(i)} \le \theta_k^{(i)} \le t_f^{(i)}, \ k = 1, \dots, n_s^{(i)}$$

1.8.3 Statistical measures on parameter estimates

 \mathcal{PSOPT} computes a residual matrix $[r_{j,k}^{(i)}]$ for each phase i and for the final value of the estimated parameters in all phases $\hat{p} \in \mathcal{R}^{n_p}$, where each element of the residual matrix is related to an individual measurement sample and observation within a phase. \mathcal{PSOPT} also computes the covariance matrix $C \in \mathcal{R}^{n_p \times n_p}$ of the parameter estimates using the method described in [27], which uses a QR decomposition of the Jacobian matrix of the equality and active inequality constraints, together with the Jacobian matrix of the residual vector function (a stack of the elements of the residual matrices for all phases) with respect to all decision variables. In addition \mathcal{PSOPT} computes 95% confidence intervals on the estimated parameters. The upper and lower limits of the confidence interval around the estimated value for parameter \hat{p}_i are computed from [30]:

$$\delta_i = \pm t_{N_s - n_p}^{1 - (\alpha/2)} \sqrt{C_{ii}} \tag{1.49}$$

where N_s is the total number of individual samples, n_p is the number of parameters, t is the inverse two tailed cumulative t-distribution with confidence level α , and $N - n_p$ degrees of freedom.

The residual matrix, the covariance matrix and the confidence intervals can be used to refine the parameter estimation problem. For instance, if the resulting confidence interval of one particular parameter is found to be small, the value of this parameter can be fixed by the user in a subsequent run, which may improve the estimates other parameters being estimated and reduces the possibility of having an overdetermined problem (i.e. a problem with too many parameters to be estimated). See [37] pages 210-211 for more details.

Notice, however, that the statistical analysis performed is based on a linearization of the model. As a result, the validity of the statistical analysis is dependent on the quality of the linearization and the curvature of the underlying functions being linearized, so care must be taken with the interpretation of results of the statistical analysis of the parameter estimates [37].

1.8.4 Remarks on parameter estimation

In contrast to continuous optimal control problems, the kind of parameter estimation problem considered involves the evaluation of the objective at a finite number of sampling points. Internally, the values of the state and controls are interpolated over the collocation points to find estimated values at the sampling points. The type of interpolation employed depends on the collocation method specified by the user.

- Note that the sampling instants do not have to be sorted in ascending or descending order. Because of this, it is possible to accommodate problems with non-simultaneous observations of different variables by stacking the measured data and sampling instants for the different variables.
- It is possible to use an alternative objective function where the residuals are weighted with the covariance of the measurements simply by multiplying the observations function and the measurements vectors by the square root of the covariance matrix, see [4], page 221 for more details.
- When defining parameter estimation problems, the user needs to ensure that the underlying nonlinear programming problem has sufficient degrees of freedom. This is particularly important as it is common for parameter estimation problems not to involve any control variables. The number of degrees of freedom is the difference between the number of decision variables and the total number of equality and active inequality constraints. For example, in the case of a single phase problem having n_x differential states, n_u control variables (or algebraic states), n_h equality path constraints, and n_e equality event constraints, the number of relevant constraints is given by:

$$n_c = n_x(N+1) + n_h(N+1) + n_e + 1$$

where N is the degree of the polynomial approximation (in the case of a pseudospectral discretization). The number of decision variables is given by:

$$n_y = n_u(N+1) + n_x(N+1) + n_p + 2$$

The difference is:

$$n_{v} - n_{c} = (n_{u} - n_{h})(N+1) + n_{p} + 1 - n_{e}$$

For the problem to be solvable it is important that $n_y - n_c \geq 0$, ideally $n_y - n_c \geq 1$. The total numbers of constraints and decision variables are always reported in the terminal window when a \mathcal{PSOPT} problem is run. It should be noted that the nonlinear programming solver (IPOPT) may modify the numbers by eliminating redundant constraints or decision variables. These modifications are also visible when a problem is run.

1.9 Alternative local discretizations

Direct collocation methods that use local information to approximate the functions associated with an optimal control problem are well established [3].

Sometimes, it may be convenient for users to compare the performance and solutions obtained by means of the pseudospectral methods implemented in \mathcal{PSOPT} , with local discretization methods. Also, if a given problem cannot be solved by means of a pseudospectral discretization, the user has the option to try the local discretizations implemented in \mathcal{PSOPT} . The main impact of using a local discretization method as opposed to a pseudospectral discretization method, is that the resulting Jacobian and Hessian matrices needed by the NLP solver are more sparse with local methods, which facilitates the NLP solution. This becomes more noticeable as the number of grid points increases. The disadvantage of using a local method is that the spectral accuracy in the discretization of the differential constraints offered by pseudospectral methods is lost. Moreover, the accuracy of Gauss type integration employed in pseudospectral methods is also lost if pseudospectral grids are not used.

Note also that local mesh refinement methods are well established. These methods concentrate more grid points in areas of greater activity in the function, which helps improve the local accuracy of the solution. The trapezoidal method has an accuracy of $\mathcal{O}(h^2)$, while the Hermite-Simpson method has an accuracy of $\mathcal{O}(h^4)$, where h is the local interval between grid points. Both the trapezoidal and Hermite-Simpson discretization methods are widely used in computational optimal control, and have solve many challenging problems [3]. When the user selects the trapezoidal or Hermite-Simpson discretizations, and if the initial grid points are not provided, the grid is started with equal spacing between grid points. In these two cases any integrals associated with the problem are computed using the trapezoidal and Simpson quadrature method, respectively.

Additionally, an option is provided to use a differentiation matrix based on the central difference method (which has an accuracy of $\mathcal{O}(h^2)$) in conjunction with pseudospectral grids. The central differences option uses either the LGL or the Chebyshev points and Gauss-type quadrature.

The local discretizations implemented in \mathcal{PSOPT} are described below. For simplicity, the phase index has been omitted and reference is made to single phase problems. However, the methods can also be used with multiphase problems.

1.9.1 Trapezoidal method

With the trapezoidal method [3], the defect constraints are computed as follows:

$$\zeta(\tau_k) = x(\tau_{k+1}) - x(\tau_k) - \frac{h_k}{2}(f_k + f_{k+1}), \tag{1.50}$$

where $\zeta(\tau_k) \in \Re^{n_x}$ is the vector of differential defect constraints at node τ_k , $k = 0, \ldots, N-1$, $h_k = \tau_{k+1} - \tau_k$, $f_k = f[(\tau_k), u(\tau_k), p, \tau_k]$, $f_{k+1} = f[(\tau_k), u(\tau_k), p, \tau_k]$

 $f[x(\tau_{k+1}), u(\tau_{k+1}), p, \tau_{k+1}]$. This gives rise to $n_x N$ differential defect constraints. In this case, the decision vector for single phase problems is given by equation (1.39), so that it is the same as the one used in the Legendre and Chebyshev methods.

1.9.2 Hermite-Simpson method

With the Hermite-Simpson method [3], the defect constraints are computed as follows:

$$\zeta(\tau_k) = x(\tau_{k+1}) - x(\tau_k) - \frac{h_k}{6} (f_k + 4\bar{f}_{k+1} + f_{k+1}), \tag{1.51}$$

where

$$\bar{f}_{k+1} = f[\bar{x}_{k+1}, \bar{u}_{k+1}, p, \tau_k + \frac{h_k}{2}]$$

$$\bar{x}_{k+1} = \frac{1}{2}(x(\tau_k) + x(\tau_{k+1})) + \frac{h_k}{8}(f_k - f_{k+1})$$

where $\zeta(\tau_k) \in \Re^{n_x}$ is the vector of differential defect constraints at node τ_k , $k = 0, \ldots, N-1$, $h_k = \tau_{k+1} - \tau_k$, $f_k = f[(\tau_k), u(\tau_k), p, \tau_k]$, $f_{k+1} = f[x(\tau_{k+1}), u(\tau_{k+1}), p, \tau_{k+1}]$, and $\bar{u}_{k+1} = \bar{u}(\tau_{k+1})$ is a vector of midpoint controls (which are also decision variables). This gives rise to $n_x N$ differential defect constraints. In this case, the decision vector for single phase problems is given by

$$y = \begin{bmatrix} \operatorname{vec}(U^{N}) \\ \operatorname{vec}(X^{N}) \\ p \\ \operatorname{vec}(\bar{U}^{N}) \\ t_{0} \\ t_{f} \end{bmatrix}$$
 (1.52)

with

$$\bar{U}^{N} = \begin{bmatrix}
\bar{u}_{1}(\tau_{1}) & \bar{u}_{1}(\tau_{2}) & \dots & \bar{u}_{1}(\tau_{N}) \\
\bar{u}_{2}(\tau_{1}) & \bar{u}_{2}(\tau_{2}) & \dots & \bar{u}_{2}(\tau_{N}) \\
\vdots & \vdots & \ddots & \vdots \\
\bar{u}_{n_{u}}(\tau_{1}) & \bar{u}_{n_{u}}(\tau_{2}) & \dots & \bar{u}_{n_{u}}(\tau_{N})
\end{bmatrix}$$
(1.53)

so that this decision vector is different from the one used in the Legendre and Chebyshev methods as it includes the midpoint controls.

1.9.3 Central difference method

This method computes the differential defect constraints using equation (1.34), but using a $(N+1) \times (N+1)$ differentiation matrix given by:

$$D_{0,0} = -1/h_0$$

$$D_{0,1} = 1/h_0$$

$$D_{i-1,i} = 1/(h_i + h_{i-1}), i = 2, ... N$$

$$D_{i-1,i-2} = -1/(h_i + h_{i-1}) i = 2, ... N$$

$$D_{N,N-1} = -1/h_{N-1}$$

$$D_{N,N} = 1/h_{N-1}$$

where $h_k = \tau_{k+1} - \tau_k$. The method uses forward differences at τ_0 , backward differences at τ_N , and central differences at τ_k , k = 1, ..., N-1. In this case, the decision vector for single phase problems is given by equation (1.39), so that it is the same as the one used in the Legendre and Chebyshev methods. Notice that this discretization has less accuracy at both ends of the interval. This is compensated by the use of pseudospectral grids, which concentrate more grid points at both ends of the interval.

1.9.4 Costate estimates with local discretizations

In the case of the trapezoidal and Hermite-Simpson discretizations, the costates at the discretization nodes are approximated according to the following equation:

$$\lambda(t_{k+\frac{1}{2}}) \approx \frac{\tilde{\lambda}_k}{2h_k}, \ k = 0, \dots N-1$$

where $\lambda(t_{k+\frac{1}{2}})$ is the costate estimate at the midpoint in the interval between t_k and t_k+ , $\tilde{\lambda}_k\in\Re^{n_x}$ is the vector of Lagrange multiplers obtained from the nonlinear programming solver corresponding to the differential defect constraints, and $h_k=t_{k+1}-t_k$.

In the case of the central-differences discretization, the costates are estimated as described in section 1.7.1.

1.10 External software libraries used by PSOPT

PSOPT relies on various of libraries to perform a number of tasks.

1.10.1 BLAS and CLAPACK (or LAPACK)

These are standard and widely used linear algebra packages which can be downloaded in source and binary form from http://www.netlib.org. Some current Linux distributions, such as Ubuntu, make it very easy to install both BLAS and LAPACK libraries using a package manager.

1.10.2 DMatrix library

This is a C++ matrix library developed by the author which is included with the distrubution. DMatrix and SparseMatrix objects are used internally in the implementation, while DMatrix objects are used as part of the interface. Documentation on the use of this library is included with the distribution, under the directory psopt-master/dmatrix/doc, although the essential use of the DMatrix objects is quite intuitive and can be learned from the examples given in this document. The DMatrix library makes direct use of LAPACK, SuiteSparse and LUSOL functions.

1.10.3 SuiteSparse

This is an open source sparse matrix computation library written in C by T. Davis [14], which can be downloaded from

http://faculty.cse.tamu.edu/davis/suitesparse.html

1.10.4 LUSOL

This is an open source sparse LU factorisation library written by M.A. Saunders and co-workers [21], which can be downloaded from

http://www.stanford.edu/group/SOL/software/lusol/lusol.zip

1.10.5 IPOPT

IPOPT is an open source C++ package for large-scale nonlinear optimization, which uses an interior point method [44]. IPOPT is the default nonlinear programming algorithm used by \mathcal{PSOPT} . IPOPT can be downloaded from

https://projects.coin-or.org/Ipopt

The current release of PSOPT uses IPOPT version 3.12.12.

Note that the installation script also installs the linear algebra library MUMPS and the matrix odering algorithm METIS, which are used by IPOPT.

1.10.6 ADOL-C

ADOL-C is a library for the automatic differentiation of C++ code. It allows to compute automatically the gradients and sparse Jacobians required by \mathcal{PSOPT} . At the heart of the ADOL-C library is the "adouble" data type, which can be mostly treated as a C++ "double". A copy of ADOL-C is included with the distribution of \mathcal{PSOPT} . Some current Linux distrubutions, such as Ubuntu, make it very easy to install the ADOL-C library and headers using a package manager. It can also be downloaded from:

https://projects.coin-or.org/ADOL-C

The current release of PSOPT uses ADOL-C version 2.6.3.

An important thing to keep in mind is that if an intermediate variable within a C++ function depends on one or more adouble variables, it should be declared as adouble. Conversely, if a C++ variable within a function does not depend on any adouble variables, it can be declared as the usual double type.

Note that the installation script also install the graph colouring library COLPACK, which is used by ADOL-C.

1.10.7 GNUplot (optional)

Gnuplot is a portable command-line driven interactive data and function plotting utility which runs on many computer platforms. The software is freely distributed. The source code can be downloaded from the following page:

http://www.gnuplot.info

Some current Linux distrubutions, such as Ubuntu, make it very easy to install GNUplot using a package manager.

1.11 Supported platform

The current release of \mathcal{PSOPT} has been successfully compiled under the following operating system and compiler:

• Ubuntu Linux version 18.04. It has been tested on Intel based PC's under the 64 bit variant of this operating system using the GCC compiler version 7.3.0, which is installed with the above release of Ubuntu.

It is possible that PSOPT will also compile and work on earlier versions of the above operating system and compiler, but time and resources do not allow for testing all possible combinations.

1.12 Repository and home page

The downloadable \mathcal{PSOPT} distribution is held in its GitHub page:

https://github.com/PSOPT/psopt

An web page is maintained to provide general information about \mathcal{PSOPT} : http://www.psopt.org.

1.13 Release numbering

PSOPT release numbering is sequential increasing by 1 with every release. The versio control software Git may provide additional tags to identify releases and builds.

1.14 Installing and compiling PSOPT

1.14.1 Ubuntu Linux 18.4

To install PSOPT on a Ubuntu 18.04 distribution, simply download the installation script install-ubuntu-18.04.sh from the GitHub page:

https://github.com/PSOPT/psopt

and execute it from a terminal window. This script will install and download all the required libraries and programmes from the Ubuntu repository, and also will download, compile and install other software libraries that are needed. You will need the root password to perform and complete the installation.

The installation process will create the following directory structure under the home folder.

psopt-master

-	$\operatorname{dmatrix}$	
-	_	src
-	-	examples
-	_	doc
-	_	include
-	PSOPT	
-	-	src
-	_	examples
-	_	doc

The installation process will generate a number of exacutables within the various directories under the psopt-master/PSOPT/examples directory. It will also run one of the examples as a test. You will see a plot appearing on the screen.

After successful compilation, \mathcal{PSOPT} is ready to be used. To see some of the examples running, move to the appropriate directory and run the executable file. For example, to run the "launch" example, do as follows:

```
$ cd PSOPT/examples/launch
$ ./launch
```

1.15 Limitations and known issues

1. The discretization techniques used by \mathcal{PSOPT} give approximate solutions for the state and control trajectories. The software is intended to be used for problems where the control variables are continuous (within a phase) and the state variables have continuous derivatives (within a phase). If within a phase the solution to the optimal control problem is of a different nature, the results may be incorrect or the optimization algorithm may fail to converge. Furthermore, \mathcal{PSOPT} may not be

- suitable for solving problems involving differential-algebraic equations with index greater than one. Some of these issues can be avoided by reformulating the problem to have several phases.
- 2. The solution obtained by \mathcal{PSOPT} corresponds to a local minimum of the discretized optimization problem. If the problem is suspected to have several local minima, then it may be worth trying various initial guesses.
- 3. The automatic scaling procedures work well for all the examples provided. However, note that the scaling of variables depends on the user provided bounds. If these bounds are not adequate for the problem, then the resulting scaling may be poor and this may lead to incorrect results or convergence problems. In some cases, users may need to provide the scaling factors manually to obtain satisfactory results.
- 4. The automatic mesh refinement procedures require an initial guess for the number of nodes in the global case (the number and/or initial distribution of nodes in the local case). If this initial guess is not adequate (e.g. the grid is too coarse or to dense), the mesh refinement procedure may fail to converge. In some cases, the user may need to manually tune some of the parameters of the mesh refinement procedure to achieve satisfactory results.
- 5. The efficiency with which the optimal control problem is solved depends in a good deal on the correct formulation of the problem. Unsuitable formulations may lead to trouble in finding a solution. Moreover, if the constraints are such that the problem is infeasible or if for any other reason the solution does not exist, then the nonlinear programming algorithm will fail.
- 6. The user supplied functions which define the cost function, DAE's, event and linkage constraints, are all assumed to be continuous and to have continuous first and second derivatives. Non-differentiable functions may cause covergence problems to the optimization algorithm. Moreover, it is known that discontinuities in the second derivatives may also cause convergence problems.
- 7. Only single phase problems are supported if the dynamics involve delays in the states or controls.
- Note that the constraints associated with the problem are only enforced at the discretization nodes, not in the interval between the nodes.
- 9. When the problem requires a large number of nodes (say over 200) the nonlinear programming algorithm may have problems to converge

if global collocation is being used. This may be due to numerical difficulties within the nonlinear programming solver as the Jacobian (and Hessian) matrices may not be sufficiently sparse. This occurs because the pseudospectral differentiation matrices are dense. When faced with this problem the user may wish to try the local collocation options available within \mathcal{PSOPT} , or to split the problem into multiple segments to increase the sparsity of the derivatives. Note that the sparsity of the Jacobian and Hessian matrices is problem dependent.

- 10. The co-state approximations resulting from the Legendre pseudospectral method are not as accurate as those obtained by means of the Gauss pseudospectral method [2]. Moreover, the co-state approximations obtained by \mathcal{PSOPT} using the Chebyshev pseudospectral methods are rather innacurate close to the edges of the time interval within each phase. Also the co-state approximation used in the the case of local discretizations (trapezoidal, Hermite-Simpson) converges at a lower rate (is less accurate) than the states or the controls.
- 11. Sometimes there are crashes when computing sparse derivatives with ADOL-C if the number of NLP variables is very large. This can be avoided by switching to numerical differentiation.

Chapter 2

Defining optimal control and estimation problems for PSOPT

Defining an optimal control or parameter estimation problem involves specifying all the necessary values and functions that are needed to solve the problem. With \mathcal{PSOPT} , this is done by implementing C++ functions (e.g. the cost function), and assigning values to data structures which are described below. Once a \mathcal{PSOPT} has obtained a solution, the relevant variables can be obtained by interrogating a data structure.

2.1 Interface data structures

The role of each structure used in the \mathcal{PSOPT} interface is summarised below.

- Problem data structure: This structure is used to specify problem information, including the number of phases and pointers to the relevant functions, as well as phase related information such as number of states, controls, parameters, number of grid points, bounds on variables (e.g. state bounds), and functions (e.g. path function bounds).
- Algorithm data structure: This is used to control the solution algorithm and to pass parameters to the NLP solver.
- Solution data structure: This is used to store the resulting variables of a \mathcal{PSOPT} run.

2.2 Required functions

Table 2.1 lists and describes the parameters used by the interface functions.

Parameter	\mathbf{Type}	\mathbf{Role}	Description
controls	adouble*	input	Array of intantaneous controls
derivatives	adouble*	output	Array of intantaneous state derivatives
е	adouble*	output	Array of event constraints
final_states	adouble*	input	Array of final states within a phase
initial_states	adouble*	input	Array of initial states within a phase
iphase	int	input	Phase index (starting from 1)
linkages	adouble*	output	Array of linkage constraints
parameters	adouble*	input	Array of static parameters within a phase
states	adouble*	input	Array of intantaneous states within a phase
time	adouble	input	Instant of time within a phase
t0	adouble	input	Initial phase time
tf	adouble	input	final phase time
xad	adouble*	input	vector of scaled decision variables
workspace	Workspace*	input	Pointer to workspace structure

Table 2.1: Description of parameters used by the \mathcal{PSOPT} interface functions

2.2.1 endpoint_cost function

The purpose of this function is to specify the terminal costs $\phi_i[\cdot]$, $i = 1, \ldots, N$. The function prototype is as follows:

The function should return the value of the end point cost, depending on the value of phase index iphase, which takes on values between 1 and problem.nphases.

Example of writing the endpoint cost function for a single phase problem with the following endpoint cost:

$$\varphi(x(t_f)) = x_1(t_f)^2 + x_2(t_f)^2 \tag{2.1}$$

```
Workspace* workspace)
{
   adouble x1f = final_states[ CINDEX(1) ];
   adouble x2f = final_states[ CINDEX(2) ];

   return ( x1f*x1f + x2f*x2f);
}
```

2.2.2 integrand_cost function

The purpose of this function is to specify the integrand costs $L_i[\cdot]$ for each phase as a function of the states, controls, static parameters and time. The function prototype is as follows:

The function should return the value of the integrand cost, depending on the phase index iphase, which takes on values between 1 and problem.nphases.

```
Example of writing the integrand cost for a single phase problem with
L given by:
              L(x(t), u(t), t) = x_1(t)^2 + x_2(t)^2 + 0.01u(t)^2
                                                                 (2.2)
adouble integrand_cost(adouble* states,
                       adouble* controls,
                       adouble* parameters,
                       adouble& time,
                       adouble* xad,
                       int iphase,
                       Workspace* workspace)
{
    adouble x1 = states[
                             CINDEX(1) ];
    adouble x2 = states[
                             CINDEX(2) ];
    adouble u = controls[ CINDEX(1) ];
```

```
return ( x1*x1 + x2*x2 + 0.01*u*u );
}
```

If the problem does not involve any cost integrand, the user may simply not register any cost_integrand function, or register it as follows: problem.cost_integrand=NULL.

2.2.3 dae function

This function is used to speficy the time derivatives of the states $\dot{x}^{(i)} = f_i[\cdot]$ for each phase as a function of the states themselves, controls, static parameters, and time, as well as the algebraic functions related to the path constraints. Its prototype is as follows:

This is an example of writing the dae function for a single phase problem with the following state equations and path constraints:

$$\dot{x}_1 = x_2
\dot{x}_2 = -3\exp(x_1) - 4x_2 + u
0 \le x_1^2 + x_2^2 \le 1$$
(2.3)

Note that the bounds are specified separately.

```
Workspace* workspace)
{
   adouble x1 = states[    CINDEX(1) ];
   adouble x2 = states[    CINDEX(2) ];
   adouble u = controls[ CINDEX(1) ];

   derivatives[ CINDEX(1) ] = x2;
   derivatives[ CINDEX(2) ] = -3*exp(x1)-4*x2+u;
   path[    CINDEX(1) ] = x1*x1 + x2*x2
}
```

2.2.4 events function

This function is used to speficy the values of the event constraint functions $e_i[\cdot]$ for each phase. Its prototype is as follows:

The following is an example of writing the events function for a single phase problem with the event constraints:

$$1 = e_1(t_0) = x_1(t_0)$$

$$2 = e_2(t_0) = x_2(t_0)$$

$$-0.1 \le e_3(t_0) = x_1(t_f)x_2(t_f) \le 0.1$$
(2.4)

Note that the bounds are specified separately.

```
adouble x2i = initial_states[ CINDEX(2)];
adouble x1f = final_states[ CINDEX(1)];
adouble x2f = final_states[ CINDEX(2)];

e[ CINDEX(1)] = x1i;
e[ CINDEX(2)] = x2i;
e[ CINDEX(3)] = x1f*x2f;
}
```

2.2.5 linkages function

This function is used to speficy the values of the phase linkage constraint functions $\Psi[\cdot]$. Its prototype is as follows:

The following is an example of writing the linkages function for a two phase problem with two states in each phase and with the linkage constraints:

$$0 = \Psi_1 = x_1^{(0)}(t_f^{(1)}) - x_1^{(2)}(t_i^{(2)})$$

$$0 = \Psi_2 = x_2^{(1)}(t_f^{(1)}) - x_2^{(2)}(t_i^{(2)})$$

$$0 = \Psi_3 = t_f^{(1)} - t_i^{(2)}$$
(2.5)

Note that the bounds are specified separately. These type of state and time continuity constraint can be entered automatically by using the auto_link function as shown below.

```
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
{
   int index = 0;
   // Link phases 1 and 2
   auto_link( linkages, &index, xad, 1, 2 );
}
```

It is of course also possible to implement more general linkage constraints, as illustrated through the following example.

Consider a two phase problem with two states in each phase and with the nonlinear linkage constraints:

```
0 = \Psi_1 = x_1^{(1)}(t_f^{(1)}) - \sin[x_1^{(2)}(t_i^{(2)})]
                     0 = \Psi_2 = x_2^{(1)}(t_f^{(1)}) - \cos[x_2^{(2)}(t_i^{(2)})]
                                                                           (2.6)
                     0 = \Psi_3 = t_f^{(1)} - t_i^{(2)}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
     adouble xf_p0[ 2 ];
     adouble xi_p1[ 2 ];
     adouble tf_p0;
     adouble ti_p1;
     get_final_states( xf_p0, xad, 1);
     get_initial_states( xf_p1, xad, 2 );
     tf_p0 = get_final_time( xad, 1);
     ti_p1 = get_initial_time( xad, 2);
     linkages[CINDEX(1)] = xf_p0[CINDEX(1)] - sin(xi_p1[CINDEX(1)]);
     linkages[CINDEX(2)] = xf_p0[CINDEX(2)] - cos(xi_p1[CINDEX(2)]);
     linkages[CINDEX(3)]=tf_p0 - ti_p1;
}
```

2.2.6 Main function

Declaration of data structures

The main() function is used to declare and initialise the problem, solution, and algorithm data structures, to call the \mathcal{PSOPT} algorithm, and to post-process the results. To declare the data structures the user may wish to use the following commands:

```
Alg algorithm;
Sol solution;
Prob problem;
```

Problem level information

The user should then define the problem name as follows:

```
problem.name = "My problem";
```

The number of phases and the number of linkage constraints should be declared afterwards. For example, for a single phase problem:

```
problem.nphases=1;
problem.nlinkages=0;
```

This declaration should be followed by the following function call, which initialises problem level structures.

```
psopt_level1_setup(problem);
```

Phase level information

After this, the user needs to specify phase level parameters using the following syntax:

The number of nodes in the grid can be speficied as a single value (e.g. 30), or a character string with the node sequence to be tried (if manual mesh refinement is being used): "[30, 50, 60]".

Once the phase level dimensions have been specified it is necessary to call the following function:

```
psopt_level2_setup(problem, algorithm);
```

Phase bounds information

The syntax to enter state bounds is as follows:

```
problem.phases(iphase).bounds.lower.states(j) = REAL;
problem.phases(iphase).bounds.upper.states(j) = REAL;
```

where iphase is a phase index between 1 and problem.nphases, and j is an index between 1 and problem.phases(iphase).nstates.

The syntax to enter control bounds is as follows:

```
problem.phases(iphase).bounds.lower.controls(j) = REAL;
problem.phases(iphase).bounds.upper.controls(j) = REAL;
```

where j is an index between 1 and problem.phases(iphase).ncontrols.

The syntax to enter event bounds is as follows:

```
problem.phases(iphase).bounds.lower.events(j) = REAL;
problem.phases(iphase).bounds.upper.events(j) = REAL;
```

where j is an index between 1 and problem.phases(iphase).nevents.

The bounds on the start time for each phase are entered using the following syntax:

```
problem.phases(iphase).bounds.lower.StartTime = REAL;
problem.phases(iphase).bounds.upper.StartTime = REAL;
```

The bounds on the end time for each phase are entered using the following syntax:

```
problem.phases(iphase).bounds.lower.EndTime = REAL;
problem.phases(iphase).bounds.upper.EndTime = REAL;
```

Linkage bounds information

The syntax to enter linkage bounds values is as follows:

```
problem.bounds.lower.linkage(j) = REAL;
problem.bounds.upper.linkage(j) = REAL;
```

j is an index between 1 and problem.nlinkages. The default value of the linkage bounds is zero.

Specifying the initial guess for each phase

The user may wish to specify an initial guess for the solution, rather than allowing \mathcal{PSOPT} to determine the initial guess automatically. The user may specify any of the following for each phase: the control vector history, the state vector history and the time vector corresponding to the control and state histories, as well as a guess for the static parameter vector.

To specify the initial guesses for each phase, the user needs to create DMatrix objects to hold the initial guesses, and then assign the addresses of these objects to relevant pointers within the Guess structure.

The syntax to specify the initial guess in a particular phase is as follows:

where uGuess, xGuess, pGuess and tGuess are DMatrix objects that contain the relevant guesses. Users may find it useful to employ the functions zeros, ones, and linspace to specify the initial guesses. For example, the following code creates an object to store an initial control guess with 20 grid points, and assigns zeros to it.

```
DMatrix uGuess = zeros(1, 20);
```

The following code defines a linear history in the interval [10, 15] for the first state, and a constant history for the second state, for a system with two states assuming 20 grid points:

```
DMatrix xGuess(2,20);
xGuess(1,colon()) = linspace( 10, 15, 20);
xGuess(2,colon()) = 10*ones( 1, 20);
```

The following code defines a time vector with equally spaced values in the interval [0, 10] assuming 20 grid points:

```
DMatrix tGuess = linspace( 0, 10, 20);
```

Scaling information

The user may wish to supply the scaling factors rather than allowing \mathcal{PSOPT} to compute them automatically.

Scaling factors for controls, states, event constraints, derivatives, path constraints, and time for each phase can be entered as follows:

The scaling factor for the objective function is entered as follows:

```
problem.scale.objective = REAL;
```

Scaling factors for the linkage constraints are entered as follows:

```
problem.scale.linkage(j) = REAL;
```

Passing user data to the interface functions

It is possible to pass user data to the different interface functions by using a void pointer that is a member of the problem data structure. This is good programming practice, as it helps avoid the use of global or static variables.

```
For example, the user could define a data structure to encapsulate some
key data values, such as:
typedef struct{
double c1;
double c2;
double c3;
} Mydata;
   In the main function, an instance of this data structure can be allocated:
Mydata* md = (Mydata*) malloc(sizeof(Mydata));
and its elements given values:
md -> c1 = 1.0;
md \rightarrow c2 = 100.0;
md -> c3 = 1000.0;
   In the main() function, after the problem data structure has been de-
clared, then the pointer to the instance of the Mydata data structure can be
stored in the user_data member of the problem data structure, as follows:
problem.user_data = (void*) md;
   Finally, the user can access this data from within the interface functions.
For example, to access the data from within the integrand_cost function,
the following can be done:
adouble integrand_cost(adouble* states,
adouble* controls,
adouble* parameters,
adouble& time,
adouble* xad,
int iphase,
Workspace* workspace)
                          CINDEX(1) ];
adouble x1 = states[
```

```
adouble x2 = states[ CINDEX(2)];
adouble u = controls[ CINDEX(1)];

Mydata* md = (Mydata*) workspace->problem->user_data;

double c1 = md->c1;
double c2 = md->c2;
double c3 = md->c3;

return ( c1*x1*x1 + c2*x2*x2 + c3*u*u );
}
```

Specifying algorithm options

Algorithm options and parameters can be specified as follows:

```
algorithm.nlp_method
                                                = STRING;
algorithm.scaling
                                                = STRING;
algorithm.defect_scaling
                                                = STRING;
algorithm.derivatives
                                                = STRING;
algorithm.collocation_method
                                                = STRING;
algorithm.nlp_iter_max
                                                = INTEGER;
algorithm.nlp_tolerance
                                                = REAL;
algorithm.print_level
                                                = INTEGER;
algorithm.jac_sparsity_ratio
                                                = REAL;
algorithm.hess_sparsity_ratio
                                                = REAL;
algorithm.hessian
                                                = STRING;
algorithm.mesh_refinement
                                                = STRING;
algorithm.ode_tolerance
                                                = REAL;
algorithm.mr_max_iterations
                                                = INTEGER;
algorithm.mr_min_extrapolation_points
                                                = INTEGER;
algorithm.mr_initial_increment
                                                = INTEGER;
algorithm.mr_kappa
                                                = REAL;
algorithm.mr_M1
                                                = INTEGER;
algorithm.switch_order
                                                = INTEGER;
algorithm.mr_max_increment_factor
                                                = REAL;
```

Note that:

- algorithm.nlp_method takes the (only) option "IPOPT" (default).
- algorithm.scaling takes the options "automatic" (default) or "user".

- algorithm.defect_scaling takes the options "state-based" (default) or "jacobian-based".
- algorithm.derivatives takes the options "automatic" (default) or "numerical".
- algorithm.collocation_method takes the options "Legendre" (default), "Chebyshev", "trapezoidal", or "Hermite-Simpson".
- algorithm.diff_matrix takes the options "standard" (default), "reduced-roundoff", or "central-differences".
- algorithm.print_level takes the values 1 (default), which causes \mathcal{PSOPT} and the NLP solver to print information on the screen, or 0 to supress all output.
- algorithm.nlp_tolerance is a real positive number that is used as a tolerance to check convergence of the NLP solver (default 10^{-6}).
- algorithm.jac_sparsity_ratio is a real number in the interval (0,1] which indicates the maximum Jacobian density, which is ratio of nonzero elements to the total number of elements of the NLP constraint Jacobian matrix (default 0.5).
- algorithm.hess_sparsity_ratio is a real number in the interval (0,1] which indicates the maximum Hessian density, ratio of nonzero elements to the total number of elements of the NLP Hessian matrix (default 0.2).
- algorithm.hessian takes the options "reduced-memory" or "exact". The "exact" option is only used together with the IPOPT NLP solver.
- algorithm.nsteps_error_integration is an integer number that gives the number of integration steps to be taken within each interval when calculating the relative ODE error. The default value is 10.
- algorithm.mesh_refinement takes the values "manual" (default) or "automatic".
- algorithm.ode_tolerance is a small real value that is used as one of the stopping criteria for mesh refinement. If the maximum relative ODE error falls below this value, the mesh refinement iterations are terminated. The default value is 10⁻³.
- algorithm.mr_max_iterations is a positive integer with the maximum number of mesh refinement iterations (default 7).

- algorithm.mr_min_extrapolation_points is the minimum number points to use to calculate the regression that is employed to extrapolate the number of nodes. This is only used if a global collocation method is employed (default 2).
- algorithm.mr_initial_increment is a positive integer with the initial increment in the number of nodes. This is only used if a global collocation method is employed (default 10).
- algorithm.mr_kappa is a positive real number used by the local mesh refinement algorithm (default 0.1).
- algorithm.mr_M1 is a positive integer used by the local mesh refinement algorithm (default 5).
- algorithm.switch_order is a positive integer indicating the local mesh refinement iteration after which the order is switched from 2 (trapezoidal) to 4 (Hermite-Simpson). If the entered value is zero, then the order is not switched and the collocation method specified through the option algorithm.collocation_method is used in all mesh refinement iterations. This option only applies if a local collocation method is specified (default 2).
- algorithm.mr_max_increment_factor is a positive real number in the range (0,1] used by the mesh refinement algorithms (default 0.4).

Calling PSOPT

Once everything is ready, then the psopt algorithm can be called as follows:

```
psopt(problem, solution, algorithm);
```

Error checking

 \mathcal{PSOPT} will set solution.error_flag to "true" if an run time error is caught. This flag can be checked for errors so that appropriate action can be taken once \mathcal{PSOPT} returns. A diagostic message will be printed on the screen. The diagnostic message can also be recovered from solution.error_message. Moreover, the error message is printed to file error_message.txt. \mathcal{PSOPT} checks automatically many of the user supplied parameters and will return an error if an inconsistency is found. The following example shows a call to \mathcal{PSOPT} , followed by error checking (in this case, the program exits with code 1 if the error flag is true).

```
psopt(problem, solution, algorithm);
if (solution.error_flag)
{
```

```
exit(1);
}
```

Postprocessing the results

The psopt() function returns the results of the optimisation within the solution data structure. The results may then be post-processed.

```
For example, to save the time, control and state vectors of the first phase, the user may use the following commands:

DMatrix x = solution.get_states_in_phase(1);

DMatrix u = solution.get_controls_in_phase(1);

DMatrix t = solution.get_time_in_phase(1);

x.Save("x.dat");

u.Save("u.dat");

t.Save("t.dat");
```

Plotting with the GNUplot interface

If the software GNUplot is available in the system where \mathcal{PSOPT} is being run, then the user may employ the plot(), multiplot(), surf(), plot3() and polar() functions, which constitute a simple interface to GNUplot implemented within the \mathcal{PSOPT} library.

The prototype of the plot() function is as follows:

where x is a column or row vector with n elements and y is a matrix with one either row or column dimension equal to n. xlabel is a string with the label for the x-axis, ylabel is a string with the label for y-axis, legend is a string with the legends for each curve that is plotted, separated by commas. terminal is a string with the GNUplot terminal to be used (see Table 2.2), and output is a string with the filename to be used for the output, if any.

The function is overloaded, such that the user may plot together curves generated from different x, y pairs, up to three pairs. The additional prototypes are as follows:

```
void plot(DMatrix& x1, DMatrix& y1,
          DMatrix& x2, DMatrix& y2,
          const string& title,
          char* xlabel,
          char* ylabel,
          char* legend=NULL,
          char* terminal=NULL,
          char* output=NULL);
void plot(DMatrix& x1, DMatrix& y1,
          DMatrix& x2, DMatrix& y2,
          DMatrix& x3, DMatrix& y3,
          const string& title,
          char* xlabel,
          char* ylabel,
          char* legend=NULL,
          char* terminal=NULL,
          char* output=NULL);
```

For example, if the user wishes to display a plot of the control trajectories of a system with two control variables which have been stored in DMatrix object "u", and assuming that the corresponding time vector has been stored in DMatrix object "t", then an example of the syntax to call the plot() function is:

```
plot(t,u,"Control variable","time (s)", "u", "u1 u2");
```

It is also possible to save plots to graphical files supported by GNUplot. For example, to save the above plot to an encapsulated postscript file (instead of displaying it), the command is as follows:

The function spplot() allows to plot one or more curves together with one or more sets of isolated points (without joining the dots). This can be useful, for example, to compare how an estimated continuous variable compares with experimental data points. The prototype is as follows:

where x1 is a column or row vector with n_1 elements and y1 is a matrix with one either row or column dimension equal to n_1 . The pair (x1, y1) is used to generate curve(s). x2 is a column or row vector with n_2 elements and y2 is a matrix with one either row or column dimension equal to n_2 . The pair (x2, y2) is used to plot data points.

For example, if the user wishes to display a curve on the basis of the pair (t, y1) and on the same plot compare with experimental points stored in the pair (te, ye), then an example of the syntax to call the spplot() function is:

```
\verb"plot(t,y,te, ye, "Data fit for y","time (s)", "u", "y ye");
```

The multiplot() function allows the user to plot on a single window an array of sub-plots, having one curve per subplot. The function prototype is as follows:

where x is a column or row vector with n elements and y is a matrix with one either row or column dimension equal to n, xlabel should be a string with the common label for the x-axis of all subplots, ylabel should be a string with the labels for all y-axes of all subplots, separated by spaces, nrows is the number of rows of the array of subplots, ncols is the number of columns of the array of subplots. If nrows and ncols are not provided, then the array

of subplots has a single column. Note that the product nrows*ncols should be equal to n, which is the number of curves to be plotted.

For example, if the user wishes to display an array of subplots of the state trajectories of a system with four state variables which have been stored in DMatrix object "y", and assuming that the corresponding time vector has been stored in DMatrix object "t", then an example of the syntax to call the multiplot() function is:

In the above case, a 4×1 array of sub-plots is produced. If a 2×2 array of sub-plots is required, then the following command can be used:

The function **surf()** plots the colored parametric surface defined by three matrix arguments. The prototype of the **surf()** function is as follows:

Here view is a character string with two constants <rot_x>,<rot_y> (e.g. "50,60"), where rot_x is an angle in the interval [0,180] degrees, and rot_y is an angle in the interval [0,360] degrees. This is used to set the viewing angle of the surface plot.

For example, if the user wishes to display a surface plot of a $N \times M$ matrix Z with respect to the $1 \times N$ vector X and the $1 \times M$ vector Y, stored, respectively, in DMatrix objects "z", "x" and "y", then an example of the syntax to call the surf() function is:

```
surf(x, y, z, "Title", "x-label", "y-label", "z-label");
```

The function plot3() plots a 3D parametric curve defined by three vector arguments. The prototype of the plot3() function is as follows:

Here view is a character string with two constants <rot_x>,<rot_y> (e.g. "50,60"), where rot_x is an angle in the interval [0,180] degrees, and rot_y is an angle in the interval [0,360] degrees. This is used to set the viewing angle of the 3D plot.

For example, if the user wishes to display a 3D parametric curve of a $1 \times N$ vector Z with respect to the $1 \times N$ vector X and the $1 \times M$ vector Y, stored, respectively, in DMatrix objects "z", "x" and "y", then an example of the syntax to call the plot3() function is:

```
\verb"plot3"(x, y, z, "Title", "x-label", "y-label", "z-label");
```

The function polar() plots a polar curve defined by two vector arguments. The prototype of the polar() function is as follows:

For example, if the user wishes to display a polar plot using a of a $1 \times N$ vector θ (the angle values in radians), and a $1 \times N$ vector r (the corresponding values of the radius), stored, respectively, in DMatrix objects "theta" and "r", then an example of the syntax to call the polar() function is:

```
polar(theta, r, "Title");
```

Terminal	Description
postscript eps	Encapsulated postscript
pdf	Adobe portable document format (pdf)
$_{ m Jpeg}$	jpg graphical format
Png	png graphical format
latex	LaTeX graphical code

Table 2.2: Some of the available GNUplot output graphical formats

The polar() function is overloaded so that the user may plot together up to three different polar curves. The additional prototypes are given below. For two polar curves:

```
void polar(DMatrix& theta,
           DMatrix& r,
           DMatrix& theta2,
           DMatrix& r2,
           const string& title,
           char* legend=NULL,
           char* terminal=NULL,
           char* output=NULL);
For three polar curves.
void polar(DMatrix& theta,
           DMatrix& r,
           DMatrix& theta2,
           DMatrix& r2,
           DMatrix& theta3,
           DMatrix& r3,
           const string& title,
           char* legend=NULL,
           char* terminal=NULL,
           char* output=NULL);
```

Some common GNUplot terminals (graphical formats) are given in Table 2.2. See the GNUplot documentation for further details on the keywords needed to specify different graphical formats.

http://www.gnuplot.info/documentation.html

2.3 Specifying a parameter estimation problem

To use the parameter estimation facilities implemented in \mathcal{PSOPT} for problems where the observation function is defined, and where there is a set of observed data at given sampling points (see section 1.8). The user needs to specify, for each phase, the number of observed variables and the number of sampling points:

where nobserved is the number of simultaneous measurements taking place at each sampling node, and nsamples is the total number of sampling nodes. The above parameters should be entered before calling the function psopt_level2_setup(problem, algorithm). After this, additional information may be entered:

where observation_nodes is a $1 \times$ nsamples matrix, observations is a nobserved \times nsamples matrix, residual_weights is a $1 \times$ nobserved \setminus times nsamples matrix. The residual_weights matrix is by default full of ones.

If parameter estimation data for a particular phase is saved in a text file with the column format specified below, then an auxiliary function, which is described below, can be used to load the data:

```
< Time > < Obs. # 1> < Weight # 1> ... < Obs. # n> < Weight # n>
```

where each column is separated by either tabs or spaces, the first column contains the time stamps of the samples, the second column contains the observations of the first variable, the third column contains the weights for each observation of the first variable, and so on. It is then possible to load observation nodes, observations, and residual weights and assign them to the appropriate fields of the problem structure by using the function load_parameter_estimation_data, whose prototype is given below.

Note that the user should not register the problem.end_point_cost or the problem.integrand_cost functions, but the user needs to register problem.observation_function. The prototype of this function is as follows:

where on output the function should return the array of observed variables corresponding to sampling index k at sampling instant time_k. The rest of the interface is the same as for general optimal control problems.

2.4 Automatic scaling

If the user specifies the option algorithm.scaling as "automatic", then \mathcal{PSOPT} will calculate scaling factors as follows.

- 1. Scaling factors for controls, states, static parameters, and time, are computed based on the user supplied bounds for these variables. For finite bounds, the variables are scaled such that their original value multipled by the scaling factor results in a number within the range [-1,1]. If any of the bounds is greater or equal than the constant inf, then the variable is scaled to lie within the intervals, [-inf, 1], [1, inf] or [-inf, inf]. The constant inf is defined in the include file psopt.h as 1 × 10¹⁹.
- 2. Scaling factors for all constraints (except for the differential defect constraints) are computed as follows. The scaling factor for the i-th constraint is the reciprocal of the norm of the i-th row of the Jacobian of the constraints (Betts, 2001). If the computed norm is zero, then the scaling factor is set to 1.
- 3. The scaling factors of each differential defect constraint is by default equal to the scaling factor of the corresponding state by default (Betts, 2001). However, if algorithm.defect_scaling is set to "jacobian-based", then the scaling factors of the differential defect constraints are computed as is done for the other constraints.
- 4. The scaling factor for the objective function is the reciprocal of the norm of the gradient of the objective function evaluated at the initial guess. If the norm of the objective function at the initial guess is zero, then the scaling factor of the objective function is set to one.

2.5 Differentiation

Users are encouraged to use, whenever possible, the automatic differentiation facilities provided by the ADOL-C library. The use of automatic derivatives is the default behaviour, but it may be specified explicitly by setting the derivatives option to "automatic". \mathcal{PSOPT} uses the ADOL-C drivers for sparsity determination, Jacobian and gradient evaluation. Automatic derivatives are more accurate than numerical derivatives as they are free of truncation errors. Moreover, \mathcal{PSOPT} works faster when using automatic derivatives.

There may be cases, however, where it is preferrable or necessary to use numerical derivatives. If the user specifies the option algorithm.derivatives as "numerical", then \mathcal{PSOPT} will calculate the derivatives required by the nonlinear programming algorithm as follows.

1. If IPOPT is being used for optimization, then the Jacobian of the constraints is computed by using sparse finite differences, such that groups of variables are perturbed simultaneously [13]. It is assumed that the Jacobian of the constraint function G(y) is divided into constant and variable terms as follows:

$$\frac{\partial G(y)}{\partial y} = A + \frac{\partial g(y)}{\partial y} \tag{2.7}$$

where matrices A and $\partial g(y)/\partial y$ do not have non-zero elements with the same indices. The constant part A of the constraint Jacobian is estimated first, and only the variable part of the jacobian $\partial g(y)/\partial y$ is estimated by sparse finite differences.

The gradient of the objective function is computed by perturbing one variable at a time. Normally the central difference formula is used, but if the perturbed variable is at (or very close to) one of its bounds, then the forward or backward difference formulas are employed.

2.6 Generation of initial guesses

If no guesses are supplied by the user, then \mathcal{PSOPT} computes the initial guess for the unspecified decision variables as follows. Each variable is assumed to be constant and equal to the mean value of its bounds, provided none of the bounds is defined as inf or -inf. If only one of the bounds is inf or -inf, then the variable is initialized with the value of the other bound. If the upper and lower bounds are inf and -inf, respectively, then the variable is initialized at zero.

The variables that are initialized automatically for each phase include: the control variables, the state variables, the static parameters, the initial time, and the final time. The user may also compute initial guesses for the state variables by propagating the differential equations associated with the problem. Two auxiliary functions are provided for this purpose. See section 2.10 for more details.

2.7 Evaluating the discretization error

PSOPT evaluates the discretization error using a method adopted from [3]. Define the error in the differential equation as a function of time:

$$\epsilon(t) = \dot{\tilde{x}}(t) - f[\tilde{x}(t), \tilde{u}(t), p, t]$$

where \tilde{x} is an interpolated value of the state vector given the grid point values of the state vector, \tilde{x} is an estimate of the derivative of the state vector given the state vector interpolant, and \tilde{u} is an interpolated value of the control vector given the grid points values of the control vector. The type of interpolation used depends on the collocation method employed. For Legendre and Chebyshev methods, the interpolation done by the Lagrange interpolant. For Trapezoidal and Hermite-Simpson methods and central difference methods, cubic spline interpolation is used. The absolute local error corresponding to state i on a particular interval $t \in [t_k, t_{k+1}]$, is defined as follows:

$$\eta_{i,k} = \int_{t_i}^{t_{k+1}} |\epsilon_i(t)| \mathrm{d}t$$

where the integral is computed using the composite Simpson method. The default number of integration steps for each interval is 10, but this can be changed by means of the input parameter algorithm.nsteps_error_integration. The relative local error is defined as:

$$\epsilon_k = \max_i \frac{\eta_{i,k}}{w_i + 1}$$

where

$$w_i = \max_{k=1}^{N} \left[|\tilde{x}_{i,k}|, |\dot{\tilde{x}}_{i,k}| \right]$$

After each PSOPT run, the sequence ϵ_k for each phase is available through the solution structure as follows:

epsilon = solution.get_relative_local_error_in_phase(iphase)

where epsilon is a DMatrix object. The error sequence can be analysed by the user to assess the quality of the discretization. This information may be useful to aid the mesh refinement process.

Additionally, the maximum value of the sequence ϵ_k for each phase is printed in the solution summary at the end of an execution.

2.8 Mesh refinement

2.8.1 Manual mesh refinement

Manual mesh refinement, which is the default option, is performed by interpolating a previous solution based on n_1 nodes, into a new mesh based on n_2 nodes, where $n_2 > n_1$, and using the interpolated solution as an initial guess for a new optimization. If global collocation is being used, \mathcal{PSOPT} employs Lagrange polynomials to perform the interpolation associated with mesh refinement. If local collocation is being used, \mathcal{PSOPT} employs cubic splines to perform the interpolation. The variables which are interpolated include the controls, states and Lagrange multipliers associated with the differential defect constraints, which are related to the co-states. The other decision variables (start and final times, and static parameters) do not need to be interpolated.

To perform mesh refinement, the user must supply the desired sequence of grid points (or nodes) for each phase through a string constant with the values separated by commas which is assigned to

problem.phases(iphase).nodes

The number of mesh refinements to be carried out is one less than the amount of nodes to be tried. Note that the number of nodes to be tried must be the same in all phases (but not necessarily their value).

For example to try the sequence 10, 20 and 50 nodes in phase iphase, then the following command specifies that:

```
problem.phases(iphase).nodes = "[10, 20, 50]";
```

If the user wishes to try only a single grid size (with no mesh refinement), this is specified by providing a single value as follows:

```
problem.phases(iphase).nodes = INTEGER;
```

In problems with more than one phase, the length of the node sequence to be tried needs to be the same in each phase, but the actual grid sizes need not be the same between phases.

2.8.2 Automatic mesh refinement with pseudospectral grids

If a global collocation method is being used and algorithm.mesh_refinement is set to "automatic", then, mesh refinement is carried out as described below. \mathcal{PSOPT} will compute the maximum discretization error $\epsilon^{(i,m)}$ for every phase i at every mesh refinement iteration m, as described in Section 2.7.

The method is based on a nonlinear least squares fit of the maximum discretization error for each phase with respect to the mesh size:

$$\hat{y}^i = \varphi_1 \theta_1 + \theta_2$$

where \hat{y}^i is an estimate of $\log(\epsilon^{(i)})$, $\varphi_1 = \log(N)$, θ_1 and θ_2 are parameters which are estimated based on the mesh refinement history. This is equivalent to modelling the dependency of $\epsilon^{(i)}$ with respect to the number of nodes N_i as follows:

$$\epsilon^{(i)} = C \frac{1}{N_i^m}$$

where $m = -\theta_1$, $C = \exp(\theta_2)$. This dependency relates to the upper bound on the \mathcal{L}_2 norm of the interpolation error given in [10]. Given a desired tolerance ϵ_{max} , this approximation is applied when the discretization error has been reduced for at least two iterations to find an extrapolated number of nodes which reduces the discretization error by a factor of 0.25.

The user specifies an initial number of nodes for each phase, as follows:

problem.phases(iphase).nodes = INTEGER.

The user may also specify values for the following parameters which control the mesh refinement procedure. The default values are those shown:

Maximum discretization error, ϵ_{max} :

```
algorithm.ode_tolerance = 1.e-3;
```

Maximum increment factor, F:

```
algorithm.mr_max_increment_factor = 0.4;
```

Maximum number of mesh refinement interations, m_{max} :

```
algorithm.mr_max_iterations = 7;
```

Minimum number of extrapolation points:

```
algorithm.mr_min_extrapolation_points = 3;
```

Initial increment for the number of nodes, ΔN_0 :

The mesh refinement algorithm is decribed below.

- 1. Set the iteration index m=1.
- 2. If $m > m_{\text{max}}$, terminate.

- 3. Solve the nonlinear programming problem for the current mesh, and find the maximum discretization error $\epsilon^{(i,m)}$ for each phase i.
- 4. If $\epsilon^{(i,m)} < \epsilon_{\text{max}}$ for all phases, terminate.
- 5. The increment in the number of nodes in each phase i, denoted by ΔN_i , is computed as follows:
 - (a) If $m < m_{\min}$ then $\Delta N_i = \Delta N_0$
 - (b) if $\epsilon^{(i,m)}$ has increased in the last two iterations, then $\Delta N_i = 5$
 - (c) if $\epsilon^{(i,m)}$ has decreased in at least the last two iterations, compute the parameters θ_1 and θ_2 by solving a least squares problem based on the monotonic part of the mesh refinement history, then ΔN_i is computed as follows:

$$\Delta N_i = \max \left(\inf \left[\exp \left(\frac{y_d - \theta_2}{\theta_1} \right) \right] - N_i, \Delta N_{\max} \right)$$

where $y_d = \max(\log(0.25\epsilon^{(i,m)}), \log(0.99\epsilon_{\max}))$, and

$$\Delta N_{\text{max}} = F N_i$$

where F is the maximum increment factor.

6. Increment the number of nodes in the mesh for each phase:

$$N_i \leftarrow N_i + \Delta N_i$$

7. Set $m \leftarrow m + 1$, and go back to step 2.

2.8.3 Automatic mesh refinement with local collocation

If a local collocation method (trapezoidal, Hermite-Simpson) is being used, and algorithm.mesh_refinement is set to "automatic", then, mesh refinement is carried out as described below. \mathcal{PSOPT} will compute the discretization error $\epsilon^{(i,m)}$ for every phase i at every mesh refinement iteration m, as described in Section 2.7. The method is based on the mesh refinement algorithm described by Betts [3]. If the current discretization method is trapezoidal, then the order p=2, otherwise if the current method is Hermite-Simpson, then p=4. Conversely, if p changes from 2 to 4, then the discretization method is changed from trapezoidal to Hermite-Simpson.

The user specifies an initial number of nodes for each phase, as follows:

problem.phases(iphase).nodes = INTEGER.

The user may also specify values for the following parameters which control the mesh refinement procedure. The default values are those shown:

Maximum discretization error, ϵ_{max} :

```
algorithm.ode_tolerance = 1.e-3;
```

Minimum increment factor, κ :

```
algorithm.mr_kappa = 0.1;
```

Maximum increment factor, ρ :

```
algorithm.mr_max_increment_factor = 0.4;
```

Maximum number of mesh refinement interations, m_{max} :

```
algorithm.mr_max_iterations = 7;
```

Maximum nodes to add within a single interval, M_1 :

```
algorithm.mr_M1 = 5;
```

Define $M' = \min(M_1, \kappa N_i) + 1$, where N_i is the current number of nodes in phase i. The local mesh refinement algorithm is as follows.

- 1. Set the iteration index m=1.
- 2. If $m > m_{\text{max}}$, terminate.
- 3. Solve the nonlinear programming problem for the current mesh, and find the discretization error $\epsilon_k^{(i,m)}$ for each interval k and each phase i.
- 4. If $\max_k \epsilon_k^{(i,m)} < \epsilon_{\max}$ for all phases, terminate the mesh refinement iterations.
- 5. Select the primary order for the new mesh:
 - (a) If p < 4 and $\epsilon_{\alpha} \leq 2\bar{\epsilon}^{(i,m)}$, where $\bar{\epsilon}^{(i,m)}$ is the average discretization error in phase i.
 - (b) Otherwise, if p < 4 and i > 2, then set p = 4.
- 6. Estimate the order reduction. The current and previous grid are compared and the order reduction r_k is computed for each interval in each phase. The order reduction is computed from:

$$r_k = \max[0, \min(\operatorname{nint}(\hat{r}_k), p)]$$

where

$$\hat{r}_k = p + 1 - \frac{\theta_k/\eta_k}{1 + I_k}$$

where nint() is the nearest integer function, I_k is the number of points being added to interval k, η_k is the estimated discretization error within interval k of the old grid, after the subdivision, and θ_k is the discretization error on the old grid before the subdivision.

- 7. Construct the new mesh.
 - (a) Compute the interval α with maximum error within phase i:

$$\epsilon_{\alpha}^{(i)} = \max_{k} \epsilon_{k}^{(i,m)}$$

- (b) Terminate step 7 if
 - i. M' nodes have been added, and
 - ii. the error is below the tolerance in each phase: $\epsilon_{\alpha}^{(i)} < \epsilon_{\text{max}}$ and $I_{\alpha} = 0$, or
 - iii. the predicted error is well below the tolerance $\epsilon_{\alpha}^{(i)} < \kappa \epsilon_{\text{max}}$ and $0 \leq I_{\alpha} < M_1$, or
 - iv. $\rho(N_i 1)$ nodes have been added, or
 - v. M_1 nodes have been added to a single interval.
- (c) Add one node to interval α , so that $I_{\alpha} \leftarrow I_{\alpha} + 1$.
- (d) Update the predicted error for interval α using

$$\epsilon_{\alpha} \leftarrow \epsilon_{\alpha} \left(\frac{1}{1 + I_k} \right)^{p - r_k + 1}$$

- (e) Return to step 7(a).
- 8. Set $m \leftarrow m + 1$ and go back to step 2.

2.8.4 LATEX code generation

IMTEX code is generated automatically producing a table with a summary of information about the mesh refinement process. It may be useful to include this summary in publications that incorporate results generated with \mathcal{PSOPT} . A file named mesh_statistics_\$\$\$.tex is automatically created, unless algorithm.print_level is set to zero, where \$\$\$ represents the characters of problem.outfilename which occur to the left of the file extension point ".".

To include the generated table in a LATEX document, simply use the command:

\input{mesh_statistics_\$\$\$.tex}

The generated table includes a caption associated with the problem name as set through problem.name, as well as a label which is generated by concatenating the string "mesh_stats_" with the characters of problem.outfilename which occur to the left of the file extension point ".". The caption and label can easily be changed to suit the user requirements by editing or renaming the generated file. A key to the abbreviations used in the file is also printed. The abbreviations for the discretization methods used are described in Table 2.3

Abbreviation	Description
LGL-ST	LGL nodes with standard differentiation matrix
	given by equation (1.12)
LGL-RR	LGL nodes with reduced round-off differentia-
	tion matrix given by equation (1.24)
LGL-CD	LGL nodes with reduced central-differences dif-
	ferentiation matrix given by equation (1.24)
CGL-ST	CLG nodes with standard differentiation matrix
	given by equation (1.19)
CGL-RR	LGL nodes with reduced round-off differentia-
	tion matrix given by equation (1.24)
CGL-CD	LGL nodes with reduced central-differences dif-
	ferentiation matrix given by equation (1.24)
TRP	Trapezoidal discretization, see equation (1.50)
H-S	Hermite-Simpson discretization, see equation
	(1.51)

Table 2.3: Description of the abbreviations used for the discretization methods which are shown in the automatically generated LATEX table

2.9 Implementing multi-segment problems

Sometimes, it is useful for computational or other reasons to define a multi-segment problem. A multi-segment problem is an optimal control problem with multiple sequential phases that has the same dynamics and path constraints in each phase. The multi-segment facilities implemented in \mathcal{PSOPT} allow the user to specify multi-segment problems in an easier way than defining a multi-phase problem. Special functions are called automatically to patch consecutive segments and ensure state and time continuity across the segment boundaries.

To specify a multi-segment problem the it is necessary to create a data structure of the type MSdata (in addition to the problem, algorithm and solution structures) and assign values to its elements as follows:

MSdata msdata;

```
msdata.nsegments
                              = INTEGER;
msdata.nstates
                              = INTEGER;
msdata.ncontrols
                              = INTEGER;
msdata.nparameters
                              = INTEGER;
msdata.npath
                              = INTEGER;
msdata.n_initial_events
                              = INTEGER;
msdata.n_final_events
                              = INTEGER;
msdata.nodes
                              = INTEGER OR STRING;
```

If it is desired to enforce control continuity across the segment boundaries, then set msdata.continuous_controls to true. By default the controls are allowed to be discontinuous across the segment boundaries.

The number of nodes per segment can be speficied as follows (note that it is possible to create grids with segments that have different number of nodes):

- as a single value (e.g. 30), such that the same number of nodes is employed in each segment.
- If algorithm.mesh_refinement is set to "manual", a character string can be entered with the node sequence to be tried per segment as part of a manual mesh refinement strategy (e.g. "[30, 50, 60]"). Here the number of values corresponds to the number of mesh refinement iterations to be performed. It is assumed that the same node sequence is tried for each segment. If algorithm.mesh_refinement is set to "automatic", then only the first value of the specified sequence is used to start the automatic mesh refinement iterations.
- If algorithm.mesh_refinement is set to "manual", a matrix can be entered, such that each row of the matrix corresponds to the node sequence to be tried in the corresponding segment (a character string can be used to enter the matrix, e.g. "[30, 50, 60; 10, 15, 20; 5, 10, 15]", noting the semicolons that separate the rows). Here the number of rows corresponds to the number of segments, and the number of columns corresponds to the number of manual mesh refinement iterations to be performed. If algorithm.mesh_refinement is set to "automatic", then only the first value of the specified sequence for each segment is used to start the automatic mesh refinement iterations.

After this, the following function should be called:

```
multi_segment_setup(problem, algorithm, msdata);
```

The upper and lower bounds on the relevant event times of the problem (start time for each segment, and end time for the last segment) can be entered as follows:

```
problem.bounds.lower.times = DMATRIX OR STRING;
problem.bounds.upper.times = DMATRIX OR STRING;
```

where entered value specifies the time bounds in the following order:

$$[t_0^{(1)}, t_0^{(2)}, \dots, t_0^{(N_p)}, t_f^{(N_p)}]$$

At this point, the bound information for segment 1 (phase 1) can be entered (bounds for states, controls, event constraints, path constraints, and parameters), as described in section 2.2.6. This should be followed by the bound information for the event constraints of the last phase or segment. After entering the bound information, the auxiliary function auto_phase_bounds should be called as follows:

```
auto_phase_bounds(problem);
```

The initial guess for the solution can be specified by a call to the function auto_phase_guess. See section 2.10.

See section 3.30 for an example on the use of the multi-segment facilities available within \mathcal{PSOPT} .

2.10 Other auxiliary functions available to the user

PSOPT implements a number of auxiliary functions to help the user define optimal control problems. Most (but not all) of these functions are suitable for use with automatic differentiation. All the functions can also be used with numerical differentiation. See the examples section for further details on the use of these functions.

2.10.1 cross function

This function takes two arrays of adoubles x and y, each of dimension 3, and returns in array z (also of dimension 3) the result of the vector cross product of x and y. The prototype of the function is as follows:

```
void cross(adouble* x, adouble* y, adouble* z);
```

2.10.2 dot function

This function takes two arrays of adoubles x and y, each of dimension n, and returns the dot product of x and y. The prototype of the function is as follows:

```
adouble dot(adouble* x, adouble* y, int n);
```

2.10.3 get_delayed_state function

This function allows the user to implement DAE's with delayed states. Use only in single-phase problems. Its prototype is as follows:

The function parameters are as follows:

- delayed_state: on output, the variable pointed by this pointer contrains the value of the delayed state.
- state_index: is the index of the state vector whose delayed value is to be found (starting from 1).
- iphase: is the phase index (starting from 1).
- time: is the value of the current instant of time within the phase.
- delay: is the value of the delay.
- xad: is the vector of scaled decision variables.

2.10.4 get_delayed_control function

This function allows the user to implement DAE's with delayed controls. Use only in single-phase problems. Its prototype is as follows:

- delayed_control: on output, the variable pointed by this pointer contrains the value of the delayed state.
- control_index: is the index of the control vector whose delayed value is to be found (starting from 1).
- iphase: is the phase index (starting from 1).
- time: is the value of the current instant of time within the phase.
- delay: is the value of the delay.
- xad: is the vector of scaled decision variables.

2.10.5 get_interpolated_state function

This function allows the user to obtain interpolated values of the state at arbitrary values of time within a phase. Its prototype is as follows:

- interp_state: on output, the variable pointed by this pointer contrains the value of the interpolated state.
- state_index: is the index of the state vector whose interpolated value is to be found (starting from 1).
- iphase: is the phase index (starting from 1).
- time: is the value of the current instant of time within the phase.
- xad: is the vector of scaled decision variables.

2.10.6 get_interpolated_control function

This function allows the user to obtain interpolated values of the control at arbitrary values of time within a phase. Its prototype is as follows:

- interp_control: on output, the variable pointed by this pointer contains the value of the interpolated control.
- control_index: is the index of the control vector whose interpolated value is to be found (starting from 1).
- iphase: is the phase index (starting from 1).
- time: is the value of the current instant of time within the phase.
- xad: is the vector of scaled decision variables.

2.10.7 get_control_derivative function

This function allows the user to obtain the value of the derivative of a specified control variable at arbitrary values of time within a phase. Its prototype is as follows:

- control_derivative: on output, the variable pointed by this pointer contains the value of the control derivative.
- control_index: is the index of the control vector whose interpolated value is to be found (starting from 1).
- iphase: is the phase index (starting from 1).
- time: is the value of the current instant of time within the phase.
- xad: is the vector of scaled decision variables.

2.10.8 get_state_derivative function

This function allows the user to obtain the value of the derivative of a specified state variable at arbitrary values of time within a phase. Its prototype is as follows:

- state_derivative: on output, the variable pointed by this pointer contains the value of the state derivative.
- state_index: is the index of the state vector whose interpolated value is to be found (starting from 1).
- iphase: is the phase index (starting from 1).
- time: is the value of the current instant of time within the phase.
- xad: is the vector of scaled decision variables.

2.10.9 get_initial_states function

This function allows the user to obtain the values of the states at the initial time of a phase. Its prototype is as follows:

void get_initial_states(adouble* states, adouble* xad, int iphase);

- states: on output, this array contains the values of the initial states within the specified phase.
- iphase: is the phase index (starting from 1).
- xad: is the vector of scaled decision variables.

2.10.10 get_final_states function

This function allows the user to obtain the values of the states at the final time of a given phase. Its prototype is as follows:

void get_initial_states(adouble* states, adouble* xad, int iphase);

- states: on output, this array contains the values of the final states within the specified phase.
- iphase: is the phase index (starting from 1).
- xad: is the vector of scaled decision variables.

2.10.11 get_initial_controls function

This function allows the user to obtain the values of the controls at the initial time of a phase. Its prototype is as follows:

void get_initial_controls(adouble* controls, adouble* xad, int iphase);

- controls: on output, this array contains the values of the initial controls within the specified phase.
- iphase: is the phase index (starting from 1).
- xad: is the vector of scaled decision variables.

2.10.12 get_final_controls function

This function allows the user to obtain the values of the controls at the final time of a given phase. Its prototype is as follows:

void get_initial_controls(adouble* controls, adouble* xad, int iphase);

- controls: on output, this array contains the values of the final controls within the specified phase.
- iphase: is the phase index (starting from 1).
- xad: is the vector of scaled decision variables.

2.10.13 get_initial_time function

This function allows the user to obtain the value of the initial time of a given phase. Its prototype is as follows:

adouble get_initial_time(adouble* xad, int iphase);

- iphase: is the phase index (starting from 1).
- xad: is the vector of scaled decision variables.
- The function returns the value of the initial time within the specified phase as an adouble type.

2.10.14 get_final_time function

This function allows the user to obtain the value of the final time of a given phase. Its prototype is as follows:

adouble get_final_time(adouble* xad, int iphase);

- iphase: is the phase index (starting from 1).
- xad: is the vector of scaled decision variables.
- The function returns the value of the final time within a phase as an adouble type.

2.10.15 auto_link function

This function allows the user to automatically link two phases by generating suitable state and time continuity constraints. It is assumed that the number of states in the two phases being linked is the same. The function is intended to be called from within the user supplied linkages function. Each call to auto_link generates an additional number of linkage constraints given by the number of states being linked plus one.

The function prototype is as follows:

- linkages: on output, this is the updated array of linkage constraint values.
- index: on input, the variable pointed to by this pointer contains the next value of the linkages array to be updated. On output, this value is updated to be used in the next call to the auto_link function. The first time the function is called, the value should be 0.
- xad: is the vector of scaled decision variables.
- iphase_a: is the phase index (starting from 1) of one phase to be linked.
- iphase_b: is the phase index (starting from 1) of the other phase to be linked.

2.10.16 auto_link_2 function

This function works in a simular way as the auto_link function, but it also forces the control variables to be continuous at the boundaries. It requires a match in the number of states and in the number of controls between the phases being linked. Each call to auto_link_2 generates an additional number of linkage constraints given by the number of states plus the number of controls, plus one.

The function prototype is as follows:

- linkages: on output, this is the updated array of linkage constraint values.
- index: on input, the variable pointed to by this pointer contains the next value of the linkages array to be updated. On output, this value is updated to be used in the next call to the auto_link_2 function. The first time the function is called, the value should be 0.
- xad: is the vector of scaled decision variables.
- iphase_a: is the phase index (starting from 1) of one phase to be linked.
- iphase_b: is the phase index (starting from 1) of the other phase to be linked.

2.10.17 auto_phase_guess function

This function allows the user to automatically specify the initial guess in a multi-segment problem. The function prototype is as follows:

so that the controls, states, time and static parameters are specified as if the problem was single-phase.

2.10.18 linear_interpolation function

This function interpolates a point defined function using classical linear interpolation. The function is not suitable for automatic differentiation, so it should only be used with numerical differentiation. This is useful when the problem involves tabular data. The function prototype is as follows:

• y: on output, the variable pointed to by this pointer contains the interpolated function value.

- x: is the value of the independent variable for which the interpolated function value is sought.
- pointx: is the DMatrix object of independent data points.
- pointy: is a DMatrix object of dependent data points.
- npoints: is the number of points in the data objects pointx and pointy.

2.10.19 smoothed_linear_interpolation function

This function interpolates a point defined function using a smoothed linear interpolation. The method used avoids joining sharp corners between adjacent linear segments. Instead, smoothed pulse functions are used to join the segments. The function is suitable for automatic differentiation. This is useful when the problem involves tabular data. The function prototype is as follows:

- y: on output, the variable pointed to by this pointer contains the interpolated function value.
- x: is the value of the independent variable for which the interpolated function value is sought.
- pointx: is the DMatrix object of independent data points.
- pointy: is a DMatrix object of dependent data points.
- npoints: is the number of points in the data objects pointx and pointy.

2.10.20 spline_interpolation function

This function interpolates a point defined function using cubic spline interpolation. The function is not suitable for automatic differentiation, so it should only be used with numerical differentiation. This is useful when the problem involves tabular data. The function prototype is as follows:

```
DMatrix& pointx,
DMatrix& pointy,
int npoints);
```

- y: on output, the variable pointed to by this pointer contains the interpolated function value.
- x: is the value of the independent variable for which the interpolated function value is sought.
- pointx: is the DMatrix object of independent data points.
- pointy: is a DMatrix object of dependent data points.
- npoints: is the number of points in the data objects pointx and pointy.

2.10.21 bilinear_interpolation function

The function interpolates functions of two variables on a regular grid using the classical bilinear interpolation method. This is useful when the problem involves tabular data. The function prototype is as follows.

```
void bilinear_interpolation(adouble* z,
adouble& x,
adouble& y,
DMatrix& X,
DMatrix& Y,
DMatrix& Z)
```

- z: on output the adouble variable pointed to by this pointer contains the interpolated function value.
- The adouble pair of variables (x, y) represents the point at which the interpolated value of the function is returned.
- X: is a vector (DMatrix object) of dimension nxpoints × 1.
- Y: is a vector (DMatrix object) of dimension nypoints × 1.
- Z: is a matrix (DMatrix object) of dimensions nxpoints × nypoints. Each element Z(i,j) corresponds to the pair (X(i), Y(j))

The function does not deal with sparse data. This function does not allow the use of automatic differentiation, so it should only be used with numerical differentiation.

2.10.22 smooth_bilinear_interpolation function

The function interpolates functions of two variables on a regular grid using the a smoothed bilinear interpolation method which allows the use of automatic differentiation. This is useful when the problem involves tabular data. The function prototype is as follows.

- z: on output the adouble variable pointed to by this pointer contains the interpolated function value.
- The adouble pair of variables (x, y) represents the point at which the interpolated value of the function is returned.
- X: is a vector (DMatrix object) of dimension nxpoints × 1.
- Y: is a vector (DMatrix object) of dimension nypoints \times 1.
- Z: is a matrix (DMatrix object) of dimensions nxpoints × nypoints. Each element Z(i,j) corresponds to the pair (X(i), Y(j))

The function does not deal with sparse data.

2.10.23 spline_2d_interpolation function

The function interpolates functions of two variables on a regular grid using the a cubic spline interpolation method. This is useful when the problem involves tabular data. The function prototype is as follows.

```
void spline_2d_interpolation(adouble* z,
adouble& x,
adouble& y,
DMatrix& X,
DMatrix& Y,
DMatrix& Z)
```

- z: on output the adouble variable pointed to by this pointer contains the interpolated function value.
- The adouble pair of variables (x, y) represents the point at which the interpolated value of the function is returned.

- X: is a vector (DMatrix object) of dimension nxpoints × 1.
- Y: is a vector (DMatrix object) of dimension nypoints \times 1.
- Z: is a matrix (DMatrix object) of dimensions nxpoints × nypoints. Each element Z(i,j) corresponds to the pair (X(i), Y(j))

The function does not deal with sparse data. This function does not allow the use of automatic differentiation, so it should only be used with numerical differentiation.

2.10.24 smooth_heaviside function

This function implements a smooth version of the Heaviside function H(x), defined as H(x) = 1, x > 0, H(x) = 0 otherwise. The approximation is implemented as follows:

$$H(x) \approx 0.5(1 + \tanh(x/a)) \tag{2.8}$$

where a > 0 is a small real number. The function prototype is as follows:

adouble smooth_heaviside(adouble x, double a);

2.10.25 smooth_sign function

This function implements a smooth version of the function sign(x), defined as sign(x) = 1, x > 0, sign(x) = -1, x < 0, and sign(0) = 0. The approximation is implemented as follows:

$$sign(x) \approx \tanh(x/a) \tag{2.9}$$

where a > 0 is a small real number. The function prototype is as follows:

adouble smooth_sign(adouble x, double a);

See the examples section for further details on usage of this function.

2.10.26 smooth_fabs function

This function implements a smooth version of the absolute value function |x|. The approximation is implemented as follows:

$$|x| \approx \sqrt{x^2 + a^2} \tag{2.10}$$

where a > 0 is a small real number. The function prototype is as follows:

adouble smooth_fabs(adouble x, double a);

2.10.27 integrate function

The integrate function computes the numerical quadrature Q of a scalar function g over the a single phase as a function of states, controls, static parameters and time.

$$Q = \int_{t_0^{(i)}}^{t_f^{(i)}} g[x^{(i)}(t), u^{(i)}(t), p^{(i)}, t] dt$$
 (2.11)

The integration is done using the Gauss-Lobatto method. This is useful, for example, to incorporate constraints involving integrals over a phase, which can be included as additional event constraints:

$$Q_l \le \int_{t_0^{(i)}}^{t_f^{(i)}} g[x^{(i)}(t), u^{(i)}(t), p^{(i)}, t] dt \le Q_u$$
 (2.12)

Function integrate has the following prototype:

- integrand: this is a pointer to the function to be integrated.
- xad: is the vector of scaled decision variables.
- iphase: is the phase index (starting from 1).
- The function returns the value of the integral as an adouble type.

The user needs to implement separately the integrand function, which must have the prototype:

• states: this is an array of instantaneous states.

- controls: is an array of instantaneous controls.
- parameters: is an array of static parameter values.
- time: is the value of the current instant of time within the phase.
- xad: is the vector of scaled decision variables.
- iphase: is the phase index (starting from 1).
- the function must return the value of the integrand function given the supplied parameters as an adouble type.

2.10.28 product_ad functions

There are two versions of this function. The first version has the prototype:

This function multiplies a constant matrix stored in DMatrix object A by adouble vector stored in array x, which has length nx, and returns the result in adouble array y.

The second version has the prototype:

This function multiplies the $(na \times nb)$ matrix stored column by column in adouble array Apr, by the $(nb \times mb)$ matrix stored column by column in adouble array Bpr. The result is stored (column by column) in adouble array ABpr.

2.10.29 sum_ad function

This function adds a matrix or vector stored columnwise in adouble array a, to a matrix or vector of the same dimensions stored columnwise in adouble array b. Both arrays are assumed to have a total of n elements. The result is returned in adouble array c. The function prototype is as follows.

2.10.30 subtract_ad function

This function subtracts a matrix or vector stored columnwise in adouble array a, to a matrix or vector of the same dimensions stored columnwise in adouble array b. Both arrays are assumed to have a total of n elements. The result is returned in adouble array c. The function prototype is as follows.

2.10.31 inverse_ad function

This function computes the inverse of an $n \times n$ square matrix stored columnwise in adouble array a. The result is returned in adouble array ainv, also using columnwise storage. The function prototype is as follows.

2.10.32 rk4_propagate function

This function may be used to generate an initial guess for the state trajectory by propagating the dynamics using 4th order Runge-Kutta integration. Note that no bounds are considered on states or controls and that any path constraints specified in function dae() are ignored. The user needs to specify a control trajectory and the corresponding time vector. The function prototype is as follows:

• dae is a pointer to the problem's dae function;

- control_trajectory is a DMatrix object of dimensions problem.phases(iphase).ncontrols × M
 with the initial guess for the controls.
- time_vector is a DMatrix object of dimensions 1 × M with the time instants that correspond to each element of control_trajectory.
- initial_state is a DMatrix object of dimensions problem.phases(iphase).nstates × 1 with the value of the initial state vector.
- parameters is a DMatrix object of dimensions problem.phases(iphase).nparameters × 1 with given values for the static parameters.
- problem is a Prob structure.
- iphase is the phase index.
- state_trajectory is a DMatrix object with dimensions problem.phases(iphase).nstates × M which on output contains the result of the of the propagation. The values of the states correspond to the time vector time_vector.

2.10.33 rkf_propagate function

This function may be used to generate an initial guess for the state trajectory by propagating the dynamics using the Runge-Kutta-Fehlberg method with variable step size and relative local truncation error within a given tolerance. Note that no bounds are considered on states or controls and that any path constraints specified in function dae() are ignored. The user needs to specify a control trajectory and the corresponding time vector, as well as minimum and maximum values for the integration step size, and a tolerance. Note that the function throws an error if the minimum step size is violated. The function prototype is as follows:

```
Prob & problem,
int iphase,
DMatrix& state_trajectory,
DMatrix& new_time_vector,
DMatrix& new_control_trajectory);
```

- dae is a pointer to the problem's dae function;
- control_trajectory is a DMatrix object of dimensions problem.phases(iphase).ncontrols × M
 with the initial guess for the controls.
- time_vector is a DMatrix object of dimensions 1 × M with the time instants that correspond to each element of control_trajectory.
- initial_state is a DMatrix object of dimensions problem.phases(iphase).nstates × 1 with the value of the initial state vector.
- parameters is a DMatrix object of dimensions problem.phases(iphase).nparameters × 1 with given values for the static parameters.
- tolerance is a positive value for the tolerance against which the maximum relative error in the state vector is compared.
- hmin is the minimum integration step size.
- hmax is the maximum integration step size.
- problem is a Prob structure.
- iphase is the phase index.
- state_trajectory is a DMatrix object with dimensions problem.phases(iphase).nstates × M which on output contains the result of the of the propagation. The values of the states correspond to the time vector new_time_vector.
- new_time_vector is a DMatrix object with dimensions $1 \times N$ which on output contains the time values of the propagation.
- new_control_trajectory is a DMatrix object with dimensions problem.phases(iphase).nstates × N
 which on output containts interpolated values of the control trajectory corresponding to the time vector new_time_vector. Linear interpolation is employed.

2.10.34 resample_trajectory function

This function resamples a trajectory given new values of the time vector using natural cubic spline interpolation.

- Y is, on output, a DMatrix object with dimensions $n_y \times N$ with the interpolated values of the dependent variable.
- t is a DMatrix object of dimensions 1 × N with the values of the independent variable at which the interpolated values are required. The elements of this vector should be monotonically increasing, i.e. t(j+1) > t(j). The following restrictions should be satisfied: t(1) ≥ tdata(1), and t(N) ≤ tdata(M).
- Ydata is a DMatrix object of dimensions $n_y \times M$ with the data values of the dependent variable.
- tdata is a DMatrix object of dimensions $1 \times M$ with the data values of the independent variable. The elements of this vector should be monotonically increasing, i.e. t(j+1) > t(j).

2.11 Pre-defined constants

The following constants are defined within the header file psopt.h:

- pi: defined as 3.141592653589793;
- inf: defined as 1×10^{19} .

2.12 Standard output

PSOPT will by default produce output information on the screen as it runs. PSOPT will produce a short file with a summary of information named with the string provided in algorithm.outfilelname. This file contains the problem name, the total CPU time spent, the NLP solver used, the optimal value of the objective function, the values of the endpoint cost function and cost integrals, the initial and final time, the maximum discretization error, and the output string from the NLP solver.

Additionally, every time a \mathcal{PSOPT} excutable is run, it will produce a file named psopt_solution_\$\$\$.txt (\$\$\$ represents the characters of

problem.outfilename which occur to the left of the file extension point "."). This file contains the problem name, time stamps, a summary of the algorithm options used, and results obtained, the final grid points, the final control variables, the final state variables, the final static parameter values. The file also contains a summary of all constraints functions associated with the NLP problem, including their final scaled value, bounds, and scaling factor used; a summary of the final NLP decision variables, including their final unscaled values, bounds and scaling factors used; and a summary of the mesh refinement process. An indication is given at the end of a constraint line, or decision variable line, if a scaled constraint function or scaled decision variable is within algorithm.nlp_tolerance of one of its bounds, or if a scaled constraint function or scaled decision variable has violated one of its bounds by more than algorithm.nlp_tolerance. For parameter estimation problems this file also contains the covariance matrix of the parameter vector, and the 95% confidence interval for each estimated parameter.

LATEX code to produce a table with a summary of the mesh refinement process is also automatically generated as described in section 2.8.4.

If algorithm.print_level is set to zero, then no output is produced.

2.13 Implementing your own problem

A template C++ file named user.cxx is provided in the directory

psopt-master/PSOPT/examples/user

This file can be modified by the user to implement their own problem. and an executable can then be built easily.

2.13.1 Building the user code from Linux

After modifying the user.cxx code, open a command prompt and cd to the base directory of the \mathcal{PSOPT} installation. Then simply type

- \$ cd PSOPT/examples/user
- \$ make user

If no compilation errors occur, an executable named user should be created in the directory psopt-master/PSOPT/examples/user.

Chapter 3

Examples of using PSOPT

The following examples have been mostly selected from the literature such that their solution can be compared with published results by consulting the references provided.

3.1 Alp rider problem

Consider the following optimal control problem, which is known in the literature as the Alp rider problem [3]. It is known as Alp rider because the minimum of the objective function forces the states to ride the path constraint. Minimize the cost functional

$$J = \int_0^{20} (100(x_1^2 + x_2^2 + x_3^2 + x_4^2) + 0.01(u_1^2 + u_2^2)) dt$$
 (3.1)

subject to the dynamic constraints

$$\dot{x}_1 = -10x_1 + u_1 + u_2
\dot{x}_2 = -2x_2 + u_1 + 2u_2
\dot{x}_3 = -3x_3 + 5x_4 + u_1 - u_2
\dot{x}_4 = 5x_3 - 3x_4 + u_1 + 3u_2$$
(3.2)

the path constraint

$$x_1^2 + x_2^2 + x_3^2 + x_4^2 - 3p(t,3,12) - 3p(t,6,10) - 3p(t,10,16) - 8p(t,15,4) - 0.01 \leq 0 \tag{3.3}$$

where the exponential peaks are $p(t, a, b) = e^{-b(t-a)^2}$, and the boundary conditions are given by:

$$x_1(0) = 2$$

 $x_2(0) = 1$
 $x_3(0) = 2$
 $x_4(0) = 1$
 $x_1(20) = 2$
 $x_2(20) = 3$
 $x_3(20) = 1$
 $x_4(20) = -2$ (3.4)

The \mathcal{PSOPT} code that solves this problem is shown below.

```
alpine_rider.cxx
/////// Reference: Betts (2001)
////// (See PSOPT handbook for full reference)
                                         #include "psopt.h"
adouble pk( adouble t, double a, double b)
  return exp(-b*(t-a)*(t-a));
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
               adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
/////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
                adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
   adouble x1 = states[CINDEX(1)];
adouble x2 = states[CINDEX(2)];
adouble x3 = states[CINDEX(3)];
   adouble x4 = states[CINDEX(4)];
adouble u1 = controls[CINDEX(1)];
adouble u2 = controls[CINDEX(2)];
   adouble L:
```

```
L = 100.0*(x1*x1 + x2*x2 + x3*x3 + x4*x4) + 0.01*(u1*u1 + u2*u2);
   return L;
adouble x1 = states[CINDEX(1)]:
   adouble x2 = states[CINDEX(2)];
   adouble X2 = states[CINDEX(2)];
adouble x3 = states[CINDEX(3)];
adouble x4 = states[CINDEX(4)];
adouble u1 = controls[CINDEX(1)];
adouble u2 = controls[CINDEX(2)];
adouble t = time;
  derivatives[CINDEX(1)] = -10*x1 + u1 + u2:
  derivatives[CINDEX(I)] = -10*X1 + u1 + u2;
derivatives[CINDEX(2)] = -2*x2 + u1 + 2*u2;
derivatives[CINDEX(3)] = -3*x3 + 5*x4 + u1 - u2;
derivatives[CINDEX(4)] = 5*x3 - 3*x4 + u1 + 3*u2;
  void events(adouble* e, adouble* initial_states, adouble* final_states,
          adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble x1i = initial_states[ CINDEX(1) ];
  adouble x11 = Initial_states[ CINDEX(1) ];
adouble x3i = initial_states[ CINDEX(2) ];
adouble x4i = initial_states[ CINDEX(3) ];
adouble x4f = final_states[ CINDEX(4) ];
  adouble x2f = final_states[ CINDEX(2) ];
  adouble x3f = final_states[ CINDEX(3) ];
  adouble x4f = final_states[ CINDEX(4) ];
  e[ CINDEX(1) ] = x1i;
  e[CINDEX(2)] = x2i;
e[CINDEX(3)] = x3i;
  e[ CINDEX(3) ] = X31;
e[ CINDEX(4) ] = x41;
e[ CINDEX(5) ] = x1f;
e[ CINDEX(6) ] = x2f;
e[ CINDEX(7) ] = x3f;
e[ CINDEX(8) ] = x4f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
 // No linkages as this is a single phase problem
int main(void)
```

```
Alg algorithm;
Sol solution;
  Prob problem;
problem.name
            problem.outfilename
problem.nphases
  problem.nlinkages
                     = 0:
  psopt_level1_setup(problem);
problem.phases(1).nstates
                 = 4:
  problem.phases(1).ncontrols = 2;
  problem.phases(1).nevents = 8;
problem.phases(1).npath = 1;
                         = "[120]";
  problem.phases(1).nodes
  psopt_level2_setup(problem, algorithm);
problem.phases(1).bounds.lower.states = "[-4.0, -4.0, -4.0, -4.0]";
  problem.phases (1).bounds.upper.states = "[ 4.0, 4.0, 4.0, 4.0]";
  problem.phases(1).bounds.lower.controls = "[ -500.0, -500 ]";
  problem.phases(1).bounds.upper.controls = "[ 500.0, 500 ]";
  problem.phases(1).bounds.lower.events = "[2.0, 1.0, 2.0, 1.0, 2.0, 3.0, 1.0, -2.0]";
  problem.phases(1).bounds.upper.events = problem.phases(1).bounds.lower.events;
                         = 100.0:
  problem.phases(1).bounds.upper.path
  problem.phases(1).bounds.lower.path
                         = 0.0:
  problem.phases(1).bounds.lower.StartTime = 0.0;
  problem.phases(1).bounds.upper.StartTime
                         = 0.0:
  problem.phases(1).bounds.lower.EndTime
                         = 20.0:
  problem.phases(1).bounds.upper.EndTime
                         = 20.0;
problem.integrand_cost = &integrand_cost;
  problem.endpoint_cost = &endpoint_cost;
problem.dae = &dae;
  problem.events = &events;
  problem.linkages = &linkages;
```

```
int nnodes
               = problem.phases(1).nodes(1);
  DMatrix x_guess
                       = zeros(4,nnodes);
  x_guess(1,colon())
x_guess(2,colon())
                  = linspace(2,1,nnodes);
                  = linspace(2,3,nnodes);
   x_guess(3,colon())
                  = linspace(2,1,nnodes);
                  = linspace(1,-2,nnodes);
  x_guess(4,colon())
  problem.phases(1).guess.controls
problem.phases(1).guess.states
problem.phases(1).guess.time
                            = zeros(2,nnodes);
                            = x_guess;
= linspace(0.0,20.0,nnodes+1);
algorithm.nlp_iter_max
                           = 1000;
  algorithm.nlp_tolerance algorithm.nlp_method
                           = 1.e-6:
                           = "automatic";
  algorithm.scaling
  algorithm.derivatives
                           = "automatic";
  algorithm.jac_sparsity_ratio
                           = 0.20:
                           = "Legendre";
= "central-differences";
  algorithm.collocation_method
  algorithm.diff_matrix
  algorithm.mesh_refinement
                           = "automatic";
  algorithm.mr max increment factor
                           = 0.3:
  algorithm.defect_scaling
                           = "jacobian-based";
psopt(solution, problem, algorithm);
DMatrix x = solution.get_states_in_phase(1);
  DMatrix u = solution.get_controls_in_phase(1);
  DMatrix t = solution.get_time_in_phase(1);
u.Save("u.dat"):
  t.Save("t.dat");
plot(t,x(1,colon()),problem.name+": state", "time (s)", "state","x1");
  plot(t.x(2.colon()).problem.name+": state", "time (s)", "state", "x2");
  plot(t,x(3,colon()),problem.name+": state", "time (s)", "state","x3");
  plot(t,x(4,colon()),problem.name+": state", "time (s)", "state","x4");
  plot(t,u(1,colon()),problem.name+": control","time (s)", "control", "u1");
  plot(t,u(2,colon()),problem.name+": control","time (s)", "control", "u2");
  plot(t,x(1,colon()),problem.name+": state x1", "time (s)", "state","x1",
                          "pdf", "alpine_state1.pdf");
```

The output from \mathcal{PSOPT} is summarized in the box below and shown in Figures 3.1-3.4 and Figures 3.5-3.6, which contain the elements of the state and the control, respectively. Table ?? shows the mesh refinement history for this problem.

```
PSOPT results summary
_____
Problem: Alp rider problem
CPU time (seconds): 1.151346e+02
NLP solver used: IPOPT
PSOPT release number: 4.0
Date and time of this run:
                          Thu Feb 21 15:28:52 2019
Optimal (unscaled) cost function value:
                                       2.026847e+03
Phase 1 endpoint cost function value: 0.000000e+00
Phase 1 integrated part of the cost: 2.026847e+03
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 2.000000e+01
Phase 1 maximum relative local error: 2.990169e-03
NLP solver reports: The problem has been solved!
```

3.2 Brachistochrone problem

Consider the following optimal control problem. Minimize the cost functional

$$J = t_f \tag{3.5}$$




Figure 3.1: State $x_1(t)$ for the Alp rider problem




Figure 3.2: State $x_2(t)$ for the Alp rider problem




Figure 3.3: State $x_3(t)$ for the Alp rider problem




Figure 3.4: State $x_4(t)$ for the Alp rider problem




Figure 3.5: Control $u_1(t)$ for the Alp rider problem




Figure 3.6: Control $u_2(t)$ for the Alp rider problem

subject to the dynamic constraints

$$\dot{x} = v \sin(\theta)
\dot{y} = v \cos(\theta)
\dot{v} = g \cos(\theta)$$
(3.6)

and the boundary conditions

$$x(0) = 0$$

 $y(0) = 0$
 $v(0) = 0$
 $x(t_f) = 2$
 $y(t_f) = 2$ (3.7)

where g = 9.8. A version of this problem was originally formulated by Johann Bernoulli in 1696 and is referred to as the *Brachistochrone* problem. The \mathcal{PSOPT} code that solves this problem is shown below.

```
#include "psopt.h"
adouble endpoint cost(adouble* initial states, adouble* final states,
          adouble* parameters, adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  return tf;
Define the integrand (Lagrange) cost function
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  return 0.0;
adouble xdot, ydot, vdot;
```

```
adouble x = states[ CINDEX(1) ];
  adouble y = states[ CINDEX(2) ];
adouble v = states[ CINDEX(3) ];
  adouble theta = controls[ CINDEX(1) ];
  xdot = v*sin(theta);
  ydot = v*cos(theta);
  vdot = 9.8*cos(theta);
 derivatives[ CINDEX(1) ] = xdot;
derivatives[ CINDEX(2) ] = ydot;
derivatives[ CINDEX(3) ] = vdot;
void events(adouble* e, adouble* initial_states, adouble* final_states,
       adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble x0 = initial_states[ CINDEX(1) ];
  adouble y0 = initial_states[ CINDEX(2) ];
adouble v0 = initial_states[ CINDEX(3) ];
adouble xf = final_states[ CINDEX(1)];
  adouble yf = final_states[ CINDEX(2)];
  e[ CINDEX(1) ] = x0;
  e[ CINDEX(2) ] = y0;
e[ CINDEX(3) ] = v0;
e[ CINDEX(4) ] = xf;
  e[ CINDEX(5) ] = yf;
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
 // No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
problem.name
               = "Brachistochrone Problem";
  problem.outfilename
                          = "brac1.txt";
Define problem level constants & do level 1 setup /////////
problem.nphases = 1;
                          = 0;
  problem.nlinkages
  psopt_level1_setup(problem);
///////// Define phase related information & do level 2 setup /////////
```

```
problem.phases(1).nstates
   problem.phases(1).ncontrols = 1;
   problem.phases(1).nevents = 5;
   problem.phases(1).npath
   problem.phases(1).nodes
                                    = "[40]";
   psopt_level2_setup(problem, algorithm);
problem.phases(1).bounds.lower.states = "[ 0; 0; 0]";
problem.phases(1).bounds.upper.states = "[20; 20; 20]";
   problem.phases(1).bounds.upper.states
   problem.phases(1).bounds.lower.controls = 0.0;
problem.phases(1).bounds.upper.controls = 2*pi;
  problem.phases(1).bounds.lower.StartTime
                                   = 0.0;
= 0.0;
   problem.phases(1).bounds.upper.StartTime
                                    = 0.0;
= 10.0;
   {\tt problem.phases(1).bounds.lower.EndTime}
   problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
   problem.dae = &dae;
   problem.events = &events;
problem.linkages = &linkages;
problem.phases(1).scale.controls = 1.0*ones(1,1);
    problem.phases(1).scale.controls
problem.phases(1).scale.states
problem.phases(1).scale.events
problem.phases(1).scale.defects
                               = 1.0*ones(5,1);
= 1.0*ones(3,1);
= 1.0;
   problem.phases(1).scale.time
//
//
   problem.scale.objective
                               = 1.0:
DMatrix x0(3,20):
   x0(1,colon()) = linspace(0.0,1.0, 20);
  x0(2,colon()) = linspace(0.0,1.0, 20);
x0(3,colon()) = linspace(0.0,1.0, 20);
                                = ones(1,20);
   problem.phases(1).guess.controls
  problem.phases(1).guess.states = x0;
problem.phases(1).guess.time = lins
                                = linspace(0.0, 2.0, 20);
= "TPOPT":
   {\tt algorithm.nlp\_method}
                               = "automatic";
= "automatic":
   algorithm.scaling
   algorithm.derivatives
   algorithm.nlp_iter_max
                                = 1000;
   algorithm.nlp_tolerance
                                = 1.e-6:
```

```
algorithm.hessian = "exact";
                         = "Legendre";
  algorithm.collocation_method
psopt(solution, problem, algorithm);
  if (solution.error_flag) exit(0);
DMatrix x = solution.get_states_in_phase(1);
DMatrix u = solution.get_controls_in_phase(1);
DMatrix t = solution.get_time_in_phase(1);
  DMatrix t = solution.get_laml_namiltonian_in_phase(1);

DMatrix lambda = solution.get_dual_costates_in_phase(1);
x.Save("x.dat");
  u.Save("u.dat"):
  lambda.Save("p.dat");
plot(t,x,problem.name + ": states", "time (s)", "states", "x y v");
  plot(t,u,problem.name + ": control", "time (s)", "control", "u");
  plot(t,H,problem.name + ": Hamiltonian", "time (s)", "H", "H");
  plot(t,lambda,problem.name + ": costates", "time (s)", "lambda", "lambda_1 lambda_2 lambda_3");
  plot(t,x,problem.name + ": states", "time (s)", "states", "x y v", \\ "pdf", "brac1_states.pdf");
  plot(t,u,problem.name + ": control", "time (s)", "control", "u",
                 "pdf", "brac1_control.pdf");
  plot(t,H,problem.name + ": Hamiltonian", "time (s)", "H", "H",
                    "pdf", "brac1_hamiltonian.pdf");
  }
```

The output from \mathcal{PSOPT} is summarized in the box below and shown in Figures 3.7, 3.8, which contain the elements of the state, and the control respectively.

```
PSOPT results summary
```




Figure 3.7: States for brachistochrone problem

Problem: Brachistochrone Problem

CPU time (seconds): 1.794096e+00

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 16:06:01 2019

Optimal (unscaled) cost function value: 8.247591e-01 Phase 1 endpoint cost function value: 8.247591e-01 Phase 1 integrated part of the cost: 0.000000e+00

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 8.247591e-01

Phase 1 maximum relative local error: 2.774874e-07 NLP solver reports: The problem has been solved!

3.3 Breakwell problem

Consider the following optimal control problem, which is known in the literature as the Breakwell problem [8]. The problem benefits from having an analytical solution, which is reported (with some errors) in the book by




Figure 3.8: Control for brachistochrone problem

Bryson and Ho (1975). Minimize the cost functional.

$$J = \int_0^{t_f} u(t)^2 \mathrm{d}t \tag{3.8}$$

subject to the dynamic constraints

$$\begin{array}{rcl}
\dot{x} & = & v \\
\dot{v} & = & u
\end{array} \tag{3.9}$$

the state dependent constraint

$$x(t) \le l \tag{3.10}$$

where $l = 0.1, t_f = 1$. and the boundary conditions

$$x(0) = 0$$

 $v(0) = 1$
 $x(t_f) = 0$
 $v(t_f) = -1$ (3.11)

The analytical solution of the problem (valid for $0 \le l \le 1/6$) is given by:

$$u(t) = \begin{cases} -\frac{2}{3l}(1 - \frac{t}{3l}), & 0 \le t \le 3l\\ 0, & 3l \le t \le 1 - 3l\\ -\frac{2}{3l}(1 - \frac{1-t}{3l}), & 1 - 3l \le t \le 1 \end{cases}$$
(3.12)

$$x(t) = \begin{cases} l\left(1 - \left(1 - \frac{t}{3l}\right)^3\right), & 0 \le t \le 3l\\ l, & 3l \le t \le 1 - 3l\\ l\left(1 - \left(1 - \frac{1 - t}{3l}\right)^3\right), & 1 - 3l \le t \le 1 \end{cases}$$
(3.13)

$$v(t) = \begin{cases} \left(1 - \frac{t}{3l}\right)^2, & 0 \le t \le 3l\\ 0, & 3l \le t \le 1 - 3l\\ \left(1 - \frac{1 - t}{3l}\right)^2, & 1 - 3l \le t \le 1 \end{cases}$$
(3.14)

$$\lambda_x(t) = \begin{cases} \frac{2}{9l^2}, & 0 \le t \le 3l\\ 0, & 3l \le t \le 1 - 3l\\ -\frac{2}{9l^2}, & 1 - 3l \le t \le 1 \end{cases}$$
(3.15)

$$\lambda_v(t) = \begin{cases} \frac{2}{3l} (1 - \frac{t}{3l}), & 0 \le t \le 3l\\ 0, & 3l \le t \le 1 - 3l\\ \frac{2}{3l} (1 - \frac{1 - t}{3l}), & 1 - 3l \le t \le 1 \end{cases}$$
 (3.16)

where $\lambda_x(t)$ and $\lambda_v(t)$ are the costates. The analytical optimal value of the objective function is J = 4/(9l) = 4.4444444. The \mathcal{PSOPT} code that solves this problem is shown below.

```
/////// (866 1661 1 MANAGOSM 161 1411 1666161666)
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
          adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
 return (0);
////////////// Define the integrand (Lagrange) cost function //////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters,
          adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble u = controls[0];
return 0.5*u*u;
```

```
adouble xdot, vdot;
 double g = 1.0;
double a = 0.5*g;
 adouble x = states[ CINDEX(1) ];
adouble v = states[ CINDEX(2) ];
 adouble u = controls[ CINDEX(1) ]:
 xdot = v;
 vdot = u:
 derivatives[ CINDEX(1) ] = xdot;
derivatives[ CINDEX(2) ] = vdot;
int iphase, Workspace* workspace)
 adouble x0 = initial_states[ CINDEX(1) ];
adouble v0 = initial_states[ CINDEX(2) ];
adouble xf = final_states[ CINDEX(1) ];
adouble vf = final_states[ CINDEX(2) ];
 e[ CINDEX(1) ] = x0;
e[ CINDEX(2) ] = v0;
 e[ CINDEX(3) ] = xf;
e[ CINDEX(4) ] = vf;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem }
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
problem.name
            = "Breakwell Problem":
  problem.outfilename
                    = "breakwell.txt";
```

```
problem.nphases
  problem.nlinkages
  psopt_level1_setup(problem);
problem.phases(1).nstates
   problem.phases(1).ncontrols = 1;
   problem.phases(1).nevents = 4;
  problem.phases(1).npath
problem.phases(1).nodes
                       = 0;
                            = "[200]";
  psopt_level2_setup(problem, algorithm);
DMatrix lambda, H:
double xL = -2.0;
  double vL = -2.0;
double xU = 0.1;
   double vU = 2.0;
  double uL = -10.0;
  double uU = 10.0;
  double x0 = 0.0;
double v0 = 1.0;
   double xf = 0.0:
  double vf = -1.0;
  problem.phases(1).bounds.lower.states(1) = xL;
  problem.phases(1).bounds.lower.states(2) = vL;
  problem.phases(1).bounds.upper.states(1) = xU;
problem.phases(1).bounds.upper.states(2) = vU;
   problem.phases(1).bounds.lower.controls(1) = uL;
  problem.phases(1).bounds.upper.controls(1) = uU;
   problem.phases(1).bounds.lower.events(1) = x0;
   problem.phases(1).bounds.lower.events(2) = v0;
problem.phases(1).bounds.lower.events(3) = xf;
   problem.phases(1).bounds.lower.events(4) = vf;
  problem.phases(1).bounds.upper.events(1) = x0;
problem.phases(1).bounds.upper.events(2) = v0;
problem.phases(1).bounds.upper.events(3) = xf;
problem.phases(1).bounds.upper.events(4) = vf;
   problem.phases(1).bounds.lower.StartTime
                                 = 0.0;
  problem.phases(1).bounds.upper.StartTime
  problem.phases(1).bounds.lower.EndTime
                                 = 1.0;
   problem.phases(1).bounds.upper.EndTime
                                 = 1.0;
```

```
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
  problem.dae
                  = &dae:
  problem.events = &events;
  problem.linkages = &linkages;
int nnodes
  int ncontrols
  int nstates
  DMatrix x_guess = zeros(nstates,nnodes);
  x_guess(1,colon()) = x0*ones(1,nnodes);
x_guess(2,colon()) = v0*ones(1,nnodes);
  problem.phases(1).guess.controls
                           = zeros(ncontrols,nnodes);
  = 1000;
= 1.e-6;
= "IPOPT";
  algorithm.nlp_iter_max
  algorithm.nlp_tolerance
algorithm.nlp_method
  algorithm.scaling
algorithm.derivatives
                           = "automatic";
                           = "automatic";
  algorithm.hessian
algorithm.mesh_refinement
                           = "exact";
= "automatic";
  algorithm.defect_scaling = "jacobian-based";
                               central-differences";
  algorithm.nlp_tolerance
psopt(solution, problem, algorithm);
DMatrix muE:
       = solution.get_states_in_phase(1);
      = solution.get_controls_in_phase(1);
       = solution.get_time_in_phase(1);
  lambda = solution.get_dual_costates_in_phase(1);
H = solution.get_dual_hamiltonian_in_phase(1);
muE = solution.get_dual_events_in_phase(1);
double l = 0.1;
  double t2 = 1.0-3*1;
  int nn = length(t);
  DMatrix ua(1,nn), xa(2,nn), pa(2,nn);
  for(int i=1:i <=nn:i++) {
```

```
if (t(i)<t1) {
             \begin{array}{lll} (t(i)t1) & \{ & \\ ua(1,i) & = -2.0/(3.0*1)*(1.0-t(i)/(3.0*1)); \\ xa(1,i) & = 1*( \ 1.0 - pow( \ (1.0-t(i)/(3.0*1), \ 3.0) \ ); \\ xa(2,i) & = pow( \ 1.0 - t(i)/(3.0*1), \ 2.0); \\ pa(1,i) & = 2.0/(9.0*1*1); \\ pa(2,i) & = 2.0/(3.0*1)*(1.0-t(i)/(3*1)); \end{array} 
         else if (t(i)>=t1 && t(i)<t2) {
            ua(1,i) = 0.0;
            xa(1,i) = 0.0;

xa(1,i) = 1;

xa(2,i) = 0.0;

pa(1,i) = 0.0;
            pa(2,i) = 0.0;
       felse if (t(i)>=t2) {
    ua(1,i) = -2.0/(3*1)*(1.0-(1.0-t(i))/(3.0*1));
    xa(1,i) = 1*(1.0 - pow( (1.0-(1.0-t(i))/(3.0*1)), 3.0));
    xa(2,i) = -pow(1.0-(1.0-t(i))/(3.0*1), 2.0);
    pa(1,i) = -2.0/(9.0*1*1);
    pa(2,i) = 2.0/(3.0*1)*(1.0-(1.0-t(i))/(3*1));
       }
x.Save("x.dat");
    u.Save("u.dat");
t.Save("t.dat");
    lambda.Save("p.dat");
H.Save("H.dat");
plot(t,x,t,xa,problem.name+": states", "time (s)", "states","x v xa va");
    plot(t,u,t,ua,problem.name+": controls","time (s)", "control", "u ua");
    plot(t,lambda,t,pa, problem.name+": costates","time (s)", "costates", "l_x l_v la_x la_v");
    plot(t,H,problem.name+": Hamiltonian","time (s)", "H", "H");
    plot(t.x.t.xa.problem.name+": states", "time (s)", "states", "x v xa va", "pdf", "breakwell states.pdf");
    plot(t,u,t,ua,problem.name+": control", "time (s)", "control", "u ua", "pdf", "breakwell_control.pdf");
    plot(t,lambda,t,pa, problem.name+": costates", "time (s)", "costates", "l_x l_v la_x la_v", "pdf", "breakwell_cdstates.pdf");
```

The output from \mathcal{PSOPT} is summarized in the following box and shown in Figures 3.9 and 3.10, which contain the elements of the state and the control, respectively, and Figure 3.11 which shows the costates. The figures include curves with the analytical solution for each variable, which is very close to the computed solution.




Figure 3.9: States for Breakwell problem

3.4 Bryson-Denham problem

Consider the following optimal control problem, which is known in the literature as the Bryson-Denham problem [7]. Minimize the cost functional




Figure 3.10: Control for Breakwell problem




Figure 3.11: Costates for Breakwell problem

$$J = x_3(t_f) \tag{3.17}$$

subject to the dynamic constraints

$$\begin{array}{rcl}
 \dot{x}_1 & = & x_2 \\
 \dot{x}_2 & = & u \\
 \dot{x}_3 & = & \frac{1}{2}u^2
 \end{array}$$
(3.18)

the state bound

$$0 \le x_1 \le 1/9 \tag{3.19}$$

and the boundary conditions

$$x_1(0) = 0$$

 $x_2(0) = 1$
 $x_3(0) = 0$
 $x_1(t_f) = 0$
 $x_2(t_f) = -1$ (3.20)

The \mathcal{PSOPT} code that solves this problem is shown below.

```
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
         adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
 adouble x3f = final_states[ CINDEX(3) ];
 return x3f;
adouble integrand_cost(adouble* states, adouble* controls,
         adouble* parameters, adouble& time, adouble* xad,
         int iphase, Workspace* workspace)
 return 0.0;
```

```
void dae(adouble* derivatives, adouble* path, adouble* states,
     adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
  adouble x1 = states[CINDEX(1)];
adouble x2 = states[CINDEX(2)];
  adouble x3 = states[CINDEX(3)];
  adouble u = controls[CINDEX(1)];
  derivatives[ CINDEX(1) ] = x2:
  derivatives[ CINDEX(2) ] = u;
  derivatives[ CINDEX(3) ] = u*u/2;
void events(adouble* e, adouble* initial_states, adouble* final_states,
        adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble x10 = initial_states[ CINDEX(1) ];
adouble x20 = initial_states[ CINDEX(2) ];
  adouble x30 = initial_states[ CINDEX(3) ];
adouble x1f = final_states[ CINDEX(1) ];
  adouble x2f = final_states[ CINDEX(2) ];
  e[ CINDEX(1) ] = x10;
  e[ CINDEX(1) ] = x10;
e[ CINDEX(2) ] = x20;
e[ CINDEX(3) ] = x30;
e[ CINDEX(4) ] = x1f;
  e[CINDEX(5)] = x2f;
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem \mbox{\}}
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
problem.name
                = "Bryson-Denham Problem";
  problem.outfilename
                          = "bryden.txt";
problem.nphases
               = 1:
  problem.nlinkages
```

```
psopt_level1_setup(problem);
problem.phases(1).nstates = 3;
problem.phases(1).ncontrols = 1;
    problem.phases(1).nevents
    problem.phases(1).npath
                                             = "[10, 50]";
    problem.phases(1).nodes
   psopt_level2_setup(problem, algorithm);
DMatrix x, u, t;
DMatrix lambda, H;
problem.phases(1).bounds.lower.states(1) = 0.0;
   problem.phases(1).bounds.lower.states(2) = -10.0;
problem.phases(1).bounds.lower.states(3) = -10.0;
   problem.phases(1).bounds.upper.states(1) = 1.0/9.0;
problem.phases(1).bounds.upper.states(2) = 10.0;
problem.phases(1).bounds.upper.states(3) = 10.0;
   problem.phases(1).bounds.lower.controls(1) = -10.0;
problem.phases(1).bounds.upper.controls(1) = 10.0;
   problem.phases(1).bounds.lower.events(1) = 0.0;
problem.phases(1).bounds.lower.events(2) = 1.0;
    problem.phases(1).bounds.lower.events(3) = 0.0;
problem.phases(1).bounds.lower.events(4) = 0.0;
    problem.phases(1).bounds.lower.events(5) = -1.0;
    problem.phases(1).bounds.upper.events(1) = 0.0;
    problem.phases(1).bounds.upper.events(2) = 1.0;
    problem.phases(1).bounds.upper.events(3) = 0.0;
    problem.phases(1).bounds.upper.events(4)
                                          = 0.0;
    problem.phases(1).bounds.upper.events(5) = -1.0;
   problem.phases(1).bounds.lower.StartTime = 0.0;
problem.phases(1).bounds.lower.EndTime = 0.0;
problem.phases(1).bounds.lower.EndTime = 0.0;
                                            = 0.0;
= 50.0;
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
    problem.dae = &dae;
   problem.events = &events;
problem.linkages = &linkages;
DMatrix x0(3,10);
   x0(1,colon()) = linspace(0.0, 0.0, 10);
x0(2,colon()) = linspace(1.0,-1.0, 10);
x0(3,colon()) = linspace(0.0, 0.0, 10);
    problem.phases(1).guess.controls
                                       = zeros(1,10);
   problem.phases(1).guess.states
problem.phases(1).guess.time
                                        = x0:
                                        = linspace(0.0, 0.5, 10);
```

```
/////// Enter algorithm options
.......
  algorithm.nlp_method algorithm.scaling
                       = "IPOPT":
                       = "automatic";
= "automatic";
  algorithm.derivatives
                       = 1000;
  algorithm.nlp_iter_max
  algorithm.nlp_tolerance
                       = 1.e-6:
psopt(solution, problem, algorithm);
//////// Extract relevant variables from solution structure ////////
      = solution.get_states_in_phase(1);
      = solution.get_controls_in_phase(1);
  t = solution.get_time_in_phase(1);
lambda = solution.get_dual_costates_in_phase(1);
H = solution.get_dual_hamiltonian_in_phase(1);
x.Save("x.dat");
  t.Save("t.dat");
  lambda.Save("lambda.dat");
H.Save("H.dat");
plot(t,x,problem.name, "time (s)", "states", "x1 x2 x3");
  plot(t,u, problem.name ,"time (s)", "control", "u");
  plot(t,lambda, problem.name ,"time (s)", "lambda", "1 2 3");
  plot(t,x,problem.name, "time (s)", "states", "x1 x2 x3",
                   "pdf", "bryden_states.pdf");
  plot(t,lambda, problem.name ,"time (s)", "lambda", "1 2 3",
                   "pdf", "bryden_lambda.pdf");
}
```

The output from \mathcal{PSOPT} is summarized in the following box and shown in Figures 3.12 and 3.13, which contain the elements of the state and the control, respectively.

```
PSOPT results summary
```




Figure 3.12: States for Bryson Denham problem

Problem: Bryson-Denham Problem CPU time (seconds): 2.550521e+00

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 15:31:41 2019

Optimal (unscaled) cost function value: 3.999539e+00 Phase 1 endpoint cost function value: 3.999539e+00 Phase 1 integrated part of the cost: 0.000000e+00

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 6.474067e-01

Phase 1 maximum relative local error: 6.431444e-05 NLP solver reports: The problem has been solved!

3.5 Bryson's maximum range problem

Consider the following optimal control problem, which is known in the literature as the Bryson's maximum range problem [7]. Minimize the cost functional

$$J = x(t_f) (3.21)$$




Figure 3.13: Control for Bryson Denham problem

subject to the dynamic constraints

$$\dot{x} = vu_1
\dot{y} = vu_2
\dot{v} = a - gu_2$$
(3.22)

the path constraint

$$u_1^2 + u_2^2 = 1 (3.23)$$

and the boundary conditions

$$x(0) = 0$$

 $y(0) = 0$
 $v(0) = 0$
 $y(t_f) = 0.1$ (3.24)

where $t_f = 2$, g = 1 and a = 0.5g. The \mathcal{PSOPT} code that solves this problem is shown below.

```
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states, adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble x = final states[0]:
  return (-x);
///////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
   return 0.0;
void dae(adouble* derivatives, adouble* path, adouble* states,
       adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble xdot, ydot, vdot;
  double g = 1.0;
  double \bar{a} = 0.5*g;
  adouble x = states[ CINDEX(1) ];
adouble y = states[ CINDEX(2) ];
adouble v = states[ CINDEX(3) ];
  adouble u1 = controls[ CINDEX(1) ];
adouble u2 = controls[ CINDEX(2) ];
  ydot = v*u2;
  vdot = a-g*u2;
  derivatives[ CINDEX(1) ] = xdot;
derivatives[ CINDEX(2) ] = ydot;
derivatives[ CINDEX(3) ] = vdot;
  path[ CINDEX(1) ] = (u1*u1) + (u2*u2);
int iphase, Workspace* workspace)
  adouble x0 = initial_states[ CINDEX(1) ];
  adouble y0 = initial_states[ CINDEX(2) ];
adouble v0 = initial_states[ CINDEX(3) ];
adouble xf = final_states[ CINDEX(1) ];
adouble yf = final_states[ CINDEX(2) ];
  e[ CINDEX(1) ] = x0;
e[ CINDEX(2) ] = y0;
e[ CINDEX(3) ] = v0;
  e[ CINDEX(4) ] = yf;
```

```
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
\ensuremath{//} No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
 Prob problem;
= "Bryson Maximum Range Problem";
 problem.name
 problem.outfilename
                  = "brymr.txt";
Define problem level constants & do level 1 setup ////////
problem.nphases
          = 1:
 problem.nlinkages
 psopt_level1_setup(problem);
problem.phases(1).nstates
 problem.phases(1).npath
problem.phases(1).nodes
                      = "[20]";
 psopt_level2_setup(problem, algorithm);
DMatrix lambda, H:
double xL = -10.0;
 double xL = -10.0;
double yL = -10.0;
double vL = -10.0;
double xU = 10.0;
double yU = 10.0;
double vU = 10.0;
 double u1L = -10.0;
 double u2L = -10.0;
 double u1U = 10.0;
double u2U = 10.0;
 double x0 = 0.0;
```

```
double y0 = 0.0;
double v0 = 0.0;
   double yf = 0.1;
   problem.phases(1).bounds.lower.states(1) = xL;
   problem.phases(1).bounds.lower.states(2) = yL;
problem.phases(1).bounds.lower.states(3) = vL;
   problem.phases(1).bounds.upper.states(1) = xU;
problem.phases(1).bounds.upper.states(2) = yU;
   problem.phases(1).bounds.upper.states(3) = vU;
   problem.phases(1).bounds.lower.controls(1) = u1L;
   problem.phases(1).bounds.lower.controls(2) = u2L:
   problem.phases(1).bounds.upper.controls(1) = u1U;
   problem.phases(1).bounds.upper.controls(2) = u2U;
   problem.phases(1).bounds.lower.events(1)
   problem.phases(1).bounds.lower.events(2) = y0;
problem.phases(1).bounds.lower.events(3) = v0;
   problem.phases(1).bounds.lower.events(4) = yf;
   problem.phases(1).bounds.upper.events(1) = x0;
   problem.phases(1).bounds.upper.events(2) = y0;
problem.phases(1).bounds.upper.events(3) = v0;
   problem.phases(1).bounds.upper.events(4) = yf;
   problem.phases(1).bounds.upper.path(1) = 1.0;
problem.phases(1).bounds.lower.path(1) = 1.0;
   problem.phases(1).bounds.lower.StartTime
   problem.phases(1).bounds.upper.StartTime
                                            = 0.0;
   problem.phases(1).bounds.lower.EndTime
                                            = 2.0;
   problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
   problem.dae
                           = &dae;
   problem.events = &events;
   problem.linkages = &linkages;
= problem.phases(1).ncontrols;
= problem.phases(1).nstates;
   int nstates
   DMatrix x_guess = zeros(nstates,nnodes);
   x_guess(1,colon()) = x0*ones(1,nnodes);
   x_guess(2,colon()) = y0*ones(1,nnodes);
x_guess(3,colon()) = v0*ones(1,nnodes);
   problem.phases(1).guess.controls
                                       = zeros(ncontrols,nnodes);
   algorithm.nlp_iter_max
                                       = 1000;
   algorithm.nlp_tolerance algorithm.nlp_method
                                       = 1.e-4;
                                       = "IPOPT";
                                       = "automatic";
   algorithm.scaling
```

```
algorithm.derivatives
                          = "automatic"
                          = "automatic";
  algorithm.mesh_refinement
  algorithm.collocation_method = "trapezoidal";
algorithm.defect_scaling = "jacobian-based"
  algorithm.ode_tolerance
psopt(solution, problem, algorithm);
= solution.get_states_in_phase(1);
      = solution.get_controls_in_phase(1);
      = solution.get_time_in_phase(1);
  lambda = solution.get_dual_costates_in_phase(1);
     = solution.get_dual_hamiltonian_in_phase(1);
x.Save("x.dat");
  u.Save("u.dat");
t.Save("t.dat");
  lambda.Save("lambda.dat");
H.Save("H.dat");
plot(t,x,problem.name+": states", "time (s)", "states", "x y v");
  \verb|plot(t,u,problem.name+": controls","time (s)", "controls", "u_1 u_2"); \\
  \label{eq:plot_problem.name+} $$ plot(t,x,problem.name+": states", "time (s)", "states","x y v", "pdf", "brymr_states.pdf");
   plot(t,u,problem.name+": controls","time (s)", "controls", "u_1 u_2", "pdf", "brymr_controls.pdf"); 
}
```

The output from \mathcal{PSOPT} is summarized in the box below and shown in Figures 3.14 and 3.15, which contain the elements of the state and the control, respectively.




Figure 3.14: States for Bryson's maximum range problem

Optimal (unscaled) cost function value: -1.712319e+00
Phase 1 endpoint cost function value: -1.712319e+00
Phase 1 integrated part of the cost: 0.000000e+00

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 2.000000e+00

Phase 1 maximum relative local error: 1.170448e-04 NLP solver reports: The problem has been solved!

3.6 Catalytic cracking of gas oil

Consider the following optimization problem, which involves finding optimal static parameters subject to dynamic constraints [15]. Minimize

$$J = \sum_{i=1}^{21} (y_1(t_i) - y_{m,1}(i))^2 + (y_2(t_i) - y_{m,2}(i))^2$$
 (3.25)

subject to the dynamic constraints

$$\dot{y}_1 = -(\theta_1 + \theta_3)y_1^2
\dot{y}_2 = \theta_1 y_1^2 - \theta_2 y_2$$
(3.26)




Figure 3.15: Controls for Bryson's maximum range problem

the parameter constraint

$$\theta_1 \ge 0$$

$$\theta_2 \ge 0$$

$$\theta_3 \ge 0$$
(3.27)

Note that, given the nature of the problem, the parameter estimation facilities of \mathcal{PSOPT} are used in this example. In this case, the observations function is simple:

$$g(x(t), u(t), p, t) = [y_1 \ y_2]^T$$

The \mathcal{PSOPT} code that solves this problem is shown below. The code includes the values of the measurement vectors $y_{m,1}$, and $y_{m,2}$, as well as the vector of sampling instants $\theta_i, i = 1, ..., 21$.

```
#include "psopt.h"
void observation_function( adouble* observations,
                   adouble* states, adouble* controls,
                   adouble* parameters, adouble& time, int k, adouble* xad, int iphase, Workspace* workspace)
{
    observations[ CINDEX(1) ] = states[ CINDEX(1) ];
observations[ CINDEX(2) ] = states[ CINDEX(2) ];
7-
void dae(adouble* derivatives, adouble* path, adouble* states,
      adouble* controls, adouble* parameters, adouble& time,
      adouble* xad, int iphase, Workspace* workspace)
  adouble y1 = states[CINDEX(1)];
  adouble y2 = states[CINDEX(2)];
  adouble theta1 = parameters[ CINDEX(1) ];
adouble theta2 = parameters[ CINDEX(2) ];
adouble theta3 = parameters[ CINDEX(3) ];
  derivatives[CINDEX(1)] = -(theta1 + theta3)*y1*y1;
derivatives[CINDEX(2)] = theta1*y1*y1 - theta2*y2;
}
int iphase, Workspace* workspace)
  // No events
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem }
int main(void)
  DMatrix y1meas, y2meas, tmeas;
  // Measured values of y1
y1meas = "[1.0,0.8105,0.6208,0.5258,0.4345,0.3903,0.3342,0.3034, \
            0.2735,0.2405,0.2283,0.2071,0.1669,0.153,0.1339,0.1265, \
0.12,0.099,0.087,0.077,0.069]";
  // Measured values of y2
y2meas = "[0.0,0.2,0.2886,0.301,0.3215,0.3123,0.2716,0.2551,0.2258, \
          0.1959,0.1789,0.1457,0.1198,0.0909,0.0719,0.0561,0.046,\
0.028,0.019,0.014,0.01]";
```

```
0.3.0.35.0.4.0.45.0.5.0.55.0.65.0.75.0.85.0.95]":
Alg algorithm;
Sol solution;
  Prob problem;
problem.nphases
                        = 0:
  problem.nlinkages
  psopt_level1_setup(problem);
problem.phases(1).nstates = 2;
problem.phases(1).ncontrols = 0;
  problem.phases(1).nevents = 0;
problem.phases(1).npath = 0;
  problem.phases(1).nodes = problem.phases(1).nobserved = 2;
problem.phases(1).nsamples = 21;
  psopt_level2_setup(problem, algorithm);
problem.phases(1).observation_nodes
problem.phases(1).observations
  problem.phases(1).observation_nodes
problem.phases(1).observations
problem.phases(1).residual_weights
= tmeas;
= (y1meas && y2meas);
= ones(2,21);
DMatrix x, p, t;
problem.phases(1).bounds.lower.states(1) = 0.0;
  problem.phases(1).bounds.lower.states(2) = 0.0;
  problem.phases(1).bounds.upper.states(1) = 2.0;
problem.phases(1).bounds.upper.states(2) = 2.0;
  problem.phases(1).bounds.lower.parameters(1) = 0.0;
  problem.phases(1).bounds.lower.parameters(2) = 0.0;
problem.phases(1).bounds.lower.parameters(3) = 0.0;
  problem.phases(1).bounds.upper.parameters(1) = 20.0;
problem.phases(1).bounds.upper.parameters(2) = 20.0;
  problem.phases(1).bounds.upper.parameters(3) = 20.0;
  problem.phases(1).bounds.lower.StartTime
                            = 0.0:
  problem.phases(1).bounds.upper.StartTime
```

```
problem.phases(1).bounds.lower.EndTime
                   = 0.95:
                   = 0.95;
 problem.phases(1).bounds.upper.EndTime
problem.dae = &dae;
 problem.events = &events;
problem.linkages = &linkages;
 problem.observation_function = & observation_function;
DMatrix state_guess(2, 40);
 state_guess(1,colon()) = linspace(1.0,0.069, 40);
 state_guess(2,colon()) = linspace(0.30,0.01, 40);
 Enter algorithm options
algorithm.nlp_method
                = "IPOPT":
                = "automatic";
 algorithm.scaling
                = "automatic";
= "Hermite-Simpson";
 algorithm.derivatives
  algorithm.collocation_method
 algorithm.nlp_iter_max
                = 1000;
                = 1.e-4;
 algorithm.nlp_tolerance
 algorithm.jac_sparsity_ratio
                = 0.52;
psopt(solution, problem, algorithm);
x = solution.get_states_in_phase(1);
t = solution.get_time_in_phase(1);
 p = solution.get_parameters_in_phase(1);
t.Save("t.dat");
 p.Print("Estimated parameters");
END OF FILE
```

The output from \mathcal{PSOPT} is summarized in the box below and shown in Figure 3.16, which shows the states of the system. The optimal parameters

found were:

$$\theta_1 = 11.40825702$$
 $\theta_2 = 8.123367918$
 $\theta_3 = 1.668727477$
(3.28)

PSOPT results summary

Problem: Catalytic cracking of gas oil

CPU time (seconds): 5.681664e+00

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 16:06:49 2019

Optimal (unscaled) cost function value: 4.326398e-03 Phase 1 endpoint cost function value: 4.326398e-03 Phase 1 integrated part of the cost: 0.000000e+00

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 9.500000e-01

Phase 1 maximum relative local error: 6.513072e-10 NLP solver reports: The problem has been solved!

3.7 Catalyst mixing problem

Consider the following optimal control problem, which attempts to determine the optimal mixing policy of two catalysts along the length of a tubular plug flow reactor involving several reactions [38]. The catalyst mixing problem is a typical bang-singular-bang problem. Minimize the cost functional

$$J = -1 + x_1(t_f) + x_2(t_f) (3.29)$$

subject to the dynamic constraints

$$\dot{x}_1 = u(10x_2 - x_1)
\dot{x}_2 = u(x_1 - 10x_2) - (1 - u)x_2$$
(3.30)

the boundary conditions

$$x_1(0) = 1$$

 $x_2(0) = 0$
 $x_1(t_f) \le 0.95$ (3.31)




Figure 3.16: States for catalytic cracking of gas oil problem

and the box constraints:

$$\begin{array}{ll} 0.9 & \leq x_1(t) \leq 1.0 \\ 0 & \leq x_2(t) \leq 0.1 \\ 0 & \leq u(t) \leq 1 \end{array} \tag{3.32}$$

where $t_f = 1$. The \mathcal{PSOPT} code that solves this problem is shown below.

```
return -(1.0-x1f-x2f):
adouble integrand_cost(adouble* states, adouble* controls,
             adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  return 0.0;
}
adouble* xad, int iphase, Workspace* workspace)
 adouble xdot, ydot, vdot;
 adouble x1 = states[ CINDEX(1) ]:
 adouble x2 = states[ CINDEX(2) ];
adouble u = controls[ CINDEX(1) ];
 }
void events(adouble* e, adouble* initial_states, adouble* final_states,
      adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
 adouble x10 = initial_states[ CINDEX(1)];
 adouble x20 = initial_states[ CINDEX(2) ];
adouble x1f = final_states[ CINDEX(1) ];
 e[ CINDEX(1) ] = x10;
e[ CINDEX(2) ] = x20;
e[ CINDEX(3) ] = x1f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
 \ensuremath{//} No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
Prob problem;
problem.name
  problem.outfilename
```

```
//////// Define problem level constants & do level 1 setup /////////
problem.nphases
problem.nlinkages
  psopt_level1_setup(problem);
problem.phases(1).nstates
  problem.phases(1).ncontrols = 1;
problem.phases(1).nevents = 3;
  problem.phases(1).npath
                      = 0:
  problem.phases(1).nodes
                                 = 40;
  psopt_level2_setup(problem, algorithm);
DMatrix x. u. t:
  DMatrix lambda, H;
problem.phases(1).bounds.lower.states(1) = 0.9;
problem.phases(1).bounds.lower.states(2) = 0.0;
  problem.phases(1).bounds.upper.states(1) = 1.0;
  problem.phases(1).bounds.upper.states(2) = 0.1;
  problem.phases(1).bounds.lower.controls(1) = 0.0;
problem.phases(1).bounds.upper.controls(1) = 1.0;
  problem.phases(1).bounds.lower.events(1) = 1.0;
  problem.phases(1).bounds.lower.events(2) = 0.0;
problem.phases(1).bounds.lower.events(3) = 0.0;
  problem.phases(1).bounds.upper.events(1) = 1.0;
  problem.phases(1).bounds.upper.events(2) = 0.0;
problem.phases(1).bounds.upper.events(3) = 0.95;
  problem.phases(1).bounds.lower.StartTime
                                = 0.0:
  problem.phases(1).bounds.upper.StartTime = 0.0;
                                = 1.0;
= 1.0;
  problem.phases(1).bounds.lower.EndTime
  problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
  problem.dae = &dae:
  problem.events = &events;
problem.linkages = &linkages;
DMatrix u0(1,40);
DMatrix x0(3,40);
```

```
DMatrix t0 = linspace(0.0, 1.0, 40);
  x0(1,colon()) = ones(1,40) - 0.085*t0;
x0(2,colon()) = 0.05*t0;
         = ones(1,40)- t0;
  problem.phases(1).guess.controls
                       = u0;
  problem.phases(1).guess.states
                        = x0;
  problem.phases(1).guess.time
                        = t0:
{\tt algorithm.nlp\_method}
                       = "TPOPT":
                       = "automatic";
= "automatic";
  algorithm.scaling
  algorithm.derivatives
                       = 1000;
= 1.e-6;
  algorithm.nlp_iter_max
  algorithm.nlp_tolerance
psopt(solution, problem, algorithm);
Extract relevant variables from solution structure
x = solution.get_states_in_phase(1)
  u = solution.get_controls_in_phase(1);
  t = solution.get_time_in_phase(1);
lambda = solution.get_dual_costates_in_phase(1);
  H = solution.get_dual_hamiltonian_in_phase(1);
x.Save("x.dat");
  u.Save("u.dat");
  t Save("t dat"):
  lambda.Save("lambda.dat");
  H.Save("H.dat");
plot(t,x,problem.name + ": states", "time (s)", "states", "x1 x2");
  plot(t,u,problem.name + ": control", "time (s)", "control", "u");
  plot(t,x,problem.name + ": states", "time (s)", "states", "x1 x2", \\ "pdf", "catmix_states.pdf");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.17 and 3.18, which contain the elements of the state and the control, respectively.




Figure 3.17: States for catalyist mixing problem




Figure 3.18: Control for catalyst mixing problem

3.8 Coulomb friction

Consider the following optimal control problem, which consists of a system that exhibits Coulomb friction [29]. Minimize the cost:

$$J = t_f (3.33)$$

subject to the dynamic constraints

$$\ddot{q}_1 = (-(k_1 - k_2)q_1 + k_2q_2 - \mu \operatorname{sign}(\dot{q}_1) + u_1)/m_1
\ddot{q}_2 = (k_2q_1 - k_2q_2 - \mu \operatorname{sign}(\dot{q}_2) + u_2)/m_2$$
(3.34)

and the boundary conditions

$$q_{1}(0) = 0$$

$$\dot{q}_{1}(0) = -1$$

$$q_{2}(0) = 0$$

$$\dot{q}_{2}(0) = -2$$

$$q_{1}(t_{f}) = 1$$

$$\dot{q}_{1}(t_{f}) = 0$$

$$q_{2}(t_{f}) = 2$$

$$\dot{q}_{2}(t_{f}) = 0$$
(3.35)

where $k_1 = 0.95$, $k_2=0.85$, $\mu = 1.0$, $m_1=1.1$, $m_2=1.2$. The \mathcal{PSOPT} code that solves this problem is shown below.

```
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
               adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
{
  return tf;
/////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
                adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  return 0.0;
}
void dae(adouble* derivatives, adouble* path, adouble* states.
      adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
            = states[ CINDEX(1) ]:
  adouble g1
  adouble q1dot = states[ CINDEX(3) ];
adouble q2 = states[ CINDEX(3) ];
adouble q2dot = states[ CINDEX(4) ];
  adouble u1 = controls[ CINDEX(1) ];
adouble u2 = controls[ CINDEX(2) ];
  double k1 = 0.95;
  double k2 = 0.85;
double mu = 1.0;
  double m1 = 1.1;
  double m2 = 1.2;
  double epsilon = 0.01;
   \begin{array}{lll} \mbox{derivatives[ CINDEX(1) ] = q1dot;} \\ \mbox{derivatives[ CINDEX(2) ] = ( $(-k1-k2)*q1+k2*q2-mu*smooth\_sign(q1dot,epsilon)+u1 )/m1;} \\ \mbox{derivatives[ CINDEX(3) ] = q2dot;} \\ \mbox{derivatives[ CINDEX(4) ] = ( $k2*q1-k2*q2-mu*smooth\_sign(q2dot,epsilon)+u2 )/m2;} \\ \end{array} 
void events(adouble* e, adouble* initial_states, adouble* final_states,
        adouble* parameters,adouble% t0, adouble% tf, adouble* xad, int iphase, Workspace* workspace)
{
```

```
adouble q1_0
           = initial_states[ CINDEX(1) ];
 adouble q1dot_0 = initial_states[ CINDEX(1) ];
adouble q2_0 = initial_states[ CINDEX(3) ];
 adouble q2dot_0 = initial_states[ CINDEX(4) ];
 adouble q1_f = final_states[ CINDEX(1) ];
adouble q1dot_f = final_states[ CINDEX(2) ];
adouble q2_f = final_states[ CINDEX(3) ];
adouble q2dot_f = final_states[ CINDEX(4) ];
 e[ CINDEX(1) ] = q1_0;
e[ CINDEX(2) ] = q1dot_0;
e[ CINDEX(3) ] = q2_0;
 e[ CINDEX(4) ] = q2dot_0;
 e[CINDEX(5)] = q1_f;
e[CINDEX(6)] = q1dot_f;
e[CINDEX(7)] = q2_f;
 e[ CINDEX(8) ] = q2dot_f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
= "Coulomb friction problem";
  problem.name
  problem.outfilename
                        = "coulomb.txt";
Define problem level constants & do level 1 setup /////////
problem.nphases = 1;
                        = 0;
  problem.nlinkages
  psopt_level1_setup(problem);
problem.phases(1).nstates
  problem.phases(1).ncontrols = 2;
problem.phases(1).nevents = 8;
problem.phases(1).npath = 0;
  problem.phases(1).nodes
                            = 40;
  psopt_level2_setup(problem, algorithm);
double q1_0 =
                0.0:
```

```
double dotq1_0 =
    double q2_0 =
    double dotq2_0 = double q1_f =
                               -2.0;
1.0;
    double dotq1_f =
double q2_f =
                                0.0;
    double dotq2_f =
                                0.0:
    problem.phases(1).bounds.lower.states(1) = -2.0;
    problem.phases(1).bounds.lower.states(2) = -20.0;
problem.phases(1).bounds.lower.states(3) = -2.0;
    problem.phases(1).bounds.lower.states(4) = -20.0;
    problem.phases(1).bounds.upper.states(1) = 2.0;
    problem.phases(1).bounds.upper.states(2) = 20.0;
problem.phases(1).bounds.upper.states(3) = 2.0;
    problem.phases(1).bounds.upper.states(4) = 20.0;
     problem.phases(1).bounds.lower.controls(1) = -4.0;
     problem.phases(1).bounds.lower.controls(2) = -4.0;
    problem.phases(1).bounds.upper.controls(1) = 4.0;
problem.phases(1).bounds.upper.controls(2) = 4.0;
    problem.phases(1).bounds.lower.events(1) = q1_0;
    problem.phases(1).bounds.lower.events(2) = dotq1_0;
problem.phases(1).bounds.lower.events(3) = q2_0;
    problem.phases(1).bounds.lower.events(4) = dotq2_0;
problem.phases(1).bounds.lower.events(5) = q1_f;
    problem.phases(1).bounds.lower.events(6) = dotq1_f;
problem.phases(1).bounds.lower.events(7) = q2_f;
problem.phases(1).bounds.lower.events(8) = dotq2_f;
    problem.phases(1).bounds.upper.events(1) = q1_0;
problem.phases(1).bounds.upper.events(2) = dotq1_0;
    problem.phases(1).bounds.upper.events(3) = q2_0;
problem.phases(1).bounds.upper.events(4) = dotq2_0;
    problem.phases(1).bounds.upper.events(5) = q1_f;
problem.phases(1).bounds.upper.events(6) = dotq1_f;
     problem.phases(1).bounds.upper.events(7) = q2_f;
    problem.phases(1).bounds.upper.events(8) = dotq2_f;
    problem.phases(1).bounds.lower.StartTime
                                                       = 0.0;
= 0.0;
    problem.phases(1).bounds.upper.StartTime
    problem.phases(1).bounds.lower.EndTime
                                                       = 4.0;
    problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
    problem.dae = &dae;
    problem.events = &events;
    problem.linkages = &linkages;
DMatrix x0(4,40);
     x0(1,colon()) = linspace(q1_0,q1_f, 40);
    x0(2,colon()) = linspace(dotq1_0, dotq1_f, 40);
x0(3,colon()) = linspace(q2_0, q2_f, 40);
x0(4,colon()) = linspace(dotq2_0, dotq2_f, 40);
                                                = zeros(2,40);
    problem.phases(1).guess.controls
problem.phases(1).guess.states
                                                = linspace(0.0, 4.0,40);
    problem.phases(1).guess.time
```

```
= "IPOPT";
  algorithm.nlp_method
                     = "automatic";
= "automatic";
  algorithm.scaling
  algorithm.derivatives algorithm.nlp_iter_max
  algorithm.nlp_tolerance
                     = 1.e-6;
psopt(solution, problem, algorithm);
  if (solution.error_flag) exit(0);
x = solution.get_states_in_phase(1);
u = solution.get_controls_in_phase(1);
  t = solution.get_time_in_phase(1);
x.Save("x.dat");
 u.Save("u.dat");
t.Save("t.dat");
DMatrix q12 = x(1,colon()) && x(3,colon());
 \label{eq:plot_plot} $$plot(t,q12,problem.name + ": states q1 and q2", $$ "time (s)", "states", "q1 q2");
  plot(t,u,problem.name + ": controls", "time (s)", "control", "u1 u2");
  plot(t,q12,problem.name + ": states q1 and q2",
            "time (s)", "states", "q1 q2"
"pdf", "coulomb_states.pdf");
```

The output from \mathcal{PSOPT} summarised in the box below and shown in Figures 3.19 and 3.20, which contain the elements of the state and the control, respectively.




Figure 3.19: States for Coulomb friction problem

Date and time of this run: Thu Feb 21 17:28:32 2019

Optimal (unscaled) cost function value: 2.104992e+00
Phase 1 endpoint cost function value: 2.104992e+00
Phase 1 integrated part of the cost: 0.000000e+00
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 2.104992e+00
Phase 1 maximum relative local error: 7.858415e-03
NLP solver reports: The problem has been solved!

3.9 DAE index 3 parameter estimation problem

Consider the following parameter estimation problem, which involves a differential-algebraic equation of index 3 with four differential states and one algebraic state [37].

The dynamics consists of the differential equations

$$\dot{x}_1(t) = x_3(t)
\dot{x}_2(t) = x_4(t)
\dot{x}_3(t) = \lambda(t)x_1(t)
\dot{x}_4(t) = \lambda(t)x_2(t)$$
(3.36)




Figure 3.20: Controls for Coulomb friction problem

and the algebraic equation

$$0 = L^2 - x_1(t)^2 - x_2(t)^2 (3.37)$$

where $x_j(t), j = 1, ..., 4$ are the differential states, $\lambda(t)$ is an algebraic state (note that algebraic states are treated as control variables), and L is a parameter to be estimated.

The observations function is given by:

$$y_1 = x_1 y_2 = x_2$$
 (3.38)

And the following least squares objective is minimised:

$$J = \sum_{k=1}^{n_s} \left[(y_1(t_k) - \hat{y}_1(t_k))^2 + (y_2(t_k) - \hat{y}_2(t_k))^2 \right]$$
 (3.39)

where $n_s = 20$, $t_1 = 0.5$ and $t_{20} = 10.0$.

The \mathcal{PSOPT} code that solves this problem is shown below.

```
////// Reference:
               Schittkowski (2002)
                                   #include "psopt.h"
adouble* parameters, adouble& time, int k, adouble* xad, int iphase, Workspace* workspace)
ł
    observations[ CINDEX(1) ] = states[ CINDEX(1) ];
observations[ CINDEX(2) ] = states[ CINDEX(2) ];
}
void dae(adouble* derivatives, adouble* path, adouble* states,
     adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
  // Variables
    adouble x1, x2, x3, x4, L, OMEGA, LAMBDA;
    adouble dx1, dx2, dx3, dx4;
  // Differential states
    x1 = states[CINDEX(1)];
x2 = states[CINDEX(2)];
    x3 = states[CINDEX(3)];
    x4 = states[CINDEX(4)];
  // Algebraic variables
  LAMBDA = controls[CINDEX(1)];
  // Parameters
  L = parameters[CINDEX(1)];
// Differential equations
   dx1 = x3:
    dx2 = x4:
    dx3 = LAMBDA*x1;
    dx4 = LAMBDA*x2:
    derivatives[ CINDEX(1) ] = dx1;
    derivatives[ CINDEX(2) ] = dx2;
derivatives[ CINDEX(3) ] = dx3;
    derivatives[ CINDEX(4) ] = dx4;
   // algebraic equation
    path[ CINDEX(1) ] = L*L - x1*x1 - x2*x2;
```

```
int iphase, Workspace* workspace)
{
   // no events
   return;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem }
Alg algorithm;
Sol solution;
  Prob problem;
problem.nphases
  problem.nlinkages
  psopt_level1_setup(problem);
problem.phases(1).nstates
  problem.phases(1).ncontrols = 1;
  problem.phases(1).nevents = 0;
problem.phases(1).npath = 1;
  problem.phases(1).nparameters = 1;
problem.phases(1).nodes = "[10,20,30]";
  problem.phases(1).nobserved
problem.phases(1).nsamples
                  = 2;
= 20;
  psopt_level2_setup(problem, algorithm);
Load data for parameter estimation
load_parameter_estimation_data(problem, iphase, "dae_i3.dat");
 problem.phases(1).observation_nodes.Print("observation nodes");
 problem.phases(1).observations.Print("observations");
problem.phases(1).residual_weights.Print("weights");
DMatrix x, u, p, t;
```

```
problem.phases(1).bounds.lower.states(1) = -2.0;
   problem.phases(1).bounds.lower.states(2) = -2.0;
problem.phases(1).bounds.lower.states(3) = -2.0;
    problem.phases(1).bounds.lower.states(4) = -2.0;
    problem.phases(1).bounds.upper.states(1) = 2.0;
    problem.phases(1).bounds.upper.states(2) = 2.0;
   problem.phases(1).bounds.upper.states(3) = 2.0;
problem.phases(1).bounds.upper.states(4) = 2.0;
   problem.phases(1).bounds.lower.controls(1) = -10.0;
problem.phases(1).bounds.upper.controls(1) = 10.0;
   problem.phases(1).bounds.lower.parameters(1) = 0.0;
problem.phases(1).bounds.upper.parameters(1) = 5.0;
   problem.phases(1).bounds.lower.path(1) = 0.0;
problem.phases(1).bounds.upper.path(1) = 0.0;
    problem.phases(1).bounds.lower.StartTime
   problem.phases(1).bounds.upper.StartTime = 0.5;
problem.phases(1).bounds.upper.StartTime = 0.5;
    problem.phases(1).bounds.lower.EndTime
                                            = 10.0:
    problem.phases(1).bounds.upper.EndTime
problem.events = &events;
problem.linkages = &linkages;
problem.observation_function = & observation_function;
(int) problem.phases(1).nsamples;
    int nnodes =
   DMatrix state_guess(4, nnodes);
DMatrix control_guess(1,nnodes);
   DMatrix param_guess(1,1);
   state_guess(1,colon()) = problem.phases(1).observations(1,colon());
state_guess(2,colon()) = problem.phases(1).observations(2,colon());
state_guess(3,colon()) = ones(1,nnodes);
    state_guess(4,colon()) = ones(1,nnodes);
   control_guess(1,colon()) = zeros(1,nnodes);
   param_guess = 0.5;
   problem.phases(1).guess.states
problem.phases(1).guess.time
problem.phases(1).guess.parameters
problem.phases(1).guess.controls
problem.phases(1).guess.controls
= state_guess;
= problem.phases(1).observation_nodes;
= param_guess;
= control_guess;
algorithm.nlp_method algorithm.scaling
                                       = "IPOPT":
                                       = "automatic";
   algorithm.derivatives = "automatic
algorithm.collocation_method = "Legendre";
into comparity ratio = 0.50;
                                      = "automatic";
psopt(solution, problem, algorithm);
```

```
x = solution.get_states_in_phase(1);
  u = solution.get_controls_in_phase(1);
  t = solution.get_time_in_phase(1);
  p = solution.get_parameters_in_phase(1);
x.Save("x.dat"):
  u.Save("u.dat");
  t Save("t dat"):
  p.Print("Estimated parameter");
DMatrix tm:
   tm = problem.phases(1).observation_nodes;
   ym = problem.phases(1).observations;
    plot(t,x(1,colon()),tm,ym(1,colon()),problem.name, "time (s)", "state x1", "x1 yhat1"); \\ plot(t,x(2,colon()),tm,ym(2,colon()),problem.name, "time (s)", "state x2", "x2 yhat2"); \\ plot(t,u,problem.name, "time (s)", "algebraic state u", "u"); \\ \end{cases} 
   "x1.pdf");
   plot(t,x(2,colon()),tm,ym(2,colon()),problem.name, "time (s)", "state x2", "x2 yhat2",
 "pdf", "x2.pdf");
   plot(t,u,problem.name, "time (s)", "algebraic state lambda", "lambda", "pdf", "lambda.pdf");
}
```

The output from \mathcal{PSOPT} summarised in the box below and shown in Figures 3.21 and 3.22, which compare the observations with the estimated outputs, and 3.23, which shows the algebraic state. The exact solution to the problem is L=1 and $\lambda(t)=-1$. The numerical solution obtained is L=1.000000188 and $\lambda(t)=-0.999868$. The 95% confidence interval for the estimated parameter is [0.9095289, 1.090471]




Figure 3.21: State x_1 and observations

```
Optimal (unscaled) cost function value: 1.965352e+01
Phase 1 endpoint cost function value: 1.965352e+01
Phase 1 integrated part of the cost: 0.000000e+00
Phase 1 initial time: 5.000000e-01
Phase 1 final time: 1.000000e+01
Phase 1 maximum relative local error: 8.341290e-08
NLP solver reports: The problem solved!
```

3.10 Delayed states problem 1

Consider the following optimal control problem, which consists of a linear system with delays in the state equations [29]. Minimize the cost functional:

$$J = x_3(t_f) \tag{3.40}$$

subject to the dynamic constraints

$$\dot{x}_1 = x_2(t)
\dot{x}_2 = -10x_1(t) - 5x_2(t) - 2x_1(t-\tau) - x_2(t-\tau) + u(t)
\dot{x}_3 = 0.5(10x_1^2(t) + x_2^2(t) + u^2(t))$$
(3.41)




Figure 3.22: State x_2 and observations




Figure 3.23: Algebraic state $\lambda(t)$

and the boundary conditions

$$x_1(0) = 1$$

 $x_2(0) = 1$
 $x_3(0) = 0$ (3.42)

where $t_f = 5$ and $\tau = 0.25$. The \mathcal{PSOPT} code that solves this problem is shown below.

```
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
               adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
   adouble x3f = final_states[CINDEX(3)];
  return x3f;
adouble integrand_cost(adouble* states, adouble* controls,
                adouble* parameters, adouble& time, adouble* xad,
               int iphase, Workspace* workspace)
  return 0.0;
void dae(adouble* derivatives, adouble* path, adouble* states,
      adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble x1delayed, x2delayed;
  double tau = 0.25;
  adouble x1 = states[CINDEX(1)];
adouble x2 = states[CINDEX(2)];
  adouble x3 = states[CINDEX(3)];
  get_delayed_state( &x1delayed, 1, iphase, time, tau, xad, workspace);
get_delayed_state( &x2delayed, 2, iphase, time, tau, xad, workspace);
  adouble u = controls[CINDEX(1)];
  derivatives[CINDEX(1)] = x2;
derivatives[CINDEX(2)] = -10*x1-5*x2-2*x1delayed-x2delayed+u;
```

```
// [uncomment the line below for approximate solution]
 derivatives[CINDEX(2)] = (-12*x1+(2*tau-6)*x2+u)/(1-tau);
derivatives[CINDEX(3)] = 0.5*(10*x1*x1+x2*x2+u*u);
void events(adouble* e, adouble* initial_states, adouble* final_states,
       adouble* parameters,adouble% t0, adouble% tf, adouble* xad,
       int iphase, Workspace* workspace)
 adouble x10 = initial_states[CINDEX(1)];
adouble x20 = initial_states[CINDEX(2)];
adouble x30 = initial_states[CINDEX(3)];
 e[CINDEX(1)] = x10;
 e[CINDEX(2)] = x20;
e[CINDEX(3)] = x30;
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
= "Time delay problem 1";
me = "delay1.txt";
  problem.name
  problem.outfilename
problem.nphases
  problem.nlinkages
                       = 0;
  psopt_level1_setup(problem);
problem.phases(1).nstates = 3;
  problem.phases(1).ncontrols = 1;
  problem.phases(1).nevents = 3;
problem.phases(1).npath = 0;
  problem.phases(1).npath
  problem.phases(1).nodes = "[30]";
  psopt_level2_setup(problem, algorithm);
```

```
DMatrix x, u, t;
   DMatrix lambda, H:
double x1I = -100.0
   double x2L = -100.0;
double x3L = -100.0;
   double x1U = 100.0;
   double x2U = 100.0:
   double x3U = 100.0;
   double uL = -100.0;
double uU = 100.0;
   problem.phases(1).bounds.lower.states(1) = x1L;
   problem.phases(1).bounds.lower.states(2) = x2L;
problem.phases(1).bounds.lower.states(3) = x3L;
   problem.phases(1).bounds.upper.states(1) = x1U;
   problem.phases(1).bounds.upper.states(2) = x2U;
   problem.phases(1).bounds.upper.states(3) = x3U;
   problem.phases(1).bounds.lower.controls(1) = uL;
   problem.phases(1).bounds.upper.controls(1) = uU;
   problem.phases(1).bounds.lower.events(1) = 1.0;
problem.phases(1).bounds.lower.events(2) = 1.0;
   problem.phases(1).bounds.lower.events(3) = 0.0;
   problem.phases(1).bounds.upper.events(1) = 1.0;
   problem.phases(1).bounds.upper.events(2) = 1.0;
problem.phases(1).bounds.upper.events(3) = 0.0;
   problem.phases(1).bounds.lower.StartTime
                                         = 0.0;
   problem.phases(1).bounds.upper.StartTime
                                         = 0.0:
                                         = 5.0:
   problem.phases(1).bounds.lower.EndTime
                                         = 5.0;
   problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
   problem.dae
                        = &dae:
   problem.events = &events;
   problem.linkages = &linkages;
DMatrix x0(3,60);
   x0(1,colon()) = linspace(1.0,1.0, 60);
x0(2,colon()) = linspace(1.0,1.0, 60);
   x0(3,colon()) = linspace(0.0,0.0, 60);
   problem.phases(1).guess.controls
                                    = zeros(1,60);
   = "TPOPT":
   algorithm.nlp_method
   algorithm.scaling
algorithm.derivatives
                                    = "automatic";
= "automatic":
   algorithm.nlp_iter_max
                                    = 1000;
                                    = 1.e-6;
   algorithm.nlp_tolerance
```

```
algorithm.collocation_method
              = "Hermite-Simpson";
  algorithm.mesh_refinement
               "automatic";
psopt(solution, problem, algorithm);
x = solution.get_states_in_phase(1);
 u = solution.get_controls_in_phase(1);
t = solution.get_time_in_phase(1);
x.Save("x.dat"):
 u.Save("u.dat");
t.Save("t.dat");
"pdf", "delay1_controls.pdf");
}
```

The output from \mathcal{PSOPT} summarised in the box below and shown in Figures 3.24 and 3.25, which contain the elements of the state and the control, respectively.




Figure 3.24: States for time delay problem 1

NLP solver reports: The problem has been solved!

3.11 Dynamic MPEC problem

Consider the following optimal control problem, which involves special handling of a system with a discontinuous right hand side [4]. Minimize the cost functional:

$$J = [y(2) - 5/3]^2 + \int_0^2 y^2(t)dt$$
 (3.43)

subject to

$$\dot{y} = 2 - \operatorname{sgn}(y) \tag{3.44}$$

and the boundary condition

$$y(0) = -1 (3.45)$$

Note that there is no control variable, and the analytical solution of this problem satisfies $\dot{y}(t) = 3$, $0 \le t \le 1/3$, and $\dot{y}(t) = 1$, $1/3 \le t \le 2$.

In order to handle the discontinuous right hand side, the problem is converted into the following equivalent problem, which has three algebraic (control) variables. This type of problem is known in the literature as a




Figure 3.25: Control for time delay problem 1

dynamic MPEC problem.

$$J = [y(2) - 5/3]^2 + \int_0^2 (y^2(t) + \rho \{p(t)[s(t) + 1] + q(t)[1 - s(t)]\}) dt \quad (3.46)$$

subject to

$$\dot{y} = 2 - \text{sgn}(y)
0 = -y(t) - p(t) + q(t)$$
(3.47)

the boundary condition

$$y(0) = -1 (3.48)$$

and the bounds:

$$-1 \le s(t) \le 1,$$

 $0 \le p(t),$
 $0 \le q(t).$ (3.49)

The \mathcal{PSOPT} code that solves this problem is shown below.

```
////// This is part of the PSOPT software library, which//////////
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
                 adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble y_f = final_states[ CINDEX(1) ];
  return pow( y_f - (5.0/3.0) , 2.0);
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters,
                adouble& time, adouble* xad, int iphase, Workspace* workspace)
   adouble y = states[ CINDEX(1) ];
adouble s = controls[ CINDEX(1) ];
adouble p = controls[ CINDEX(2) ];
adouble q = controls[ CINDEX(3) ];
   adouble retval:
   double rho = 1.e3;
   retval = y*y + rho*( p*(s+1.0)+ q*(1.0-s));
   return retval;
}
void dae(adouble* derivatives, adouble* path, adouble* states,
       adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
  adouble y = states[ CINDEX(1) ];
adouble ydot;
  adouble s = controls[ CINDEX(1) ];
  adouble p = controls[ CINDEX(2) ];
adouble q = controls[ CINDEX(3) ];
  ydot = 2.0 -s;
  derivatives[ CINDEX(1) ] = ydot;
  path[CINDEX(1)] = -y - p + q;
}
void events(adouble* e, adouble* initial_states, adouble* final_states,
         adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble v0 = initial states[ CINDEX(1) ]:
```

```
e[ CINDEX(1) ] = y0;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem \,
int main(void)
Alg algorithm;
Sol solution;
Prob problem;
"mpec.txt";
Define problem level constants & do level 1 setup ////////
......
  problem.nphases
          = 1:
                   = 0;
 problem.nlinkages
 psopt_level1_setup(problem);
problem.phases(1).nstates = 1;
problem.phases(1).ncontrols = 3;
 problem.phases(1).ncontrols - o,
problem.phases(1).nevents = 1;
problem.phases(1).npath = 1;
 problem.phases(1).npath
problem.phases(1).nodes
                   = "[20]";
 psopt_level2_setup(problem, algorithm);
DMatrix y, controls, s, p, q, t;
......
 double y0 = -1.0;
  problem.phases(1).bounds.lower.states(1) = -10.0;
  problem.phases(1).bounds.upper.states(1) = 10.0;
  problem.phases(1).bounds.lower.controls(1) = -1.0;
  problem.phases(1).bounds.lower.controls(2) = 0.0;
  problem.phases(1).bounds.lower.controls(3) = 0.0;
```

```
problem.phases(1).bounds.upper.controls(1) = 1.0;
problem.phases(1).bounds.upper.controls(2) = inf;
  problem.phases(1).bounds.upper.controls(3) = inf;
  problem.phases(1).bounds.lower.events(1) = y0;
problem.phases(1).bounds.upper.events(1) = y0;
  problem.phases(1).bounds.upper.path(1) = 0.0;
problem.phases(1).bounds.lower.path(1) = 0.0;
  problem.phases(1).bounds.lower.EndTime
                               = 2.0;
= 2.0;
  problem.phases(1).bounds.upper.EndTime
problem.events = &events;
  problem.linkages = &linkages;
int nnodes
int ncontrols = problem.phases(1).nodes(1);
int ncontrols = problem.phases(1).
                 = problem.phases(1).ncontrols;
= problem.phases(1).nstates;
  DMatrix x_guess = zeros(nstates,nnodes);
  x_guess(1,colon()) = y0*ones(1,nnodes);
  algorithm.nlp_iter_max
                           = 1000:
  algorithm.nlp_tolerance
                           = 1.e-4;
= "IPOPT";
  algorithm.nlp_method
algorithm.scaling
                           = "automatic";
  algorithm.derivatives
                           = "automatic";
  algorithm.mesh_refinement
  algorithm.collocation_method = "trapezoidal";
    algorithm.defect_scaling = "jacobian-based"
  algorithm.ode tolerance
psopt(solution, problem, algorithm);
= solution.get_states_in_phase(1);
  controls = solution.get_controls_in_phase(1);
      = solution.get_time_in_phase(1);
= controls(1,colon());
        = controls(2,colon());
= controls(3,colon());
```

```
y.Save("y.dat");
  controls.Save("controls.dat");
t.Save("t.dat");
plot(t,y,problem.name+": state", "time (s)", "state","y");
  plot(t,s,problem.name+": algebraic variable s","time (s)", "s", "s");
  plot(t,p,problem.name+": algebraic variable p","time (s)", "p", "p");
  plot(t,q,problem.name+": algebraic variable q","time (s)", "q", "q");\\
   plot(t,s,problem.name+": algebraic variable s","time (s)", "s", "s", "pdf", "s.pdf"); \\
  plot(t,p,problem.name+": algebraic variable p","time (s)", "p", "p",
     "pdf", "p.pdf");
  plot(t,q,problem.name+": algebraic variable q","time (s)", "q", "q",\\
     "pdf", "q.pdf");
```

The output from \mathcal{PSOPT} summarised in the box below and shown in Figures 3.26, 3.27, 3.28, and 3.29.




Figure 3.26: State y for dynamic MPEC problem

3.12 Geodesic problem

This problem is about calculating the geodesic curve ¹ that joins two points on Earth using optimal control. The problem is posed in the form of estimating the shortest fligh path for an airliner to fly from New Yorks's JFK to London's LHR airport.

The formulation is as follows. Find the trajectories for the elevation and azimuth angles $\theta(t)$ and $\phi(t) \in [0, t_f]$ to minimize the cost functional

$$J = \int_0^{t_f} \sqrt{\dot{x}^2 + \dot{y}^2 + \dot{z}^2} dt \tag{3.50}$$

subject to the dynamic constraints

$$\dot{x} = V \sin(\theta) \cos(\phi)
\dot{y} = V \sin(\theta) \sin(\phi)
\dot{z} = V \cos(\theta)$$
(3.51)

The path constraint, which corresponds to the Earth's spheroid 2 shape:

$$\frac{x^2}{a^2} + \frac{y^2}{a^2} + \frac{z^2}{b^2} - 1.0 = 0 {(3.52)}$$

¹See http://mathworld.wolfram.com/Geodesic.html

²See http://mathworld.wolfram.com/Ellipsoid.html




Figure 3.27: Algebraic variable s for dynamic MPEC problem




Figure 3.28: Algebraic variable p for dynamic MPEC problem




Figure 3.29: Algebraic variable q for dynamic MPEC problem

the boundary conditions, which correspond to the geographical coordinates of LHR (51.4700° N, 0.4543° W) and JFK (40.6413° N, 73.7781° W)

$$\begin{aligned}
 x(0) &= x_0 \\
 y(0) &= y_0 \\
 z(0) &= z_0 \\
 x(t_f) &= x_f \\
 y(t_f) &= y_f \\
 z(t_f) &= z_f
 \end{aligned}
 \tag{3.53}$$

and the control bounds

$$\begin{array}{rcl}
0 & \leq & \theta(t) & \leq & \pi \\
0 & \leq & \phi(t) & \leq & 2\pi
\end{array} \tag{3.54}$$

where x,y,z are the Cartesian coordinates (in km) with origin on the centre of Earth, t is time in hours, V=900 km/h corresponds to the cruising speed of a typical airliner, a=6384 km is the Earth's semi-major axis, and b=6353 km is the Earth's semi-minor axis, which is the length of the Earth's axis of rotation from the north pole to the south pole. For simplicity, the altitude of the aircraft is neglected.

The \mathcal{PSOPT} code that solves this problem is shown below.

```
PSOPT Example
////// Title: Geodesic calculation problem /////// Last modified: 22 February 2019
                                      #include "psopt.h"
typedef struct {
  double V;
double a;
  double b:
} Constants;
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
               adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase,Workspace* workspace)
ſ
}
////////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
               adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  Constants* C = (Constants*) workspace->user_data;
  double V = C \rightarrow V:
  adouble theta = controls[ CINDEX(1) ];
adouble phi = controls[ CINDEX(2) ];
  // These are the components of the velocity vector in spherical coordinates.
  adouble dxdt = V*sin(theta)*cos(phi);
adouble dydt = V*sin(theta)*sin(phi);
  adouble dzdt = V*cos(theta):
  // The integrand is the norm of the speed vector adouble L = sqrt( pow(dxdt,2.0) + pow(dydt,2.0)+pow(dzdt,2.0) );
}
adouble* xad, int iphase, Workspace* workspace)
  Constants* C = (Constants*) workspace->user_data;
  adouble x = states[ CINDEX(1) ];
  adouble y = states[ CINDEX(2) ];
adouble z = states[ CINDEX(3) ];
  double V = C->V; // Speed
  double a = C->a; // Semi-major axis
double b = C->b; // Semi-minor axis
  // These are the angles of the velocity vector in spherical coordinates
  adouble theta = controls[ CINDEX(1) ];
```

```
adouble phi = controls[ CINDEX(2) ];
  // Simple kinematic equations of motion in spherical coordinates
  adouble dxdt = V*sin(theta)*cos(phi);
adouble dydt = V*sin(theta)*sin(phi);
adouble dzdt = V*cos(theta);
  derivatives[ CINDEX(1) ] = dxdt;
derivatives[ CINDEX(2) ] = dydt;
  derivatives[ CINDEX(3) ] = dzdt;
  \ensuremath{//} This is the geodesic constraint to stay on the surface of the spheroid
  path[ CINDEX(1) ] = x*x/(a*a) + y*y/(a*a) + z*z/(b*b) - 1.0;
}
int iphase, Workspace* workspace)
 adouble x0 = initial_states[ CINDEX(1) ];
adouble y0 = initial_states[ CINDEX(2) ];
adouble z0 = initial_states[ CINDEX(3) ];
adouble xf = final_states[ CINDEX(1) ];
adouble yf = final_states[ CINDEX(2) ];
adouble zf = final_states[ CINDEX(3) ];
  e[ CINDEX(1) ] = x0;
 e[ CINDEX(1) ] = x0;
e[ CINDEX(2) ] = y0;
e[ CINDEX(3) ] = z0;
e[ CINDEX(4) ] = xf;
e[ CINDEX(5) ] = yf;
e[ CINDEX(6) ] = zf;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace) {
 \ensuremath{//} No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
  Prob problem:
= "Geodesic problem";
  problem.name
  problem.outfilename
                          = "geodesic.txt";
problem.nphases
                     = 1:
```

```
problem.nlinkages
     psopt_level1_setup(problem);
= 3:
     problem.phases(1).nstates
     problem.phases(1).ncontrols = 2;
     problem.phases(1).nevents = 6;
problem.phases(1).npath =
                                            = "[30]":
     problem.phases(1).nodes
     psopt_level2_setup(problem, algorithm);
Constants* C = new Constants;
    problem.user_data = (void*) C;
   C->V = 900.00; // Speed in km/h C->a = 6384.0; // Earth's semi-major axis in km
    C->b = 6353.0; // Earth's semi-minor axis in km
     double a = C->a:
     double b = C->b;
     double yL = -a;
double zL = -b;
     double xU = a;
double yU = a;
     double zU = b;
     double thetaL = 0.0:
     double thetaU = pi;
double phiL = 0.0;
double phiU = 2.0*pi;
     // Coordinates of LHR: 51.4700 N, 0.4543 W
     double lat_lhr = 51.74*pi/180.0;
double lon_lhr = 0.4543*pi/180.0;
      // Coordinates of JFK: 40.6413 N, 73.7781 W
     double lat_jfk = 40.6413*pi/180.0;
double lon_jfk = 73.7781*pi/180.0;
     // Below, theta=0 corresponds to 90 deg latitude north, growing positive towards the south // while phi=0 corresponds to 0 longitude, growing positive towards the east.
     double thetaf = pi/2.0 - lat_lhr; // Final elevation angle, for LHR in London double phif = 2.0*pi - lon_lhr; // Final azimuth angle, for LHR in London
     // Here we calculate initial and final Cartesian coordinates using
     // the parametric equations of the ellipsoid.
     double x0 = a*sin(theta0)*cos(phi0);
    double x0 = a*sin(theta0)*cos(phi0);
double y0 = a*sin(theta0)*sin(phi0);
double z0 = b*cos(theta0);
double xf = a*sin(thetaf)*cos(phif);
double yf = a*sin(thetaf)*sin(phif);
double zf = b*cos(thetaf);
     problem.phases(1).bounds.lower.states(1) = xL;
     problem.phases(1).bounds.lower.states(1) = XL;
problem.phases(1).bounds.lower.states(2) = yL;
problem.phases(1).bounds.lower.states(3) = zL;
     problem.phases(1).bounds.upper.states(1) = xU;
problem.phases(1).bounds.upper.states(2) = yU;
problem.phases(1).bounds.upper.states(3) = zU;
     problem.phases(1).bounds.lower.controls(1) = thetaL;
     problem.phases(1).bounds.upper.controls(1) = thetail;
problem.phases(1).bounds.lower.controls(2) = phiL;
problem.phases(1).bounds.upper.controls(2) = phiU;
```

```
problem.phases(1).bounds.lower.events(1) = x0;
    problem.phases(1).bounds.lower.events(2) = y0;
    problem.phases(1).bounds.lower.events(3) = z0;
    problem.phases(1).bounds.lower.events(4) = xf;
    problem.phases(1).bounds.lower.events(5) = yf;
    problem.phases(1).bounds.lower.events(6) = zf;
    problem.phases(1).bounds.upper.events(1) = x0;
problem.phases(1).bounds.upper.events(2) = y0;
    problem.phases(1).bounds.upper.events(3) = z0;
    problem.phases(1).bounds.upper.events(4) = xf;
    problem.phases(1).bounds.upper.events(5) = yf;
problem.phases(1).bounds.upper.events(6) = zf;
    problem.phases(1).bounds.lower.path(1) = 0.0;
    problem.phases(1).bounds.upper.path(1) = 0.0;
                                               = 0.0;
= 0.0;
    {\tt problem.phases (1).bounds.lower.StartTime}
    problem.phases(1).bounds.upper.StartTime
    problem.phases(1).bounds.lower.EndTime
                                               = 3.0: // lower bound in hours
    problem.phases(1).bounds.upper.EndTime
                                               = 10.0; // upper bound in hours
problem.integrand_cost = &integrand_cost;
    problem.endpoint_cost
problem.dae = &dae;
    problem.events = &dae;
problem.events = &events;
    problem.linkages
                          = &linkages;
= 30;
    int nnodes
                                        = problem.phases(1).ncontrols;
= problem.phases(1).nstates;
    int ncontrols
    int nstates
    DMatrix u_guess = zeros(ncontrols,nnodes);
DMatrix x_guess = zeros(nstates,nnodes);
DMatrix time_guess = linspace(0.0,7.0,nnodes);
   u_guess(1,colon()) = linspace(theta0,thetaf,nnodes);
u_guess(2,colon()) = linspace(phi0,phif,nnodes);
    for (int i = 1;i<= nnodes;i++) {
      x_guess(1,i) = a*sin(u_guess(1,i))*cos(u_guess(2,i));
     x_guess(2,i) = a*sin(u_guess(1,i))*sin(u_guess(2,i));
x_guess(3,i) = b*cos(u_guess(1,i));
    problem.phases(1).guess.controls
                                          = u_guess;
    problem.phases(1).guess.states
problem.phases(1).guess.time
                                          = x_guess;
= time_guess;
= 1000;
= 1.e-4;
= "IPOPT";
    algorithm.nlp_iter_max
    algorithm.nlp_tolerance
    algorithm.nlp_method
                                         = "automatic";
    algorithm.scaling algorithm.derivatives
                                         = "automatic";
= "automatic";
= "trapezoidal";
= "automatic";
    algorithm.collocation_method algorithm.mesh_refinement
```

```
psopt(solution, problem, algorithm);
DMatrix states
           = solution.get_states_in_phase(1);
  DMatrix states - solution.get_controls_in_phase(1);

DMatrix t = solution.get_time_in_phase(1);
  DMatrix x = states(1,colon());
  DMatrix y = states(2,colon());
DMatrix z = states(3,colon());
  DMatrix theta = controls(1,colon());
DMatrix phi = controls(2,colon());
x.Save("x.dat"):
  z.Save("z.dat");
  theta.Save("theta.dat");
  phi.Save("phi.dat"):
plot3(x(1,colon()), y(1,colon()), z(1,colon()),
    "Geodesic problem", "x", "y", "z", NULL, NULL, "30,97");
  plot3(x(1,colon()), y(1,colon()), z(1,colon()),
   "Geodesic problem", "x", "y", "z", "pdf", "trajectory.pdf", "30,97");
plot(t,states,problem.name, "time (s)", "states", "x y z");
  plot(t,controls,problem.name, "time (s)", "controls", "theta phi");
}
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.30, 3.31 and 3.32, which show the flight path, the elements of the state vector, and the elements of the control vector, respectively. Note that \mathcal{PSOPT} predicts that the length of the shortest flightpath is 5,540.4 km, and the flight time is 6 hours 9 min.

PSOPT results summary

Problem: Geodesic problem

CPU time (seconds): 1.405730e+01

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Fri Feb 22 08:38:37 2019

Optimal (unscaled) cost function value: 5.540469e+03 Phase 1 endpoint cost function value: 0.000000e+00 Phase 1 integrated part of the cost: 5.540469e+03

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 6.156077e+00

Phase 1 maximum relative local error: 1.530431e-04 NLP solver reports: The problem has been solved!

3.13 Goddard rocket maximum ascent problem

Consider the following optimal control problem, which is known in the literature as the Goddard rocket maximum ascent problem [6]. Find t_f and $T(t) \in [t_0, t_f]$ to minimize the cost functional

$$J = h(t_f) \tag{3.55}$$

subject to the dynamic constraints

$$\dot{v} = \frac{1}{m}(T - D) - g$$

$$\dot{h} = v$$

$$\dot{m} = -\frac{T}{c}$$
(3.56)

the boundary conditions:

$$v(0) = 0$$

 $h(0) = 1$
 $m(0) = 1$
 $m(t_f) = 0.6$ (3.57)

the state bounds:

$$0.0 \le v(t) \le 2.0$$

 $1.0 \le h(t) \le 2.0$
 $0.6 \le m(t) \le 1.0$ (3.58)




Figure 3.30: Flight path for geodesic problem




Figure 3.31: States for geodesic problem




Figure 3.32: Controls for geodesic problem

and the control bounds

$$0 \le T(t) \le 3.5 \tag{3.59}$$

where

$$D = D_0 v^2 \exp(-\beta h) g = 1/(h^2) , (3.60)$$

 $D_0 = 310$, $\beta = 500$, and c = 0.5, $0.1 \le t_f \le 1$. The \mathcal{PSOPT} code that solves this problem is shown below.

```
{
    adouble hf = final_states[1];
return -hf;
}
////////// Define the integrand (Lagrange) cost function /////
{
  return 0.0;
}
adouble vdot, hdot, mdot:
  adouble v = states[0];
  adouble h = states[1];
adouble m = states[2];
  adouble T = controls[0];
  double c
              = 0.5;
           = 310.0;
= 500.0;
  double DO
  double beta
            = 1.0/(h*h);
= D0*v*v*exp(-beta*h);
  adouble g
  adouble D
  vdot = 1.0/m*(T-D)-g;
hdot = v;
mdot = -T/c;
  derivatives[0] = vdot;
derivatives[1] = hdot;
derivatives[2] = mdot;
void events(adouble* e, adouble* initial_states, adouble* final_states,
        adouble* parameters.adouble& t0. adouble& tf. adouble* xad.
        int iphase, Workspace* workspace)
 adouble vi = initial_states[0];
adouble hi = initial_states[1];
adouble mi = initial_states[2];
adouble mf = final_states[2];
   e[0] = vi;
   e[1] = hi;
e[2] = mi;
e[3] = mf;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
{
```

```
int main(void)
.
........
Alg algorithm;
Sol solution;
  Prob problem;
= "Goddard Rocket Maximum Ascent";
  problem.outfilename
                    = "goddard.txt";
= 1:
  problem.nphases
  problem.nlinkages
                    = 0;
  psopt_level1_setup(problem);
problem.phases(1).nstates
                = 3:
 problem.phases(1).nevents = 4;
problem.phases(1).revents = 4;
  problem.phases(1).npath
                 = 0;
  problem.phases(1).nodes
  psopt_level2_setup(problem, algorithm);
double v L = 0:
 double v_L = 0;
double h_L = 1.0;
double m_L = 0.6;
double v_U = 2.0;
double h_U = 2.0;
  double m_U = 1.0;
 double T_L = 0.0;
double T_U = 3.5;
  double v_i = 0.0;
  double h_i = 1.0;
double m_i = 1.0;
  double m_f = 0.6;
  \label{eq:problem.phases(1).bounds.lower.states(1) = v_L;} problem.phases(1).bounds.lower.states(2) = h_L;}
  problem.phases(1).bounds.lower.states(3) = m_L;
  problem.phases(1).bounds.upper.states(1) = v_U;
problem.phases(1).bounds.upper.states(2) = h_U;
```

```
problem.phases(1).bounds.upper.states(3) = m_U;
   problem.phases(1).bounds.lower.controls(1) = T_L;
problem.phases(1).bounds.upper.controls(1) = T_U;
   problem.phases(1).bounds.lower.events(1) = v_i;
   problem.phases(1).bounds.lower.events(2) = h_i;
problem.phases(1).bounds.lower.events(3) = m_i;
   problem.phases(1).bounds.lower.events(4) = m_f;
   problem.phases(1).bounds.upper.events(1) = v_i;
problem.phases(1).bounds.upper.events(2) = h_i;
problem.phases(1).bounds.upper.events(3) = m_i;
problem.phases(1).bounds.upper.events(4) = m_f;
   problem.phases(1).bounds.lower.StartTime
                                      = 0.0:
   problem.phases(1).bounds.upper.StartTime
                                       = 0.1;
= 1.0;
   problem.phases(1).bounds.lower.EndTime
   problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
problem.dae = &dae;
problem.events = &events;
   problem.linkages = &linkages;
DMatrix x0(3,20);
   x0(1,colon()) = linspace(v_i,v_i, 20);
x0(2,colon()) = linspace(h_i,h_i, 20);
x0(3,colon()) = linspace(m_i,m_i, 20);
   problem.phases(1).guess.controls
                                  = T_U*ones(1,20);
   problem.phases(1).guess.states
problem.phases(1).guess.time
                                   = linspace(0.0, 15.0, 20);
algorithm.nlp_method
                                  = "IPOPT";
                                  = "automatic":
   algorithm.scaling
   algorithm.derivatives
                                  = "automatic";
                                  = 1000;
   algorithm.nlp_iter_max
   algorithm.nlp_tolerance
   algorithm.collocation_method
algorithm.mesh_refinement
algorithm.mr_max_iterations
                                  = "trapezoidal";
                                  = "automatic";
= 5;
psopt(solution, problem, algorithm);
x = solution.get_states_in_phase(1);
u = solution.get_controls_in_phase(1);
   t = solution.get_time_in_phase(1);
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.33 and 3.34, which contain the elements of the state and the control, respectively.

3.14 Hang glider

This problem is about the range maximisation of a hang glider in the presence of a specified thermal draft [4]. Find t_f and $C_L(t), t \in [0, t_f]$, to min-




Figure 3.33: States for Goddard rocket problem




Figure 3.34: Control for Goddard rocket problem

imise,

$$J = x(t_f) \tag{3.61}$$

subject to the dynamic constraints

$$\dot{x} = v_x
\dot{y} = v_y
\dot{v}_x = \frac{1}{m}(-L\sin\eta - D\cos\eta)
\dot{v}_y = \frac{1}{m}(L\cos\eta - D\sin\eta - W)$$
(3.62)

where

$$C_D = C_0 + kC_L^2$$

$$v_r = \sqrt{v_x^2 + v_y^2}$$

$$D = \frac{1}{2}C_D\rho S v_r^2$$

$$L = \frac{1}{2}C_L\rho S v_r^2$$

$$X = \left(\frac{x}{R} - 2.5\right)^2$$

$$u_a = u_M(1 - X) \exp(-X)$$

$$V_y = v_y - ua$$

$$\sin \eta = \frac{V_y}{v_r}$$

$$\cos \eta = \frac{v_x}{v_r}$$

$$W = mg$$

$$(3.63)$$

The control is bounded as follows:

$$0 \le C_L \le 1.4$$
 (3.64)

and the following boundary conditions:

$$x(0) = 0,$$
 $x(t_f) = \text{free}$
 $y(0) = 1000,$ $y(t_f) = 900$
 $v_x(0) = 13.227567500,$ $v_x(t_f) = 13.227567500$
 $v_y(0) = -1.2875005200,$ $v_y(t_f) = -1.2875005200$ (3.65)

With the following parameter values:

$$u_M = 2.5,$$
 $m = 100.0$
 $R = 100.0,$ $S = 14,$
 $C_0 = 0.034,$ $\rho = 1.13$
 $k = 0.069662,$ $q = 9.80665$ (3.66)

 \mathcal{PSOPT} code that solves this problem is shown below.

```
////// Title: Hang glider problem ////// Last modified: 11 July 2009
                                     ////// Reference: PROPT User Manual
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
                adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble xf = final_states[CINDEX(1)];
  return -(xf);
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters,
               adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
 return 0.0;
}
void dae(adouble* derivatives, adouble* path, adouble* states,
      adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
   adouble CL = controls[ CINDEX(1) ]:
   adouble x = states[ CINDEX(1) ]
              = states[ CINDEX(2) ];
   adouble y = states[ CINDEX(2)
adouble vx = states[ CINDEX(3) ];
   adouble vy
              = states[ CINDEX(4) ];
  double m = 100.0,
double uM = 2.5,
double CO = 0.034,
double S = 14.0,
                    g = 9.80665;
R = 100.0;
                  k = 100.0;
k = 0.069662;
rho = 1.13;
   adouble sin eta, cos eta, D. L. CD. Vv. ua, X. vr. W:
   CD = CO + k*CL*CL;
   vr = sqrt(vx*vx + vy*vy);
   D = 0.5*CD*rho*S*vr*vr;
L = 0.5*CL*rho*S*vr*vr;
   X = pow(x/R - 2.5, 2.0);

ua = uM*(1.0-X)*exp(-X);
   Vy = vy-ua;
sin_eta = Vy/vr;
cos_eta = vx/vr;
```

```
W = m*g;
   derivatives[ CINDEX(1) ] =
   derivatives[ CINDEX(2) ] = vy;

derivatives[ CINDEX(3) ] = 1.0/m*(-L*sin_eta - D*cos_eta );

derivatives[ CINDEX(4) ] = 1.0/m*( L*cos_eta - D*sin_eta - W);
}
void events(adouble* e. adouble* initial states, adouble* final states,
          adouble* e, adouble* initial_states, adouble tf, adouble* xad, int iphase, Workspace* workspace)
{
   adouble x_i = initial_states[ CINDEX(1) ];
adouble y_i = initial_states[ CINDEX(2) ];
adouble vx_i = initial_states[ CINDEX(3) ];
adouble vy_i = initial_states[ CINDEX(4) ];
   adouble x_f = final_states[ CINDEX(1) ];
adouble y_f = final_states[ CINDEX(2) ];
adouble vx_f = final_states[ CINDEX(3) ];
adouble vy_f = final_states[ CINDEX(4) ];
   e[ CINDEX(1) ]
   e[CINDEX(2)]
e[CINDEX(3)]
                  = y_i;
= vx_i;
                  = vy_i;
   e[CINDEX(4)]
   e[ CINDEX(5) ] = y_f;
e[ CINDEX(6) ] = vx_f;
e[ CINDEX(7) ] = vy_f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
  // Single phase problem
}
int main(void)
Alg algorithm;
Sol solution;
   Prob problem;
problem.outfilename
////////// Define problem level constants & do level 1 setup /////////
```

```
problem.nphases = 1;
   problem.nlinkages
                                = 0;
   psopt_level1_setup(problem);
problem.phases(1).nstates
   problem.phases(1).nevents = 7;
problem.phases(1).nevents = 7;
   problem.phases(1).npath
   problem.phases(1).nodes
                                      = "[30 40 50 80]";
   psopt_level2_setup(problem, algorithm);
problem.phases(1).bounds.lower.controls(1) = 0.0;
   problem.phases(1).bounds.upper.controls(1) = 1.4;
   problem.phases(1).bounds.lower.events="[0.0,1000.0,13.2275675,-1.28750052,900.00,13.2275675,-1.28750052]";
   problem.phases(1).bounds.upper.events="[0.0,1000.0,13.2275675,-1.28750052,900.00,13.2275675,-1.28750052]";
   problem.phases(1).bounds.lower.StartTime = 0.0;
   problem.phases(1).bounds.upper.StartTime
                                      = 0.0;
   problem.phases(1).bounds.lower.EndTime
problem.phases(1).bounds.upper.EndTime
                                      = 0.1:
                                      = 200.0;
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
   problem.dae
                       = &dae:
   problem.events = &events;
   problem.linkages = &linkages;
int nnodes
             = problem.phases(1).nodes(1);
                    = problem.phases(1).ncontrols;
= problem.phases(1).nstates;
   int nstates
   DMatrix state_guess = zeros(nstates,nnodes);
DMatrix control_guess = 1.0*ones(ncontrols,nnodes);
DMatrix time_guess = linspace(0.0,105.0,nnodes);
   state_guess(1,colon()) = linspace(0.0, 1250, nnodes);
state_guess(2,colon()) = linspace(1000.0, 900.0, nnodes);
state_guess(3,colon()) = 13.23*ones(1,nnodes);
state_guess(4,colon()) = -1.288*ones(1,nnodes);
   problem.phases(1).guess.states = state_guess;
   problem.phases(1).guess.controls = control_guess;
problem.phases(1).guess.time = time_guess;
```

```
= 1000;
= 1.e-6;
= "IPOPT";
  algorithm.nlp_iter_max
  algorithm.nlp_tolerance
algorithm.nlp_method
algorithm.scaling
  algorithm.scaling
algorithm.derivatives
                         = "automatic";
                         = "automatic";
psopt(solution, problem, algorithm);
DMatrix states, CL, t, x, y, speeds;
         = solution.get_states_in_phase(1);
  CL
         = solution.get_controls_in_phase(1);
= solution.get_time_in_phase(1);
states.Save("states.dat");
  CL.Save("cL.dat");
t.Save("t.dat");
x = states(1,colon());
   = states(2,colon());
  speeds = (states(3,colon()) && states(4,colon()));
  plot(x,y,problem.name+": trajectory","x [m]", "y [m]", "traj");
 plot(t,speeds,problem.name+": speeds","time (s)", "speeds [m/s]", "dxdt dydt");
  plot(t,CL,problem.name+": control","time (s)", "control", "CL");
 \verb|plot(x,y,problem.name+": trajectory","x [m]", "y [m]", "traj", "pdf", "traj.pdf");|\\
 plot(t, speeds, problem.name+": speeds", "time (s)", "speeds [m/s]", "dxdt dydt", "pdf", "velocities.pdf");
  plot(t,CL,problem.name+": control - lift coefficient","time (s)", "CL", "CL", "pdf", "control.pdf");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.35, 3.36 and 3.37.




Figure 3.35: x - y trajectory for hang glider




Figure 3.36: Velocities for hang glider




Figure 3.37: Lift coefficient for hang glider problem

3.15 Hanging chain problem

Consider the following optimal control problem, which includes an integral constraint. Minimize the cost functional

$$J = \int_0^{t_f} \left[x \sqrt{1 + (\dot{x})^2} \right] dt \tag{3.67}$$

subject to the dynamic constraint

$$\dot{x} = u \tag{3.68}$$

the integral constraint:

$$\int_0^{t_f} \left[\sqrt{1 + \left(\frac{dx}{dt}\right)^2} \right] dt = 4 \tag{3.69}$$

the boundary conditions

$$\begin{array}{rcl}
x(0) & = & 1 \\
x(t_f) & = & 3
\end{array}$$
(3.70)

and the bounds:

$$-20 \le u(t) \le 20 -10 \le x(t) \le 10$$
 (3.71)

where $t_f = 1$. The \mathcal{PSOPT} code that solves this problem is shown below.

```
chain.cxx
                              ////// Title: Hanging chain problem
////// Last modified: 29 January 2009
                                  ////// This is part of the PSOPT software library, which /////////
////// is distributed under the terms of the GNU Lesser //////////
////// General Public License (LGPL)
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states, adouble* parameters,adouble& t0, adouble& tf,
             adouble* xad, int iphase, Workspace* workspace)
  return 0.0:
////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
             adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble x = states[ CINDEX(1)];
adouble dxdt = controls[CINDEX(1)];
  adouble L = x*sqrt(1.0+ pow(dxdt,2.0)):
  return L;
}
adouble* xad, int iphase, Workspace* workspace)
 adouble xdot, ydot, vdot;
 adouble x = states[ CINDEX(1) ];
 adouble dxdt = controls[ CINDEX(1) ];
 derivatives[ CINDEX(1) ] = dxdt;
}
adouble integrand( adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
 adouble G;
 adouble dxdt = controls[ CINDEX(1) ];
 G = sqrt( 1.0 + pow(dxdt,2.0));
 return G;
```

```
void events(adouble* e, adouble* initial_states, adouble* final_states,
      adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
 adouble x0 = initial_states[ CINDEX(1) ];
adouble xf = final_states[ CINDEX(1) ];
 adouble Q;
 // Compute the integral to be constrained
 \mathbb{Q} = integrate( integrand, xad, iphase, workspace );
 e[ CINDEX(1) ] = x0;
e[ CINDEX(2) ] = xf;
e[ CINDEX(3) ] = Q;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
^{\prime} // No linkages as this is a single phase problem }
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
= "Hanging chain problem";
  problem.name
  problem.outfilename
problem.nlinkages
                     = 0:
  psopt_level1_setup(problem);
problem.phases(1).nstates
                 = 1:
  problem.phases(1).ncontrols = 1;
problem.phases(1).nevents = 3;
problem.phases(1).revents = 3;
  problem.phases(1).npath
                  = "[20, 50]";
  problem.phases(1).nodes
  psopt_level2_setup(problem, algorithm);
```

```
problem.phases(1).bounds.lower.states(1) = -10.0;
problem.phases(1).bounds.upper.states(1) = 10.0;
   problem.phases(1).bounds.lower.controls(1) = -20.0;
problem.phases(1).bounds.upper.controls(1) = 20.0;
   problem.phases(1).bounds.lower.events(1) = 1.0;
problem.phases(1).bounds.lower.events(2) = 3.0;
   problem.phases(1).bounds.lower.events(3) = 4.0;
  problem.phases(1).bounds.upper.events(1) = 1.0;
problem.phases(1).bounds.upper.events(2) = 3.0;
problem.phases(1).bounds.upper.events(3) = 4.0;
   problem.phases(1).bounds.lower.StartTime
                                    = 0.0;
   problem.phases(1).bounds.upper.StartTime
   problem.phases(1).bounds.lower.EndTime
                                    = 1.0;
   problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
   problem.dae = &dae;
problem.events = &events;
   problem.linkages = &linkages;
= 2.0*ones(1,30);
   problem.phases(1).guess.controls
  problem.phases(1).guess.states
problem.phases(1).guess.time
                               = linspace(1.0,3.0, 30);
= linspace(0.0,1.0, 30);
= "IPOPT":
  algorithm.scaling
algorithm.derivatives
algorithm.nlp_iter_max
algorithm.nlp_tolerance
   algorithm.nlp method
                              = "automatic";
= "automatic";
= 1000;
                                = 1.e-6:
psopt(solution, problem, algorithm);
  if (solution.error_flag) exit(0);
DMatrix x, u, t;
   x = solution.get_states_in_phase(1);
u = solution.get_controls_in_phase(1);
            = solution.get_time_in_phase(1);
```

The output from \mathcal{PSOPT} is summarized in the text box below and in Figure 3.38, which illustrates the shape of the hanging chain.

3.16 Heat difussion problem

This example can be viewed as a simplified model for the heating of a probe in a kiln [3]. The dynamics are a spatially discretized form of a partial




Figure 3.38: State for hanging chain problem

differential equation, which is obtained by using the method of the lines. The problem is formulated on the basis of the state vector $\mathbf{x} = [x_1, \dots, x_M]^T$ and the control vector $\mathbf{u} = [v_1, v_2, v_3]^T$, as follows

$$\min_{\mathbf{u}(t)} J = \frac{1}{2} \int_0^T \left\{ (x_N(t) - x_d(t))^2 + \gamma v_1(t)^2 \right\} dt$$

subject to the differential constraints

$$\dot{x}_1 = \frac{1}{(a_1 + a_2 x_1)} \left[q_1 + \frac{1}{\delta^2} (a_3 + a_4 x_1) (x_2 - 2x_1 + v_2) + a_4 \left(\frac{x_2 - x_1}{2\delta} \right)^2 \right]$$

$$\dot{x}_i = \frac{1}{(a_1 + a_2 x_i)} \left[q_i + \frac{1}{\delta^2} (a_3 + a_4 x_i) (x_{i+1} - 2x_i + x_{i-1}) + a_4 \left(\frac{x_{i+1} - x_{i-1}}{2\delta} \right)^2 \right]$$
for $i = 2, \dots, M - 1$

$$\dot{x}_M = \frac{1}{(a_1 + a_2 x_M)} \left[q_M + \frac{1}{\delta^2} (a_3 + a_4 x_M) (v_3 - 2x_N + x_{M-1}) + a_4 \left(\frac{v_3 - x_{M-1}}{2\delta} \right)^2 \right]$$

the path constraints

$$0 = g(x_1 - v_1) - \frac{1}{2\delta}(a_3 + a_4x_1)(x_2 - v_2)$$
$$0 = \frac{1}{2\delta}(a_3 + a_4x_M)(v_3 - x_{M-1})$$

the control bounds

$$u_L < v_1 < u_U$$

and the initial conditions for the states:

$$x_i(0) = 2 + \cos(\pi z_i)$$

where

$$z_{i} = \frac{i-1}{M-1}, i = 1, \dots, M$$

$$x_{d}(t) = 2 - e^{\rho t}$$

$$q(z,t) = \left[\rho(a_{1} + 2a_{2}) + \pi^{2}(a_{3} + 2a_{4})\right] e^{\rho t} \cos(\pi z)$$

$$- a_{4}\pi^{2}e^{2\pi t} + (2a_{4}\pi^{2} + \rho a_{2})e^{2\rho t} \cos^{2}(\pi z)$$

$$q_{i} \equiv q(z_{i}, t), i = 1, \dots, M$$

with the parameter values $a_1 = 4$, $a_2 = 1$, $a_3 = 4$, $a_4 = -1$, $u_U = 0.1$, $\rho = -1$, T = 0.5, $\gamma = 10^{-3}$, g = 1, $u_L = -\infty$.

A spatial discretization given by M=10 was used. The problem was solved initially by using first 50 nodes, then the mesh was refined to 60 nodes, and an interpolation of the previous solution was employed as an initial guess for the new solution.

The PSOPT code that solves this problem is shown below.

```
/////// Title: Heat difussion process /////// Last modified: 09 July 2009
////// Reference: Betts (2001)
#include "psopt.h"
#define N_DISCRETIZATION 10
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
           adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
/////////////// Define the integrand (Lagrange) cost function //////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
```

```
int N = N_DISCRETIZATION;
      double gamma = 1.0e-3;
      double rho = -1.0;
      adouble yd = 2.0-exp(rho*time);
      adouble vN = states[ CINDEX(N) ]:
      adouble v1 = controls[ CINDEX(1) ];
      return 0.5*( pow(yN-yd,2.0) + gamma*pow(v1,2.0) );
adouble* xad, int iphase, Workspace* workspace)
{
    adouble u;
    double a1 = 4.0;
   double a2 = 1.0;
double a2 = 1.0;
double a3 = 4.0;
double a4 = -1.0;
double rho = -1.0;
double T = 0.5;
    double g = 1.0;
    int N = N_DISCRETIZATION;
   int i;
    double delta = 1.0/(N-1);
    adouble* y = states;
   adouble v1 = controls[ CINDEX(1) ];
adouble v2 = controls[ CINDEX(2) ];
adouble v3 = controls[ CINDEX(3) ];
   adouble y1 = y[CINDEX(1)];
adouble y2 = y[CINDEX(2)];
adouble yN = y[CINDEX(N)];
adouble yNm1 = y[CINDEX(N-1)];
   adouble x1 = 0;
adouble xN = 1;
   for(i=2;i<=(N-1);i++) {
   adouble yi = y[CINDEX(i)];
   adouble yimi = y[CINDEX(i-1)];
   adouble yipi = y[CINDEX(i+1)];
   adouble xi = ((double) (i-1);</pre>
         adouble qi = ((double) (i-1)) /( (double) (N-1));

adouble qi = (rho*(a1+2*a2) + pi*pi*(a3+2*a4))*exp(rho*time)*cos(pi*xi)

- a4*pi*pi*exp(2*rho*time) + (2*a4*pi*pi+rho*a2)*exp(2*rho*time)*pow(cos(pi*xi),2.0);
         \begin{split} \text{derivatives} & [\texttt{CINDEX(i)}] = 1.0/(a1 + a2 * yi) * (qi + (1.0/pow(delta, 2.0)) * \\ & (a3 + a4 * yi) * (yip1 - 2 * yi + yim1) + a4 * pow( (yip1 - yim1)/(2 * delta), 2.0) ); \end{split} 
   7
    \begin{array}{lll} \mbox{derivatives[ CINDEX(N) ] = } & 1.0/(a1+a2*yN)*(qN+(1.0/pow(delta,2.0))* \\ & (a3+a4*yN)*(v3-2*yN+yNm1)+a4*pow( (v3-yNm1)/(2*delta), \ 2.0) \ ); \end{array} 
    path[CINDEX(1)] = g*(y1-v1) - (1.0/(2*delta))*(a3+a4*y1)*(y2-v2);
```

```
path[CINDEX(2)] = (1.0/(2*delta))*(a3+a4*yN)*(v3-yNm1);
}
int iphase, Workspace* workspace)
{
 int i:
int N = N DISCRETIZATION:
for(i=1;i<= N; i++) {
    e[CINDEX(i)] = initial_states[CINDEX(i)];</pre>
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// Single phase problem
}
int main(void)
 int N = N_DISCRETIZATION;
Alg algorithm;
Sol solution;
 Prob problem;
= "heat.txt";
problem.nphases
        = 1;
 problem.nlinkages
               = 0;
 psopt_level1_setup(problem);
Define phase related information & do level 2 setup /////////
problem.phases(1).nstates = N;
problem.phases(1).ncontrols = 3;
 problem.phases(1).nevents = N;
            = 2;
 problem.phases(1).npath
 problem.phases(1).nodes
                  = "[20 50 60]":
```

```
psopt_level2_setup(problem, algorithm);
\label{eq:problem.phases(1).bounds.lower.states = zeros(N,1);} \\ problem.phases(1).bounds.upper.states = 3.0*ones(N,1); \\ \end{cases}
     problem.phases(1).bounds.lower.controls(1) = 0.0;
     problem.phases(1).bounds.lower.controls(2) = 0.0;
     problem.phases(1).bounds.lower.controls(3) = 0.0;
    problem.phases(1).bounds.upper.controls(1) = 0.1;
    problem.phases(1).bounds.upper.controls(2) = 3.0;
problem.phases(1).bounds.upper.controls(3) = 3.0;
problem.phases(1).bounds.upper.controls(3) = 3.0;
    for(i = 1; i<= N; i++ ) {
   double xi = ( (double) (i-1) ) /( (double) (N-1) );
double yI = 2.0+cos(pi*xi);</pre>
     problem.phases(1).bounds.lower.events(i) = yI;
problem.phases(1).bounds.upper.events(i) = yI;
    problem.phases(1).bounds.upper.path(1) = 0.0;
    problem.phases(1).bounds.upper.path(2) = 0.0;
problem.phases(1).bounds.lower.path(1) = 0.0;
     problem.phases(1).bounds.lower.path(2) = 0.0;
    problem.phases(1).bounds.lower.StartTime
problem.phases(1).bounds.upper.StartTime
                                                      = 0.0;
     problem.phases(1).bounds.lower.EndTime
                                                       = 0.5;
     problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
     problem.dae
                                 = &dae:
    problem.events = &events;
     problem.linkages = &linkages;
= problem.phases(1).nodes(1);
     int nnodes
                                               = problem.phases(1).ncontrols;
= problem.phases(1).nstates;
     int ncontrols
     int nstates
    DMatrix state_guess = zeros(nstates,nnodes);
DMatrix control_guess = zeros(ncontrols,nnodes);
DMatrix param_guess = zeros(0,0);
DMatrix time_guess = linspace(0,0.5,nnodes);
    for(i = 1; i<= N; i++ ) {
   double xi = ( (double) (i-1) ) /( (double) (N-1) );
double yI = 2.0+cos(pi*xi);
state_guess(i,colon()) = yI*ones(1,nnodes);</pre>
     control_guess(1,colon()) = linspace(0.1,0.1, nnodes);
control_guess(2,colon()) = state_guess(1,colon());
control_guess(3,colon()) = state_guess(N,colon());
```

```
auto_phase_guess(problem, control_guess, state_guess, param_guess, time_guess);
algorithm.nlp_iter_max
  algorithm.nlp_tolerance
algorithm.nlp_method
  algorithm.scaling algorithm.derivatives
                           = "automatic";
                            = "automatic";
= "jacobian-based";
  algorithm.defect_scaling
psopt(solution, problem, algorithm);
DMatrix y, u, t;
       = solution.get_states_in_phase(1);
       = solution.get_controls_in_phase(1);
= solution.get_time_in_phase(1);
y.Save("y.dat");
  u.Save("u.dat");
t.Save("t.dat");
  DMatrix x(N);
  for(i = 1; i<= N; i++ ) {
    x(i) = ( (double) (i-1) ) /( (double) (N-1) );
\verb|plot(t,u(1,colon()),problem.name+": control","time (s)", "control", "u");|\\
\label{local_problem.name+": control", "time (s)", "control", "v1", "pdf", "heat_control.pdf");
  plot(t,y(1,colon()),problem.name+": state","time (s)", "state", "x1");
  plot(t,y(1,colon()),problem.name+": state","time (s)", "state", "x1",
"pdf", "heat_state1.pdf");
  plot(t,y(N,colon()),problem.name+": state","time (s)", "state", "xN");
\label{local_problem.name+} $$ plot(t,y(N,colon()),problem.name+": state","time (s)", "state", "xN", "pdf", "heat_stateN.pdf"); 
  surf(x, t, y, problem.name, "x", "t", "h");
  \verb"surf(x, t, y, problem.name, "z", "t", "x", "pdf", "heat_surf.pdf");
```

The output from \mathcal{PSOPT} is summarized the box below. Figure 3.39 shows the control variable v_1 as a function of time. Figure 3.40 shows the

resulting temperature distribution.

PSOPT results summary

Problem: Heat diffusion process CPU time (seconds): 3.369917e+01

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 15:52:38 2019

Optimal (unscaled) cost function value: 4.417826e-05 Phase 1 endpoint cost function value: 0.000000e+00 Phase 1 integrated part of the cost: 4.417826e-05

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 5.000000e-01

Phase 1 maximum relative local error: 1.629944e-05 NLP solver reports: The problem has been solved!




Figure 3.39: Optimal control distribution for the heat diffusion process




Figure 3.40: Optimal temperature distribution for the heat diffusion process

3.17 Hypersensitive problem

Consider the following optimal control problem, which is known in the literature as the hypesensitive optimal control problem [34]. Minimize the cost functional

$$J = \frac{1}{2} \int_0^{t_f} [x^2 + u^2] dt \tag{3.72}$$

subject to the dynamic constraint

$$\dot{x} = -x^3 + u \tag{3.73}$$

and the boundary conditions

$$x(0) = 1.5$$

 $x(t_f) = 1$ (3.74)

where $t_f = 50$. The \mathcal{PSOPT} code that solves this problem is shown below.

```
////// Last modified: 05 January 2009
                                  #include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
             adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
{
 return 0.0;
}
adouble integrand_cost(adouble* states, adouble* controls,
             adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
   adouble x = states[0];
adouble u = controls[0];
   adouble L = 0.5*(x*x + u*u);
   return L;
}
void dae(adouble* derivatives, adouble* path, adouble* states,
     adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble x = states[0];
adouble u = controls[0];
  adouble xdot = -pow(x,3) + u;
  derivatives[0] = xdot;
void events(adouble* e, adouble* initial_states, adouble* final_states,
       adouble* parameters,adouble& t0, adouble& tf, adouble* xad,
       int iphase, Workspace* workspace)
  adouble xi = initial_states[0];
adouble xf = final_states[0];
  e[0] = xi;
e[1] = xf;
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
 // No linkages as this is a single phase problem \,
```

```
int main(void)
Alg algorithm;
Sol solution;
Prob problem;
problem.name
problem.nphases
  problem.nlinkages
                        = 0;
  psopt_level1_setup(problem);
problem.phases(1).nstates = 1;
problem.phases(1).ncontrols = 1;
  problem.phases(1).nevents = 2;
problem.phases(1).npath = 0;
  problem.phases(1).nodes
                         = "[25, 50]";
  psopt_level2_setup(problem, algorithm);
double xi = 1.5;
double xf = 1.0;
  problem.phases(1).bounds.lower.states(1) = -50.0;
problem.phases(1).bounds.upper.states(1) = 50.0;
  problem.phases(1).bounds.lower.controls(1) = -50.0;
problem.phases(1).bounds.upper.controls(1) = 50.0;
  problem.phases(1).bounds.lower.events(1) = xi;
problem.phases(1).bounds.upper.events(1) = xi;
  problem.phases(1).bounds.lower.events(2) = xf;
  problem.phases(1).bounds.upper.events(2) = xf;
  problem.phases(1).bounds.lower.StartTime
                            = 0.0;
  problem.phases(1).bounds.upper.StartTime
                            = 50.0;
= 50.0;
  problem.phases(1).bounds.lower.EndTime
  problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
```

```
problem.dae = &dae;
problem.events = &events;
problem.linkages = &linkages;
problem.phases(1).guess.controls
problem.phases(1).guess.states
problem.phases(1).guess.time
= zeros(1,60);
= linspace(1,1,60);
= linspace(0.0,50.0,60);
= "IPOPT";
  algorithm.nlp_method
  algorithm.scaling
algorithm.derivatives
                         = "automatic":
                         = "automatic";
  algorithm.nlp_iter_max
                        = 1000:
                         = 1.e-6;
  algorithm.nlp_tolerance
   algorithm.ps_method = "none";
algorithm.refinement_strategy = "TH";
 algorithm.mr_tolerance = 1.e-8;
algorithm.mr_max_iterations = 8;
psopt(solution, problem, algorithm);
= solution.get_states_in_phase(1);
= solution.get_controls_in_phase(1);
= solution.get_time_in_phase(1);
  DMatrix u
  DMatrix t
x.Save("x.dat");
  u.Save("u.dat");
  t.Save("t.dat");
plot(t,x,problem.name + ": state", "time (s)", "state", "x");
  \verb|plot(t,u,problem.name + ": control", "time (s)", "control", "u");|\\
  \verb|plot(t,x,problem.name + ": state", "time (s)", "state", "x", "pdf", "hyper_state.pdf");|
  plot(t,u,problem.name + ": control", "time (s)", "control", "u", "pdf", "hyper_control.pdf");
```




Figure 3.41: State for hypersensitive problem

The output from \mathcal{PSOPT} is summarized the box below and shown in the following plots that contain the elements of the state and the control, respectively.




Figure 3.42: Control for hypersensitive problem

3.18 Interior point constraint problem

Consider the following optimal control problem, which involves a scalar system with an interior point constraint on the state [24]. Minimize the cost functional

$$J = \int_0^1 [x^2 + u^2] dt \tag{3.75}$$

subject to the dynamic constraint

$$\dot{x} = u, \tag{3.76}$$

the boundary conditions

$$\begin{array}{rcl}
x(0) & = & 1, \\
x(1) & = & 0.75,
\end{array}$$
(3.77)

and the interior point constraint:

$$x(0.75) = 0.9. (3.78)$$

The problem is divided into two phases and the interior point constraint is accommodated as an event constraint at the end of the first phase. The \mathcal{PSOPT} code that solves this problem is shown below.

```
////// Title: Problem with interior point constraint ////// Last modified: 05 January 2009
                               /////// Reference: Miser Manual /////// (See PSOPT handbook for full reference)
                               #include "psopt.h"
adouble endpoint cost(adouble* initial states, adouble* final states,
            adouble* parameters, adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
 return 0.0;
}
////////////// Define the integrand (Lagrange) cost function ///////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble x = states[0];
adouble u = controls[0];
  adouble L = x*x + u*u;
  return L:
adouble* xad, int iphase, Workspace* workspace)
  adouble x = states[0]:
  adouble u = controls[0];
  derivatives[0] = xdot;
int iphase, Workspace* workspace)
  adouble xi = initial_states[0];
adouble xf = final_states[0];
  adouble x075;
  if (iphase == 1) {
    xi = initial_states[0];
   x075 = final_states[0];
    e[0] = xi;
   e[1] = x075:
```

```
if (iphase == 2) {
   xf = final_states[0];
  e[0] = xf;
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
 auto_link(linkages, &index, xad, 1, 2, workspace );
int main(void)
Alg algorithm;
Sol solution;
 Prob problem;
problem.nphases
 problem.nlinkages
                = 2:
 psopt_level1_setup(problem);
problem.phases(1).nstates = 1;
problem.phases(1).ncontrols = 1;
 problem.phases(1).nevents = 2;
             = 0;
 problem.phases(1).npath
 problem.phases(1).nodes
 problem.phases(2).nstates = 1;
problem.phases(2).ncontrols = 1;
 problem.phases(2).nevents
             = 0;
 problem.phases(2).npath
problem.phases(2).nodes
 psopt_level2_setup(problem, algorithm);
double xi = 1;
double x075 = 0.9;
double xf = 0.75;
 problem.phases(1).bounds.lower.states(1) = -1.0;
```

```
problem.phases(1).bounds.upper.states(1) = 1.0;
   problem.phases(1).bounds.lower.controls(1) = -1.0;
problem.phases(1).bounds.upper.controls(1) = 1.0;
   problem.phases(1).bounds.lower.events(1) = xi;
   problem.phases(1).bounds.upper.events(1) = xi;
   problem.phases(1).bounds.lower.events(2) = x075;
problem.phases(1).bounds.upper.events(2) = x075;
   problem.phases(1).bounds.lower.StartTime
   problem.phases(1).bounds.upper.StartTime
   problem.phases(1).bounds.lower.EndTime
                                    = 0.75:
   problem.phases(1).bounds.upper.EndTime
   ///////// Phase 2 bounds ///////////
   problem.phases(2).bounds.lower.states(1) = -1.0;
problem.phases(2).bounds.upper.states(1) = 1.0;
   problem.phases(2).bounds.lower.controls(1) = -1.0:
   problem.phases(2).bounds.upper.controls(1) = 1.0;
   problem.phases(2).bounds.lower.events(1) = xf;
   problem.phases(2).bounds.upper.events(1) = xf;
  problem.phases(2).bounds.lower.EndTime
problem.phases(2).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
problem.dae = &dae;
problem.events = &events;
problem.linkages = &linkages;
problem.phases(1).guess.controls = zeros(1,20); = linspace(xi,x075, 20); = linspace(xi,x075, 20);
  problem.phases(1).guess.states
problem.phases(1).guess.time
                                = linspace(0.0, 0.75, 20);
   = "IPOPT";
   algorithm.nlp_method
                                = "automatic";
   algorithm.scaling
   algorithm.scaling
algorithm.derivatives
algorithm.nlp_iter_max
                               = "automatic";
   algorithm.nlp_tolerance
                               = 1.e-6;
```

```
psopt(solution, problem, algorithm);
Extract relevant variables from solution structure
DMatrix x, u, t;
  x=solution.get_states_in_phase(1) || solution.get_states_in_phase(2);
  u=solution.get_controls_in_phase(1)|| solution.get_controls_in_phase(2);
t=solution.get_time_in_phase(1) || solution.get_time_in_phase(2);
x.Save("x.dat"):
 u.Save("u.dat");
t.Save("t.dat");
plot(t,x,problem.name + ": state", "time (s)", "state", "x");
  plot(t,u,problem.name + ": control", "time (s)", "control", "u");
  plot(t,x,problem.name + ": state", "time (s)", "state", "x",
              "pdf", "ipc_state.pdf");
```

The output from \mathcal{PSOPT} is summarized the box below and shown in the following plots that contain the elements of the state and the control, respectively.




Figure 3.43: State for interior point constraint problem

Phase 1 maximum relative local error: 2.352899e-08
Phase 2 endpoint cost function value: 0.000000e+00
Phase 2 integrated part of the cost: 2.597438e-01
Phase 2 initial time: 7.500000e-01
Phase 2 final time: 1.000000e+00
Phase 2 maximum relative local error: 6.986779e-09
NLP solver reports: The problem has been solved!

3.19 Isoperimetric constraint problem

Consider the following optimal control problem, which includes an integral constraint. Minimize the cost functional

$$J = \int_0^{t_f} x^2(t)dt (3.79)$$

subject to the dynamic constraint

$$\dot{x} = -\sin(x) + u \tag{3.80}$$

the integral constraint:

$$\int_0^{t_f} u^2(t)dt = 10 \tag{3.81}$$




Figure 3.44: Control for interior point constraint problem

the boundary conditions

$$\begin{array}{rcl}
x(0) & = & 1 \\
x(t_f) & = & 0
\end{array} \tag{3.82}$$

and the bounds:

$$-4 \le u(t) \le 4 -10 \le x(t) \le 10$$
 (3.83)

where $t_f = 1$. The \mathcal{PSOPT} code that solves this problem is shown below.

```
return 0.0;
//////////// Define the integrand (Lagrange) cost function /////
adouble x = states[0];
  adouble L = x;
void dae(adouble* derivatives, adouble* path, adouble* states,
     adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
 adouble xdot, ydot, vdot;
 adouble x = states[ CINDEX(1) ];
 adouble u = controls[ CINDEX(1) ];
 derivatives[0] = -sin(x) + u;
adouble integrand( adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
 adouble g;
adouble u = controls[ CINDEX(1) ];
 g = u*u ;
 return g;
}
int iphase, Workspace* workspace)
 adouble x0 = initial_states[ CINDEX(1) ];
adouble xf = final_states[ CINDEX(1) ];
adouble Q;
 // Compute the integral to be constrained {\tt Q} = integrate( integrand, xad, iphase, workspace );
 e[ CINDEX(1) ] = x0;
e[ CINDEX(2) ] = xf;
e[ CINDEX(3) ] = Q;
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
```

```
// No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
= "Isoperimetric constraint problem";
  problem.outfilename
                        = "isoperimetric.txt";
problem.nphases
  problem.nlinkages
  psopt_level1_setup(problem);
problem.phases(1).nstates
                   = 1:
  problem.phases(1).ncontrols = 1;
problem.phases(1).nevents = 3;
problem.phases(1).npath = 0;
  problem.phases(1).npath
problem.phases(1).nodes = 50;
  psopt_level2_setup(problem, algorithm);
problem.phases(1).bounds.lower.states(1) = -10:
  problem.phases(1).bounds.upper.states(1) = 10;
  problem.phases(1).bounds.lower.controls(1) = -4.0;
problem.phases(1).bounds.upper.controls(1) = 4.0;
  problem.phases(1).bounds.lower.events(1) = 1.0:
  problem.phases(1).bounds.lower.events(2) = 0.0;
problem.phases(1).bounds.lower.events(3) = 10.0;
  problem.phases(1).bounds.upper.events(1) = 1.0;
  problem.phases(1).bounds.upper.events(2) = 0.0;
problem.phases(1).bounds.upper.events(3) = 10.0;
                             = 0.0;
= 0.0;
  problem.phases(1).bounds.lower.StartTime
  problem.phases(1).bounds.upper.StartTime
  problem.phases(1).bounds.lower.EndTime
problem.phases(1).bounds.upper.EndTime
                             = 1.0;
= 1.0;
```

```
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
  problem.dae = &dae;
problem.events = &events;
  problem.linkages = &linkages;
problem.phases(1).guess.controls = zeros(1,30);
  problem.phases(1).guess.states
problem.phases(1).guess.time
                        = zeros(1,30);
                       = linspace(0.0,1.0,30);
= "IPOPT":
  algorithm.nlp method
  algorithm.scaling
algorithm.derivatives
                       = "automatic";
= "automatic";
  algorithm.derivatives
algorithm.nlp_iter_max
algorithm.nlp_tolerance
                       = 1000;
                        = 1.e-6;
psopt(solution, problem, algorithm);
  if (solution.error_flag) exit(0);
x = solution.get_states_in_phase(1);
   = solution.get_controls_in_phase(1);
         = solution.get_time_in_phase(1);
x.Save("x.dat"):
  u.Save("u.dat");
t.Save("t.dat");
plot(t,x,problem.name + ": state", "time (s)", "x", "x");
  \verb|plot(t,u,problem.name + ": control", "time (s)", "u", "u");|\\
  \verb|plot(t,x,problem.name + ": state", "time (s)", "x", "x", \\
                "pdf", "isop_state.pdf");
  \verb|plot(t,u,problem.name + ": control", "time (s)", "u", "u", \\
               "pdf", "isop_control.pdf");
```

The output from \mathcal{PSOPT} is summarized in the text box below and in Figures 3.45 and 3.46, which show the optimal state and control, respec-




Figure 3.45: State for isoperimetric constraint problem

tively.

3.20 Lambert's problem

This example demonstrates the use of the \mathcal{PSOPT} for a classical orbit determination problem, namely the determination of an orbit from two position




Figure 3.46: Control for isoperimetric constraint problem

vectors and time (Lambert's problem) [42]. The problem is formulated as follows. Find $\mathbf{r}(t) \in [0, t_f]$ and $\mathbf{v}(t) \in [0, t_f]$ to minimise:

$$J = 0 (3.84)$$

subject to

$$\dot{\mathbf{r}} = \mathbf{v}$$

$$\dot{\mathbf{v}} = -\mu \frac{\mathbf{r}}{||\mathbf{r}||^3}$$
(3.85)

with the boundary conditions:

$$\mathbf{r}(\mathbf{0}) = [15945.34\text{E}3, 0.0, 0.0]^T$$

$$\mathbf{r}(t_f) = [12214.83899\text{E}3, 10249.46731\text{E}3, 0.0]^T$$
(3.86)

where $\mathbf{r} = [x, y, z]^T$ (m) is a cartesian position vector, and $\mathbf{v} = [v_x, v_z, v_z]^T$ is the corresponding velocity vector, $\mu = GM_e$, G (m³/(kg s²)) is the universal gravitational constant and M_e (kg) is the mass of Earth.

The \mathcal{PSOPT} code that solves this problem is shown below.

```
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states, adouble* parameters,adouble& t0, adouble& tf,
                adouble* xad, int iphase, Workspace* workspace)
 return 0.0;
//////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters,
                adouble& time, adouble* xad, int iphase, Workspace* workspace)
  return 0.0:
void dae(adouble* derivatives, adouble* path, adouble* states,
      adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  // Define constants:
  double G = 6.6720e-11; // Universal gravity constant [m^3/(kg s^2)] double Me = 5.9742e24; // Mass of earth;[kg]
  double mu = G*Me;
                    // [m^3/sec^2]
  ADMatrix r(3), v(3);
  // Extract individual variables
  r(1) = states[ CINDEX(1) ];
r(2) = states[ CINDEX(2) ];
  v(1) = states[ CINDEX(4) ];
  v(2) = states[ CINDEX(5) ];
v(3) = states[ CINDEX(6) ];
  ADMatrix rdd(3):
  adouble rr = sqrt(r(1)*r(1)+r(2)*r(2)+r(3)*r(3));
  adouble r3 = pow(rr,3.0);
  rdd(1) = -mu*r(1)/r3;
rdd(2) = -mu*r(2)/r3;
  rdd(3) = -mu*r(3)/r3;
  derivatives[ CINDEX(1) ] = v(1);
  derivatives[ CINDEX(2) ] = v(2);
derivatives[ CINDEX(3) ] = v(3);
  derivatives[ CINDEX(4) ] = rdd(1);
derivatives[ CINDEX(5) ] = rdd(2);
  derivatives[ CINDEX(6) ] = rdd(3);
}
```

```
void events(adouble* e, adouble* initial_states, adouble* final_states,
       adouble* parameters,adouble& t0, adouble& tf, adouble* xad,
      int iphase, Workspace* workspace)
{
 adouble ri1 = initial_states[ CINDEX(1) ];
adouble ri2 = initial_states[ CINDEX(2) ];
adouble ri3 = initial_states[ CINDEX(3) ];
 adouble rf1 = final_states[ CINDEX(1) ];
adouble rf2 = final_states[ CINDEX(2) ];
adouble rf3 = final_states[ CINDEX(3) ];
 e[ CINDEX(1) ] = ri1;
 e[ CINDEX(2) ] = ri2;
e[ CINDEX(3) ] = ri3;
 e[ CINDEX(4) ] = rf1;
e[ CINDEX(5) ] = rf2;
e[ CINDEX(6) ] = rf3;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// auto_link_multiple(linkages, xad, N_PHASES);
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
  MSdata msdata;
problem.nphases = 1;
problem.nlinkages
                      = 0;
  psopt_level1_setup(problem);
problem.phases(1).nstates = 6;
problem.phases(1).ncontrols = 0;
```

```
problem.phases(1).nevents = 6;
      problem.phases(1).nparameters
problem.phases(1).npath =
                                                                    = 6;
                                               = 0:
                                                           = "[100]";
      problem.phases(1).nodes
     psopt_level2_setup(problem, algorithm);
double r1i = 15945.34e3; // m
double r2i = 0.0;
double r3i = 0.0;
     double r1f = 12214.83899e3; //m
double r2f = 10249.46731e3; //m
double r3f = 0.0;
     double TF = 76.0*60.0: // seconds
      problem.phases(1).bounds.lower.states(1) = -10*max(r1i.r1f):
      problem.phases(1).bounds.lower.states(2) = -10*max(r3i,r3f);
problem.phases(1).bounds.lower.states(3) = -10*max(r3i,r3f);
     problem.phases(1).bounds.upper.states(1) = 10*max(ri,rif);
problem.phases(1).bounds.upper.states(2) = 10*max(ri,r2f);
problem.phases(1).bounds.upper.states(3) = 10*max(r3i,r3f);
      problem.phases(1).bounds.lower.states(4) = -10*max(r1i,r1f)/TF;
problem.phases(1).bounds.lower.states(5) = -10*max(r1i,r1f)/TF;;
     problem.phases(1).bounds.lower.states(5) = -10*max(rli,r1f)/TF;;
problem.phases(1).bounds.lower.states(6) = -10*max(rli,r1f)/TF;
problem.phases(1).bounds.upper.states(4) = 10*max(rli,r1f)/TF;
problem.phases(1).bounds.upper.states(5) = 10*max(r2i,r2f)/TF;
problem.phases(1).bounds.upper.states(6) = 10*max(r3i,r3f)/TF;
     problem.phases(1).bounds.lower.events(1) = r1i;
problem.phases(1).bounds.upper.events(1) = r1i;
      problem.phases(1).bounds.lower.events(2) = r2i;
      problem.phases(1).bounds.upper.events(2) = r2i;
      problem.phases(1).bounds.lower.events(3) = r3i;
      problem.phases(1).bounds.upper.events(3) = r3i;
      problem.phases(1).bounds.lower.events(4) = r1f;
      problem.phases(1).bounds.upper.events(4) = r1f;
      problem.phases(1).bounds.lower.events(5) = r2f;
      problem.phases(1).bounds.upper.events(5) = r2f;
      problem.phases(1).bounds.lower.events(6) = r3f;
      problem.phases(1).bounds.upper.events(6) = r3f;
      problem.phases(1).bounds.lower.StartTime
      problem.phases(1).bounds.upper.StartTime
                                                                  = 0.0:
      problem.phases(1).bounds.lower.EndTime
                                                                    = TF:
      problem.phases(1).bounds.upper.EndTime
problem.phases(1).name.states(1) = "x position";
problem.phases(1).name.states(2) = "y position";
problem.phases(1).name.states(3) = "z position";
problem.phases(1).name.states(4) = "x velocity";
problem.phases(1).name.states(5) = "y velocity";
problem.phases(1).name.states(6) = "z velocity";
      problem.phases(1).units.states(1) = "m";
      problem.phases(1).units.states(2) = "m";
problem.phases(1).units.states(3) = "m";
     problem.phases(1).units.states(4) = "m";
problem.phases(1).units.states(5) = "m/s";
problem.phases(1).units.states(6) = "m/s";
```

```
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
                  = &dae:
  problem.dae
  problem.events = &events;
  problem.linkages = &linkages;
int nnodes
           = 20:
  int ncontrols
                          = problem.phases(1).ncontrols;
                          = problem.phases(1).nstates;
  int nstates
  DMatrix x_guess = zeros(nstates,nnodes);
DMatrix time_guess = linspace(0.0,TF,nnodes);
  x_guess(1,colon()) = linspace(r1i,r1f, nnodes);
  x_guess(1,colon()) = linspace(r11,r11, nnodes);
x_guess(2,colon()) = linspace(r21,r2f,nnodes);
x_guess(3,colon()) = linspace(r31,r3f,nnodes);
x_guess(4,colon()) = linspace(r11,r1f,nnodes)/TF;
x_guess(5,colon()) = linspace(r21,r2f,nnodes)/TF;
x_guess(6,colon()) = linspace(r31,r3f, nnodes)/TF;
  algorithm.nlp_iter_max algorithm.nlp_tolerance
                           = 1000;
                           = 1.e-6;
= "IPOPT";
  algorithm.nlp_method
algorithm.scaling
                           = "automatic";
                           = "automatic":
  algorithm.derivatives
  psopt(solution, problem, algorithm);
DMatrix x, u, t, xi, ui, ti;
      = solution.get_states_in_phase(1);
      = solution.get_controls_in_phase(1);
= solution.get_time_in_phase(1);
x.Save("x.dat");
  u.Save("u.dat");
t.Save("t.dat");
```

```
DMatrix r1 = x(1,colon());
DMatrix r2 = x(2,colon());
DMatrix r3 = x(3,colon());
   DMatrix v1 = x(4,colon());
   DMatrix v2 = x(5,colon());
DMatrix v3 = x(6,colon());
   DMatrix vi(3), vf(3);
   vi(1) = v1(1);
vi(2) = v2(1);
vi(3) = v3(1);
   vf(2) = v2("end");
vf(3) = v3("end");
   vi.Print("Initial velocity vector [m/s]");
   vf.Print("Final velocity vector [m/s]");
   plot(t,r1,problem.name+": x", "time (s)", "x", "x");
   plot(t,r2,problem.name+": y", "time (s)", "x", "y");
   plot(t,r3,problem.name+": z", "time (s)", "z","z");
   plot(r1,r2,problem.name+": x-y", "x (m)", "y (m)", "y");
   plot(r1,r2,problem.name+": x-y trajectory", "x (m)", "y (m)","y", "pdf", "lambert_xy.pdf");
   plot3(r1,r2,r3,problem.name+": trajectory", "x (m)", "y (m)", "z (m)");
```

The output from \mathcal{PSOPT} is summarized in the text box below and in Figure 3.47, which show the trajectory from $\mathbf{r}(0)$ to $\mathbf{r}(t_f)$, respectively.




Figure 3.47: Trajectory between the initial and final positions for Lambert's problem

The resulting initial and final velocity vectors are:

$$\mathbf{v}(0) = [2058.902605, 2915.961924, -6.878790137E - 13]^{T}$$

$$\mathbf{v}(t_f) = [-3451.55505, 910.3192974, -6.878787164E - 13]^{T}$$
(3.87)

3.21 Lee-Ramirez bioreactor

Consider the following optimal control problem, which is known in the literature as the Lee-Ramirez bioreactor [29, 36]. Find t_f and $u(t) \in [0, t_f]$ to minimize the cost functional

$$J = -x_1(t_f)x_4(t_f) + \int_0^{t_f} \rho[\dot{u}_1(t)^2 + \dot{u}_2(t)^2]dt$$
 (3.88)

subject to the dynamic constraints

$$\dot{x}_{1} = u_{1} + u_{2};$$

$$\dot{x}_{2} = g_{1}x_{2} - \frac{u_{1} + u_{2}}{x_{1}}x_{2};$$

$$\dot{x}_{3} = 100\frac{u_{1}}{x_{1}} - \frac{u_{1} + u_{2}}{x_{1}}x_{3} - (g_{1}/0.51)x_{2};$$

$$\dot{x}_{4} = R_{fp}x_{2} - \frac{u_{1} + u_{2}}{x_{1}}x_{4};$$

$$\dot{x}_{5} = 4\frac{u_{2}}{x_{1}} - \frac{u_{1} + u_{2}}{x_{1}}x_{5};$$

$$\dot{x}_{6} = -k_{1}x_{6};$$

$$\dot{x}_{7} = k_{2}(1 - x_{7}).$$
(3.89)

where $t_f = 10$, $\rho = 1/N$, and N is the number of discretization nodes,

$$k_1 = 0.09x_5/(0.034 + x_5);$$

$$k_2 = k_1;$$

$$g_1 = (x_3/(14.35 + x_3(1.0 + x_3/111.5)))(x_6 + 0.22x_7/(0.22 + x_5));$$

$$R_{fp} = (0.233x_3/(14.35 + x_3(1.0 + x_3/111.5)))((0.0005 + x_5)/(0.022 + x_5));$$

$$(3.90)$$

the initial conditions:

$$x_1(0) = 1$$

 $x_2(0) = 0.1$
 $x_3(0) = 40$
 $x_4(0) = 0$
 $x_5(0) = 0$
 $x_6(0) = 1.0$
 $x_7(0) = 0$ (3.91)

The \mathcal{PSOPT} code that solves this problem is shown below.

```
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
                   adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble x1tf = final_states[CINDEX(1)];
  adouble x4tf = final_states[CINDEX(4)];
  return -(x1tf*x4tf);
////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
    adouble u2 = controls[ CINDEX(2) ];
    adouble dot u1. dot u2:
    double Q = 0:
    get_control_derivative( &dot_u1, 1, iphase, time, xad, workspace);
    get_control_derivative( &dot_u2, 2, iphase, time, xad, workspace);
    double rho = 0.1/get_number_of_nodes(*workspace->problem, iphase);
    return (Q*u2 + rho*(dot_u1*dot_u1 + dot_u2*dot_u2));
}
void dae(adouble* derivatives, adouble* path, adouble* states,
       adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
ſ
   adouble u1 = controls[ CINDEX(1) ];
adouble u2 = controls[ CINDEX(2) ];
   adouble x1 = states[ CINDEX(1) ];
   adouble x2 = states[ CINDEX(2) ]:
   adouble x2 = states[ CINDEX(2) ];
adouble x3 = states[ CINDEX(3) ];
adouble x4 = states[ CINDEX(4) ];
adouble x5 = states[ CINDEX(5) ];
adouble x6 = states[ CINDEX(6) ];
   adouble x7 = states[ CINDEX(7) ];
   adouble k1 = 0.09*x5/(0.034 + x5);
   adouble k2 = k1:
   adouble g1 = (x3/(14.35 + x3*(1.0+x3/111.5)))*(x6 + 0.22*x7/(0.22+x5));
   adouble Rfp = (0.233*x3/(14.35 + x3*(1.0+x3/111.5)))*((0.0005+x5)/(0.022+x5));
   derivatives[ CINDEX(1) ] = u1 + u2;
```

```
int iphase, Workspace* workspace)
{
 int i;
for(i=1;i<= 7; i++) {
    e[CINDEX(i)] = initial_states[CINDEX(i)];</pre>
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// Single phase problem
}
int main(void)
Alg algorithm;
Sol solution;
 Prob problem;
= 0:
 problem.nlinkages
 psopt_level1_setup(problem);
problem.phases(1).nstates
 problem.phases(1).ncontrols = 2;
problem.phases(1).nevents = 7;
 problem.phases(1).npath
problem.phases(1).nodes
                = "[20 35 50]";
 psopt_level2_setup(problem, algorithm);
```

```
int i;
    problem.phases(1).bounds.lower.states = -10.0*ones(7,1);
problem.phases(1).bounds.upper.states = "[10.0 10.0 50.0 10.0 10.0 10.0 10.0]";
   problem.phases(1).bounds.lower.controls(1) = 0.0;
problem.phases(1).bounds.lower.controls(2) = 0.0;
    problem.phases(1).bounds.upper.controls(1) = 1.0;
    problem.phases(1).bounds.upper.controls(2) = 1.0;
   problem.phases(1).bounds.lower.events = "[1.0 0.1 40.0 0.0 0.0 1.0 0.0]";
problem.phases(1).bounds.upper.events = "[1.0 0.1 40.0 0.0 0.0 1.0 0.0]";
    problem.phases(1).bounds.lower.StartTime
                                                 = 0.0;
    problem.phases(1).bounds.upper.StartTime
    problem.phases(1).bounds.lower.EndTime
                                                = 10.0;
= 10.0;
    problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
    problem.dae
                              = &dae;
    problem.events = &events;
    problem.linkages = &linkages;
int nnodes
                  = problem.phases(1).nodes(1);
                                         = problem.phases(1).ncontrols;
= problem.phases(1).nstates;
    int ncontrols
    int nstates
   state guess(1,colon()) = 1.0*ones(1,nnodes):
   state_guess(1,colon()) = 1.0*ones(1,nnodes);
state_guess(2,colon()) = 0.1*ones(1,nnodes);
state_guess(3,colon()) = 40.0*ones(1,nnodes);
state_guess(4,colon()) = 0.0*ones(1,nnodes);
state_guess(5,colon()) = 0.0*ones(1,nnodes);
state_guess(6,colon()) = 1.0*ones(1,nnodes);
state_guess(7,colon()) = 0.0*ones(1,nnodes);
   control_guess(1,colon()) = time_guess/30.0;
control_guess(2,colon()) = zeros(1,nnodes);
    auto_phase_guess(problem, control_guess, state_guess, param_guess, time_guess);
algorithm.nlp_iter_max
                                            = 1000;
    algorithm.nlp_tolerance
algorithm.nlp_method
                                           = 1.e-5;
= "IPOPT";
    algorithm.scaling
                                            = "automatic":
```

```
= "automatic";
= "jacobian-based";
  algorithm.derivatives
 algorithm.defect_scaling
                   = "central-differences";
 algorithm.diff_matrix
psopt(solution, problem, algorithm);
DMatrix x. u. t:
     = solution.get_states_in_phase(1);
     = solution.get_controls_in_phase(1);
    = solution.get_time_in_phase(1);
x.Save("x.dat");
u.Save("u.dat");
 t.Save("t.dat");
\verb|plot(t,u,problem.name+": control","time (s)", "control 1", "u1 u2");|\\
 x(3,colon()) = x(3,colon())/10.0:
 plot(t,x,problem.name+": state","time (s)", "state", "x1 x2 x3/10 x4 x5 x6 x7");
 plot(t,u,problem.name+": control","time (s)", "control 1", "u1 u2",
    "pdf", "bioreactor_controls.pdf");
 x(3,colon()) = x(3,colon())/10.0;
 }
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.48 and 3.49, which contain the elements of the state and the control, respectively.




Figure 3.48: States for the Lee-Ramirez bioreactor problem

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 15:57:58 2019

Returned (unscaled) cost function value: -6.048409e+00 Phase 1 endpoint cost function value: -6.049249e+00 Phase 1 integrated part of the cost: 8.402028e-04

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 1.000000e+01

Phase 1 maximum relative local error 2.082149e-03

NLP solver reports: *** The problem FAILED! - see screen output

3.22 Li's parameter estimation problem

This is a parameter estimation problem with two parameters and three observed variables, which is presented b Li et. al [28].

The dynamic equations are given by:

$$\frac{dx}{dt} = M(t, p)x + f(t), \ t \in [0, \pi]$$
 (3.92)

with boundary condition:

$$x(0) + x(\pi) = (1 + e^{\pi})[1, 1, 1]^{T}$$




Figure 3.49: Control for the Lee-Ramirez bioreactor problem

where

$$M(t,p) = \begin{bmatrix} p_2 - p_1 \cos(p_2 t) & 0 & p_2 + p_1 \sin(p_2 t) \\ 0 & p_1 & 0 \\ -p_2 + p_1 \sin(p_2 t) & 0 & p_2 + p_1 \cos(p_2 t) \end{bmatrix}$$
(3.93)

and

$$f(t) = \begin{bmatrix} -1 + 19(\cos(t) - \sin(t)) \\ -18 \\ 1 - 19(\cos(t) + \sin(t)) \end{bmatrix}$$
(3.94)

and the observation functions are:

$$g_1 = x_1$$

 $g_2 = x_2$
 $g_3 = x_3$ (3.95)

The trajectories of the dynamic system is characterised by rapidly varying fast and slow components if the difference between the two parameters p_1 and p_2 is large, which may cause numerical problems to some ODE solvers.

The estimation data set is generated by adding Gaussian noise with standard deviation 1 around the solution $[x_1(t), x_2(t), x_3(t)]^T = [e^t, e^t, e^t]^T$, with N = 33 equidistant samples within the interval $t = [0, \pi]$. The true values of the parameters are $p_1 = 19$ and $p_2 = 1$. The weights of the three observations are the same and equal to one.

The solution is found using Legendre discretisation with 40 grid points. The code that solves the problem is shown below. The estimated parameter values and their 95% confidence limits for $n_s = 129$ samples are shown in

Table 3.22. Figure 3.50 shows the observations as well as the estimated values of variable x_1 .

```
#include "psopt.h"
void observation_function( adouble* observations
                 adouble* states, adouble* controls,
adouble* parameters, adouble& time, int k,
adouble* xad, int iphase, Workspace* workspace)
int i;
for (i=0; i<3; i++) {
       observations[ i ] = states[ i ];
}
void dae(adouble* derivatives, adouble* path, adouble* states,
     adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  // Variables
    adouble x1, x2, x3, p1, p2, t;
  // Differential states
    x1 = states[CINDEX(1)];
x2 = states[CINDEX(2)];
x3 = states[CINDEX(3)];
  // Parameters
    p1 = parameters[CINDEX(1)];
p2 = parameters[CINDEX(2)];
  ADMatrix M(3,3), f(3,1), dxdt(3,1), x(3,1), y(3,1);
  x(1,1) = x1; x(2,1) = x2; x(3,1) = x3;
  f(1,1) = \exp(t)*(-1.0 + 19.0*(\cos(t) - \sin(t)));
  f(2,1) = \exp(t)*(-18.0);

f(3,1) = \exp(t)*(1.0 - 19.0*(\cos(t) + \sin(t)));
    // Differential equations
```

```
product_ad(M, x, &y);
 sum_ad(y, f, &dxdt );
     derivatives[CINDEX(1)] = dxdt(1,1);
     derivatives[CINDEX(2)] = dxdt(2,1);
 derivatives[CINDEX(3)] = dxdt(3,1);
}
int iphase, Workspace* workspace)
 int i:
 double rhs = 1.0 + exp(pi);
 for (i=0; i<3; i++) {
  e[i] = initial_states[i] + final_states[i] - rhs;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem \,
int main(void)
Alg algorithm;
Sol solution;
Prob problem;
problem.name = "Parameter estimation for ODE with two parameters";
problem.outfilename = "param2 tv+".
problem.nphases
                   = 0;
 problem.nlinkages
 psopt_level1_setup(problem);
///////// Define phase related information & do level 2 setup /////////
problem.phases(1).nstates
  problem.phases(1).ncontrols = 0;
  problem.phases(1).nevents = 3;
  problem.phases(1).npath
  problem.phases(1).nparameters
                      = 2:
```

```
problem.phases(1).nodes
                                     = 40:
   problem.phases(1).nobserved problem.phases(1).nsamples
                                            = 3;
= 129;
   psopt_level2_setup(problem, algorithm);
int iphase = 1;
   load_parameter_estimation_data(problem, iphase, "param2.dat");
   problem.phases(1).observation_nodes.Print("observation nodes");
   problem.phases(1).observations.Print("observations");
   problem.phases(1).residual_weights.Print("weights");
DMatrix x, p, t;
problem.phases(1).bounds.lower.states(1) = 0.0;
problem.phases(1).bounds.lower.states(2) = 0.0;
   problem.phases(1).bounds.lower.states(3) = 0.0;
   problem.phases(1).bounds.upper.states(1) = 30.0;
   problem.phases(1).bounds.upper.states(2) = 30.0;
problem.phases(1).bounds.upper.states(3) = 30.0;
   problem.phases(1).bounds.lower.events(1) = 0.0;
problem.phases(1).bounds.lower.events(2) = 0.0;
   problem.phases(1).bounds.lower.events(3) = 0.0;
   problem.phases(1).bounds.upper.events(1) = 0.0;
   problem.phases(1).bounds.upper.events(1) = 0.0;
problem.phases(1).bounds.upper.events(2) = 0.0;
problem.phases(1).bounds.upper.events(3) = 0.0;
   problem.phases(1).bounds.lower.parameters(1) = 0.0;
problem.phases(1).bounds.lower.parameters(2) = 0.0;
   problem.phases(1).bounds.upper.parameters(1) = 30.0;
problem.phases(1).bounds.upper.parameters(2) = 30.0;
   problem.phases(1).bounds.lower.StartTime
                                            = 0.0:
   problem.phases(1).bounds.upper.StartTime
                                            = pi;
= pi;
   problem.phases(1).bounds.lower.EndTime
   problem.phases(1).bounds.upper.EndTime
problem.dae = &dae;
   problem.events = &events;
problem.linkages = &linkages;
   problem.observation_function = & observation_function;
int nnodes =
                 (int) problem.phases(1).nsamples;
   DMatrix state_guess(3, nnodes);
DMatrix param_guess(2,1);
   state_guess(1,colon()) = linspace(1.0, exp(pi), nnodes );
state_guess(2,colon()) = linspace(1.0, exp(pi), nnodes );
state_guess(3,colon()) = linspace(1.0, exp(pi), nnodes );
```

```
param_guess(1) = 19.0*1.5;
param_guess(2) = 1.0*1.5;
   problem.phases(1).guess.states = state_guess;
   problem.phases(1).guess.time = linspace(0.0, pi, nnodes);
problem.phases(1).guess.parameters = param_guess;
algorithm.nlp_method
   algorithm.scaling
                                    = "automatic":
   algorithm.derivatives
                                     = "automatic";
   algorithm.collocation_method
algorithm.mesh_refinement
algorithm.defect_scaling
algorithm.nlp_iter_max
algorithm.ode tolerance
                                    = "Legendre";
= "automatic";
= "jacobian-based";
   algorithm.ode_tolerance
                                    = 1.e-4:
psopt(solution, problem, algorithm);
x = solution.get_states_in_phase(1);
   t = solution.get_time_in_phase(1);
   p = solution.get_parameters_in_phase(1);
x.Save("x.dat"):
   t.Save("t.dat");
   p.Print("Estimated parameters");
DMatrix ym;
    tm = problem.phases(1).observation_nodes;
ym = problem.phases(1).observations;
     \begin{split} & \text{spplot(t,x(1,colon()),tm,ym(1,colon()),problem.name, "time (s)", "state x1", "x1 y1");} \\ & \text{spplot(t,x(2,colon()),tm,ym(2,colon()),problem.name, "time (s)", "state x2", "x2 y2");} \\ & \text{spplot(t,x(3,colon()),tm,ym(3,colon()),problem.name, "time (s)", "state x3", "x3 y3");} \\ \end{split} 
     \begin{aligned} & \text{spplot(t,x(1,colon()),tm,ym(1,colon()),problem.name, "time (s)", "state x1", "x1 y1", "pdf", "x1.pdf");} \\ & \text{spplot(t,x(2,colon()),tm,ym(2,colon()),problem.name, "time (s)", "state x2", "x2 y2", "pdf", "x2.pdf");} \\ & \text{spplot(t,x(3,colon()),tm,ym(3,colon()),problem.name, "time (s)", "state x3", "x3 y3", "pdf", "x3.pdf");} \end{aligned} 
}
END OF FILE
```

Table 3.1: Estimated parameter values and 95 percent statistical confidence limits on estimated parameters $\frac{1}{2}$

Parameter	Low Confidence Limit	Value	High Confidence Limit
p_1	1.907055e + 01	1.907712e+01	1.908369e + 01
p_2	9.984900e-01	9.984990 e-01	9.985080 e-01




Figure 3.50: Observations and estimated state $x_1(t)$

3.23 Linear tangent steering problem

Consider the following optimal control problem, which is known in the literature as the linear tangent steering problem [3]. Find t_f and $u(t) \in [0, t_f]$ to minimize the cost functional

$$J = t_f \tag{3.96}$$

subject to the dynamic constraints

$$\dot{x}_1 = x_2
\dot{x}_2 = a\cos(u)
\dot{x}_3 = x_4
\dot{x}_4 = a\sin(u)$$
(3.97)

the boundary conditions:

$$\begin{aligned}
 x_1(0) &= 0 \\
 x_2(0) &= 0 \\
 x_3(0) &= 0 \\
 x_4(0) &= 0 \\
 x_2(t_f) &= 45.0 \\
 x_3(t_f) &= 5.0 \\
 x_4(t_f) &= 0.0
 \end{aligned} \tag{3.98}$$

The \mathcal{PSOPT} code that solves this problem is shown below.

```
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad,
                      int iphase, Workspace* workspace)
    return 0.0;
void dae(adouble* derivatives, adouble* path, adouble* states,
        adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
ſ
   adouble x1 = states[ CINDEX(1) ];
adouble x2 = states[ CINDEX(2) ];
adouble x3 = states[ CINDEX(3) ];
   adouble x4 = states[ CINDEX(4) ];
   adouble u = controls[ CINDEX(1) ];
   double a = 100.0;
  derivatives[ CINDEX(1) ] = x2;
derivatives[ CINDEX(2) ] = a*cos(u);
derivatives[ CINDEX(3) ] = x4;
derivatives[ CINDEX(4) ] = a*sin(u);
void events(adouble* e, adouble* initial_states, adouble* final_states,
           adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble x10 = initial_states[ CINDEX(1) ];
adouble x20 = initial_states[ CINDEX(2) ];
adouble x30 = initial_states[ CINDEX(3) ];
adouble x40 = initial_states[ CINDEX(4) ];
adouble x2f = final_states[ CINDEX(2) ];
adouble x3f = final_states[ CINDEX(3) ];
adouble x4f = final_states[ CINDEX(4) ];
  e[ CINDEX(1) ] = x10;
e[ CINDEX(2) ] = x20;
e[ CINDEX(3) ] = x30;
e[ CINDEX(4) ] = x40;
   e[ CINDEX(4) ] = x40;
e[ CINDEX(5) ] = x2f;
e[ CINDEX(6) ] = x3f;
e[ CINDEX(7) ] = x4f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
^{\prime} // No linkages as this is a single phase problem }
int main(void)
Alg algorithm;
Sol solution;
    Prob problem;
```

```
problem.name
                   = "Linear Tangent Steering Problem";
                               = "lts.txt";
   problem.outfilename
problem.nphases
problem.nlinkages
                 = 1;
   psopt_level1_setup(problem);
problem.phases(1).nstates
   problem.phases(1).ncontrols = 1;
   problem.phases(1).nevents
                          = 0;
   problem.phases(1).npath
   problem.phases(1).nodes
                                      = "[10, 30]";
   psopt_level2_setup(problem, algorithm);
DMatrix x, u, t;
   DMatrix lambda, H;
problem.phases(1).bounds.lower.states(1) = -100.0;
   problem.phases(1).bounds.lower.states(2) = -100.0;
   problem.phases(1).bounds.lower.states(3) = -100.0;
problem.phases(1).bounds.lower.states(4) = -100.0;
   problem.phases(1).bounds.upper.states(1) = 100.0;
   problem.phases(1).bounds.upper.states(2) = 100.0;
problem.phases(1).bounds.upper.states(3) = 100.0;
   problem.phases(1).bounds.upper.states(4) = 100.0;
   problem.phases(1).bounds.lower.controls(1) = -pi/2.0;
problem.phases(1).bounds.upper.controls(1) = pi/2.0;
   problem.phases(1).bounds.lower.events(1) = 0.0;
   problem.phases(1).bounds.lower.events(2) = 0.0;
   problem.phases(1).bounds.lower.events(2) = 0.0;
problem.phases(1).bounds.lower.events(3) = 0.0;
problem.phases(1).bounds.lower.events(4) = 0.0;
   problem.phases(1).bounds.lower.events(5) = 45.0;
problem.phases(1).bounds.lower.events(6) = 5.0;
   problem.phases(1).bounds.lower.events(7) = 0.0;
   problem.phases(1).bounds.upper.events(1) = 0.0;
   problem.phases(1).bounds.upper.events(2) = 0.0;
problem.phases(1).bounds.upper.events(3) = 0.0;
problem.phases(1).bounds.upper.events(4) = 0.0;
   problem.phases(1).bounds.upper.events(5) = 45.0;
problem.phases(1).bounds.upper.events(6) = 5.0;
   problem.phases(1).bounds.upper.events(7) = 0.0;
   problem.phases(1).bounds.lower.StartTime
                                      = 0.0;
                                      = 0.0;
   problem.phases(1).bounds.upper.StartTime
   problem.phases(1).bounds.lower.EndTime
                                     = 0.0;
= 1.0;
   problem.phases(1).bounds.upper.EndTime
```

```
problem.integrand_cost = &integrand_cost;
  problem.endpoint_cost = &endpoint_cost;
  problem.dae = &dae;
  problem.events = &events;
problem.linkages = &linkages;
DMatrix x0(3,10);
  x0(1,colon()) = linspace(0.0, 12.0, 10);
x0(2,colon()) = linspace(0.0, 45.0, 10);
x0(3,colon()) = linspace(0.0, 5.0, 10);
x0(3,colon()) = linspace(0.0, 0.0, 10);
  problem.phases(1).guess.controls
                         = ones(1,10);
  problem.phases(1).guess.states
problem.phases(1).guess.time
                         = x0:
                        = linspace(0.0,1.0, 10);
= "IPOPT":
  algorithm.nlp method
 algorithm.scaling
algorithm.derivatives
algorithm.nlp_iter_max
algorithm.nlp_tolerance
                        = "automatic";
= "automatic";
= 1000;
                         = 1.e-6;
psopt(solution, problem, algorithm);
  if (solution.error_flag) exit(0);
x = solution.get_states_in_phase(1);
  u = solution.get_controls_in_phase(1);
t = solution.get_time_in_phase(1);
x.Save("x.dat");
  u.Save("u.dat");
t.Save("t.dat");
Plot some results if desired (requires gnuplot) ///////////
plot(t,x,problem.name + ": states", "time (s)", "states", "x1 x2 x3 x4");
  plot(t,u,problem.name + ": control", "time (s)", "control", "u");
  \verb|plot(t,u,problem.name + ": control", "time (s)", "control", "u", \\
                  "pdf", "lts_control.pdf");
}
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.51 and 3.52, which contain the elements of the state and the control, respectively.

PSOPT results summary

Problem: Linear Tangent Steering Problem

CPU time (seconds): 1.188370e+00

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 17:16:35 2019

Optimal (unscaled) cost function value: 5.545709e-01 Phase 1 endpoint cost function value: 5.545709e-01 Phase 1 integrated part of the cost: 0.000000e+00

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 5.545709e-01

Phase 1 maximum relative local error: 1.603284e-07 NLP solver reports: The problem has been solved!

3.24 Low thrust orbit transfer

The goal of this problem is to compute an optimal low thrust policy for an spacecraft to go from a standard space shuttle park orbit to a specified final orbit, while maximising the final weight of the spacecraft. The problem is described in detail by Betts [3]. The problem is formulated as follows. Find $\mathbf{u}(t) = [u_r(t), u_\theta(t), u_h(t)]^T, t \in [0, t_f]$, the unknown throtle parameter τ , and the final time t_f , such that the following objective function is minimised:

$$J = -w(t_f) \tag{3.99}$$

subject to the dynamic constraints:

$$\dot{\mathbf{y}} = \mathbf{A}(\mathbf{y})\Delta + \mathbf{b}$$

$$\dot{\mathbf{w}} = -T[1 + 0.01\tau]/I_{sp}$$
(3.100)

the path constraint:

$$||u(t)||^2 = 1 (3.101)$$




Figure 3.51: States for the linear tangent steering problem




Figure 3.52: Control for the linear tangent steering problem

and the parameter bounds:

$$\tau_L \le \tau \le 0 \tag{3.102}$$

where $\mathbf{y} = [p, f, g, h, k, L, w]^T$ is the vector of modified equinoctial elements, w(t) is the weight of the spacecraft, I_{sp} is the specific impulse of the engine, expressions for $\mathbf{A}(\mathbf{y})$ and \mathbf{b} are given in [3], the disturbing acceleration Δ is given by:

$$\Delta = \Delta_q + \Delta_T \tag{3.103}$$

where Δ_g is the gravitational disturbing acceleration due to the oblatness of Earth (given in [3]), and Δ_T is the thurst acceleration, given by:

$$\Delta_T = \frac{g_0 T [1 + 0.01\tau]}{w} \mathbf{u}$$

where T is the maximum thrust, and g_0 is the mass to weight conversion factor.

The boundary conditions of the problem are given by:

$$p(t_f) = 40007346.015232 \text{ ft}$$

$$\sqrt{f(t_f)^2 + g(t_f)^2} = 0.73550320568829$$

$$\sqrt{h(t_f)^2 + k(t_f)^2} = 0.61761258786099$$

$$f(t_f)h(t_f) + g(t_f)k(t_f) = 0$$

$$g(t_f)h(t_f) - k(t_f)f(t_f) = 0$$

$$p(0) = 21837080.052835 \text{ft}$$

$$f(0) = 0$$

$$g(0) = 0$$

$$h(0) = 0$$

$$h(0) = 0$$

$$k(0) = 0$$

$$L(0) = \pi \text{ (rad)}$$

$$w(0) = 1 \text{ (lb)}$$

and the values of the parameters are: $g_0=32.174~({\rm ft/sec^2}),~I_{sp}=450~({\rm sec}),~T=4.446618\times 10^{-3}~({\rm lb}),~\mu=1.407645794\times 10^{16}~({\rm ft^3/sec^2}),~R_e=20925662.73~({\rm ft}),~J_2=1082.639\times 10^{-6},~J_3=-2.565\times 10^{-6},~J_4=-1.608\times 10^{-6},~\tau_L=-50.$

An initial guess was computed by forward propagation from the initial conditions, assuming that the direction of the thrust vector is parallel to the cartesian velocity vector, such that the initial control input was computed as follows:

$$\mathbf{u}(t) = \mathbf{Q}_r^T \frac{\mathbf{v}}{||\mathbf{v}||} \tag{3.105}$$

where \mathbf{Q}_r is a matrix whose columns are the directions of the rotating radial frame:

 $\mathbf{Q}_r = \begin{bmatrix} \mathbf{i}_r & \mathbf{i}_\theta & \mathbf{i}_h \end{bmatrix} = \begin{bmatrix} \frac{\mathbf{r}}{||\mathbf{r}||} & \frac{(\mathbf{r} \times \mathbf{v}) \times \mathbf{r}}{||\mathbf{r} \times \mathbf{v}||||\mathbf{r}||} & \frac{(\mathbf{r} \times \mathbf{v})}{||\mathbf{r} \times \mathbf{v}||} \end{bmatrix}$ (3.106)

The problem was solved using local collocation (trapezoidal followed by Hermite-Simpson) with automatic mesh refinement. The \mathcal{PSOPT} code that solves the problem is shown below.

```
#include "psopt.h"
adouble legendre_polynomial( adouble x, int n)
// This function computes the value of the legendre polynomials // for a given value of the argument x and for n=0...5 only
 adouble retval=0.0;
 switch(n) {
      retval=1.0; break;
   case 1:
      retval= x; break;
   case 2:
      retval= 0.5*(3.0*pow(x,2)-1.0); break;
   case 3:
     retval= 0.5*(5.0*pow(x,3)- 3*x); break;
      retval= (1.0/8.0)*(35.0*pow(x,4) - 30.0*pow(x,2) + 3.0); break;
   case 5:
      retval= (1.0/8.0)*(63.0*pow(x,5) - 70.0*pow(x,3) + 15.0*x); break;
   default:
      \label{lem:condition} error\_message("legendre\_polynomial(x,n) is limited to n=0...5");
 return retval:
}
adouble legendre_polynomial_derivative( adouble x, int n)
// This function computes the value of the legendre polynomial derivatives // for a given value of the argument x and for n=0...5 only.
 adouble retval=0.0;
 switch(n) {
   case 0:
      retval=0.0; break;
   case 1:
      retval= 1.0; break;
      retval= 0.5*(2.0*3.0*x); break;
```

```
retval= 0.5*(3.0*5.0*pow(x,2)-3.0); break;
    case 4:
        retval= (1.0/8.0)*(4.0*35.0*pow(x,3) - 2.0*30.0*x ); break;
    case 5:
        retval= (1.0/8.0)*(5.0*63.0*pow(x,4) - 3.0*70.0*pow(x,2) + 15.0); break;
    default:
       error_message("legendre_polynomial_derivative(x,n) is limited to n=0...5");
 return retval;
}
void compute_cartesian_trajectory(const DMatrix& x, DMatrix& xyz )
   int npoints = x.GetNoCols();
   xyz.Resize(3,npoints);
   for(int i=1; i<=npoints;i++) {
  double p = x(1,i);
double f = x(2,i);
double g = x(3,i);
  double k = x(4,i);
double k = x(5,i);
   double L = x(6,i);
  double q = 1.0 + f*cos(L) + g*sin(L);
double r = p/q;
double alpha2 = h*h - k*k;
double X = sqrt( h*h + k*k );
double s2 = 1 + X*X;
  xyz(1,i) = r1;
  xyz(2,i) = r1;

xyz(2,i) = r2;

xyz(3,i) = r3;
  }
}
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
                    adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
{
  if (iphase == 1) {
  adouble w = final_states[CINDEX(7)];
   return (-w);
   else {
  return (0);
///////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
   return 0.0;
}
void dae(adouble* derivatives, adouble* path, adouble* states,
```

```
adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
   // Local integers
   int i, j;
// Define constants:
  J[4] = -1.608e-6;
   // Extract individual variables
  adouble p = states[ CINDEX(1) ];
adouble f = states[ CINDEX(2) ];
adouble g = states[ CINDEX(3) ];
adouble h = states[ CINDEX(4) ];
adouble k = states[ CINDEX(6) ];
adouble L = states[ CINDEX(6) ];
adouble w = states[ CINDEX(7) ];
   adouble* u = controls;
   adouble tau = parameters[ CINDEX(1) ];
   // Define some dependent variables
  adouble q = 1.0 + f*cos(L) + g*sin(L);
adouble r = p/q;
adouble alpha2 = h*h - k*k;
adouble X = sqrt( h*h + k*k );
adouble s2 = 1 + X*X;
   rvec[ CINDEX(1) ] = r1; rvec[ CINDEX(2)] = r2; rvec[ CINDEX(3) ] = r3;
   adouble vvec[3];
   vvec[ CINDEX(1) ] = v1; vvec[ CINDEX(2)] = v2; vvec[ CINDEX(3) ] = v3;
   // compute Qr
   adouble ir[3], ith[3], ih[3];
   adouble rv[3];
   adouble rvr[3];
   cross( rvec, vvec, rv );
   cross( rv, rvec, rvr );
   adouble norm_r = sqrt( dot(rvec, rvec, 3) );
   adouble norm_rv = sqrt( dot(rv, rv, 3) );
   for (i=0; i<3; i++) {
     ir[i] = rvec[i]/norm_r;
     ith[i] = rvr[i]/( norm_rv*norm_r );
      ih[i] = rv[i]/norm_rv;
   adouble Qr1[3], Qr2[3], Qr3[3];
   for(i=0: i< 3: i++)
```

```
// Columns of matrix Qr
        Qr1[i] = ir[i];
Qr2[i] = ith[i];
Qr3[i] = ih[i];
 // Compute in
 en[ CINDEX(1) ] = 0.0; en[ CINDEX(2) ]= 0.0; en[ CINDEX(3) ] = 1.0;
 adouble enir = dot(en,ir,3);
 adouble in[3]:
 for(i=0;i<3;i++) {
   in[i] = en[i] - enir*ir[i];
}</pre>
 adouble norm_in = sqrt( dot( in, in, 3 ) );
 in[i] = in[i]/norm_in;
}
 for(i=0:i<3:i++) {
 // Geocentric latitude angle:
 adouble sin_phi = rvec[ CINDEX(3) ]/ sqrt( dot(rvec,rvec,3) ) ;
adouble cos_phi = sqrt(1.0- pow(sin_phi,2.0));
 adouble deltagn = 0.0;
adouble deltagr = 0.0;
 adouble deitagr = 0.0;
for (j=2; j<=4;j++) {
    adouble Pdash_j = legendre_polynomial_derivative( sin_phi, j );
    adouble P_j = legendre_polynomial( sin_phi, j );
    deltagn += -mu*cos_phi/(r*r)*pow(Re/r,j)*Pdash_j*J[j];
    deltagr += -mu/(r*r)* (j+1)*pow( Re/r,j)*P_j*J[j];
}

 // Compute vector delta_g
 adouble delta_g[3];
 for (i=0;i<3;i++) {
    delta_g[i] = deltagn*in[i] - deltagr*ir[i];</pre>
 // Compute vector DELTA_g
 adouble DELTA_g[3];
 DELTA_g[ CINDEX(1) ] = dot(Qr1, delta_g,3);
DELTA_g[ CINDEX(2) ] = dot(Qr2, delta_g,3);
DELTA_g[ CINDEX(3) ] = dot(Qr3, delta_g,3);
 // Compute DELTA_T
 adouble DELTA T[3]:
 for(i=0;i<3;i++) {
    DELTA_T[i] = g0*T*(1.0+0.01*tau)*u[i]/w;
 // Compute DELTA
 adouble DELTA[3];
 for(i=0;i<3;i++) {
   DELTA[i] = DELTA_g[i] + DELTA_T[i];</pre>
 adouble delta1= DELTA[ CINDEX(1) ];
 adouble delta2= DELTA[ CINDEX(2) ];
adouble delta3= DELTA[ CINDEX(3) ];
// derivatives
 * delta2:
```

```
adouble\ gdot = -sqrt(p/mu)*cos(L) * delta1 + sqrt(p/mu)*(1.0/q)*((q+1.0)*sin(L)+g) * delta2 + sqrt(p/mu)*(1.0/q)*((q+1.0)*sin(L)+g) 
                                                        -sqrt(p/mu)*cos(L) * delta1 * sqrt(p/mu)* (f/q)*(h*sin(L)-k*cos(L)) * delta3;

sqrt(p/mu)*s2*cos(L)/(2.0*q) * delta3;
         adouble hdot = \operatorname{sqrt}(p/mu)*s2*\cos(L)/(2.0*q) * \operatorname{delti} adouble kdot = \operatorname{sqrt}(p/mu)*s2*\sin(L)/(2.0*q) * \operatorname{delti} adouble Ldot = \operatorname{sqrt}(p/mu)*(1.0/q)*(h*\sin(L)-k*\cos(L))* delta3
                                                                                                                                                                                    * delta3;
                                                                                                                                                                                                                  + sqrt(mu*p)*pow( (q/p),2.);
         adouble wdot = -T*(1.0+0.01*tau)/Isp;
         derivatives[ CINDEX(1) ] = pdot;
derivatives[ CINDEX(2) ] = fdot;
        derivatives[ CINDEX(3) ] = gdot;
derivatives[ CINDEX(4) ] = hdot;
derivatives[ CINDEX(5) ] = kdot;
derivatives[ CINDEX(6) ] = Ldot;
derivatives[ CINDEX(7) ] = wdot;
          path[\ CINDEX(1)\ ] \ = \ pow(\ u[CINDEX(1)]\ , \ 2) \ + \ pow(\ u[CINDEX(2)], \ 2) \ + \ pow(\ u[CINDEX(3)], \ 2); 
}
void events(adouble* e. adouble* initial states, adouble* final states,
                                    adouble* parameters,adouble& t0, adouble& tf, adouble* xad,
                                    int iphase, Workspace* workspace)
{
         int offset;
         adouble pti = initial_states[ CINDEX(1) ];
adouble fti = initial_states[ CINDEX(2) ];
         adouble gti = initial_states[ CINDEX(3) ];
adouble hti = initial_states[ CINDEX(4) ];
         adouble htt = initial_states[ CINDEX(6) ];
adouble Lti = initial_states[ CINDEX(6) ];
adouble wti = initial_states[ CINDEX(7) ];
         adouble ptf = final_states[ CINDEX(1) ];
        adouble fif = final_states[ CINDEX(3) ];
adouble gff = final_states[ CINDEX(3) ];
adouble hff = final_states[ CINDEX(4) ];
adouble kff = final_states[ CINDEX(4) ];
adouble Lff = final_states[ CINDEX(6) ];
         if (iphase==1) {
          if (iphase==1) {
    e[ CINDEX(1) ] = pti;
    e[ CINDEX(2) ] = fti;
    e[ CINDEX(3) ] = gti;
    e[ CINDEX(4) ] = hti;
    e[ CINDEX(5) ] = kti;
    e[ CINDEX(6) ] = Lti;
    e[ CINDEX(7) ] = wti;
         if (1 == 1) offset = 7;
         else offset = 0;
         if (iphase == 1 ) {
          if (iphase == 1 ) {
    e[ offset + CINDEX(1) ] = ptf;
    e[ offset + CINDEX(2) ] = sqrt( ftf*ftf + gtf*gtf );
    e[ offset + CINDEX(3) ] = sqrt( htf*htf + ktf*ktf );
    e[ offset + CINDEX(4) ] = ftf*htf + gtf*ktf;
    e[ offset + CINDEX(5) ] = gtf*htf - ktf*ftf;
}
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
    // auto_link_multiple(linkages, xad, 1);
```

```
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
= "lowthrust.txt":
problem.nphases
  problem.nlinkages
                        = 0:
  psopt_level1_setup(problem);
problem.phases(1).nstates
  problem.phases(1).nstates - 7,
problem.phases(1).ncontrols = 3;
  problem.phases(1).ncontrols
problem.phases(1).nparameters
problem.phases(1).nevents
problem.phases(1).npath = 1;
                             = 1:
                        = 12;
  problem.phases(1).npath
problem.phases(1).nodes
                             = 80;
  psopt_level2_setup(problem, algorithm);
double tauL = -50.0;
double tauU = 0.0;
  double pti = 21837080.052835;
  double fti = 0.0;
double gti = 0.0;
  double hti = -0.25396764647494;
double kti = 0.0;
  double Lti = pi;
double wti = 1.0;
  double wtf_guess;
  double SISP = 450.0;
  double DELTAV = 22741.1460;
double CM2W = 32.174;
  wtf_guess = wti*exp(-DELTAV/(CM2W*SISP));
  double ptf
               = 40007346.015232;
  double ptr = 4000/346.015232;
double event_final_9 = 0.73550320568829;
double event_final_10 = 0.61761258786099;
double event_final_11 = 0.0;
double event_final_12_upper = 0.0;
  double event_final_12_lower = -10.0;
```

```
problem.phases(1).bounds.lower.parameters(1) = tauL;
     problem.phases(1).bounds.upper.parameters(1) = tauU;
     problem.phases(1).bounds.lower.states(1) = 10.e6;
      problem.phases(1).bounds.lower.states(2) = -0.20;
     problem.phases(1).bounds.lower.states(3) = -0.10;
     problem.phases(1).bounds.lower.states(4) = -1.0;
     problem.phases(1).bounds.lower.states(5) = -0.20;
     problem.phases(1).bounds.lower.states(6) = pi;
problem.phases(1).bounds.lower.states(7) = 0.0;
     problem.phases(1).bounds.upper.states(1) = 60.e6;
     problem.phases(1).bounds.upper.states(2) = 0.20;
problem.phases(1).bounds.upper.states(3) = 1.0;
     problem.phases(1).bounds.upper.states(4) = 1.0;
     problem.phases(1).bounds.upper.states(5) = 0.20;
     problem.phases(1).bounds.upper.states(6) = 20*pi;
problem.phases(1).bounds.upper.states(7) = 2.0;
     problem.phases(1).bounds.lower.controls(1) = -1.0;
     problem.phases(1).bounds.lower.controls(2) = -1.0;
problem.phases(1).bounds.lower.controls(3) = -1.0;
     problem.phases(1).bounds.upper.controls(3) = 1.0;
problem.phases(1).bounds.upper.controls(2) = 1.0;
problem.phases(1).bounds.upper.controls(3) = 1.0;
     problem.phases(1).bounds.lower.events(1)
     problem.phases(1).bounds.lower.events(2) = fti;
problem.phases(1).bounds.lower.events(3) = gti;
     problem.phases(1).bounds.lower.events(4)
     problem.phases(1).bounds.lower.events(5) = kti;
problem.phases(1).bounds.lower.events(6) = Lti;
     problem.phases(1).bounds.lower.events(6)
     problem.phases(1).bounds.lower.events(7) = wti;
     problem.phases(1).bounds.lower.events(8) = ptf;
problem.phases(1).bounds.lower.events(9) = event_final_9;
     problem.phases(1).bounds.lower.events(10) = event_final_10;
problem.phases(1).bounds.lower.events(11) = event_final_11;
     problem.phases(1).bounds.lower.events(12) = event_final_12_lower;
     problem.phases(1).bounds.upper.events(1) = pti;
problem.phases(1).bounds.upper.events(2) = fti;
problem.phases(1).bounds.upper.events(3) = gti;
     problem.phases(1).bounds.upper.events(4) = hti;
     problem.phases(1).bounds.upper.events(5)
                                                           = kti;
     problem.phases(1).bounds.upper.events(6)
problem.phases(1).bounds.upper.events(7)
                                                          = Lti:
     problem.phases(1).bounds.upper.events(8) = ptf;
problem.phases(1).bounds.upper.events(9) = event_final_9;
     problem.phases(1).bounds.upper.events(10) = event_final_10;
problem.phases(1).bounds.upper.events(11) = event_final_11;
problem.phases(1).bounds.upper.events(12) = event_final_12_upper;
     double EQ TOL = 0.001:
     problem.phases(1).bounds.upper.path(1) = 1.0+EQ_TOL;
problem.phases(1).bounds.lower.path(1) = 1.0-EQ_TOL;
     problem.phases(1).bounds.lower.StartTime
                                                             = 0.0:
     problem.phases(1).bounds.upper.StartTime
                                                             = 50000.0;
= 100000.0;
     problem.phases(1).bounds.lower.EndTime
     problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
     problem.endpoint_cost = &endpoint_cost;
problem.dae = &dae;
     problem.dae = problem.events = &events;
     problem.linkages = &linkages;
```

```
int nnodes
        = 141;
  int ncontrols
                   = problem.phases(1).ncontrols;
  int nstates
                   = problem.phases(1).nstates;
 {\tt DMatrix\ param\_guess\ =\ -25.0*ones(1,1);}
 u_guess.Load("U0.dat");
  x_guess.Load("X0.dat")
 time_guess.Load("T0.dat");
 auto_phase_guess(problem, u_guess, x_guess, param_guess, time_guess);
= 1000:
 algorithm.nlp_iter_max
  algorithm.nlp_tolerance
  algorithm.nlp_method
algorithm.scaling
                    = "IPOPT":
                    = "automatic";
                    = "automatic";
 algorithm.derivatives
psopt(solution, problem, algorithm);
DMatrix x, u, t;
     = solution.get_states_in_phase(1);
     = solution.get_controls_in_phase(1);
     = solution.get_time_in_phase(1);
 t = t/3600.0:
 DMatrix tau = solution.get_parameters_in_phase(1);
  tau.Print("tau");
u.Save("u.dat"):
 t.Save("t.dat");
DMatrix x1 = x(1,colon())/1.e6;
DMatrix x2 = x(2,colon());
 DMatrix x3 = x(3,colon());
DMatrix x4 = x(4,colon());
 DMatrix x5 = x(5,colon());
  DMatrix x6 = x(6,colon());
 DMatrix x7 = x(7,colon());
```

```
DMatrix u1 = u(1.colon()):
    DMatrix u2 = u(2,colon());
DMatrix u3 = u(3,colon());
    plot(t,x1,problem.name+": states", "time (h)", "p (1000000 ft)", "p (1000000 ft)");
    plot(t,x2,problem.name+": states", "time (h)", "f","f");
    plot(t,x3,problem.name+": states", "time (h)", "g", "g");
    \verb|plot(t,x4,problem.name+": states", "time (h)", "h","h");|\\
    plot(t,x5,problem.name+": states", "time (h)", "k", "k");
    plot(t,x6,problem.name+": states", "time (h)", "L (rev)", "L (rev)");
    plot(t,x7,problem.name+": states", "time (h)", "w (lb)", "w (lb)"):
    plot(t,u1,problem.name+": controls","time (h)", "ur", "ur");
    plot(t,u2,problem.name+": controls", "time (h)", "ut", "ut");
    plot(t,u3,problem.name+": controls","time (h)", "uh", "uh");
    plot(t,x1,problem.name+": states", "time (h)", "p (1000000 ft)", "p (1000000 ft)",
          "pdf","lowthr_x1.pdf");
    \verb|plot(t,x2,problem.name+": states", "time (h)", "f", "f", \\
   "pdf","lowthr_x2.pdf");
    plot(t.x3.problem.name+": states", "time (h)", "g", "g",
   "pdf","lowthr_x3.pdf");
   \label{eq:plot_plot} $$ plot(t,x4,problem.name+": states", "time (h)", "h","h", "pdf","lowthr_x4.pdf"); 
   plot(t,x5,problem.name+": states", "time (h)", "k", "k",
              "pdf","lowthr_x5.pdf");
   \label{local_problem.name+} $$ plot(t,x6,problem.name+": states", "time (h)", "L (rev)","L (rev)", "pdf","lowthr_x6.pdf"); 
    plot(t,x7,problem.name+": states", "time (h)", "w (lb)", "w (lb)",
   "pdf","lowthr_x7.pdf");
    plot(t,u1,problem.name+": controls","time (h)", "ur", "ur",
   "pdf", "lowthr_u1.pdf");
   plot(t,u2,problem.name+": controls","time (h)", "ut", "ut",
"pdf","lowthr_u2.pdf");
   plot(t,u3,problem.name+": controls","time (h)", "uh", "uh",
   "pdf","lowthr_u3.pdf");
    DMatrix r:
    compute cartesian trajectory(x.r):
    double ft2km = 0.0003048:
    r = r*ft2km;
   DMatrix rnew, tnew:
    tnew = linspace(0.0, t("end"), 1000);
    resample_trajectory( rnew, tnew, r, t );
   plot3(rnew(1,colon()), rnew(2,colon()), rnew(3,colon()),
    "Low thrust transfer trajectory", "x (km)", "y (km)", "z (km)",
    NULL, NULL, "30,97");
   plot3(rnew(1,colon()), rnew(2,colon()), rnew(3,colon()),
   "Low thrust transfer trajectory", "x (km)", "y (km)", "z (km)",
   "pdf", "trajectory.pdf", "30,97");
END OF FILE
```

Table 3.2: Mesh refinement statistics: Low thrust transfer problem

Iter	DM	M	NV	NC	OE	$^{\mathrm{CE}}$	$_{ m JE}$	$^{\mathrm{HE}}$	RHS	$\epsilon_{ ext{max}}$	CPU_a
1	$_{\mathrm{TRP}}$	80	803	653	1968	362	181	0	57558	2.208e-03	5.560e + 00
2	TRP	98	983	797	118	119	110	0	23205	2.263e-03	4.060e + 00
3	H-S	108	1404	984	145	146	141	0	47012	1.180e-03	7.650e + 00
4	H-S	116	1508	1056	209	210	185	0	72660	3.514e-04	1.119e + 01
CPU_b	-	-	-	-	-	-	-	-	-	-	8.250e+00
_	_	-	-	_	2440	837	617	0	200435	_	3.671e + 01

Key: Iter=iteration number, DM= discretization method, M=number of nodes, NV=number of variables, NC=number of constraints, OE=objective evaluations, CE = constraint evaluations, JE = Jacobian evaluations, HE = Hessian evaluations, RHS = ODE right hand side evaluations, $\epsilon_{\rm max}$ = maximum relative ODE error, CPUa = CPU time in seconds spent by NLP algorithm, CPUb = additional CPU time in seconds spent by PSOPT

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.53, to 3.58 and 3.59 to 3.61, which contain the modified equinoctial elements and the controls, respectively.

PSOPT results summary

Problem: Low thrust transfer problem

CPU time (seconds): 4.712761e+01

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 16:09:27 2019

Optimal (unscaled) cost function value: -2.203414e-01 Phase 1 endpoint cost function value: -2.203414e-01 Phase 1 integrated part of the cost: 0.000000e+00

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 8.684094e+04

Phase 1 maximum relative local error: 5.604141e-04 NLP solver reports: The problem has been solved!

3.25 Manutec R3 robot

The DLR model 2 of the Manutec r3 robot, reported and validated by Otter and co-workers [31, 20], describes the motion of three links of the robot as a function of the control input signals of the robot drive:




Figure 3.53: Modified equinoctial element p




Figure 3.54: Modified equinoctial element f




Figure 3.55: Modified equinoctial element g




Figure 3.56: Modified equinoctial element h




Figure 3.57: Modified equinoctial element k




Figure 3.58: Modified equinoctial element ${\cal L}$




Figure 3.59: Radial component of the thrust direction vector, u_r




Figure 3.60: Tangential component of the thrust direction vector, u_t




Figure 3.61: Normal component of the thrust direction vector, u_h

$$\mathbf{M}(\mathbf{q}(t))\ddot{\mathbf{q}}(t) = \mathbf{V}(\mathbf{q}(t), \dot{\mathbf{q}}(t)) + \mathbf{G}(\mathbf{q}(t)) + \mathbf{D}\mathbf{u}(t)$$

where $\mathbf{q} = [q_1(t), q_2(t), q_3(t)]^T$ is the vector of relative angles between the links, the normalized torque controls are $\mathbf{u}(t) = [u_1(t), u_2(t), u_3(t)]^T$, \mathbf{D} is a diagonal matrix with constant values, $\mathbf{M}(\mathbf{q})$ is a symmetric inertia matrix, $\mathbf{V}(\mathbf{q}(t), \dot{\mathbf{q}}(t))$ are the torques caused by coriolis and centrifugal forces, $\mathbf{G}(\mathbf{q}(t))$ are gravitational torques. The model is described in detail in [31] and is fully included in the code for this example³.

The example reported here consists of a minimum energy point to point trajectory, so that the objective is to find t_f and $\mathbf{u}(t) = [u_1(t), u_2(t), u_3(t)]^T$, $t \in [0, t_f]$ to minimise:

$$J = \int_0^{t_f} \mathbf{u}(t)^T \mathbf{u}(t) dt$$
 (3.107)

The boundary conditions associated with the problem are:

$$\mathbf{q}(0) = \begin{bmatrix} 0 & -1.5 & 0 \end{bmatrix}^{T}$$

$$\dot{\mathbf{q}}(0) = \begin{bmatrix} 0 & 0 & 0 \end{bmatrix}^{T}$$

$$\mathbf{q}(t_f) = \begin{bmatrix} 1.0 & -1.95 & 1.0 \end{bmatrix}^{T}$$

$$\dot{\mathbf{q}}(t_f) = \begin{bmatrix} 0 & 0 & 0 \end{bmatrix}^{T}$$
(3.108)

 $^{^3}$ Dr. Martin Otter from DLR, Germany, has kindly authorised the author to publish a translated form of subroutine R3M2SI as part of the \mathcal{PSOPT} distribution.

The \mathcal{PSOPT} code that solves this problem is shown below.

```
#include "psopt.h"
// Set option to: 1 for minimum time problem
// 2 for minimum time with regularization
// 3 for minimum energy problem
#define OBJ OPTION 3
typedef struct {
typedef struct {
    double g; // Gravity constant
    double pl; // Point mass of load;
    double Ia1; // Moment of inertia of arm 1, element (3,3)
    DMatrix* Fc; // Voltage-force constant of motor
    DMatrix* In; // Gear ratio of motor
    DMatrix* In; // Moment of inertia of motor
    DMatrix* In; // Moment of inertia of motor
DMatrix* in, // Mass of arm 2 and 3
DMatrix* L; // Length of arm 2 and 3 (inc. tool)
DMatrix* com; // Center of mass coordinates of arm 2 and 3;
DMatrix* Ia; // Moment of inertia arm 2 and 3;
} CONSTANTS_;
CONSTANTS_ CONSTANTS;
typedef struct {
adouble* qdd_ad;
adouble* F_ad;
adouble* qd_ad;
adouble* q_ad;
adouble* kw;
adouble* beta:
adouble* afor;
adouble* wabs:
adouble* zeta;
adouble* cosp;
adouble* ator;
adouble* sinp;
adouble* rhicm;
adouble* genvd ;
adouble* mrel12;
adouble* mrel22;
adouble* rhrel2;
adouble* workm3;
adouble* workm6;
adouble* works1;
adouble* works2;
adouble* workv3;
adouble* workv6;
adouble* cmhges;
adouble* ihhges;
adouble* inertc;
adouble* inertg;
adouble* inerth;
adouble* workam;
adouble* workas;
adouble* wworkm:
```

```
adouble* wworkv;
} VARS :
VARS_ VARS;
void r3m2si(double *ml, adouble *aq, adouble *aqd,
adouble *fgen, adouble *aqdd, VARS_ *vars);
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
                     adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble retval;
   if (OBJ_OPTION==1 || OBJ_OPTION==2 ) retval = tf;
   else retval = 0.0;
  return retval;
////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
   adouble retval;
   adouble* u = controls;
   adouble* qdot = &states[3];
  if (OBJ_OPTION==1) rho = 0.0;
else if (OBJ_OPTION==2) rho = 1.e-5;
else if (OBJ_OPTION==3) rho = 1.0;
  retval = rho*dot( u, u, 3 );
  return (retval);
int i;
double g = CONSTANTS.g;

DMatrix& Fc = *CONSTANTS.Fc;

DMatrix& r = *CONSTANTS.r;

DMatrix& Im = *CONSTANTS.Im;
DMatrix& m = *CONSTANTS.m;

double pl = CONSTANTS.pl;

DMatrix& L = *CONSTANTS.L;
 DMatrix& com= *CONSTANTS.com;
double Ia1= CONSTANTS.Ia1;
DMatrix& Ia = *CONSTANTS.Ia;
adouble* F = VARS.F_ad;
adouble* qdd = VARS.qdd_ad;
adouble* qd = VARS.qdd_ad;
```

```
adouble* q = VARS.q_ad;
double ml = pl;
  q[i] = states[i];
qd[i] = states[3+i];
  F[i] = Fc(i+1)*controls[i]:
r3m2si(&m1, q, qd, F, qdd, &VARS);
derivatives[CINDEX(1)] =  qd[CINDEX(1)];
derivatives[CINDEX(2)] =  qd[CINDEX(2)];
derivatives[CINDEX(3)] =  qd[CINDEX(3)];
derivatives[CINDEX(4)] = qdd[CINDEX(1)];
derivatives[CINDEX(5)] = qdd[CINDEX(2)];
derivatives[CINDEX(6)] = qdd[CINDEX(3)];
void events(adouble* e, adouble* initial_states, adouble* final_states,
            adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
{
    int i;
   for (i=0; i< 6; i++ ) {
    e[6 + i ] = final_states[ i ];
}</pre>
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
   // Single phase problem
}
int main(void)
 double g = 9.81;
                                                        // Gravity constant [m/s2]
 double pl= 0.0;
double Ia1 = 1.16;
                                                        // Point mass of load; [kg]
// Moment of inertia of arm 1, element (3,3) [kgm^2]
double Ia1 = 1.16;
DMatrix Fc(3,1); Fc = "[-126.0;252.0; 72.0]";
DMatrix r(3,1); r = "[-105; 210; 60]";
DMatrix Im(3,1); Im = "[1.3e-3; 1.3e-3]";
DMatrix m(2,1); m = "[56.5; 60.3]";
DMatrix L(2,1); L = "[0.5; 0.98]";
                                                       // Voltage-force constant of motor [N*m/V]
// Gear ratio of motor
// Moment of inertia of motor [kg*m^2]
                                                       // Mass of arm 2 and 3 [kg]
// Length of arm 2 and 3 (inc. tool) [m]
// Center of mass coordinates of arm 2 and 3; [m]
 DMatrix com(2,2);
 DMatrix Ia(4,2);
                                                        // Moment of inertia arm 2 and 3 [kg*m^2]
 com(1,1)=0.172; com(1,2)=0.028; com(2,1)=0.205; com(2,2)=0.202;
 Ia(1,1)=2.58; Ia(1,2)=11.0;
 Ia(2,1)=2.73; Ia(2,2)=8.0;
Ia(3,1)=0.64; Ia(3,2)=0.80;
```

```
Ia(4,1)=-0.46; Ia(4,2)=0.50;
 Fc.Print("Fc");
r.Print("r");
 Im.Print("Im"):
 m.Print("m");
 L.Print("L");
com.Print("com");
 Ia.Print("Ia");
 CONSTANTS.g = g;
CONSTANTS.pl = pl;
CONSTANTS.Ia1 = Ia1;
 CONSTANTS.Fc = &Fc;
CONSTANTS.r = &r;
  CONSTANTS.Im = &Im:
 CONSTANTS.m = &m;
CONSTANTS.L = &L;
  CONSTANTS.com= &com;
 CONSTANTS.Ia = &Ia:
 VARS.qdd_ad = new adouble[3];
VARS.qd_ad = new adouble[3];
VARS.q_ad = new adouble[3];
VARS.F_ad = new adouble[3];
 VARS.kw = new adouble[9]:
 VARS.kw = new adouble[9];
VARS.beta = new adouble[18];
VARS.afor = new adouble[9];
VARS.xeta = new adouble[18];
VARS.ceta = new adouble[18];
VARS.cosp = new adouble[19];
VARS.ator = new adouble[9];
 VARS.ator = new adouble[9];
VARS.sinp = new adouble[3];
VARS.rhicm = new adouble[3];
VARS.mrel12 = new adouble[3];
VARS.mrel12 = new adouble[18];
VARS.mrel22 = new adouble[3];
 VARS.rhre12 = new adouble[3];
VARS.workm3 = new adouble[9];
VARS.works1 = new adouble[120];
VARS.works2 = new adouble[12];
VARS.workv3 = new adouble[6];
VARS.workv6 = new adouble[24];
VARS.workv6 = new adouble[24];
 VARS.mbges = new adouble[24];
VARS.chhges = new adouble[3];
VARS.inertc = new adouble[27];
VARS.inerttg = new adouble[27];
VARS.inerth = new adouble[108];
 VARS.workam = new adouble[144];
VARS.workas = new adouble[40];
VARS.wworkm = new adouble[54];
VARS.wworkw = new adouble[9];
Alg algorithm;
Sol solution;
     Prob problem;
problem.name
                                 = "Manutec R3 robot problem";
      problem.outfilename
                                                         = "manutec.txt";
problem.nphases
      problem.nlinkages
                                                         = 0:
      psopt_level1_setup(problem);
```

```
problem.phases(1).nstates = 6;
problem.phases(1).ncontrols = 3;
    problem.phases(1).nevents = 12;
problem.phases(1).npath = 0;
    problem.phases(1).nodes
                                                = "[20, 30, 40, 60, 80]";
   psopt_level2_setup(problem, algorithm);
DMatrix qmax(1,3), qdmax(1,3), qddmax(1,3);
    // Joint position limits in rad
    qmax(1) = 2.97; qmax(2) = 2.01; qmax(3) = 2.86;
    // Joint angular velocity limits in rad/s
    qdmax(1) = 3.0; qdmax(2) = 1.5; qdmax(3) = 5.2;
   problem.phases(1).bounds.lower.states = (-qmax || -qdmax);
problem.phases(1).bounds.upper.states = ( qmax || qdmax);
    DMatrix umax(1,3);
    // Control variable limits in V
    umax(1) = 7.5; umax(2) = 7.5; umax(3) = 7.5;
    problem.phases(1).bounds.lower.controls = -umax;
    problem.phases(1).bounds.upper.controls = umax;
    DMatrix qi(1,3), qf(1,3), qdi(1,3), qdf(1,3);
    // Initial joint positions in rad
    qi(1) = 0.0; qi(2) = -1.5; qi(3) = 0.0;
    // Final joint positions in rad qf(1) = 1.0; qf(2) = -1.95; qf(3) = 1.0;
    // Initial joint velocities in rad/s
    qdi = zeros(1,3);
    // Final joint velocities in rad/s
    qdf = zeros(1,3);
     \begin{tabular}{ll} problem.phases(1).bounds.lower.events = (qi || qdi || qf || qdf); \\ problem.phases(1).bounds.upper.events = (qi || qdi || qf || qdf); \\ \end{tabular} 
   problem.phases(1).bounds.lower.StartTime = 0.0;
problem.phases(1).bounds.upper.StartTime = 0.0;
    problem.phases(1).bounds.upper.StartTime
    if (OBJ_OPTION==1 || OBJ_OPTION==2) {
  problem.phases(1).bounds.lower.EndTime
                                                  = 0.0;
     problem.phases(1).bounds.upper.EndTime
    else {
     problem.phases(1).bounds.lower.EndTime
                                                 = 0.53;
= 0.53;
    problem.phases(1).bounds.lower.EndTime
```

```
problem.integrand_cost = &integrand_cost;
  = problem.phases(1).nodes(1);
  int nnodes
                        = problem.phases(1).ncontrols;
= problem.phases(1).nstates;
  int ncontrols
  state_guess(1,colon()) = linspace( qi(1), qf(1), nnodes );
state_guess(2,colon()) = linspace( qi(2), qf(2), nnodes );
state_guess(3,colon()) = linspace( qi(3), qf(3), nnodes );
state_guess(4,colon()) = linspace( qi(4), qf(4), nnodes );
state_guess(5,colon()) = linspace( qi(5), qf(5), nnodes );
state_guess(6,colon()) = linspace( qi(6), qf(6), nnodes );
  algorithm.nlp_iter_max
                         = 1000:
                         = 1.e-6;
= "IPOPT";
  algorithm.nlp_tolerance
  algorithm.nlp_method
  algorithm.scaling
                         = "automatic";
  algorithm.derivatives
                         = "automatic":
  algorithm.mesh_refinement
                         = "automatic";
  algorithm.ode_tolerance
                         = 1.e-5;
  algorithm.mr_max_iterations
psopt(solution, problem, algorithm);
DMatrix x, u, t;
         = solution.get_states_in_phase(1);
         = solution.get_controls_in_phase(1);
         = solution.get_time_in_phase(1);
x.Save("x.dat");
  u.Save("u.dat");
  t.Save("t.dat");
  DMatrix q = x( colon(1,3), colon() );
DMatrix qd= x( colon(4,6), colon() );
```

```
plot(t,q,problem.name+": positions","t", "q (rad)", "q1 q2 q3");
    plot(t,qd,problem.name+": velocities","t", "qdot (rad/s)", "qd1 qd2 qd3");
     plot(t,u(1,colon()),problem.name+": control u1","time (s)", "control", "u1");
    \verb|plot(t,u(2,colon()),problem.name+": control u2","time (s)", "control", "u2");|\\
    \verb|plot(t,u(3,colon()),problem.name+": control u3","time (s)", "control", "u3");|\\
    plot(t,q,problem.name+": positions","t", "q (rad)", "q1 q2 q3", "pdf",
                         "positions.pdf");
    plot(t,qd,problem.name+": velocities","t", "qdot (rad/s)", "qd1 qd2 qd3", "pdf",
                          "velocities.pdf");
     plot(t,u,problem.name+": controls","time (s)", "controls", "u1 u2 u3",
 "pdf", "controls.pdf");
 {
adouble mhges;
adouble* kw = vars->kw;
adouble* beta = vars->beta;
adouble* afor = vars->afor;
adouble* wabs = vars->wabs;
adouble* zeta = vars->zeta;
adouble* cosp = vars->cosp;
adouble* ator = vars->ator;
adouble* sinp = vars->sinp;
adouble* rhicm = vars->rhicm;
adouble* genvd = vars->genvd;
adouble* mrel12 = vars->mrel12;
adouble* mrel22 = vars->mrel22:
adouble* rhrel2 = vars->rhrel2;
adouble* workm3 = vars->workm3:
adouble* workm6 = vars->workm6;
adouble* works1 = vars->works1:
adouble* works2 = vars->works2;
adouble* workv3 = vars->workv3:
adouble* workv6 = vars->workv6;
adouble* cmhges = vars->cmhges;
adouble* ihhges = vars->ihhges;
adouble* inertc = vars->inertc;
adouble* inertg = vars->inertg;
adouble* inerth = vars->inerth;
adouble* workam = vars->workam;
adouble* workas = vars->workas;
adouble* wworkm = vars->wworkm;
adouble* wworkv = vars->wworkv;
/* Simulation model equations of the Manutec r3 robot (DFVLR model 2) */
/* Similation model equations of the manufactor for the model 2/ 7/

* This is a modified C++ translation of the original Fortran subroutine R3M2SI */

/* by Otter and co-workers, published here with kind persmission from Dr. Martin Otter */
/* DSL, Germany */
/* Procedure purpose: */   
/* This subroutine calculates the generalized accelerations (AQDD) for */  
     the Manutec r3 robot of the DFVLR model 2. This model is based on */ the following assumptions: */
      - The last 3 joints (joints 4,5,6) of the robot hand do not move. */
        This corresponds to the case that the brakes in these joints are */ blocked (joints 4,5,6 are taken into account in model 1). */
     - The robot consists of a base body (the environment), three arms */
```

```
and three rotors. The rotors represent the inertia effects of the */
/*
/*
/*
          motors and of the wheels of the gear boxes. The rotors are */ embedded in the preceeding arms, e.g. the rotor 2, which drives */ arm2, is embedded in arm1. */
/*
       - Arms and rotors are considered to be rigid bodies. */
     - Elasticity, backlash and friction in the gear boxes are neglected. */
       - The motors are modelled as ideal voltage-torque converters */
          without any dynamic effects. As input arguments of the subroutine */
the torques at the gear output (FGEN in <Nm>) must be given. If the */
voltage (U in <V>) at the input of the current regulator of the */
motor is given, FGEN must be calculated (before calling this */
/*
/*
/*
.
/*
/*
          FGEN(1) = -126.0*U(1) */
FGEN(2) = 252.0*U(2) */
FGEN(3) = 72.0*U(3) */
/*
/*
       - At the robot's tip a load mass (ML) is attached. It can range \ast/
/*
          between 0 ... 15 kg. */
       Given the actual value ML of the load mass, the joint angles AQ(i), */ the derivatives of the joint angles AQD(i), and the driving torques */ in the joints FGEN(i), the second derivatives of the joint angles */
        AQDD(i) are calculated by this subroutine. */
       CALL R3M2SI (ML, AQ, AQD, FGEN, AQDD) */
               : IN, DOUBLE, <kg>, 0<=ML<=15 */
       ML
             /*
/*
       AQ
/*
/*
/*
/*
/*
                     (The given limits are hardware constraints by limit switches). 
 \ast /
                    Vector of generalized coordinates (relative angles between */
                     two contigous robot arms). */
                    AQ(1) is not used in this subroutine, because it is not */
/*
/*
/*
/*
/*
/*
       needed to calculate AQDD. */
AQD : IN, DOUBLE(3), <rad/sec>, */
                                                 -3.0 <= AQD(1) <= 3.0 (+/- 172 deg/sec), */
-1.5 <= AQD(2) <= 1.5 (+/- 86 deg/sec), */
-5.2 <= AQD(3) <= 5.2 (+/- 298 deg/sec) */
                    Derivative of AQ. */
       FGEN : IN, DOUBLE(3), <Nm>,
                                                       -945.0 <= FGEN(1) <= 945.0, */
-1890.0 <= FGEN(2) <= 1890.0, */
-540.0 <= FGEN(3) <= 540.0 */
       Torque at the gear output. */
AQDD : OUT, DOUBLE(3), <rad/sec**2> */
Second derivative of AQ. */
/*
/*
/* Bibliography: */
/*
     A detailed description of the model, together with the body-data */
/*
/*
       (mass, center of mass etc. of the arms and rotors) is given in */
          Otter M., Tuerk S., Mathematical Model of the Manutec r3 Robot, */
(DFVLR Model No. 2), DFVLR - Oberpfaffenhofen, Institut fuer */
Dynamik der Flugsysteme, D-8031 Wessling, West Germany, */
/*
/*
/*
                    corrected version april 1988. */
       This subroutine was generated by the program MYROBOT. See \ast/
/*
/*
/*
          Otter M., Schlegel S., Symbolic generation of efficient simulation */
codes for robots. 2nd European Simulation Multiconference, */
June 1-3, 1988, Nice. */
       The underlying multibody algorithm is a modified version of */
                   H., Johanni R., Otter M., A very efficient algorithm for the */ simulation of robots and similar multibody systems without */
/*
/*
/*
/*
                     inversion of the mass matrix. IFAC/IFIP/IMACS International \ast/
                    Symposium on Theory of Robots, december 3-5, 1986, Vienna, */
/* Remarks: */
       - The limits given for the input variables are not checked in */
this subroutine. The user is responsible for proper data. */
       - If a SINGLE PRECISION version of this subroutine is desired, just */
          change all strings from DOUBLE PRECISION to REAL in the declaration \ast/ part. \ast/
/* Copyright: */
       1988 DFVLR - Institut fuer Dynamik der Flugsysteme */
/* Life cycle: */
```

```
1988 APR M. Otter, S. Tuerk (DFVLR)
                                                                                             : specified. */
        1988 APR M. Otter (DFVLR) : generated. */
1988 APR M. Otter, C. Schlegel, S. Tuerk (DFVLR): tested. */
      Statistical information (MySymbol-Version 1.2) */
      1. Number of Operations: */
                                                   +-| * | / | sin | cos | sqrt| */
      Without simplifications 3180 | 3702 |
                                                                           261
      Terms simplified
                                                                          ----|----|-
      Unnecessary statements
                                                    140 | 159 | 17 | 2 | 2 |
      removed
                                                                                                           01 */
      2. Storage information: */
                                         INTEGER |
      available storage
                                       100000 | 100.0 % |
      array-elements
                                           1412 | 1.4 % |
                                        104 | 0.1 % |
      statement buffer
                                             2552 | 2.6 % |
/* used storage
/*
/* free storage
                                         4068 | 4.1 % | */
                                           95932 | 95.9 % | */
/* Parameter adjustments */
        --aqdd;
       --fgen;
       --aqd;
      --aq;

/* Function Body */
workv3[14] = *ml * .98;
workv3[17] = workv3[14] + 12.1806;
mhges = *ml + 60.3;
cmhges[0] = 1.6884 / mhges;
cmhges[0] = workv3[17] / mhges;
workv3[20] = workv3[14] * .98;
ihhges[0] = workv3[20] + 7.8704812;
ihhges[0] = workv3[20] + 8.1077564;
sinp[1] = sin(aq[2]);
cosp[1] = cos(aq[2]);
wworkv[0] = mhges * cmhges[0];
wworkv[0] = mhges * cmhges[2];
wworkv[3] = cmhges[0] * wworkv[0];
wworkv[6] = wworkv[3] * wworkv[5];
wworkv[6] = wworkv[3] + wworkv[5];
wworkm[0] = wworkv[6] - wworkv[5];
wworkm[0] = wworkv[0] * cmhges[2];
inertc[18] = ihhges[0] - wworkw[0];
inertc[22] = ihhges[4] - wworkw[6];
inertc[24] = -.0110568 - wworkm[6];
inertc[26] = .4372752 - wworkm[8];
sinp[2] = sin(aq[3]);
cosp[2] = cos(aq[3]):
sinp[2] = sin(aq[3]);
cosp[2] = cos(aq[3]);
/* ** The equations of motion have been generated with the algorithm */
/* ** of Brandl/Johanni/Otter (variant 6) */
kw[3] = aqd[2] * 4.9544125 - wabs[5] * 2.45219;
```

```
kw[4] = wabs[4] * 6.7759085;
kw[5] = aqd[2] * -2.45219 + wabs[5] * 2.311496;
-- Quantities of body 3 */
workv3[19] = -sinp[2] * cmhges[2];
workv3[20] = cosp[2] * cmhges[2];
workm3[4] = cosp[2] * inertc[22];
workm3[6] = sinp[2] * inertc[22];
workm3[7] = -sinp[2] * inertc[26];
workm3[8] = cosp[2] * inertc[26];
inertc[21] = -inertc[24] * sinp[2];
inertc[22] = workm3[4] * cosp[2] - workm3[7] * sinp[2];
inertc[24] *= cosp[2];
 inertc[22] = workm3[4] * cosp[2] - workm3[7] * sinp[2];
inertc[24] *= cosp[2];
inertc[25] = workm3[4] * sinp[2] + workm3[7] * cosp[2];
inertc[26] = workm3[6] * sinp[2] + workm3[8] * cosp[2];
workv3[21] = mhges * cmhges[0];
workv3[22] = mhges * workv3[9];
workv3[23] = mhges * workv3[21];
workv3[24] = cmhges[0] * workv3[21];
workv3[25] = workv3[19] * workv3[22];
workv3[26] = workv3[20] * workv3[25] + workv3[26];
inerth[18] = workv3[27] - workv3[24];
inerth[22] = workv3[27] - workv3[26];
inerth[26] = workv3[27] - workv3[26];
inerth[27] = workv3[27] * workv3[26];
inerth[28] = workv3[27] * workv3[29];
inerth[29] = workv3[21] * workv3[29];
    inerth[24] = -workv3[21] * workv3[20];
inerth[25] = -workv3[22] * workv3[20];
    inerth[25] = -workv5[22] ;
inerth[18] += inertc[18];
inerth[21] += inertc[21];
    inerth[22] += inertc[22];
inerth[24] += inertc[24];
    inerth[25] += inertc[25];
inerth[26] += inertc[26];
  inerth[26] += inertc[26];
wabs[6] = aqd[3] + aqd[2];
workv3[1] = wabs[5] * aqd[3];
workv3[2] = -wabs[4] * aqd[3];
workv3[6] = wabs[4] * .5;
workv3[7] = -aqd[2] * .5;
workv3[9] = -wabs[5] * workv3[7];
workv3[10] = wabs[5] * workv3[6];
workv3[11] = aqd[2] * workv3[7] - wabs[4] * workv3[6];
rhicm[6] = mbres * cmbres[0]:
   workvo[ii] = adv[2] * workvo[i];
rhicm[6] = mhges * cmhges[0];
rhicm[7] = mhges * workv3[19];
rhicm[8] = mhges * workv3[20];
kw[6] = inerth[18] * wabs[6] + inerth[21] * wabs[4] + inerth[24] * wabs[5]
    kw[7] = inerth[21] * wabs[6] + inerth[22] * wabs[4] + inerth[25] * wabs[5]
    kw[8] = inerth[24] * wabs[6] + inerth[25] * wabs[4] + inerth[26] * wabs[5]
      ,
ator[3] = -wabs[4] * kw[5] + wabs[5] * kw[4];
   ator[3] = -wabs[1] * kw[3] + ads[3] * kw[4];
ator[6] = -wabs[6] * kw[3] + adq[2] * kw[5];
ator[5] = -aqd[2] * kw[4] + wabs[4] * kw[3];
ator[6] = -wabs[4] * kw[8] + wabs[5] * kw[7];
ator[7] = -wabs[6] * kw[6];
ator[8] = -wabs[6] * kw[7] + wabs[4] * kw[6];
   ator(8) = -wabs(6) * kW(7) + wabs(4) * kW(6);
workv3[15] = wabs[4] * rhicm[8] - wabs[5] * rhicm[7];
workv3[16] = wabs[5] * rhicm[6] - wabs[6] * rhicm[8];
workv3[17] = wabs[6] * rhicm[7] - wabs[4] * rhicm[6];
afor[6] = -wabs[4] * workv3[17] + wabs[5] * workv3[16];
afor[7] = -wabs[5] * workv3[15] + wabs[6] * workv3[17];
** Backward recursion -----
-- Quantities of body 3 */
  -- Quantities of body 3 */
mrel22[2] = inerth[18] + 4.68;
workw6[0] = ator[6] - inerth[21] * workv3[1] - inerth[24] * workv3[2] +
rhicm[8] * workv3[10] - rhicm[7] * workv3[11];
workv6[1] = ator[7] - inerth[22] * workv3[1] - inerth[25] * workv3[2] -
rhicm[8] * workv3[9] + rhicm[6] * workv3[11];
workv6[2] = ator[8] - inerth[25] * workv3[1] - inerth[26] * workv3[2] +
rhicm[7] * workv3[9] - rhicm[6] * workv3[10];
workv6[3] = afor[6] - rhicm[8] * workv3[1] + rhicm[7] * workv3[9] - mhges
* workv3[9]:
      * workv3[9];
    workv6[3], workv3[4] = afor[7] - rhicm[6] * workv3[2] - mhges * workv3[10]; rhre12[2] = fgen[3] + workv6[0];
  rhrel2[2] = fgen[3] + workv6[0];
mrel12[12] = inerth[18] + .078 + rhicm[8] * .5;
workv6[18] = workv6[0] - workv6[4] * .5;
workv6[19] = workv6[1] + workv6[3] * .5;
workm6[108] = inerth[18] - rhicm[8] * -.5;
workm6[112] = -rhicm[8] + mhges * -.5;
workm6[115] = inerth[22] + rhicm[8] * .5;
workm6[117] = rhicm[8] + mhges * .5;
inertg[36] = workm6[108] + 4.9544125 - workm6[112] * .5;
inertg[43] = workm6[115] + 6.7759085 + workm6[117] * .5;
```

```
inertg[48] = inerth[24] - 2.45219 - rhicm[6] * .5;
inertg[49] = inerth[25] - rhicm[7] * .5;
inertg[50] = inerth[26] + 2.311496;
inertg[60] = -11.5825 - rhicm[8] - mhges * .5;
inertg[62] = rhicm[6] + 9.718;
inertg[67] = -9.718 - rhicm[6];
beta[6] = ator[3] + workv6[18];
beta[7] = ator[4] + workv6[19];
beta[8] = ator[5] + workv6[2];
works2[0] = mrel12[12] / mrel22[2];
works2[1] = inerth[21] / mrel22[2];
works2[4] = -rhicm[8] / mrel22[2];
works2[5] = rhicm[7] / mrel22[2];
inertg[36] -= mrel12[12] * works2[0];
inertg[42] = inerth[21] - mrel12[12] * works2[1];
inertg[48] -= inerth[21] * works2[1];
inertg[48] -= inerth[21] * works2[2];
inertg[49] -= inerth[21] * works2[2];
inertg[60] -= inerth[21] * works2[4];
inertg[61] = -inerth[21] * works2[4];
inertg[61] = -inerth[21] * works2[4];
inertg[61] -= -inerth[21] * works2[4];
                                   inertg[60] -= mrel12[12] * works2[4];
inertg[61] = -inerth[21] * works2[4];
inertg[62] -= inerth[24] * works2[4];
inertg[66] = rhicm[7] - mrel12[12] * works2[5];
inertg[67] -= inerth[21] * works2[5];
inertg[68] = -inerth[24] * works2[5];
                            inertg[68] = -inerth[24] * works2[5];
beta[6] == works2[0] * rhrel2[2];
beta[7] -= works2[1] * rhrel2[2];
beta[8] -= works2[2] * rhrel2[2];
-- (uantities of body 2 */
mrel22[1] = inertg[36] + 57.33;
workv6[0] = beta[6] - inertg[42] * zeta[7] - inertg[48] * zeta[8];
workv6[1] = beta[7] - inertg[43] * zeta[7] - inertg[49] * zeta[8];
workv6[1] = beta[7] - inertg[49] * zeta[7] - inertg[49] * zeta[8];
workv6[1] = fgen[2] + workv6[0];
works1[8] = sinp[1] * inertg[42] + cosp[1] * inertg[48];
works1[11] = sinp[1] * inertg[60] + cosp[1] * inertg[66];
workv6[14] = sinp[1] * workv6[1] + cosp[1] * workv6[2];
worksa[30] = cosp[1] + sinp[1];
worksa[31] = cosp[1] - sinp[1];
worksa[32] = cosp[1] * sinp[1];
                            workas[31] = cosp[1] - sinp[1];
workas[33] = workas[30] * workas[31];
workas[32] = cosp[1] * sinp[1];
workas[34] = workas[32] + workas[32];
workas[0] = inertg[50] + inertg[43];
workas[1] = inertg[50] - inertg[43];
workas[1] = inertg[50] - inertg[43];
workas[4] = workas[0] / 2.;
workas[8] = workas[1] / 2.;
workas[8] = workas[33] * workas[5] + workas[34] * inertg[49];
workam[115] = workas[4] + workas[8];
workas[20] = inertg[68] + inertg[61];
workas[21] = inertg[68] - inertg[61];
workas[24] = workas[20] / 2.;
workas[25] = workas[21] / 2.;
workas[28] = -inertg[62] - inertg[67];
workas[28] = workas[23] / 2.;
workas[28] = workas[33] * workas[25] - workas[34] * workas[27];
workas[28] = workas[33] * workas[28];
inertg[14] = workas[11] / mre122[1];
inertg[14] = workas[11] / mre122[1];
inertg[32] = workas[13] * workas[2] * workas[5];
beta[2] = workas[14] + works[2] * rhre12[1];
-- Quantities of body 1 */
mre122[0] = beta[2] - inertg[52] * 9.81;
   workv6[11];
genvd[2] = rhrel2[2] / mrel22[2];
                                       aqdd[1] = genvd[0];
```

Table 3.3: Mesh refinement statistics: Manutec R3 robot problem

Iter	DM	Μ	NV	NC	OE	$^{\mathrm{CE}}$	$_{ m JE}$	$^{ m HE}$	RHS	$\epsilon_{ ext{max}}$	CPUa
1	LGL-ST	20	182	133	43	43	35	0	860	4.676e-05	8.334e-01
2	LGL-ST	25	227	163	34	35	30	0	875	3.636e-05	3.836e-01
3	LGL-ST	35	317	223	12	13	12	0	455	2.787e-05	2.682e-01
4	LGL-ST	49	443	307	35	36	33	0	1764	7.655e-06	1.356e + 00
CPU _b	-	-	-	-	-	-	-	-	-	=	4.804e+00
_	_	-	-	_	124	127	110	0	3954	_	7.645e + 00

Key: Iter=iteration number, DM= discretization method, M=number of nodes, NV=number of variables, NC=number of constraints, OE=objective evaluations, CE = constraint evaluations, JE = Jacobian evaluations, HE = Hessian evaluations, RHS = ODE right hand side evaluations, $\epsilon_{\rm max}$ = maximum relative ODE error, CPUa = CPU time in seconds spent by NLP algorithm, CPUb = additional CPU time in seconds spent by PSOPT

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.62, 3.63 and 3.64, which contain the elements of the position vector $\mathbf{q}(t)$, the velocity vector $\dot{\mathbf{q}}(t)$, and the controls $\mathbf{u}(t)$, respectively. The mesh refinement process is described in Table 3.3.

```
PSOPT results summary
_____
Problem:
        Manutec R3 robot problem
CPU time (seconds): 7.645063e+00
NLP solver used:
                IPOPT
PSOPT release number: 4.0
Date and time of this run: Thu Feb 21 16:10:35 2019
Optimal (unscaled) cost function value:
                                       2.040419e+01
Phase 1 endpoint cost function value: 0.000000e+00
Phase 1 integrated part of the cost: 2.040419e+01
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 5.300000e-01
Phase 1 maximum relative local error: 7.655210e-06
NLP solver reports: The problem has been solved!
```




Figure 3.62: States q_1,q_2 and q_3 for the Manutec R3 robot minimum energy problem




Figure 3.63: States \dot{q}_1,\dot{q}_2 and \dot{q}_3 for the Manutec R3 robot minimum energy problem




Figure 3.64: Controls u_1, u_2 and u_3 for the Manutec R3 robot minimum energy problem

3.26 Minimum swing control for a container crane

Consider the following optimal control problem [40], which seeks to minimise the load swing of a container crane, while the load is transferred from one location to another. Find $u(t) \in [0, t_f]$ to minimize the cost functional

$$J = 4.5 \int_0^{t_f} \left[x_3^2(t) + x_6^2(t) \right] dt$$
 (3.109)

subject to the dynamic constraints

$$\dot{x}_1 = 9x_4
\dot{x}_2 = 9x_5
\dot{x}_3 = 9x_6
\dot{x}_4 = 9(u_1 + 17.2656x_3)
\dot{x}_5 = 9u_2
\dot{x}_6 = -\frac{9}{x_2}[u_1 + 27.0756x_3 + 2x_5x_6]$$
(3.110)

the boundary conditions

$$\begin{aligned}
 x_1(0) &= 0 & x_1(t_f) &= 10 \\
 x_2(0) &= 22 & x_2(t_f) &= 14 \\
 x_3(0) &= 0 & x_3(t_f) &= 0 \\
 x_4(0) &= 0 & x_4(t_f) &= 2.5 \\
 x_5(0) &= -1 & x_5(t_f) &= 0 \\
 x_6(0) &= 0 & x_6(t_f) &= 0
 \end{aligned}$$
(3.111)

and the bounds

$$-2.83374 \le u_1(t) \le 2.83374,$$

$$-0.80865 \le u_2(t) \le 0.71265,$$

$$-2.5 \le x_4(t) \le 2.5,$$

$$-1 \le x_5(t) \le 1.$$
(3.112)

The \mathcal{PSOPT} code that solves this problem is shown below.

```
crane.cxx
#include "psopt.h"
adouble endpoint cost(adouble* initial states, adouble* final states,
                 adouble* parameters,adouble& t0, adouble& tf,
                 adouble* xad, int iphase, Workspace* workspace)
   return 0;
}
////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
                  adouble* parameters, adouble& time, adouble* xad,
                  int iphase, Workspace* workspace)
   adouble x3 = states[CINDEX(3)];
adouble x6 = states[CINDEX(6)];
   return 4.5*( pow(x3,2) + pow(x6,2) );
void dae(adouble* derivatives, adouble* path, adouble* states,
       adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble xdot, ydot, vdot;
  adouble x1 = states[ CINDEX(1) ];
  adouble x1 = states[ CINDEX(2) ];
adouble x2 = states[ CINDEX(3) ];
adouble x3 = states[ CINDEX(3) ];
adouble x4 = states[ CINDEX(4) ];
adouble x5 = states[ CINDEX(6) ];
adouble x6 = states[ CINDEX(6) ];
  adouble u1 = controls[ CINDEX(1) ];
adouble u2 = controls[ CINDEX(2) ];
  derivatives[ CINDEX(1) ] = 9*x4;
```

```
derivatives[ CINDEX(2) ] = 9*x5;
  derivatives[ CINDEX(3) ] = 9*x6;
derivatives[ CINDEX(4) ] = 9*(u1 + 17.2656*x3);
derivatives[ CINDEX(5) ] = 9*u2;
derivatives[ CINDEX(6) ] = -(9/x2)*(u1 + 27.0756*x3 + 2*x5*x6);
}
void events(adouble* e. adouble* initial states, adouble* final states,
         adouble* parameters,adouble& t0, adouble& tf, adouble* xad,
         int iphase, Workspace* workspace)
  adouble x10 = initial_states[ CINDEX(1) ];
adouble x20 = initial_states[ CINDEX(2) ];
adouble x30 = initial_states[ CINDEX(3) ];
  adouble x40 = initial_states[ CINDEX(4) ];
adouble x50 = initial_states[ CINDEX(5) ];
  adouble x60 = initial_states[ CINDEX(6) ];
adouble x1f = final_states[ CINDEX(1) ];
  adouble x2f = final_states[ CINDEX(2) ];
  adouble x3f = final_states[ CINDEX(3) ];
  adouble x5f = final_states[ CINDEX(4) ];
adouble x5f = final_states[ CINDEX(5) ];
adouble x6f = final_states[ CINDEX(6) ];
  e[ CINDEX(1) ] = x10;
e[ CINDEX(2) ] = x20;
e[ CINDEX(3) ] = x30;
  e[ CINDEX(4) ]
              = x40;
               = x50;
  e[ CINDEX(5) ]
  e[ CINDEX(6) ]
              = x60;
  e[ CINDEX(7) ]
              = x1f;
  e[ CINDEX(8) ]
              = x2f;
  e[ CINDEX(9) ] = x3f;
  e[CINDEX(3)] = x4f;
e[CINDEX(10)] = x4f;
e[CINDEX(11)] = x5f;
e[CINDEX(12)] = x6f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
{
 // No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
   Prob problem;
problem.name = "Minimum swing control for a container crane";
   problem.outfilename
//////// Define problem level constants & do level 1 setup /////////
```

```
problem.nphases
    problem.nlinkages
                                            = 0;
    psopt_level1_setup(problem);
///////// Define phase related information & do level 2 setup /////////
problem.phases(1).nstates
    problem.phases(1).ncontrols = 2;
    problem.phases(1).nevents = 12;
    problem.phases(1).npath
problem.phases(1).nodes
                                    = 0:
                                = "[40, 60, 80]";
    psopt_level2_setup(problem, algorithm);
problem.phases(1).bounds.lower.states(1) = -5.0:
    problem.phases(1).bounds.lower.states(2) = -5.0;
problem.phases(1).bounds.lower.states(2) = -5.0;
problem.phases(1).bounds.lower.states(3) = -5.0;
    problem.phases(1).bounds.lower.states(4) = -2.5;
problem.phases(1).bounds.lower.states(5) = -1.0;
    problem.phases(1).bounds.lower.states(6) = -5.0;
    problem.phases(1).bounds.upper.states(1) = 15.0;
problem.phases(1).bounds.upper.states(2) = 25.0;
problem.phases(1).bounds.upper.states(3) = 15.0;
problem.phases(1).bounds.upper.states(4) = 2.5;
    problem.phases(1).bounds.upper.states(5) = 1.0;
problem.phases(1).bounds.upper.states(6) = 15.0;
    problem.phases(1).bounds.lower.controls(1) = -2.83374;
    problem.phases(1).bounds.lower.controls(2) = -0.80865;
problem.phases(1).bounds.upper.controls(1) = 2.83374;
    problem.phases(1).bounds.upper.controls(2) = 0.71265;
     // Initial states
    problem.phases(1).bounds.lower.events(1) = 0.0;
    problem.phases(1).bounds.lower.events(2) = 22.0;
problem.phases(1).bounds.lower.events(3) = 0.0;
    problem.phases(1).bounds.lower.events(4) = 0.0;
problem.phases(1).bounds.lower.events(5) = -1.0;
    problem.phases(1).bounds.lower.events(6) = 0.0;
     // Final states
    problem.phases(1).bounds.lower.events(7) =
    problem.phases(1).bounds.lower.events(8) = 14.0;
problem.phases(1).bounds.lower.events(9) = 0.0;
    problem.phases(1).bounds.lower.events(10)= 2.5:
    problem.phases(1).bounds.lower.events(11)= 0.0;
    problem.phases(1).bounds.lower.events(12)= 0.0;
    problem.phases(1).bounds.upper.events = problem.phases(1).bounds.lower.events;
    problem.phases(1).bounds.lower.StartTime
                                                    = 0.0:
    problem.phases(1).bounds.upper.StartTime
    problem.phases(1).bounds.lower.EndTime
problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
    problem.endpoint_cost = &endpoint_cost;
problem.dae = &dae;
     problem.events = &events;
    problem.linkages = &linkages;
```

```
DMatrix x0(6.20):
  x0(1,colon()) = linspace(0.0,10.0, 20);
x0(2,colon()) = linspace(22.0,14.0, 20);
  x0(3,colon()) = linspace(0.,0., 20);
x0(4,colon()) = linspace(0.,2.5, 20);
x0(5,colon()) = linspace(-1.0,0., 20);
  x0(6,colon()) = linspace(0.,0., 20);
  problem.phases(1).guess.controls
                           = zeros(2, 20);
  problem.phases(1).guess.states
problem.phases(1).guess.time
                            = x0:
                            = linspace(0.0, 1.0, 20);;
algorithm.nlp_method
                           = "IPOPT";
                           = "automatic";
  algorithm.scaling
  algorithm.derivatives
                           = "automatic";
  algorithm.nlp_iter_max algorithm.nlp_tolerance
                           = 1000:
                           = 1.e-6;
= "Legendre";
  algorithm.collocation_method
psopt(solution, problem, algorithm);
DMatrix x = solution.get_states_in_phase(1);
DMatrix u = solution.get_controls_in_phase(1);
  DMatrix t = solution.get_time_in_phase(1);
u.Save("u.dat");
t.Save("t.dat");
  DMatrix x13 = x(colon(1,3), colon() );
DMatrix x46 = x(colon(4,6), colon() );
\verb|plot(t,x13,problem.name + ": states x1, x2 and x3", "time (s)", "states", "x1 x2 x3"); \\
  plot(t,x46,problem.name + ": states x4, x5 and x6", "time (s)", "states", "x4 x5 x6");
  plot(t,u,problem.name + ": controls", "time", "controls", "u1 u2");
  plot(t,x13,problem.name + ": states x1, x2 and x3", "time (s)", "states", "x1 x2 x3",
                      "pdf", "crane_states13.pdf");
  plot(t,x46,problem.name + ": states x4, x5 and x6", "time (s)", "states", "x4 x5 x6", "pdf", "crane_states46.pdf");
  plot(t,u,problem.name + ": controls", "time", "controls", "u1 u2",
                   "pdf", "crane_controls.pdf");
}
END OF FILE
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.65, 3.66 and 3.67, which contain the elements of the state x_1 to x_3 , x_4 to x_6 , and the controls, respectively.

PSOPT results summary

Problem: Minimum swing control for a container crane

CPU time (seconds): 2.236445e+01

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 17:14:50 2019

Optimal (unscaled) cost function value: 5.151343e-03 Phase 1 endpoint cost function value: 0.000000e+00 Phase 1 integrated part of the cost: 5.151343e-03

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 1.000000e+00

Phase 1 maximum relative local error: 1.091430e-04 NLP solver reports: The problem has been solved!

3.27 Minimum time to climb for a supersonic aircraft

Consider the following optimal control problem, which finds the minimum time to climb to a given altitude for a supersonic aircraft [4]. Minimize the cost functional

$$J = t_f \tag{3.113}$$

subject to the dynamic constraints

$$\dot{h} = v \sin \gamma
\dot{v} = \frac{1}{m} [T(M,h) \cos \alpha - D] - \frac{\mu}{(R_e+h)^2} \sin \gamma
\dot{\gamma} = \frac{1}{mv} [T(M,h) \sin \alpha + L] + \cos \gamma \left[\frac{v}{(R_e+h)} - \frac{\mu}{v(R_e+h)^2} \right]
\dot{w} = \frac{-T(M,h)}{I_{sp}}$$
(3.114)

where h is the altitude (ft), v is the velocity (ft/s), γ is the flight path angle (rad), w is the weight (lb), L is the lift force, D is the drag force (lb), T is




Figure 3.65: States x_1, x_2 and x_3 for minimum swing crane control problem




Figure 3.66: States x_4, x_5 and x_6 for minimum swing crane control problem




Figure 3.67: Controls for minimum swing crane control problem

the thrust (lb), M = v/c is the mach number, $m = w/g_0$ (slug) is the mass, c(h) is the speed of sound (ft/s), R_e is the radious of Earth, and μ is the gravitational constant. The control input α is the angle of attack (rad).

The speed of sound is given by:

$$c = 20.0468\sqrt{\theta} \tag{3.115}$$

where $\theta = \theta(h)$ is the atmospheric temperature (K).

The aerodynamic forces are given by:

$$D = \frac{1}{2}C_D S \rho v^2$$

$$L = \frac{1}{2}C_L S \rho v^2$$
(3.116)

where

$$C_L = c_{L\alpha}(M)\alpha$$

$$C_D = c_{D0}(M) + \eta(M)c_{L\alpha}(M)\alpha^2$$
(3.117)

where C_L and C_D are aerodynamic lift and drag coefficients, S is the aerodynamic reference area of the aircraft, and $\rho = \rho(h)$ is the air density.

The boundary conditions are given by:

$$h(0) = 0 \text{ (ft)},$$

$$h(t_f) = 65600.0 \text{ (ft)}$$

$$v(0) = 424.260 \text{ (ft/s)},$$

$$v(t_f) = 968.148 \text{ (ft/s)}$$

$$\gamma(0) = \gamma(t_f) = 0 \text{ (rad)}$$

$$w(0) = 42000.0 \text{ lb}$$
(3.118)

The parameter values are given by:

$$S = 530 \text{ (ft}^2),$$

 $I_{sp} = 1600.0 \text{ (sec)}$
 $\mu = 0.14046539 \times 10^{17} \text{ (ft}^3/\text{s}^2),$ (3.119)
 $g_0 = 32.174 \text{ (ft/s}^2)$
 $R_e = 20902900 \text{ (ft)}$

The variables $c_{L\alpha}(M)$, $c_{D0}(M)$, $\eta(M)$ are interpolated from 1-D tabular data which is given in the code and also in [4], using spline interpolation, while the thrust T(M,h) is interpolated from 2-D tabular data given in the code and in [4], using 2D spline interpolation.

The air density ρ and the atmospheric temperature θ were calculated using the US Standard Atmosphere Model 1976⁴, based on the standard temperature of 15 (deg C) at zero altitude and the standard air density of 1.22521 (slug/ft³) at zero altitude.

The \mathcal{PSOPT} code that solves this problem is shown below.

⁴see http://www.pdas.com/programs/atmos.f90

```
struct Constants {
 double g0;
double S;
  double Re;
 double Isp;
double mu;
 DMatrix* CLa_table;
DMatrix* CDO_table;
 DMatrix* eta_table;
DMatrix* T_table;
DMatrix* M1;
  DMatrix* M2;
  DMatrix* h1:
  DMatrix* htab;
  DMatrix* ttab:
  DMatrix* ptab;
 DMatrix* gtab;
};
typedef struct Constants Constants_;
void atmosphere(adouble* alt,adouble* sigma,adouble* delta,adouble* theta, Constants_& CONSTANTS);
void atmosphere_model(adouble* rho, adouble* M, adouble v, adouble h, Constants_& CONSTANTS);
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
                       adouble* parameters, adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
return tf;
/////////////// Define the integrand (Lagrange) cost function //////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
   return 0.0;
void dae(adouble* derivatives, adouble* path, adouble* states,
         adouble* controls, adouble* parameters, adouble& time,
         adouble* xad, int iphase, Workspace* workspace)
ſ
 Constants_& CONSTANTS = *( (Constants_ *) workspace->problem->user_data );
 adouble alpha = controls[ CINDEX(1)]; // Angle of attack (rad)
 adouble h = states[ CINDEX(1) ]; // Altitude (ft)
adouble v = states[ CINDEX(2) ]; // Velocity (ft/s)
adouble gamma = states[ CINDEX(3) ]; // Flight path angle (rad)
adouble w = states[ CINDEX(4) ]; // weight (1b)
 double g0 = CONSTANTS.g0;
double S = CONSTANTS.S;
double Re = CONSTANTS.Re;
double Isp = CONSTANTS.Isp;
double mu = CONSTANTS.mu;
  DMatrix& M1
                       = *CONSTANTS.M1:
                       = *CONSTANTS.M2;
  DMatrix& M2
                       = *CONSTANTS.h1;
  DMatrix& h1
 DMatrix& CLa_table = *CONSTANTS.CLa_table;
DMatrix& CDO_table = *CONSTANTS.CDO_table;
```

```
DMatrix& eta_table = *CONSTANTS.eta_table;
DMatrix& T_table = *CONSTANTS.T_table;
   int lM1 = length(M1);
   adouble rho;
   adouble m = w/g0;
adouble M;
   atmosphere_model( &rho, &M, v, h, CONSTANTS);
   adouble CL_a, CDO, eta, T;
   spline_interpolation( &CL_a, M, M1, CLa_table, lM1);
spline_interpolation( &CD0, M, M1, CD0_table, lM1);
spline_interpolation( &eta, M, M1, eta_table, lM1);
   spline_2d_interpolation(&T, M, h, M2, h1, T_table, workspace);
// smooth_linear_interpolation( &CL_a, M, M1, CLa_table, 1M1);
// smooth_linear_interpolation( &CDO, M, M1, CDO_table, 1M1);
// smooth_linear_interpolation( &eta, M, M1, eta_table, 1M1);
// smooth_bilinear_interpolation(&T, M, h, M2, h1, T_table);
// linear_interpolation( &CL_a, M, M1, CLa_table, lM1);
// linear_interpolation( &CDO, M, M1, CDO_table, lM1);
// linear_interpolation( &eta, M, M1, eta_table, lM1);
// bilinear_interpolation(&T, M, h, M2, h1, T_table);
     adouble CL = CL_a*alpha;
adouble CD = CDO + eta*CL_a*alpha*alpha;
     adouble D = 0.5*CD*S*rho*v*v;
     adouble L = 0.5*CL*S*rho*v*v;
    derivatives[ CINDEX(1) ] = hdot;
derivatives[ CINDEX(2) ] = vdot;
derivatives[ CINDEX(3) ] = gammadot;
derivatives[ CINDEX(4) ] = wdot;
void events(adouble* e, adouble* initial_states, adouble* final_states,
                    adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
{
                               = initial_states[CINDEX(1)];
= initial_states[CINDEX(2)];
          adouble hO
          adouble v0
         adouble gamma0 = initial_states[CINDEX(3)];
adouble w0 = initial_states[CINDEX(4)];
         adouble hf
adouble vf = final_states[CINDEX(1)];
adouble gammaf = final_states[CINDEX(3)];
          e[ CINDEX(1) ] = h0;
         e[ CINDEX(2) ] = v0;
e[ CINDEX(3) ] = gamma0;
e[ CINDEX(4) ] = w0;
e[ CINDEX(5) ] = hf;
e[ CINDEX(6) ] = vf;
e[ CINDEX(7) ] = gammaf;
```

```
void linkages( adouble* linkages, adouble* xad, Workspace* workspace) {
// Single phase problem
}
Alg algorithm;
Sol solution;
 Prob problem;
problem.name = "Minimum time to climb for a supersonic aircraft";
problem.outfilename = "climb.txt";
problem.nphases
 problem.nlinkages
              = 0:
 psopt_level1_setup(problem);
problem.phases(1).nstates = 4;
problem.phases(1).ncontrols = 1;
 problem.phases(1).nevents = 7;
problem.phases(1).npath = 0;
 problem.phases(1).nodes
           = "[30,60]";
 psopt_level2_setup(problem, algorithm);
Constants_ CONSTANTS;
 problem.user_data = (void*) &CONSTANTS;
Declare DMatrix objects to store results //////////
DMatrix x, u, t, H;
CONSTANTS.g0 = 32.174; // ft/s^2
     = 530.0; // ft<sup>2</sup>
= 20902900.0; // ft
 CONSTANTS S
```

```
CONSTANTS.Isp = 1600.00; //s
CONSTANTS.mu = 0.14076539E17; // ft^3/s^2
DMatrix M1(1,9,
0.E0, .4E0, .8E0, .9E0, 1.E0, 1.2E0, 1.4E0, 1.6E0, 1.8E0);
0.E0, .2E0, .4E0, .6E0, .8E0, 1.E0, 1.2E0, 1.4E0, 1.6E0, 1.8E0);
DMatrix h1(1.10.
0.E0, 5E3, 10.E3, 15.E3, 20.E3, 25.E3, 30.E3, 40.E3, 50.E3, 70.E3);
DMatrix CLa_table(1,9,
3.44E0, 3.44E0, 3.44E0, 3.58E0, 4.44E0, 3.44E0, 3.01E0, 2.86E0, 2.44E0);
DMatrix CDO_table(1,9,
.013E0, .013E0, .013E0, .014E0, .031E0, 0.041E0, .039E0, .036E0, .035E0);
DMatrix eta_table(1,9, .54E0, .54E0, .54E0, .54E0, .79E0, .79E0, .78E0, .89E0, .93E0, .93E0);
DMatrix T table(10.10.
24200., 24000., 20300., 17300.,14500.,12200.,10200.,5700.,3400.,100., 28000., 24600., 21100., 18100.,15200.,12800.,10700.,6500.,3900.,200., 28300., 25200., 21900., 18700.,15900.,13400.,11200.,7300.,4400.,400.,
30800., 27200., 23800., 20500.,17300.,14700.,12300.,8100.,4900.,800.,
34500., 30300., 26600., 23200.,19800.,16800.,14100.,9400.,5600.,1100.
34300., 34300., 36400., 26800.,23300.,19800.,16800.,11200.,6800.,1400.,
36100., 38000., 34900., 31300.,27300.,23600.,20100.,13400.,8300.,1700.,
34300., 36600., 38500., 36100.,31600.,28100.,24200.,16200.,10000.,2200.,
32500., 35200., 42100., 38700.,35700.,32000.,28100.,19300.,119300.,1900.,2900.,
30700., 33800., 45700., 41300.,39800.,34600.,31100.,21700.,13300.,3100.);
DMatrix htab(1,8,
                      0.0, 11.0, 20.0, 32.0, 47.0, 51.0, 71.0, 84.852);
DMatrix ttab(1,8,
288.15,\ 216.65,\ 216.65,\ 228.65,\ 270.65,\ 270.65,\ 214.65,\ 186.946); DMatrix ptab(1,8,
                 1.0, 2.233611E-1, 5.403295E-2, 8.5666784E-3, 1.0945601E-3, 6.6063531E-4, 3.9046834E-5, 3.68501E-6);
DMatrix gtab(1,8, -6.5, 0.0, 1.0, 2.8, 0.0, -2.8, -2.0, 0.0);
M1.Print("M1"):
M2.Print("M2");
h1.Print("h1"):
CLa table.Print("CLa table"):
CDO_table.Print("CDO_table");
eta table.Print("eta table"):
T table.Print("T_table");
CONSTANTS.M1
                              = &M1;
CONSTANTS.M2
                              = &M2:
CONSTANTS.h1
                               = &h1;
CONSTANTS.CLa_table = &CLa_table;
CONSTANTS.CDO_table = &CDO_table;
CONSTANTS.eta_table = &eta_table;
CONSTANTS.T_table = &T_table;
CONSTANTS.htab = &htab;
                              = &ttab;
= &ptab;
CONSTANTS.ttab
CONSTANTS.ptab
CONSTANTS.gtab
                              = &gtab;
double h0
                   = 0.0:
                  = 65600.0;
= 424.26;
double hf
double v0
                    = 968.148;
double vf
double gamma0 = 0.0;
double gammaf = 0.0;
double w0 = 42000.0;
double hmin = 0;
double hmax = 69000.0;
double vmin = 1.0;
double vmax = 2000.0;
double gammamin = -89.0*pi/180.0; // -89.0*pi/180.0;
```

```
double gammamax = 89.0*pi/180.0; // 89.0*pi/180.0;
   double gammamax = 89.0*p1/180.0;
double wmin = 0.0;
double wmax = 45000.0;
double alphamin = -20.0*pi/180.0;
double alphamax = 20.0*pi/180.0;
   double t0min = 0.0;
double t0max = 0.0;
   double tfmin = 200.0;
double tfmax = 500.0;
int iphase = 0:
     problem.phase[iphase].bounds.lower.StartTime
problem.phase[iphase].bounds.upper.StartTime
                                                                = t0min;
= t0max;
                                                                = tfmin;
= tfmax;
     {\tt problem.phase[iphase].bounds.lower.EndTime}
     problem.phase[iphase].bounds.upper.EndTime
     problem.phase[iphase].bounds.lower.states(1) = hmin;
     problem.phase[iphase].bounds.upper.states(1) = hmax;
problem.phase[iphase].bounds.lower.states(2) = vmin;
     problem.phase[iphase].bounds.upper.states(2) = vmax;
problem.phase[iphase].bounds.lower.states(3) = gammamin;
     problem.phase[iphase].bounds.upper.states(3) = gammamn;
problem.phase[iphase].bounds.lower.states(4) = wmin;
problem.phase[iphase].bounds.upper.states(4) = wmax;
     problem.phase[iphase].bounds.lower.controls(1) = alphamin;
problem.phase[iphase].bounds.upper.controls(1) = alphamax;
     // The following bounds fix the initial and final state conditions
     problem.phase[iphase].bounds.lower.events(1) = h0;
     problem.phase[iphase].bounds.upper.events(1) = h0;
problem.phase[iphase].bounds.lower.events(2) = v0;
     problem.phase[iphase].bounds.lower.events(2) = v0;
problem.phase[iphase].bounds.lower.events(3) = gamma0;
problem.phase[iphase].bounds.upper.events(3) = gamma0;
problem.phase[iphase].bounds.lower.events(4) = w0;
     problem.phase[iphase].bounds.upper.events(4) = w0;
problem.phase[iphase].bounds.lower.events(5) = hf;
     problem.phase[iphase].bounds.upper.events(5) = hf;
problem.phase[iphase].bounds.lower.events(6) = vf;
     problem.phase[iphase].bounds.upper.events(6) = vf;
problem.phase[iphase].bounds.lower.events(7) = gammaf;
     problem.phase[iphase].bounds.upper.events(7) = gammaf;
int nnodes = problem.phases(1).nodes(1);
     DMatrix stateGuess(4.nnodes):
     stateGuess(1, colon()) = linspace(h0,hf,nnodes);
     stateGuess(2, colon()) = linspace(v0,vf,nnodes);
stateGuess(3, colon()) = linspace(gamma0,gammaf,nnodes);
     stateGuess(4, colon()) = linspace(w0,0.8*w0,nnodes);
     problem.phases(1).guess.controls
problem.phases(1).guess.states
                                                     = zeros(1,nnodes);
                                                      = stateGuess;
     problem.phases(1).guess.time
                                                     = linspace(t0min, tfmax, nnodes);
problem.integrand_cost = &integrand_cost;
```

```
problem.endpoint_cost = &endpoint_cost;
   problem.dae = &dae;
problem.events = &events;
   problem.linkages = &linkages;
algorithm.nlp_method algorithm.scaling
                                = "TPOPT":
                                 = "automatic";
                                = "numerical";
= "trapezoidal";
   algorithm.derivatives
   algorithm.collocation_method
                                 = 1000;
   algorithm.nlp_iter_max
   algorithm.nlp_tolerance
                                 = 1.e-6;
= "automatic";
   algorithm.mesh refinement
   algorithm.mr_max_iterations
                                 = "jacobian-based";
   algorithm.defect_scaling
psopt(solution, problem, algorithm);
Extract relevant variables from solution structure
x = solution.get_states_in_phase(1);
u = solution.get_controls_in_phase(1);
   t = solution.get_time_in_phase(1);
            = solution.get_dual_hamiltonian_in_phase(1);
   DMatrix h = x(1,colon());

DMatrix v = x(2,colon());
   DMatrix gamma = x(3,colon());
             = x(4,colon());
   DMatrix w
x.Save("x.dat"):
   u.Save("u.dat");
t.Save("t.dat");
plot(t,h/1000.0,problem.name + ": altitude", "time (s)", "altitude (x1,000 ft)", "h");
plot(t,v/100.0,problem.name + ": velocity", "time (s)", "velocity (x100 ft/s)", "v");
plot(t,gamma*180/pi,problem.name + ": flight path angle", "time (s)", "gamma (deg)", "gamma");
plot(t,v/10000.0,problem.name + ": weight", "time (s)", "w (x10,000 lb)", "w");
plot(t,u*180/pi,problem.name + ": angle of attack", "time (s)", "alpha (deg)", "alpha");
   plot(t,h/1000.0,problem.name + ": altitude", "time (s)", "altitude (x1,000 ft", "h",
  }
void atmosphere(adouble* alt,adouble* sigma,adouble* delta,adouble* theta, Constants_& CONSTANTS)
// US Standard Atmosphere Model 1976
// Adopted from original Fortran 90 code by Ralph Carmichael
```

```
// Fortran code located at: http://www.pdas.com/programs/atmos.f90
! PURPOSE - Compute the properties of the 1976 standard atmosphere to 86 km.
 AUTHOR - Ralph Carmichael, Public Domain Aeronautical Software
 NOTE - If alt > 86, the values returned will not be correct, but they will
   not be too far removed from the correct values for density.

The reference document does not use the terms pressure and temperature
                   _____
    ARGUMENTS
              ! geometric altitude, km.
! density/sea-level standard density
! pressure/sea-level standard pressure
  alt
  sigma
  delta
 theta
             ! temperature/sea-level standard temperature
     LOCAL CONSTANTS
                                            // radius of the Earth (km)
// hydrostatic constant
  double REARTH = 6369.0;
 double GMR = 34.163195;
int NTAB=8; // num
                     // number of entries in the defining tables
    LOCAL VARIABLES
 int i.i.k:
                                                                       // counters
  adouble h;
                                                         // geopotential altitude (km)
 adouble h; // geoputential and asset temp of this layer adouble tlocal; // temperature gradient and base temp of this layer adouble tlocal; // local temperature adouble deltah; // height above base of this layer
     LOCAL ARRAYS (1976 STD. ATMOSPHERE) |
 DMatrix& htab = *CONSTANTS.htab;

DMatrix& ttab = *CONSTANTS.ttab;

DMatrix& ptab = *CONSTANTS.ptab;
  DMatrix& gtab = *CONSTANTS.gtab;
 h=(*alt)*REARTH/((*alt)+REARTH);
                                         //convert geometric to geopotential altitude
  j=NTAB;
                                                      // setting up for binary search
  while (j<=i+1) {
 k=(i+j)/2;
                                                                    // integer division
    if (h < htab(k)) {
   j=k;
} else {
    }
  tgrad=gtab(i);
                                                          // i will be in 1...NTAB-1
  tbase=ttab(i);
  deltah=h-htab(i);
  tlocal=tbase+tgrad*deltah:
                                                                    // temperature ratio
 if (tgrad == 0.0) {
  *delta=ptab(i)*exp(-GMR*deltah/tbase);
                                                              // pressure ratio
    *delta=ptab(i)*pow(tbase/tlocal, GMR/tgrad);
  *sigma=(*delta)/(*theta);
                                                                                // density ratio
 return;
\verb|void atmosphere_model(adouble* rho, adouble* M, adouble v, adouble h, Constants\_\& CONSTANTS)| \\
   double feet2meter = 0.3048:
   double kgperm3_to_slug_per_feet3 = 0.062427960841/32.174049;
   adouble alt, sigma, delta, theta;
```

Iter	Method	Nodes	NV	NC	OE	$^{\mathrm{CE}}$	$_{ m JE}$	$_{ m HE}$	RHS	$\epsilon_{ ext{max}}$	CPU(sec)
1	LGL-ST	80	322	247	747	746	89	0	59680	1.752e-03	8.020e+00
2	LGL-ST	90	362	277	70	71	55	0	6390	1.706e-03	6.890e + 00
3	LGL-ST	100	402	307	28	29	28	0	2900	7.940e-04	4.810e + 00
					945	946	179	Ω	69070		1.0720 ± 01

Key: Iter=iteration number, NV=number of variables, NC=number of constraints, OE=objective evaluations, CE = constraint evaluations, JE = Jacobian evaluations, HE = Hessian evaluations, RHS = ODE right hand side evaluations, ϵ_{max} = maximum relative ODE error, CPU(sec) = CPU time in seconds spent by nonlinear programming algorithm

Table 3.4: Mesh refinement statistics: Minimum time to climb for a supersonic aircraft

```
alt = h.value()*feet2meter/1000.0;
  // Call the standard atmosphere model 1976
  atmosphere(&alt, &sigma, &delta, &theta, CONSTANTS);
  adouble rho1 = 1.22521 * sigma; // Multiply by standard density at zero altitude and 15 deg C.
  rho1 = rho1*kgperm3_to_slug_per_feet3;
  *rho = rho1;
  adouble T;
adouble mach;
  double TempStandardSeaLevel = 288.15; // in K, or 15 deg C.
  T = theta*TempStandardSeaLevel;
  adouble a = 20.0468 * sqrt(T); // Speed of sound in m/s.
  a = a/feet2meter; // Speed of sound in ft/s
  mach = v/a;
  *M = mach;
 return;
```

The output from \mathcal{PSOPT} is summarized in the box below and Figures 3.68, to 3.72. The results can be compared with those presented in [4]. Table ?? shows the mesh refinement history for this problem.




Figure 3.68: Altitude for minimum time to climb problem

```
Date and time of this run: Thu Feb 21 15:51:19 2019

Optimal (unscaled) cost function value: 3.188143e+02
Phase 1 endpoint cost function value: 3.188143e+02
Phase 1 integrated part of the cost: 0.000000e+00
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 3.188143e+02
Phase 1 maximum relative local error: 1.665362e-03
NLP solver reports: The problem has been solved!
```

3.28 Missile terminal burn maneouvre

This example illustrates the design of a missile trajectory to strike a specified target from given initial conditions in minimum time [39]. Figure 3.28 shows the variables associated with the dynamic model of the missile employed in this example, where γ is the flight path angle, α is the angle of attack, V is the missile speed, x is the longitudinal position, h is the altitude, D is the axial aerodynamic force, L is the normal aerodynamic force, and T is the thrust.

The equations of motion of the missile are given by:




Figure 3.69: Velocity for minimum time to climb problem




Figure 3.70: Flight path angle for minimum time to climb problem




Figure 3.71: Weight for minimum time to climb problem




Figure 3.72: Angle of attack (α) for minimum time to climb problem




Figure 3.73: Ilustration of the variables associated with the missile model

$$\begin{split} \dot{\gamma} &= \frac{T-D}{mg} \sin \alpha + \frac{L}{mV} \cos \alpha - \frac{g \cos \gamma}{V} \\ \dot{V} &= \frac{T-D}{m} \cos \alpha - \frac{L}{m} \sin \alpha - g \cos \gamma \\ \dot{x} &= V \cos \gamma \\ \dot{h} &= V \sin \gamma \end{split}$$

where

$$D = \frac{1}{2}C_d\rho V^2 Sref$$

$$C_d = A_1\alpha^2 + A_2\alpha + A_3$$

$$L = \frac{1}{2}C_l\rho V^2 Sref$$

$$C_l = B_1\alpha + B_2$$

$$\rho = C_1h^2 + C_2h + C_3$$

where all the model parameters are given in Table 3.5. The initial conditions for the state variables are:

$$\gamma(0) = 0$$
 $V(0) = 272 \text{m/s}$
 $x(0) = 0 \text{m}$
 $h(0) = 30 \text{m}$

The terminal conditions on the states are:

$$\gamma(t_f) = -\pi/2$$

$$V(t_f) = 310 \text{m/s}$$

$$x(t_f) = 10000 \text{m}$$

$$h(t_f) = 0 \text{m}$$

The problem constraints are given by:

$$\begin{array}{l} 200 \leq V \leq 310 \\ 1000 \leq T \leq 6000 \\ -0.3 \leq \alpha \leq 0.3 \\ -4 \leq \frac{L}{mg} \leq 4 \\ h \geq 30 \; (\text{for} \; x \leq 7500\text{m}) \\ h \geq 0 \; (\text{for} \; x > 7500\text{m}) \end{array}$$

Table 3.5: Parameters values of the missile model

Parameter	Value	Units
m	1005	kg
g	9.81	$\mathrm{m/s^2}$
$S_{ m ref}$	0.3376	m^2
A_1	-1.9431	
A_2	-0.1499	
A_3	0.2359	
B_1	21.9	
B_2	0	
C_1	3.312×10^{-9}	${ m kg/m^5}$
C_2	-1.142×10^{-4}	kg/m^4
C_3	1.224	kg/m^3

Note that the path constraints on the altitude are non-smooth. Given that non-smoothness causes problems with nonlinear programming, the constraints on the altitude were approximated by a single smooth constraint:

$$\mathcal{H}_{\epsilon}(x-7500)h(t) + [1-\mathcal{H}_{\epsilon}(x-7500)][h(t)-30] \ge 0$$

where $\mathcal{H}_{\epsilon}(z)$ is a smooth version of the Heaviside function, which is computed as follows:

$$\mathcal{H}_{\epsilon}(z) = 0.5(1 + \tanh(z/\epsilon))$$

where $\epsilon > 0$ is a small number.

The problem is solved by using automatic mesh refinement starting with 50 nodes. The final solution, which is found after six mesh refinement iterations, has 85 nodes. Figure 3.74 shows the missile altitude as a function of the longitudinal position. Figures 3.75 and 3.76 show, respectively, the missile speed and angle of attack as functions of time. The output from \mathcal{PSOPT} is summarised in the box below.

PSOPT results summary

Problem: Missile problem

CPU time (seconds): 4.394547e+00

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 17:16:57 2019

Optimal (unscaled) cost function value: 4.091759e+01 Phase 1 endpoint cost function value: 4.091759e+01 Phase 1 integrated part of the cost: 0.000000e+00

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 4.091759e+01

Phase 1 maximum relative local error: 4.925376e-04 NLP solver reports: The problem has been solved!




Figure 3.74: Missile altitude and a function of the longitudinal position

3.29 Moon lander problem

Consider the following optimal control problem, which is known in the literature as the moon lander problem [36]. Find t_f and $T(t) \in [0, t_f]$ to minimize the cost functional

$$J = \int_0^{t_f} T(t)dt \tag{3.120}$$

subject to the dynamic constraints

$$\dot{h} = v
\dot{v} = -g + T/m
\dot{m} = -T/E$$
(3.121)




Figure 3.75: Missile speed as a function of time




Figure 3.76: Missile angle of attack as a function of time

the boundary conditions:

$$h(0) = 1$$

$$v(0) = -0.783$$

$$m(0) = 1$$

$$h(t_f) = 0.0$$

$$v(t_f) = 0.0$$
(3.122)

and the bounds

$$0 \le T(t) \le 1.227$$

$$-20 \le h(t) \le 20$$

$$-20 \le v(t) \le 20$$

$$0.01 \le m(t) \le 1$$

$$0 \le t_f \le 1000$$
(3.123)

where g = 1.0, and E = 2.349. The \mathcal{PSOPT} code that solves this problem is shown below.

```
#include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
          adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
 return 0.0;
/////////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble thrust = controls[0];
  return thrust;
void dae(adouble* derivatives, adouble* path, adouble* states,
    adouble* controls, adouble* parameters, adouble& time,
```

```
adouble* xad, int iphase, Workspace* workspace)
  adouble altitude_dot, speed_dot, mass_dot;
  adouble altitude = states[0];
  adouble speed = states[1];
adouble mass = states[2];
  adouble thrust = controls[0];
 double exhaust_velocity = 2.349;
double gravity = 1.0;
 altitude_dot = speed;
speed_dot = -gravity + thrust/mass;
mass_dot = -thrust/exhaust_velocity;
  derivatives[0] = altitude_dot;
  derivatives[1] = speed_dot;
derivatives[2] = mass_dot;
void events(adouble* e. adouble* initial states, adouble* final states.
        adouble* parameters,adouble& t0, adouble& tf, adouble* xad,
        int iphase, Workspace* workspace)
 adouble altitude i = initial states[0]:
 adouble altitude_1 = initial_states[0];
adouble speed_i = initial_states[1];
adouble mass_i = initial_states[2];
adouble altitude_f = final_states[0];
adouble speed_f = final_states[1];
  e[0] = altitude_i;
 e[1] = speed_i;
e[2] = mass_i;
  e[3] = altitude_f;
e[4] = speed_f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
 // No linkages as this is a single phase problem
}
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
problem.name
                = "Moon Lander Problem";
  problem.outfilename
                           = "moon.txt";
problem.nphases
  problem.nlinkages
                           = 0:
  psopt_level1_setup(problem);
```

```
problem.phases(1).nstates
                               = 3:
    problem.phases(1).ncontrols = 1;
    problem.phases(1).nevents = 5;
   problem.phases(1).npath
                               = 0;
    problem.phases(1).nodes
                                             = 70:
   psopt_level2_setup(problem, algorithm);
   int nodes = 70;
DMatrix x, u, t;
DMatrix lambda, H;
= -20.0;
    double altitudeL
   double speedL = -20.0;
double massL = 0.01;
   double massL = 0.01;
double altitudeU = 20.0;
double speedU = 20.0;
double massU = 1.0;
    double thrustL
                      = 0.0;
                      = 1.227;
    double thrustU
   double altitude_i = 1.0;
double speed_i = -0.783;
   double speed_i
double mass_i
                      = 1.0;
   double altitude_f = 0.0;
double speed_f = 0.0;
    double speed_f
   problem.phases(1).bounds.lower.states(1) = altitudeL;
   problem.phases(1).bounds.lower.states(2) = speedL;
problem.phases(1).bounds.lower.states(3) = massL;
    problem.phases(1).bounds.upper.states(1) = altitudeU;
   problem.phases(1).bounds.upper.states(2) = speedU;
problem.phases(1).bounds.upper.states(3) = massU;
    problem.phases(1).bounds.lower.controls(1) = thrustL;
    problem.phases(1).bounds.upper.controls(1) = thrustU;
    problem.phases(1).bounds.lower.events(1) = altitude_i;
   problem.phases(1).bounds.lower.events(1) = altitude_i;
problem.phases(1).bounds.lower.events(2) = speed_i;
problem.phases(1).bounds.lower.events(3) = mass_i;
problem.phases(1).bounds.lower.events(4) = altitude_f;
problem.phases(1).bounds.lower.events(5) = speed_f;
   problem.phases(1).bounds.upper.events = problem.phases(1).bounds.lower.events;
    problem.phases(1).bounds.lower.StartTime
                                            = 0.0:
    problem.phases(1).bounds.upper.StartTime
    problem.phases(1).bounds.lower.EndTime
                                          = 0.0;
= 1000.0;
    problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
    problem.dae = &dae;
   problem.events = &events;
problem.linkages = &linkages;
```

```
DMatrix states_guess(3,nodes+1);
  states_guess(1,colon()) = linspace(altitude_i, altitude_f, nodes+1);
states_guess(2,colon()) = linspace(speed_i, speed_f, nodes+1);
states_guess(3,colon()) = linspace(mass_i, massL, nodes+1);
  algorithm.nlp_iter_max = 1000;
algorithm.nlp_tolerance = 1.e-6;
algorithm.nlp_method = "IPOPT";
algorithm.scaling = "automatic";
algorithm.derivatives = "automatic";
psopt(solution, problem, algorithm);
x = solution.get_states_in_phase(1)
  u = solution.get_controls_in_phase(1);
t = solution.get_time_in_phase(1);
lambda = solution.get_dual_costates_in_phase(1);
H = solution.get_dual_hamiltonian_in_phase(1);
u.Save("u.dat");
t.Save("t.dat");
  lambda.Save("lambda.dat"):
  H.Save("H.dat");
plot(t,x,problem.name, "time (s)", "states", "altitude speed mass");
  plot(t,u,problem.name, "time (s)", "control", "thrust");
  plot(t,x,problem.name, "time (s)", "states", "altitude speed mass",
                "pdf", "moon_states.pdf");
  plot(t,u,problem.name, "time (s)", "control", "thrust",
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.77 and 3.78, which contain the elements of the state and the control, respectively.




Figure 3.77: States for moon lander problem

3.30 Multi-segment problem

Consider the following optimal control problem, where the optimal control has a characteristic stepped shape [22]. Find $u(t) \in [0,3]$ to minimize the




Figure 3.78: Control for moon lander problem

cost functional

$$J = \int_0^3 x(t)dt \tag{3.124}$$

subject to the dynamic constraints

$$\dot{x} = u \tag{3.125}$$

the boundary conditions:

$$\begin{array}{rcl}
x(0) & = & 1 \\
x(3) & = & 1
\end{array} \tag{3.126}$$

and the bounds

$$-1 \le u(t) \le 1$$

$$x(t) \ge 0$$

$$(3.127)$$

The analytical optimal control is given by:

$$u(t) = \begin{cases} -1, & t \in [0, 1) \\ 0, & t \in [1, 2] \\ 1, & t \in (2, 3] \end{cases}$$
 (3.128)

The problem has been solved using the multi-segment paradigm. Three segments are defined in the code, such that the initial time is fixed at $t_0^{(1)} = 0$, the final time is fixed at $t_f^{(3)} = 3$, and the intermediate junction times are $t_f^{(1)}=1,$ and $t_f^{(2)}=2.$ The \mathcal{PSOPT} code that solves this problem is shown below.

```
////// Title: Steps problem
////// Last modified: 12 July 2009
////// Reference: Gong, Farhoo
                       Gong, Farhoo, and Ross (2008)
                          #include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
          adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
 return 0.0;
}
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
 adouble x = states[ CINDEX(1) ];
 return (x);
void dae(adouble* derivatives, adouble* path, adouble* states,
    adouble* controls, adouble* parameters, adouble& time,
    adouble* xad, int iphase, Workspace* workspace)
  adouble u = controls[CINDEX(1)];
  derivatives[ CINDEX(1) ] = u;
int iphase, Workspace* workspace)
{
  adouble x1_i = initial_states[ CINDEX(1) ];
 adouble x1_f = final_states[ CINDEX(1) ];
 if ( iphase==1 ) {
 e[ CINDEX(1) ] = x1_i;
 else if ( iphase==3 ) {
```

```
e[ CINDEX(1) ] = x1_f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
}
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
  MSdata msdata;
msdata.nsegments
                = 3;
  msdata.nstates
  msdata.ncontrols
                = 1:
  msdata.nparameters
  msdata.npath
                = 0:
  msdata.ninitial_events = 1;
  msdata.ninitlar_events = 1;
msdata.nfinal_events = 20; // nodes per segment
  multi_segment_setup(problem, algorithm, msdata );
problem.phases(1).bounds.lower.controls(1) = -1.0;
  problem.phases(1).bounds.upper.controls(1) = 1.0;
  problem.phases(1).bounds.lower.states(1) = 0.0;
problem.phases(1).bounds.upper.states(1) = 5.0;
problem.phases(1).bounds.lower.events(1) = 1.0;
  problem.phases(3).bounds.lower.events(1) = 1.0;
  problem.phases(1).bounds.upper.events=problem.phases(1).bounds.lower.events:
  problem.phases(3).bounds.upper.events=problem.phases(3).bounds.lower.events;
  {\tt problem.phases(1).bounds.lower.StartTime}
  problem.phases(1).bounds.upper.StartTime
  problem.phases(3).bounds.lower.EndTime
  problem.phases(3).bounds.upper.EndTime
                             = 3.0;
   problem.bounds.lower.times = "[0.0, 1.0, 2.0, 3.0]";
problem.bounds.upper.times = "[0.0, 1.0, 2.0, 3.0]";
```

```
problem.bounds.lower.times = "[0.0, 1.0, 2.0, 3.0]";
problem.bounds.upper.times = "[0.0, 1.0, 2.0, 3.0]";
   auto_phase_bounds(problem);
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
   problem.dae
                     = &dae:
   problem.events = &events;
   problem.linkages = &linkages;
= problem.phases(1).ncontrols;
= problem.phases(1).nstates;
   int nstates
  DMatrix state_guess = zeros(nstates,nnodes);
DMatrix time_guess
DMatrix param_guess;

= zeros(ncontrols,nnodes);
= linspace(0.0,3.0,nnodes);
   state_guess(1,colon()) = linspace(1.0, 1.0, nnodes);
   control_guess(1,colon()) = zeros(1,nnodes);
   auto_phase_guess(problem, control_guess, state_guess, param_guess, time_guess);
algorithm.nlp_iter_max algorithm.nlp_tolerance
                              = 1000;
                              = 1.e-6;
= "IPOPT";
   algorithm.nlp_method
                               = "automatic"
   algorithm.scaling
   algorithm.derivatives
                               = "automatic":
   algorithm.hessian
                               = "exact";
                               = "automatic";
   algorithm.mesh_refinement
algorithm.ode_tolerance
psopt(solution, problem, algorithm);
DMatrix x, u, t, xi, ui, ti;
        = solution.get_states_in_phase(1);
        = solution.get controls in phase(1):
        = solution.get_time_in_phase(1);
  for(int i=2;i<=problem.nphases;i++) {
    xi = solution.get_states_in_phase(i);
    ui = solution.get_controls_in_phase(i);
    ti = solution.get_time_in_phase(i);</pre>
x = x \mid \mid xi;
     u = u || ui;
      t = t || ti;
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.79 and 3.80, which contain the elements of the state and the control, respectively.

```
PSOPT results summary
================
Problem: Steps problem
CPU time (seconds): 8.536780e-01
NLP solver used: IPOPT
PSOPT release number: 4.0
Date and time of this run: Thu Feb 21 17:24:35 2019
Optimal (unscaled) cost function value: 1.000010e+00
Phase 1 endpoint cost function value: 0.000000e+00
Phase 1 integrated part of the cost: 5.000034e-01
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 1.000000e+00
Phase 1 maximum relative local error: 6.960834e-07
Phase 2 endpoint cost function value: 0.000000e+00
Phase 2 integrated part of the cost: 3.401579e-06
Phase 2 initial time: 1.000000e+00
Phase 2 final time: 2.000000e+00
```




Figure 3.79: State trajectory for the multi-segment problem

```
Phase 2 maximum relative local error: 4.856300e-06
Phase 3 endpoint cost function value: 0.000000e+00
Phase 3 integrated part of the cost: 5.000034e-01
Phase 3 initial time: 2.000000e+00
Phase 3 final time: 3.000000e+00
Phase 3 maximum relative local error: 6.961454e-07
NLP solver reports: The problem has been solved!
```

3.31 Notorious parameter estimation problem

Consider the following parameter estimation problem, which is known to be challenging to single-shooting methods because of internal instability of the differential equations [37]. Find $p \in \Re$ to minimize

$$J = \sum_{i=1}^{200} (y_1(t_i) - \tilde{y}_1(i))^2 + (y_2(t_i) - \tilde{y}_2(i))^2$$
 (3.129)

subject to the dynamic constraints




Figure 3.80: Control trajectory for the multi-segment problem

where $\mu = 60.0$, $y_1(0) = 0$, $y_2(0) = \pi$. The parameter estimation facilities of \mathcal{PSOPT} are used in this example. In this case, the observations function is:

$$g(x(\theta_k), u(\theta_k), p, \theta_k) = [y_1(\theta_k) \ y_2(\theta_k)]^T$$

The \mathcal{PSOPT} code that solves this problem is shown below. The code includes the generation of the measurement vectors \tilde{y}_1 , and \tilde{y}_2 by adding Gaussian noise with standard deviation 0.05 to the exact solution of the problem with $p = \pi$, which is given by:

$$y_1(t) = \sin(\pi t)$$
$$y_2(t) = \pi \cos(\pi t)$$

The code also defines the vector of sampling instants θ_i , i = 1, ..., 200 as a uniform random samples in the interval [0, 1].

```
#include "psopt.h"
void observation_function( adouble* observations,
                   adouble* states, adouble* controls,
                   adouble* parameters, adouble& time, int k, adouble* xad, int iphase, Workspace* workspace)
{
    observations[ CINDEX(1) ] = states[ CINDEX(1) ];
observations[ CINDEX(2) ] = states[ CINDEX(2) ];
void dae(adouble* derivatives, adouble* path, adouble* states,
      adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble x1 = states[ CINDEX(1) ];
adouble x2 = states[ CINDEX(2) ];
 adouble p = parameters[ CINDEX(1) ];
adouble t = time;
 double mu = 60.0;
 derivatives[CINDEX(1)] = x2;
derivatives[CINDEX(2)] = mu*mu*x1 - (mu*mu + p*p)*sin(p*t);
void events(adouble* e, adouble* initial_states, adouble* final_states,
        adouble* parameters,adouble& t0, adouble& tf, adouble* xad,
        int iphase, Workspace* workspace)
ł
 e[ 0 ] = initial_states[0];
e[ 1 ] = initial_states[1];
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
 \ensuremath{//} No linkages as this is a single phase problem
int main(void)
 int nobs =200:
  // Generate true solution at sampling points and add noise
```

```
double sigma = 0.05;
  DMatrix theta, y1m, y2m, ym;
  theta = randu(1,nobs);
  sort(theta);
 y1m = sin( pi* theta ) + sigma*randn(1,nobs);
  y2m = pi*cos(pi*theta) + sigma*randn(1,nobs);
Alg algorithm;
Sol solution;
  Prob problem;
= "Bocks notorious parameter estimation problem";
  problem.outfilename
                          = "notorious.txt";
problem.nphases
              = 1;
  problem.nlinkages
                          = 0;
  psopt_level1_setup(problem);
problem.phases(1).nstates = 2,
problem.phases(1).ncontrols = 0;
problem.phases(1).nevents = 2;
...hjom.phases(1).npath = 0;
  problem.phases(1).nevenus
problem.phases(1).npath = 0;
problem.phases(1).nparameters = 1;
problem.phases(1).nodes = "[80]";
= 2;
  problem.phases(1).nsamples
                               = nobs;
  psopt_level2_setup(problem, algorithm);
problem.phases(1).observation_nodes
                             = (theta);
  problem.phases(1).observations
                            = (y1m && y2m);
problem.phases(1).bounds.lower.states(1) = -10.0;
problem.phases(1).bounds.lower.states(2) = -100.0;
  problem.phases(1).bounds.upper.states(1) = 10.0;
problem.phases(1).bounds.upper.states(2) = 100.0;
  problem.phases(1).bounds.lower.parameters(1) = -10.0;
problem.phases(1).bounds.upper.parameters(1) = 10.0;
  problem.phases(1).bounds.lower.events(1) = 0.0;
```

```
problem.phases(1).bounds.upper.events(1) = 0.0;
  problem.phases(1).bounds.lower.events(2) = pi;
problem.phases(1).bounds.upper.events(2) = pi;
  problem.phases(1).bounds.lower.StartTime
  problem.phases(1).bounds.upper.StartTime
                           = 0.0;
  problem.phases(1).bounds.lower.EndTime
problem.phases(1).bounds.upper.EndTime
                           = 1.0:
                           = 1.0;
problem.events = &events;
problem.linkages = &linkages;
  problem.observation_function = & observation_function;
int nnodes = problem.phases(1).nodes(1);
  DMatrix state_guess;
  state_guess = zeros(2,nnodes);
  algorithm.nlp_method
                        = "IPOPT";
  algorithm.scaling algorithm.derivatives
                        = "automatic";
= "automatic";
                        = "trapezoidal";
  algorithm.collocation_method
  algorithm.nlp_tter_max
algorithm.nlp_tolerance
algorithm.mesh_refinement
algorithm.ode_tolerance
                        = 200;
                        = 1.e-4;
= "automatic";
= 1.e-6;
psopt(solution, problem, algorithm);
DMatrix states, x1, x2, p, t;
states = solution.get states in phase(1):
      = solution.get_time_in_phase(1);
      = solution.get_parameters_in_phase(1);
      = states(1,colon());
     = states(2,colon());
states.Save("states.dat"):
  t.Save("t.dat");
  p.Print("Estimated parameter");
```

The output from \mathcal{PSOPT} is summarized in the box below. The optimal parameter found was p = 3.141180, which is an approximation of π with an error of the order of 10^{-4} . The 95% confidence interval of the estimated parameter is [3.132363, 3.149998].

3.32 Predator-prey parameter estimation problem

This is a well known model that describes the behaviour of predator and prey species of an ecological system. The Letka-Volterra model system consist of two differential equations [37].

The dynamic equations are given by:

$$\dot{x}_1 = -p_1 x_1 + p_2 x_1 x_2
\dot{x}_2 = p_3 x_2 - p_4 x_1 x_2$$
(3.131)

with boundary condition:

$$x_1(0) = 0.4$$

 $x_2(0) = 1$

The observation functions are:

$$g_1 = x_1 g_2 = x_2$$
 (3.132)

The measured data, with consists of $n_s = 10$ samples over the interval $t \in [0, 10]$, was constructed from simulations with parameter values $[p_1, p_2, p_3, p_4] = [1, 1, 1, 1]$ with added noise. The weights of both observations are the same and equal to one.

The solution is found using local discretisation (trapezoidal, Hermite-Simpson) and automatic mesh refinement, starting with 20 grid points with ODE tolerance 10^{-4} . The code that solves the problem is shown below. The estimated parameter values and their 95% confidence limits are shown in Table 3.32. Figure 3.81 shows the observations as well as the estimated values of variables x_1 and x_2 . The mesh statistics can be seen in Table 3.7

```
#include "psopt.h"
void observation_function( adouble* observations,
        adouble* states, adouble* controls,
        adouble* parameters, adouble& time, int k, adouble* xad, int iphase, Workspace* workspace)
for (i=0; i<2; i++) {
   observations[ i ] = states[ i ];
adouble* xad, int iphase, Workspace* workspace)
```

```
{
  // Variables
    adouble x1, x2, p1, p2, p3, p4;
  // Differential states
    x1 = states[CINDEX(1)];
x2 = states[CINDEX(2)];
  // Parameters
 p1 = parameters[CINDEX(1)];
p2 = parameters[CINDEX(2)];
p3 = parameters[CINDEX(3)];
    p4 = parameters[CINDEX(4)];
    \label{eq:cindex} \texttt{derivatives} \texttt{[CINDEX(1)]} \ = \ -p1*x1 \ + \ p2*x1*x2;
    derivatives[CINDEX(2)] = p3*x2 - p4*x1*x2;
}
void events(adouble* e, adouble* initial_states, adouble* final_states,
       adouble* parameters,adouble& t0, adouble& tf, adouble* xad,
       int iphase, Workspace* workspace)
{
 int i:
 for (i=0; i<2; i++) {
   e[i] = initial_states[i];
 }
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
 \ensuremath{//} No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
Register problem name
problem.name
               = "Predator-prey example";
= "predator.txt";
  problem.outfilename
                        "predator.txt";
problem.nphases
                        = 0;
  problem.nlinkages
  psopt_level1_setup(problem);
```

```
problem.phases(1).nstates
   problem.phases(1).ncontrols = 0;
   problem.phases(1).nevents = 2;
problem.phases(1).npath = 0;
   problem.phases(1).nparameters = problem.phases(1).nodes = 20;
                              = 4;
   problem.phases(1).nobserved
                              = 2.
   problem.phases(1).nsamples
   psopt_level2_setup(problem, algorithm);
load_parameter_estimation_data(problem, iphase, "predator.dat");
  problem.phases(1).observation_nodes.Print("observation nodes"):
  problem.phases(1).observations.Print("observations");
  problem.phases(1).residual_weights.Print("weights");
problem.phases(1).bounds.lower.states(1) = 0.0;
   problem.phases(1).bounds.lower.states(2) = 0.0;
   problem.phases(1).bounds.upper.states(1) = 3.0;
   problem.phases(1).bounds.upper.states(2) = 3.0;
   problem.phases(1).bounds.lower.events(1) = 0.4;
   problem.phases(1).bounds.lower.events(2) = 1.0;
   problem.phases(1).bounds.upper.events(1) = 0.4;
   problem.phases(1).bounds.upper.events(2) = 1.0;
problem.phases(1).bounds.lower.parameters(1) = -1.0;
problem.phases(1).bounds.lower.parameters(2) = -1.0;
problem.phases(1).bounds.lower.parameters(3) = -1.0;
problem.phases(1).bounds.lower.parameters(4) = -1.0;
problem.phases(1).bounds.upper.parameters(1) = 5.0;
problem.phases(1).bounds.upper.parameters(2) = 5.0;
problem.phases(1).bounds.upper.parameters(3) = 5.0;
problem.phases(1).bounds.upper.parameters(4) = 5.0;
                                  = 0.0;
= 0.0;
   problem.phases(1).bounds.lower.StartTime
   problem.phases(1).bounds.upper.StartTime
   problem.phases(1).bounds.lower.EndTime
                                    = 10.0:
                                   = 10.0;
   problem.phases(1).bounds.upper.EndTime
problem.dae = &dae;
   problem.events = &events;
problem.linkages = &linkages;
   problem.observation_function = & observation_function;
```

```
int nnodes =
               (int) problem.phases(1).nsamples;
   DMatrix state_guess(3, nnodes);
   DMatrix param_guess(2,1);
   state_guess(1,colon()) = linspace(0.4, 0.4, nnodes );
state_guess(2,colon()) = linspace(1.0, 1.0, nnodes );
param_guess(1) = 0.8;
param_guess(2) = 0.8;
param_guess(3) = 1.5;
param_guess(4) = 1.5;
   problem.phases(1).guess.states = state_guess;
   problem.phases(1).guess.time = linspace(0.0 problem.phases(1).guess.parameters = param_guess;
                                = linspace(0.0, 10.0, nnodes);
algorithm.nlp method
                               = "IPOPT":
                                = "automatic";
= "automatic";
   algorithm.scaling
   algorithm.derivatives
   algorithm.derivatives = "automatic";
algorithm.collocation_method = "trapezoidal";
algorithm.mesh_refinement = "automatic";
algorithm.ode_tolerance = 1.e-4;
    algorithm.ode_tolerance
                                = 1.e-4;
psopt(solution, problem, algorithm);
Extract relevant variables from solution structure
x = solution.get_states_in_phase(1);
t = solution.get_time_in_phase(1);
   p = solution.get_parameters_in_phase(1);
x.Save("x.dat");
   t.Save("t.dat"):
   p.Print("Estimated parameters");
DMatrix tm;
    DMatrix ym;
    tm = problem.phases(1).observation_nodes;
    ym = problem.phases(1).observations;
    spplot(t,x,tm,ym,problem.name, "time (s)", "state x1", "x1 x2 y1 y2");
spplot(t,x,tm,ym,problem.name, "time (s)", "state x1", "x1 x2 y1 y2", "pdf", "x1x2.pdf");
}
```

Table 3.6: Estimated parameter values and 95 percent statistical confidence limits on estimated parameters

Parameter	Low Confidence Limit	Value	High Confidence Limit
p_1	7.166429e-01	9.837490 e-01	1.250855e + 00
p_2	7.573469e-01	9.803930 e-01	1.203439e+00
p_3	7.287846e-01	1.016900e+00	1.305015e+00
p_4	6.914964 e-01	1.022702e+00	1.353909e+00




Figure 3.81: Observations y_1 , y_2 and estimated states $x_1(t)$ and $x_2(t)$

3.33 Rayleigh problem with mixed state-control path constraints

Consider the following optimal control problem, which involves a path constraint in which the control and the state appear explicitly [4]. Find $u(t) \in [0, t_f]$ to minimize the cost functional

$$J = \int_0^{t_f} \left[x_1(t)^2 + u(t)^2 \right] dt \tag{3.133}$$

Table 3.7: Mesh refinement statistics: Predator-prey example

Iter	DM	М	NV	NC	OE	$^{\mathrm{CE}}$	JE	$^{\mathrm{HE}}$	RHS	$\epsilon_{ m max}$	CPUa
1	TRP	20	46	43	20	20	20	0	780	1.615e-02	4.000e-02
2	TRP	28	62	59	14	14	14	0	770	8.919e-03	4.000e-02
3	H-S	39	84	81	9	9	9	0	1035	1.670e-03	4.000e-02
4	H-S	54	114	111	11	11	11	0	1760	1.114e-04	5.000e-02
5	H-S	62	130	127	10	10	10	0	1840	3.985e-05	5.000e-02
CPU _b	-	-	-	-	-	-	-	-	-	-	4.500e-01
-	-	-	-	-	64	64	64	0	6185	_	6.700e-01

Key: Iter=iteration number, DM= discretization method, M=number of nodes, NV=number of variables, NC=number of constraints, OE=objective evaluations, CE = constraint evaluations, JE = Jacobian evaluations, HE = Hessian evaluations, RHS = ODE right hand side evaluations, $\epsilon_{\rm max}$ = maximum relative ODE error, CPU_a = CPU time in seconds spent by NLP algorithm, CPU_b = additional CPU time in seconds spent by PSOPT

subject to the dynamic constraints

$$\dot{x}_1 = x_2
\dot{x}_2 = -x_1 + x_2(1.4 - px_2^2) + 4u\sin(\theta)$$
(3.134)

The path constraint:

$$u + \frac{x_1}{6} \le 0 \tag{3.135}$$

and the boundary conditions:

$$\begin{array}{rcl}
x_1(0) & = & -5 \\
x_2(0) & = & -5
\end{array}$$
(3.136)

where $t_f = 4.5$, and p = 0.14. The \mathcal{PSOPT} code that solves this problem is shown below.

```
///////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
          adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
 adouble x1 = states[CINDEX(1)];
adouble u = controls[CINDEX(1)];
 return (u*u + x1*x1);
adouble* xad, int iphase, Workspace* workspace)
 adouble x1 = states[CINDEX(1)];
adouble x2 = states[CINDEX(2)];
 adouble u = controls[CINDEX(1)]:
 double p = 0.14;
 derivatives[ CINDEX(1) ] = x2; derivatives[ CINDEX(2) ] = -x1 + x2*(1.4-p*x2*x2) + 4.0*u;
 path[ CINDEX(1) ] = u + x1/6.0;
adouble x10 = initial_states[ CINDEX(1) ];
adouble x20 = initial_states[ CINDEX(2) ];
 e[ CINDEX(1) ] = x10;
e[ CINDEX(2) ] = x20;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem }
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
```

```
problem.name
                = "Rayleigh problem";
  problem.outfilename
                          = "rayleigh.txt";
problem.nphases
  problem.nlinkages
                          = 0:
  psopt_level1_setup(problem);
problem.phases(1).nstates
                     = 2:
  problem.phases(1).ncontrols = 1;
  problem.phases(1).nevents = 2;
problem.phases(1).npath = 1;
  problem.phases(1).npath
                               = "[80]":
  problem.phases(1).nodes
  psopt_level2_setup(problem, algorithm);
DMatrix x. u. t:
  DMatrix lambda, H, mu;
problem.phases(1).bounds.lower.states(1) = -10.0;
  problem.phases(1).bounds.lower.states(2) = -10.0;
  problem.phases(1).bounds.upper.states(1) = 10.0;
problem.phases(1).bounds.upper.states(2) = 10.0;
  problem.phases(1).bounds.lower.controls(1) = -10.0;
  problem.phases(1).bounds.upper.controls(1) = 10.0;
  problem.phases(1).bounds.lower.events(1) = -5.0;
  problem.phases(1).bounds.lower.events(2) = -5.0;
  problem.phases(1).bounds.upper.events(1) = -5.0;
  problem.phases(1).bounds.upper.events(2) = -5.0;
  problem.phases(1).bounds.lower.path(1) = -100.0;
  problem.phases(1).bounds.upper.path(1) = 0.0;
  problem.phases(1).bounds.lower.StartTime = 0.0;
problem.phases(1).bounds.lower.StartTime = 0.0;
problem.phases(1).bounds.lower.EndTime = 4.5;
problem.phases(1).bounds.upper.EndTime = 4.5;
problem.integrand cost = &integrand cost:
  problem.endpoint_cost = &endpoint_cost;
  problem.dae = &dae;
  problem.events = &events;
problem.linkages = &linkages;
DMatrix x0(2,30);
  x0(1,colon()) = -5.0*ones(1,30);
x0(2,colon()) = -5.0*ones(1, 30);
```

```
problem.phases(1).guess.controls
                               = zeros(1,30);
   problem.phases(1).guess.states
problem.phases(1).guess.time
                               = x0;
                               = linspace(0.0, 4.5, 30);
algorithm.nlp_method
  algorithm.sip_method = "IPOPT":
algorithm.caling = "automat
algorithm.collocation_method = "Hermite
algorithm.nlp_iter_max = 1000;
algorithm.nlp_tolerance = 1.e-10;
                             = "automatic":
                             = "Hermite-Simpson";
psopt(solution, problem, algorithm);
= solution.get_states_in_phase(1);
       = solution.get_controls_in_phase(1);
= solution.get_time_in_phase(1);
  lambda = solution.get_dual_costates_in_phase(1);
  mu = solution.get_dual_path_in_pnase(1);
H = solution.get_dual_hamiltonian_in_phase(1);
plot(t,x,problem.name, "time (s)", "states", "x1 x2" );
plot(t,u,problem.name, "time (s)", "control", "u" );
plot(t,lambda,problem.name, "time (s)", "costates", "p1 p2");
plot(t,mu, problem.name, "time (s)", "mu", "mu");
  plot(t,x,problem.name, "time (s)", "states", "x1 x2", "pdf", "rayleigh_states.pdf" );
plot(t,u,problem.name ,"time (s)", "control", "u", "pdf", "rayleigh_control.pdf" );
plot(t,lambda,problem.name ,"time (s)", "costates", "l1 l2", "pdf", "rayleigh_costates.pdf");
plot(t,mu, problem.name,"time (s)", "mu", "mu", "pdf", "rayleigh_mu.pdf");
END OF FILE
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.82, 3.83, 3.85, 3.85, which show, respectively, the trajectories of the states, control, costates and path constraint multiplier. The results are comparable to those presented by [4].

```
PSOPT results summary
```




Figure 3.82: States for Rayleigh problem

Problem: Rayleigh problem

CPU time (seconds): 1.295778e+00

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 17:06:44 2019

Optimal (unscaled) cost function value: 4.477625e+01 Phase 1 endpoint cost function value: 0.000000e+00 Phase 1 integrated part of the cost: 4.477625e+01

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 4.500000e+00

Phase 1 maximum relative local error: 2.329140e-03 NLP solver reports: The problem has been solved!

3.34 Obstacle avoidance problem

Consider the following optimal control problem, which involves finding an optimal trajectory for a particle to travel from A to B while avoiding two




Figure 3.83: Optimal control for Rayleigh problem




Figure 3.84: Costates for Rayleigh problem




Figure 3.85: Path constraint multiplier for Rayleigh problem

forbidden regions [36]. Find $\theta(t) \in [0, t_f]$ to minimize the cost functional

$$J = \int_0^{t_f} \left[\dot{x}(t)^2 + \dot{y}(t)^2 \right] dt \tag{3.137}$$

subject to the dynamic constraints

$$\dot{x} = V \cos(\theta)
\dot{y} = V \sin(\theta)$$
(3.138)

The path constraints:

$$(x(t) - 0.4)^{2} + (y(t) - 0.5)^{2} \ge 0.1$$

$$(x(t) - 0.8)^{2} + (y(t) - 1.5)^{2} \ge 0.1,$$
(3.139)

and the boundary conditions:

$$x(0) = 0$$

 $y(0) = 0$
 $x(t_f) = 1.2$
 $y(t_f) = 1.6$ (3.140)

where $t_f = 1.0$, and V = 2.138. The \mathcal{PSOPT} code that solves this problem is shown below.

```
obstacle.cxx
////// Title: Obstacle avoidance problem /////// Last modified: 05 January 2009
                                              /////// Reference: PROPT User's Guide
/////// (See PSOPT handbook for full reference)
                                              #include "psopt.h"
adouble endpoint cost(adouble* initial states, adouble* final states,
                 adouble* parameters, adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
 return 0;
}
//////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
                  adouble* parameters, adouble& time, adouble* xad,
                  int iphase, Workspace* workspace)
   double V = 2.138;
   adouble theta = controls[ CINDEX(1) ];
   adouble dxdt = V*cos(theta);
adouble dydt = V*sin(theta);
//
     adouble dxdt, dydt;
//
     get_state_derivative( &dxdt, 1, iphase, time, xad);
     get_state_derivative( &dydt, 2, iphase, time, xad);
   adouble L = pow(dxdt, 2.0) + pow(dydt, 2.0);
   return L;
void dae(adouble* derivatives, adouble* path, adouble* states,
      adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble x = states[ CINDEX(1) ];
adouble y = states[ CINDEX(2) ];
  adouble theta = controls[ CINDEX(1) ];
  double V = 2.138;
  adouble dxdt = V*cos(theta);
adouble dydt = V*sin(theta);
  derivatives[ CINDEX(1) ] = dxdt;
derivatives[ CINDEX(2) ] = dydt;
  path[ CINDEX(1) ] = pow(x-0.4,2.0) + pow(y-0.5,2.0);
```

```
path[ CINDEX(2) ] = pow(x-0.8,2.0) + pow(y-1.5,2.0);
}
adouble x0 = initial_states[ CINDEX(1) ];
 adouble y0 = initial_states[ CINDEX(2) ];
adouble xf = final_states[ CINDEX(1) ];
adouble yf = final_states[ CINDEX(2) ];
 e[ CINDEX(1) ] = x0;
e[ CINDEX(2) ] = y0;
e[ CINDEX(3) ] = xf;
 e[ CINDEX(4) ] = yf;
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
\ensuremath{//} No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
 Prob problem;
= "Obstacle avoidance problem";
 problem.name
 problem.outfilename
problem.nphases
 problem.nlinkages
 psopt_level1_setup(problem);
problem.phases(1).nstates
 problem.phases(1).ncontrols = 1;
problem.phases(1).nevents = 4;
 problem.phases(1).npath
problem.phases(1).nodes
                     = 2;
= "[20]";
 psopt_level2_setup(problem, algorithm);
```

```
double xL = 0.0;
    double yL = 0.0;
double xU = 2.0;
    double yU = 2.0;
    double thetaL = -10.0;
double thetaU = 10.0;
    double x0 = 0.0;
double y0 = 0.0;
double xf = 1.2;
    double yf = 1.6;
    problem.phases(1).bounds.lower.states(1) = xL;
    problem.phases(1).bounds.lower.states(2) = yL;
    problem.phases(1).bounds.upper.states(1) = xU;
problem.phases(1).bounds.upper.states(2) = yU;
    problem.phases(1).bounds.lower.controls(1) = thetaL:
    problem.phases(1).bounds.upper.controls(1) = thetaU;
    problem.phases(1).bounds.lower.events(1) = x0;
    problem.phases(1).bounds.lower.events(2) = y0;
problem.phases(1).bounds.lower.events(3) = xf;
    problem.phases(1).bounds.lower.events(4) = yf;
    problem.phases(1).bounds.upper.events(1) = x0;
problem.phases(1).bounds.upper.events(2) = y0;
problem.phases(1).bounds.upper.events(3) = xf;
    problem.phases(1).bounds.upper.events(4) = yf;
    problem.phases(1).bounds.lower.path(1) = 0.1;
    problem.phases(1).bounds.upper.path(1) = 100.0;
    problem.phases(1).bounds.lower.path(2) = 0.1;
problem.phases(1).bounds.upper.path(2) = 100.0;
    problem.phases(1).bounds.lower.StartTime
                                                  = 0.0:
    problem.phases(1).bounds.upper.StartTime
    problem.phases(1).bounds.lower.EndTime
                                                  = 1.0;
= 1.0;
    problem.phases(1).bounds.upper.EndTime
problem.dae = problem.events = &events;
    problem.linkages = &linkages;
int ncontrols
                                          = problem.phases(1).ncontrols:
    int nstates
                                          = problem.phases(1).nstates;
    DMatrix u_guess = zeros(ncontrols,nnodes);
DMatrix x_guess = zeros(nstates,nnodes);
DMatrix time_guess = linspace(0.0,1.0,nnodes);
    x_guess(1,colon()) = linspace(x0,xf,nnodes);
x_guess(2,colon()) = linspace(y0,yf,nnodes);
    u guess(1,colon()) = zeros(1,nnodes);
    problem.phases(1).guess.controls
                                             = u_guess;
```

```
problem.phases(1).guess.states
                               = x_guess;
   problem.phases(1).guess.time
                               = time_guess;
algorithm.nlp_iter_max = 1000;
algorithm.nlp_tolerance = 1.e-4;
algorithm.nlp_method = "IPOPT";
                             = "automatic";
   algorithm.scaling
                             = "automatic"
   algorithm.derivatives
   algorithm.collocation_method
algorithm.mesh_refinement
algorithm.ode_tolerance
                             = "trapezoidal";
                             = "automatic";
   algorithm.ode_tolerance
                             = 1.0e-2:
psopt(solution, problem, algorithm);
DMatrix states = solution.get_states_in_phase(1);
DMatrix t theta = solution.get_controls_in_phase(1);
DMatrix t = solution.get_time_in_phase(1);
DMatrix mu = solution.get_dual_path_in_phase(1);
  DMatrix lambda = solution.get_dual_costates_in_phase(1);
  DMatrix x = states(1,colon());
DMatrix y = states(2,colon());
x.Save("obstacle_x.dat");
   y.Save("obstacle_y.dat");
theta.Save("obstacle_theta.dat");
  t.Save("obstacle_t.dat");
DMatrix alpha = colon(0.0, pi/20, 2*pi);
   DMatrix xObs1 = sqrt(0.1)*cos(alpha) + 0.4;
  DMatrix yObs1 = sqrt(0.1)*sin(alpha) + 0.5;
  DMatrix x0bs2 = sqrt(0.1)*cos(alpha) + 0.8;

DMatrix y0bs2 = sqrt(0.1)*sin(alpha) + 1.5;
  plot(t,theta, problem.name+": theta","t", "theta");
  plot(t,mu, problem.name+": path constraint multipliers","t", "mu_1 mu_2");
  plot(t,lambda, problem.name+": costates","t", "lambda_1 lambda_2");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in




Figure 3.86: Optimal (x, y) trajectory for obstacle avoidance problem

Figure 3.86, which illustrates the optimal (x, y) trajectory of the particle.

3.35 Reorientation of an asymmetric rigid body

Consider the following optimal control problem, which consists of the reorientation of an asymmetric rigid body in minimum time [4]. Find t_f , $\hat{\mathbf{u}}(t) = [u_1(t), u_2(t), u_3(t), q_4(t)]^T$ to minimize the cost functional

$$J = t_f (3.141)$$

subject to the dynamic constraints

$$\dot{q}_{1} = \frac{1}{2} \left[\omega_{1} q_{4} - \omega_{2} q_{3} + \omega_{3} q_{2} \right]
\dot{q}_{2} = \frac{1}{2} \left[\omega_{1} q_{3} + \omega_{2} q_{4} - \omega_{3} q_{1} \right]
\dot{q}_{3} = \frac{1}{2} \left[-\omega_{1} q_{2} + \omega_{2} q_{1} + \omega_{3} q_{4} \right]
\dot{\omega}_{1} = \frac{u_{1}}{I_{x}} - \left[\frac{I_{z} - I_{y}}{I_{x}} \omega_{2} \omega_{3} \right]
\dot{\omega}_{2} = \frac{u_{2}}{I_{y}} - \left[\frac{I_{x} - I_{z}}{I_{y}} \omega_{1} \omega_{3} \right]
\dot{\omega}_{3} = \frac{u_{3}}{I_{z}} - \left[\frac{I_{y} - I_{x}}{I_{z}} \omega_{1} \omega_{2} \right]$$
(3.142)

The path constraint:

$$0 = q_1^2 + q_2^2 + q_3^2 + q_4^2 - 1 (3.143)$$

the boundary conditions:

$$q_{1}(0) = 0,$$

$$q_{2}(0) = 0,$$

$$q_{3}(0) = 0,$$

$$q_{4}(0) = 1.0$$

$$q_{1}(t_{f}) = \sin \frac{\phi}{2},$$

$$q_{2}(t_{f}) = 0,$$

$$q_{3}(t_{f}) = 0,$$

$$q_{4}(t_{f}) = \cos \frac{\phi}{2}$$

$$\omega_{1}(0) = 0,$$

$$\omega_{2}(0) = 0,$$

$$\omega_{1}(t_{f}) = 0,$$

$$\omega_{1}(t_{f}) = 0,$$

$$\omega_{2}(t_{f}) = 0,$$

$$\omega_{2}(t_{f}) = 0,$$

$$\omega_{3}(t_{f}) = 0,$$

where $\phi = 150 \,\mathrm{deg}$ is the Euler axis rotation angle, $\mathbf{q} = [q_1, q_2, q_3, q_4]^T$ is the quarternion vector, $\omega = [\omega_1, \omega_2, \omega_3]^T$ is the angular velocity vector, and $\mathbf{u} = [u_1, u_2, u_3]^T$ is the control vector. Note that in the implementation, variable $q_4(t)$ is treated as an algebraic variable (i.e. as a control variable).

The variable bounds and other parameters are given in the code. The \mathcal{PSOPT} code that solves this problem is shown below.

```
/////// Reference: Fleming et al
#include "psopt.h"
adouble endpoint cost(adouble* initial states, adouble* final states,
            adouble* parameters, adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
 return tf;
///////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters,
            adouble& time, adouble* xad, int iphase, Workspace* workspace)
 return 0.0;
void dae(adouble* derivatives, adouble* path, adouble* states,
     adouble* controls, adouble* parameters, adouble& time,
     adouble* xad, int iphase, Workspace* workspace)
  adouble u1 = controls[CINDEX(1)];
adouble u2 = controls[CINDEX(2)];
adouble u3 = controls[CINDEX(3)];
  adouble q4
             = controls[ CINDEX(4) ];
  adouble q1 = states[ CINDEX(1) ];
adouble q2 = states[ CINDEX(2) ];
adouble q3 = states[ CINDEX(3) ];
adouble omega1 = states[ CINDEX(4) ];
adouble omega2 = states[ CINDEX(5) ];
adouble omega3 = states[ CINDEX(6) ];
  double Ix = 5621.0;
double Iy = 4547.0;
```

```
double Iz = 2364.0;
    derivatives[ CINDEX(1) ] =
derivatives[ CINDEX(2) ] =
derivatives[ CINDEX(3) ] =
                                        da1:
                                        dq3;
domega1;
    derivatives[CINDEX(4)] = domega1;
derivatives[CINDEX(5)] = domega2;
derivatives[CINDEX(6)] = domega3;
    path[ CINDEX(1) ] = q1*q1 + q2*q2 + q3*q3 + q4*q4 - 1.0;
}
void events(adouble* e, adouble* initial_states, adouble* final_states,
               adouble* parameters,adouble% t0, adouble% tf, adouble* xad,
              int iphase, Workspace* workspace)
    adouble q1i = initial_states[ CINDEX(1) ];
adouble q2i = initial_states[ CINDEX(2) ];
adouble q3i = initial_states[ CINDEX(3) ];
     adouble omega1i = initial_states[ CINDEX(4) ];
adouble omega2i = initial_states[ CINDEX(5) ];
adouble omega3i = initial_states[ CINDEX(6) ];
    adouble initial_controls[4], final_controls[4], q4i, q4f;
     get_initial_controls( initial_controls, xad, iphase, workspace );
     get_final_controls( final_controls , xad, iphase, workspace);
    q4i = initial_controls[ CINDEX(4) ];
    q4f = final_controls[ CINDEX(4)];
    adouble q1f = final_states[ CINDEX(1) ];
adouble q2f = final_states[ CINDEX(2) ];
adouble q3f = final_states[ CINDEX(3) ];
adouble omega1f = final_states[ CINDEX(4) ];
adouble omega2f = final_states[ CINDEX(5) ];
adouble omega3f = final_states[ CINDEX(6) ];
    e[CINDEX(1)] = q1i;
e[CINDEX(2)] = q2i;
e[CINDEX(3)] = q3i;
    e[ CINDEX(4) ] = q4i;
e[ CINDEX(5) ] = omega1i;
e[ CINDEX(6) ] = omega2i;
e[ CINDEX(7) ] = omega3i;
    e[ CINDEX(8) ] = q1f;
                         = q2f;
= q3f;
= q4f;
    e[CINDEX(9)]
e[CINDEX(10)]
     e[CINDEX(11)]
    e[CINDEX(12)] = omega1f;
e[CINDEX(13)] = omega2f;
e[CINDEX(14)] = omega3f;
}
```

```
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
 // Single phase problem
int main(void)
Alg algorithm;
Sol solution;
 Prob problem;
= "Reorientation of a rigid body";
= "reorientation.txt";
 problem.name
 problem.outfilename
problem.nlinkages
 psopt_level1_setup(problem);
problem.phases(1).nodes
                      = "[60]";
 psopt_level2_setup(problem, algorithm);
problem.phases(1).bounds.lower.controls = "[-50.0 -50.0 -50.0 -1.0]";
 problem.phases(1).bounds.upper.controls = "[ 50.0 50.0 50.0 1.0]";
 problem.phases(1).bounds.lower.path(1) = 0.000;
 problem.phases(1).bounds.upper.path(1) = 0.000;
 DMatrix q0, qf, omega0, omegaf;
 double phi = 150.0*(pi/180.0);
 q0(1) = 0.0; q0(2) = 0.0; q0(3)=0.0; q0(4)=1.0;
 qf(1) = sin(phi/2.0); qf(2) = 0.0; qf(3) = 0.0; qf(4) = cos(phi/2.0);
 omega0 = zeros(1,3); omegaf = zeros(1,3);
```

```
problem.phases(1).bounds.lower.events = q0 || omega0 || qf || omegaf;
problem.phases(1).bounds.upper.events = problem.phases(1).bounds.lower.events;
    problem.phases(1).bounds.lower.StartTime
                                                = 0.0:
                                                = 0.0;
    problem.phases(1).bounds.upper.StartTime
    problem.phases(1).bounds.lower.EndTime
    problem.phases(1).bounds.upper.EndTime
                                                = 35.0:
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
problem.dae = &dae;
    problem.events = &events;
    problem.linkages = &linkages;
int nnodes
                  = problem.phases(1).nodes(1);
                                      = problem.phases(1).ncontrols;
= problem.phases(1).nstates;
    int ncontrols
    DMatrix state_guess = zeros(nstates,nnodes);
DMatrix control_guess = 50.0*ones(ncontrols,nnodes);
DMatrix time_guess = linspace(0.0,40,nnodes);
   state_guess(1, colon() ) = linspace( q0(1), qf(1), nnodes );
state_guess(2, colon() ) = linspace( q0(2), qf(2), nnodes );
state_guess(3, colon() ) = linspace( q0(3), qf(3), nnodes );
control_guess(4, colon() ) = linspace( q0(4), qf(4), nnodes );
state_guess(4, colon() ) = linspace( omega0(1), omegaf(1), nnodes );
state_guess(5, colon() ) = linspace( omega0(2), omegaf(2), nnodes );
state_guess(6, colon() ) = linspace( omega0(3), omegaf(3), nnodes );
    problem.phases(1).guess.states
                                     = state_guess;
    problem.phases(1).guess.controls = control_guess;
problem.phases(1).guess.time = time_guess;
algorithm.nlp_iter_max
                                          = 1000:
                                          = 1.e-6;
= "IPOPT";
    algorithm.nlp_tolerance
   algorithm.nip_woll-
algorithm.nlp_method
algorithm.scaling
                                          = "automatic";
                                         = "automatic";
    algorithm.derivatives
    algorithm.collocation_method
algorithm.mesh_refinement
algorithm.ode_tolerance
                                         = "trapezoidal";
= "automatic";
                                       = 1.e-5;
    algorithm.ode_tolerance
psopt(solution, problem, algorithm);
DMatrix states, controls, t, q1, q2, q3, q4, omega, u, q;
               = solution.get_states_in_phase(1);
= solution.get_controls_in_phase(1);
    controls
               = solution.get_time_in_phase(1);
    q1 = states(1,colon());
```

```
q2 = states(2,colon());
  q3 = states(3,colon());
q4 = controls(4, colon());
  q = q1 && q2 && q3 && q4;
  omega = states(colon(4,6), colon());
  u = controls(colon(1,3), colon());
states.Save("states.dat");
  controls.Save("controls.dat");
t.Save("t.dat");
\verb| multiplot(t,q,problem.name+": quarternion","time (s)", "q1 q2 q3 q4", "q1 q2 q3 q4", 2, 2); \\
  multiplot(t,u, problem.name+": controls", "time (s)", "u1 u2 u3", "u1 u2 u3");
  \label{limit} $$ \text{multiplot(t,q,problem.name+": quarternion","time (s)", "q1 q2 q3 q4", "q1 q2 q3 q4", 2, 2, "pdf", "reorientation_q.pdf");}
  \label{eq:multiplot(t,u, problem.name+": controls", "time (s)", "u1 u2 u3", "u1 u2 u3", 3, 1, "pdf", "reorientation_u.pdf");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.87 to 3.88, which contain the elements of the quarternion vector \mathbf{q} , and the control vector $\mathbf{u} = [u_1, u_2, u_3]^T$, respectively.




Figure 3.87: Quarternion vector elements for the reorientation problem

Phase 1 final time: 2.863041e+01

Phase 1 maximum relative local error: 1.772329e-05 NLP solver reports: The problem has been solved!

3.36 Shuttle re-entry problem

Consider the following optimal control problem, which is known in the literature as the shuttle re-entry problem [3]. Find t_f , $\alpha(t)$ and $\beta(t) \in [0, t_f]$ to minimize the cost functional

$$J = -\frac{180}{\pi}\theta(t_f) \tag{3.145}$$

subject to the dynamic constraints

$$\dot{h} = v \sin(\gamma)
\dot{\phi} = \frac{v}{r} \cos(\gamma) \sin(\psi) / \cos(\theta)
\dot{m} = \frac{v}{r} \cos(\gamma) \cos(\psi)
\dot{v} = -\frac{D}{m} - g \sin(\gamma)
\dot{\gamma} = \frac{L}{mv} \cos(\beta) + \cos(\gamma) (\frac{v}{r} - \frac{g}{v})
\dot{\psi} = \frac{1}{mv \cos(\gamma)} L \sin(\beta) + \frac{v}{r \cos(\theta)} \cos(\gamma) \sin(\psi) \sin(\theta)$$
(3.146)




Figure 3.88: Control vector elements for the reorientation problem

the boundary conditions:

$$h(0) = 260000.0$$

$$\phi(0) = -0.6572$$

$$\theta(0) = 0.0$$

$$v(0) = 25600.0$$

$$\gamma(0) = -0.0175$$

$$h(t_f) = 80000.0$$

$$v(t_f) = 2500.0$$

$$\gamma(t_f) = -0.0873$$

$$(3.147)$$

The variable bounds and other parameters are given in the code. The \mathcal{PSOPT} code that solves this problem is shown below.

```
#define H_INDX
#define PHI_INDX 2
#define THETA_INDX 3
#define V_INDX 4
#define GAMMA_INDX 5
#define PSI_INDX 6
#define ALPHA_INDX
#define BETA_INDX 2
#define DEG2RAD(x) (3.141592653589793*(x)/180.0)
adouble endpoint_cost(adouble* initial_states, adouble* final_states, adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
   adouble theta = final_states[THETA_INDX-1];
   return (-theta*180/3.141592653589793);
///////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
                     adouble* parameters,
                     adouble* parameters,
adouble* time, adouble* xad,
int iphase, Workspace* workspace)
{
   return 0.0;
}
adouble alpha, beta;
adouble alt = states[H_INDX-1];
adouble lon = states[PHI_INDX-1];
adouble lat = states[THETA_INDX-1];
adouble vel = states[V_INDX-1];
adouble gamma = states[GAMMA_INDX-1];
adouble azi = states[PSI_INDX-1];
alpha = controls[ALPHA_INDX-1];
beta = controls[BETA_INDX-1];
= 3.141592653589793;
             = 32.174;
= 20902900.0;
double cm2w
double cea
double mu
double rho0
             = 0.14076539e17;
             = 0.002378;
double href
             = 23800.0:
double c10
              = -0.20704;
double cd0
             = 0.029244;
              = 0.07854;
double cd1 double cd2
             = -6.1592e-3;
= 6.21408e-4;
             = 2690.0;
double sref
```

```
double mass
                = weight/cm2w;
adouble sgamma = sin(gamma);
adouble cgamma = cos(gamma);
adouble sazi = sin(azi);
adouble cazi
                   = cos(azi);
                  = sin(beta);
adouble sbeta
adouble cbeta = cos(beta);
adouble slat = sin(lat);
adouble clat
                 = cos(lat):
adouble alphad = cr2d*alpha;
adouble radius = cea+alt;
adouble grav = mu/pow(radius,2);
adouble rhodns = rho0*exp(-alt/href);
adouble dynp = 0.5*(rhodns*pow(vel,2));
adouble subl = cl0+cl1*alphad;
adouble subd = cd0+((cd1+cd2*alphad)*alphad);
adouble drag = (dynp*subd)*sref;
adouble lift = (dynp*subd)*sref;
adouble vrelg = (vel/radius)-(grav/vel);
derivatives[V_INDX-1] = d_vel_dt ;
derivatives[GAMMA_INDX-1] = d_gamma_dt ;
derivatives[PSI_INDX-1] = d_azi_dt ;
}
void events(adouble* e, adouble* initial_states, adouble* final_states,
              adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
   adouble h0 = initial_states[H_INDX-1];
adouble phi0 = initial_states[PHI_INDX-1];
adouble theta0 = initial_states[THETA_INDX-1];
    adouble v0 = initial_states[V_INDX-1];
    adouble gamma0 = initial_states[GAMMA_INDX-1];
    adouble psi0
                           = initial_states[PSI_INDX-1];
                  = final_states[H_INDX-1];
= final_states[V_INDX-1];
af = final_states[GAMMA_INDX-1];
    adouble hf
    adouble vf
    adouble gammaf
    e[H_INDX-1] = h0;
   e[H_INDX-1] = h0;

e[PHI_INDX-1] = phi0;

e[THETA_INDX-1] = theta0;

e[V_INDX-1] = v0;

e[GAMMA_INDX-1] = gamma0;

e[PSI_INDX-1] = psi0;
   e[6] = hf;
e[7] = vf;
e[8] = gammaf;
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
```

```
// No linkages as this is a single phase problem
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
problem.nphases
  problem.nlinkages
                          = 0;
  psopt_level1_setup(problem);
//////// Define phase related information & do layed 2 cotton /////////
problem.phases(1).nstates = 6;
problem.phases(1).ncontrols = 2;
  problem.phases(1).nevents = 9;
problem.phases(1).npath
                          = 0;
  problem.phases(1).nodes
                               = "[60 80]";
                               = true;
  problem.phases(1).zero_cost_integrand
  psopt_level2_setup(problem, algorithm);
///////// Declare DMatrix objects to store results //////////
DMatrix x, u, t;
double hL
           = 0.0:
  double hU
           = 300000.0;
          = DEG2RAD(-45.0);
= DEG2RAD( 45.0);
= 1000.0 ;
  double phiL
double phiU
  double vL
double vU
           = 40000.0
  double thetaL = DEG2RAD(-89.0);
  double thetaU = DEGZRAD(-89.0);
double thetaU = DEGZRAD(-89.0);
double gammaL = DEGZRAD(-89.0);
double gammaU = DEGZRAD(-89.0);
double psiL = DEGZRAD(-180.0);
double psiU = DEGZRAD(180.0);
  double alphaL = DEG2RAD(-89.0) ;
  double alphaU = DEG2RAD( 89.0);
double betaL = DEG2RAD( 90.0);
double betaU = DEG2RAD( 1.0);
  double qU
           = -INF;
  double qL
            = 260000.0
= 25600.0
  double h0
  double v0
  double phi0 = DEG2RAD(-0.5*75.3153);
double gamma0 = DEG2RAD(-1.0);
```

```
double theta0 = 0.0 ;
double psi0 = DEG2RAD(90.0) ;
     double psi0
                        = 80000.0
     double vf
                        = 2500.0
     double gammaf = DEG2RAD(-5.0);
     double pi = 3.141592653589793;
     problem.phases(1).bounds.lower.states(H_INDX) = hL;
     problem.phases(1).bounds.lower.states(PHI_INDX) = phiL;
problem.phases(1).bounds.lower.states(THETA_INDX) = thetaL;
     problem.phases(1).bounds.lower.states(V_INDX) = vL;
     problem.phases(1).bounds.lower.states(GAMMA_INDX) = gammaL;
problem.phases(1).bounds.lower.states(PSI_INDX) = psiL;
     problem.phases(1).bounds.upper.states(H_INDX) = hU;
     problem.phases(1).bounds.upper.states(PHI_INDX) = phiU;
problem.phases(1).bounds.upper.states(THETA_INDX) = thetaU;
     problem.phases(1).bounds.upper.states(V INDX) = vU:
     problem.phases(1).bounds.upper.states(GAMMA_INDX) = gammaU;
     problem.phases(1).bounds.upper.states(PSI_INDX) = psiU;
     problem.phases(1).bounds.lower.controls(ALPHA_INDX) = alphaL;
     problem.phases(1).bounds.upper.controls(ALPHA_INDX) = alphaU;
problem.phases(1).bounds.lower.controls(BETA_INDX) = betaL;
problem.phases(1).bounds.upper.controls(BETA_INDX) = betaU;
     problem.phases(1).bounds.lower.events(H_INDX) = h0;
     problem.phases(1).bounds.lower.events(PHI_INDX) = phi0;
problem.phases(1).bounds.lower.events(THETA_INDX) = theta0;
     problem.phases(1).bounds.lower.events(V_INDX) = v0;
problem.phases(1).bounds.lower.events(GAMMA_INDX) = gamma0;
     problem.phases(1).bounds.lower.events(PSI_INDX) = psi0;
problem.phases(1).bounds.lower.events(7) = hf;
problem.phases(1).bounds.lower.events(8) = vf;
     problem.phases(1).bounds.lower.events(9) = gammaf;
     problem.phases(1).bounds.upper.events(H_INDX) = h0;
problem.phases(1).bounds.upper.events(PHI_INDX) = phi0;
problem.phases(1).bounds.upper.events(THETA_INDX) = theta0;
problem.phases(1).bounds.upper.events(V_INDX) = v0;
problem.phases(1).bounds.upper.events(GAMMA_INDX) = gamma0;
problem.phases(1).bounds.upper.events(PSI_INDX) = psi0;
problem.phases(1).bounds.upper.events(T) = hfc.
     problem.phases(1).bounds.upper.events(7) = hf;
problem.phases(1).bounds.upper.events(8) = vf;
problem.phases(1).bounds.upper.events(9) = gammaf;
     problem.phases(1).bounds.lower.path(1)
                                                                         = qL;
     problem.phases(1).bounds.upper.path(1) = qU;
     problem.phases(1).bounds.lower.StartTime
     problem.phases(1).bounds.upper.StartTime
     problem.phases(1).bounds.lower.EndTime
                                                              = 100.0;
                                                              = 4000.0;
     problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
     problem.endpoint_cost = &endpoint_cost;
     problem.dae = &dae;
     problem.events = &events;
     problem.linkages = &linkages;
int nodes = (int) problem.phases(1).nodes(1);
```

```
DMatrix x_guess = zeros(6,nodes+1);
  x_guess(H_INDX,colon()) = linspace(h0, hf, nodes+1);
x_guess(PHI_INDX,colon()) = -0.5*DEG2RAD(90.0)*ones(1,nodes+1);
x_guess(THETA_INDX,colon()) = DEG2RAD(-89.0)*ones(1,nodes+1);
x_guess(V_INDX,colon()) = linspace(v0,vf, nodes+1);
   x_guess(GAMMA_INDX,colon()) = linspace(gamma0, gammaf, nodes+1);
x_guess(PSI_INDX,colon()) = linspace(pi/2, -pi/2, nodes+1);
   time_guess = linspace(0.0, 1000.0, nodes+1);
   problem.phases(1).guess.controls = u_guess;
  problem.phases(1).guess.states = x_guess;
problem.phases(1).guess.time = time_guess;
algorithm.nlp_method
                                = "IPOPT";
  algorithm.nlp_method = "rurr |
algorithm.nlp_tolerance = 5e-6;
algorithm.scaling = "automatic";
algorithm.derivatives = "automatic";
algorithm.collocation_method = "trapezc"
                               = 5e-6;
= "automatic";
                               = "trapezoidal";
= "automatic";
   algorithm.mesh_refinement
psopt(solution, problem, algorithm);
x = solution.get_states_in_phase(1);
   u = solution.get_controls_in_phase(1);
   t = solution.get_time_in_phase(1);
Save solution data to files if desired
x.Save("x.dat"):
   u.Save("u.dat");
   t.Save("t.dat"):
DMatrix h
             = x(1,colon()):
   DMatrix phi = x(2,colon());

DMatrix theta = x(3,colon());

DMatrix v = x(4,colon());
   DMatrix gamma = x(5,colon());
   DMatrix psi = x(6,colon());

DMatrix alpha = u(1,colon());

DMatrix beta = u(2,colon());
   plot(t.x(1,colon()),problem.name, "time (s)", "x1", "altitude");
   plot(t,u(1,colon()),problem.name,"time (s)", "alpha");
   plot(t,u(2,colon()),problem.name,"time (s)", "beta");
   plot(t,h, problem.name+": altitude", "time (s)", "h (ft)",
         "altitude", "pdf", "shutt_alt.pdf");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.89 to 3.96, which contain the elements of the state and the control vectors.

3.37 Singular control problem

Consider the following optimal control problem, whose solution is known to have a singular arc [29, 36]. Find $u(t), t \in [0, 1]$ to minimize the cost




Figure 3.89: Altitude h(t) for the shuttle re-entry problem




Figure 3.90: Longitude $\phi(t)$ for the shuttle re-entry problem




Figure 3.91: Latitude $\theta(t)$ for the shuttle re-entry problem




Figure 3.92: Velocity v(t) for the shuttle re-entry problem




Figure 3.93: Flight path angle $\gamma(t)$ for the shuttle re-entry problem




Figure 3.94: Azimuth $\psi(t)$ for the shuttle re-entry problem




Figure 3.95: Angle of attack $\alpha(t)$ for the shuttle re-entry problem




Figure 3.96: Bank angle $\beta(t)$ for the shuttle re-entry problem

functional

$$J = \int_0^1 \left[x_1^2 + x_2^2 + 0.0005(x_2 + 16x_5 - 8 - 0.1x_3u^2)^2 \right] dt$$
 (3.148)

subject to the dynamic constraints

$$\begin{aligned}
 \dot{x}_1 &= x_2 \\
 \dot{x}_2 &= -x_3 u + 16t - 8 \\
 \dot{x}_3 &= u
 \end{aligned}
 \tag{3.149}$$

the boundary conditions:

$$x_1(0) = 0$$

 $x_2(0) = -1$
 $x_3(0) = \sqrt{5}$ (3.150)

and the control bounds

$$-4 \le u(t) \le 10$$
 (3.151)

The \mathcal{PSOPT} code that solves this problem is shown below.

```
adouble u = controls[ CINDEX(1) ];
 adouble t = time;
 adouble L;
 L = x1*x1 + x2*x2 + 0.0005*pow(x2+16*t-8.0-0.1*x3*u*u,2.0);
void dae(adouble* derivatives, adouble* path, adouble* states,
     adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
 adouble x1 = states[ CINDEX(1) ];
adouble x2 = states[ CINDEX(2) ];
adouble x3 = states[ CINDEX(3) ];
 adouble u = controls[ CINDEX(1) ];
adouble t = time;
 derivatives[ CINDEX(1) ] = x2;
derivatives[ CINDEX(2) ] = -x3*u + 16*t - 8.0;
derivatives[ CINDEX(3) ] = u;
}
int iphase, Workspace* workspace)
 adouble x10 = initial_states[ CINDEX(1) ];
adouble x20 = initial_states[ CINDEX(2) ];
adouble x30 = initial_states[ CINDEX(3) ];
 e[ CINDEX(1) ] = x10;
e[ CINDEX(2) ] = x20;
e[ CINDEX(3) ] = x30;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace) {
}
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
  MSdata msdata;
= "Singular control 5";
  problem.name
  problem.outfilename
                      = "sing5.txt";
```

```
//////// Define problem level constants & do level 1 setup /////////
problem.nphases
problem.nlinkages
   psopt_level1_setup(problem);
problem.phases(1).nstates
   problem.phases(1).ncontrols = 1;
   problem.phases(1).nevents = 3;
   problem.phases(1).npath
problem.phases(1).nodes
                                         = 0;
= "[80]";
   psopt_level2_setup(problem, algorithm);
problem.phases(1).bounds.lower.states(1) = -inf;
problem.phases(1).bounds.lower.states(2) = -inf;
   problem.phases(1).bounds.lower.states(3) = -inf;
   problem.phases(1).bounds.upper.states(1) = inf;
problem.phases(1).bounds.upper.states(2) = inf;
   problem.phases(1).bounds.upper.states(3) = inf;
   problem.phases(1).bounds.lower.controls(1) = 0.0;
problem.phases(1).bounds.upper.controls(1) = 10.0;
   problem.phases(1).bounds.lower.events(1) = 0.0;
problem.phases(1).bounds.lower.events(2) = -1.0;
problem.phases(1).bounds.lower.events(3) = -sqrt(5.0);
   problem.phases(1).bounds.upper.events(1) = 0.0;
problem.phases(1).bounds.upper.events(2) = -1.0;
   problem.phases(1).bounds.upper.events(3) = -sqrt(5.0);
   problem.bounds.lower.times = "[0.0, 1.0]";
problem.bounds.upper.times = "[0.0, 1.0]";
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
   problem.endpoint_cost = &
problem.dae = &dae;
problem.events = &events;
   problem.linkages = &linkages;
DMatrix state_guess(3,20), control_guess(1,20), param_guess, time_guess;
   state_guess(1,colon())= linspace(0.0, 0.0, 20);
state_guess(2,colon())= linspace(-1.0, -1.0, 20);
state_guess(3,colon())= linspace(-sqrt(5.0),-sqrt(5.0), 20);
   control_guess = zeros(1,20);
   time_guess = linspace(0.0, 1.0, 20);
   auto_phase_guess(problem, control_guess, state_guess, param_guess, time_guess);
```

```
= 1000;
= 1.e-7;
  algorithm.nlp_iter_max
 algorithm.nlp_tolerance
                 = "IPOPT":
 algorithm.nlp_method
algorithm.scaling
                  = "automatic";
 algorithm.derivatives algorithm.defect_scaling
                  = "jacobian-based";
  algorithm.collocation_method
                  = "trapezoidal";
= "automatic";
  algorithm.mesh_refinement
                  = 5.e-3 ;
  algorithm.ode_tolerance
  algorithm.mr_max_iterations
psopt(solution, problem, algorithm);
DMatrix x, u, t, xi, ui, ti;
    = solution.get_states_in_phase(1);
     = solution.get_controls_in_phase(1);
    = solution.get_time_in_phase(1);
x.Save("x.dat"):
 t.Save("t.dat");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.97 and 3.98, which contain the elements of the state and the control, respectively.




Figure 3.97: States for singular control problem

Optimal (unscaled) cost function value: 1.192562e-01 Phase 1 endpoint cost function value: 0.000000e+00 Phase 1 integrated part of the cost: 1.192562e-01

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 1.000000e+00

Phase 1 maximum relative local error: 2.503060e-04 NLP solver reports: The problem has been solved!

3.38 Time varying state constraint problem

Consider the following optimal control problem, which involves a time varying state constraint [40]. Find $u(t) \in [0, 1]$ to minimize the cost functional

$$J = \int_0^1 [x_1^2(t) + x_2^2(t) + 0.005u^2(t)]dt$$
 (3.152)

subject to the dynamic constraints

$$\begin{array}{rcl}
\dot{x}_1 & = & x_2 \\
\dot{x}_2 & = & -x_2 + u
\end{array} \tag{3.153}$$




Figure 3.98: Control for singular control problem

the boundary conditions:

$$\begin{array}{rcl}
x_1(0) & = & 0 \\
x_2(0) & = & -1
\end{array}
\tag{3.154}$$

and the path constraint

$$x_2 \le 8(t - 0.5)^2 - 0.5 \tag{3.155}$$

The \mathcal{PSOPT} code that solves this problem is shown below.

```
adouble* xad, int iphase, Workspace* workspace)
  adouble retval = 0.0;
  return retval;
adouble integrand_cost(adouble* states, adouble* controls,
           adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
  adouble x1 = states[0];
  adouble x2 = states[1];
adouble u = controls[0];
  return ( x1*x1 + x2*x2 + 0.005*u*u);
}
adouble xdot, ydot, vdot;
 adouble x1 = states[0];
 adouble x2 = states[1];
adouble t = time;
 adouble u = controls[0];
 derivatives[0] = x2;
derivatives[1] = -x2 + u;
 path[0] = -( 8.0*((t-0.5)*(t-0.5)) -0.5 - x2);
void events(adouble* e, adouble* initial_states, adouble* final_states,
      adouble* parameters,adouble% t0, adouble% tf, adouble* xad, int iphase, Workspace* workspace)
 adouble x10 = initial_states[0];
adouble x20 = initial_states[1];
 e[0] = x10;
e[1] = x20;
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
// No linkages as this is a single phase problem
int main(void)
```

```
Alg algorithm;
Sol solution;
  Prob problem;
problem.name = "Time varying state constraint problem";
problem.outfilename= "stc1.txt";
problem.nphases
                          = 0:
  problem.nlinkages
  psopt_level1_setup(problem);
problem.phases(1).nstates
                     = 2;
  problem.phases(1).ncontrols = 1;
  problem.phases(1).nevents = 2;
  problem.phases(1).npath
                               = "[20 50]";
  problem.phases(1).nodes
  psopt_level2_setup(problem, algorithm);
problem.phases(1).bounds.lower.states(1) = -2.0;
problem.phases(1).bounds.lower.states(2) = -2.0;
  problem.phases(1).bounds.upper.states(1) = 2.0;
  problem.phases(1).bounds.upper.states(2) = 2.0;
  problem.phases(1).bounds.lower.controls(1) = -20.0;
problem.phases(1).bounds.upper.controls(1) = 20.0;
  problem.phases(1).bounds.lower.events(1) = 0.0;
  problem.phases(1).bounds.lower.events(2) = -1.0;
  problem.phases(1).bounds.upper.events(1) = 0.0;
  problem.phases(1).bounds.upper.events(2) = -1.0;
  problem.phases(1).bounds.upper.path(1) = 0.0;
problem.phases(1).bounds.lower.path(1) = -100.0;
                              = 0.0;
= 0.0;
  problem.phases(1).bounds.lower.StartTime
  problem.phases(1).bounds.upper.StartTime
  problem.phases(1).bounds.lower.EndTime
                               = 1.0;
  problem.phases(1).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
  problem.dae = &dae;
  problem.events = &events;
  problem.linkages = &linkages;
```

```
= "automatic";
= "automatic";
  algorithm.scaling
  algorithm.derivatives
  algorithm.nlp_iter_max = 1000
algorithm.nlp_tolerance = 1.e-4;
               = 1000;
  algorithm.nlp_method ="IPOPT";
psopt(solution, problem, algorithm);
//////// Extract relevant variables from solution structure ////////
  DMatrix x = solution.get_states_in_phase(1);
  DMatrix u = solution.get_controls_in_phase(1);
DMatrix t = solution.get_time_in_phase(1);
x.Save("x.dat");
  t.Save("t.dat");
// Generate points to plot the constraint boundary
  DMatrix x2c = 8.0*((t-0.5)^2.0) -0.5*ones(1,length(t));
  \label{eq:plot_states} $$ plot(t,x,t,x2c,"states","time (s)", "x", "x1 x2 constraint"); $$ plot(t,u,"control","time (s)", "u"); $$ 
  plot(t,x,t,x2c,"states","time (s)", "x", "x1 x2 constraint",
 "pdf", "stc1_states.pdf");
plot(t,u,"control","time (s)", "u", "u", "pdf","stc1_control.pdf");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.99 and 3.100, which contain the elements of the states with the boundary of the constraint on x_2 , and the control, respectively.




Figure 3.99: States for time-varying state constraint problem

```
NLP solver used: IPOPT
PSOPT release number: 4.0
Date and time of this run: Thu Feb 21 17:07:14 2019

Optimal (unscaled) cost function value: 1.698182e-01
Phase 1 endpoint cost function value: 0.000000e+00
Phase 1 integrated part of the cost: 1.698182e-01
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 1.000000e+00
Phase 1 maximum relative local error: 3.150532e-05
NLP solver reports: The problem has been solved!
```

3.39 Two burn orbit transfer

The goal of this problem is to compute a trajectory for an spacecraft to go from a standard space shuttle park orbit to a geosynchronous final orbit. It is assumed that the engines operate over two short periods during the mission, and it is desired to compute the timing and duration of the burn periods, as well as the instantaneous direction of the thrust during these two periods, to maximise the final weight of the spacecraft. The problem is described in detail by Betts [3]. The mission then involves four phases: coast, burn, coast and burn. The problem is formulated as follows. Find $\mathbf{u}(t) =$




Figure 3.100: Control for time-varying state constraint problem

 $[\theta(t),\phi(t)]^T,t\in[t_f^{(1)},t_f^{(2)}]$ and $t\in[t_f^{(3)},t_f^{(4)}]$, and the instants $t_f^{(1)},t_f^{(2)},t_f^{(3)},t_f^{(4)}$ such that the following objective function is minimised:

$$J = -w(t_f) \tag{3.156}$$

subject to the dynamic constraints for phases 1 and 3:

$$\dot{\mathbf{y}} = \mathbf{A}(\mathbf{y})\Delta_q + \mathbf{b} \tag{3.157}$$

the following dynamic constraints for phases 2 and 4:

$$\dot{\mathbf{y}} = \mathbf{A}(\mathbf{y})\Delta + \mathbf{b}$$

$$\dot{w} = -T/I_{sp}$$
(3.158)

and the following linkages between phases

$$\mathbf{y}(t_f^{(1)}) = \mathbf{y}(t_0^{(2)})$$

$$\mathbf{y}(t_f^{(2)}) = \mathbf{y}(t_0^{(3)})$$

$$\mathbf{y}(t_f^{(3)}) = \mathbf{y}(t_0^{(4)})$$

$$t_f^{(1)} = t_0^{(2)}$$

$$t_f^{(2)} = t_0^{(3)}$$

$$t_f^{(3)} = t_0^{(4)}$$

$$w(t_f^{(2)}) = w(t_0^{(4)})$$
(3.159)

where $\mathbf{y} = [p, f, g, h, k, L, w]^T$ is the vector of modified equinoctial elements, w is the spacecraft weight, I_{sp} is the specific impulse of the engine, T is the maximum thrust, expressions for $\mathbf{A}(\mathbf{y})$ and \mathbf{b} are given in [3]. the disturbing acceleration is $\Delta = \Delta_g + \Delta_T$, where Δ_g is the gravitational disturbing acceleration due to the oblatness of Earth (given in [3]), and Δ_T is the thurst acceleration, given by:

$$\Delta_T = \mathbf{Q}_r \mathbf{Q}_v \begin{bmatrix} T_a \cos \theta \cos \phi \\ T_a \cos \theta \sin \phi \\ T_a \sin \theta \end{bmatrix}$$
(3.160)

where $T_a(t) = g_0 T/w(t)$, g_0 is a constant, θ is the pitch angle and ϕ is the yaw angle of the thurst, matrix \mathbf{Q}_v is given by:

$$\mathbf{Q}_{v} = \left[\frac{\mathbf{v}}{||\mathbf{v}||}, \frac{\mathbf{v} \times r}{||\mathbf{v} \times \mathbf{r}||}, \frac{\mathbf{v}}{||\mathbf{v}||} \times \frac{\mathbf{v} \times r}{||\mathbf{v} \times \mathbf{r}||} \right]$$
(3.161)

matrix \mathbf{Q}_r is given by:

$$\mathbf{Q}_r = \begin{bmatrix} \mathbf{i}_r & \mathbf{i}_\theta & \mathbf{i}_h \end{bmatrix} = \begin{bmatrix} \mathbf{r} & \frac{(\mathbf{r} \times \mathbf{v}) \times \mathbf{r}}{||\mathbf{r} \times \mathbf{v}||||\mathbf{r}||} & \frac{(\mathbf{r} \times \mathbf{v})}{||\mathbf{r} \times \mathbf{v}||} \end{bmatrix}$$
(3.162)

The boundary conditions of the problem are given by:

$$p(0) = 218327080.052835$$

$$f(0) = 0$$

$$g(0) = 0$$

$$h(0) = 0$$

$$h(0) = 0$$

$$k(0) = 0$$

$$L(0) = \pi \text{ (rad)}$$

$$w(0) = 1 \text{ (lb)}$$

$$p(t_f) = 19323/\sigma + R_e$$

$$f(t_f) = 0$$

$$g(t_f) = 0$$

$$h(t_f) = 0$$

$$k(t_f) = 0$$

and the values of the parameters are: $g_0 = 32.174$ (ft/sec²), $I_{sp} = 300$ (sec), T = 1.2 (lb), $\mu = 1.407645794 \times 10^{16}$ (ft³/sec²), $R_e = 20925662.73$ (ft), $\sigma = 1.0/6076.1154855643$, $J_2 = 1082.639 \times 10^{-6}$, $J_3 = -2.565 \times 10^{-6}$, $J_4 = -1.608 \times 10^{-6}$.

An initial guess was computed by forward propagation from the initial conditions, assuming the following guesses for the controls and burn periods [3]:

$$\mathbf{u}(t) = \begin{bmatrix} 0.148637 \times 10^{-2}, & -9.08446 \end{bmatrix}^{T} \quad t \in [2840, 21650]$$

$$\mathbf{u}(t) = \begin{bmatrix} -0.136658 \times 10^{-2}, & 49.7892 \end{bmatrix} \quad t \in [21650, 21700]$$
(3.164)

The problem was solved using local collocation (trapezoidal followed by Hermite-Simpson) with automatic mesh refinement. The \mathcal{PSOPT} code that solves the problem is shown below.

```
////// Last modified: 07 February 2010
////// Reference: Betts (2001)
                             #include "psopt.h"
adouble legendre_polynomial( adouble x, int n)
// This function computes the value of the legendre polynomials // for a given value of the argument x and for n=0...5 only
 switch(n) {
   case 0:
     retval=1.0; break;
   case 1:
    retval= x; break;
   retval= 0.5*(3.0*pow(x,2)-1.0); break; case 3:
     retval= 0.5*(5.0*pow(x,3)- 3*x); break;
     retval= (1.0/8.0)*(35.0*pow(x,4) - 30.0*pow(x,2) + 3.0); break;
     retval= (1.0/8.0)*(63.0*pow(x,5) - 70.0*pow(x,3) + 15.0*x); break;
     \verb|error_message("legendre_polynomial(x,n) is limited to n=0...5");|\\
}
adouble legendre_polynomial_derivative( adouble x, int n)
// This function computes the value of the legendre polynomial derivatives
// for a given value of the argument x and for n=0...5 only.
 adouble retval=0.0:
```

```
switch(n) {
     case 0:
         retval=0.0; break;
     case 1:
        retval= 1.0; break;
     case 2:
     retval= 0.5*(2.0*3.0*x); break; case 3:
        retval= 0.5*(3.0*5.0*pow(x,2)-3.0); break;
     case 4:
        retval= (1.0/8.0)*(4.0*35.0*pow(x,3) - 2.0*30.0*x); break;
     case 5:
         retval= (1.0/8.0)*(5.0*63.0*pow(x,4) - 3.0*70.0*pow(x,2) + 15.0); break;
     default:
        error_message("legendre_polynomial_derivative(x,n) is limited to n=0...5");
void compute_cartesian_trajectory(const DMatrix& x, DMatrix& xyz ) {
   int npoints = x.GetNoCols();
   xyz.Resize(3,npoints);
   for(int i=1; i<=npoints;i++) {</pre>
   double p = x(1,i);
double f = x(2,i);
   double f = x(2,1);
double g = x(3,i);
double h = x(4,i);
   double k = x(5,i);
double L = x(6,i);
   double q = 1.0 + f*cos(L) + g*sin(L);
double r = p/q;
double alpha2 = h*h - k*k;
   xyz(1,i) = r1;
   xyz(2,i) = r2;
xyz(3,i) = r3;
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
                      adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  if (iphase == 4) {
adouble w = final_states[CINDEX(7)];
return (-w);
   else {
   return (0);
}
//////////////// Define the integrand (Lagrange) cost function //////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
ſ
   return 0.0;
```

```
void dae(adouble* derivatives, adouble* path, adouble* states,
        adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
   // Local integers
   int i, j;
// Define constants:
  double J[5];
   J[2] = 1082.639e-6;
J[3] = -2.565e-6;
J[4] = -1.608e-6;
   // Extract individual variables
   adouble p = states[ CINDEX(1) ];
adouble f = states[ CINDEX(2) ];
adouble g = states[ CINDEX(3) ];
   adouble k = states[CINDEX(4)];
adouble k = states[CINDEX(5)];
adouble L = states[CINDEX(6)];
   adouble w;
   adouble* u = controls;
   // Define some dependent variables
  adouble q = 1.0 + f*cos(L) + g*sin(L);
adouble r = p/q;
adouble alpha2 = h*h - k*k;
adouble X = sqrt( h*h + k*k );
adouble s2 = 1 + X*X;
   // r and v
   adouble rvec[3]:
   rvec[ CINDEX(1) ] = r1: rvec[ CINDEX(2)] = r2: rvec[ CINDEX(3) ] = r3:
   adouble vvec[3];
   vvec[ CINDEX(1) ] = v1; vvec[ CINDEX(2)] = v2; vvec[ CINDEX(3) ] = v3;
   // compute Qr
   adouble ir[3], ith[3], ih[3];
   adouble rv[3];
   adouble rvr[3]:
   cross( rvec, vvec, rv );
   cross( rv, rvec, rvr );
   adouble norm_r = sqrt( dot(rvec, rvec, 3) );
   adouble norm_rv = sqrt( dot(rv, rv, 3) );
   for (i=0; i<3; i++) {
      ir[i] = rvec[i]/norm_r;
      ith[i] = rvr[i]/( norm_rv*norm_r );
```

```
ih[i] = rv[i]/norm_rv;
 adouble Qr1[3], Qr2[3], Qr3[3];
 for(i=0; i< 3; i++)
       // Columns of matrix Qr
Qr1[i] = ir[i];
Qr2[i] = ith[i];
Qr3[i] = ih[i];
 adouble Qv1[3], Qv2[3], Qv3[3];
 adouble norm_v = sqrt( dot(vvec, vvec,3) );
 for(i=0;i<3;i++)
Qv1[i] = vvec[i]/norm_v;
}
 adouble vr[3];
 cross( vvec, rvec, vr);
 adouble norm_vr = sqrt( dot(vr, vr,3) );
 for(i=0:i<3:i++)
Qv2[i] = vr[i]/norm_vr;
}
 cross( Qv1, Qv2, Qv3 );
 // Compute in
 adouble en[3]; en[ CINDEX(1) ] = 0.0; en[ CINDEX(2) ]= 0.0; en[ CINDEX(3) ] = 1.0;
 adouble enir = dot(en,ir,3);
 adouble in[3];
for(i=0;i<3;i++) {
  in[i] = en[i] - enir*ir[i];
}</pre>
 adouble norm_in = sqrt( dot( in, in, 3 ) );
- \1 - \, 1 < 3; i++) {
    in[i] = in[i]/norm_in;
}
 for(i=0;i<3;i++) {
 // Geocentric latitude angle:
 adouble sin_phi = rvec[ CINDEX(3) ]/ sqrt( dot(rvec,rvec,3) ) ;
adouble cos_phi = sqrt(1.0- pow(sin_phi,2.0));
adouble deltagn = 0.0;
adouble deltagr = 0.0;
for (j=2; j<=4;j++) {
    adouble Pdash_j = legendre_polynomial_derivative( sin_phi, j );
    adouble P_j = legendre_polynomial( sin_phi, j );
    deltagn += -mu*cos_phi/(r*r)*pow(Re/r,j)*Pdash_j*J[j];
    deltagr += -mu/(r*r)* (j+1)*pow( Re/r,j)*P_j*J[j];
}</pre>
 // Compute vector delta_g
 adouble delta_g[3];
for (i=0;i<3;i++) {</pre>
     delta_g[i] = deltagn*in[i] - deltagr*ir[i];
 // Compute vector DELTA_g
 adouble DELTA_g[3];
 DELTA_g[ CINDEX(1) ] = dot(Qr1, delta_g,3);
DELTA_g[ CINDEX(2) ] = dot(Qr2, delta_g,3);
DELTA_g[ CINDEX(3) ] = dot(Qr3, delta_g,3);
```

```
// Compute DELTA_T
 adouble DELTA_T[3];
 if (iphase == 1 || iphase==3) {
    for(i=0;i<3;i++) {
        DELTA_T[i] = 0.0;
}</pre>
 }
 else {
      adouble Qr[9], Qrt[9], Qv[9], Tvel[3];
      for(i=0;i<3;i++) {
Qr[i] = Qr1[i];
Qr[3+i] = Qr2[i];
Qr[6+i] = Qr3[i];
Qv[i] = Qv1[i];
Qv[3+i] = Qv2[i];
Qv[6+i] = Qv3[i];
      transpose_ad(Qr, 3, 3, Qrt );
      adouble theta = u[ CINDEX(1) ];
adouble phi = u[ CINDEX(2) ];
      adouble Tvec[3]:
      w = states[CINDEX(7)];
      adouble mass = w/CM2W;
      adouble Tacc = T/mass;
      Tvec[ CINDEX(1) ] = Tacc*cos(theta)*cos(phi);
Tvec[ CINDEX(2) ] = Tacc*cos(theta)*sin(phi);
Tvec[ CINDEX(3) ] = Tacc*sin(theta);
      product_ad( Qv, Tvec, 3, 3, 3, 1, Tvel );
      product_ad(Qrt, Tvel, 3, 3, 3, 1, DELTA_T );
 }
 // Compute DELTA
 adouble DELTA[3];
 DELTA[i] = DELTA_g[i] + DELTA_T[i];
}
 for(i=0;i<3;i++) {
 adouble delta1= DELTA[ CINDEX(1) ];
adouble delta2= DELTA[ CINDEX(2) ];
adouble delta3= DELTA[ CINDEX(3) ];
// derivatives
if (iphase==2 || iphase==4) {
 -- \ipnase==2 ||
  wdot = -T/Isp;
}
 else {
    wdot = 0.0;
 1
 derivatives[ CINDEX(1) ] = pdot;
derivatives[ CINDEX(2) ] = fdot;
```

```
derivatives[ CINDEX(3) ] = gdot;
derivatives[ CINDEX(4) ] = hdot;
derivatives[ CINDEX(5) ] = kdot;
derivatives[ CINDEX(6) ] = Ldot;
     if (iphase==2 || iphase==4) {
  derivatives[ CINDEX(7) ] = wdot;
void events(adouble* e, adouble* initial_states, adouble* final_states,
                     adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
     adouble pti = initial_states[ CINDEX(1) ]:
    adouble fti = initial_states[ CINDEX(1) ];
adouble fti = initial_states[ CINDEX(2) ];
adouble gti = initial_states[ CINDEX(3) ];
adouble hti = initial_states[ CINDEX(5) ];
adouble kti = initial_states[ CINDEX(6) ];
adouble Lti = initial_states[ CINDEX(6) ];
     adouble wti;
     if (iphase==2) {
  wti = initial_states[ CINDEX(7) ];
    adouble ptf = final_states[ CINDEX(1) ];
adouble ftf = final_states[ CINDEX(2) ];
adouble gtf = final_states[ CINDEX(3) ];
adouble htf = final_states[ CINDEX(4) ];
adouble ktf = final_states[ CINDEX(6) ];
adouble Ltf = final_states[ CINDEX(6) ];
    if (iphase==1) {
    e[ CINDEX(1) ] = pti;
    e[ CINDEX(2) ] = fti;
    e[ CINDEX(3) ] = gti;
    e[ CINDEX(4) ] = hti;
    e[ CINDEX(5) ] = kti;
    e[ CINDEX(6) ] = Lti;
    -- \'\pnase==2) {
    e[ CINDEX(1) ] = wti;
}
     if (iphase==2) {
    if (iphase == 4) {
    e[ CINDEX(1) ] = ptf;
    e[ CINDEX(2) ] = ftf;
    e[ CINDEX(3) ] = gtf;
    e[ CINDEX(4) ] = htf;
    e[ CINDEX(5) ] = ktf;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
       // Numeber of linkages:
       // Boundary of phases 1,2: 6 state continuity + 1 time continuity
       // Boundary of phases 2,3: 6 state continuity + 1 time continuity // Boundary of phases 3,4: 6 state continuity + 1 time continuity
       // 1 extra linkage w(tf2) = w(ti4)
// Total: 22 linkage constraints
       adouble xf[7], xi[7], t0a, t0b, tfa, tfb, wtf2, wti4;
       // Linking phases 1 and 2
```

```
get_final_states(
                                 xf, xad, 1, workspace );
     linkages[ CINDEX(1) ] = xf[ CINDEX(1) ] - xi[ CINDEX(1) ];
linkages[ CINDEX(2) ] = xf[ CINDEX(2) ] - xi[ CINDEX(2) ];
linkages[ CINDEX(3) ] = xf[ CINDEX(3) ] - xi[ CINDEX(3) ];
linkages[ CINDEX(4) ] = xf[ CINDEX(4) ] - xi[ CINDEX(4) ];
linkages[ CINDEX(6) ] = xf[ CINDEX(6) ] - xi[ CINDEX(5) ];
linkages[ CINDEX(6) ] = xf[ CINDEX(6) ] - xi[ CINDEX(6) ];
linkages[ CINDEX(7) ] = tOb - tfa;
     // Linking phases 2 and 3
    wtf2 = xf[CINDEX(7)];
    linkages[CINDEX(8)] = xf[CINDEX(1)] - xi[CINDEX(1)];
linkages[CINDEX(9)] = xf[CINDEX(2)] - xi[CINDEX(2)];
linkages[CINDEX(10)] = xf[CINDEX(3)] - xi[CINDEX(3)];
linkages[CINDEX(11)] = xf[CINDEX(4)] - xi[CINDEX(4)];
linkages[CINDEX(12)] = xf[CINDEX(5)] - xi[CINDEX(6)];
linkages[CINDEX(13)] = xf[CINDEX(6)] - xi[CINDEX(6)];
linkages[CINDEX(14)] = t0b - tfa;
     // Linking phases 3 and 4 \,
    wti4 = xi[ CINDEX(7) ];
    linkages[ CINDEX(15) ] = xf[ CINDEX(1) ] - xi[ CINDEX(1) ];
linkages[ CINDEX(16) ] = xf[ CINDEX(2) ] - xi[ CINDEX(2) ];
linkages[ CINDEX(17) ] = xf[ CINDEX(3) ] - xi[ CINDEX(3) ];
linkages[ CINDEX(18) ] = xf[ CINDEX(4) ] - xi[ CINDEX(4) ];
linkages[ CINDEX(19) ] = xf[ CINDEX(5) ] - xi[ CINDEX(5) ];
linkages[ CINDEX(20) ] = xf[ CINDEX(6) ] - xi[ CINDEX(6) ];
linkages[ CINDEX(21) ] = tob - tfa;
     // Linking the weight at the end of phase 2 with the weight at the beginning of phase 4
    linkages[ CINDEX(22) ] = wtf2 - wti4;
}
int main(void)
Alg algorithm;
Sol solution;
    Prob problem;
    MSdata msdata;
= "Two burn transfer problem";
    problem.outfilename
                                                = "twoburn.txt";
//////// Define problem level constants & do level 1 setup /////////
```

```
problem.nphases = 4;
problem.nlinkages
                                            = 22;
    psopt_level1_setup(problem);
problem.phases(1).nstates = 6;
problem.phases(1).ncontrols = 0;
problem.phases(1).nparameters
archlom.phases(1).neunts
    problem.phases(1).nevents
problem.phases(1).neath = 0;
                                                    = 0;
                                            = 6:
    problem.phases(1).nodes
                                                    = 10:
    problem.phases(2).nstates = 7;
problem.phases(2).ncontrols = 2;
    problem.phases(2).nevents
problem.phases(2).nevents
problem.phases(2).npath = 0;
    problem.phases(2).nparameters
                                                    = 0:
    problem.phases(2).npath
problem.phases(2).nodes
                                                    = 10;
    problem.phases(3).nstates = 6;
problem.phases(3).ncontrols = 0;
problem.phases(3).nparameters
                                                    = 0;
    = 0;
    problem.phases(3).nodes
                                                    = 10:
    problem.phases(4).nstates = 7;
problem.phases(4).ncontrols = 2;
problem.phases(4).nparameters
                                                    = 0;
    problem.phases(4).nevents
problem.phases(4).npath = 0;
                                            = 5;
    problem.phases(4).nodes
                                                    = 10;
    psopt_level2_setup(problem, algorithm);
double pti = 21837080.052835;
double fti = 0.0;
    double gti = 0.0;
double hti = -0.25396764647494;
double kti = 0.0;
    double Lti = pi;
double wti = 1.0;
    double SISP = 300.0;
    double DELTAV2 = 8000;
double DELTAV4 = 3000;
    double CM2W = 32.174;
    double sigma = 1.0/6076.1154855643;
    double Re = 20925662.73;
    double wtf2 = wti*exp(-DELTAV2/(CM2W*SISP));
double wtf4 = wtf2*exp(-DELTAV4/(CM2W*SISP));
    double ptf = 19323/sigma + Re;
double ftf = 0.0;
double gtf = 0.0;
double htf = 0.0;
double ktf = 0.0;
    double D2R = pi/180.0;
   // BOUNDS FOR PHASE 1
    problem.phases(1).bounds.lower.states(1) = 10.e6;
    problem.phases(1).bounds.lower.states(2) = -1;
```

```
problem.phases(1).bounds.lower.states(3) = -1;
problem.phases(1).bounds.lower.states(4) = -1;
problem.phases(1).bounds.lower.states(5) = -1;
problem.phases(1).bounds.lower.states(6) = pi;
problem.phases(1).bounds.upper.states(1) = 2e8;
problem.phases(1).bounds.upper.states(2) = 1;
problem.phases(1).bounds.upper.states(3) = 1;
problem.phases(1).bounds.upper.states(4) = 1;
problem.phases(1).bounds.upper.states(5) = 1;
problem.phases(1).bounds.upper.states(6) = 30*pi;
problem.phases(1).bounds.lower.events(1) = pti;
problem.phases(1).bounds.lower.events(2) = fti;
problem.phases(1).bounds.lower.events(3) = gti;
problem.phases(1).bounds.lower.events(4) = hti;
problem.phases(1).bounds.lower.events(5) = kti;
problem.phases(1).bounds.lower.events(6) = Lti;
problem.phases(1).bounds.upper.events(1) = pti;
problem.phases(1).bounds.upper.events(2) = fti;
problem.phases(1).bounds.upper.events(3)
problem.phases(1).bounds.upper.events(4)
                                                             = gti;
= hti;
problem.phases(1).bounds.upper.events(5) = kti;
problem.phases(1).bounds.upper.events(6) = Lti;
problem.phases(1).bounds.lower.StartTime
                                                                 = 0.0;
problem.phases(1).bounds.upper.StartTime
problem.phases(1).bounds.lower.EndTime
problem.phases(1).bounds.upper.EndTime
                                                                 = 2000.0:
                                                                 = 3000.0;
// BOUNDS FOR PHASE 2
problem.phases(2).bounds.lower.states(1) = 10.e6;
problem.phases(2).bounds.lower.states(2) = -1;
problem.phases(2).bounds.lower.states(3) = -1;
problem.phases(2).bounds.lower.states(4) = -1;
problem.phases(2).bounds.lower.states(5) = -1;
problem.phases(2).bounds.lower.states(6) = pi;
problem.phases(2).bounds.lower.states(7) = 0.0;
problem.phases(2).bounds.upper.states(1) = 2.e8;
problem.phases(2).bounds.upper.states(2) = 1;
problem.phases(2).bounds.upper.states(3) = 1;
problem.phases(2).bounds.upper.states(4) = 1;
problem.phases(2).bounds.upper.states(5) = 1;
problem.phases(2).bounds.upper.states(6) = 30*pi;
problem.phases(2).bounds.upper.states(7) = 2.0;
problem.phases(2).bounds.lower.controls(1) = -pi;
problem.phases(2).bounds.lower.controls(2) = -pi;
problem.phases(2).bounds.upper.controls(1) = pi;
problem.phases(2).bounds.upper.controls(2) = pi;
problem.phases(2).bounds.lower.events(1) = wti;
problem.phases(2).bounds.upper.events(1) = wti;
problem.phases(2).bounds.lower.StartTime
problem.phases(2).bounds.upper.StartTime
                                                                 = 2000:
problem.phases(2).bounds.lower.EndTime
                                                                 = 2100:
 problem.phases(2).bounds.upper.EndTime
                                                                 = 3100:
// BOUNDS FOR PHASE 3
problem.phases(3).bounds.lower.states(1) = 10.e6;
problem.phases(3).bounds.lower.states(2) = -1;
problem.phases(3).bounds.lower.states(3) = -1;
problem.phases(3).bounds.lower.states(4) = -1;
problem.phases(3).bounds.lower.states(5) = -1;
problem.phases(3).bounds.lower.states(6) = pi:
```

```
problem.phases(3).bounds.upper.states(1) = 2.e8;
    problem.phases(3).bounds.upper.states(2) = 1.0;
problem.phases(3).bounds.upper.states(3) = 1.0;
problem.phases(3).bounds.upper.states(4) = 1.0;
     problem.phases(3).bounds.upper.states(5) = 1.0;
    problem.phases(3).bounds.upper.states(6) = 30*pi;
    problem.phases(3).bounds.lower.StartTime
problem.phases(3).bounds.upper.StartTime
                                                       = 2100;
= 3100;
    problem.phases(3).bounds.lower.EndTime
                                                       = 21600;
                                                       = 21800;
     problem.phases(3).bounds.upper.EndTime
    // BOUNDS FOR PHASE 4
    problem.phases(4).bounds.lower.states(1) = 10.e6;
    problem.phases(4).bounds.lower.states(2) = -1;
problem.phases(4).bounds.lower.states(3) = -1;
     problem.phases(4).bounds.lower.states(4) = -1;
    problem.phases(4).bounds.lower.states(5) = -1;
     problem.phases(4).bounds.lower.states(6) = pi;
    problem.phases(4).bounds.lower.states(7) = 0.0;
    problem.phases(4).bounds.upper.states(1) = 2.e8;
    problem.phases(4).bounds.upper.states(2) = 1;
problem.phases(4).bounds.upper.states(3) = 1;
    problem.phases(4).bounds.upper.states(4) = 1;
problem.phases(4).bounds.upper.states(5) = 1;
problem.phases(4).bounds.upper.states(6) = 30*pi;
    problem.phases(4).bounds.upper.states(7) = 2.0;
    problem.phases(4).bounds.lower.controls(1) = -pi;
    problem.phases(4).bounds.lower.controls(2) = -pi;
problem.phases(4).bounds.upper.controls(1) = pi;
     problem.phases(4).bounds.upper.controls(2) = pi;
    problem.phases(4).bounds.lower.events(1) = ptf;
    problem.phases(4).bounds.lower.events(2) = ftf;
problem.phases(4).bounds.lower.events(3) = gtf;
    problem.phases(4).bounds.lower.events(4) = htf;
problem.phases(4).bounds.lower.events(5) = ktf;
    problem.phases(4).bounds.upper.events(1) = ptf;
    problem.phases(4).bounds.upper.events(2) = ftf;
problem.phases(4).bounds.upper.events(3) = gtf;
                                                    = gtf;
    problem.phases(4).bounds.upper.events(4)
problem.phases(4).bounds.upper.events(5)
                                                       = 21600;
= 21800;
    problem.phases(4).bounds.lower.StartTime
    problem.phases(4).bounds.upper.StartTime
    problem.phases(4).bounds.lower.EndTime
                                                       = 21650:
    problem.phases(4).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
    problem.dae
    problem.events = &events;
    problem.linkages = &linkages;
int ncontrols;
     int nstates;
     int iphase;
    DMatrix x_guess, u_guess, time_guess, param_guess, xini, xfinal;
    // Phase 1
    nnodes
               = problem.phases(1).nodes(1);
```

```
nstates
                                = problem.phases(1).nstates;
iphase = 1;
x_guess = zeros(nstates,nnodes);
time_guess = linspace(0.0,2690,nnodes);
xini.Resize(6,1);
xini(1)= pti; xini(2)=fti;xini(3)=gti;xini(4)=hti;xini(5)=kti;xini(6)=Lti;
rk4_propagate( dae, u_guess, time_guess, xini, param_guess, problem, iphase, x_guess, NULL);
tra(x_guess).Print("x_guess(iphase=1)");
xfinal = x_guess(colon(),nnodes);
problem.phases(1).guess.states = x_guess;
problem.phases(1).guess.time = time_guess;
// Phase 2
nnodes = problem.phases(2).nodes(1);
                = problem.phases(2).nstates;
= problem.phases(2).ncontrols;
nstates
ncontrols
iphase = 2;
u_guess = zeros(ncontrols,nnodes);
x_guess = zeros(nstates,nnodes);
time_guess = linspace(2690,2840,nnodes);
xini.Resize(7,1);
xini(1)= xfinal(1); xini(2)=xfinal(2);xini(3)=xfinal(3);xini(4)=xfinal(4);xini(5)=xfinal(5);xini(6)=xfinal(6);
xini(7)= wti;
u_guess(1,colon()) = 0.148637e-2*D2R*ones(1,nnodes);
u_guess(2,colon()) = -9.08446*D2R*ones(1,nnodes);
\verb|rk4_propagate( dae, u_guess, time_guess, xini, param_guess, problem, iphase, x_guess, \verb|NULL||;||
\verb|tra(x_guess).Print("x_guess(iphase=2)");|\\
xfinal = x_guess(colon(),nnodes);
double wtf2__ = xfinal(7);
// Phase 3
          = problem.phases(3).nodes(1);
nnodes
                                = problem.phases(3).nstates;
iphase = 3:
x_guess = zeros(nstates,nnodes);
time_guess = linspace(2840,21650,nnodes);
xini.Resize(6,1);
xini(1)= xfinal(1); xini(2)=xfinal(2);xini(3)=xfinal(3);xini(4)=xfinal(4);xini(5)=xfinal(5);xini(6)=xfinal(6);
rk4_propagate( dae, u_guess, time_guess, xini, param_guess, problem, iphase, x_guess, NULL);
tra(x guess).Print("x guess(iphase=3)"):
xfinal = x_guess(colon(),nnodes);
problem.phases(3).guess.states = x_guess;
problem.phases(3).guess.time = time_guess;
// Phase 4
nnodes = problem.phases(4).nodes(1);
                  = problem.phases(4).nstates;
= problem.phases(4).ncontrols;
nstates
ncontrols
iphase = 4;
```

```
= zeros(ncontrols,nnodes);
    u_guess
               = zeros(nstates,nnodes);
    x_guess
    time_guess = linspace(21650,21700,nnodes);
    u_guess(1,colon()) = -0.136658e-2*D2R*ones(1,nnodes);
u_guess(2,colon()) = 49.7892*D2R*ones(1,nnodes);
    xini(1)= xfinal(1); xini(2)=xfinal(2);xini(3)=xfinal(3);xini(4)=xfinal(4);xini(5)=xfinal(5);xini(6)=xfinal(6);
xini(7)= wtf2__;
    rk4_propagate( dae, u_guess, time_guess, xini, param_guess, problem, iphase, x_guess, NULL);
    tra(x_guess).Print("x_guess(iphase=4)");
    problem.phases(4).guess.states = x_guess;
problem.phases(4).guess.controls = u_guess;
    problem.phases(4).guess.time = time_guess;
= 1000;
= 1.e-6;
= "IPOPT";
    algorithm.nlp_iter_max
    algorithm.nlp_tolerance
    algorithm.nlp_method
                                           = "automatic";
    algorithm.scaling
                                          = "automatic";
= "automatic";
= "jacobian-based";
= 0.11;
= "trapezoidal";
    algorithm.derivatives
    algorithm.defect_scaling
   algorithm.defect_scaling
algorithm.jac_sparsity_ratio
algorithm.collocation_method
algorithm.diff_matrix
algorithm.mesh_refinement
algorithm.mesh_refinement
algorithm.diff_matrix
                                           = "central-differences";
= "automatic";
                                           = 5;
= 1.0e-6;
    algorithm.ode_tolerance
psopt(solution, problem, algorithm);
DMatrix x, t, w2, xi, w4, ti;
          = solution.get_states_in_phase(1);
          = solution.get_time_in_phase(1);
        = solution.get_states_in_phase(2);
= w2(7,colon());
    w2
        = solution.get_states_in_phase(4);
= w4(7,colon());
   for(int i=2;i<=problem.nphases;i++) {
    xi = solution.get_states_in_phase(i);
    ti = solution.get_time_in_phase(i);</pre>
xi = xi(colon(1,6),colon());
x = x \mid \mid xi;
        t = t || ti;
   }
                        = solution.get_controls_in_phase(2);
= solution.get_controls_in_phase(4);
= solution.get_time_in_phase(2);
    {\tt DMatrix\ u\_phase2}
   DMatrix u_phase4
DMatrix t2
    DMatrix t4
                        = solution.get_time_in_phase(4);
```

```
x.Save("x.dat");
    u.Save("u.dat");
    t.Save("t.dat");
double R2D = 180/\text{pi}:
   DMatrix x1 = x(1,colon())/1.e6;
DMatrix x2 = x(2,colon());
   DMatrix x3 = x(3, colon()):
   DMatrix x4 = x(4,colon());
   DMatrix x5 = x(5,colon());
   DMatrix x6 = x(6,colon());

DMatrix x7 = x(7,colon());

DMatrix theta_phase2;
   DMatrix theta_phase4;
DMatrix phi_phase2;
   DMatrix phi_phase4;
   DMatrix r;
   theta_phase2 = u_phase2(1,colon())*R2D;
   phi_phase2 = u_phase2(2,colon())*R2D;
theta_phase4 = u_phase4(1,colon())*R2D;
phi_phase4 = u_phase4(2,colon())*R2D;
   compute_cartesian_trajectory(x,r);
   r.Save("r.dat");
   double ft2km = 0.0003048;
   r = r*ft2km;
   \verb|plot(t2,theta_phase2,problem.name+": thrust theta phase 2","time (s)", "theta (deg)", "theta"); \\
   plot(t2,phi_phase2,problem.name+": thrust phi phase 2","time (s)", "phi (deg)", "phi");
   plot(t4,theta_phase4,problem.name+": thrust theta phase 4","time (s)", "theta (deg)", "theta");
   \verb|plot(t4,phi_phase4,problem.name+": thrust phi phase 4","time (s)", "phi (deg)", "phi"); \\
   plot(t2,theta_phase2,problem.name+": thrust pitch angle phase 2","time (s)", "theta (deg)", "theta",
 "pdf", "theta2.pdf");
   plot(t2,phi_phase2,problem.name+": thrust angle phase 2","time (s)", "phi (deg)", "phi",
 "pdf", "phi2.pdf");
   "pdf", "theta4.pdf");
   plot(t4,phi_phase4,problem.name+": thrust yaw angle phase 4","time (s)", "phi (deg)", "phi",
     "pdf", "phi4.pdf");
   plot3(r(1,colon()), r(2,colon()), r(3,colon()), "Two burn transfer trajectory", "x (km)", "y (km)", "z (km)",
  NULL, NULL, "30,110");
   plot3(r(1,colon()),\ r(2,colon()),\ r(3,colon()),\ "Two\ burn\ transfer\ trajectory",\ "x\ (km)",\ "y\ (km)",\ "z\ (km)",\ "pdf",\ "trajectory.pdf",\ "30,110"); 
   plot(r(1,colon()), r(2,colon()), "Two burn trajectory - projection on the equatorial plane", "x (km)", "y (km)");
}
```

The output from \mathcal{PSOPT} is summarised in the box below. The controls during the burn periods are shown Figures 3.101 to 3.104, which show the control variables during phases 2 and 4, and Figure 3.105, which shows the trajectory in cartesian co-ordinates.

```
PSOPT results summary
______
Problem: Two burn transfer problem
CPU time (seconds): 8.818389e+00
NLP solver used: IPOPT
PSOPT release number: 4.0
Date and time of this run: Thu Feb 21 15:55:48 2019
Optimal (unscaled) cost function value: -2.367249e-01
Phase 1 endpoint cost function value: 0.000000e+00
Phase 1 integrated part of the cost: 0.000000e+00
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 2.609964e+03
Phase 1 maximum relative local error: 1.385002e-06
Phase 2 endpoint cost function value: 0.000000e+00
Phase 2 integrated part of the cost: 0.000000e+00
Phase 2 initial time: 2.609964e+03
Phase 2 final time: 2.751426e+03
Phase 2 maximum relative local error: 1.225041e-06
Phase 3 endpoint cost function value: 0.000000e+00
Phase 3 integrated part of the cost: 0.000000e+00
Phase 3 initial time: 2.751426e+03
Phase 3 final time: 2.163415e+04
Phase 3 maximum relative local error: 1.174820e-05
Phase 4 endpoint cost function value: -2.367249e-01
Phase 4 integrated part of the cost: 0.000000e+00
Phase 4 initial time: 2.163415e+04
Phase 4 final time: 2.168351e+04
Phase 4 maximum relative local error: 5.521144e-06
NLP solver reports: The problem has been solved!
```

Iter	Method	Nodes	NV	NC	$^{\mathrm{OE}}$	$^{\mathrm{CE}}$	$_{ m JE}$	$_{\mathrm{HE}}$	RHS	$\epsilon_{ ext{max}}$	CPU_a
1	TRAPZ	40	308	298	637	636	20	0	48336	4.942e-02	2.400e-01
2	TRAPZ	56	428	402	25	26	23	0	2808	4.129e-03	3.600e-01
3	H-S	76	650	532	38	39	37	0	8580	1.568e-04	1.000e + 00
4	H-S	104	888	714	46	47	41	0	14288	2.222e-05	1.590e + 00
5	H-S	133	1132	902	66	67	57	0	26197	8.212e-06	2.880e+00
CPU _b	-	-	-	-	-	-	-	-	-	=	3.786e+01
_	_	_	_	_	812	815	178	0	100209	_	4.393e+01

Key: Iter=iteration number, NV=number of variables, NC=number of constraints, OE=objective evaluations, CE = constraint evaluations, JE = Jacobian evaluations, HE = Hessian evaluations, RHS = ODE right hand side evaluations, $\epsilon_{\rm max}$ = maximum relative ODE error, CPU_a = CPU time in seconds spent by NLP algorithm, CPU_b = additional CPU time in seconds spent by PSOPT

Table 3.8: Mesh refinement statistics: Two burn transfer problem




Figure 3.101: Pitch angle during phase 2




Figure 3.102: Yaw angle during phase 2




Figure 3.103: Pitch angle during phase 4




Figure 3.104: Yaw angle during phase 4

Two burn transfer trajectory




Figure 3.105: Two burn transfer trajectory

3.40 Two link robotic arm

Consider the following optimal control problem [29]. Find t_f , and $u(t) \in [0, t_f]$ to minimize the cost functional

$$J = t_f \tag{3.165}$$

subject to the dynamic constraints

$$\dot{x}_{1} = \frac{\sin(x_{3})(\frac{9.0}{4.0}\cos(x_{3})x_{1}^{2} + 2*x_{2}^{2}) + \frac{4.0}{3.0}(u_{1} - u_{2}) - \frac{3.0}{2.0}\cos(x_{3})u_{2}}{\frac{31.0}{36.0} + \frac{9.0}{4.0\sin^{2}(x_{3})}}$$

$$\dot{x}_{2} = \frac{-(\sin(x_{3})*(\frac{7.0}{2.0}*x_{1}^{2} + \frac{9.0}{4.0}\cos(x_{3})x_{2}^{2}) - \frac{7.0}{3.0}u_{2} + \frac{3.0}{2.0}\cos(x_{3})(u_{1} - u_{2}))}{\frac{31.0}{36.0} + \frac{9.0}{4.0\sin^{2}(x_{3})}}$$

$$\dot{x}_{3} = x_{2} - x_{1}$$

$$\dot{x}_{4} = x_{1}$$
(3.166)

the boundary conditions:

$$\begin{array}{rclrcl}
x_1(0) & = & 0 & x_1(t_f) & = & 0 \\
x_2(0) & = & 0 & x_2(t_f) & = & 0 \\
x_3(0) & = & 0.5 & x_3(t_f) & = & 0.5 \\
x_4(0) & = & 0.0 & x_4(t_f) & = & 0.522
\end{array}$$
(3.167)

The control bounds:

$$-1 \le u_1(t) \le 1$$

-1 \le u_2(t) \le 1 (3.168)

The \mathcal{PSOPT} code that solves this problem is shown below.

```
return tf;
///////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
                       adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
    return 0.0;
}
void dae(adouble* derivatives, adouble* path, adouble* states,
         adouble* controls, adouble* parameters, adouble& time,
        adouble* xad, int iphase, Workspace* workspace)
   adouble xdot, vdot, vdot:
   adouble x1 = states[ CINDEX(1) ];
   adouble x2 = states[ CINDEX(2) ];
adouble x3 = states[ CINDEX(3) ];
   adouble x4 = states[ CINDEX(4) ];
   adouble u1 = controls[ CINDEX(1) ];
adouble u2 = controls[ CINDEX(2) ];
   adouble num1 = sin(x3)*((9.0/4.0)*cos(x3)*x1*x1+2*x2*x2)
                   + (4.0/3.0)*(u1-u2)-(3.0/2.0)*cos(x3)*u2;
   \begin{array}{lll} \text{adouble num2} &=& -(\sin(x3)*((7.0/2.0)*x1*x1+(9.0/4.0)*\cos(x3)*x2*x2) \\ && -(7.0/3.0)*u2+(3.0/2.0)*\cos(x3)*(u1-u2)); \end{array}
   adouble den = 31.0/36.0 + 9.0/4.0*pow(sin(x3),2);
   derivatives[ CINDEX(1) ] = num1/den;
derivatives[ CINDEX(2) ] = num2/den;
derivatives[ CINDEX(3) ] = x2 - x1;
   derivatives[ CINDEX(4) ] = x1;
void events(adouble* e, adouble* initial_states, adouble* final_states,
            adouble* parameters,adouble& t0, adouble& tf, adouble* xad,
            int iphase, Workspace* workspace)
  adouble x10 = initial_states[ CINDEX(1) ];
adouble x20 = initial_states[ CINDEX(2) ];
adouble x30 = initial_states[ CINDEX(3) ];
adouble x40 = initial_states[ CINDEX(4) ];
   adouble x1f = final_states[ CINDEX(1) ];
adouble x2f = final_states[ CINDEX(2) ];
   adouble x3f = final_states[ CINDEX(3) ];
adouble x4f = final_states[ CINDEX(4) ];
   e[ CINDEX(1) ] = x10;
   e[CINDEX(2)] = x20;
e[CINDEX(3)] = x30;
   e[ CINDEX(4) ] = x40;
e[ CINDEX(5) ] = x1f;
e[ CINDEX(6) ] = x2f;
e[ CINDEX(7) ] = x3f;
e[ CINDEX(8) ] = x4f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
  \ensuremath{//} No linkages as this is a single phase problem
```

```
int main(void)
Alg algorithm;
Sol solution;
  Prob problem;
= "Two link robotic arm";
  problem.outfilename
                           = "twolink.txt";
= 0;
  problem.nlinkages
  psopt_level1_setup(problem);
problem.phases(1).nstates
  problem.phases(1).ncontrols = 2;
  problem.phases(1).nevents = 8;
problem.phases(1).npath = 0;
   problem.phases(1).nodes
                                 = 40;
  psopt_level2_setup(problem, algorithm);
DMatrix x, u, t;
  DMatrix lambda, H;
problem.phases(1).bounds.lower.states(1) = -2.0;
  problem.phases(1).bounds.lower.states(2) = -2.0;
problem.phases(1).bounds.lower.states(3) = -2.0;
  problem.phases(1).bounds.lower.states(4) = -2.0;
  problem.phases(1).bounds.upper.states(1) = 2.0;
problem.phases(1).bounds.upper.states(2) = 2.0;
  problem.phases(1).bounds.upper.states(3) = 2.0;
  problem.phases(1).bounds.upper.states(4) = 2.0;
  problem.phases(1).bounds.lower.controls(1) = -1.0;
problem.phases(1).bounds.lower.controls(2) = -1.0;
  problem.phases(1).bounds.upper.controls(1) = 1.0;
problem.phases(1).bounds.upper.controls(2) = 1.0;
  problem.phases(1).bounds.lower.events(1) = 0.0;
  problem.phases(1).bounds.lower.events(2) = 0.0;
problem.phases(1).bounds.lower.events(3) = 0.5;
  problem.phases(1).bounds.lower.events(4) = 0.0;
problem.phases(1).bounds.lower.events(5) = 0.0;
   problem.phases(1).bounds.lower.events(6) = 0.0;
```

```
problem.phases(1).bounds.lower.events(7) = 0.5;
  problem.phases(1).bounds.lower.events(8) = 0.522;
  problem.phases(1).bounds.upper.events = problem.phases(1).bounds.lower.events;
  problem.phases(1).bounds.lower.StartTime
  problem.phases(1).bounds.upper.StartTime
                             = 0.0;
  problem.phases(1).bounds.lower.EndTime
problem.phases(1).bounds.upper.EndTime
                             = 1.0:
                             = 10.0;
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
problem.dae = &dae;
  problem.events = &events;
  problem.linkages = &linkages;
DMatrix x0(4,40);
  x0(1,colon()) = linspace(0.0,0.0, 40);
  x0(2,colon()) = linspace(0.0,0.0, 40);
x0(3,colon()) = linspace(0.5,0.5, 40);
  x0(4,colon()) = linspace(0.522,0.522, 40);
  problem.phases(1).guess.controls
problem.phases(1).guess.states
                          = zeros(1,40);
                          = x0;
  problem.phases(1).guess.time
                          = linspace(0.0, 3.0, 40);
algorithm.nlp_method
                         = "IPOPT";
  algorithm.scaling
algorithm.derivatives
                         = "automatic":
                         = "automatic";
  algorithm.nlp_iter_max algorithm.nlp_tolerance
                         = 1000:
psopt(solution, problem, algorithm);
x = solution.get_states_in_phase(1);
  x = solution.geo_seases_in_phase(1);
u = solution.get_controls_in_phase(1);
t = solution.get_time_in_phase(1);
x.Save("x.dat");
  u.Save("u.dat");
  t.Save("t.dat");
plot(t,x,problem.name + ": states", "time (s)", "states", "x1 x2 x3 x4");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.106 and 3.107, which contain the elements of the state and the control, respectively.

3.41 Two-phase path tracking robot

Consider the following two-phase optimal control problem, which consists of a robot following a specified path [38, 36]. Find $u(t) \in [0, 2]$ to minimize the cost functional

$$J = \int_0^2 [100(x_1 - x_{1,ref})^2 + 100(x_2 - x_{2,ref})^2 + 500(x_3 - x_{3,ref})^2 + 500(x_4 - x_{4,ref})^2] dt$$
(3.169)




Figure 3.106: States for two-link robotic arm problem




Figure 3.107: Controls for two link robotic arm problem

subject to the dynamic constraints

$$\begin{array}{rcl}
 \dot{x}_1 & = & x_3 \\
 \dot{x}_2 & = & x_4 \\
 \dot{x}_3 & = & u_1 \\
 \dot{x}_4 & = & u_2
 \end{array}$$
(3.170)

the boundary conditions:

$$x_1(0) = 0$$
 $x_1(2) = 0.5$
 $x_2(0) = 0$ $x_2(2) = 0.5$
 $x_3(0) = 0.5$ $x_3(2) = 0$
 $x_4(0) = 0.0$ $x_4(2) = 0.5$ (3.171)

where the reference signals are given by:

$$x_{1,ref} = \frac{t}{2} (0 \le t < 1), \frac{1}{2} (1 \le t \le 2)$$

$$x_{2,ref} = 0 (0 \le t < 1), \frac{t-1}{2} (1 \le t \le 2)$$

$$x_{3,ref} = \frac{1}{2} (0 \le t < 1), 0 (1 \le t \le 2)$$

$$x_{4,ref} = 0 (0 \le t < 1), \frac{1}{2} (1 \le t \le 2)$$

$$(3.172)$$

The \mathcal{PSOPT} code that solves this problem is shown below. The first phase covers the period $t \in [0, 1]$, while the second phase covers the period $t \in [1, 2]$.

```
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad,
                     int iphase, Workspace* workspace)
   adouble retval;
    adouble x1, x2, x3, x4;
   adouble x1ref, x2ref, x3ref, x4ref;
   double w1, w2, w3, w4;
   w1 = 100.0:
   w1 = 100.0;

w2 = 100.0;

w3 = 500.0;

w4 = 500.0;
  x1 = states[0];
  x2 = states[1];
x3 = states[2];
x4 = states[3];
  if (iphase==1) {
  x1ref = time/2;
   x2ref = 0.0;
   x3ref = 0.5;
   x4ref = 0.0;
  }
   if (iphase==2) {
   x1ref = 0.5;
   x2ref = (time-1.0)/2.0;
   x3ref = 0.0;
  x4ref = 0.5;
  \texttt{retval = w1*pow(x1-x1ref,2)+w2*pow(x2-x2ref,2)+w3*pow(x3-x3ref,2)+w4*pow(x4-x4ref,2);}
  return retval;
void dae(adouble* derivatives, adouble* path, adouble* states,
        adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
  adouble x3, x4, u1, u2;
  x3 = states[2];
x4 = states[3];
  u1 = controls[0];
u2 = controls[1];
  derivatives[0] = x3;
derivatives[1] = x4;
derivatives[2] = u1;
   derivatives[3] = u2;
}
void events(adouble* e, adouble* initial_states, adouble* final_states,
```

```
{\tt adouble*\ parameters,adouble\&\ t0,\ adouble\&\ tf,\ adouble*\ xad,} \\ {\tt int\ iphase,\ Workspace*\ workspace)}
 adouble x1i, x2i, x3i, x4i;
 adouble x1f, x2f, x3f, x4f;
 if (iphase == 1)
   x1i = initial_states[0];
   x2i = initial_states[1];
x3i = initial_states[2];
   x4i = initial_states[3];
   e[0] = x1i;
   e[1] = x2i;
e[2] = x3i;
   e[3] = x4i;
 else if (iphase == 2)
   x1f = final_states[0];
   x11 = linal_states[0];
x2f = final_states[1];
x3f = final_states[2];
   x4f = final_states[3];
   e[0] = x1f;
e[1] = x2f;
e[2] = x3f;
   e[3] = x4f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
{
  int index = 0:
  auto_link( linkages, &index, xad, 1, 2, workspace );
int main(void)
Alg algorithm;
Sol solution;
Prob problem;
problem.nphases
            = 2;
  problem.nlinkages
```

```
psopt_level1_setup(problem);
problem.phases(1).nstates
     problem.phases(1).ncontrols = 2;
     problem.phases(1).nevents = 4;
problem.phases(1).npath = 0;
     problem.phases(2).nstates
     problem.phases(2).nevents = 4;
problem.phases(2).nevents = 4;
     problem.phases(2).npath
                                             = 0:
     problem.phases(1).nodes
                                                 = 30:
     problem.phases(2).nodes
     psopt_level2_setup(problem, algorithm);
double x1i = 0.0;
double x2i = 0.0;
double x3i = 0.5;
     double x4i = 0.0;
     double x1f = 0.5;
double x2f = 0.5;
double x3f = 0.0;
double x4f = 0.5;
     // Phase 0 bounds
     problem.phases(1).bounds.lower.states(1) = -10.0;
     problem.phases(1).bounds.lower.states(2) = -10.0;
problem.phases(1).bounds.lower.states(3) = -10.0;
     problem.phases(1).bounds.lower.states(4) = -10.0;
     problem.phases(1).bounds.upper.states(1) = 10.0;
     problem.phases(1).bounds.upper.states(1) = 10.0;
problem.phases(1).bounds.upper.states(2) = 10.0;
problem.phases(1).bounds.upper.states(3) = 10.0;
problem.phases(1).bounds.upper.states(4) = 10.0;
     problem.phases(1).bounds.lower.controls(1) = -10.0;
problem.phases(1).bounds.upper.controls(1) = 10.0;
problem.phases(1).bounds.lower.controls(2) = -10.0;
problem.phases(1).bounds.upper.controls(2) = 10.0;
     problem.phases(1).bounds.lower.events(1) =
     problem.phases(1).bounds.lower.events(2) = x2i;
problem.phases(1).bounds.lower.events(3) = x3i;
     problem.phases(1).bounds.lower.events(4) = x4i;
     problem.phases(1).bounds.upper.events(1) = x1i;
problem.phases(1).bounds.upper.events(2) = x2i;
problem.phases(1).bounds.upper.events(3) = x3i;
problem.phases(1).bounds.upper.events(4) = x4i;
     problem.phases(1).bounds.lower.StartTime
problem.phases(1).bounds.upper.StartTime
     problem.phases(1).bounds.lower.EndTime
                                                                  = 1.0:
                                                                  = 1.0;
     problem.phases(1).bounds.upper.EndTime
     // Phase 1 bounds
     problem.phases(2).bounds.lower.states(1) = -10.0;
problem.phases(2).bounds.lower.states(2) = -10.0;
problem.phases(2).bounds.lower.states(3) = -10.0;
     problem.phases(2).bounds.lower.states(4) = -10.0;
     problem.phases(2).bounds.upper.states(1) = 10.0;
problem.phases(2).bounds.upper.states(2) = 10.0;
```

```
problem.phases(2).bounds.upper.states(3) = 10.0;
problem.phases(2).bounds.upper.states(4) = 10.0;
    problem.phases(2).bounds.lower.controls(1) = -10.0;
problem.phases(2).bounds.upper.controls(1) = 10.0;
problem.phases(2).bounds.lower.controls(2) = -10.0;
    problem.phases(2).bounds.upper.controls(2) = 10.0;
    problem.phases(2).bounds.lower.events(1) = x1f;
problem.phases(2).bounds.lower.events(2) = x2f;
     problem.phases(2).bounds.lower.events(3) = x3f;
    problem.phases(2).bounds.lower.events(4) = x4f;
    problem.phases(2).bounds.upper.events(1) = x1f;
    problem.phases(2).bounds.upper.events(2) = x2f;
    problem.phases(2).bounds.upper.events(3) = x3f;
problem.phases(2).bounds.upper.events(4) = x4f;
    problem.phases(2).bounds.lower.StartTime = 1.0;
problem.phases(2).bounds.upper.StartTime = 1.0;
    problem.phases(2).bounds.lower.EndTime
                                                       = 2.0:
    problem.phases(2).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
problem.dae = &dae;
problem.events = &events;
    problem.linkages = &linkages;
int iphase;
    DMatrix u0(2,30):
    DMatrix x0(4,30);
    DMatrix time_guess0 = linspace(0.0, 1.0 , 30);
DMatrix time_guess1 = linspace(1.0, 2.0 , 30);
    iphase = 1:
    u0 = zeros(2,30+1);
    x0(1,colon()) = linspace(x1i,(x1i+x1f)/2, 30);
    x0(2,colon()) = linspace(x1,(x1+x1+x1-/2, 30), x0(3,colon()) = linspace(x3i,(x3i+x3f)/2, 30); x0(4,colon()) = linspace(x4i,(x4i+x4f)/2, 30);
    problem.phases(iphase).guess.controls = u0;
    problem.phases(iphase).guess.states = x0;
problem.phases(iphase).guess.time = time_guess0;
    u0 = zeros(2,30+1);
    x0(1,colon()) = linspace((x1i+x1f)/2, x1f, 30);
x0(2,colon()) = linspace((x2i+x2f)/2, x2f, 30);
x0(3,colon()) = linspace((x3i+x3f)/2, x3f, 30);
x0(4,colon()) = linspace((x4i+x4f)/2, x4f, 30);
    problem.phases(iphase).guess.controls = u0;
    problem.phases(iphase).guess.states = x0;
problem.phases(iphase).guess.time = time_guess1;
algorithm.nlp method
                                                  = "IPOPT":
     algorithm.scaling
                                                  = "automatic";
                                                  = "automatic":
    algorithm.derivatives
```

```
= "exact";
                         = 1000;
  algorithm.nlp_iter_max
  algorithm.nlp_tolerance
                         = 1.e-6:
psopt(solution, problem, algorithm);
DMatrix xphase1 = solution.get_states_in_phase(1);
  DMatrix uphase1 = solution.get_controls_in_phase(1);
DMatrix tphase1 = solution.get_time_in_phase(1);
  DMatrix xphase2 = solution.get_states_in_phase(2);
DMatrix uphase2 = solution.get_controls_in_phase(2);
DMatrix tphase2 = solution.get_time_in_phase(2);
  DMatrix x = (xphase1 || xphase2);
DMatrix u = (uphase1 || uphase2);
DMatrix t = (tphase1 || tphase2);
x.Save("x.dat");
  u.Save("u.dat");
t.Save("t.dat");
plot(t,x,problem.name, "time (s)", "states");
  plot(t,u,problem.name, "time (s)", "control");
  plot(t,u,problem.name+": controls", "time (s)", "controls", "u1 u2",
                "pdf", "twophro_controls.pdf" );
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.108 and 3.109, which contain the elements of the state and the control, respectively.




Figure 3.108: States for two-phase path tracking robot problem

```
Date and time of this run: Thu Feb 21 17:07:41 2019

Optimal (unscaled) cost function value: 1.042568e+00
Phase 1 endpoint cost function value: 0.000000e+00
Phase 1 integrated part of the cost: 5.212840e-01
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 1.000000e+00
Phase 1 maximum relative local error: 3.443287e-04
Phase 2 endpoint cost function value: 0.000000e+00
Phase 2 integrated part of the cost: 5.212840e-01
Phase 2 initial time: 1.000000e+00
Phase 2 final time: 2.000000e+00
Phase 2 final time: 3.443298e-04
NLP solver reports: The problem has been solved!
```

3.42 Two-phase Schwartz problem

Consider the following two-phase optimal control problem [36]. Find $u(t) \in [0, 2.9]$ to minimize the cost functional

$$J = 5(x_1(t_f)^2 + x_2(t_f)^2) (3.173)$$




Figure 3.109: Control for two phase path tracking robot problem

subject to the dynamic constraints

$$\dot{x}_1 = x_2
 \dot{x}_2 = u - 0.1(1 + 2x_1^2)x_2$$
(3.174)

the boundary conditions:

$$\begin{array}{rcl}
x_1(0) & = & 1 \\
x_2(0) & = & 1
\end{array}
\tag{3.175}$$

and the constraints for t < 1:

$$1-9(x_1-1)^2 - \left(\frac{x_2-0.4}{0.3}\right)^2 \le 0$$

$$-0.8 \le x_2$$

$$-1 \le u \le 1$$
(3.176)

The \mathcal{PSOPT} code that solves this problem is shown below. The problem has been divided into two phases. The first phase covers the period $t \in [0, 1]$, while the second phase covers the period $t \in [1, 2.9]$.

```
////// Last modified:
                      09 January 2009
                                         #include "psopt.h"
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
               adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
  adouble x1f, x2f;
  // Phase 1 cost
  if ( iphase == 1)
  retval = 0.0;
  // Phase 2 cost
  if( iphase == 2 ) {
  x1f = final_states[0];
x2f = final_states[1];
  retval = 5*(x1f*x1f + x2f*x2f);
  return retval;
}
///////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls,
                adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
  return 0.0;
}
void dae(adouble* derivatives, adouble* path, adouble* states,
      adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
  adouble x1 = states[0];
adouble x2 = states[1];
  adouble u = controls[0];
  derivatives[0] = x2;
derivatives[1] = u-0.1*(1+2*x1*x1)*x2;
  if(iphase==1) {
      path[0] = 1.0 - 9.0*((x1-1.0)*(x1-1.0)) - ((x2-0.4)*(x2-0.4))/(0.3*0.3);
```

```
adouble x1i = initial_states[0];
adouble x2i = initial_states[1];
 if (iphase==1) {
  e[0] = x1i;
  e[1] = x2i;
}
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
  int index = 0;
 auto_link( linkages, &index, xad, 1, 2, workspace );
}
int main(void)
Alg algorithm;
Sol solution;
 Prob problem;
= "Two phase Schwartz problem";
  problem.outfilename
                   = "twophsc.txt";
problem.nphases = 2;
 problem.nlinkages
                   = 3;
  psopt_level1_setup(problem);
Define phase related information & do level 2 setup ////////
problem.phases(1).nstates = 2;
  problem.phases(1).ncontrols = 1;
  problem.phases(1).nevents = 2;
problem.phases(1).npath = 1;
 problem.phases(1).npath
  problem.phases(2).nstates
 problem.phases(2).ncontrols = 1;
problem.phases(2).nevents = 0;
problem.phases(2).npath = 0;
  problem.phases(1).nodes
problem.phases(2).nodes
               = 40:
```

```
psopt_level2_setup(problem, algorithm);
double x1L = -20.0;
    double x2L_phase1 = -0.8;
double x2L_phase2 = -10.0;
double uL = -1.0;
    double x1U = 10.0;
   double x2U = 10.0;
double uU = 1.0;
double hL = -100.0;
double hU = 0.0;
    problem.phases(1).bounds.lower.states(1) = x1L;
    problem.phases(1).bounds.lower.states(2) = x2L phase1;
    problem.phases(1).bounds.upper.states(1) = x1U;
problem.phases(1).bounds.upper.states(2) = x2U;
   problem.phases(1).bounds.lower.controls(1) = uL;
problem.phases(1).bounds.upper.controls(1) = uU;
    problem.phases(1).bounds.lower.events(1) = 1.0:
    problem.phases(1).bounds.lower.events(2) = 1.0;
    problem.phases(1).bounds.upper.events(1) = 1.0;
problem.phases(1).bounds.upper.events(2) = 1.0;
    problem.phases(1).bounds.lower.path(1) = hL;
problem.phases(1).bounds.upper.path(1) = hU;
    {\tt problem.phases(1).bounds.lower.StartTime}
                                                  = 0.0;
                                                 = 0.0;
    problem.phases(1).bounds.upper.StartTime
                                                  = 1.0;
= 1.0;
    problem.phases(1).bounds.lower.EndTime
    problem.phases(1).bounds.upper.EndTime
    // Phase 1 bounds
   problem.phases(2).bounds.lower.states(1) = x1L;
problem.phases(2).bounds.lower.states(2) = x2L_phase2;
    problem.phases(2).bounds.upper.states(1) = x1U;
    problem.phases(2).bounds.upper.states(2) = x2U;
    problem.phases(2).bounds.lower.controls(1) = -50.0;
    problem.phases(2).bounds.upper.controls(1) = 50.0;
   problem.phases(2).bounds.lower.StartTime = 1.0;
problem.phases(2).bounds.upper.StartTime = 1.0;
    problem.phases(2).bounds.upper.StartTime
    problem.phases(2).bounds.lower.EndTime
                                                 = 2.9;
    problem.phases(2).bounds.upper.EndTime
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
   problem.dae = &dae;
problem.events = &events;
problem.linkages = &linkages;
int iphase;
    DMatrix u0(1.40):
    DMatrix x0(2,40);
```

```
DMatrix time_guess0 = linspace(0.0, 1.0 , 40);

DMatrix time_guess1 = linspace(1.0, 2.9 , 40);
   iphase = 1;
   u0 = zeros(1.40):
   u0 = zeros(1,40);
x0(1,colon()) = linspace(1.0,1.0, 40);
x0(2,colon()) = linspace(1.0,1.0, 40);
   problem.phases(iphase).guess.controls = u0;
problem.phases(iphase).guess.states = x0;
problem.phases(iphase).guess.time = time_guess0;
   iphase = 2;
   u0 = zeros(1,40);
  x0(1,colon()) = linspace(1.0,1.0, 40);
x0(2,colon()) = linspace(1.0,1.0, 40);
  problem.phases(iphase).guess.controls = u0;
problem.phases(iphase).guess.states = x0;
problem.phases(iphase).guess.time = time_guess1;
= "IPOPT":
   algorithm.nlp method
   algorithm.scaling
                                 = "automatic";
                                 = "automatic";
   algorithm.derivatives
   algorithm.nlp_iter_max
                                = 1000;
                                 = 1.e-6;
   algorithm.nlp_tolerance
psopt(solution, problem, algorithm);
DMatrix xphase1 = solution.get_states_in_phase(1);
   DMatrix uphase1 = solution.get_controls_in_phase(1);
DMatrix tphase1 = solution.get_time_in_phase(1);
  DMatrix xphase2 = solution.get_states_in_phase(2);
DMatrix uphase2 = solution.get_controls_in_phase(2);
DMatrix tphase2 = solution.get_time_in_phase(2);
  DMatrix x = (xphase1 || xphase2);
DMatrix u = (uphase1 || uphase2);
   DMatrix t = (tphase1 || tphase2);
x.Save("x.dat");
  u.Save("u.dat");
t.Save("t.dat");
plot(t,x,problem.name, "time (s)", "states", "x1 x2");
   plot(t,u,problem.name, "time (s)", "control", "u");
   plot(t,x,problem.name, "time (s)", "states", "x1 x2",
                     "pdf", "twophsc_states.pdf");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.110 and 3.111, which contain the elements of the state and the control, respectively.

```
PSOPT results summary
===============
Problem: Two phase Schwartz problem
CPU time (seconds): 1.668786e+00
                 IPOPT
NLP solver used:
PSOPT release number: 4.0
Date and time of this run:
                           Thu Feb 21 17:25:06 2019
Optimal (unscaled) cost function value: 4.640127e-15
Phase 1 endpoint cost function value: 0.000000e+00
Phase 1 integrated part of the cost: 0.000000e+00
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 1.000000e+00
Phase 1 maximum relative local error: 5.734565e-06
Phase 2 endpoint cost function value: 4.640127e-15
Phase 2 integrated part of the cost: 0.000000e+00
Phase 2 initial time: 1.000000e+00
Phase 2 final time: 2.900000e+00
Phase 2 maximum relative local error: 9.827730e-05
NLP solver reports: The problem has been solved!
```

3.43 Vehicle launch problem

This problem consists of the launch of a space vehicle. See [33, 2] for a full description of the problem. Only a brief description is given here. The flight of the vehicle can be divided into four phases, with dry masses ejected from the vehicle at the end of phases 1, 2 and 3. The final times of phases 1, 2 and 3 are fixed, while the final time of phase 4 is free. The optimal control




Figure 3.110: States for two-phase Schwartz problem




Figure 3.111: Control for two-phase Schwartz problem

problem is to find the control, u, that minimizes the cost function

$$J = -m^{(4)}(t_f) (3.177)$$

In other words, it is desired to maximise the vehicle mass at the end of phase 4. The dynamics are given by:

$$\dot{\mathbf{r}} = \mathbf{v}$$

$$\dot{\mathbf{v}} = -\frac{\mu}{\|\mathbf{r}\|^3}\mathbf{r} + \frac{T}{m}\mathbf{u} + \frac{\mathbf{D}}{m}$$

$$\dot{m} = -\frac{T}{g_0 I_{sp}}$$
(3.178)

where $\mathbf{r}(t) = \begin{bmatrix} x(t) & y(t) & z(t) \end{bmatrix}^T$ is the position, $\mathbf{v} = \begin{bmatrix} v_x(t) & v_y(t) & v_z(t) \end{bmatrix}^T$ is the Cartesian ECI velocity, μ is the gravitational parameter, T is the vacuum thrust, m is the mass, g_0 is the acceleration due to gravity at sea level, I_{sp} is the specific impulse of the engine, $\mathbf{u} = \begin{bmatrix} u_x & u_y & u_z \end{bmatrix}^T$ is the thrust direction, and $\mathbf{D} = \begin{bmatrix} D_x & D_y & D_z \end{bmatrix}^T$ is the drag force, which is given by:

$$\mathbf{D} = -\frac{1}{2}C_D A_{ref} \rho \|\mathbf{v}_{rel}\| \mathbf{v}_{rel}$$
(3.179)

where C_D is the drag coefficient, A_{ref} is the reference area, ρ is the atmospheric density, and \mathbf{v}_{rel} is the Earth relative velocity, where \mathbf{v}_{rel} is given as

$$\mathbf{v}_{rel} = \mathbf{v} - \boldsymbol{\omega} \times \mathbf{r} \tag{3.180}$$

where ω is the angular velocity of the Earth relative to inertial space. The atmospheric density is modeled as follows

$$\rho = \rho_0 \exp[-h/h_0] \tag{3.181}$$

where ρ_0 is the atmospheric density at sea level, $h = ||\mathbf{r}|| - R_e$ is the altitude, R_e is the equatorial radius of the Earth, and h_0 is the density scale height. The numerical values for these constants can be found in the code.

The vehicle starts on the ground at rest (relative to the Earth) at time t_0 , so that the initial conditions are

$$\mathbf{r}(t_0) = \mathbf{r}_0 = \begin{bmatrix} 5605.2 & 0 & 3043.4 \end{bmatrix}^T \text{ km}$$
 $\mathbf{v}(t_0) = \mathbf{v}_0 = \begin{bmatrix} 0 & 0.4076 & 0 \end{bmatrix}^T \text{ km/s}$
 $m(t_0) = m_0 = 301454 \text{ kg}$
(3.182)

The terminal constraints define the target transfer orbit, which is defined in orbital elements as

$$a_f = 24361.14 \text{ km},$$

 $e_f = 0.7308,$
 $i_f = 28.5 \text{ deg},$ (3.183)
 $\Omega_f = 269.8 \text{ deg},$
 $\omega_f = 130.5 \text{ deg}$

There is also a path constraint associated with this problem:

$$||\mathbf{u}||^2 = 1\tag{3.184}$$

The following linkage constraints force the position and velocity to be continuous and also account for discontinuity in the mass state due to the ejections at the end of phases 1, 2 and 3:

$$\mathbf{r}^{(p)}(t_f) - \mathbf{r}^{(p+1)}(t_0) = \mathbf{0}, \mathbf{v}^{(p)}(t_f) - \mathbf{v}^{(p+1)}(t_0) = \mathbf{0}, \qquad (p = 1, \dots, 3) m^{(p)}(t_f) - m_{dry}^{(p)} - m^{(p+1)}(t_0) = 0$$
(3.185)

where the superscript (p) represents the phase number.

The \mathcal{PSOPT} code that solves this problem is shown below.

```
#include "psopt.h"
void oe2rv(DMatrix& oe, double mu, DMatrix* ri, DMatrix* vi);
void rv2oe(adouble* rv, adouble* vv, double mu, adouble* oe);
//////// Declare an auxiliary structure to hold local constants //////
struct Constants {
 DMatrix* omega_matrix;
 double cd;
 double sa;
 double rho0:
 double H;
 double Re:
 double g0;
 double thrust_srb;
double thrust_first;
 double thrust second:
 double ISP_srb;
 double ISP_first;
 double ISP_second;
typedef struct Constants Constants_;
```

```
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
                       adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
    adouble retval;
    adouble mass_tf = final_states[6];
   if (iphase < 4)
  retval = 0.0;</pre>
    if (iphase== 4)
      retval = -mass tf:
   return retval;
////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
    return 0.0;
}
void dae(adouble* derivatives, adouble* path, adouble* states,
         adouble* controls, adouble* parameters, adouble& time, adouble* xad, int iphase, Workspace* workspace)
{
    {\tt Constants\_\&~CONSTANTS~=~*(~(Constants\_~*)~workspace->problem->user\_data~);}
    adouble* x = states;
    adouble* u = controls;
    adouble r[3]; r[0]=x[0]; r[1]=x[1]; r[2]=x[2];
    adouble v[3]; v[0]=x[3]; v[1]=x[4]; v[2]=x[5];
    adouble m = x[6];
    double T_first, T_second, T_srb, T_tot, m1dot, m2dot, mdot;
    adouble rad = sqrt( dot( r, r, 3) );
    DMatrix& omega_matrix = *CONSTANTS.omega_matrix;
    adouble vrel[3];
    for (j=0;j<3;j++)

vrel[j] = v[j] - omega_matrix(j+1,1)*r[0] - omega_matrix(j+1,2)*r[1] - omega_matrix(j+1,3)*r[2];
    adouble speedrel = sqrt( dot(vrel,vrel,3) );
adouble altitude = rad-CONSTANTS.Re;
   adouble rho = CONSTANTS.rho0*exp(-altitude/CONSTANTS.H);
double a1 = CONSTANTS.rho0*CONSTANTS.sa*CONSTANTS.cd;
adouble a2 = a1*exp(-altitude/CONSTANTS.H);
adouble bc = (rho/(2*m))*CONSTANTS.sa*CONSTANTS.cd;
    adouble bcspeed = bc*speedrel;
    adouble Drag[3];
    for(j=0;j<3;j++) \ Drag[j] = - (vrel[j]*bcspeed);
    adouble muoverradcubed = (CONSTANTS.mu)/(pow(rad,3));
```

```
if (iphase==1) {
  T_srb = 6*CONSTANTS.thrust_srb;
      T_first = CONSTANTS.thrust_first;
T_tot = T_srb+T_first;
      midot = -T_srb/(CONSTANTS.g0*CONSTANTS.ISP_srb);
m2dot = -T_first/(CONSTANTS.g0*CONSTANTS.ISP_first);
      mdot = m1dot+m2dot:
    else if (iphase==2) {
      T_srb = 3*CONSTANTS.thrust_srb;
T_first = CONSTANTS.thrust_first;
      T_tot = T_srb+T_first;
      m1dot = -T_srb/(CONSTANTS.g0*CONSTANTS.ISP_srb);
m2dot = -T_first/(CONSTANTS.g0*CONSTANTS.ISP_first);
      mdot = m1dot+m2dot;
    else if (iphase==3) {
      T_first = CONSTANTS.thrust_first;
T_tot = T_first;
      mdot = -T_first/(CONSTANTS.go*CONSTANTS.ISP_first);
   eise if (iphase==4) {
   T_second = CONSTANTS.thrust_second;
   T_tot = T_second;
   mdot = -T_second/(CONSTANTS.go*CONSTANTS.ISP_second);
}
    else if (iphase==4) {
   adouble Toverm = T_tot/m;
    adouble thrust[3];
   for(j=0;j<3;j++) thrust[j] = Toverm*u[j];</pre>
    adouble rdot[3];
    for(j=0;j<3;j++) rdot[j] = v[j];</pre>
   adouble vdot[3];
for(j=0;j<3;j++) vdot[j] = thrust[j]+Drag[j]+grav[j];</pre>
    derivatives[0] = rdot[0];
    derivatives[1] = rdot[1];
   derivatives[1] = rdot[1];
derivatives[2] = rdot[2];
derivatives[3] = vdot[0];
derivatives[4] = vdot[1];
derivatives[5] = vdot[2];
   derivatives[6] = mdot;
   path[0] = dot( controls, controls, 3);
}
void events(adouble* e, adouble* initial_states, adouble* final_states,
              adouble* parameters, adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
{
   Constants_& CONSTANTS = *( (Constants_ *) workspace->problem->user_data );
    adouble rv[3]; rv[0]=final_states[0]; rv[1]=final_states[1]; rv[2]=final_states[2];
    adouble vv[3]; vv[0]=final_states[3]; vv[1]=final_states[4]; vv[2]=final_states[5];
    adouble oe[6];
    int j;
   if(iphase==1) {
    // These events are related to the initial state conditions in phase 1
        for(j=0;j<7;j++) \ e[j] = initial\_states[j];
    if (iphase==4) {
      // These events are related to the final states in phase 4
```

```
rv2oe( rv, vv, CONSTANTS.mu, oe );
for(j=0;j<5;j++) e[j]=oe[j];</pre>
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace) \{
 int index=0:
 auto_link(linkages, &index, xad, 1, 2, workspace );
linkages[index-2]-= 6*m_dry_srb;
 auto_link(linkages, &index, xad, 2, 3, workspace );
linkages(index-2]-= 3*m_dry_srb;
auto_link(linkages, &index, xad, 3, 4, workspace );
linkages(index-2]-= m_dry_first;
}
int main(void)
Alg algorithm;
Sol solution;
 Prob problem;
= "Multiphase vehicle launch";
  problem.name
  problem.outfilename
Constants CONSTANTS:
 problem.user_data = (void*) &CONSTANTS;
problem.nphases
 problem.nlinkages
                  = 24;
 psopt_level1_setup(problem);
problem.phases(1).nstates = 7;
```

```
problem.phases(1).ncontrols = 3;
     problem.phases(1).nevents = 7;
problem.phases(1).npath = 1;
     problem.phases(2).nstates = 7;
     problem.phases(2).ncontrols = 3;
    problem.phases(2).nevents = 0;
problem.phases(2).npath = 1;
     problem.phases(3).nstates = 7;
     problem.phases(3).ncontrols = 3;
    problem.phases(3).nevents = 0;
problem.phases(3).npath = 1;
     problem.phases(4).nstates
    problem.phases(4).ncontrols = 3;
problem.phases(4).nevents = 5;
problem.phases(4).npath = 1;
    problem.phases(1).nodes = "[5, 15]";
problem.phases(2).nodes = "[5, 15]";
problem.phases(3).nodes = "[5, 15]";
problem.phases(4).nodes = "[5, 15]";
     psopt_level2_setup(problem, algorithm);
DMatrix x, u, t, H;
double omega
                                 = 7.29211585e-5; // Earth rotation rate (rad/s)
     DMatrix omega_matrix(3,3);
    CONSTANTS.omega_matrix = &omega_matrix; // Rotation rate matrix (rad/s)
     CONSTANTS.sa = 4*pi; // Surface area (m^2)
CONSTANTS.rho0 = 1.225; // sea level gravity (kg/m^3)
CONSTANTS.H = 7200.0; // Density scale height (m)
CONSTANTS.Re = 6378145.0; // Radius of earth (m)
CONSTANTS.g0 = 9.80665; // sea level gravity (m/s^2)
     double lat0 = 28.5*pi/180.0:
                                                        // Geocentric Latitude of Cape Canaveral
     double x0 = CONSTANTS.Re*cos(lat0);
double z0 = CONSTANTS.Re*sin(lat0);
                                                   // x component of initial position
// z component of initial position
    double y0 = 0;
DMatrix r0(3,1, x0, y0, z0);
     DMatrix v0 = omega_matrix*r0;
    double bt_srb = 75.2;
double bt_first = 261.0;
     double bt_second = 700.0;
     double t0 = 0:
    double t0 = 0,
double t1 = 75.2;
double t2 = 150.4;
double t3 = 261.0;
     double t4 = 961.0;
     double m_tot_srb
                           = 19290.0;
= 17010.0;
     double m_prop_srb
     double m_dry_srb = m_tot_srb-m_prop_srb;
double m_tot_first = 104380.0;
    double m_prop_first = 95550.0;
double m_dry_first = m_tot_fir
double m_tot_second = 19300.0;
                                m_tot_first-m_prop_first;
```

```
double m_prop_second = 16820.0;
double m_dry_second = m_tot_second-m_prop_second;
double m_payload = 4164.0;
double thrust_srb = 62850.0;
double thrust_first = 1083100.0;
      double thrust_second = 110094.0;
     double af = 24361140.0;
double ef = 0.7308;
      double incf = 28.5*pi/180.0;
double Omf = 269.8*pi/180.0;
      double omf = 130.5*pi/180.0;
     double nuguess = 0;
double cosincf = cos(incf);
     double cosInf = cos(Inf);
double cosOmf = cos(Omf);
double cosomf = cos(omf);
DMatrix oe(6,1, af, ef, incf, Omf, omf, nuguess);
      DMatrix rout(3,1);
      DMatrix vout(3,1);
      oe2rv(oe,CONSTANTS.mu, &rout, &vout);
     rout.Transpose();
      vout.Transpose();
      double m10 = m_payload+m_tot_second+m_tot_first+9*m_tot_srb;
     double m1f = m10-(6*mdot_srb+mdot_first)*t1;
double m20 = m1f-6*m_dry_srb;
      double m2f = m20-(3*mdot_srb+mdot_first)*(t2-t1);
double m30 = m2f-3*m_dry_srb;
     double m3f = m30-mdot_first*(t3-t2);
double m40 = m3f-m_dry_first;
     double m4f = m_payload;
     CONSTANTS.thrust_srb = thrust_sro;

CONSTANTS.thrust_first = thrust_first;

CONSTANTS.thrust_second = thrust_second;

CONSTANTS.ISP_srb = ISP_srb;

CONSTANTS.ISP_first = ISP_first;

CONSTANTS.ISP_second = ISP_second;
      CONSTANTS.thrust srb
                                      = thrust srb:
     double rmin = -2*CONSTANTS.Re;
     double rmax = -rmin;
double vmin = -10000.0;
double vmax = -vmin;
int iphase;
     problem.bounds.lower.times = "[0, 75.2, 150.4, 261.0, 261.0]";
problem.bounds.upper.times = "[0, 75.2, 150.4 261.0, 961.0]";
     // Phase 1 bounds
     iphase = 1:
      problem.phases(iphase).bounds.lower.states(1) = rmin;
     problem.phases(iphase).bounds.upper.states(1) = rmax;
problem.phases(iphase).bounds.lower.states(2) = rmin;
      problem.phases(iphase).bounds.upper.states(2) = rmax;
problem.phases(iphase).bounds.lower.states(3) = rmin;
      problem.phases(iphase).bounds.upper.states(3) = rmax;
problem.phases(iphase).bounds.lower.states(4) = vmin;
      problem.phases(iphase).bounds.upper.states(4) = vmax;
problem.phases(iphase).bounds.lower.states(5) = vmin;
      problem.phases(iphase).bounds.upper.states(5) = vmax;
```

```
problem.phases(iphase).bounds.lower.states(6) = vmin;
problem.phases(iphase).bounds.upper.states(6) = vmax;
problem.phases(iphase).bounds.lower.states(7) = m1f;
problem.phases(iphase).bounds.upper.states(7) = m10;
problem.phases(iphase).bounds.lower.controls(1) = -1.0;
problem.phases(iphase).bounds.upper.controls(1) = 1.0;
problem.phases(iphase).bounds.lower.controls(2) = -1.0;
problem.phases(iphase).bounds.upper.controls(2) = 1.0;
problem.phases(iphase).bounds.lower.controls(3) = -1.0;
problem.phases(iphase).bounds.upper.controls(3) = 1.0;
problem.phases(iphase).bounds.lower.path(1)
                                                            = 1.0;
problem.phases(iphase).bounds.upper.path(1)
// The following bounds fix the initial state conditions in phase 0.
problem.phases(iphase).bounds.lower.events(1) = r0(1);
problem.phases(iphase).bounds.upper.events(1) = r0(1);
problem.phases(iphase).bounds.lower.events(2) = r0(2);
problem.phases(iphase).bounds.lower.events(2) = r0(2);
problem.phases(iphase).bounds.lower.events(3) = r0(3);
problem.phases(iphase).bounds.upper.events(3) = r0(3);
problem.phases(iphase).bounds.lower.events(4) = v0(1);
problem.phases(iphase).bounds.upper.events(4) = v0(1);
problem.phases(iphase).bounds.lower.events(5) = v0(2);
problem.phases(iphase).bounds.upper.events(5) = v0(2);
problem.phases(iphase).bounds.lower.events(6) = v0(3)
problem.phases(iphase).bounds.upper.events(6) = v0(3);
problem.phases(iphase).bounds.lower.events(7) = m10;
problem.phases(iphase).bounds.upper.events(7) = m10;
// Phase 2 bounds
iphase = 2;
problem.phases(iphase).bounds.lower.states(1) = rmin;
problem.phases(iphase).bounds.upper.states(1) = rmax;
problem.phases(iphase).bounds.lower.states(2) = rmin;
problem.phases(iphase).bounds.upper.states(2) =
                                                            rmax;
problem.phases(iphase).bounds.lower.states(3) = rmin;
problem.phases(iphase).bounds.upper.states(3)
                                                            rmax;
problem.phases(iphase).bounds.lower.states(4) = vmin;
problem.phases(iphase).bounds.upper.states(4) =
                                                            vmax;
problem.phases(iphase).bounds.lower.states(5) = vmin;
problem.phases(iphase).bounds.upper.states(5) = vmax;
problem.phases(iphase).bounds.lower.states(6) = vmin;
problem.phases(iphase).bounds.upper.states(6) = vmax;
problem.phases(iphase).bounds.lower.states(7) = m2f;
problem.phases(iphase).bounds.upper.states(7) = m20;
problem.phases(iphase).bounds.lower.controls(1) = -1.0;
problem.phases(iphase).bounds.upper.controls(1) = 1.0;
problem.phases(iphase).bounds.lower.controls(2) = -1.0;
problem.phases(iphase).bounds.lower.controls(2) = 1.0;
problem.phases(iphase).bounds.lower.controls(3) = -1.0;
problem.phases(iphase).bounds.upper.controls(3) = 1.0;
problem.phases(iphase).bounds.lower.path(1)
                                                            = 1.0:
problem.phases(iphase).bounds.upper.path(1)
// Phase 3 bounds
iphase = 3;
problem.phases(iphase).bounds.lower.states(1) = rmin;
problem.phases(iphase).bounds.upper.states(1) = rmax;
problem.phases(iphase).bounds.lower.states(2) = rmin;
problem.phases(iphase).bounds.upper.states(2) = rmax;
problem.phases(iphase).bounds.lower.states(3) = rmin;
problem.phases(iphase).bounds.upper.states(3) = rmax;
problem.phases(iphase).bounds.lower.states(4) = vmin;
problem.phases(iphase).bounds.upper.states(4) = vmax;
problem.phases(iphase).bounds.lower.states(5) = vmin;
problem.phases(iphase).bounds.upper.states(5) = vmax;
```

```
problem.phases(iphase).bounds.lower.states(6) = vmin;
     problem.phases(iphase).bounds.upper.states(6) = vmax;
problem.phases(iphase).bounds.lower.states(7) = m3f;
     problem.phases(iphase).bounds.upper.states(7) = m30;
     problem.phases(iphase).bounds.lower.controls(1) = -1.0;
     problem.phases(iphase).bounds.upper.controls(1) = 1.0;
problem.phases(iphase).bounds.lower.controls(2) = -1.0;
     problem.phases(iphase).bounds.upper.controls(2) = 1.0;
problem.phases(iphase).bounds.lower.controls(3) = -1.0;
     problem.phases(iphase).bounds.upper.controls(3) = 1.0;
     problem.phases(iphase).bounds.lower.path(1)
     problem.phases(iphase).bounds.upper.path(1)
     // Phase 4 bounds
     problem.phases(iphase).bounds.lower.states(1) = rmin:
     problem.phases(iphase).bounds.upper.states(1) = rmax;
     problem.phases(iphase).bounds.lower.states(2) = rmin:
     problem.phases(iphase).bounds.upper.states(2) = rmax;
     problem.phases(iphase).bounds.lower.states(3) = rmin;
     problem.phases(iphase).bounds.upper.states(3) = rmax;
     problem.phases(iphase).bounds.lower.states(4) =
                                                                vmin;
     problem.phases(iphase).bounds.upper.states(4) = vmax;
     problem.phases(iphase).bounds.lower.states(5) = vmin:
     problem.phases(iphase).bounds.upper.states(5) = vmax;
     problem.phases(iphase).bounds.lower.states(6) = vmin;
     problem.phases(iphase).bounds.upper.states(6) = vmax;
problem.phases(iphase).bounds.lower.states(7) = m4f;
     problem.phases(iphase).bounds.upper.states(7) = m40;
     problem.phases(iphase).bounds.lower.controls(1) = -1.0;
     problem.phases(iphase).bounds.upper.controls(1) = 1.0;
     problem.phases(iphase).bounds.lower.controls(2) = -1.0;
     problem.phases(iphase).bounds.upper.controls(2) = 1.0;
     problem.phases(iphase).bounds.lower.controls(3) = -1.0;
     problem.phases(iphase).bounds.upper.controls(3) = 1.0;
     problem.phases(iphase).bounds.lower.path(1)
                                                                 = 1.0;
     problem.phases(iphase).bounds.upper.path(1)
     problem.phases(iphase).bounds.lower.events(1)
                                                                   = af:
                                                                   = ef;
     problem.phases(iphase).bounds.lower.events(2)
     problem.phases(iphase).bounds.lower.events(3)
                                                                   = incf:
     problem.phases(iphase).bounds.lower.events(4)
                                                                   = Omf;
     problem.phases(iphase).bounds.lower.events(5) problem.phases(iphase).bounds.upper.events(1)
                                                                   = omf:
     problem.phases(iphase).bounds.upper.events(2)
                                                                   = ef:
     problem.phases(iphase).bounds.upper.events(3)
                                                                   = incf;
= Omf;
     problem.phases(iphase).bounds.upper.events(4)
     problem.phases(iphase).bounds.upper.events(5)
problem.phases(iphase).guess.states = zeros(7,5);
     problem.phases(iphase).guess.states(1, colon()) = linspace( r0(1), r0(1), 5);
problem.phases(iphase).guess.states(2, colon()) = linspace( r0(2), r0(2), 5);
     problem.phases(iphase).guess.states(2, colon()) = linspace( r0(3), r0(3), 5); problem.phases(iphase).guess.states(3, colon()) = linspace( r0(3), r0(3), 5); problem.phases(iphase).guess.states(4, colon()) = linspace( v0(1), v0(1), 5); problem.phases(iphase).guess.states(5, colon()) = linspace( v0(2), v0(2), 5); problem.phases(iphase).guess.states(6, colon()) = linspace( v0(3), v0(3), 5); problem.phases(iphase).guess.states(7, colon()) = linspace( m10 , m1f , 5);
     problem.phases(iphase).guess.controls = zeros(3,5);
     problem.phases(iphase).guess.controls(1,colon()) = ones( 1, 5);
problem.phases(iphase).guess.controls(2,colon()) = zeros(1, 5);
     problem.phases(iphase).guess.controls(3,colon()) = zeros(1, 5);
     problem.phases(iphase).guess.time = linspace(t0,t1, 5);
```

```
iphase = 2;
      problem.phases(iphase).guess.states = zeros(7,5);
      problem.phases(iphase).guess.states(1, colon()) = linspace( r0(1), r0(1), 5);
problem.phases(iphase).guess.states(2, colon()) = linspace( r0(2), r0(2), 5);
      problem.phases(iphase).guess.states(2, colon()) = linspace( r0(2), r0(2), 5); problem.phases(iphase).guess.states(4, colon()) = linspace( v0(1), v0(1), 5); problem.phases(iphase).guess.states(5, colon()) = linspace( v0(2), v0(2), 5); problem.phases(iphase).guess.states(5, colon()) = linspace( v0(2), v0(2), 5); problem.phases(iphase).guess.states(6, colon()) = linspace( v0(3), v0(3), 5); problem.phases(iphase).guess.states(7, colon()) = linspace( m20 , m2f , 5);
      problem.phases(iphase).guess.controls = zeros(3,5);
      problem.phases(iphase).guess.controls(1,colon()) = ones( 1, 5);
      problem.phases(iphase).guess.controls(2,colon()) = zeros(1, 5);
      problem.phases(iphase).guess.controls(3,colon()) = zeros(1, 5);
      problem.phases(iphase).guess.time = linspace(t1,t2, 5);
      problem.phases(iphase).guess.states = zeros(7,5);
     problem.phases(iphase).guess.states(1, colon()) = linspace( rout(1), rout(1), 5);
problem.phases(iphase).guess.states(2, colon()) = linspace( rout(2), rout(2), 5);
problem.phases(iphase).guess.states(3, colon()) = linspace( rout(3), rout(3), 5);
problem.phases(iphase).guess.states(4, colon()) = linspace( vout(1), vout(1), 5);
      problem.phases(iphase).guess.states(5, colon()) = linspace( vout(2), vout(2), 5); problem.phases(iphase).guess.states(6, colon()) = linspace( vout(3), vout(3), 5); problem.phases(iphase).guess.states(7, colon()) = linspace( m30 , m3f , 5);
      problem.phases(iphase).guess.controls = zeros(3,5);
      problem.phases(iphase).guess.controls(1,colon()) = zeros( 1, 5);
problem.phases(iphase).guess.controls(2,colon()) = zeros( 1, 5);
      problem.phases(iphase).guess.controls(3,colon()) = ones( 1, 5);
      problem.phases(iphase).guess.time = linspace(t2,t3, 5);
      iphase = 4;
      problem.phases(iphase).guess.states = zeros(7,5);
      problem.phases(iphase).guess.states(1, colon()) = linspace( rout(1), rout(1), 5);
     problem.phases(iphase).guess.states(3, colon()) = linspace( rout(2), rout(2), 5); problem.phases(iphase).guess.states(3, colon()) = linspace( rout(3), rout(3), 5); problem.phases(iphase).guess.states(4, colon()) = linspace( vout(1), vout(1), 5); problem.phases(iphase).guess.states(5, colon()) = linspace( vout(2), vout(2), 5); problem.phases(iphase).guess.states(6, colon()) = linspace( vout(3), vout(3), 5); problem.phases(iphase).guess.states(7, colon()) = linspace( m40 , m4f , 5);
      problem.phases(iphase).guess.controls = zeros(3,5);
      problem.phases(iphase).guess.controls(1,colon()) = zeros( 1, 5);
      problem.phases(iphase).guess.controls(2,colon()) = zeros(1, 5);
      problem.phases(iphase).guess.controls(3,colon()) = ones(1,5);
      problem.phases(iphase).guess.time = linspace(t3,t4, 5);
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
      problem.dae = &dae;
problem.events = &events;
      problem.linkages = &linkages;
algorithm.nlp_method
      algorithm.scaling
algorithm.derivatives
                                                                   = "automatic":
                                                                   = "automatic";
```

```
algorithm.nlp_iter_max
                            = 500;
                                 = "automatic";
   algorithm.mesh_refinement
  algorithm.collocation_method = "trapezoidal";
algorithm.ode_tolerance = 1.e-5;
psopt(solution, problem, algorithm);
u = (solution.get_controls_in_phase(1) || solution.get_controls_in_phase(2) || solution.get_controls_in_phase(3) || solution.get_controls_in_phase(4) );
  t = (solution.get_time_in_phase(1) || solution.get_time_in_phase(2) || solution.get_time_in_phase(3) || solution.get_time_in_phase(4) );
x.Save("x.dat");
  u.Save("u.dat");
  t.Save("t.dat");
DMatrix r = x(colon(1,3),colon());
  DMatrix v = x(colon(4,6),colon());
  DMatrix altitude = Sqrt(sum(elemProduct(r,r)))/1000.0;
  DMatrix speed = Sqrt(sum(elemProduct(v,v)));
  plot(t,altitude,problem.name, "time (s)", "position (km)");
  plot(t,speed,problem.name, "time (s)", "speed (m/s)");
  plot(t.u.problem.name."time (s)", "u"):
   plot(t,altitude,problem.name, "time (s)", "position (km)", "alt", \\ "pdf", "launch_position.pdf"); 
  \label{eq:plot_speed_problem.name, "time (s)", "speed (m/s)", "speed", \\ "pdf", "launch_speed.pdf");
  }
void rv2oe(adouble* rv, adouble* vv, double mu, adouble* oe) {
    int j;
    adouble K[3]; K[0] = 0.0; K[1]=0.0; K[2]=1.0;
    adouble hv[3];
cross(rv,vv, hv);
    adouble nv[3];
    cross(K, hv, nv);
    adouble n = sqrt( dot(nv,nv,3));
```

```
adouble h2 = dot(hv,hv,3);
         adouble v2 = dot(vv, vv, 3);
         adouble r
                                = sqrt(dot(rv,rv,3));
         = h2/mu;
adouble e = sqrt(dot(ev,ev,3)); // eccentricity
adouble a = p/(1-e*e); // semimajor axis adouble i = acos(hv[2]/sqrt(h2)); // inclination
#define USE_SMOOTH_HEAVISIDE
          double a_eps = 0.1;
#ifndef USE SMOOTH HEAVISIDE
  adouble Om = acos(nv[0]/n); // RAAN
if ( nv[1] < -DMatrix::GetEPS() ){ // fix quadrant
Om = 2*pi-Om;
#endif
\verb|#ifdef USE_SMOOTH_HEAVISIDE|\\
          #endif
#ifndef USE_SMOOTH_HEAVISIDE
  adouble om = acos(dot(nv,ev,3)/n/e); // arg of periapsis if ( ev[2] < 0 ) { // fix quadrant om = 2*pi-om;
}
#endif
#ifdef USE_SMOOTH_HEAVISIDE
       adouble om = smooth_heaviside( (ev[2]), a_eps )*acos(dot(nv,ev,3)/n/e) 
+smooth_heaviside( -(ev[2]), a_eps )*(2*pi-acos(dot(nv,ev,3)/n/e));
#endif
#ifndef USE_SMOOTH_HEAVISIDE
  adouble nu = acos(dot(ev,rv,3)/e/r); // true anomaly
  if ( dot(rv,vv,3) < 0 ) { // fix quadrant
    nu = 2*pi-nu;</pre>
#ifdef USE_SMOOTH_HEAVISIDE
         adouble nu = smooth_heaviside( dot(rv,vv,3), a_eps )*acos(dot(ev,rv,3)/e/r) +smooth_heaviside( -dot(rv,vv,3), a_eps )*(2*pi-acos(dot(ev,rv,3)/e/r));
#endif
          oe[0] = a;
          oe[0] = a;
oe[1] = e;
oe[2] = i;
oe[3] = 0m;
oe[4] = om;
oe[5] = nu;
           return;
}
void oe2rv(DMatrix& oe, double mu, DMatrix* ri, DMatrix* vi)
double a=oe(1), e=oe(2), i=oe(3), Om=oe(4), om=oe(5), nu=oe(6);
double a = a*(1-e*e);
double p = a*(1-e*e);
double r = p/(1+e*cos(nu));
DMatrix rv(3,1);
    rv(1) = r*cos(nu);
    rv(2) = r*sin(nu);
    rv(3) = 0.0;
DMatrix vv(3,1);
           vv(1) = -sin(nu);
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.112, 3.113 and 3.114, which contain the trajectories of the altitude, speed and the elements of the control vector, respectively.

```
PSOPT results summary
Problem: Multiphase vehicle launch
CPU time (seconds): 3.356515e+00
NLP solver used: IPOPT
PSOPT release number: 4.0
Date and time of this run: Thu Feb 21 16:00:31 2019
Optimal (unscaled) cost function value: -7.529661e+03
Phase 1 endpoint cost function value: 0.000000e+00
Phase 1 integrated part of the cost: 0.000000e+00
Phase 1 initial time: 0.000000e+00
Phase 1 final time: 7.520000e+01
Phase 1 maximum relative local error: 1.173524e-06
Phase 2 endpoint cost function value: 0.000000e+00
Phase 2 integrated part of the cost:
                                     0.00000e+00
Phase 2 initial time: 7.520000e+01
Phase 2 final time: 1.504000e+02
Phase 2 maximum relative local error: 1.301765e-06
Phase 3 endpoint cost function value: 0.000000e+00
Phase 3 integrated part of the cost:
                                     0.000000e+00
Phase 3 initial time: 1.504000e+02
Phase 3 final time: 2.610000e+02
```




Figure 3.112: Altitude for the vehicle launch problem

```
Phase 3 maximum relative local error: 3.952037e-07
Phase 4 endpoint cost function value: -7.529661e+03
Phase 4 integrated part of the cost: 0.000000e+00
Phase 4 initial time: 2.610000e+02
Phase 4 final time: 9.241413e+02
Phase 4 maximum relative local error: 1.631374e-06
NLP solver reports: The problem has been solved!
```

3.44 Zero propellant maneouvre of the International Space Station

This problem illustrates the use of \mathcal{PSOPT} for solving an optimal control problem associated with the design of a zero propellant maneouvre for the international space station by means of control moment gyroscopes (CMGs). The example is based on the results presented in the thesis by Bhatt [5] and also reported by Bedrossian and co-workers [1]. The original 90 and 180 degree maneouvres were computed using DIDO, and they were actually implemented on the International Space Station on 5 November 2006 and 2 January 2007, respectively, resulting in savings for NASA of around US\$1.5m in propellant costs. The dynamic model employed here does not account for atmospheric drag as the atmosphere model used in the orig-




Figure 3.113: Speed for the vehicle launch problem




Figure 3.114: Controls for the vehicle launch problem

inal study is not available. Otherwise, the equations and parameters are the same as those reported by Bhatt in his thesis. The effects of atmospheric drag are, however, small, and the results obtained are comparable with those given in Bhatt's thesis. The implemented case corresponds with a maneovure lasting 7200 seconds and using 3 CMG's.

The problem is formulated as follows. Find $\mathbf{q_c}(t) = [q_{c,1}(t) \, q_{c,2}(t) \, q_{c,3}(t) \, q_{c,4}]^T$, $t \in [t_0, t_f]$ and the scalar parameter γ to minimise,

$$J = 0.1\gamma + \int_{t_0}^{t_f} ||u(t)||^2 dt$$
 (3.186)

subject to the dynamical equations:

$$\dot{\mathbf{q}}(t) = \frac{1}{2}\mathbf{T}(\mathbf{q})(\omega(t) - \omega_o(\mathbf{q}))$$

$$\dot{\omega}(t) = \mathbf{J}^{-1}\left(\tau_d(\mathbf{q}) - \omega(t) \times (\mathbf{J}\omega(t)) - \mathbf{u}(t)\right)$$

$$\dot{\mathbf{h}}(t) = \mathbf{u}(t) - \omega(t) \times \mathbf{h}(t)$$
(3.187)

the path constraints:

$$\begin{aligned} ||\mathbf{q}(t)||_{2}^{2} &= 1\\ ||\mathbf{q}_{c}(t)||_{2}^{2} &= 1\\ ||\mathbf{h}(t)||_{2}^{2} &\leq \gamma\\ ||\dot{\mathbf{h}}(t)||_{2}^{2} &= \dot{h}_{\max}^{2} \end{aligned}$$
(3.188)

the parameter bounds

$$0 \le \gamma \le h_{\text{max}}^2 \tag{3.189}$$

and the boundary conditions:

$$\mathbf{q}(t_0) = \bar{\mathbf{q}}_0 \quad \omega(t_0) = \omega_o(\bar{\mathbf{q}}_0) \quad \mathbf{h}(t_0) = \bar{\mathbf{h}}_0 \mathbf{q}(t_f) = \bar{\mathbf{q}}_f \quad \omega(t_f) = \omega_o(\bar{\mathbf{q}}_f) \quad \mathbf{h}(t_f) = \bar{\mathbf{h}}_f$$
(3.190)

where **J** is a 3×3 inertia matrix, $\mathbf{q} = [q_1, q_2, q_3, q_4]^T$ is the quarternion vector, ω is the spacecraft angular rate relative to an inertial reference frame and expressed in the body frame, **h** is the momentum, $\mathbf{T}(\mathbf{q})$ is given by:

$$\mathbf{T}(\mathbf{q}) = \begin{bmatrix} -q_2 & -q_3 & -q_4 \\ q_1 & -q_4 & q_3 \\ q_4 & q_1 & -q_2 \\ -q_3 & q_2 & q_1 \end{bmatrix}$$
(3.191)

u is the control force, which is given by:

$$\mathbf{u}(t) = \mathbf{J} \left(K_P \tilde{\varepsilon}(q, q_c) + K_D \tilde{\omega}(\omega, q_c) \right)$$
(3.192)

where

$$\tilde{\varepsilon}(\mathbf{q}, \mathbf{q}_c) = 2\mathbf{T}(\mathbf{q}_c)^T \mathbf{q}$$

$$\tilde{\omega}(\omega, \omega_c) = \omega - \omega_c$$
(3.193)

 ω_o is given by:

$$\omega_o(\mathbf{q}) = n\mathbf{C}_2(\mathbf{q}) \tag{3.194}$$

where n is the orbital rotation rate, \mathbf{C}_j is the j column of the rotation matrix:

$$\mathbf{C}(\mathbf{q}) = \begin{bmatrix} 1 - 2(q_3^2 + q_4^2) & 2(q_2q_3 + q_1q_4) & 2(q_2q_4 - q_1q_3) \\ 2(q_2q_3 - q_1q_4) & 1 - 2(q_2^2 + q_4^2) & 2(q_3q_4 + q_1q_2) \\ 2(q_2q_4 + q_1q_3) & 2(q_3q_4 - q_1q_2) & 1 - 2(q_2^2 + q_3^2) \end{bmatrix}$$
(3.195)

 τ_d is the disturbance torque, which in this case only incorporates the gravity gradient torque τ_{gg} (the disturbance torque also incorporates the atmospheric drag torque in the original study):

$$\tau_d = \tau_{gg} = 3n^2 \mathbf{C}_3(\mathbf{q}) \times (\mathbf{J}\mathbf{C}_3(\mathbf{q})) \tag{3.196}$$

The constant parameter values used were: $n=1.1461\times 10^{-3}$ rad/s, $h_{\rm max}=3\times 3600.0$ ft-lbf-sec, $\dot{h}_{\rm max}=200.0$ ft-lbf, $t_0=0$ s, $t_f=7200$ s, and

$$\mathbf{J} = \begin{bmatrix} 18836544.0 & 3666370.0 & 2965301.0 \\ 3666370.0 & 27984088.0 & -1129004.0 \\ 2965301.0 & -1129004.0 & 39442649.0 \end{bmatrix} \text{ slug - ft}^2$$
 (3.197)

The PSOPT code that solves this problem is shown below.

```
void Tfun( adouble T[][3], adouble *q)
adouble q1 = q[CINDEX(1)];
adouble q2 = q[CINDEX(2)];
adouble q3 = q[CINDEX(3)];
adouble q4 = q[CINDEX(4)];
 T[\texttt{CINDEX}(1)] [\texttt{CINDEX}(1)] = -q2 \; ; \; T[\texttt{CINDEX}(1)] [\texttt{CINDEX}(2)] = -q3 ; \; T[\texttt{CINDEX}(1)] [\texttt{CINDEX}(3)] = -q4 ; \; T[\texttt{CINDEX}(1)] [\texttt{CINDEX}(1)] [\texttt{CINDEX}(1)] [\texttt{CINDEX}(1)] 
 \texttt{T[CINDEX(2)][CINDEX(1)] = q1 ; T[CINDEX(2)][CINDEX(2)] = -q4; T[CINDEX(2)][CINDEX(3)] = q3; } 
 \texttt{T[CINDEX(3)][CINDEX(1)] = } \quad \texttt{q4} \; ; \; \texttt{T[CINDEX(3)][CINDEX(2)] = } \quad \texttt{q1}; \; \texttt{T[CINDEX(3)][CINDEX(3)] = } -\texttt{q2}; 
 \texttt{T[CINDEX(4)][CINDEX(1)] = -q3;} \quad \texttt{T[CINDEX(4)][CINDEX(2)] = } \quad \texttt{q2;} \quad \texttt{T[CINDEX(4)][CINDEX(3)] = } \quad \texttt{q1;} 
}
void compute_omega0(adouble* omega0, adouble* q)
// This function computes the angular speed in the rotating LVLH reference frame
int i;
double n = CONSTANTS.n;
adouble C2[3];
            adouble q1 = q[CINDEX(1)];
adouble q2 = q[CINDEX(2)];
adouble q3 = q[CINDEX(3)];
adouble q4 = q[CINDEX(4)];
 \begin{array}{l} \texttt{C2[ CINDEX(1) ] = 2*(q2*q3 + q1*q4);} \\ \texttt{C2[ CINDEX(2) ] = 1.0-2.0*(q2*q2+q4*q4);} \\ \texttt{C2[ CINDEX(3) ] = 2*(q3*q4-q1*q2);} \\ \end{array} 
for (i=0;i<3;i++) omega0[i] = -n*C2[i];
\verb|void compute_control_torque(adouble* u, adouble* q, adouble* qc, adouble* omega |)|\\
^{\prime\prime} // This function computes the control torque ^{\prime\prime}
double Kp = CONSTANTS.Kp; // Proportional gain
double Kd = CONSTANTS.Kd; // Derivative gain
double n = CONSTANTS.n; // Orbital rotation rate [rad/s]
int i, j;
DMatrix& J = CONSTANTS.J;
adouble T[4][3];
Tfun( T, q );
adouble Tc[4][3];
Tfun( Tc, qc);
adouble epsilon_tilde[3];
pepsilon_tilde[i] = 0.0;
for(j=0;j<4;j++) {
    epsilon_tilde[i] += 2*Tc[j][i]*q[j];
adouble omega_c[3];
compute_omega0( omega_c, qc );
adouble omega_tilde[3];
for(i=0;i<3;i++) {
  omega_tilde[i] = omega[i]-omega_c[i];
}</pre>
adouble uaux[3];
```

```
for(i=0;i<3;i++) {
uaux[i]= Kp*epsilon_tilde[i]+Kd*omega_tilde[i];
product_ad( J, uaux, 3, u );
void quarternion2Euler( DMatrix& phi, DMatrix& theta, DMatrix& psi, DMatrix& q)
^{\prime\prime} // This function finds the Euler angles given the quarternion vector
long N = q.GetNoCols();
DMatrix q0 = q(1,colon());

DMatrix q1 = q(2,colon());

DMatrix q2 = q(3,colon());

DMatrix q3 = q(4,colon());
theta.Resize(1,N);
psi.Resize(1,N);
}
void compute_aerodynamic_torque(adouble* tau_aero, adouble& time )
\{ // This function approximates the aerodynamic torque by using the model and
// Inter Inter the Applications and the Applications of the Model and Applications (// A. Chun Lee (2003) "Robust Momentum Manager Controller for Space Station Applications".
// Master of Arts Thesis, Rice University.
//
double alpha1[3] = {1.0, 4.0, 1.0};
    double alpha2[3] = {1.0, 2.0, 1.0};
    double alpha3[3] = {0.5, 0.5, 0.5};
adouble t = time;
double phi1 = 0.0;
double phi2 = 0.0;
double n = CONSTANTS.n;
  for(int i=0;i<3;i++) {
// Aerodynamic torque in [lb-ft]
tau_aero[i] = alpha1[i] + alpha2[i]*sin( n*t + phi1 ) + alpha3[i]*sin( 2*n*t + phi2);
adouble endpoint_cost(adouble* initial_states, adouble* final_states,
                      adouble* parameters,adouble& t0, adouble& tf, adouble* xad, int iphase, Workspace* workspace)
ſ
double end_point_weight = 0.1;
       adouble gamma = parameters[ CINDEX(1) ];
return (end_point_weight*gamma);
////////// Define the integrand (Lagrange) cost function /////
adouble integrand_cost(adouble* states, adouble* controls, adouble* parameters,
```

```
adouble% time, adouble* xad, int iphase, Workspace* workspace)
double running_cost_weight = 1.0;
adouble q[4]; // quarternion vector adouble u[3]; // control torque
q[CINDEX(1)] = states[ CINDEX(1) ];
q[CINDEX(2)] = states[ CINDEX(2) ];
q[CINDEX(3)] = states[ CINDEX(3) ];
q[CINDEX(4)] = states[ CINDEX(4) ];
adouble omega[3]; // angular rate vector
omega[CINDEX(1)] = states[ CINDEX(5) ];
omega[CINDEX(2)] = states[ CINDEX(6) ];
omega[CINDEX(3)] = states[ CINDEX(7) ];
adouble qc[4]; // control vector
qc[CINDEX(1)] = controls[ CINDEX(1) ];
qc[CINDEX(2)] = controls[ CINDEX(2) ];
qc[CINDEX(3)] = controls[ CINDEX(3) ];
qc[CINDEX(4)] = controls[ CINDEX(4) ];
compute_control_torque(u,q,qc,omega);
{\tt return \; running\_cost\_weight*dot(u,u,3);}
adouble* xad, int iphase, Workspace* workspace)
{
int i,j;
double n = CONSTANTS.n; // Orbital rotation rate [rad/s]
adouble q[4]; // quarternion vector
q[CINDEX(1)] = states[ CINDEX(1) ];
q[CINDEX(2)] = states[ CINDEX(2) ];
q[CINDEX(3)] = states[ CINDEX(3) ];
q[CINDEX(4)] = states[ CINDEX(4) ];
adouble omega[3]; // angular rate vector
omega[CINDEX(1)] = states[ CINDEX(5) ];
omega[CINDEX(2)] = states[ CINDEX(6) ];
omega[CINDEX(3)] = states[ CINDEX(7) ];
adouble h[3]; // momentum vector
h[CINDEX(1)] = states[ CINDEX(8) ];
h[CINDEX(2)] = states[ CINDEX(9) ];
h[CINDEX(3)] = states[ CINDEX(10) ];
adouble qc[4]; // control vector
qc[CINDEX(1)] = controls[ CINDEX(1) ];
qc[CINDEX(2)] = controls[ CINDEX(2) ];
qc[CINDEX(3)] = controls[ CINDEX(3) ];
qc[CINDEX(4)] = controls[ CINDEX(4) ];
adouble C2[3], C3[3];
adouble u[3];
adouble gamma;
gamma = parameters[ CINDEX(1) ];
// Inertia matrix in slug-ft^2
```

```
DMatrix& J = CONSTANTS.J;
DMatrix Jinv; Jinv = inv(J);
adouble q1 = q[CINDEX(1)];
adouble q2 = q[CINDEX(2)];
adouble q3 = q[CINDEX(3)];
adouble q4 = q[CINDEX(4)];
adouble T[4][3];
Tfun( T, q );
adouble qdot[4];
adouble omega0[3];
compute_omega0( omega0, q);
// Quarternion attitude kinematics
for(j=0;j<4;j++) {
qdot[j]=0;
for(i=0;i<3;i++) {
   qdot[j] += 0.5*T[j][i]*(omega[i]-omega0[i]);
}
}
adouble Jomega[3];
product_ad( J, omega, 3, Jomega );
adouble omegaCrossJomega[3];
cross(omega, Jomega, omegaCrossJomega);
adouble F[3];
// Compute the torque disturbances:
adouble tau_grav[3], tau_aero[3];
adouble v1[3];
for(i=0;i<3;i++) {
  v1[i] = 3*pow(n,2)*C3[i];
}</pre>
adouble JC3[3];
product_ad(J, C3, 3, JC3);
//gravity gradient torque
cross( v1, JC3, tau_grav );
//Aerodynamic torque
compute_aerodynamic_torque(tau_aero, time );
 for (i=0; i<3; i++) \ \{ \\ // \ Uncomment \ this \ section \ to \ ignore \ the \ aerodynamic \ disturbance \ torque \\ tau_aero[i] = 0.0; \\ 
adouble tau_d[3];
for (i=0;i<3;i++) {
    tau_d[i] = tau_grav[i] + tau_aero[i];
```

```
compute_control_torque(u, q, qc, omega );
for (i=0;i<3;i++) {
   F[i]
               = tau_d[i] - omegaCrossJomega[i] - u[i];
adouble omega_dot[3];
// Rotational dynamics
product_ad( Jinv, F, 3, omega_dot );
adouble OmegaCrossH[3];
cross( omega, h , OmegaCrossH );
adouble hdot[3];
//Momemtum derivative
caru, 1<3; i++) {
  hdot[i] = u[i] - OmegaCrossH[i];
}</pre>
derivatives[CINDEX(1)] =
                                               qdot[ CINDEX(1) ];
derivatives[CINDEX(2)] =
derivatives[CINDEX(3)] =
                                              qdot[ CINDEX(2) ];
qdot[ CINDEX(3) ];
                                              qdot[CINDEX(4)];
qdot[CINDEX(4)];
omega_dot[CINDEX(1)];
derivatives[CINDEX(4)] =
derivatives[CINDEX(5)] =
derivatives[CINDEX(6)] =
derivatives[CINDEX(7)] =
                                              omega_dot[ CINDEX(2) ];
omega_dot[ CINDEX(3) ];
derivatives[CINDEX(8)] =
derivatives[CINDEX(9)] =
                                              hdot[CINDEX(1)];
hdot[CINDEX(2)];
derivatives[CINDEX(10)] =
                                              hdot[CINDEX(3)];
path[ CINDEX(1) ] =  dot( q, q, 4);
path[ CINDEX(2) ] =  dot( qc, qc, 4);
path[ CINDEX(3) ] =  dot( h, h, 3 ) - gamma; // <= 0
path[ CINDEX(4) ] =  dot( hdot, hdot, 3); // <= hdotmax^2,</pre>
7-
void events(adouble* e. adouble* initial states, adouble* final states.
                  adouble* e, adouble* initial_states, adouble* final_states, adouble* parameters, adouble to, adouble tf, adouble* xad, int iphase, Workspace* workspace)
{
adouble g1 i
                              = initial states[CINDEX(1)]:
adouble q2_i
adouble q3_i
                              = initial_states[CINDEX(2)];
= initial_states[CINDEX(3)];
adouble q4_i
adouble omega1_i
                              = initial_states[CINDEX(4)];
= initial_states[CINDEX(5)];
adouble omega2_i
                              = initial_states[CINDEX(6)];
= initial_states[CINDEX(7)];
adouble omega3 i
                            = initial_states[CINDEX(7)];
= initial_states[CINDEX(8)];
= initial_states[CINDEX(10)];
adouble h1_i
adouble h2_i
adouble h3_i
                              = final_states[CINDEX(1)];
= final_states[CINDEX(2)];
adouble q1_f
adouble q2_f
adouble q3_f
adouble q4_f
                              = final_states[CINDEX(3)];
= final_states[CINDEX(4)];
adouble omega1_f
adouble omega2_f
                              = final_states[CINDEX(5)];
= final_states[CINDEX(6)];
adouble omega3_f
adouble h1_f
                              = final states[CINDEX(7)]:
                              = final_states[CINDEX(8)];
= final_states[CINDEX(9)];
adouble h2 f
```

```
adouble h3 f
                          = final_states[CINDEX(10)];
// Initial conditions
e[ CINDEX(1) ] = q1_i;
e[ CINDEX(2) ] = q2_i;
e[ CINDEX(3) ] = q3_i;
e[ CINDEX(4) ] = q4_i;
e[ CINDEX(5) ] = omega1_i;
e[ CINDEX(6) ] = omega2_i;
e[ CINDEX(6) ] = omega2_1;
e[ CINDEX(7) ] = omega3_i;
e[ CINDEX(8) ] = h1_i;
e[ CINDEX(9) ] = h2_i;
e[ CINDEX(10)] = h3_i;
// Final conditions
e[ CINDEX(11) ] = q1_f;
e[ CINDEX(12) ] = q2_f;
e[ CINDEX(13) ] = q3_f;
e[ CINDEX(14) ] = q4_f;
e[ CINDEX(15) ] = omega1_f;
e[ CINDEX(15) ] = omega2_f;
e[ CINDEX(15) ] = omega3_f;
e[ CINDEX(15) ] = h1_f;
e[ CINDEX(18) ] = h1_f;
e[ CINDEX(19) ] = h2_f;
e[ CINDEX(20) ] = h3_f;
}
void linkages( adouble* linkages, adouble* xad, Workspace* workspace)
     // Single phase
int main(void)
Alg algorithm;
Sol solution;
Prob problem;
    CONSTANTS.Kp = 0.000128; // Proportional gain CONSTANTS.Kd = 0.015846; // Derivative gain
    double hmax; // maximum momentum magnitude in [ft-lbf-sec]
    if (CASE==1) {
CONSTANTS.n = 1.1461E-3; // Orbital rotation rate [rad/s] hmax = 4*3600.0; // 4 CMG's
    else if (CASE==2) {
CONSTANTS.n = 1.1475E-3;
hmax = 3*3600.0; // 3 CMG's
    CONSTANTS.hmax = hmax;
    DMatrix& J = CONSTANTS.J;
    J.Resize(3.3):
    // Inertia matrix in slug-ft^2
```

```
if (CASE=1) {
   J(1,1) = 17834580.0;   J(1,2)= 2787992.0;   J(1,3)= 2873636.0;
   J(2,1) = 2787992.0;   J(2,2)= 2773815.0;  J(2,3)= -863810.0;
   J(3,1) = 28736361.0;   J(3,2)= -863810.0;  J(3,3)= 38030467.0;
else if (CASE==2) {
   J(1,1) = 18836544.0 ; J(1,2)= 3666370.0; J(1,3)= 2965301.0;
   J(2,1) = 3666370.0 ; J(2,2)= 27984088.0; J(2,3)= -1129004.0;
   J(3,1) = 2965301.0 ; J(3,2)= -1129004.0; J(3,3)= 39442649.0;
= "Zero Propellant Maneouvre of the ISS";
     problem.name
    problem.outfilename
                                                = "zpm.txt";
problem.nphases
     problem.nlinkages
    psopt_level1_setup(problem);
problem.phases(1).nstates = 10;
problem.phases(1).ncontrols = 4;
    problem.phases(1).nevents
problem.phases(1).npath
                                                = 20;
                                       = 4;
     problem.phases(1).nodes
                                                         = "[20, 30, 40, 50, 60]";
                                                         = 1;
    problem.phases(1).nparameters
    psopt_level2_setup(problem, algorithm);
// Control bounds
     problem.phases(1).bounds.lower.controls(1) = -1.0:
    problem.phases(1).bounds.lower.controls(1) = -1.0;
problem.phases(1).bounds.lower.controls(2) = -1.0;
problem.phases(1).bounds.lower.controls(3) = -1.0;
     problem.phases(1).bounds.lower.controls(4) = -1.0;
    problem.phases(1).bounds.upper.controls(1) = 1.0;
problem.phases(1).bounds.upper.controls(2) = 1.0;
problem.phases(1).bounds.upper.controls(3) = 1.0;
     problem.phases(1).bounds.upper.controls(4) = 1.0;
     problem.phases(1).bounds.lower.states(1) = -1.0;
problem.phases(1).bounds.lower.states(2) = -0.2;
     problem.phases(1).bounds.lower.states(3) = -0.2;
problem.phases(1).bounds.lower.states(4) = -1.0;
     problem.phases(1).bounds.lower.states(5) = -1.E-2;
problem.phases(1).bounds.lower.states(6) = -1.E-2;
     problem.phases(1).bounds.lower.states(7) = -1.E-2;
problem.phases(1).bounds.lower.states(8) = -8000.0;
problem.phases(1).bounds.lower.states(9) = -8000.0;
     problem.phases(1).bounds.lower.states(10) = -8000.0;
     problem.phases(1).bounds.upper.states(1) = 1.0;
     problem.phases(1).bounds.upper.states(2) = 0.2;
problem.phases(1).bounds.upper.states(3) = 0.2;
     problem.phases(1).bounds.upper.states(4) = 1.0;
problem.phases(1).bounds.upper.states(5) = 1.E-2;
```

```
problem.phases(1).bounds.upper.states(6) = 1.E-2;
            problem.phases(1).bounds.upper.states(7) = 1.E-2;
problem.phases(1).bounds.upper.states(8) = 8000.0;
problem.phases(1).bounds.upper.states(9) = 8000.0;
            problem.phases(1).bounds.upper.states(10)= 8000.0;
         // Parameter bound
           problem.phases(1).bounds.lower.parameters(1) = 0.0;
problem.phases(1).bounds.upper.parameters(1) = hmax*hmax;
            // Event bounds
          {\tt adouble \ q\_ad[4], \ omega\_ad[3];}
         // Initial conditions
          // Initial conditions
if (CASE==1) {
   q_i(1) = 0.98966;
   q_i(2) = 0.02690;
   q_i(3) = -0.08246;
   q_i(4) = 0.11425;
                     q_ad[ CINDEX(1) ]=q_i(1);
q_ad[ CINDEX(2) ]=q_i(2);
q_ad[ CINDEX(3) ]=q_i(3);
q_ad[ CINDEX(4) ]=q_i(4);
compute_omegaO( omega_ad, q_ad);
omega_i(1) = omega_ad[ CINDEX(1) ].value();
omega_i(2) = omega_ad[ CINDEX(2) ].value();
omega_i(3) = omega_ad[ CINDEX(3) ].value();
            omega_i(1) = -2.5410E-4;
omega_i(2) = -1.1145E-3;
omega_i(3) = 8.2609E-5;
             h_i(1) = -496.0;
h_i(2) = -175.0;
h_i(3) = -3892.0;
else if (CASE==2) {
q_i(1) = 0.98996;
q_i(2) = 0.02650;
q_i(3) = -0.07891;
q_i(4) = 0.11422;
q_ad[ CINDEX(1) ]=q_i(1);
                    q_ad( CINDEX(1) ]=q_1(1);
q_ad( CINDEX(2) ]=q_i(2);
q_ad( CINDEX(3) ]=q_i(3);
q_ad( CINDEX(4) ]=q_i(4);
compute_omega0( omega_ad, q_ad);
omega_i(1) = omega_ad( CINDEX(1) ].value();
omega_i(2) = omega_ad( CINDEX(2) ].value();
omega_i(3) = omega_ad( CINDEX(3) ].value();
   // omega_i(1) = -2.5470E-4;
// omega_i(2) = -1.1159E-3;
// omega_i(3) = 8.0882E-5;
             h_i(1) = 1000.0;
h_i(2) = -500.0;
h_i(3) = -4200.0;
          // Final conditions
q_f(1) = 0.70531;
q_f(2) = -0.06201;
q_f(3) = -0.03518;
q_f(4) = -0.70531;
          q_ad[ CINDEX(1) ]=q_f(1);
q_ad[ CINDEX(2) ]=q_f(2);
q_ad[ CINDEX(3) ]=q_f(3);
q_ad[ CINDEX(4) ]=q_f(4);
           q_ad_CINDEX(4) j=q_1(4);
compute_omega(0 omega_ad, q_ad);
omega_f(1) = omega_ad[ CINDEX(1) ].value();
omega_f(2) = omega_ad[ CINDEX(2) ].value();
omega_f(3) = omega_ad[ CINDEX(3) ].value();
```

```
omega_f(1) = 1.1353E-3;
omega_f(2) = 3.0062E-6;
omega_f(3) = -1.5713E-4;
      h_f(1) = -9.0;
h_f(2) = -3557.0;
h_f(3) = -135.0;
       double DQ = 0.0001;
double DWF = 0.0;
       double DHF = 0.0:
        problem.phases(1).bounds.lower.events(1) = q_i(1)-DQ;
       problem.phases(1).bounds.lower.events(1) - q_{\perp}(1)^{-}\nu q_{\tau}
problem.phases(1).bounds.lower.events(2) = q_{\perp}(2)^{-}\nu q_{\tau}
problem.phases(1).bounds.lower.events(3) = q_{\perp}(3)^{-}\nu q_{\tau}
       problem.phases(1).bounds.lower.events(4) = q_i(4)-DQ;
        problem.phases(1).bounds.lower.events(5) = omega_i(1);
       problem.phases(1).bounds.lower.events(6) = omega_i(2);
       problem.phases(1).bounds.lower.events(7) = omega_i(3);
problem.phases(1).bounds.lower.events(8) = h_i(1);
problem.phases(1).bounds.lower.events(9) = h_i(2);
       problem.phases(1).bounds.lower.events(10) = h_i(3)
       problem.phases(1).bounds.lower.events(11) = q_f(1)-DQ;
problem.phases(1).bounds.lower.events(12) = q_f(2)-DQ;
problem.phases(1).bounds.lower.events(13) = q_f(3)-DQ;
       problem.phases (1).bounds.lower.events (13) = q_f(3)-DQ;
problem.phases (1).bounds.lower.events (14) = q_f(4)-DQ;
problem.phases (1).bounds.lower.events (15) = omega_f(1)-DWF;
problem.phases (1).bounds.lower.events (16) = omega_f(2)-DWF;
problem.phases (1).bounds.lower.events (17) = omega_f(3)-DWF;
       problem.phases(1).bounds.lower.events(18) = h_f(1)-DHF;
problem.phases(1).bounds.lower.events(19) = h_f(2)-DHF;
       problem.phases(1).bounds.lower.events(20) = h_f(3)-DHF;
       problem.phases(1).bounds.upper.events(1) = q_i(1)+DQ;
       problem.phases(1).bounds.upper.events(2) = q_i(2)+DQ;
problem.phases(1).bounds.upper.events(3) = q_i(3)+DQ;
        problem.phases(1).bounds.upper.events(4) = q_i(4)+DQ;
       problem.phases(1).bounds.upper.events(5) = omega_i(1);
       problem.phases(1).bounds.upper.events(6) = omega_i(2);
problem.phases(1).bounds.upper.events(7) = omega_i(3);
       problem.phases(1).bounds.upper.events(8) = h_i(1);
problem.phases(1).bounds.upper.events(9) = h_i(2);
        problem.phases(1).bounds.upper.events(10) = h_i(3);
       problem.phases(1).bounds.upper.events(10) = h_i(3);
problem.phases(1).bounds.upper.events(11) = q_f(1)+DQ;
problem.phases(1).bounds.upper.events(12) = q_f(2)+DQ;
problem.phases(1).bounds.upper.events(13) = q_f(3)+DQ;
problem.phases(1).bounds.upper.events(14) = q_f(4)+DQ;
problem.phases(1).bounds.upper.events(15) = omega_f(1)+DWF;
       problem.phases(1).bounds.upper.events(16) = omega_1(2)+DWF;
problem.phases(1).bounds.upper.events(16) = omega_1(3)+DWF;
problem.phases(1).bounds.upper.events(18) = h_f(1)+DHF;
problem.phases(1).bounds.upper.events(19) = h_f(2)+DHF;
problem.phases(1).bounds.upper.events(20) = h_f(3)+DHF;
       // Path bounds
       double hdotmax = 200.0: // [ft-lbf]
       double EQ_TOL = 0.0002;
       problem.phases(1).bounds.lower.path(1) = 1.0-EQ TOL:
       problem.phases(1).bounds.upper.path(1) = 1.0+EQ_TOL;
       problem.phases(1).bounds.lower.path(2) = 1.0-EQ_TOL;
problem.phases(1).bounds.upper.path(2) = 1.0+EQ_TOL;
        problem.phases(1).bounds.lower.path(3) = -hmax*hmax;
       problem.phases(1).bounds.upper.path(3) = 0.0;
       problem.phases(1).bounds.lower.path(4) = 0.0;
problem.phases(1).bounds.upper.path(4) = hdotmax*hdotmax;
       double TFINAL;
        if (CASE==1) {
TFINAL = 6000.0:
```

```
else {
TFINAL = 7200.0;
    problem.phases(1).bounds.lower.StartTime
                                                 = 0.0;
    problem.phases(1).bounds.upper.StartTime
   problem.phases(1).bounds.lower.EndTime
problem.phases(1).bounds.upper.EndTime
                                                 = TFINAL:
problem.integrand_cost = &integrand_cost;
problem.endpoint_cost = &endpoint_cost;
   DMatrix time_guess = linspace(0.0, TFINAL, 50 );
DMatrix state_guess = zeros(10,50);
DMatrix control_guess = zeros(4,50);
   DMatrix parameter_guess = hmax*hmax*ones(1,1);
   control_guess(1, colon() ) = linspace( q_i(1), q_i(1), 50 );
   control_guess(2, colon()) = linspace( q_i(2), q_i(2), 50 );

control_guess(3, colon()) = linspace( q_i(3), q_i(3), 50 );

control_guess(4, colon()) = linspace( q_i(4), q_i(4), 50 );
  state_guess(1, colon() ) = linspace( q_i(1), q_i(1), 50);
state_guess(2, colon() ) = linspace( q_i(2), q_i(2), 50);
state_guess(3, colon() ) = linspace( q_i(3), q_i(3), 50);
state_guess(4, colon() ) = linspace( q_i(4), q_i(4), 50);
   state_guess(8, colon() ) = linspace( h_i(1), h_f(1), 50);
state_guess(9, colon() ) = linspace( h_i(2), h_f(2), 50);
state_guess(10, colon()) = linspace( h_i(3), h_f(3), 50);
  problem.phases(1).guess.controls = control_guess;
problem.phases(1).guess.states = state_guess;
problem.phases(1).guess.time = time_guess;
   problem.phases(1).guess.parameters=parameter_guess;
algorithm.nlp_iter_max algorithm.nlp_tolerance
                                          = 1000;
                                          = 1.e-5;
= "IPOPT";
    algorithm.nlp_method
                                           = "automatic";
    algorithm.scaling
    algorithm.derivatives
                                           = "automatic";
                                           = "jacobian-based";
    algorithm.defect_scaling
    algorithm.jac_sparsity_ratio
                                          = 0.104;
psopt(solution, problem, algorithm);
```

```
/////// Extract relevant variables from solution structure
DMatrix states, controls, t;
   states = solution.get_states_in_phase(1);
controls = solution.get_controls_in_phase(1);
t = solution.get_time_in_phase(1);
states.Save("states.dat");
controls.Save("controls.dat");
t.Save("t.dat");
   DMatrix omega, h, q, phi, theta, psi, qc, euler_angles;
   q = states( colon(1,4), colon() );
omega = states( colon(5,7), colon() );
h = states( colon(8,10),colon() );
   qc = controls;
   quarternion2Euler(phi, theta, psi, q);
   euler_angles = phi && theta && psi;
   adouble qc_ad[4], u_ad[3];
   DMatrix u(3,length(t));
   DMatrix hnorm(1,length(t));
   DMatrix hi;
DMatrix hm = hmax*ones(1,length(t));
   int i,j;
   for (i=1; i<= length(t); i++ ) {
for(j=1; j<=3; j++) {
  omega_ad[j-1] = omega(j,i);</pre>
for(j=1;j<=4;j++) {
  q_ad[j-1] = q(j,i);
qc_ad[j-1] = qc(j,i);
}
\label{lem:compute_control_torque} \mbox{\tt compute\_control\_torque(u\_ad, q\_ad, qc\_ad, omega\_ad);}
for(j=1;j<=3;j++) {
  u(j,i) = u_ad[j-1].value();
      hi = h(colon(),i);
hnorm(1.i) = enorm(hi):
   omega = omega*(180.0/pi)*1000: // convert to mdeg/s
   phi = phi*180.0/pi; theta=theta*180.0/pi; psi=psi*180.0/pi;
   u.Save("u.dat");
   euler_angles.Save("euler_angles.dat");
plot(t,q,problem.name+" quarternion elements: q", "time (s)", "q", "q");
   plot(t,qc,problem.name+" Control variables: qc", "time (s)", "qc", "qc");
   plot(t,phi,problem.name+" Euler angles: phi",
                                              "time (s)", "angles (deg)", "phi");
```

```
plot(t,theta,problem.name+" Euler angles: theta", "time (s)", "angles (deg)", "theta");
                  plot(t,psi,problem.name+" Euler angle: psi",
                                                                                                                                                                                                                                                 "time (s)", "psi (deg)", "psi");
                  plot(t,omega(1,colon()),problem.name+": omega 1","time (s)", "omega1", "omega1");
                  plot(t,omega(2,colon()),problem.name+": omega 2","time (s)", "omega2", "omega2");
                  \verb|plot(t,omega(3,colon()),problem.name+": omega 3","time (s)", "omega3", "omega3"); \\
                  plot(t,h(1,colon()),problem.name+": momentum 1","time (s)", "h1", "h1");
                  \verb|plot(t,h(2,colon()),problem.name+": momentum 2","time (s)", "h2", "h2");|\\
                  plot(t,h(3,colon()),problem.name+": momentum 3","time (s)", "h3", "h3");
                  \verb|plot(t,u(1,colon()),problem.name+": control torque 1","time (s)", "u1", "u1");|\\
                 plot(t,u(2,colon()),problem.name+": control torque 2","time (s)", "u2", "u2");
                  plot(t,u(3,colon()),problem.name+": control torque 3","time (s)", "u3", "u3"):
                  plot(t,hnorm,t,hm,problem.name+": momentum norm", "time (s)", "h", "h hmax");
                plot(t,theta,problem.name+" Euler angles: theta", "time (s)", "angles (deg)", "theta",
                                  "pdf", "zpm_theta.pdf");
                plot(t,psi,problem.name+" Euler angle: psi",
    "pdf", "zpm_psi.pdf");
                                                                                                                                                                                                                                             "time (s)", "psi (deg)", "psi",
                 plot(t,omega(1,colon()),problem.name+": omega 1","time (s)", "omega1", "omega1",
                                  "pdf", "zpm_omega1.pdf");
                 \verb|plot(t,omega(2,colon()),problem.name+": omega 2","time (s)", "omega2", "
                                 "pdf", "zpm_omega2.pdf");
                 plot(t,omega(3,colon()),problem.name+": omega 3","time (s)", "omega3", "omega3",
    "pdf", "zpm_omega3.pdf");
                  plot(t,h(1,colon()),problem.name+": momentum 1","time (s)", "h1", "h1", "pdf", "zpm_h1.pdf"); \\
                 plot(t,h(2,colon()),problem.name+": momentum 2","time (s)", "h2", "h2",
                             "pdf", "zpm_h2.pdf");
                 \verb|plot(t,h(3,colon()),problem.name+": momentum 3","time (s)", "h3", "h
                              "pdf", "zpm_h3.pdf");
                 plot(t,u(1,colon()),problem.name+": control torque 1","time (s)", "u1", "u1",
                              "pdf", "zpm_u1.pdf");
                 \verb|plot(t,u(2,colon()),problem.name+": control torque 2","time (s)", "u2", "u
                              "pdf", "zpm_u2.pdf");
                 \label{plot} $$ plot(t,u(3,colon()),problem.name+": control torque 3","time (s)", "u3", "u3", "pdf", "zpm_u3.pdf"); $$ $$ (s) $$ (s)
                 plot(t,hnorm,t,hm,problem.name+": momentum norm", "time (s)", "h (ft-lbf-sec)", "h hmax",
                            "pdf", "zpm_hnorm.pdf");
                plot(t,u,problem.name+": control torques","time (s)", "u (ft-lbf)", "u1 u2 u3",
    "pdf", "zpm_controls.pdf");
```

The output from \mathcal{PSOPT} is summarised in the box below and shown in Figures 3.115 to 3.127..




Figure 3.115: Euler angle ϕ (roll)

PSOPT results summary

Problem: Zero Propellant Maneouvre of the ISS

CPU time (seconds): 5.996709e+01

NLP solver used: IPOPT PSOPT release number: 4.0

Date and time of this run: Thu Feb 21 16:03:58 2019

Optimal (unscaled) cost function value: 6.680109e+06 Phase 1 endpoint cost function value: 5.238287e+06 Phase 1 integrated part of the cost: 1.441822e+06

Phase 1 initial time: 0.000000e+00 Phase 1 final time: 7.200000e+03

Phase 1 maximum relative local error: 1.008458e-03 NLP solver reports: The problem has been solved!




Figure 3.116: Euler angle θ (pitch)




Figure 3.117: Euler angle ψ (yaw)




Figure 3.118: Angular speed ω_1 (roll)




Figure 3.119: Angular speed ω_2 (pitch)




Figure 3.120: Angular speed ω_3 (yaw)




Figure 3.121: Momentum h_1 (roll)




Figure 3.122: Momentum h_2 (pitch)




Figure 3.123: Momentum h_3 (yaw)




Figure 3.124: Control torque u_1 (roll)




Figure 3.125: Control torque u_2 (pitch)




Figure 3.126: Control torque u_3 (yaw)




Figure 3.127: Momentum norm $||\mathbf{h}(t)||$

Acknowledgements

The author is grateful to Dr. Martin Otter from the Institute for Robotics and System Dynamics, DLR, Germany, for kindly allowing the publication of a translated version of the DLR model 2 of the Manutec R3 robot (original Fortran subroutine R3M2SI) with the distribution of \mathcal{PSOPT} .

The author is also grateful to Naz Bedrossian from the Draper Laboratory (USA) for facilitating the thesis of S. Bhatt, where the dynamic model of the International Space Station is described.

References

- [1] N.S. Bedrossian, S. Bhatt, W. Kang, and I.M. Ross. Zero Propellant Maneuver Guidance. *IEEE Control Systems Magazine*, 29:53–73, 2009.
- [2] D. A. Benson. A Gauss Pseudospectral Transcription for Optimal Control. PhD thesis, MIT, Department of Aeronautics and Astronautics, Cambridge, Mass., 2004.
- [3] J. T. Betts. Practical Methods for Optimal Control Using Nonlinear Programming. SIAM, 2001.
- [4] J. T. Betts. Practical Methods for Optimal Control and Estimation Using Nonlinear Programming. SIAM, 2010.
- [5] S.A. Bhatt. Optimal reorientation of spacecraft using only control moment gyroscopes. Master's thesis, Rice University, Houston, Texas, 2007.
- [6] A.E. Bryson. Dynamic Optimization. Addison-Wesley, 1999.
- [7] A.E. Bryson, M.N. Desai, and W.C. Hoffman. Energy-State Approximation in Performance Optimization of Supersonic Aircraft. *Journal of Aircraft*, 6:481–488, 1969.
- [8] A.E. Bryson and Yu-Chi Ho. *Applied Optimal Control*. Halsted Press, 1975.
- [9] R.L. Burden and J.D. Faires. *Numerical Analysis*. Thomson Brooks/Cole, 2005.
- [10] C. Canuto, M.Y. Hussaini, A. Quarteroni, and T.A. Zang. Spectral Methods: Fundamentals in Single Domains. Springer-Verlag, Berlin, 2006.
- [11] C. Canuto, M.Y. Hussaini, A. Quarteroni, and T.A. Zang. Spectral Methods: Evolution to Complex Geometries and Applications to Fluid Dynamics. Springer, Heidelberg, Germany, 2007.

- [12] C.G. Canuto, M.Y. Hussaini, A. Quarteroni A., and T.A. Zang. Spectral Methods in Fluid Dynamics. Springer-Verlag, 1988.
- [13] A. R. Curtis, M. J. D. Powell, and J. K. Reid. On the Estimation of Sparse Jacobian Matrices. *Journal of the Institute of Mathematics and Applications*, 13:117–120, 1974.
- [14] T. Davis. Direct Methods for Sparse Linear Systems. SIAM, 2006.
- [15] E. D. Dolan and J. J. More. Benchmarking optimization software with COPS 3.0. Argonne National Laboratory, 9700 South Cass Avenue, Argonne, Illinois 60439, 2004.
- [16] G. Elnagar, M. A. Kazemi, and M. Razzaghi. The Pseudospectral Legendre Method for Discretizing Optimal Control Problems. *IEEE Transactions on Automatic Control*, 40:1793–1796, 1995.
- [17] F. Fahroo and I.M. Ross. Costate Estimation by a Legendre Pseudospectral Method. *Journal of Guidance, Control, and Dynamics*, 24:270–277, 2001.
- [18] F. Fahroo and I.M. Ross. Costate Estimation by a Legendre Pseudospectral Method. *Journal of Guidance, Control, and Dynamics*, 24:270–277, 2002.
- [19] F. Fahroo and I.M. Ross. Direct Trajectory Optimization by a Chebyshev Pseudospectral Method. *Journal of Guidance Control and Dynamics*, 25, 2002.
- [20] J. Franke and M. Otter. The manutec r3 benchmark models for the dynamic simulation of robots. Technical report, Institute for Robotics and System Dynamics, DLR Oberpfaffenhofen, 1993.
- [21] P.E. Gill, W. Murray, M.A. Saunders, and M.H. Wright. Maintaining LU factors of a general sparse matrix. *Linear Algebra and its Applica*tions, 88/89:239–270, 1987.
- [22] Q. Gong, F. Fahroo, and I.M. Ross. Spectral algorithms for pseudospectral methods in optimal control. *Journal of Guidance Control and Dynamics*, 31:460–471, 2008.
- [23] J. Hesthaven, S. Gottlieb, and D. Gottlieb. Spectral Methods for Time-Dependent Problems. Cambridge University Press, Cambridge, 2007.
- [24] L.S. Jennings, M.E. Fisher, K.L. Teo, and C.J. Goh. *MISER3 Optimal Control Software Version 2.0 Theory and User Manual.* Department of Mathematics, The University of Western Australia, 2002.

- [25] W. Kang and N. Bedrossian. Pseudospectral Optimal Control Theory Makes Debut Flight, Saves nasa \$1m in Under Three Hours. SIAM News, 40, 2007.
- [26] W. Kang, Q. Gong, I. M. Ross, and F. Fahroo. On the Convergence of Nonlinear Optimal Control Using Pseudospectral Methods for Feedback Linearizable Systems. *International Journal of Robust and Nonlinear Control*, 17:1251–1277, 2007.
- [27] E. Kostina, M.A. Saunders, and I. Schierle. Computation of covariance matrices for constrained parameter estimation problems using lsqr. Technical Report SOL-2009-1, Standford University, System Optimization Laboratory, 2009.
- [28] Z. Li, M. R. Osborne, and T. Prvan. Parameter estimation of ordinary differential equations. *IMA Journal of Numerical Analysis*, 25:264–285, 2005.
- [29] R. Luus. *Iterative Dynamic Programming*. Chapman and Hall / CRC, 2002.
- [30] S. Marsili-Libelli, S. Guerrizio, and N. Checchi. Confidence regions of estimated parameters for ecological systems. *Ecological Modelling*, 165:127–146, 2003.
- [31] M. Otter and S. Turk. The dfvrl models 1 and 2 of the manutec r3 robot. Technical report, Institute for Robotics and System Dynamics, DLR Oberpfaffenhofen, Germany, 1987.
- [32] J.A. Pietz. Pseudospectral Collocation Methods for the Direct transcription of Optimal Control Problems. Master's thesis, Rice University, Houston, Texas, 2003.
- [33] A.V. Rao, D. Benson, G. Huntington, and C. Francolin. *User's manual for GPOPS version 1.3: A Matlab package for dynamic optimization using the Gauss pseudospectral method.* 2008.
- [34] A.V. Rao and K.D. Mease. Eigenvector Approximate Dichotomic Basis Method for Solving Hyper- sensitive Optimal Control Problems. Optimal Control Applications and Methods, 21:1–19, 2000.
- [35] I.M. Ross and F. Fahroo. Pseudospectral Knotting Methods for Solving Nonsmooth Optimal Control Problems. *Journal of Guidance Control* and Dynamics, 27:397–405, 2004.
- [36] P. E. Rutquist and M. M. Edvall. *PROPT Matlab Optimal Control Software*. TOMLAB Optimization, 2009.

- [37] K. Schittkowski. Numerical Data Fitting in Dynamical Systems. Kluwer Academic Publishers, Dordrecht, The Netherlands, 2002.
- [38] O. Von Stryk. User's guide for DIRCOL (Version 2.1): A direct collocation method for the numerical solution of optimal control problems. Technical Report, Technische Universität Munchen, 1999.
- [39] S. Subchan and R. Zbikowski. Computational optimal control: tools and practice. Wiley, 2009.
- [40] K.L. Teo, C.J. Goh, and K.H. Wong. A Unified Computational Approach to Optimal Control Problems. Wiley, New York, 1991.
- [41] Lloyd N. Trefethen. Spectral Methods in MATLAB. SIAM, Philadelphia, 2000.
- [42] D.A. Vallado. Fundamentals of Astrodynamics and Applications. Kluwer Academic Publishers, Dordrecht, The Netherlands, 2001.
- [43] J. Vlassenbroeck and R. Van Doreen. A Chebyshev Technique for Solving Nonlinear Optimal Control Problems. *IEEE Transactions on Automatic Control*, 33:333–340, 1988.
- [44] A. Wächter and L. T. Biegler. On the Implementation of a Primal-Dual Interior Point Filter Line Search Algorithm for Large-Scale Nonlinear Programming. *Mathematical Programming*, 106:25–57, 2006.