



Name :

Roll No. :

Invigilator's Signature :

CS/B.TECH(CSE/IT)(OLD)/SEM-4/EC-411/2012

2012

PRINCIPLES OF COMMUNICATION ENGINEERING

Time Allotted : 3 Hours

Full Marks : 70

The figures in the margin indicate full marks.

*Candidates are required to give their answers in their own words
as far as practicable.*

GROUP – A


(Multiple Choice Type Questions)

1. Choose the correct alternatives for any *ten* of the following :

10 × 1 = 10

- i) The high frequency range extends from
 - a) 300 kHz - 3000 kHz b) 3 MHz - 30 MHz
 - c) 30 MHz - 300 MHz d) 300 MHz - 3000 MHz.
- ii) The function of the input transducer in a communication system is
 - a) to transmit the message signal
 - b) to modulate the message signal
 - c) to convert message sound signal into electrical signal
 - d) none of these.

- 4301(O)



vii) Bandwidth of a single tone WBFM, given by Carson's Rule is

- a) $\Delta\omega + \omega_m$ b) $2(\Delta\omega + \omega_m)$
 c) $2\Delta\omega$ d) $2\omega_m$.

viii) Which of the following modulations is digital in nature ?

- a) PAM b) PPM
 c) DM d) AM.

ix) A super-heterodyne receiver with an IF of 450 kHz is tuned to a signal at 1200 kHz. The image frequency is


- a) 750 kHz b) 1650 kHz
 c) 2100 kHz d) 2000 kHz.

x) Companding is used in PCM to

- a) reduce bandwidth
 b) reduce power
 c) increase S/N ratio
 d) get almost uniform S/N ratio.

xi) In the bipolar NRZ or AMI line codes the binary zero is represented by

- a) alternate 0s and 1s
 b) alternate + A and – A amplitudes
 c) zero amplitude
 d) none of these.



- xii) Which of the following is a disadvantage of TDM?
- a) Inter-modulation distortion is absent
 - b) Full available channel bandwidth can be utilized for each channel
 - c) Due to slow narrow band fading all the TDM channel may get wiped out
 - d) Problem of cross talk is severe.
- xiii) Which of the following is not a property of Hamming code?
- a) No. of check bits $q \geq 3$
 - b) Block length $n = 2^q + 1$
 - c) No. of message bits $k = n - q$
 - d) Minimum distance $d_{\min} = 3$.
- xiv) The height of the geostationary satellite from the earth surface is approximately
- a) 42,600 km
 - b) 15,000 km
 - c) 35,786 km
 - d) 6,400 km.
- xv) The range of azimuth angle in satellite communication is
- a) 0° to 90°
 - b) 0° to 360°
 - c) 0° to 180°
 - d) 90° to 180° .



GROUP – B

(Short Answer Type Questions)

Answer any *three* of the following. $3 \times 5 = 15$

2. a) Why modulation is needed ?
b) What do you mean by AM envelope ?
c) What are the frequency components in an AM wave ?
Write the bandwidth of AM. $2 + 1 + 2$
3. a) What is angle modulation ?
b) Write the advantages and disadvantages of FM compared to AM ?
c) State Carson's rule of FM bandwidth.
4. a) State sampling theorem. Define aliasing.
b) Make comparison of different pulse analog modulation methods. $2 + 3$
5. Discuss the indirect method of generating a wide-band FM signal. $3 + 2$
6. a) An SSB signal contains 1 kW power. How much power is contained in the side band and how much at the carrier frequency ?
b) What is VSB modulation ? $2 + 2 + 1$

GROUP – C

(Long Answer Type Questions)

Answer any *three* of the following. $3 \times 15 = 45$

7. a) Define the following terms :
Block Code, Code Vectors, Code Weight, Code Word.



- b) Consider a (7, 4) linear block code whose generator matrix is given below :

$$G = \begin{bmatrix} 1 & 0 & 0 & 0 & 1 & 0 & 1 \\ 0 & 1 & 0 & 0 & 1 & 1 & 1 \\ 0 & 0 & 1 & 0 & 1 & 1 & 0 \\ 0 & 0 & 0 & 1 & 0 & 1 & 1 \end{bmatrix}$$

Find the code vector for a message 1011 and also the parity check matrix.

- c) The parity check bits of an (8 , 4) block code are given by,

$$c_1 = m_1 + m_2 + m_3$$

$$c_2 = m_1 + m_2 + m_3$$

$$c_3 = m_1 + m_3 + m_4$$

$$c_4 = m_2 + m_3 + m_4$$

Find generator matrix and parity check for this code.

- d) What is Hamming code ? 4 + 5 + 5 + 1

8. a) Explain the detection of AM signals using envelope detector.
- b) Explain with block diagram low level and high level modulation techniques.
- c) A transmitter radiates 9 kW without modulation and 10.125 kW after modulation. Determine depth of modulation.
- d) Find the bandwidth of a commercial FM transmission, if frequency deviation is 75 kHz and modulating frequency is 15 kHz. 4 + 4 + 4 + 3



9. a) Explain with the block diagram the generation and detection process of PCM.
- b) A telephone signal has a maximum frequency of 4 kHz. It is limited within the voltage of +V & -V. It is transmitted by using PCM. The required signal to quantization noise ratio is 40 dB. What is the minimum bandwidth required for the transmission ?
- c) Distinguish between ASK, FSK and PSK in terms of their performances.
- d) Encode the bit sequence 10110011010 in the NRZ-polar and RZ-bipolar format. 6 + 4 + 3 + 2
10. a) What is satellite ? Explain Kepler's law of planetary motion.
- b) Find out the height of the geostationary satellite.
- c) Explain the satellite uplink model.
- d) Define Lock Angles. 4 + 4 + 5 + 2
11. Write short notes on any *three* of the following : 3 × 5
- a) Balanced Modulator
- b) Super-heterodyne receiver
- c) Frequency Shift Keying
- d) Satellite Link Model
- e) Error Detection Methods.

=====