

Continuous Assessment Test - II

Programme Name & Branch: B.Tech. (BME, BCL)

Course Name & Code: Fluid Mechanics (MEE 1004)

Class Number: Common To A2 Slot Slot: A2 Exam Duration: 90 mins Max. Marks: 50

General instruction(s); Missing data, if any, may be suitably assumed.

Section - A (5 x 10 = 50 Marks)		
S.No.	Question	Outcome (CO)
	A 300 mm a 150 mm venturimeter is provided in a vertical pipeline carrying oil of Sp Gravity 0.9, the flow being upwards. The difference in elevations of the throat section and entrance section of the venturimeter is 300 mm. The differential U tube mercury manometer shows a gauge deflection of 250 mm. If the meter coefficient is 0.98 calculate at discharge of the oil b) pressure difference b/w the entrance and throat section. What would be the pressure difference for the same discharge if the wenturimenter is made horizontal?	
2	The fluid flowing in a reversing elbow makes a 180° U-furn before it is discharged, as shown in Figure 1. The elevation difference between the inlet and the exit sections is 0.3 m. Determine the anchoring force needed to hold the elbow at place.	3
2	Two reservoirs have 6 m difference in water levels, and are connected by a pipe 60 cm diameter and 3000 m long. Then, the pipe branches into two pipes each 30 cm diameter and 1500 m long. The friction coefficient is pipes each 30 cm diameter and 1500 m long. The friction coefficient is	4
4:	Consider a laminar flow of water (1.512 x 10° m's') through a pipe of diameter 200 mm. If the maximum flow velocity is 1.5 m/s, calculate the following: a) mean velocity and the radius at which it occurs b) selectly at 4 cm from the wall of the pipe	
3/	A horizontal pipe line is connected to a water tank at one end and discharges freely into the atmosphere at the other end. The specifications of the system are shown in Figure 2. Take f = 0.01 for both the sections of the pipe and draw the total energy line and the hydraulic gradient.	

