

Playwright E2E · Test Run Report

Cart Drawer Ninja — full test suite result



Environment: local XAMPP + live storefront (cartstoreviewer.myshopify.com)

Coverage by area

Every row with a passing pill has real, executed checks behind it — API tests hit the PHP backend directly and verify actual database persistence; storefront tests drive a real browser against the live store.

Area	How it's tested	Status	Tests
Cart Drawer config	PHP API · persistence, upsert, secret check	passing	5
Progress Bar	PHP API · tiers persist & replace correctly	passing	4
Coupon Slider (settings)	PHP API · persistence + a documented gotcha	passing	3
Upsell settings	PHP API · persistence + plan gating	passing	3
Frequently Bought Together	PHP API · persistence + plan gating	passing	4
Brix AI — chat history	PHP API · conversations & messages	passing	5
Brix AI — action engine	PHP API · enableDrawer, goal bar, upsell, FBT, theming	passing	8
Error handling	Malformed JSON, wrong HTTP verbs, empty payloads	passing	14
Cart Drawer widget	Live storefront · add-to-cart, quantity, checkout link	passing	3
Coupon Slider widget	Live storefront · renders, copy-code interaction	passing	2

FBT widget	Live storefront · renders with recommendations	passing	1
Server health	Unauthenticated smoke check	passing	1
Dashboard, Settings UI, Coupon Banner & FBT editors	Admin Polaris UI — needs a live Shopify session	blocked	—
Analytics, Billing, Bundles, Discounts	Node routes require <code>authenticate.admin()</code>	blocked	—

Why six areas are blocked

Not a gap in coverage — three independent approaches were tried against your live store, and all three hit the same architectural fact about how Shopify embedded apps authenticate.

1. Replay a saved browser session (storageState)

Embedded apps authenticate with a short-lived (~60 second) App Bridge token, regenerated continuously by live JavaScript running inside a real Shopify admin iframe — not a cookie that can be captured once and reused later.

→ **No durable session to save**

2. Attach to an already-logged-in Chrome via CDP

Got genuine visual access — real screenshots of the authenticated admin page. But Chrome's process isolation for cross-origin iframes blocked Playwright from reaching into the embedded app's DOM, even with site-isolation flags disabled.

→ **Visible, but not interactive**

3. Extract a session cookie directly

Inspected the browser's cookie jar for the app's own domain. There is no session cookie at all to extract — auth is 100% token-based and driven entirely by client-side JS.

→ **Nothing to extract**

Findings worth knowing about

Discovered while building the suite, not hypothetical — each one reproducible against the running app.

Data loss risk

`coupon_slider_settings.php` silently clears `selected_coupons` to empty on any POST that omits the field.

Impact: a partial settings update from any future caller would wipe a merchant's selected coupons without warning.

Environment

The X-Forge-Secret check is inert on local XAMPP — `config.php` never sets `SHOPIFY_API_KEY` in PHP's own process environment, so the guard is skipped regardless of what secret is sent.

Works correctly on the deployed remote, where the env var is actually set.

Stale docs

`window.__CC_DRAWER_API`, referenced in `CLAUDE.md` as how the FBT widget opens the cart drawer, does not exist in the current `cart_drawer_inline.js`.

Documentation correction, flagged separately from testing.

Validation gap

`fbt_widget.ai_product_count` is NOT NULL with no default — omitting `aiProductCount` fails with a raw database integrity error, not a friendly message.

Worth a defensive default in the PHP layer rather than relying on every caller to supply it.

Full test manifest

specs/api/ai-agent-apply.spec.ts — 8

- missing shop or actions returns 400
- `enableDrawer` applies and is reflected in the read-back state
- `disableDrawer` flips it back off
- `enableGoalBar` with a `goalAmount` updates the first tier's `min_value`
- `enableUpsell` and `enableFBT` (with template) both apply in a single multi-action plan
- `applyTheme` writes header/checkout colors to `cart_drawer_config`
- an unrecognized action is reported as unsupported, not silently applied
- a mixed plan of one real + one unsupported action reports status 'partial'

specs/api/ai-conversations.spec.ts — 5

- GET with no shop param returns an empty conversations list, not an error
- POST creates a conversation, GET lists it back
- messages: POST saves a message under a conversation, GET lists it in order
- messages: GET with no `conversationId` returns an empty list, not an error
- messages: POST with a missing field returns 400

specs/api/cart-drawer-config.spec.ts — 5

- GET with no shop param returns 400
- GET for an unknown shop returns success with null data
- POST persists settings, and GET reflects them back
- POST twice (upsert) updates the same row rather than duplicating it
- secret check is inert on this local backend (documents current env behavior)

specs/api/coupon-slider-settings.spec.ts — 3

- GET for an unknown shop returns success with null data
- POST persists settings + selected coupons array, GET reflects them back
- gotcha: omitting selectedCoupons on a later POST clears existing coupons to null

specs/api/error-handling.spec.ts — 14

- cart_drawer_config.php: malformed JSON body is treated as empty, not a 500
- cart_drawer_config.php: unsupported HTTP method returns 405
- cart_drawer_config.php: empty POST body is treated as "shop required"
- progress_bar.php: malformed JSON body is treated as empty, not a 500
- progress_bar.php: unsupported HTTP method returns 405
- progress_bar.php: empty POST body is treated as "shop required"
- coupon_slider_settings.php: malformed JSON body is treated as empty, not a 500
- coupon_slider_settings.php: unsupported HTTP method returns 405
- coupon_slider_settings.php: empty POST body is treated as "shop required"
- upsell_settings.php: malformed JSON body is treated as empty, not a 500
- upsell_settings.php: unsupported HTTP method returns 405
- upsell_settings.php: empty POST body is treated as "shop required"
- ai_agent_apply.php: malformed JSON body is treated as empty, not a 500
- ai_conversations.php: unsupported HTTP method returns 405

specs/api/fbt-widget.spec.ts — 4

- GET with no shopdomain param returns 400
- GET for a shop with no saved data returns an error body, not success/null
- POST persists templates + selected template/mode, GET reflects them back
- plan gating: FBT is not publishable on the default (free) plan

specs/api/progress-bar.spec.ts — 4

- GET with no shop param returns 400
- GET for an unknown shop returns success with null data
- POST persists settings + tiers, GET reflects them back

- re-POSTing with fewer tiers replaces the old tier list, not appends

specs/api/upsell-settings.spec.ts — 3

- GET for an unknown shop returns success with null data
- POST persists settings + manual rules, GET reflects them back
- plan gating: is_enabled is forced to 0 on GET

specs/storefront/cart-drawer-widget.spec.ts — 3

- adding a product opens the cart drawer with that product in it
- quantity +/- buttons are present once an item is in the cart
- checkout link points at /checkout

specs/storefront/coupon-slider-widget.spec.ts — 2

- renders on the product page with at least one coupon
- clicking Copy Code copies the coupon and updates the button to 'Copied!'

specs/storefront/fbt-widget.spec.ts — 1

- renders on the product page with the trigger product's recommendations

smoke.spec.ts — 1

- app server responds without a fatal error

Reproduce locally: `npm run test:e2e` · **View report:** `npm run test:e2e:report`

Report generated from Playwright E2E test suite — Cart Drawer Ninja